Gateway Documentation - FCUBSEXTPDService
Oracle FLEXCUBE Universal Banking
Release 12.87.02.0.0
[Febraury][2016]

Table Of Contents

1. Background **1**

2. FCUBSEXTPDService **2**

2.1.AuthorizePDDTRAUT **2**

2.1.1.PD-AuthorizePDDTRAUT-Req-Full-MSG.xsd 2

2.1.2.PD-AuthorizePDDTRAUT-Req-IO-MSG.xsd 11

2.1.3.PD-AuthorizePDDTRAUT-Res-Full-MSG.xsd 18

2.1.4.PD-AuthorizePDDTRAUT-Res-PK-MSG.xsd 29

2.2.CreatePDContract **38**

2.2.1.PD-CreatePDContract-Req-Full-MSG.xsd 38

2.2.2.PD-CreatePDContract-Req-IO-MSG.xsd 100

2.2.3.PD-CreatePDContract-Res-Full-MSG.xsd 144

2.2.4.PD-CreatePDContract-Res-PK-MSG.xsd 208

2.3.DeletePDContract **255**

2.3.1.PD-DeletePDContract-Req-Full-MSG.xsd 255

2.3.2.PD-DeletePDContract-Req-IO-MSG.xsd 317

2.3.3.PD-DeletePDContract-Res-Full-MSG.xsd 324

2.3.4.PD-DeletePDContract-Res-PK-MSG.xsd 387

2.4.LiquidatePDContract **396**

2.4.1.PD-LiquidatePDContract-Req-Full-MSG.xsd 396

2.4.2.PD-LiquidatePDContract-Req-IO-MSG.xsd 458

2.4.3.PD-LiquidatePDContract-Res-Full-MSG.xsd 481

2.4.4.PD-LiquidatePDContract-Res-PK-MSG.xsd 544

2.5.ModifyPDContract **569**

2.5.1.PD-ModifyPDContract-Req-Full-MSG.xsd 569

2.5.2.PD-ModifyPDContract-Req-IO-MSG.xsd 632

2.5.3.PD-ModifyPDContract-Res-Full-MSG.xsd 660

2.5.4.PD-ModifyPDContract-Res-PK-MSG.xsd 724

2.6.QueryPDContract **755**

2.6.1.PD-QueryPDContract-Req-IO-MSG.xsd 755

2.6.2.PD-QueryPDContract-Res-Full-MSG.xsd 762

2.7.ReversePDContract **826**

2.7.1.PD-ReversePDContract-Req-Full-MSG.xsd 826

2.7.2.PD-ReversePDContract-Req-IO-MSG.xsd 888

2.7.3.PD-ReversePDContract-Res-Full-MSG.xsd 895

2.7.4.PD-ReversePDContract-Res-PK-MSG.xsd 958

1. Background

Integration of different applications and solutions is a key area in today's systems.A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data.The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs.The integration needs supported by the Gateway can be broadly categorized from the perspective of Gateway as follows

1. Inbound application integration :

This is used when any external system needs to add, modify or query information within FLEXCUBE UBS

2. Outbound application integration :

This is used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS

The following sections provide detailed XSD documentation of all operations available in FCUBSEXTPDService of Branch Module

2. FCUBSEXTPDService

2.1.AuthorizePDDTRAUT

2.1.1.PD-AuthorizePDDTRAUT-Req-Full-MSG.xsd

- *AUTHORIZEPDDTRAUT_FSFS_REQ*
  - *FCUBS_HEADER*
    - *SOURCE*
    - *UBSCOMP*
    - *MSGID*
    - *CORRELID*
    - *USERID*
    - *BRANCH*
    - *MODULEID*
    - *SERVICE*
    - *OPERATION*
    - *SOURCE_OPERATION*
    - *SOURCE_USERID*
    - *DESTINATION*
    - *MULTITRIPID*
    - *FUNCTIONID*
    - *ACTION*
    - *MSGSTAT*
    - *PASSWORD*
    - *ADDL*
      - *PARAM*
        - *NAME*
        - *VALUE*
  - *FCUBS_BODY*
    - *Onlin-Auth-Full*
      - *CONTREFNNO*
      - *EVSEQNO*
      - *INPTBY*
      - *EVENTDT*

Contract-Ovd

REMARKS

CONFIRMED

OVDSTAT

AUTHBY

AUTHDT

TXTSTATUS

OVDMSGS

AUTHORIZEPDDTRAUT_FSFS_REQ

Attribute	Description
Name	AUTHORIZEPDDTRAUT_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Onlin-Auth-Full

Attribute	Description
Name	Onlin-Auth-Full
Datatype	
Description	

CONTREFNNO

Attribute	Description

Name	CONTREFNNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

EVSEQNO

Attribute	**Description**
Name	EVSEQNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

INPTBY

Attribute	**Description**
Name	INPTBY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

EVENTDT

Attribute	**Description**
Name	EVENTDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Contract-Ovd

Attribute	**Description**
Name	Contract-Ovd
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

CONFIRMED

Attribute	Description
Name	CONFIRMED
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

OVDSTAT

Attribute	Description
Name	OVDSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

AUTHBY

Attribute	Description
Name	AUTHBY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

AUTHDT

Attribute	Description
Name	AUTHDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TXTSTATUS

Attribute	Description
Name	TXTSTATUS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

2.1.2.PD-AuthorizePDDTRAUT-Req-IO-MSG.xsd

AUTHORIZEPDDTRAUT_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Onlin-Auth-IO

CONTREFNNO

AUTHORIZEPDDTRAUT_IOPK_REQ

Attribute	Description
Name	AUTHORIZEPDDTRAUT_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String

Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Onlin-Auth-IO

Attribute	Description
Name	Onlin-Auth-IO
Datatype	
Description	

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

2.1.3.PD-AuthorizePDDTRAUT-Res-Full-MSG.xsd

AUTHORIZEPDDTRAUT_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Onlin-Auth-Full

CONTREFNNO

EVSEQNO

INPTBY

EVENTDT

Contract-Ovd

REMARKS

CONFIRMED

OVDSTAT

AUTHBY

AUTHDT

TXTSTATUS

OVDMSGS

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZEPDDTRAUT_FSFS_RES

Attribute	Description
Name	AUTHORIZEPDDTRAUT_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Onlin-Auth-Full

Attribute	Description
Name	Onlin-Auth-Full
Datatype	
Description	

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	16

EVSEQNO

Attribute	Description
Name	EVSEQNO
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

INPTBY

Attribute	Description
Name	INPTBY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

EVENTDT

Attribute	Description
Name	EVENTDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Contract-Ovd

Attribute	Description
Name	Contract-Ovd
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

CONFIRMED

Attribute	Description
Name	CONFIRMED
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / Y,N

OVDSTAT

Attribute	**Description**
Name	OVDSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

AUTHBY

Attribute	**Description**
Name	AUTHBY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

AUTHDT

Attribute	**Description**
Name	AUTHDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

TXTSTATUS

Attribute	**Description**
Name	TXTSTATUS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	1

OVDMSGS

Attribute	Description
Name	OVDMSGS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4000

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description

Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.1.4.PD-AuthorizePDDTRAUT-Res-PK-MSG.xsd

AUTHORIZEPDDTRAUT_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Onlin-Auth-PK

CONTREFNNO

Onlin-Auth-IO

CONTREFNNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZEPDDTRAUT_IOPK_RES

Attribute	Description
Name	AUTHORIZEPDDTRAUT_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	**Description**
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	**Description**
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Onlin-Auth-PK

Attribute	Description
Name	Onlin-Auth-PK
Datatype	
Description	

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

Onlin-Auth-IO

Attribute	Description
Name	Onlin-Auth-IO
Datatype	
Description	

CONTREFNNO

Attribute	Description
Name	CONTREFNNO
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

WCODE

Attribute	Description

Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.2.CreatePDContract

2.2.1.PD-CreatePDContract-Req-Full-MSG.xsd

CREATEPDCONTRACT_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Pdvws-Pdc-Master-Full

TRNREFNO

EVSEQNO

SCODE

XREF

PRDCD

BRANCH_CODE

REMITTER_ACCOUNT_NO

BENACNO

INSTRNO

CCY

AMT

VALDT

CLEARING_PRODUCT

RTNGNO

ENDPNT

ISSUER_BANK

ISSUER_BRANCH

PURPOSE

ACTIVATION_DT

LOCNOFCHQ

BLKTXNREF

CHARGE_BRANCH

CHG_ACC_NUMBER

CHGCCY

MAKERID

AUTHSTAT

ONCEAUTH

MAKERSTAMP

CHECKERID

CHECKERSTAMP

MODNO

PRODDESC

BRNDESC

CLGPRODDESC

ISRBNKDESC

ISRBRNDESC

ENDPNTDESC

CHGPAYBRNDESC

CLRBNK

PCCLGBRN

SECTORCD

RECSTAT

DUMMY

LOAN_ACCNO

REMARKS

CREDITLINE

LIMTRACKREQD

FRM_DT

TODATE

DOWNPMT

CHQ_INQUIRY

OPERATION

USERREFNO

DRWPARTYID

CHQDATE

TXNSTAT

REMACDESC

BEN_NAME

CHARGE_AC_DESC

SCHEDULEDATE

Pdvws-All-Ac-Entries--Master

- *EVENT*
- *Pdvws-All-Ac-Entries*
  - *EVENT*

ACBRN

ACNO

DRCRIND

ACCCY

CODE

FCYAMT

EXCHRATE

LCYAMT

TRNDT

VALUEDT

AMTTAG

Csvws-Contract-Ovd

OVDRIDES

Master

Detb-Pdc-Linkages

CUSTOMERNO

LINKAGE_TYPE

LINKREFNO

LNKPXNTG

LINKAMT

Misdetails

CONREFNO

MISGRP

RELACC

RELETED_REFERENCE

MISHEAD

RATEFLG

POOLCD

REFINANCE_RATE

REFRATETYP

PROCALCMTH

REFSPREAD

REFRATECD

COSTCD1

COSTCD2

COSTCD3

COSTCD4

COSTCD5

TXNMIS1

TXNMIS10

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

MISGRPCOMP

MISGRPTXN

COMPMIS1

COMPMIS10

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

FUNDMIS1

FUNDMIS10

FUNDMIS2

FUNDMIS3

FUNDMIS4

FUNDMIS5

FUNDMIS6

FUNDMIS7

FUNDMIS8

FUNDMIS9

MISGRPFUN

TRANMIS1

TRANMIS2

TRANMIS3

TRANMIS4

TRANMIS5

TRANMIS6

TRANMIS7

TRANMIS8

TRANMIS9

TRANMIS10

COMMIS1

COMMIS2

COMMIS3

COMMIS4

COMMIS5

COMMIS6

COMMIS7

COMMIS8

COMMIS9

COMMIS10

FUNMIS1

FUNMIS2

FUNMIS3

FUNMIS4

FUNMIS5

FUNMIS6

FUNMIS7

FUNMIS8

FUNMIS9

FUNMIS10

Txnmisdetails

Compmisdetails

Fundmisdetails

Control

Balance-Trnsfer-Log-Details

BRANCH

PERIOD_CODE

FIN_YEAR

REFERENCE_NO

GL_CODE

REFERENCE_TYPE

TRANSFER_IND

MIS_CLASS

TXN_DATE

OLD_MIS_CODE

NEW_MIS_CODE

CCY

AMOUNT

EX_RATE

Charge

TRNREF

EVSEQNO

Contract-Charges

COMPONENT

PICKUP_EVENT_SEQUENCE_NUMBER

VALUE_DATE

EVENT_SEQ_NO

TRANSACTION_DATE

CHANGE_DURING_AMENDMENT

CURRENCY

AMOUNT

STATUS

WAIVER

RATE

RATE_TYPE

EVENT

PARTY

TXNUDFDETAILS

FLDNAME

FLDVAL

CREATEPDCONTRACT_FSFS_REQ

Attribute	Description
Name	CREATEPDCONTRACT_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE

Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	

Pdvws-Pdc-Master-Full

Attribute	**Description**

Name	Pdvws-Pdc-Master-Full
Datatype	
Description	

TRNREFNO

Attribute	Description
Name	TRNREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

EVSEQNO

Attribute	Description
Name	EVSEQNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

SCODE

Attribute	Description
Name	SCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

REMITTER_ACCOUNT_NO

Attribute	Description
Name	REMITTER_ACCOUNT_NO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

BENACNO

Attribute	Description
Name	BENACNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String

Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

AMT

Attribute	Description
Name	AMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

VALDT

Attribute	Description
Name	VALDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

CLEARING_PRODUCT

Attribute	Description
Name	CLEARING_PRODUCT
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 4

RTNGNO

Attribute	**Description**
Name	RTNGNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 27

ENDPNT

Attribute	**Description**
Name	ENDPNT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

ISSUER_BANK

Attribute	**Description**
Name	ISSUER_BANK
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

ISSUER_BRANCH

Attribute	**Description**
Name	ISSUER_BRANCH
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

PURPOSE

Attribute	**Description**
Name	PURPOSE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

ACTIVATION_DT

Attribute	**Description**
Name	ACTIVATION_DT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

LOCNOFCHQ

Attribute	**Description**
Name	LOCNOFCHQ
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

BLKTXNREF

Attribute	**Description**
Name	BLKTXNREF
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	
	Restrictions / **Description**: maxLength / 16

CHARGE_BRANCH

Attribute	Description
Name	CHARGE_BRANCH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

CHG_ACC_NUMBER

Attribute	Description
Name	CHG_ACC_NUMBER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	12

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	U,A

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

BRNDESC

Attribute	Description
Name	BRNDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

CLGPRODDESC

Attribute	Description
Name	CLGPRODDESC

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

ISRBNKDESC

Attribute	**Description**
Name	ISRBNKDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

ISRBRNDESC

Attribute	**Description**
Name	ISRBRNDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

ENDPNTDESC

Attribute	**Description**
Name	ENDPNTDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

CHGPAYBRNDESC

Attribute	**Description**
Name	CHGPAYBRNDESC

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

CLRBNK

Attribute	**Description**
Name	CLRBNK
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 36

PCCLGBRN

Attribute	**Description**
Name	PCCLGBRN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 36

SECTORCD

Attribute	**Description**
Name	SECTORCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 36

RECSTAT

Attribute	**Description**
Name	RECSTAT

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

DUMMY

Attribute	**Description**
Name	DUMMY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

LOAN_ACCNO

Attribute	**Description**
Name	LOAN_ACCNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

REMARKS

Attribute	**Description**
Name	REMARKS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

CREDITLINE

Attribute	**Description**
Name	CREDITLINE

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

LIMTRACKREQD

Attribute	**Description**
Name	LIMTRACKREQD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

FRM_DT

Attribute	**Description**
Name	FRM_DT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

TODATE

Attribute	**Description**
Name	TODATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

DOWNPMT

Attribute	**Description**
Name	DOWNPMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22

CHQ_INQUIRY

Attribute	Description
Name	CHQ_INQUIRY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Discounted,Normal,Purchased,Collection,Collection after purchase,Collection after discount,Returned,Passed,Pullback

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	P,,D

USERREFNO

Attribute	Description
Name	USERREFNO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

DRWPARTYID

Attribute	Description
Name	DRWPARTYID
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

CHQDATE

Attribute	**Description**
Name	CHQDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,V,U,L,K,C

REMACDESC

Attribute	**Description**
Name	REMACDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

BEN_NAME

Attribute	**Description**
Name	BEN_NAME
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	255

CHARGE_AC_DESC

Attribute	Description
Name	CHARGE_AC_DESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255

SCHEDULEDATE

Attribute	Description
Name	SCHEDULEDATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Pdvws-All-Ac-Entries--Master

Attribute	Description
Name	Pdvws-All-Ac-Entries--Master
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

Pdvws-All-Ac-Entries

Attribute	Description

Name	Pdvws-All-Ac-Entries
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

ACBRN

Attribute	Description
Name	ACBRN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

ACNO

Attribute	Description
Name	ACNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 1

ACCCY

Attribute	**Description**
Name	ACCCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

CODE

Attribute	**Description**
Name	CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

FCYAMT

Attribute	**Description**
Name	FCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

EXCHRATE

Attribute	**Description**
Name	EXCHRATE
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

LCYAMT

Attribute	**Description**
Name	LCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TRNDT

Attribute	**Description**
Name	TRNDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

VALUEDT

Attribute	**Description**
Name	VALUEDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

AMTTAG

Attribute	**Description**
Name	AMTTAG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

OVDRIDES

Attribute	Description
Name	OVDRIDES
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

Master

Attribute	Description
Name	Master
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Detb-Pdc-Linkages

Attribute	Description
Name	Detb-Pdc-Linkages
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

CUSTOMERNO

Attribute	Description
Name	CUSTOMERNO
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / P,C,F

LINKREFNO

Attribute	Description
Name	LINKREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 35

LNKPXNTG

Attribute	Description
Name	LNKPXNTG
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

LINKAMT

Attribute	Description
Name	LINKAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	

Attribute	**Attribute** / **Description** minOccurs / 0

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

MISGRP

Attribute	**Description**
Name	MISGRP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

RELACC

Attribute	**Description**
Name	RELACC
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

RELETED_REFERENCE

Attribute	**Description**
Name	RELETED_REFERENCE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>X,F,P</td></tr></table>

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>1,2,3,4,5,6,7,8,9</td></tr></table>

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Control

Attribute	Description
Name	Control
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Balance-Trnsfer-Log-Details

Attribute	Description
Name	Balance-Trnsfer-Log-Details
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

PERIOD_CODE

Attribute	**Description**
Name	PERIOD_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

FIN_YEAR

Attribute	**Description**
Name	FIN_YEAR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFERENCE_NO

Attribute	**Description**
Name	REFERENCE_NO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

GL_CODE

Attribute	**Description**

Name	GL_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFERENCE_TYPE

Attribute	**Description**
Name	REFERENCE_TYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TRANSFER_IND

Attribute	**Description**
Name	TRANSFER_IND
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

MIS_CLASS

Attribute	**Description**
Name	MIS_CLASS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TXN_DATE

Attribute	**Description**

Name	TXN_DATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

OLD_MIS_CODE

Attribute	Description
Name	OLD_MIS_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

NEW_MIS_CODE

Attribute	Description
Name	NEW_MIS_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

EX_RATE

Attribute	**Description**
Name	EX_RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 24

Charge

Attribute	**Description**
Name	Charge
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

TRNREF

Attribute	**Description**
Name	TRNREF
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

EVSEQNO

Attribute	**Description**
Name	EVSEQNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22

Contract-Charges

Attribute	Description
Name	Contract-Charges
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	15

PICKUP_EVENT_SEQUENCE_NUMBER

Attribute	Description
Name	PICKUP_EVENT_SEQUENCE_NUMBER
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

VALUE_DATE

Attribute	Description
Name	VALUE_DATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: totalDigits / 22

TRANSACTION_DATE

Attribute	**Description**
Name	TRANSACTION_DATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

CHANGE_DURING_AMENDMENT

Attribute	**Description**
Name	CHANGE_DURING_AMENDMENT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

CURRENCY

Attribute	**Description**
Name	CURRENCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

AMOUNT

Attribute	**Description**
Name	AMOUNT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: totalDigits / 22

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

RATE

Attribute	Description
Name	RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: maxLength / 1

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

PARTY

Attribute	Description
Name	PARTY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.2.2.PD-CreatePDContract-Req-IO-MSG.xsd

CREATEPDCONTRACT_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Pdvws-Pdc-Master-IO

TRNREFNO

REMITTER_ACCOUNT_NO

BENACNO

INSTRNO

CCY

AMT

CLEARING_PRODUCT

RTNGNO

ENDPNT

ISSUER_BANK

ISSUER_BRANCH

PURPOSE

ACTIVATION_DT

LOCNOFCHQ

CHARGE_BRANCH

CHG_ACC_NUMBER

CHGCCY

CLRBNK

PCCLGBRN

SECTORCD

RECSTAT

DUMMY

LOAN_ACCNO

REMARKS

CREDITLINE

LIMTRACKREQD

CHQ_INQUIRY

OPERATION

USERREFNO

DRWPARTYID

CHQDATE

SCHEDULEDATE

Pdvws-All-Ac-Entries--Master

EVENT

Pdvws-All-Ac-Entries

EVENT

ACBRN

ACNO

DRCRIND

ACCCY

CODE

FCYAMT

EXCHRATE

LCYAMT

TRNDT

VALUEDT

AMTTAG

Csvws-Contract-Ovd

OVDRIDES

Detb-Pdc-Linkages

CUSTOMERNO

LINKAGE_TYPE

LINKREFNO

LNKPXNTG

LINKAMT

Misdetails

CONREFNO

MISGRP

RELACC

RELETED_REFERENCE

MISHEAD

RATEFLG

POOLCD

REFINANCE_RATE

REFRATETYP

PROCALCMTH

REFSPREAD

REFRATECD

COSTCD1

COSTCD2

COSTCD3

COSTCD4

COSTCD5

TXNMIS1

TXNMIS10

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

MISGRPCOMP

MISGRPTXN

COMPMIS1

COMPMIS10

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

FUNDMIS1

FUNDMIS10

FUNDMIS2

FUNDMIS3

FUNDMIS4

FUNDMIS5

FUNDMIS6

FUNDMIS7

FUNDMIS8

FUNDMIS9

MISGRPFUN

Txnmisdetails

Compmisdetails

Fundmisdetails

Balance-Trnsfer-Log-Details

BRANCH

PERIOD_CODE

FIN_YEAR

REFERENCE_NO

GL_CODE

REFERENCE_TYPE

TRANSFER_IND

MIS_CLASS

TXN_DATE

OLD_MIS_CODE

NEW_MIS_CODE

CCY

AMOUNT

EX_RATE

Charge

TRNREF

EVSEQNO

Contract-Charges

PICKUP_EVENT_SEQUENCE_NUMBER

VALUE_DATE

EVENT_SEQ_NO

TRANSACTION_DATE

CHANGE_DURING_AMENDMENT

AMOUNT

STATUS

WAIVER

RATE_TYPE

PARTY

TXNUDFDETAILS

FLDNAME

FLDVAL

CREATEPDCONTRACT_IOPK_REQ

Attribute	Description
Name	CREATEPDCONTRACT_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.

Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Pdvws-Pdc-Master-IO

Attribute	Description
Name	Pdvws-Pdc-Master-IO
Datatype	
Description	

TRNREFNO

Attribute	Description
Name	TRNREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

REMITTER_ACCOUNT_NO

Attribute	Description
Name	REMITTER_ACCOUNT_NO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

BENACNO

Attribute	Description
Name	BENACNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	16

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

AMT

Attribute	Description
Name	AMT
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CLEARING_PRODUCT

Attribute	Description
Name	CLEARING_PRODUCT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

RTNGNO

Attribute	Description
Name	RTNGNO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: maxLength / 27

ENDPNT

Attribute	Description
Name	ENDPNT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

ISSUER_BANK

Attribute	Description
Name	ISSUER_BANK
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

ISSUER_BRANCH

Attribute	Description
Name	ISSUER_BRANCH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

PURPOSE

Attribute	Description
Name	PURPOSE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	105

ACTIVATION_DT

Attribute	Description
Name	ACTIVATION_DT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

LOCNOFCHQ

Attribute	Description
Name	LOCNOFCHQ
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

CHARGE_BRANCH

Attribute	Description
Name	CHARGE_BRANCH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

CHG_ACC_NUMBER

Attribute	Description
Name	CHG_ACC_NUMBER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

CLRBNK

Attribute	Description
Name	CLRBNK
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>36</td></tr></table>

PCCLGBRN

Attribute	Description
Name	PCCLGBRN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>36</td></tr></table>

SECTORCD

Attribute	Description
Name	SECTORCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>36</td></tr></table>

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

DUMMY

Attribute	Description
Name	DUMMY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

LOAN_ACCNO

Attribute	Description
Name	LOAN_ACCNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

LIMTRACKREQD

Attribute	Description
Name	LIMTRACKREQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

CHQ_INQUIRY

Attribute	Description
Name	CHQ_INQUIRY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Discounted,Normal,Purchased,Collection,Collection after purchase,Collection after discount,Returned,Passed,Pullback</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,,D</td></tr></table>

USERREFNO

Attribute	Description
Name	USERREFNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

DRWPARTYID

Attribute	Description
Name	DRWPARTYID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHQDATE

Attribute	Description
Name	CHQDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

SCHEDULEDATE

Attribute	Description
Name	SCHEDULEDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Pdvws-All-Ac-Entries--Master

Attribute	Description
Name	Pdvws-All-Ac-Entries--Master
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

Pdvws-All-Ac-Entries

Attribute	Description
Name	Pdvws-All-Ac-Entries
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

ACBRN

Attribute	Description
Name	ACBRN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

ACNO

Attribute	Description
Name	ACNO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

FCYAMT

Attribute	Description
Name	FCYAMT
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

EXCHRATE

Attribute	Description
Name	EXCHRATE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

TRNDT

Attribute	Description
Name	TRNDT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

OVDRIDES

Attribute	Description
Name	OVDRIDES
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

Detb-Pdc-Linkages

Attribute	Description
Name	Detb-Pdc-Linkages
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

CUSTOMERNO

Attribute	Description
Name	CUSTOMERNO
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	9

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Restrictions	

Restrictions	Description
enumeration	P,C,F

LINKREFNO

Attribute	Description
Name	LINKREFNO
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	35

LNKPXNTG

Attribute	Description
Name	LNKPXNTG
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

LINKAMT

Attribute	Description
Name	LINKAMT
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

Misdetails

Attribute	**Description**
Name	Misdetails
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

MISGRP

Attribute	**Description**
Name	MISGRP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

RELACC

Attribute	**Description**
Name	RELACC
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>X,F,P</td></tr></table>

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>1,2,3,4,5,6,7,8,9</td></tr></table>

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	

Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

Balance-Trnsfer-Log-Details

Attribute	Description
Name	Balance-Trnsfer-Log-Details
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

PERIOD_CODE

Attribute	Description
Name	PERIOD_CODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

FIN_YEAR

Attribute	Description
Name	FIN_YEAR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

GL_CODE

Attribute	Description
Name	GL_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFERENCE_TYPE

Attribute	Description
Name	REFERENCE_TYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TRANSFER_IND

Attribute	Description
Name	TRANSFER_IND
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

MIS_CLASS

Attribute	Description
Name	MIS_CLASS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXN_DATE

Attribute	Description
Name	TXN_DATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

OLD_MIS_CODE

Attribute	Description
Name	OLD_MIS_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

NEW_MIS_CODE

Attribute	Description
Name	NEW_MIS_CODE
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

EX_RATE

Attribute	Description
Name	EX_RATE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>24</td></tr></table>

Charge

Attribute	Description
Name	Charge
Datatype	

Description	
Attribute	

Attribute	Description
minOccurs	0

TRNREF

Attribute	Description
Name	TRNREF
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

EVSEQNO

Attribute	Description
Name	EVSEQNO
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

Contract-Charges

Attribute	Description
Name	Contract-Charges
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PICKUP_EVENT_SEQUENCE_NUMBER

Attribute	Description
Name	PICKUP_EVENT_SEQUENCE_NUMBER
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

VALUE_DATE

Attribute	Description
Name	VALUE_DATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

TRANSACTION_DATE

Attribute	Description
Name	TRANSACTION_DATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

CHANGE_DURING_AMENDMENT

Attribute	Description
Name	CHANGE_DURING_AMENDMENT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

AMOUNT

Attribute	Description

Name	AMOUNT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

STATUS

Attribute	**Description**
Name	STATUS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

RATE_TYPE

Attribute	**Description**
Name	RATE_TYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

PARTY

Attribute	**Description**

Name	PARTY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TXNUDFDETAILS

Attribute	**Description**
Name	TXNUDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FLDNAME

Attribute	**Description**
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

2.2.3.PD-CreatePDContract-Res-Full-MSG.xsd

CREATEPDCONTRACT_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Pdvws-Pdc-Master-Full

TRNREFNO

EVSEQNO

SCODE

XREF

PRDCD

BRANCH_CODE

REMITTER_ACCOUNT_NO

BENACNO

INSTRNO

CCY

AMT

VALDT

CLEARING_PRODUCT

RTNGNO

ENDPNT

ISSUER_BANK

ISSUER_BRANCH

PURPOSE

ACTIVATION_DT

LOCNOFCHQ

BLKTXNREF

CHARGE_BRANCH

CHG_ACC_NUMBER

CHGCCY

MAKERID

AUTHSTAT

ONCEAUTH

MAKERSTAMP

CHECKERID

CHECKERSTAMP

MODNO

PRODDESC

BRNDESC

CLGPRODDESC

ISRBNKDESC

ISRBRNDESC

ENDPNTDESC

CHGPAYBRNDESC

CLRBNK

PCCLGBRN

SECTORCD

RECSTAT

DUMMY

LOAN_ACCNO

REMARKS

CREDITLINE

LIMTRACKREQD

FRM_DT

TODATE

DOWNPMT

CHQ_INQUIRY

OPERATION

USERREFNO

DRWPARTYID

CHQDATE

TXNSTAT

REMACDESC

BEN_NAME

CHARGE_AC_DESC

SCHEDULEDATE

Pdvws-All-Ac-Entries--Master

- *EVENT*
- *Pdvws-All-Ac-Entries*
  - *EVENT*
  - *ACBRN*
  - *ACNO*
  - *DRCRIND*
  - *ACCCY*
  - *CODE*
  - *FCYAMT*
  - *EXCHRATE*
  - *LCYAMT*
  - *TRNDT*
  - *VALUEDT*
  - *AMTTAG*

Csvws-Contract-Ovd

OVDRIDES

Master

Detb-Pdc-Linkages

CUSTOMERNO

LINKAGE_TYPE

LINKREFNO

LNKPXNTG

LINKAMT

Misdetails

CONREFNO

MISGRP

RELACC

RELETED_REFERENCE

MISHEAD

RATEFLG

POOLCD

REFINANCE_RATE

REFRATETYP

PROCALCMTH

REFSPREAD

REFRATECD

COSTCD1

COSTCD2

COSTCD3

COSTCD4

COSTCD5

TXNMIS1

TXNMIS10

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

MISGRPCOMP

MISGRPTXN

COMPMIS1

COMPMIS10

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

FUNDMIS1

FUNDMIS10

FUNDMIS2

FUNDMIS3

FUNDMIS4

FUNDMIS5

FUNDMIS6

FUNDMIS7

FUNDMIS8

FUNDMIS9

MISGRPFUN

TRANMIS1

TRANMIS2

TRANMIS3

TRANMIS4

TRANMIS5

TRANMIS6

TRANMIS7

TRANMIS8

TRANMIS9

TRANMIS10

COMMIS1

COMMIS2

COMMIS3

COMMIS4

COMMIS5

COMMIS6

COMMIS7

COMMIS8

COMMIS9

COMMIS10

FUNMIS1

FUNMIS2

FUNMIS3

FUNMIS4

FUNMIS5

FUNMIS6

FUNMIS7

FUNMIS8

FUNMIS9

FUNMIS10

Txnmisdetails

Compmisdetails

Fundmisdetails

Control

Balance-Trnsfer-Log-Details

BRANCH

PERIOD_CODE

FIN_YEAR

REFERENCE_NO

GL_CODE

REFERENCE_TYPE

TRANSFER_IND

MIS_CLASS

TXN_DATE

OLD_MIS_CODE

NEW_MIS_CODE

CCY

AMOUNT

EX_RATE

Charge

TRNREF

EVSEQNO

Contract-Charges

COMPONENT

PICKUP_EVENT_SEQUENCE_NUMBER

VALUE_DATE

EVENT_SEQ_NO

TRANSACTION_DATE

CHANGE_DURING_AMENDMENT

CURRENCY

AMOUNT

STATUS

WAIVER

RATE

RATE_TYPE

EVENT

PARTY

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATEPDCONTRACT_FSFS_RES

Attribute	Description
Name	CREATEPDCONTRACT_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	

Pdvws-Pdc-Master-Full

Attribute	**Description**

Name	Pdvws-Pdc-Master-Full
Datatype	
Description	

TRNREFNO

Attribute	Description
Name	TRNREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

EVSEQNO

Attribute	Description
Name	EVSEQNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

SCODE

Attribute	Description
Name	SCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

REMITTER_ACCOUNT_NO

Attribute	Description
Name	REMITTER_ACCOUNT_NO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

BENACNO

Attribute	Description
Name	BENACNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

AMT

Attribute	Description
Name	AMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

VALDT

Attribute	Description
Name	VALDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

CLEARING_PRODUCT

Attribute	Description
Name	CLEARING_PRODUCT
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

RTNGNO

Attribute	**Description**
Name	RTNGNO
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 27

ENDPNT

Attribute	**Description**
Name	ENDPNT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

ISSUER_BANK

Attribute	**Description**
Name	ISSUER_BANK
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

ISSUER_BRANCH

Attribute	**Description**
Name	ISSUER_BRANCH
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

PURPOSE

Attribute	**Description**
Name	PURPOSE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

ACTIVATION_DT

Attribute	**Description**
Name	ACTIVATION_DT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

LOCNOFCHQ

Attribute	**Description**
Name	LOCNOFCHQ
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

BLKTXNREF

Attribute	**Description**
Name	BLKTXNREF
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	16

CHARGE_BRANCH

Attribute	Description
Name	CHARGE_BRANCH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

CHG_ACC_NUMBER

Attribute	Description
Name	CHG_ACC_NUMBER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	U,A

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

BRNDESC

Attribute	Description
Name	BRNDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

CLGPRODDESC

Attribute	Description
Name	CLGPRODDESC

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>420</td></tr></table>

ISRBNKDESC

Attribute	Description
Name	ISRBNKDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>420</td></tr></table>

ISRBRNDESC

Attribute	Description
Name	ISRBRNDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>420</td></tr></table>

ENDPNTDESC

Attribute	Description
Name	ENDPNTDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>420</td></tr></table>

CHGPAYBRNDESC

Attribute	Description
Name	CHGPAYBRNDESC

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

CLRBNK

Attribute	**Description**
Name	CLRBNK
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 36

PCCLGBRN

Attribute	**Description**
Name	PCCLGBRN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 36

SECTORCD

Attribute	**Description**
Name	SECTORCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 36

RECSTAT

Attribute	**Description**
Name	RECSTAT

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

DUMMY

Attribute	**Description**
Name	DUMMY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

LOAN_ACCNO

Attribute	**Description**
Name	LOAN_ACCNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

REMARKS

Attribute	**Description**
Name	REMARKS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

CREDITLINE

Attribute	**Description**
Name	CREDITLINE

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

LIMTRACKREQD

Attribute	Description
Name	LIMTRACKREQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

FRM_DT

Attribute	Description
Name	FRM_DT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TODATE

Attribute	Description
Name	TODATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DOWNPMT

Attribute	Description
Name	DOWNPMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22

CHQ_INQUIRY

Attribute	Description
Name	CHQ_INQUIRY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Discounted,Normal,Purchased,Collection,Collection after purchase,Collection after discount,Returned,Passed,Pullback

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	P,,D

USERREFNO

Attribute	Description
Name	USERREFNO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

DRWPARTYID

Attribute	Description
Name	DRWPARTYID
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

CHQDATE

Attribute	**Description**
Name	CHQDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,V,U,L,K,C

REMACDESC

Attribute	**Description**
Name	REMACDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

BEN_NAME

Attribute	**Description**
Name	BEN_NAME
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	255

CHARGE_AC_DESC

Attribute	Description
Name	CHARGE_AC_DESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255

SCHEDULEDATE

Attribute	Description
Name	SCHEDULEDATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Pdvws-All-Ac-Entries--Master

Attribute	Description
Name	Pdvws-All-Ac-Entries--Master
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

Pdvws-All-Ac-Entries

Attribute	Description

Name	Pdvws-All-Ac-Entries
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

ACBRN

Attribute	Description
Name	ACBRN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

ACNO

Attribute	Description
Name	ACNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

FCYAMT

Attribute	Description
Name	FCYAMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

EXCHRATE

Attribute	Description
Name	EXCHRATE
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: totalDigits / 22

LCYAMT

Attribute	**Description**
Name	LCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TRNDT

Attribute	**Description**
Name	TRNDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

VALUEDT

Attribute	**Description**
Name	VALUEDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

AMTTAG

Attribute	**Description**
Name	AMTTAG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

OVDRIDES

Attribute	Description
Name	OVDRIDES
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

Master

Attribute	Description
Name	Master
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Detb-Pdc-Linkages

Attribute	Description
Name	Detb-Pdc-Linkages
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

CUSTOMERNO

Attribute	Description
Name	CUSTOMERNO
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / P,C,F

LINKREFNO

Attribute	Description
Name	LINKREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 35

LNKPXNTG

Attribute	Description
Name	LNKPXNTG
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

LINKAMT

Attribute	Description
Name	LINKAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>X,F,P</td></tr></table>

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>1,2,3,4,5,6,7,8,9</td></tr></table>

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Control

Attribute	Description
Name	Control
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Balance-Trnsfer-Log-Details

Attribute	Description
Name	Balance-Trnsfer-Log-Details
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

PERIOD_CODE

Attribute	**Description**
Name	PERIOD_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

FIN_YEAR

Attribute	**Description**
Name	FIN_YEAR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFERENCE_NO

Attribute	**Description**
Name	REFERENCE_NO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

GL_CODE

Attribute	**Description**

Name	GL_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFERENCE_TYPE

Attribute	**Description**
Name	REFERENCE_TYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TRANSFER_IND

Attribute	**Description**
Name	TRANSFER_IND
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

MIS_CLASS

Attribute	**Description**
Name	MIS_CLASS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TXN_DATE

Attribute	**Description**

Name	TXN_DATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

OLD_MIS_CODE

Attribute	Description
Name	OLD_MIS_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

NEW_MIS_CODE

Attribute	Description
Name	NEW_MIS_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: totalDigits / 22

EX_RATE

Attribute	**Description**
Name	EX_RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 24

Charge

Attribute	**Description**
Name	Charge
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

TRNREF

Attribute	**Description**
Name	TRNREF
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

EVSEQNO

Attribute	**Description**
Name	EVSEQNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22

Contract-Charges

Attribute	Description
Name	Contract-Charges
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	15

PICKUP_EVENT_SEQUENCE_NUMBER

Attribute	Description
Name	PICKUP_EVENT_SEQUENCE_NUMBER
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

VALUE_DATE

Attribute	Description
Name	VALUE_DATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TRANSACTION_DATE

Attribute	**Description**
Name	TRANSACTION_DATE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

CHANGE_DURING_AMENDMENT

Attribute	**Description**
Name	CHANGE_DURING_AMENDMENT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

CURRENCY

Attribute	**Description**
Name	CURRENCY
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

AMOUNT

Attribute	**Description**
Name	AMOUNT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

RATE

Attribute	Description
Name	RATE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

PARTY

Attribute	Description
Name	PARTY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.2.4.PD-CreatePDContract-Res-PK-MSG.xsd

CREATEPDCONTRACT_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Pdvws-Pdc-Master-PK

TRNREFNO

Pdvws-Pdc-Master-IO

TRNREFNO

REMITTER_ACCOUNT_NO

BENACNO

INSTRNO

CCY

AMT

CLEARING_PRODUCT

RTNGNO

ENDPNT

ISSUER_BANK

ISSUER_BRANCH

PURPOSE

ACTIVATION_DT

LOCNOFCHQ

CHARGE_BRANCH

CHG_ACC_NUMBER

CHGCCY

CLRBNK

PCCLGBRN

SECTORCD

RECSTAT

DUMMY

LOAN_ACCNO

REMARKS

CREDITLINE

LIMTRACKREQD

CHQ_INQUIRY

OPERATION

USERREFNO

DRWPARTYID

CHQDATE

SCHEDULEDATE

Pdvws-All-Ac-Entries--Master

- *EVENT*
- *Pdvws-All-Ac-Entries*
  - *EVENT*
  - *ACBRN*
  - *ACNO*
  - *DRCRIND*
  - *ACCCY*
  - *CODE*
  - *FCYAMT*
  - *EXCHRATE*
  - *LCYAMT*
  - *TRNDT*
  - *VALUEDT*
  - *AMTTAG*

Csvws-Contract-Ovd

- *OVDRIDES*

Detb-Pdc-Linkages

- *CUSTOMERNO*
- *LINKAGE_TYPE*

LINKREFNO

LNKPXNTG

LINKAMT

Misdetails

CONREFNO

MISGRP

RELACC

RELETED_REFERENCE

MISHEAD

RATEFLG

POOLCD

REFINANCE_RATE

REFRATETYP

PROCALCMTH

REFSPREAD

REFRATECD

COSTCD1

COSTCD2

COSTCD3

COSTCD4

COSTCD5

TXNMIS1

TXNMIS10

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

MISGRPCOMP

MISGRPTXN

COMPMIS1

COMPMIS10

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

FUNDMIS1

FUNDMIS10

FUNDMIS2

FUNDMIS3

FUNDMIS4

FUNDMIS5

FUNDMIS6

FUNDMIS7

FUNDMIS8

FUNDMIS9

MISGRPFUN

Txnmisdetails

Compmisdetails

Fundmisdetails

Balance-Trnsfer-Log-Details

- *BRANCH*
- *PERIOD_CODE*
- *FIN_YEAR*
- *REFERENCE_NO*
- *GL_CODE*
- *REFERENCE_TYPE*

TRANSFER_IND

MIS_CLASS

TXN_DATE

OLD_MIS_CODE

NEW_MIS_CODE

CCY

AMOUNT

EX_RATE

Charge

TRNREF

EVSEQNO

Contract-Charges

PICKUP_EVENT_SEQUENCE_NUMBER

VALUE_DATE

EVENT_SEQ_NO

TRANSACTION_DATE

CHANGE_DURING_AMENDMENT

AMOUNT

STATUS

WAIVER

RATE_TYPE

PARTY

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATEPDCONTRACT_IOPK_RES

Attribute	Description
Name	CREATEPDCONTRACT_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL

Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Pdvws-Pdc-Master-PK

Attribute	Description
Name	Pdvws-Pdc-Master-PK
Datatype	
Description	

TRNREFNO

Attribute	Description
Name	TRNREFNO
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

Pdvws-Pdc-Master-IO

Attribute	Description

Name	Pdvws-Pdc-Master-IO
Datatype	
Description	

TRNREFNO

Attribute	Description
Name	TRNREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

REMITTER_ACCOUNT_NO

Attribute	Description
Name	REMITTER_ACCOUNT_NO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

BENACNO

Attribute	Description
Name	BENACNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

AMT

Attribute	Description
Name	AMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CLEARING_PRODUCT

Attribute	Description
Name	CLEARING_PRODUCT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

RTNGNO

Attribute	Description
Name	RTNGNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>27</td></tr></table>

ENDPNT

Attribute	Description
Name	ENDPNT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

ISSUER_BANK

Attribute	Description
Name	ISSUER_BANK
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

ISSUER_BRANCH

Attribute	Description
Name	ISSUER_BRANCH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

PURPOSE

Attribute	Description
Name	PURPOSE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

ACTIVATION_DT

Attribute	Description
Name	ACTIVATION_DT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

LOCNOFCHQ

Attribute	Description
Name	LOCNOFCHQ
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

CHARGE_BRANCH

Attribute	Description
Name	CHARGE_BRANCH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

CHG_ACC_NUMBER

Attribute	Description
Name	CHG_ACC_NUMBER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

CLRBNK

Attribute	**Description**
Name	CLRBNK
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 36

PCCLGBRN

Attribute	**Description**
Name	PCCLGBRN
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 36

SECTORCD

Attribute	**Description**
Name	SECTORCD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 36

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

DUMMY

Attribute	**Description**
Name	DUMMY
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 420

LOAN_ACCNO

Attribute	**Description**
Name	LOAN_ACCNO
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

REMARKS

Attribute	**Description**
Name	REMARKS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

CREDITLINE

Attribute	**Description**
Name	CREDITLINE
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** maxLength / 16

LIMTRACKREQD

Attribute	**Description**
Name	LIMTRACKREQD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,Y

CHQ_INQUIRY

Attribute	**Description**
Name	CHQ_INQUIRY
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Discounted,Normal,Purchased,Collection,Collection after purchase,Collection after discount,Returned,Passed,Pullback

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,,D

USERREFNO

Attribute	**Description**

Name	USERREFNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

DRWPARTYID

Attribute	**Description**
Name	DRWPARTYID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHQDATE

Attribute	**Description**
Name	CHQDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

SCHEDULEDATE

Attribute	**Description**
Name	SCHEDULEDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Pdvws-All-Ac-Entries--Master

Attribute	**Description**
Name	Pdvws-All-Ac-Entries--Master
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

Pdvws-All-Ac-Entries

Attribute	Description
Name	Pdvws-All-Ac-Entries
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

ACBRN

Attribute	Description
Name	ACBRN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

ACNO

Attribute	Description

Name	ACNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

DRCRIND

Attribute	**Description**
Name	DRCRIND
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

ACCCY

Attribute	**Description**
Name	ACCCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

CODE

Attribute	**Description**
Name	CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

FCYAMT

Attribute	**Description**

Name	FCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

EXCHRATE

Attribute	**Description**
Name	EXCHRATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

LCYAMT

Attribute	**Description**
Name	LCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TRNDT

Attribute	**Description**
Name	TRNDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

VALUEDT

Attribute	**Description**
Name	VALUEDT
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

OVDRIDES

Attribute	Description
Name	OVDRIDES
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

Detb-Pdc-Linkages

Attribute	Description
Name	Detb-Pdc-Linkages
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

CUSTOMERNO

Attribute	Description
Name	CUSTOMERNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 9

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / P,C,F

LINKREFNO

Attribute	Description
Name	LINKREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 35

LNKPXNTG

Attribute	Description
Name	LNKPXNTG
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

LINKAMT

Attribute	Description
Name	LINKAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

MISHEAD

Attribute	**Description**
Name	MISHEAD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

RATEFLG

Attribute	**Description**
Name	RATEFLG
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

POOLCD

Attribute	**Description**
Name	POOLCD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

REFINANCE_RATE

Attribute	**Description**
Name	REFINANCE_RATE
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

REFRATETYP

Attribute	**Description**
Name	REFRATETYP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,P

PROCALCMTH

Attribute	**Description**
Name	PROCALCMTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9

REFSPREAD

Attribute	**Description**
Name	REFSPREAD
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

REFRATECD

Attribute	**Description**
Name	REFRATECD
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

COSTCD1

Attribute	**Description**
Name	COSTCD1
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

COSTCD2

Attribute	**Description**
Name	COSTCD2
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

COSTCD3

Attribute	**Description**
Name	COSTCD3
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

COSTCD4

Attribute	**Description**
Name	COSTCD4
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

COSTCD5

Attribute	**Description**
Name	COSTCD5
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TXNMIS10

Attribute	**Description**
Name	TXNMIS10
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TXNMIS2

Attribute	**Description**
Name	TXNMIS2
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TXNMIS3

Attribute	**Description**
Name	TXNMIS3
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TXNMIS4

Attribute	**Description**
Name	TXNMIS4
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TXNMIS5

Attribute	**Description**
Name	TXNMIS5
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TXNMIS6

Attribute	**Description**
Name	TXNMIS6
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TXNMIS7

Attribute	**Description**
Name	TXNMIS7
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TXNMIS8

Attribute	**Description**
Name	TXNMIS8
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TXNMIS9

Attribute	**Description**
Name	TXNMIS9
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

MISGRPCOMP

Attribute	**Description**
Name	MISGRPCOMP
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

MISGRPTXN

Attribute	**Description**
Name	MISGRPTXN
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

COMPMIS1

Attribute	**Description**
Name	COMPMIS1
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

COMPMIS10

Attribute	**Description**
Name	COMPMIS10
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

COMPMIS2

Attribute	**Description**
Name	COMPMIS2
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

COMPMIS3

Attribute	**Description**
Name	COMPMIS3
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

COMPMIS4

Attribute	**Description**
Name	COMPMIS4
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

COMPMIS5

Attribute	**Description**
Name	COMPMIS5
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

COMPMIS6

Attribute	**Description**
Name	COMPMIS6
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** maxLength / 10

COMPMIS7

Attribute	**Description**
Name	COMPMIS7
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

COMPMIS8

Attribute	**Description**
Name	COMPMIS8
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

COMPMIS9

Attribute	**Description**
Name	COMPMIS9
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

FUNDMIS1

Attribute	**Description**
Name	FUNDMIS1
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 10

FUNDMIS10

Attribute	**Description**
Name	FUNDMIS10
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

FUNDMIS2

Attribute	**Description**
Name	FUNDMIS2
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

FUNDMIS3

Attribute	**Description**
Name	FUNDMIS3
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

FUNDMIS4

Attribute	**Description**
Name	FUNDMIS4
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

FUNDMIS5

Attribute	**Description**
Name	FUNDMIS5
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

FUNDMIS6

Attribute	**Description**
Name	FUNDMIS6
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

FUNDMIS7

Attribute	**Description**
Name	FUNDMIS7
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

FUNDMIS8

Attribute	**Description**
Name	FUNDMIS8
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

FUNDMIS9

Attribute	**Description**
Name	FUNDMIS9
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

MISGRPFUN

Attribute	**Description**
Name	MISGRPFUN
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

Txnmisdetails

Attribute	**Description**
Name	Txnmisdetails
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

Compmisdetails

Attribute	**Description**
Name	Compmisdetails
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

Balance-Trnsfer-Log-Details

Attribute	Description
Name	Balance-Trnsfer-Log-Details
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

PERIOD_CODE

Attribute	Description
Name	PERIOD_CODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

FIN_YEAR

Attribute	Description
Name	FIN_YEAR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

GL_CODE

Attribute	Description
Name	GL_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

REFERENCE_TYPE

Attribute	Description
Name	REFERENCE_TYPE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TRANSFER_IND

Attribute	Description
Name	TRANSFER_IND
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

MIS_CLASS

Attribute	Description
Name	MIS_CLASS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXN_DATE

Attribute	Description
Name	TXN_DATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

OLD_MIS_CODE

Attribute	Description
Name	OLD_MIS_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

NEW_MIS_CODE

Attribute	Description
Name	NEW_MIS_CODE
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

AMOUNT

Attribute	**Description**
Name	AMOUNT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

EX_RATE

Attribute	**Description**
Name	EX_RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 24

Charge

Attribute	**Description**
Name	Charge
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0

TRNREF

Attribute	Description
Name	TRNREF
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

EVSEQNO

Attribute	Description
Name	EVSEQNO
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

Contract-Charges

Attribute	Description
Name	Contract-Charges
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PICKUP_EVENT_SEQUENCE_NUMBER

Attribute	Description
Name	PICKUP_EVENT_SEQUENCE_NUMBER
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

VALUE_DATE

Attribute	Description
Name	VALUE_DATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

TRANSACTION_DATE

Attribute	Description
Name	TRANSACTION_DATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

CHANGE_DURING_AMENDMENT

Attribute	Description
Name	CHANGE_DURING_AMENDMENT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

AMOUNT

Attribute	Description

Name	AMOUNT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

STATUS

Attribute	**Description**
Name	STATUS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

RATE_TYPE

Attribute	**Description**
Name	RATE_TYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

PARTY

Attribute	**Description**

Name	PARTY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.3.DeletePDContract

2.3.1.PD-DeletePDContract-Req-Full-MSG.xsd

DELETEPDCONTRACT_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Pdvws-Pdc-Master-Full

TRNREFNO

EVSEQNO

SCODE

XREF

PRDCD

BRANCH_CODE

REMITTER_ACCOUNT_NO

BENACNO

INSTRNO

CCY

AMT

VALDT

CLEARING_PRODUCT

RTNGNO

ENDPNT

ISSUER_BANK

ISSUER_BRANCH

PURPOSE

ACTIVATION_DT

LOCNOFCHQ

BLKTXNREF

CHARGE_BRANCH

CHG_ACC_NUMBER

CHGCCY

MAKERID

AUTHSTAT

ONCEAUTH

MAKERSTAMP

CHECKERID

CHECKERSTAMP

MODNO

PRODDESC

BRNDESC

CLGPRODDESC

ISRBNKDESC

ISRBRNDESC

ENDPNTDESC

CHGPAYBRNDESC

CLRBNK

PCCLGBRN

SECTORCD

RECSTAT

DUMMY

LOAN_ACCNO

REMARKS

CREDITLINE

LIMTRACKREQD

FRM_DT

TODATE

DOWNPMT

CHQ_INQUIRY

OPERATION

USERREFNO

DRWPARTYID

CHQDATE

TXNSTAT

REMACDESC

BEN_NAME

CHARGE_AC_DESC

SCHEDULEDATE

Pdvws-All-Ac-Entries--Master

EVENT

Pdvws-All-Ac-Entries

EVENT

ACBRN

ACNO

DRCRIND

ACCCY

CODE

FCYAMT

EXCHRATE

LCYAMT

TRNDT

VALUEDT

AMTTAG

Csvws-Contract-Ovd

OVDRIDES

Master

Detb-Pdc-Linkages

CUSTOMERNO

LINKAGE_TYPE

LINKREFNO

LNKPXNTG

LINKAMT

Misdetails

CONREFNO

MISGRP

RELACC

RELETED_REFERENCE

MISHEAD

RATEFLG

POOLCD

REFINANCE_RATE

REFRATETYP

PROCALCMTH

REFSPREAD

REFRATECD

COSTCD1

COSTCD2

COSTCD3

COSTCD4

COSTCD5

TXNMIS1

TXNMIS10

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

MISGRPCOMP

MISGRPTXN

COMPMIS1

COMPMIS10

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

FUNDMIS1

FUNDMIS10

FUNDMIS2

FUNDMIS3

FUNDMIS4

FUNDMIS5

FUNDMIS6

FUNDMIS7

FUNDMIS8

FUNDMIS9

MISGRPFUN

TRANMIS1

TRANMIS2

TRANMIS3

TRANMIS4

TRANMIS5

TRANMIS6

TRANMIS7

TRANMIS8

TRANMIS9

TRANMIS10

COMMIS1

COMMIS2

COMMIS3

COMMIS4

COMMIS5

COMMIS6

COMMIS7

COMMIS8

COMMIS9

COMMIS10

FUNMIS1

FUNMIS2

FUNMIS3

FUNMIS4

FUNMIS5

FUNMIS6

FUNMIS7

FUNMIS8

FUNMIS9

FUNMIS10

Txnmisdetails

Compmisdetails

Fundmisdetails

Control

Balance-Trnsfer-Log-Details

BRANCH

PERIOD_CODE

FIN_YEAR

REFERENCE_NO

GL_CODE

REFERENCE_TYPE

TRANSFER_IND

MIS_CLASS

TXN_DATE

OLD_MIS_CODE

NEW_MIS_CODE

CCY

AMOUNT

EX_RATE

Charge

TRNREF

EVSEQNO

Contract-Charges

COMPONENT

PICKUP_EVENT_SEQUENCE_NUMBER

VALUE_DATE

EVENT_SEQ_NO

TRANSACTION_DATE

CHANGE_DURING_AMENDMENT

CURRENCY

AMOUNT

STATUS

WAIVER

RATE

RATE_TYPE

EVENT

PARTY

TXNUDFDETAILS

FLDNAME

FLDVAL

DELETEPDCONTRACT_FSFS_REQ

Attribute	Description
Name	DELETEPDCONTRACT_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Pdvws-Pdc-Master-Full

Attribute	Description

Name	Pdvws-Pdc-Master-Full
Datatype	
Description	

TRNREFNO

Attribute	Description
Name	TRNREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

EVSEQNO

Attribute	Description
Name	EVSEQNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

SCODE

Attribute	Description
Name	SCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

REMITTER_ACCOUNT_NO

Attribute	Description
Name	REMITTER_ACCOUNT_NO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

BENACNO

Attribute	Description
Name	BENACNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

AMT

Attribute	Description
Name	AMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

VALDT

Attribute	Description
Name	VALDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

CLEARING_PRODUCT

Attribute	Description
Name	CLEARING_PRODUCT
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

RTNGNO

Attribute	**Description**
Name	RTNGNO
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 27

ENDPNT

Attribute	**Description**
Name	ENDPNT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

ISSUER_BANK

Attribute	**Description**
Name	ISSUER_BANK
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

ISSUER_BRANCH

Attribute	**Description**
Name	ISSUER_BRANCH
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

PURPOSE

Attribute	**Description**
Name	PURPOSE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

ACTIVATION_DT

Attribute	**Description**
Name	ACTIVATION_DT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

LOCNOFCHQ

Attribute	**Description**
Name	LOCNOFCHQ
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

BLKTXNREF

Attribute	**Description**
Name	BLKTXNREF
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	16

CHARGE_BRANCH

Attribute	Description
Name	CHARGE_BRANCH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

CHG_ACC_NUMBER

Attribute	Description
Name	CHG_ACC_NUMBER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: maxLength / 12

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,A

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

BRNDESC

Attribute	Description
Name	BRNDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

CLGPRODDESC

Attribute	Description
Name	CLGPRODDESC

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>420</td></tr></table>

ISRBNKDESC

Attribute	Description
Name	ISRBNKDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>420</td></tr></table>

ISRBRNDESC

Attribute	Description
Name	ISRBRNDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>420</td></tr></table>

ENDPNTDESC

Attribute	Description
Name	ENDPNTDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>420</td></tr></table>

CHGPAYBRNDESC

Attribute	Description
Name	CHGPAYBRNDESC

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>420</td></tr></table>

CLRBNK

Attribute	Description
Name	CLRBNK
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>36</td></tr></table>

PCCLGBRN

Attribute	Description
Name	PCCLGBRN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>36</td></tr></table>

SECTORCD

Attribute	Description
Name	SECTORCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>36</td></tr></table>

RECSTAT

Attribute	Description
Name	RECSTAT

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

DUMMY

Attribute	Description
Name	DUMMY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>420</td></tr></table>

LOAN_ACCNO

Attribute	Description
Name	LOAN_ACCNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

CREDITLINE

Attribute	Description
Name	CREDITLINE

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

LIMTRACKREQD

Attribute	Description
Name	LIMTRACKREQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

FRM_DT

Attribute	Description
Name	FRM_DT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TODATE

Attribute	Description
Name	TODATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DOWNPMT

Attribute	Description
Name	DOWNPMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22

CHQ_INQUIRY

Attribute	Description
Name	CHQ_INQUIRY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Discounted,Normal,Purchased,Collection,Collection after purchase,Collection after discount,Returned,Passed,Pullback

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	P,,D

USERREFNO

Attribute	Description
Name	USERREFNO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

DRWPARTYID

Attribute	Description
Name	DRWPARTYID
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

CHQDATE

Attribute	**Description**
Name	CHQDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,V,U,L,K,C

REMACDESC

Attribute	**Description**
Name	REMACDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

BEN_NAME

Attribute	**Description**
Name	BEN_NAME
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	255

CHARGE_AC_DESC

Attribute	Description
Name	CHARGE_AC_DESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255

SCHEDULEDATE

Attribute	Description
Name	SCHEDULEDATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Pdvws-All-Ac-Entries--Master

Attribute	Description
Name	Pdvws-All-Ac-Entries--Master
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

Pdvws-All-Ac-Entries

Attribute	Description

Name	Pdvws-All-Ac-Entries
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

EVENT

Attribute	**Description**
Name	EVENT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

ACBRN

Attribute	**Description**
Name	ACBRN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

ACNO

Attribute	**Description**
Name	ACNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

DRCRIND

Attribute	**Description**
Name	DRCRIND
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

ACCCY

Attribute	**Description**
Name	ACCCY
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

CODE

Attribute	**Description**
Name	CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

FCYAMT

Attribute	**Description**
Name	FCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

EXCHRATE

Attribute	**Description**
Name	EXCHRATE
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

LCYAMT

Attribute	**Description**
Name	LCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TRNDT

Attribute	**Description**
Name	TRNDT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

VALUEDT

Attribute	**Description**
Name	VALUEDT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

AMTTAG

Attribute	**Description**
Name	AMTTAG
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

OVDRIDES

Attribute	Description
Name	OVDRIDES
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

Master

Attribute	Description
Name	Master
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Detb-Pdc-Linkages

Attribute	Description
Name	Detb-Pdc-Linkages
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

CUSTOMERNO

Attribute	Description
Name	CUSTOMERNO
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / P,C,F

LINKREFNO

Attribute	Description
Name	LINKREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 35

LNKPXNTG

Attribute	Description
Name	LNKPXNTG
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

LINKAMT

Attribute	Description
Name	LINKAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	

Attribute	**Attribute** / **Description** minOccurs / 0

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

MISGRP

Attribute	**Description**
Name	MISGRP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

RELACC

Attribute	**Description**
Name	RELACC
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

RELETED_REFERENCE

Attribute	**Description**
Name	RELETED_REFERENCE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>X,F,P</td></tr></table>

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>1,2,3,4,5,6,7,8,9</td></tr></table>

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Control

Attribute	Description
Name	Control
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Balance-Trnsfer-Log-Details

Attribute	Description
Name	Balance-Trnsfer-Log-Details
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

PERIOD_CODE

Attribute	**Description**
Name	PERIOD_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

FIN_YEAR

Attribute	**Description**
Name	FIN_YEAR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFERENCE_NO

Attribute	**Description**
Name	REFERENCE_NO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

GL_CODE

Attribute	**Description**

Name	GL_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFERENCE_TYPE

Attribute	**Description**
Name	REFERENCE_TYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TRANSFER_IND

Attribute	**Description**
Name	TRANSFER_IND
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

MIS_CLASS

Attribute	**Description**
Name	MIS_CLASS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TXN_DATE

Attribute	**Description**

Name	TXN_DATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

OLD_MIS_CODE

Attribute	Description
Name	OLD_MIS_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

NEW_MIS_CODE

Attribute	Description
Name	NEW_MIS_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

EX_RATE

Attribute	**Description**
Name	EX_RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 24

Charge

Attribute	**Description**
Name	Charge
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

TRNREF

Attribute	**Description**
Name	TRNREF
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

EVSEQNO

Attribute	**Description**
Name	EVSEQNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22

Contract-Charges

Attribute	Description
Name	Contract-Charges
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	15

PICKUP_EVENT_SEQUENCE_NUMBER

Attribute	Description
Name	PICKUP_EVENT_SEQUENCE_NUMBER
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

VALUE_DATE

Attribute	Description
Name	VALUE_DATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TRANSACTION_DATE

Attribute	**Description**
Name	TRANSACTION_DATE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

CHANGE_DURING_AMENDMENT

Attribute	**Description**
Name	CHANGE_DURING_AMENDMENT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

CURRENCY

Attribute	**Description**
Name	CURRENCY
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

AMOUNT

Attribute	**Description**
Name	AMOUNT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	
	Restrictions / **Description**: totalDigits / 22

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

RATE

Attribute	Description
Name	RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	1

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

PARTY

Attribute	Description
Name	PARTY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.3.2.PD-DeletePDContract-Req-IO-MSG.xsd

DELETEPDCONTRACT_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Pdvws-Pdc-Master-IO

TRNREFNO

DELETEPDCONTRACT_IOPK_REQ

Attribute	Description
Name	DELETEPDCONTRACT_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	
	Restrictions / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description**: minOccurs / 0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Pdvws-Pdc-Master-IO

Attribute	Description
Name	Pdvws-Pdc-Master-IO
Datatype	
Description	

TRNREFNO

Attribute	Description
Name	TRNREFNO
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

2.3.3.PD-DeletePDContract-Res-Full-MSG.xsd

- *DELETEPDCONTRACT_FSFS_RES*
  - *FCUBS_HEADER*
    - *SOURCE*
    - *UBSCOMP*
    - *MSGID*
    - *CORRELID*
    - *USERID*
    - *BRANCH*
    - *MODULEID*
    - *SERVICE*
    - *OPERATION*
    - *SOURCE_OPERATION*
    - *SOURCE_USERID*
    - *DESTINATION*
    - *MULTITRIPID*
    - *FUNCTIONID*
    - *ACTION*
    - *MSGSTAT*
    - *PASSWORD*
    - *ADDL*
      - *PARAM*
        - *NAME*
        - *VALUE*
  - *FCUBS_BODY*
    - *Pdvws-Pdc-Master-Full*
      - *TRNREFNO*
      - *EVSEQNO*
      - *SCODE*
      - *XREF*
      - *PRDCD*
      - *BRANCH_CODE*
      - *REMITTER_ACCOUNT_NO*

BENACNO

INSTRNO

CCY

AMT

VALDT

CLEARING_PRODUCT

RTNGNO

ENDPNT

ISSUER_BANK

ISSUER_BRANCH

PURPOSE

ACTIVATION_DT

LOCNOFCHQ

BLKTXNREF

CHARGE_BRANCH

CHG_ACC_NUMBER

CHGCCY

MAKERID

AUTHSTAT

ONCEAUTH

MAKERSTAMP

CHECKERID

CHECKERSTAMP

MODNO

PRODDESC

BRNDESC

CLGPRODDESC

ISRBNKDESC

ISRBRNDESC

ENDPNTDESC

CHGPAYBRNDESC

CLRBNK

PCCLGBRN

SECTORCD

RECSTAT

DUMMY

LOAN_ACCNO

REMARKS

CREDITLINE

LIMTRACKREQD

FRM_DT

TODATE

DOWNPMT

CHQ_INQUIRY

OPERATION

USERREFNO

DRWPARTYID

CHQDATE

TXNSTAT

REMACDESC

BEN_NAME

CHARGE_AC_DESC

SCHEDULEDATE

Pdvws-All-Ac-Entries--Master

- *EVENT*
- *Pdvws-All-Ac-Entries*
  - *EVENT*
  - *ACBRN*
  - *ACNO*
  - *DRCRIND*
  - *ACCCY*
  - *CODE*
  - *FCYAMT*
  - *EXCHRATE*

LCYAMT

TRNDT

VALUEDT

AMTTAG

Csvws-Contract-Ovd

OVDRIDES

Master

Detb-Pdc-Linkages

CUSTOMERNO

LINKAGE_TYPE

LINKREFNO

LNKPXNTG

LINKAMT

Misdetails

CONREFNO

MISGRP

RELACC

RELETED_REFERENCE

MISHEAD

RATEFLG

POOLCD

REFINANCE_RATE

REFRATETYP

PROCALCMTH

REFSPREAD

REFRATECD

COSTCD1

COSTCD2

COSTCD3

COSTCD4

COSTCD5

TXNMIS1

TXNMIS10

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

MISGRPCOMP

MISGRPTXN

COMPMIS1

COMPMIS10

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

FUNDMIS1

FUNDMIS10

FUNDMIS2

FUNDMIS3

FUNDMIS4

FUNDMIS5

FUNDMIS6

FUNDMIS7

FUNDMIS8

FUNDMIS9

MISGRPFUN

TRANMIS1

TRANMIS2

TRANMIS3

TRANMIS4

TRANMIS5

TRANMIS6

TRANMIS7

TRANMIS8

TRANMIS9

TRANMIS10

COMMIS1

COMMIS2

COMMIS3

COMMIS4

COMMIS5

COMMIS6

COMMIS7

COMMIS8

COMMIS9

COMMIS10

FUNMIS1

FUNMIS2

FUNMIS3

FUNMIS4

FUNMIS5

FUNMIS6

FUNMIS7

FUNMIS8

FUNMIS9

FUNMIS10

Txnmisdetails

Compmisdetails

Fundmisdetails

Control

Balance-Trnsfer-Log-Details

BRANCH

PERIOD_CODE

FIN_YEAR

REFERENCE_NO

GL_CODE

REFERENCE_TYPE

TRANSFER_IND

MIS_CLASS

TXN_DATE

OLD_MIS_CODE

NEW_MIS_CODE

CCY

AMOUNT

EX_RATE

Charge

TRNREF

EVSEQNO

Contract-Charges

COMPONENT

PICKUP_EVENT_SEQUENCE_NUMBER

VALUE_DATE

EVENT_SEQ_NO

TRANSACTION_DATE

CHANGE_DURING_AMENDMENT

CURRENCY

AMOUNT

STATUS

WAIVER

RATE

RATE_TYPE

EVENT

PARTY

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETEPDCONTRACT_FSFS_RES

Attribute	Description
Name	DELETEPDCONTRACT_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	**Description**
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.

Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Pdvws-Pdc-Master-Full
Datatype	
Description	

TRNREFNO

Attribute	Description
Name	TRNREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

EVSEQNO

Attribute	Description
Name	EVSEQNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

SCODE

Attribute	Description
Name	SCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	20

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	4

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

REMITTER_ACCOUNT_NO

Attribute	Description
Name	REMITTER_ACCOUNT_NO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

BENACNO

Attribute	Description
Name	BENACNO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

AMT

Attribute	Description
Name	AMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

VALDT

Attribute	Description
Name	VALDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

CLEARING_PRODUCT

Attribute	Description
Name	CLEARING_PRODUCT

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

RTNGNO

Attribute	**Description**
Name	RTNGNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 27

ENDPNT

Attribute	**Description**
Name	ENDPNT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

ISSUER_BANK

Attribute	**Description**
Name	ISSUER_BANK
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

ISSUER_BRANCH

Attribute	**Description**
Name	ISSUER_BRANCH

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

PURPOSE

Attribute	**Description**
Name	PURPOSE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

ACTIVATION_DT

Attribute	**Description**
Name	ACTIVATION_DT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

LOCNOFCHQ

Attribute	**Description**
Name	LOCNOFCHQ
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

BLKTXNREF

Attribute	**Description**
Name	BLKTXNREF
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

CHARGE_BRANCH

Attribute	**Description**
Name	CHARGE_BRANCH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

CHG_ACC_NUMBER

Attribute	**Description**
Name	CHG_ACC_NUMBER
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

CHGCCY

Attribute	**Description**
Name	CHGCCY
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>U,A</td></tr></table>

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	420

BRNDESC

Attribute	Description
Name	BRNDESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	420

CLGPRODDESC

Attribute	Description
Name	CLGPRODDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

ISRBNKDESC

Attribute	Description
Name	ISRBNKDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

ISRBRNDESC

Attribute	Description
Name	ISRBRNDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

ENDPNTDESC

Attribute	Description
Name	ENDPNTDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

CHGPAYBRNDESC

Attribute	Description
Name	CHGPAYBRNDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>420</td></tr></table>

CLRBNK

Attribute	Description
Name	CLRBNK
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>36</td></tr></table>

PCCLGBRN

Attribute	Description
Name	PCCLGBRN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>36</td></tr></table>

SECTORCD

Attribute	Description
Name	SECTORCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>36</td></tr></table>

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

DUMMY

Attribute	Description
Name	DUMMY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>420</td></tr></table>

LOAN_ACCNO

Attribute	Description
Name	LOAN_ACCNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

LIMTRACKREQD

Attribute	Description
Name	LIMTRACKREQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

FRM_DT

Attribute	Description
Name	FRM_DT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TODATE

Attribute	Description
Name	TODATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DOWNPMT

Attribute	Description
Name	DOWNPMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22

CHQ_INQUIRY

Attribute	Description
Name	CHQ_INQUIRY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Discounted,Normal,Purchased,Collection,Collection after purchase,Collection after discount,Returned,Passed,Pullback

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	P,,D

USERREFNO

Attribute	Description
Name	USERREFNO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

DRWPARTYID

Attribute	Description
Name	DRWPARTYID
Datatype	String
Description	

Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHQDATE

Attribute	**Description**
Name	CHQDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,V,U,L,K,C

REMACDESC

Attribute	**Description**
Name	REMACDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

BEN_NAME

Attribute	**Description**
Name	BEN_NAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	255

CHARGE_AC_DESC

Attribute	Description
Name	CHARGE_AC_DESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255

SCHEDULEDATE

Attribute	Description
Name	SCHEDULEDATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Pdvws-All-Ac-Entries--Master

Attribute	Description
Name	Pdvws-All-Ac-Entries--Master
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

Pdvws-All-Ac-Entries

Attribute	Description

Name	Pdvws-All-Ac-Entries
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

EVENT

Attribute	**Description**
Name	EVENT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

ACBRN

Attribute	**Description**
Name	ACBRN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

ACNO

Attribute	**Description**
Name	ACNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

DRCRIND

Attribute	**Description**
Name	DRCRIND
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

FCYAMT

Attribute	Description
Name	FCYAMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

EXCHRATE

Attribute	Description
Name	EXCHRATE
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

LCYAMT

Attribute	**Description**
Name	LCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TRNDT

Attribute	**Description**
Name	TRNDT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

VALUEDT

Attribute	**Description**
Name	VALUEDT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

AMTTAG

Attribute	**Description**
Name	AMTTAG
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

OVDRIDES

Attribute	Description
Name	OVDRIDES
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

Master

Attribute	Description
Name	Master
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Detb-Pdc-Linkages

Attribute	Description
Name	Detb-Pdc-Linkages
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

CUSTOMERNO

Attribute	Description
Name	CUSTOMERNO
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / P,C,F

LINKREFNO

Attribute	Description
Name	LINKREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 35

LNKPXNTG

Attribute	Description
Name	LNKPXNTG
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

LINKAMT

Attribute	Description
Name	LINKAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>X,F,P</td></tr></table>

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>1,2,3,4,5,6,7,8,9</td></tr></table>

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Control

Attribute	Description
Name	Control
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Balance-Trnsfer-Log-Details

Attribute	Description
Name	Balance-Trnsfer-Log-Details
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

PERIOD_CODE

Attribute	**Description**
Name	PERIOD_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

FIN_YEAR

Attribute	**Description**
Name	FIN_YEAR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFERENCE_NO

Attribute	**Description**
Name	REFERENCE_NO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

GL_CODE

Attribute	**Description**

Name	GL_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFERENCE_TYPE

Attribute	**Description**
Name	REFERENCE_TYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TRANSFER_IND

Attribute	**Description**
Name	TRANSFER_IND
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

MIS_CLASS

Attribute	**Description**
Name	MIS_CLASS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TXN_DATE

Attribute	**Description**

Name	TXN_DATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

OLD_MIS_CODE

Attribute	Description
Name	OLD_MIS_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

NEW_MIS_CODE

Attribute	Description
Name	NEW_MIS_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

EX_RATE

Attribute	**Description**
Name	EX_RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 24

Charge

Attribute	**Description**
Name	Charge
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

TRNREF

Attribute	**Description**
Name	TRNREF
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

EVSEQNO

Attribute	**Description**
Name	EVSEQNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22

Contract-Charges

Attribute	Description
Name	Contract-Charges
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	15

PICKUP_EVENT_SEQUENCE_NUMBER

Attribute	Description
Name	PICKUP_EVENT_SEQUENCE_NUMBER
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

VALUE_DATE

Attribute	Description
Name	VALUE_DATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: totalDigits / 22

TRANSACTION_DATE

Attribute	**Description**
Name	TRANSACTION_DATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

CHANGE_DURING_AMENDMENT

Attribute	**Description**
Name	CHANGE_DURING_AMENDMENT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

CURRENCY

Attribute	**Description**
Name	CURRENCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

AMOUNT

Attribute	**Description**
Name	AMOUNT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: totalDigits / 22

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

RATE

Attribute	Description
Name	RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	1

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

PARTY

Attribute	Description
Name	PARTY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.3.4.PD-DeletePDContract-Res-PK-MSG.xsd

DELETEPDCONTRACT_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Pdvws-Pdc-Master-PK

TRNREFNO

Pdvws-Pdc-Master-IO

TRNREFNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETEPDCONTRACT_IOPK_RES

Attribute	Description
Name	DELETEPDCONTRACT_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Pdvws-Pdc-Master-PK

Attribute	Description
Name	Pdvws-Pdc-Master-PK
Datatype	
Description	

TRNREFNO

Attribute	Description
Name	TRNREFNO
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

Pdvws-Pdc-Master-IO

Attribute	Description
Name	Pdvws-Pdc-Master-IO
Datatype	
Description	

TRNREFNO

Attribute	Description
Name	TRNREFNO
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

WCODE

Attribute	Description

Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.4.LiquidatePDContract

2.4.1.PD-LiquidatePDContract-Req-Full-MSG.xsd

LIQUIDATEPDCONTRACT_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Pdvws-Pdc-Master-Full

TRNREFNO

EVSEQNO

SCODE

XREF

PRDCD

BRANCH_CODE

REMITTER_ACCOUNT_NO

BENACNO

INSTRNO

CCY

AMT

VALDT

CLEARING_PRODUCT

RTNGNO

ENDPNT

ISSUER_BANK

ISSUER_BRANCH

PURPOSE

ACTIVATION_DT

LOCNOFCHQ

BLKTXNREF

CHARGE_BRANCH

CHG_ACC_NUMBER

CHGCCY

MAKERID

AUTHSTAT

ONCEAUTH

MAKERSTAMP

CHECKERID

CHECKERSTAMP

MODNO

PRODDESC

BRNDESC

CLGPRODDESC

ISRBNKDESC

ISRBRNDESC

ENDPNTDESC

CHGPAYBRNDESC

CLRBNK

PCCLGBRN

SECTORCD

RECSTAT

DUMMY

LOAN_ACCNO

REMARKS

CREDITLINE

LIMTRACKREQD

FRM_DT

TODATE

DOWNPMT

CHQ_INQUIRY

OPERATION

USERREFNO

DRWPARTYID

CHQDATE

TXNSTAT

REMACDESC

BEN_NAME

CHARGE_AC_DESC

SCHEDULEDATE

Pdvws-All-Ac-Entries--Master

- *EVENT*
- *Pdvws-All-Ac-Entries*
  - *EVENT*

ACBRN

ACNO

DRCRIND

ACCCY

CODE

FCYAMT

EXCHRATE

LCYAMT

TRNDT

VALUEDT

AMTTAG

Csvws-Contract-Ovd

OVDRIDES

Master

Detb-Pdc-Linkages

CUSTOMERNO

LINKAGE_TYPE

LINKREFNO

LNKPXNTG

LINKAMT

Misdetails

CONREFNO

MISGRP

RELACC

RELETED_REFERENCE

MISHEAD

RATEFLG

POOLCD

REFINANCE_RATE

REFRATETYP

PROCALCMTH

REFSPREAD

REFRATECD

COSTCD1

COSTCD2

COSTCD3

COSTCD4

COSTCD5

TXNMIS1

TXNMIS10

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

MISGRPCOMP

MISGRPTXN

COMPMIS1

COMPMIS10

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

FUNDMIS1

FUNDMIS10

FUNDMIS2

FUNDMIS3

FUNDMIS4

FUNDMIS5

FUNDMIS6

FUNDMIS7

FUNDMIS8

FUNDMIS9

MISGRPFUN

TRANMIS1

TRANMIS2

TRANMIS3

TRANMIS4

TRANMIS5

TRANMIS6

TRANMIS7

TRANMIS8

TRANMIS9

TRANMIS10

COMMIS1

COMMIS2

COMMIS3

COMMIS4

COMMIS5

COMMIS6

COMMIS7

COMMIS8

COMMIS9

COMMIS10

FUNMIS1

FUNMIS2

FUNMIS3

FUNMIS4

FUNMIS5

FUNMIS6

FUNMIS7

FUNMIS8

FUNMIS9

FUNMIS10

Txnmisdetails

Compmisdetails

Fundmisdetails

Control

Balance-Trnsfer-Log-Details

BRANCH

PERIOD_CODE

FIN_YEAR

REFERENCE_NO

GL_CODE

REFERENCE_TYPE

TRANSFER_IND

MIS_CLASS

TXN_DATE

OLD_MIS_CODE

NEW_MIS_CODE

CCY

AMOUNT

EX_RATE

Charge

TRNREF

EVSEQNO

Contract-Charges

COMPONENT

PICKUP_EVENT_SEQUENCE_NUMBER

VALUE_DATE

EVENT_SEQ_NO

TRANSACTION_DATE

CHANGE_DURING_AMENDMENT

CURRENCY

AMOUNT

STATUS

WAIVER

RATE

RATE_TYPE

EVENT

PARTY

TXNUDFDETAILS

FLDNAME

FLDVAL

LIQUIDATEPDCONTRACT_FSFS_REQ

Attribute	Description
Name	LIQUIDATEPDCONTRACT_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE

Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	

Pdvws-Pdc-Master-Full

Attribute	**Description**

Name	Pdvws-Pdc-Master-Full
Datatype	
Description	

TRNREFNO

Attribute	Description
Name	TRNREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

EVSEQNO

Attribute	Description
Name	EVSEQNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

SCODE

Attribute	Description
Name	SCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

REMITTER_ACCOUNT_NO

Attribute	Description
Name	REMITTER_ACCOUNT_NO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

BENACNO

Attribute	Description
Name	BENACNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

AMT

Attribute	Description
Name	AMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

VALDT

Attribute	Description
Name	VALDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

CLEARING_PRODUCT

Attribute	Description
Name	CLEARING_PRODUCT
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

RTNGNO

Attribute	**Description**
Name	RTNGNO
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 27

ENDPNT

Attribute	**Description**
Name	ENDPNT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

ISSUER_BANK

Attribute	**Description**
Name	ISSUER_BANK
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

ISSUER_BRANCH

Attribute	**Description**
Name	ISSUER_BRANCH
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** maxLength / 35

PURPOSE

Attribute	**Description**
Name	PURPOSE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

ACTIVATION_DT

Attribute	**Description**
Name	ACTIVATION_DT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

LOCNOFCHQ

Attribute	**Description**
Name	LOCNOFCHQ
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

BLKTXNREF

Attribute	**Description**
Name	BLKTXNREF
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	16

CHARGE_BRANCH

Attribute	Description
Name	CHARGE_BRANCH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

CHG_ACC_NUMBER

Attribute	Description
Name	CHG_ACC_NUMBER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: maxLength / 12

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,A

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>420</td></tr></table>

BRNDESC

Attribute	Description
Name	BRNDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>420</td></tr></table>

CLGPRODDESC

Attribute	Description
Name	CLGPRODDESC

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>420</td></tr></table>

ISRBNKDESC

Attribute	Description
Name	ISRBNKDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>420</td></tr></table>

ISRBRNDESC

Attribute	Description
Name	ISRBRNDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>420</td></tr></table>

ENDPNTDESC

Attribute	Description
Name	ENDPNTDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>420</td></tr></table>

CHGPAYBRNDESC

Attribute	Description
Name	CHGPAYBRNDESC

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>420</td></tr></table>

CLRBNK

Attribute	Description
Name	CLRBNK
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>36</td></tr></table>

PCCLGBRN

Attribute	Description
Name	PCCLGBRN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>36</td></tr></table>

SECTORCD

Attribute	Description
Name	SECTORCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>36</td></tr></table>

RECSTAT

Attribute	Description
Name	RECSTAT

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

DUMMY

Attribute	**Description**
Name	DUMMY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

LOAN_ACCNO

Attribute	**Description**
Name	LOAN_ACCNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

REMARKS

Attribute	**Description**
Name	REMARKS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

CREDITLINE

Attribute	**Description**
Name	CREDITLINE

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

LIMTRACKREQD

Attribute	**Description**
Name	LIMTRACKREQD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

FRM_DT

Attribute	**Description**
Name	FRM_DT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

TODATE

Attribute	**Description**
Name	TODATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

DOWNPMT

Attribute	**Description**
Name	DOWNPMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22

CHQ_INQUIRY

Attribute	Description
Name	CHQ_INQUIRY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Discounted,Normal,Purchased,Collection,Collection after purchase,Collection after discount,Returned,Passed,Pullback

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	P,,D

USERREFNO

Attribute	Description
Name	USERREFNO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

DRWPARTYID

Attribute	Description
Name	DRWPARTYID
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

CHQDATE

Attribute	**Description**
Name	CHQDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,V,U,L,K,C

REMACDESC

Attribute	**Description**
Name	REMACDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

BEN_NAME

Attribute	**Description**
Name	BEN_NAME
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	255

CHARGE_AC_DESC

Attribute	Description
Name	CHARGE_AC_DESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255

SCHEDULEDATE

Attribute	Description
Name	SCHEDULEDATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Pdvws-All-Ac-Entries--Master

Attribute	Description
Name	Pdvws-All-Ac-Entries--Master
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

Pdvws-All-Ac-Entries

Attribute	Description

Name	Pdvws-All-Ac-Entries
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

EVENT

Attribute	**Description**
Name	EVENT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

ACBRN

Attribute	**Description**
Name	ACBRN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

ACNO

Attribute	**Description**
Name	ACNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

DRCRIND

Attribute	**Description**
Name	DRCRIND
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 1

ACCCY

Attribute	**Description**
Name	ACCCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

CODE

Attribute	**Description**
Name	CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

FCYAMT

Attribute	**Description**
Name	FCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

EXCHRATE

Attribute	**Description**
Name	EXCHRATE
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

LCYAMT

Attribute	**Description**
Name	LCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TRNDT

Attribute	**Description**
Name	TRNDT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

VALUEDT

Attribute	**Description**
Name	VALUEDT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

AMTTAG

Attribute	**Description**
Name	AMTTAG
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

OVDRIDES

Attribute	Description
Name	OVDRIDES
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

Master

Attribute	Description
Name	Master
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Detb-Pdc-Linkages

Attribute	Description
Name	Detb-Pdc-Linkages
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

CUSTOMERNO

Attribute	Description
Name	CUSTOMERNO
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / P,C,F

LINKREFNO

Attribute	Description
Name	LINKREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 35

LNKPXNTG

Attribute	Description
Name	LNKPXNTG
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

LINKAMT

Attribute	Description
Name	LINKAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	

Attribute	**Attribute** / **Description** minOccurs / 0

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

MISGRP

Attribute	**Description**
Name	MISGRP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

RELACC

Attribute	**Description**
Name	RELACC
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

RELETED_REFERENCE

Attribute	**Description**
Name	RELETED_REFERENCE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>X,F,P</td></tr></table>

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>1,2,3,4,5,6,7,8,9</td></tr></table>

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Control

Attribute	Description
Name	Control
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Balance-Trnsfer-Log-Details

Attribute	Description
Name	Balance-Trnsfer-Log-Details
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

PERIOD_CODE

Attribute	**Description**
Name	PERIOD_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

FIN_YEAR

Attribute	**Description**
Name	FIN_YEAR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFERENCE_NO

Attribute	**Description**
Name	REFERENCE_NO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

GL_CODE

Attribute	**Description**

Name	GL_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFERENCE_TYPE

Attribute	**Description**
Name	REFERENCE_TYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TRANSFER_IND

Attribute	**Description**
Name	TRANSFER_IND
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

MIS_CLASS

Attribute	**Description**
Name	MIS_CLASS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TXN_DATE

Attribute	**Description**

Name	TXN_DATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

OLD_MIS_CODE

Attribute	Description
Name	OLD_MIS_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

NEW_MIS_CODE

Attribute	Description
Name	NEW_MIS_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Decimal
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

EX_RATE

Attribute	Description
Name	EX_RATE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>24</td></tr></table>

Charge

Attribute	Description
Name	Charge
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TRNREF

Attribute	Description
Name	TRNREF
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

EVSEQNO

Attribute	Description
Name	EVSEQNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22

Contract-Charges

Attribute	Description
Name	Contract-Charges
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	15

PICKUP_EVENT_SEQUENCE_NUMBER

Attribute	Description
Name	PICKUP_EVENT_SEQUENCE_NUMBER
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

VALUE_DATE

Attribute	Description
Name	VALUE_DATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: totalDigits / 22

TRANSACTION_DATE

Attribute	**Description**
Name	TRANSACTION_DATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

CHANGE_DURING_AMENDMENT

Attribute	**Description**
Name	CHANGE_DURING_AMENDMENT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

CURRENCY

Attribute	**Description**
Name	CURRENCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

AMOUNT

Attribute	**Description**
Name	AMOUNT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: totalDigits / 22

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

RATE

Attribute	Description
Name	RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	1

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

PARTY

Attribute	Description
Name	PARTY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.4.2.PD-LiquidatePDContract-Req-IO-MSG.xsd

LIQUIDATEPDCONTRACT_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Pdvws-Pdc-Master-IO

TRNREFNO

Misdetails

CONREFNO

MISGRP

RELACC

RELETED_REFERENCE

MISHEAD

RATEFLG

POOLCD

REFINANCE_RATE

REFRATETYP

PROCALCMTH

REFXRATE

REFSPREAD

REFRATECD

COSTCD1

COSTCD2

COSTCD3

COSTCD4

COSTCD5

TXNMIS1

TXNMIS10

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

MISGRPCOMP

MISGRPTXN

COMPMIS1

COMPMIS10

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

FUNDMIS1

FUNDMIS10

FUNDMIS2

FUNDMIS3

FUNDMIS4

FUNDMIS5

FUNDMIS6

FUNDMIS7

FUNDMIS8

FUNDMIS9

Txnmisdetails

Compmisdetails

Fundmisdetails

Charge

TRNREF

EVSEQNO

TXNUDFDETAILS

FLDNAME

FLDVAL

LIQUIDATEPDCONTRACT_IOPK_REQ

Attribute	Description

Name	LIQUIDATEPDCONTRACT_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Pdvws-Pdc-Master-IO

Attribute	Description
Name	Pdvws-Pdc-Master-IO
Datatype	
Description	

TRNREFNO

Attribute	Description
Name	TRNREFNO
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

MISHEAD

Attribute	Description
Name	MISHEAD

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

RATEFLG

Attribute	**Description**
Name	RATEFLG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

POOLCD

Attribute	**Description**
Name	POOLCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFINANCE_RATE

Attribute	**Description**
Name	REFINANCE_RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

REFRATETYP

Attribute	**Description**
Name	REFRATETYP

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>X,F,P</td></tr></table>

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>1,2,3,4,5,6,7,8,9</td></tr></table>

REFXRATE

Attribute	Description
Name	REFXRATE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

REFRATECD

Attribute	Description
Name	REFRATECD

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD4

Attribute	Description
Name	COSTCD4

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS6

Attribute	Description
Name	TXNMIS6

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS2

Attribute	Description
Name	COMPMIS2

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS1

Attribute	Description
Name	FUNDMIS1

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

FUNDMIS10

Attribute	**Description**
Name	FUNDMIS10
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

FUNDMIS2

Attribute	**Description**
Name	FUNDMIS2
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

FUNDMIS3

Attribute	**Description**
Name	FUNDMIS3
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

FUNDMIS4

Attribute	**Description**
Name	FUNDMIS4

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

FUNDMIS5

Attribute	**Description**
Name	FUNDMIS5
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

FUNDMIS6

Attribute	**Description**
Name	FUNDMIS6
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

FUNDMIS7

Attribute	**Description**
Name	FUNDMIS7
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

FUNDMIS8

Attribute	**Description**
Name	FUNDMIS8

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Charge

Attribute	Description
Name	Charge
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TRNREF

Attribute	Description
Name	TRNREF
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

EVSEQNO

Attribute	Description
Name	EVSEQNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.4.3.PD-LiquidatePDContract-Res-Full-MSG.xsd

LIQUIDATEPDCONTRACT_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Pdvws-Pdc-Master-Full

TRNREFNO

EVSEQNO

SCODE

XREF

PRDCD

BRANCH_CODE

REMITTER_ACCOUNT_NO

BENACNO

INSTRNO

CCY

AMT

VALDT

CLEARING_PRODUCT

RTNGNO

ENDPNT

ISSUER_BANK

ISSUER_BRANCH

PURPOSE

ACTIVATION_DT

LOCNOFCHQ

BLKTXNREF

CHARGE_BRANCH

CHG_ACC_NUMBER

CHGCCY

MAKERID

AUTHSTAT

ONCEAUTH

MAKERSTAMP

CHECKERID

CHECKERSTAMP

MODNO

PRODDESC

BRNDESC

CLGPRODDESC

ISRBNKDESC

ISRBRNDESC

ENDPNTDESC

CHGPAYBRNDESC

CLRBNK

PCCLGBRN

SECTORCD

RECSTAT

DUMMY

LOAN_ACCNO

REMARKS

CREDITLINE

LIMTRACKREQD

FRM_DT

TODATE

DOWNPMT

CHQ_INQUIRY

OPERATION

USERREFNO

DRWPARTYID

CHQDATE

TXNSTAT

REMACDESC

BEN_NAME

CHARGE_AC_DESC

SCHEDULEDATE

Pdvws-All-Ac-Entries--Master

- *EVENT*
- *Pdvws-All-Ac-Entries*
  - *EVENT*
  - *ACBRN*
  - *ACNO*
  - *DRCRIND*
  - *ACCCY*
  - *CODE*
  - *FCYAMT*
  - *EXCHRATE*
  - *LCYAMT*
  - *TRNDT*
  - *VALUEDT*
  - *AMTTAG*

Csvws-Contract-Ovd

- *OVDRIDES*

Master

Detb-Pdc-Linkages

- *CUSTOMERNO*
- *LINKAGE_TYPE*
- *LINKREFNO*
- *LNKPXNTG*
- *LINKAMT*

Misdetails

- *CONREFNO*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*

POOLCD

REFINANCE_RATE

REFRATETYP

PROCALCMTH

REFSPREAD

REFRATECD

COSTCD1

COSTCD2

COSTCD3

COSTCD4

COSTCD5

TXNMIS1

TXNMIS10

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

MISGRPCOMP

MISGRPTXN

COMPMIS1

COMPMIS10

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

FUNDMIS1

FUNDMIS10

FUNDMIS2

FUNDMIS3

FUNDMIS4

FUNDMIS5

FUNDMIS6

FUNDMIS7

FUNDMIS8

FUNDMIS9

MISGRPFUN

TRANMIS1

TRANMIS2

TRANMIS3

TRANMIS4

TRANMIS5

TRANMIS6

TRANMIS7

TRANMIS8

TRANMIS9

TRANMIS10

COMMIS1

COMMIS2

COMMIS3

COMMIS4

COMMIS5

COMMIS6

COMMIS7

COMMIS8

COMMIS9

COMMIS10

FUNMIS1

FUNMIS2

FUNMIS3

FUNMIS4

FUNMIS5

FUNMIS6

FUNMIS7

FUNMIS8

FUNMIS9

FUNMIS10

Txnmisdetails

Compmisdetails

Fundmisdetails

Control

Balance-Trnsfer-Log-Details

BRANCH

PERIOD_CODE

FIN_YEAR

REFERENCE_NO

GL_CODE

REFERENCE_TYPE

TRANSFER_IND

MIS_CLASS

TXN_DATE

OLD_MIS_CODE

NEW_MIS_CODE

CCY

AMOUNT

EX_RATE

Charge

TRNREF

EVSEQNO

Contract-Charges

COMPONENT

PICKUP_EVENT_SEQUENCE_NUMBER

VALUE_DATE

EVENT_SEQ_NO

TRANSACTION_DATE

CHANGE_DURING_AMENDMENT

CURRENCY

AMOUNT

STATUS

WAIVER

RATE

RATE_TYPE

EVENT

PARTY

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

LIQUIDATEPDCONTRACT_FSFS_RES

Attribute	Description
Name	LIQUIDATEPDCONTRACT_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description

Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Pdvws-Pdc-Master-Full

Attribute	Description
Name	Pdvws-Pdc-Master-Full
Datatype	
Description	

TRNREFNO

Attribute	Description
Name	TRNREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

EVSEQNO

Attribute	Description
Name	EVSEQNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

SCODE

Attribute	Description
Name	SCODE
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 16

XREF

Attribute	**Description**
Name	XREF
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

PRDCD

Attribute	**Description**
Name	PRDCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

BRANCH_CODE

Attribute	**Description**
Name	BRANCH_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

REMITTER_ACCOUNT_NO

Attribute	**Description**
Name	REMITTER_ACCOUNT_NO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	20

BENACNO

Attribute	Description
Name	BENACNO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

AMT

Attribute	Description
Name	AMT
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

VALDT

Attribute	Description
Name	VALDT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

CLEARING_PRODUCT

Attribute	Description
Name	CLEARING_PRODUCT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

RTNGNO

Attribute	Description
Name	RTNGNO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	27

ENDPNT

Attribute	Description
Name	ENDPNT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

ISSUER_BANK

Attribute	Description
Name	ISSUER_BANK
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

ISSUER_BRANCH

Attribute	Description
Name	ISSUER_BRANCH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

PURPOSE

Attribute	Description
Name	PURPOSE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

ACTIVATION_DT

Attribute	Description
Name	ACTIVATION_DT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

LOCNOFCHQ

Attribute	Description
Name	LOCNOFCHQ

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

BLKTXNREF

Attribute	**Description**
Name	BLKTXNREF
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

CHARGE_BRANCH

Attribute	**Description**
Name	CHARGE_BRANCH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

CHG_ACC_NUMBER

Attribute	**Description**
Name	CHG_ACC_NUMBER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

CHGCCY

Attribute	**Description**
Name	CHGCCY

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>U,A</td></tr></table>

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	420

BRNDESC

Attribute	Description
Name	BRNDESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	420

CLGPRODDESC

Attribute	Description
Name	CLGPRODDESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	420

ISRBNKDESC

Attribute	Description
Name	ISRBNKDESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	420

ISRBRNDESC

Attribute	Description
Name	ISRBRNDESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: maxLength / 420

ENDPNTDESC

Attribute	Description
Name	ENDPNTDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

CHGPAYBRNDESC

Attribute	Description
Name	CHGPAYBRNDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

CLRBNK

Attribute	Description
Name	CLRBNK
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 36

PCCLGBRN

Attribute	Description
Name	PCCLGBRN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	36

SECTORCD

Attribute	Description
Name	SECTORCD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	36

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

DUMMY

Attribute	Description
Name	DUMMY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	420

LOAN_ACCNO

Attribute	Description
Name	LOAN_ACCNO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: maxLength / 35

REMARKS

Attribute	**Description**
Name	REMARKS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

CREDITLINE

Attribute	**Description**
Name	CREDITLINE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

LIMTRACKREQD

Attribute	**Description**
Name	LIMTRACKREQD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

FRM_DT

Attribute	**Description**
Name	FRM_DT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

TODATE

Attribute	Description
Name	TODATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

DOWNPMT

Attribute	Description
Name	DOWNPMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CHQ_INQUIRY

Attribute	Description
Name	CHQ_INQUIRY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Discounted,Normal,Purchased,Collection,Collection after purchase,Collection after discount,Returned,Passed,Pullback

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,,D

USERREFNO

Attribute	Description
Name	USERREFNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

DRWPARTYID

Attribute	Description
Name	DRWPARTYID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

CHQDATE

Attribute	Description
Name	CHQDATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,V,U,L,K,C</td></tr></table>

REMACDESC

Attribute	Description
Name	REMACDESC
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

BEN_NAME

Attribute	Description
Name	BEN_NAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

CHARGE_AC_DESC

Attribute	Description
Name	CHARGE_AC_DESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

SCHEDULEDATE

Attribute	Description
Name	SCHEDULEDATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Pdvws-All-Ac-Entries--Master

Attribute	Description
Name	Pdvws-All-Ac-Entries--Master
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

Pdvws-All-Ac-Entries

Attribute	Description
Name	Pdvws-All-Ac-Entries
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

ACBRN

Attribute	Description
Name	ACBRN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

ACNO

Attribute	Description
Name	ACNO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: maxLength / 3

FCYAMT

Attribute	Description
Name	FCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

EXCHRATE

Attribute	Description
Name	EXCHRATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TRNDT

Attribute	Description
Name	TRNDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

OVDRIDES

Attribute	Description
Name	OVDRIDES
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

Master

Attribute	Description
Name	Master
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0

Detb-Pdc-Linkages

Attribute	Description
Name	Detb-Pdc-Linkages
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

CUSTOMERNO

Attribute	Description
Name	CUSTOMERNO
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	9

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Restrictions	

Restrictions	Description
enumeration	P,C,F

LINKREFNO

Attribute	Description
Name	LINKREFNO
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	35

LNKPXNTG

Attribute	Description
Name	LNKPXNTG
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

LINKAMT

Attribute	Description
Name	LINKAMT
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	16

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

RELACC

Attribute	Description

Name	RELACC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

RELETED_REFERENCE

Attribute	**Description**
Name	RELETED_REFERENCE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

MISHEAD

Attribute	**Description**
Name	MISHEAD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

RATEFLG

Attribute	**Description**
Name	RATEFLG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

POOLCD

Attribute	**Description**

Name	POOLCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFINANCE_RATE

Attribute	**Description**
Name	REFINANCE_RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

REFRATETYP

Attribute	**Description**
Name	REFRATETYP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F,P

PROCALCMTH

Attribute	**Description**
Name	PROCALCMTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,8,9

REFSPREAD

Attribute	**Description**

Name	REFSPREAD
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

REFRATECD

Attribute	**Description**
Name	REFRATECD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

COSTCD1

Attribute	**Description**
Name	COSTCD1
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

COSTCD2

Attribute	**Description**
Name	COSTCD2
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

COSTCD3

Attribute	**Description**

Name	COSTCD3
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

COSTCD4

Attribute	**Description**
Name	COSTCD4
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

COSTCD5

Attribute	**Description**
Name	COSTCD5
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TXNMIS10

Attribute	**Description**

Name	TXNMIS10
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TXNMIS2

Attribute	**Description**
Name	TXNMIS2
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TXNMIS3

Attribute	**Description**
Name	TXNMIS3
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TXNMIS4

Attribute	**Description**
Name	TXNMIS4
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TXNMIS5

Attribute	**Description**

Name	TXNMIS5
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TXNMIS6

Attribute	**Description**
Name	TXNMIS6
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TXNMIS7

Attribute	**Description**
Name	TXNMIS7
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TXNMIS8

Attribute	**Description**
Name	TXNMIS8
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TXNMIS9

Attribute	**Description**

Name	TXNMIS9
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

MISGRPCOMP

Attribute	**Description**
Name	MISGRPCOMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

MISGRPTXN

Attribute	**Description**
Name	MISGRPTXN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

COMPMIS1

Attribute	**Description**
Name	COMPMIS1
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

COMPMIS10

Attribute	**Description**

Name	COMPMIS10
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

COMPMIS2

Attribute	**Description**
Name	COMPMIS2
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

COMPMIS3

Attribute	**Description**
Name	COMPMIS3
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

COMPMIS4

Attribute	**Description**
Name	COMPMIS4
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

COMPMIS5

Attribute	**Description**

Name	COMPMIS5
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

COMPMIS6

Attribute	**Description**
Name	COMPMIS6
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

COMPMIS7

Attribute	**Description**
Name	COMPMIS7
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

COMPMIS8

Attribute	**Description**
Name	COMPMIS8
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

COMPMIS9

Attribute	**Description**

Name	COMPMIS9
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

FUNDMIS1

Attribute	**Description**
Name	FUNDMIS1
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

FUNDMIS10

Attribute	**Description**
Name	FUNDMIS10
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

FUNDMIS2

Attribute	**Description**
Name	FUNDMIS2
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

FUNDMIS3

Attribute	**Description**

Name	FUNDMIS3
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

FUNDMIS4

Attribute	**Description**
Name	FUNDMIS4
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

FUNDMIS5

Attribute	**Description**
Name	FUNDMIS5
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

FUNDMIS6

Attribute	**Description**
Name	FUNDMIS6
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

FUNDMIS7

Attribute	**Description**

Name	FUNDMIS7
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

FUNDMIS8

Attribute	**Description**
Name	FUNDMIS8
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

FUNDMIS9

Attribute	**Description**
Name	FUNDMIS9
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

MISGRPFUN

Attribute	**Description**
Name	MISGRPFUN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TRANMIS1

Attribute	**Description**

Name	TRANMIS1
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TRANMIS2

Attribute	**Description**
Name	TRANMIS2
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TRANMIS3

Attribute	**Description**
Name	TRANMIS3
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TRANMIS4

Attribute	**Description**
Name	TRANMIS4
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TRANMIS5

Attribute	**Description**

Name	TRANMIS5
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TRANMIS6

Attribute	**Description**
Name	TRANMIS6
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TRANMIS7

Attribute	**Description**
Name	TRANMIS7
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TRANMIS8

Attribute	**Description**
Name	TRANMIS8
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TRANMIS9

Attribute	**Description**

Name	TRANMIS9
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TRANMIS10

Attribute	**Description**
Name	TRANMIS10
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

COMMIS1

Attribute	**Description**
Name	COMMIS1
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

COMMIS2

Attribute	**Description**
Name	COMMIS2
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

COMMIS3

Attribute	**Description**

Name	COMMIS3
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

COMMIS4

Attribute	**Description**
Name	COMMIS4
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

COMMIS5

Attribute	**Description**
Name	COMMIS5
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

COMMIS6

Attribute	**Description**
Name	COMMIS6
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

COMMIS7

Attribute	**Description**

Name	COMMIS7
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

COMMIS8

Attribute	**Description**
Name	COMMIS8
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

COMMIS9

Attribute	**Description**
Name	COMMIS9
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

COMMIS10

Attribute	**Description**
Name	COMMIS10
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

FUNMIS1

Attribute	**Description**

Name	FUNMIS1
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

FUNMIS2

Attribute	**Description**
Name	FUNMIS2
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

FUNMIS3

Attribute	**Description**
Name	FUNMIS3
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

FUNMIS4

Attribute	**Description**
Name	FUNMIS4
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

FUNMIS5

Attribute	**Description**

Name	FUNMIS5
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

FUNMIS6

Attribute	**Description**
Name	FUNMIS6
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

FUNMIS7

Attribute	**Description**
Name	FUNMIS7
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

FUNMIS8

Attribute	**Description**
Name	FUNMIS8
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

FUNMIS9

Attribute	**Description**

Name	FUNMIS9
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

FUNMIS10

Attribute	**Description**
Name	FUNMIS10
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

Txnmisdetails

Attribute	**Description**
Name	Txnmisdetails
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

Compmisdetails

Attribute	**Description**
Name	Compmisdetails
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

Fundmisdetails

Attribute	**Description**
Name	Fundmisdetails
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

Control

Attribute	Description
Name	Control
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

Balance-Trnsfer-Log-Details

Attribute	Description
Name	Balance-Trnsfer-Log-Details
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

PERIOD_CODE

Attribute	Description
Name	PERIOD_CODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

FIN_YEAR

Attribute	Description
Name	FIN_YEAR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

GL_CODE

Attribute	Description
Name	GL_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

REFERENCE_TYPE

Attribute	Description
Name	REFERENCE_TYPE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

TRANSFER_IND

Attribute	Description
Name	TRANSFER_IND
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

MIS_CLASS

Attribute	Description
Name	MIS_CLASS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXN_DATE

Attribute	Description
Name	TXN_DATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

OLD_MIS_CODE

Attribute	Description
Name	OLD_MIS_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

NEW_MIS_CODE

Attribute	Description
Name	NEW_MIS_CODE
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

AMOUNT

Attribute	**Description**
Name	AMOUNT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

EX_RATE

Attribute	**Description**
Name	EX_RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 24

Charge

Attribute	**Description**
Name	Charge
Datatype	
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0

TRNREF

Attribute	Description
Name	TRNREF
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

EVSEQNO

Attribute	Description
Name	EVSEQNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

Contract-Charges

Attribute	Description
Name	Contract-Charges
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

PICKUP_EVENT_SEQUENCE_NUMBER

Attribute	Description

Name	PICKUP_EVENT_SEQUENCE_NUMBER
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

VALUE_DATE

Attribute	**Description**
Name	VALUE_DATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

EVENT_SEQ_NO

Attribute	**Description**
Name	EVENT_SEQ_NO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TRANSACTION_DATE

Attribute	**Description**
Name	TRANSACTION_DATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

CHANGE_DURING_AMENDMENT

Attribute	**Description**
Name	CHANGE_DURING_AMENDMENT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description** maxLength / 1

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	
	Restrictions / **Description**: enumeration / Y,N

RATE

Attribute	Description
Name	RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

PARTY

Attribute	Description
Name	PARTY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	9

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description

Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

LIQUIDATEPDCONTRACT_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Pdvws-Pdc-Master-PK

TRNREFNO

Pdvws-Pdc-Master-IO

TRNREFNO

Misdetails

CONREFNO

MISGRP

RELACC

RELETED_REFERENCE

MISHEAD

RATEFLG

POOLCD

REFINANCE_RATE

REFRATETYP

PROCALCMTH

REFXRATE

REFSPREAD

REFRATECD

COSTCD1

COSTCD2

COSTCD3

COSTCD4

COSTCD5

TXNMIS1

TXNMIS10

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

MISGRPCOMP

MISGRPTXN

COMPMIS1

COMPMIS10

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

FUNDMIS1

FUNDMIS10

FUNDMIS2

FUNDMIS3

FUNDMIS4

FUNDMIS5

FUNDMIS6

FUNDMIS7

FUNDMIS8

FUNDMIS9

Txnmisdetails

Compmisdetails

Fundmisdetails

Charge

TRNREF

EVSEQNO

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

Attribute	Description
Name	LIQUIDATEPDCONTRACT_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String

Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Pdvws-Pdc-Master-PK

Attribute	Description
Name	Pdvws-Pdc-Master-PK
Datatype	
Description	

TRNREFNO

Attribute	Description
Name	TRNREFNO
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

Pdvws-Pdc-Master-IO

Attribute	Description
Name	Pdvws-Pdc-Master-IO
Datatype	
Description	

TRNREFNO

Attribute	Description

Name	TRNREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

Misdetails

Attribute	**Description**
Name	Misdetails
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

MISGRP

Attribute	**Description**
Name	MISGRP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

RELACC

Attribute	**Description**
Name	RELACC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>X,F,P</td></tr></table>

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>1,2,3,4,5,6,7,8,9</td></tr></table>

REFXRATE

Attribute	Description
Name	REFXRATE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	

Attribute	

Attribute	Description
maxOccurs	unbounded

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

Charge

Attribute	Description
Name	Charge
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

TRNREF

Attribute	Description
Name	TRNREF
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

EVSEQNO

Attribute	Description
Name	EVSEQNO
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

TXNUDFDETAILS

Attribute	Description

Name	TXNUDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions

Restrictions	Description
maxLength	255
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.5.ModifyPDContract

2.5.1.PD-ModifyPDContract-Req-Full-MSG.xsd

MODIFYPDCONTRACT_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Pdvws-Pdc-Master-Full

TRNREFNO

EVSEQNO

SCODE

XREF

PRDCD

BRANCH_CODE

REMITTER_ACCOUNT_NO

BENACNO

INSTRNO

CCY

AMT

VALDT

CLEARING_PRODUCT

RTNGNO

ENDPNT

ISSUER_BANK

ISSUER_BRANCH

PURPOSE

ACTIVATION_DT

LOCNOFCHQ

BLKTXNREF

CHARGE_BRANCH

CHG_ACC_NUMBER

CHGCCY

MAKERID

AUTHSTAT

ONCEAUTH

MAKERSTAMP

CHECKERID

CHECKERSTAMP

MODNO

PRODDESC

BRNDESC

CLGPRODDESC

ISRBNKDESC

ISRBRNDESC

ENDPNTDESC

CHGPAYBRNDESC

CLRBNK

PCCLGBRN

SECTORCD

RECSTAT

DUMMY

LOAN_ACCNO

REMARKS

CREDITLINE

LIMTRACKREQD

FRM_DT

TODATE

DOWNPMT

CHQ_INQUIRY

OPERATION

USERREFNO

DRWPARTYID

CHQDATE

TXNSTAT

REMACDESC

BEN_NAME

CHARGE_AC_DESC

SCHEDULEDATE

Pdvws-All-Ac-Entries--Master

- *EVENT*
- *Pdvws-All-Ac-Entries*
  - *EVENT*
  - *ACBRN*
  - *ACNO*
  - *DRCRIND*
  - *ACCCY*
  - *CODE*
  - *FCYAMT*
  - *EXCHRATE*
  - *LCYAMT*
  - *TRNDT*
  - *VALUEDT*
  - *AMTTAG*

Csvws-Contract-Ovd

OVDRIDES

Master

Detb-Pdc-Linkages

CUSTOMERNO

LINKAGE_TYPE

LINKREFNO

LNKPXNTG

LINKAMT

Misdetails

CONREFNO

MISGRP

RELACC

RELETED_REFERENCE

MISHEAD

RATEFLG

POOLCD

REFINANCE_RATE

REFRATETYP

PROCALCMTH

REFSPREAD

REFRATECD

COSTCD1

COSTCD2

COSTCD3

COSTCD4

COSTCD5

TXNMIS1

TXNMIS10

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

MISGRPCOMP

MISGRPTXN

COMPMIS1

COMPMIS10

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

FUNDMIS1

FUNDMIS10

FUNDMIS2

FUNDMIS3

FUNDMIS4

FUNDMIS5

FUNDMIS6

FUNDMIS7

FUNDMIS8

FUNDMIS9

MISGRPFUN

TRANMIS1

TRANMIS2

TRANMIS3

TRANMIS4

TRANMIS5

TRANMIS6

TRANMIS7

TRANMIS8

TRANMIS9

TRANMIS10

COMMIS1

COMMIS2

COMMIS3

COMMIS4

COMMIS5

COMMIS6

COMMIS7

COMMIS8

COMMIS9

COMMIS10

FUNMIS1

FUNMIS2

FUNMIS3

FUNMIS4

FUNMIS5

FUNMIS6

FUNMIS7

FUNMIS8

FUNMIS9

FUNMIS10

Txnmisdetails

Compmisdetails

Fundmisdetails

Control

Balance-Trnsfer-Log-Details

BRANCH

PERIOD_CODE

FIN_YEAR

REFERENCE_NO

GL_CODE

REFERENCE_TYPE

TRANSFER_IND

MIS_CLASS

TXN_DATE

OLD_MIS_CODE

NEW_MIS_CODE

CCY

AMOUNT

EX_RATE

Charge

TRNREF

EVSEQNO

Contract-Charges

COMPONENT

PICKUP_EVENT_SEQUENCE_NUMBER

VALUE_DATE

EVENT_SEQ_NO

TRANSACTION_DATE

CHANGE_DURING_AMENDMENT

CURRENCY

AMOUNT

STATUS

WAIVER

RATE

RATE_TYPE

EVENT

PARTY

TXNUDFDETAILS

FLDNAME

FLDVAL

MODIFYPDCONTRACT_FSFS_REQ

Attribute	Description
Name	MODIFYPDCONTRACT_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Pdvws-Pdc-Master-Full

Attribute	Description
Name	Pdvws-Pdc-Master-Full
Datatype	
Description	

TRNREFNO

Attribute	Description
Name	TRNREFNO
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

EVSEQNO

Attribute	Description
Name	EVSEQNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

SCODE

Attribute	Description
Name	SCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

REMITTER_ACCOUNT_NO

Attribute	Description
Name	REMITTER_ACCOUNT_NO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

BENACNO

Attribute	Description
Name	BENACNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

CCY

Attribute	Description
Name	CCY

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

AMT

Attribute	**Description**
Name	AMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

VALDT

Attribute	**Description**
Name	VALDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

CLEARING_PRODUCT

Attribute	**Description**
Name	CLEARING_PRODUCT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

RTNGNO

Attribute	**Description**
Name	RTNGNO
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 27

ENDPNT

Attribute	**Description**
Name	ENDPNT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

ISSUER_BANK

Attribute	**Description**
Name	ISSUER_BANK
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

ISSUER_BRANCH

Attribute	**Description**
Name	ISSUER_BRANCH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

PURPOSE

Attribute	**Description**
Name	PURPOSE
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

ACTIVATION_DT

Attribute	**Description**
Name	ACTIVATION_DT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

LOCNOFCHQ

Attribute	**Description**
Name	LOCNOFCHQ
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

BLKTXNREF

Attribute	**Description**
Name	BLKTXNREF
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

CHARGE_BRANCH

Attribute	**Description**
Name	CHARGE_BRANCH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	3

CHG_ACC_NUMBER

Attribute	Description
Name	CHG_ACC_NUMBER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	U,A

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

MODNO

Attribute	Description

Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

PRODDESC

Attribute	**Description**
Name	PRODDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

BRNDESC

Attribute	**Description**
Name	BRNDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

CLGPRODDESC

Attribute	**Description**
Name	CLGPRODDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

ISRBNKDESC

Attribute	**Description**

Name	ISRBNKDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

ISRBRNDESC

Attribute	**Description**
Name	ISRBRNDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

ENDPNTDESC

Attribute	**Description**
Name	ENDPNTDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

CHGPAYBRNDESC

Attribute	**Description**
Name	CHGPAYBRNDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

CLRBNK

Attribute	**Description**

Name	CLRBNK
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 36

PCCLGBRN

Attribute	**Description**
Name	PCCLGBRN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 36

SECTORCD

Attribute	**Description**
Name	SECTORCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 36

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

DUMMY

Attribute	**Description**

Name	DUMMY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

LOAN_ACCNO

Attribute	**Description**
Name	LOAN_ACCNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

REMARKS

Attribute	**Description**
Name	REMARKS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

CREDITLINE

Attribute	**Description**
Name	CREDITLINE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

LIMTRACKREQD

Attribute	**Description**

Name	LIMTRACKREQD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

FRM_DT

Attribute	**Description**
Name	FRM_DT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

TODATE

Attribute	**Description**
Name	TODATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

DOWNPMT

Attribute	**Description**
Name	DOWNPMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CHQ_INQUIRY

Attribute	**Description**
Name	CHQ_INQUIRY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	Discounted,Normal,Purchased,Collection,Collection after purchase,Collection after discount,Returned,Passed,Pullback

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	P,,D

USERREFNO

Attribute	Description
Name	USERREFNO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

DRWPARTYID

Attribute	Description
Name	DRWPARTYID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

CHQDATE

Attribute	Description
Name	CHQDATE
Datatype	String
Description	

Attribute	

Attribute	Description
minOccurs	0

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	A,V,U,L,K,C

REMACDESC

Attribute	Description
Name	REMACDESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255

BEN_NAME

Attribute	Description
Name	BEN_NAME
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255

CHARGE_AC_DESC

Attribute	Description
Name	CHARGE_AC_DESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255

SCHEDULEDATE

Attribute	Description
Name	SCHEDULEDATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Pdvws-All-Ac-Entries--Master

Attribute	Description
Name	Pdvws-All-Ac-Entries--Master
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

Pdvws-All-Ac-Entries

Attribute	Description
Name	Pdvws-All-Ac-Entries
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

EVENT

Attribute	Description
Name	EVENT
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

ACBRN

Attribute	Description
Name	ACBRN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

ACNO

Attribute	Description
Name	ACNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String

Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

FCYAMT

Attribute	Description
Name	FCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

EXCHRATE

Attribute	Description
Name	EXCHRATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Decimal

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TRNDT

Attribute	Description
Name	TRNDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

OVDRIDES

Attribute	Description
Name	OVDRIDES
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

Master

Attribute	Description
Name	Master
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Detb-Pdc-Linkages

Attribute	Description
Name	Detb-Pdc-Linkages
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

CUSTOMERNO

Attribute	Description
Name	CUSTOMERNO
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,C,F</td></tr></table>

LINKREFNO

Attribute	Description
Name	LINKREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 35

LNKPXNTG

Attribute	Description
Name	LNKPXNTG
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

LINKAMT

Attribute	Description
Name	LINKAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F,P

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>1,2,3,4,5,6,7,8,9</td></tr></table>

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Control

Attribute	Description
Name	Control
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Balance-Trnsfer-Log-Details

Attribute	Description
Name	Balance-Trnsfer-Log-Details
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

PERIOD_CODE

Attribute	Description

Name	PERIOD_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

FIN_YEAR

Attribute	**Description**
Name	FIN_YEAR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFERENCE_NO

Attribute	**Description**
Name	REFERENCE_NO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

GL_CODE

Attribute	**Description**
Name	GL_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFERENCE_TYPE

Attribute	**Description**

Name	REFERENCE_TYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TRANSFER_IND

Attribute	**Description**
Name	TRANSFER_IND
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

MIS_CLASS

Attribute	**Description**
Name	MIS_CLASS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TXN_DATE

Attribute	**Description**
Name	TXN_DATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

OLD_MIS_CODE

Attribute	**Description**
Name	OLD_MIS_CODE
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

NEW_MIS_CODE

Attribute	**Description**
Name	NEW_MIS_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

AMOUNT

Attribute	**Description**
Name	AMOUNT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

EX_RATE

Attribute	**Description**
Name	EX_RATE
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 24

Charge

Attribute	**Description**
Name	Charge
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

TRNREF

Attribute	**Description**
Name	TRNREF
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

EVSEQNO

Attribute	**Description**
Name	EVSEQNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

Contract-Charges

Attribute	**Description**
Name	Contract-Charges
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

PICKUP_EVENT_SEQUENCE_NUMBER

Attribute	Description
Name	PICKUP_EVENT_SEQUENCE_NUMBER
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

VALUE_DATE

Attribute	Description
Name	VALUE_DATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TRANSACTION_DATE

Attribute	Description
Name	TRANSACTION_DATE
Datatype	String
Description	

Attribute	

Attribute	Description
minOccurs	0

CHANGE_DURING_AMENDMENT

Attribute	Description
Name	CHANGE_DURING_AMENDMENT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

RATE

Attribute	Description
Name	RATE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

PARTY

Attribute	Description
Name	PARTY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

MODIFYPDCONTRACT_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Pdvws-Pdc-Master-IO

TRNREFNO

REMITTER_ACCOUNT_NO

BENACNO

INSTRNO

CCY

AMT

CLEARING_PRODUCT

RTNGNO

ENDPNT

ISSUER_BANK

ISSUER_BRANCH

PURPOSE

ACTIVATION_DT

LOCNOFCHQ

CHARGE_BRANCH

CHG_ACC_NUMBER

CHGCCY

CLRBNK

PCCLGBRN

SECTORCD

LOAN_ACCNO

REMARKS

Misdetails

- *CONREFNO*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFXRATE*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*

COSTCD4

COSTCD5

TXNMIS1

TXNMIS10

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

MISGRPCOMP

MISGRPTXN

COMPMIS1

COMPMIS10

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

FUNDMIS1

FUNDMIS10

FUNDMIS2

FUNDMIS3

FUNDMIS4

FUNDMIS5

FUNDMIS6

FUNDMIS7

FUNDMIS8

FUNDMIS9

Txnmisdetails

Compmisdetails

Fundmisdetails

Charge

TRNREF

EVSEQNO

TXNUDFDETAILS

FLDNAME

FLDVAL

MODIFYPDCONTRACT_IOPK_REQ

Attribute	Description
Name	MODIFYPDCONTRACT_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	

Pdvws-Pdc-Master-IO

Attribute	**Description**

Name	Pdvws-Pdc-Master-IO
Datatype	
Description	

TRNREFNO

Attribute	Description
Name	TRNREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

REMITTER_ACCOUNT_NO

Attribute	Description
Name	REMITTER_ACCOUNT_NO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

BENACNO

Attribute	Description
Name	BENACNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

AMT

Attribute	Description
Name	AMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CLEARING_PRODUCT

Attribute	Description
Name	CLEARING_PRODUCT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

RTNGNO

Attribute	Description
Name	RTNGNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>27</td></tr></table>

ENDPNT

Attribute	Description
Name	ENDPNT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

ISSUER_BANK

Attribute	Description
Name	ISSUER_BANK
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

ISSUER_BRANCH

Attribute	Description
Name	ISSUER_BRANCH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

PURPOSE

Attribute	Description
Name	PURPOSE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

ACTIVATION_DT

Attribute	Description
Name	ACTIVATION_DT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

LOCNOFCHQ

Attribute	Description
Name	LOCNOFCHQ
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

CHARGE_BRANCH

Attribute	Description
Name	CHARGE_BRANCH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

CHG_ACC_NUMBER

Attribute	Description
Name	CHG_ACC_NUMBER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 3

CLRBNK

Attribute	**Description**
Name	CLRBNK
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 36

PCCLGBRN

Attribute	**Description**
Name	PCCLGBRN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 36

SECTORCD

Attribute	**Description**
Name	SECTORCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 36

LOAN_ACCNO

Attribute	**Description**
Name	LOAN_ACCNO
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F,P

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,8,9

REFXRATE

Attribute	Description
Name	REFXRATE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Charge

Attribute	Description
Name	Charge
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TRNREF

Attribute	Description
Name	TRNREF
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

EVSEQNO

Attribute	Description

Name	EVSEQNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TXNUDFDETAILS

Attribute	**Description**
Name	TXNUDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FLDNAME

Attribute	**Description**
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

2.5.3.PD-ModifyPDContract-Res-Full-MSG.xsd

MODIFYPDCONTRACT_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Pdvws-Pdc-Master-Full

TRNREFNO

EVSEQNO

SCODE

XREF

PRDCD

BRANCH_CODE

REMITTER_ACCOUNT_NO

BENACNO

INSTRNO

CCY

AMT

VALDT

CLEARING_PRODUCT

RTNGNO

ENDPNT

ISSUER_BANK

ISSUER_BRANCH

PURPOSE

ACTIVATION_DT

LOCNOFCHQ

BLKTXNREF

CHARGE_BRANCH

CHG_ACC_NUMBER

CHGCCY

MAKERID

AUTHSTAT

ONCEAUTH

MAKERSTAMP

CHECKERID

CHECKERSTAMP

MODNO

PRODDESC

BRNDESC

CLGPRODDESC

ISRBNKDESC

ISRBRNDESC

ENDPNTDESC

CHGPAYBRNDESC

CLRBNK

PCCLGBRN

SECTORCD

RECSTAT

DUMMY

LOAN_ACCNO

REMARKS

CREDITLINE

LIMTRACKREQD

FRM_DT

TODATE

DOWNPMT

CHQ_INQUIRY

OPERATION

USERREFNO

DRWPARTYID

CHQDATE

TXNSTAT

REMACDESC

BEN_NAME

CHARGE_AC_DESC

SCHEDULEDATE

Pdvws-All-Ac-Entries--Master

- *EVENT*
- *Pdvws-All-Ac-Entries*
  - *EVENT*
  - *ACBRN*
  - *ACNO*
  - *DRCRIND*
  - *ACCCY*
  - *CODE*
  - *FCYAMT*
  - *EXCHRATE*
  - *LCYAMT*
  - *TRNDT*
  - *VALUEDT*
  - *AMTTAG*

Csvws-Contract-Ovd

OVDRIDES

Master

Detb-Pdc-Linkages

CUSTOMERNO

LINKAGE_TYPE

LINKREFNO

LNKPXNTG

LINKAMT

Misdetails

CONREFNO

MISGRP

RELACC

RELETED_REFERENCE

MISHEAD

RATEFLG

POOLCD

REFINANCE_RATE

REFRATETYP

PROCALCMTH

REFSPREAD

REFRATECD

COSTCD1

COSTCD2

COSTCD3

COSTCD4

COSTCD5

TXNMIS1

TXNMIS10

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

MISGRPCOMP

MISGRPTXN

COMPMIS1

COMPMIS10

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

FUNDMIS1

FUNDMIS10

FUNDMIS2

FUNDMIS3

FUNDMIS4

FUNDMIS5

FUNDMIS6

FUNDMIS7

FUNDMIS8

FUNDMIS9

MISGRPFUN

TRANMIS1

TRANMIS2

TRANMIS3

TRANMIS4

TRANMIS5

TRANMIS6

TRANMIS7

TRANMIS8

TRANMIS9

TRANMIS10

COMMIS1

COMMIS2

COMMIS3

COMMIS4

COMMIS5

COMMIS6

COMMIS7

COMMIS8

COMMIS9

COMMIS10

FUNMIS1

FUNMIS2

FUNMIS3

FUNMIS4

FUNMIS5

FUNMIS6

FUNMIS7

FUNMIS8

FUNMIS9

FUNMIS10

Txnmisdetails

Compmisdetails

Fundmisdetails

Control

Balance-Trnsfer-Log-Details

BRANCH

PERIOD_CODE

FIN_YEAR

REFERENCE_NO

GL_CODE

REFERENCE_TYPE

TRANSFER_IND

MIS_CLASS

TXN_DATE

OLD_MIS_CODE

NEW_MIS_CODE

CCY

AMOUNT

EX_RATE

Charge

TRNREF

EVSEQNO

Contract-Charges

COMPONENT

PICKUP_EVENT_SEQUENCE_NUMBER

VALUE_DATE

EVENT_SEQ_NO

TRANSACTION_DATE

CHANGE_DURING_AMENDMENT

CURRENCY

AMOUNT

STATUS

WAIVER

RATE

RATE_TYPE

EVENT

PARTY

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYPDCONTRACT_FSFS_RES

Attribute	Description
Name	MODIFYPDCONTRACT_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	

Pdvws-Pdc-Master-Full

Attribute	**Description**

Name	Pdvws-Pdc-Master-Full
Datatype	
Description	

TRNREFNO

Attribute	Description
Name	TRNREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

EVSEQNO

Attribute	Description
Name	EVSEQNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

SCODE

Attribute	Description
Name	SCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

REMITTER_ACCOUNT_NO

Attribute	Description
Name	REMITTER_ACCOUNT_NO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

BENACNO

Attribute	Description
Name	BENACNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

AMT

Attribute	Description
Name	AMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

VALDT

Attribute	Description
Name	VALDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

CLEARING_PRODUCT

Attribute	Description
Name	CLEARING_PRODUCT
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

RTNGNO

Attribute	**Description**
Name	RTNGNO
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 27

ENDPNT

Attribute	**Description**
Name	ENDPNT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

ISSUER_BANK

Attribute	**Description**
Name	ISSUER_BANK
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

ISSUER_BRANCH

Attribute	**Description**
Name	ISSUER_BRANCH
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** maxLength / 35

PURPOSE

Attribute	**Description**
Name	PURPOSE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

ACTIVATION_DT

Attribute	**Description**
Name	ACTIVATION_DT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

LOCNOFCHQ

Attribute	**Description**
Name	LOCNOFCHQ
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

BLKTXNREF

Attribute	**Description**
Name	BLKTXNREF
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	16

CHARGE_BRANCH

Attribute	Description
Name	CHARGE_BRANCH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

CHG_ACC_NUMBER

Attribute	Description
Name	CHG_ACC_NUMBER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	U,A

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

BRNDESC

Attribute	Description
Name	BRNDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

CLGPRODDESC

Attribute	Description
Name	CLGPRODDESC

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

ISRBNKDESC

Attribute	**Description**
Name	ISRBNKDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

ISRBRNDESC

Attribute	**Description**
Name	ISRBRNDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

ENDPNTDESC

Attribute	**Description**
Name	ENDPNTDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

CHGPAYBRNDESC

Attribute	**Description**
Name	CHGPAYBRNDESC

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

CLRBNK

Attribute	**Description**
Name	CLRBNK
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 36

PCCLGBRN

Attribute	**Description**
Name	PCCLGBRN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 36

SECTORCD

Attribute	**Description**
Name	SECTORCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 36

RECSTAT

Attribute	**Description**
Name	RECSTAT

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

DUMMY

Attribute	**Description**
Name	DUMMY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

LOAN_ACCNO

Attribute	**Description**
Name	LOAN_ACCNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

REMARKS

Attribute	**Description**
Name	REMARKS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

CREDITLINE

Attribute	**Description**
Name	CREDITLINE

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

LIMTRACKREQD

Attribute	Description
Name	LIMTRACKREQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

FRM_DT

Attribute	Description
Name	FRM_DT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TODATE

Attribute	Description
Name	TODATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DOWNPMT

Attribute	Description
Name	DOWNPMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22

CHQ_INQUIRY

Attribute	Description
Name	CHQ_INQUIRY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Discounted,Normal,Purchased,Collection,Collection after purchase,Collection after discount,Returned,Passed,Pullback

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	P,,D

USERREFNO

Attribute	Description
Name	USERREFNO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

DRWPARTYID

Attribute	Description
Name	DRWPARTYID
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

CHQDATE

Attribute	**Description**
Name	CHQDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,V,U,L,K,C

REMACDESC

Attribute	**Description**
Name	REMACDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

BEN_NAME

Attribute	**Description**
Name	BEN_NAME
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	255

CHARGE_AC_DESC

Attribute	Description
Name	CHARGE_AC_DESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255

SCHEDULEDATE

Attribute	Description
Name	SCHEDULEDATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Pdvws-All-Ac-Entries--Master

Attribute	Description
Name	Pdvws-All-Ac-Entries--Master
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

Pdvws-All-Ac-Entries

Attribute	Description

Name	Pdvws-All-Ac-Entries
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

EVENT

Attribute	**Description**
Name	EVENT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

ACBRN

Attribute	**Description**
Name	ACBRN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

ACNO

Attribute	**Description**
Name	ACNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

DRCRIND

Attribute	**Description**
Name	DRCRIND
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 1

ACCCY

Attribute	**Description**
Name	ACCCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

CODE

Attribute	**Description**
Name	CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

FCYAMT

Attribute	**Description**
Name	FCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

EXCHRATE

Attribute	**Description**
Name	EXCHRATE
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: totalDigits / 22

LCYAMT

Attribute	**Description**
Name	LCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TRNDT

Attribute	**Description**
Name	TRNDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

VALUEDT

Attribute	**Description**
Name	VALUEDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

AMTTAG

Attribute	**Description**
Name	AMTTAG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

OVDRIDES

Attribute	Description
Name	OVDRIDES
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

Master

Attribute	Description
Name	Master
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Detb-Pdc-Linkages

Attribute	Description
Name	Detb-Pdc-Linkages
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

CUSTOMERNO

Attribute	Description
Name	CUSTOMERNO
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / P,C,F

LINKREFNO

Attribute	Description
Name	LINKREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 35

LNKPXNTG

Attribute	Description
Name	LNKPXNTG
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

LINKAMT

Attribute	Description
Name	LINKAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	

Attribute	
	Attribute / **Description** minOccurs / 0

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>X,F,P</td></tr></table>

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>1,2,3,4,5,6,7,8,9</td></tr></table>

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Control

Attribute	Description
Name	Control
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Balance-Trnsfer-Log-Details

Attribute	Description
Name	Balance-Trnsfer-Log-Details
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

PERIOD_CODE

Attribute	**Description**
Name	PERIOD_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

FIN_YEAR

Attribute	**Description**
Name	FIN_YEAR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFERENCE_NO

Attribute	**Description**
Name	REFERENCE_NO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

GL_CODE

Attribute	**Description**

Name	GL_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFERENCE_TYPE

Attribute	**Description**
Name	REFERENCE_TYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TRANSFER_IND

Attribute	**Description**
Name	TRANSFER_IND
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

MIS_CLASS

Attribute	**Description**
Name	MIS_CLASS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TXN_DATE

Attribute	**Description**

Name	TXN_DATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

OLD_MIS_CODE

Attribute	**Description**
Name	OLD_MIS_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

NEW_MIS_CODE

Attribute	**Description**
Name	NEW_MIS_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

AMOUNT

Attribute	**Description**
Name	AMOUNT
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

EX_RATE

Attribute	**Description**
Name	EX_RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 24

Charge

Attribute	**Description**
Name	Charge
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

TRNREF

Attribute	**Description**
Name	TRNREF
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

EVSEQNO

Attribute	**Description**
Name	EVSEQNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22

Contract-Charges

Attribute	Description
Name	Contract-Charges
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	15

PICKUP_EVENT_SEQUENCE_NUMBER

Attribute	Description
Name	PICKUP_EVENT_SEQUENCE_NUMBER
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

VALUE_DATE

Attribute	Description
Name	VALUE_DATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: totalDigits / 22

TRANSACTION_DATE

Attribute	**Description**
Name	TRANSACTION_DATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

CHANGE_DURING_AMENDMENT

Attribute	**Description**
Name	CHANGE_DURING_AMENDMENT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

CURRENCY

Attribute	**Description**
Name	CURRENCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

AMOUNT

Attribute	**Description**
Name	AMOUNT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: totalDigits / 22

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

RATE

Attribute	Description
Name	RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	1

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

PARTY

Attribute	Description
Name	PARTY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.5.4.PD-ModifyPDContract-Res-PK-MSG.xsd

MODIFYPDCONTRACT_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Pdvws-Pdc-Master-PK

TRNREFNO

Pdvws-Pdc-Master-IO

TRNREFNO

REMITTER_ACCOUNT_NO

BENACNO

INSTRNO

CCY

AMT

CLEARING_PRODUCT

RTNGNO

ENDPNT

ISSUER_BANK

ISSUER_BRANCH

PURPOSE

ACTIVATION_DT

LOCNOFCHQ

CHARGE_BRANCH

CHG_ACC_NUMBER

CHGCCY

CLRBNK

PCCLGBRN

SECTORCD

LOAN_ACCNO

REMARKS

Misdetails

- *CONREFNO*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFXRATE*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*
- *MISGRPCOMP*

MISGRPTXN

COMPMIS1

COMPMIS10

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

FUNDMIS1

FUNDMIS10

FUNDMIS2

FUNDMIS3

FUNDMIS4

FUNDMIS5

FUNDMIS6

FUNDMIS7

FUNDMIS8

FUNDMIS9

Txnmisdetails

Compmisdetails

Fundmisdetails

Charge

TRNREF

EVSEQNO

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYPDCONTRACT_IOPK_RES

Attribute	Description
Name	MODIFYPDCONTRACT_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String

Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.

Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Pdvws-Pdc-Master-PK

Attribute	Description
Name	Pdvws-Pdc-Master-PK
Datatype	
Description	

TRNREFNO

Attribute	Description

Name	TRNREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

Pdvws-Pdc-Master-IO

Attribute	Description
Name	Pdvws-Pdc-Master-IO
Datatype	
Description	

TRNREFNO

Attribute	Description
Name	TRNREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

REMITTER_ACCOUNT_NO

Attribute	Description
Name	REMITTER_ACCOUNT_NO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

BENACNO

Attribute	Description
Name	BENACNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

INSTRNO

Attribute	Description
Name	INSTRNO

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

AMT

Attribute	Description
Name	AMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CLEARING_PRODUCT

Attribute	Description
Name	CLEARING_PRODUCT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

RTNGNO

Attribute	Description
Name	RTNGNO

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 27

ENDPNT

Attribute	**Description**
Name	ENDPNT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

ISSUER_BANK

Attribute	**Description**
Name	ISSUER_BANK
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

ISSUER_BRANCH

Attribute	**Description**
Name	ISSUER_BRANCH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

PURPOSE

Attribute	**Description**
Name	PURPOSE

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

ACTIVATION_DT

Attribute	**Description**
Name	ACTIVATION_DT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

LOCNOFCHQ

Attribute	**Description**
Name	LOCNOFCHQ
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

CHARGE_BRANCH

Attribute	**Description**
Name	CHARGE_BRANCH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

CHG_ACC_NUMBER

Attribute	**Description**
Name	CHG_ACC_NUMBER
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 20

CHGCCY

Attribute	**Description**
Name	CHGCCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

CLRBNK

Attribute	**Description**
Name	CLRBNK
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 36

PCCLGBRN

Attribute	**Description**
Name	PCCLGBRN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 36

SECTORCD

Attribute	**Description**
Name	SECTORCD
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 36

LOAN_ACCNO

Attribute	**Description**
Name	LOAN_ACCNO
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

REMARKS

Attribute	**Description**
Name	REMARKS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

Misdetails

Attribute	**Description**
Name	Misdetails
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F,P

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>1,2,3,4,5,6,7,8,9</td></tr></table>

REFXRATE

Attribute	Description
Name	REFXRATE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Charge

Attribute	Description
Name	Charge
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TRNREF

Attribute	Description

Name	TRNREF
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

EVSEQNO

Attribute	**Description**
Name	EVSEQNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TXNUDFDETAILS

Attribute	**Description**
Name	TXNUDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FLDNAME

Attribute	**Description**
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	Indicates Field Value

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.6.QueryPDContract

2.6.1.PD-QueryPDContract-Req-IO-MSG.xsd

QUERYPDCONTRACT_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Pdvws-Pdc-Master-IO

TRNREFNO

QUERYPDCONTRACT_IOFS_REQ

Attribute	Description
Name	QUERYPDCONTRACT_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description**: minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Pdvws-Pdc-Master-IO

Attribute	Description
Name	Pdvws-Pdc-Master-IO
Datatype	
Description	

TRNREFNO

Attribute	Description

Name	TRNREFNO
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

2.6.2.PD-QueryPDContract-Res-Full-MSG.xsd

QUERYPDCONTRACT_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Pdvws-Pdc-Master-IO

TRNREFNO

Pdvws-Pdc-Master-Full

TRNREFNO

EVSEQNO

SCODE

XREF

PRDCD

BRANCH_CODE

REMITTER_ACCOUNT_NO

BENACNO

INSTRNO

CCY

AMT

VALDT

CLEARING_PRODUCT

RTNGNO

ENDPNT

ISSUER_BANK

ISSUER_BRANCH

PURPOSE

ACTIVATION_DT

LOCNOFCHQ

BLKTXNREF

CHARGE_BRANCH

CHG_ACC_NUMBER

CHGCCY

MAKERID

AUTHSTAT

ONCEAUTH

MAKERSTAMP

CHECKERID

CHECKERSTAMP

MODNO

PRODDESC

BRNDESC

CLGPRODDESC

ISRBNKDESC

ISRBRNDESC

ENDPNTDESC

CHGPAYBRNDESC

CLRBNK

PCCLGBRN

SECTORCD

RECSTAT

DUMMY

LOAN_ACCNO

REMARKS

CREDITLINE

LIMTRACKREQD

FRM_DT

TODATE

DOWNPMT

CHQ_INQUIRY

OPERATION

USERREFNO

DRWPARTYID

CHQDATE

TXNSTAT

REMACDESC

BEN_NAME

CHARGE_AC_DESC

SCHEDULEDATE

Pdvws-All-Ac-Entries--Master

EVENT

Pdvws-All-Ac-Entries

EVENT

ACBRN

ACNO

DRCRIND

ACCCY

CODE

FCYAMT

EXCHRATE

LCYAMT

TRNDT

VALUEDT

AMTTAG

Csvws-Contract-Ovd

OVDRIDES

Master

Detb-Pdc-Linkages

CUSTOMERNO

LINKAGE_TYPE

LINKREFNO

LNKPXNTG

LINKAMT

Misdetails

CONREFNO

MISGRP

RELACC

RELETED_REFERENCE

MISHEAD

RATEFLG

POOLCD

REFINANCE_RATE

REFRATETYP

PROCALCMTH

REFSPREAD

REFRATECD

COSTCD1

COSTCD2

COSTCD3

COSTCD4

COSTCD5

TXNMIS1

TXNMIS10

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

MISGRPCOMP

MISGRPTXN

COMPMIS1

COMPMIS10

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

FUNDMIS1

FUNDMIS10

FUNDMIS2

FUNDMIS3

FUNDMIS4

FUNDMIS5

FUNDMIS6

FUNDMIS7

FUNDMIS8

FUNDMIS9

MISGRPFUN

TRANMIS1

TRANMIS2

TRANMIS3

TRANMIS4

TRANMIS5

TRANMIS6

TRANMIS7

TRANMIS8

TRANMIS9

TRANMIS10

COMMIS1

COMMIS2

COMMIS3

COMMIS4

COMMIS5

COMMIS6

COMMIS7

COMMIS8

COMMIS9

COMMIS10

FUNMIS1

FUNMIS2

FUNMIS3

FUNMIS4

FUNMIS5

FUNMIS6

FUNMIS7

FUNMIS8

FUNMIS9

FUNMIS10

Txnmisdetails

Compmisdetails

Fundmisdetails

Control

Balance-Trnsfer-Log-Details

BRANCH

PERIOD_CODE

FIN_YEAR

REFERENCE_NO

GL_CODE

REFERENCE_TYPE

TRANSFER_IND

MIS_CLASS

TXN_DATE

OLD_MIS_CODE

NEW_MIS_CODE

CCY

AMOUNT

EX_RATE

Charge

TRNREF

EVSEQNO

Contract-Charges

COMPONENT

PICKUP_EVENT_SEQUENCE_NUMBER

VALUE_DATE

EVENT_SEQ_NO

TRANSACTION_DATE

CHANGE_DURING_AMENDMENT

CURRENCY

AMOUNT

STATUS

WAIVER

RATE

RATE_TYPE

EVENT

PARTY

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYPDCONTRACT_IOFS_RES

Attribute	Description
Name	QUERYPDCONTRACT_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Pdvws-Pdc-Master-IO

Attribute	Description
Name	Pdvws-Pdc-Master-IO
Datatype	
Description	

TRNREFNO

Attribute	Description
Name	TRNREFNO
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

Pdvws-Pdc-Master-Full

Attribute	Description
Name	Pdvws-Pdc-Master-Full
Datatype	
Description	

TRNREFNO

Attribute	Description
Name	TRNREFNO
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

EVSEQNO

Attribute	Description

Name	EVSEQNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

SCODE

Attribute	**Description**
Name	SCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

XREF

Attribute	**Description**
Name	XREF
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

PRDCD

Attribute	**Description**
Name	PRDCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

BRANCH_CODE

Attribute	**Description**
Name	BRANCH_CODE
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

REMITTER_ACCOUNT_NO

Attribute	Description
Name	REMITTER_ACCOUNT_NO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

BENACNO

Attribute	Description
Name	BENACNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

AMT

Attribute	**Description**
Name	AMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

VALDT

Attribute	**Description**
Name	VALDT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

CLEARING_PRODUCT

Attribute	**Description**
Name	CLEARING_PRODUCT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

RTNGNO

Attribute	**Description**
Name	RTNGNO
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	27

ENDPNT

Attribute	Description
Name	ENDPNT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

ISSUER_BANK

Attribute	Description
Name	ISSUER_BANK
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

ISSUER_BRANCH

Attribute	Description
Name	ISSUER_BRANCH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

PURPOSE

Attribute	Description
Name	PURPOSE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

ACTIVATION_DT

Attribute	Description
Name	ACTIVATION_DT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

LOCNOFCHQ

Attribute	Description
Name	LOCNOFCHQ
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

BLKTXNREF

Attribute	Description
Name	BLKTXNREF
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

CHARGE_BRANCH

Attribute	Description
Name	CHARGE_BRANCH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

CHG_ACC_NUMBER

Attribute	Description
Name	CHG_ACC_NUMBER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,A

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: totalDigits / 22

PRODDESC

Attribute	**Description**
Name	PRODDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

BRNDESC

Attribute	**Description**
Name	BRNDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

CLGPRODDESC

Attribute	**Description**
Name	CLGPRODDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

ISRBNKDESC

Attribute	**Description**
Name	ISRBNKDESC
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 420

ISRBRNDESC

Attribute	**Description**
Name	ISRBRNDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

ENDPNTDESC

Attribute	**Description**
Name	ENDPNTDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

CHGPAYBRNDESC

Attribute	**Description**
Name	CHGPAYBRNDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

CLRBNK

Attribute	**Description**
Name	CLRBNK
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 36

PCCLGBRN

Attribute	**Description**
Name	PCCLGBRN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 36

SECTORCD

Attribute	**Description**
Name	SECTORCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 36

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

DUMMY

Attribute	**Description**
Name	DUMMY
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

LOAN_ACCNO

Attribute	**Description**
Name	LOAN_ACCNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

REMARKS

Attribute	**Description**
Name	REMARKS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

CREDITLINE

Attribute	**Description**
Name	CREDITLINE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

LIMTRACKREQD

Attribute	**Description**
Name	LIMTRACKREQD
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,Y

FRM_DT

Attribute	**Description**
Name	FRM_DT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

TODATE

Attribute	**Description**
Name	TODATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

DOWNPMT

Attribute	**Description**
Name	DOWNPMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CHQ_INQUIRY

Attribute	**Description**
Name	CHQ_INQUIRY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Discounted,Normal,Purchased,Collection,Collection after purchase,Collection after discount,Returned,Passed,Pullback

ORACLE

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,,D

USERREFNO

Attribute	Description
Name	USERREFNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

DRWPARTYID

Attribute	Description
Name	DRWPARTYID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHQDATE

Attribute	Description
Name	CHQDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

TXNSTAT

Attribute	Description
Name	TXNSTAT

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,V,U,L,K,C</td></tr></table>

REMACDESC

Attribute	Description
Name	REMACDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

BEN_NAME

Attribute	Description
Name	BEN_NAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

CHARGE_AC_DESC

Attribute	Description
Name	CHARGE_AC_DESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

SCHEDULEDATE

Attribute	Description
Name	SCHEDULEDATE

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Pdvws-All-Ac-Entries--Master

Attribute	Description
Name	Pdvws-All-Ac-Entries--Master
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

Pdvws-All-Ac-Entries

Attribute	Description
Name	Pdvws-All-Ac-Entries
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

ACBRN

Attribute	Description
Name	ACBRN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

ACNO

Attribute	Description
Name	ACNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

FCYAMT

Attribute	Description
Name	FCYAMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

EXCHRATE

Attribute	Description
Name	EXCHRATE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

TRNDT

Attribute	Description
Name	TRNDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

OVDRIDES

Attribute	Description
Name	OVDRIDES
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	4000

Master

Attribute	Description
Name	Master
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

Detb-Pdc-Linkages

Attribute	Description
Name	Detb-Pdc-Linkages
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

CUSTOMERNO

Attribute	Description
Name	CUSTOMERNO
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	9

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Restrictions	

Restrictions	Description
enumeration	P,C,F

LINKREFNO

Attribute	Description
Name	LINKREFNO
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	35

LNKPXNTG

Attribute	Description
Name	LNKPXNTG
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

LINKAMT

Attribute	Description
Name	LINKAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

POOLCD

Attribute	**Description**
Name	POOLCD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

REFINANCE_RATE

Attribute	**Description**
Name	REFINANCE_RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

REFRATETYP

Attribute	**Description**
Name	REFRATETYP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / X,F,P

PROCALCMTH

Attribute	**Description**
Name	PROCALCMTH
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / 1,2,3,4,5,6,7,8,9

REFSPREAD

Attribute	**Description**
Name	REFSPREAD
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

REFRATECD

Attribute	**Description**
Name	REFRATECD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

COSTCD1

Attribute	**Description**
Name	COSTCD1
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

COSTCD2

Attribute	**Description**
Name	COSTCD2
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

COSTCD3

Attribute	**Description**
Name	COSTCD3
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

COSTCD4

Attribute	**Description**
Name	COSTCD4
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

COSTCD5

Attribute	**Description**
Name	COSTCD5
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TXNMIS10

Attribute	**Description**
Name	TXNMIS10
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TXNMIS2

Attribute	**Description**
Name	TXNMIS2
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TXNMIS3

Attribute	**Description**
Name	TXNMIS3
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TXNMIS4

Attribute	**Description**
Name	TXNMIS4
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TXNMIS5

Attribute	**Description**
Name	TXNMIS5
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TXNMIS6

Attribute	**Description**
Name	TXNMIS6
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TXNMIS7

Attribute	**Description**
Name	TXNMIS7
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TXNMIS8

Attribute	**Description**
Name	TXNMIS8
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TXNMIS9

Attribute	**Description**
Name	TXNMIS9
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

MISGRPCOMP

Attribute	**Description**
Name	MISGRPCOMP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

MISGRPTXN

Attribute	**Description**
Name	MISGRPTXN
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

COMPMIS1

Attribute	**Description**
Name	COMPMIS1
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 9

COMPMIS10

Attribute	**Description**
Name	COMPMIS10
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

COMPMIS2

Attribute	**Description**
Name	COMPMIS2
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

COMPMIS3

Attribute	**Description**
Name	COMPMIS3
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

COMPMIS4

Attribute	**Description**
Name	COMPMIS4
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 10

COMPMIS5

Attribute	**Description**
Name	COMPMIS5
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

COMPMIS6

Attribute	**Description**
Name	COMPMIS6
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

COMPMIS7

Attribute	**Description**
Name	COMPMIS7
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

COMPMIS8

Attribute	**Description**
Name	COMPMIS8
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

COMPMIS9

Attribute	**Description**
Name	COMPMIS9
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

FUNDMIS1

Attribute	**Description**
Name	FUNDMIS1
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

FUNDMIS10

Attribute	**Description**
Name	FUNDMIS10
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

FUNDMIS2

Attribute	**Description**
Name	FUNDMIS2
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

FUNDMIS3

Attribute	**Description**
Name	FUNDMIS3
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

FUNDMIS4

Attribute	**Description**
Name	FUNDMIS4
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

FUNDMIS5

Attribute	**Description**
Name	FUNDMIS5
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

FUNDMIS6

Attribute	**Description**
Name	FUNDMIS6
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

FUNDMIS7

Attribute	**Description**
Name	FUNDMIS7
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

FUNDMIS8

Attribute	**Description**
Name	FUNDMIS8
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

FUNDMIS9

Attribute	**Description**
Name	FUNDMIS9
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

MISGRPFUN

Attribute	**Description**
Name	MISGRPFUN
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** maxLength / 30

TRANMIS1

Attribute	**Description**
Name	TRANMIS1
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TRANMIS2

Attribute	**Description**
Name	TRANMIS2
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TRANMIS3

Attribute	**Description**
Name	TRANMIS3
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TRANMIS4

Attribute	**Description**
Name	TRANMIS4
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 30

TRANMIS5

Attribute	**Description**
Name	TRANMIS5
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TRANMIS6

Attribute	**Description**
Name	TRANMIS6
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TRANMIS7

Attribute	**Description**
Name	TRANMIS7
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TRANMIS8

Attribute	**Description**
Name	TRANMIS8
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TRANMIS9

Attribute	**Description**
Name	TRANMIS9
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TRANMIS10

Attribute	**Description**
Name	TRANMIS10
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

COMMIS1

Attribute	**Description**
Name	COMMIS1
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

COMMIS2

Attribute	**Description**
Name	COMMIS2
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

COMMIS7

Attribute	**Description**
Name	COMMIS7
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

COMMIS8

Attribute	**Description**
Name	COMMIS8
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

COMMIS9

Attribute	**Description**
Name	COMMIS9
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

COMMIS10

Attribute	**Description**
Name	COMMIS10
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** maxLength / 30

FUNMIS1

Attribute	**Description**
Name	FUNMIS1
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

FUNMIS2

Attribute	**Description**
Name	FUNMIS2
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

FUNMIS3

Attribute	**Description**
Name	FUNMIS3
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

FUNMIS4

Attribute	**Description**
Name	FUNMIS4
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

FUNMIS5

Attribute	**Description**
Name	FUNMIS5
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

FUNMIS6

Attribute	**Description**
Name	FUNMIS6
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

FUNMIS7

Attribute	**Description**
Name	FUNMIS7
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

FUNMIS8

Attribute	**Description**
Name	FUNMIS8
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

FUNMIS9

Attribute	**Description**
Name	FUNMIS9
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

FUNMIS10

Attribute	**Description**
Name	FUNMIS10
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

Txnmisdetails

Attribute	**Description**
Name	Txnmisdetails
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

Compmisdetails

Attribute	**Description**
Name	Compmisdetails
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

Control

Attribute	Description
Name	Control
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

Balance-Trnsfer-Log-Details

Attribute	Description
Name	Balance-Trnsfer-Log-Details
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

PERIOD_CODE

Attribute	Description
Name	PERIOD_CODE

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

FIN_YEAR

Attribute	**Description**
Name	FIN_YEAR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFERENCE_NO

Attribute	**Description**
Name	REFERENCE_NO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

GL_CODE

Attribute	**Description**
Name	GL_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFERENCE_TYPE

Attribute	**Description**
Name	REFERENCE_TYPE

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TRANSFER_IND

Attribute	**Description**
Name	TRANSFER_IND
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

MIS_CLASS

Attribute	**Description**
Name	MIS_CLASS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TXN_DATE

Attribute	**Description**
Name	TXN_DATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

OLD_MIS_CODE

Attribute	**Description**
Name	OLD_MIS_CODE
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

NEW_MIS_CODE

Attribute	**Description**
Name	NEW_MIS_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

AMOUNT

Attribute	**Description**
Name	AMOUNT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

EX_RATE

Attribute	**Description**
Name	EX_RATE
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 24

Charge

Attribute	**Description**
Name	Charge
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

TRNREF

Attribute	**Description**
Name	TRNREF
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

EVSEQNO

Attribute	**Description**
Name	EVSEQNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

Contract-Charges

Attribute	**Description**
Name	Contract-Charges
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

PICKUP_EVENT_SEQUENCE_NUMBER

Attribute	Description
Name	PICKUP_EVENT_SEQUENCE_NUMBER
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

VALUE_DATE

Attribute	Description
Name	VALUE_DATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TRANSACTION_DATE

Attribute	Description
Name	TRANSACTION_DATE
Datatype	String
Description	

Attribute	

Attribute	Description
minOccurs	0

CHANGE_DURING_AMENDMENT

Attribute	Description
Name	CHANGE_DURING_AMENDMENT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: maxLength / 1

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

RATE

Attribute	Description
Name	RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	4

PARTY

Attribute	Description
Name	PARTY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.7.ReversePDContract

2.7.1.PD-ReversePDContract-Req-Full-MSG.xsd

REVERSEPDCONTRACT_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Pdvws-Pdc-Master-Full

- *TRNREFNO*
- *EVSEQNO*
- *SCODE*
- *XREF*
- *PRDCD*
- *BRANCH_CODE*
- *REMITTER_ACCOUNT_NO*
- *BENACNO*
- *INSTRNO*
- *CCY*
- *AMT*
- *VALDT*
- *CLEARING_PRODUCT*
- *RTNGNO*
- *ENDPNT*
- *ISSUER_BANK*
- *ISSUER_BRANCH*
- *PURPOSE*
- *ACTIVATION_DT*
- *LOCNOFCHQ*
- *BLKTXNREF*
- *CHARGE_BRANCH*
- *CHG_ACC_NUMBER*
- *CHGCCY*
- *MAKERID*
- *AUTHSTAT*
- *ONCEAUTH*
- *MAKERSTAMP*
- *CHECKERID*
- *CHECKERSTAMP*
- *MODNO*

PRODDESC

BRNDESC

CLGPRODDESC

ISRBNKDESC

ISRBRNDESC

ENDPNTDESC

CHGPAYBRNDESC

CLRBNK

PCCLGBRN

SECTORCD

RECSTAT

DUMMY

LOAN_ACCNO

REMARKS

CREDITLINE

LIMTRACKREQD

FRM_DT

TODATE

DOWNPMT

CHQ_INQUIRY

OPERATION

USERREFNO

DRWPARTYID

CHQDATE

TXNSTAT

REMACDESC

BEN_NAME

CHARGE_AC_DESC

SCHEDULEDATE

Pdvws-All-Ac-Entries--Master

- *EVENT*
- *Pdvws-All-Ac-Entries*

EVENT

ACBRN

ACNO

DRCRIND

ACCCY

CODE

FCYAMT

EXCHRATE

LCYAMT

TRNDT

VALUEDT

AMTTAG

Csvws-Contract-Ovd

OVDRIDES

Master

Detb-Pdc-Linkages

CUSTOMERNO

LINKAGE_TYPE

LINKREFNO

LNKPXNTG

LINKAMT

Misdetails

CONREFNO

MISGRP

RELACC

RELETED_REFERENCE

MISHEAD

RATEFLG

POOLCD

REFINANCE_RATE

REFRATETYP

PROCALCMTH

REFSPREAD

REFRATECD

COSTCD1

COSTCD2

COSTCD3

COSTCD4

COSTCD5

TXNMIS1

TXNMIS10

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

MISGRPCOMP

MISGRPTXN

COMPMIS1

COMPMIS10

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

FUNDMIS1

FUNDMIS10

FUNDMIS2

FUNDMIS3

FUNDMIS4

FUNDMIS5

FUNDMIS6

FUNDMIS7

FUNDMIS8

FUNDMIS9

MISGRPFUN

TRANMIS1

TRANMIS2

TRANMIS3

TRANMIS4

TRANMIS5

TRANMIS6

TRANMIS7

TRANMIS8

TRANMIS9

TRANMIS10

COMMIS1

COMMIS2

COMMIS3

COMMIS4

COMMIS5

COMMIS6

COMMIS7

COMMIS8

COMMIS9

COMMIS10

FUNMIS1

FUNMIS2

FUNMIS3

FUNMIS4

FUNMIS5

FUNMIS6

FUNMIS7

FUNMIS8

FUNMIS9

FUNMIS10

Txnmisdetails

Compmisdetails

Fundmisdetails

Control

Balance-Trnsfer-Log-Details

BRANCH

PERIOD_CODE

FIN_YEAR

REFERENCE_NO

GL_CODE

REFERENCE_TYPE

TRANSFER_IND

MIS_CLASS

TXN_DATE

OLD_MIS_CODE

NEW_MIS_CODE

CCY

AMOUNT

EX_RATE

Charge

TRNREF

EVSEQNO

Contract-Charges

COMPONENT

PICKUP_EVENT_SEQUENCE_NUMBER

VALUE_DATE

EVENT_SEQ_NO

TRANSACTION_DATE

CHANGE_DURING_AMENDMENT

CURRENCY

AMOUNT

STATUS

WAIVER

RATE

RATE_TYPE

EVENT

PARTY

TXNUDFDETAILS

FLDNAME

FLDVAL

REVERSEPDCONTRACT_FSFS_REQ

Attribute	Description
Name	REVERSEPDCONTRACT_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.

Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Pdvws-Pdc-Master-Full
Datatype	
Description	

TRNREFNO

Attribute	Description
Name	TRNREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

EVSEQNO

Attribute	Description
Name	EVSEQNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

SCODE

Attribute	Description
Name	SCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	20

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	4

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

REMITTER_ACCOUNT_NO

Attribute	Description
Name	REMITTER_ACCOUNT_NO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

BENACNO

Attribute	Description
Name	BENACNO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

AMT

Attribute	Description
Name	AMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

VALDT

Attribute	Description
Name	VALDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

CLEARING_PRODUCT

Attribute	Description
Name	CLEARING_PRODUCT

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

RTNGNO

Attribute	Description
Name	RTNGNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>27</td></tr></table>

ENDPNT

Attribute	Description
Name	ENDPNT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

ISSUER_BANK

Attribute	Description
Name	ISSUER_BANK
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

ISSUER_BRANCH

Attribute	Description
Name	ISSUER_BRANCH

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

PURPOSE

Attribute	**Description**
Name	PURPOSE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

ACTIVATION_DT

Attribute	**Description**
Name	ACTIVATION_DT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

LOCNOFCHQ

Attribute	**Description**
Name	LOCNOFCHQ
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

BLKTXNREF

Attribute	**Description**
Name	BLKTXNREF
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

CHARGE_BRANCH

Attribute	**Description**
Name	CHARGE_BRANCH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

CHG_ACC_NUMBER

Attribute	**Description**
Name	CHG_ACC_NUMBER
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

CHGCCY

Attribute	**Description**
Name	CHGCCY
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,A

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	420

BRNDESC

Attribute	Description
Name	BRNDESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	420

CLGPRODDESC

Attribute	Description
Name	CLGPRODDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

ISRBNKDESC

Attribute	Description
Name	ISRBNKDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

ISRBRNDESC

Attribute	Description
Name	ISRBRNDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

ENDPNTDESC

Attribute	Description
Name	ENDPNTDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

CHGPAYBRNDESC

Attribute	Description
Name	CHGPAYBRNDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>420</td></tr></table>

CLRBNK

Attribute	Description
Name	CLRBNK
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>36</td></tr></table>

PCCLGBRN

Attribute	Description
Name	PCCLGBRN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>36</td></tr></table>

SECTORCD

Attribute	Description
Name	SECTORCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>36</td></tr></table>

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

DUMMY

Attribute	Description
Name	DUMMY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>420</td></tr></table>

LOAN_ACCNO

Attribute	Description
Name	LOAN_ACCNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

LIMTRACKREQD

Attribute	Description
Name	LIMTRACKREQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

FRM_DT

Attribute	Description
Name	FRM_DT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TODATE

Attribute	Description
Name	TODATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DOWNPMT

Attribute	Description
Name	DOWNPMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22

CHQ_INQUIRY

Attribute	Description
Name	CHQ_INQUIRY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Discounted,Normal,Purchased,Collection,Collection after purchase,Collection after discount,Returned,Passed,Pullback

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	P,,D

USERREFNO

Attribute	Description
Name	USERREFNO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

DRWPARTYID

Attribute	Description
Name	DRWPARTYID
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

CHQDATE

Attribute	**Description**
Name	CHQDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,V,U,L,K,C

REMACDESC

Attribute	**Description**
Name	REMACDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

BEN_NAME

Attribute	**Description**
Name	BEN_NAME
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	255

CHARGE_AC_DESC

Attribute	Description
Name	CHARGE_AC_DESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255

SCHEDULEDATE

Attribute	Description
Name	SCHEDULEDATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Pdvws-All-Ac-Entries--Master

Attribute	Description
Name	Pdvws-All-Ac-Entries--Master
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

Pdvws-All-Ac-Entries

Attribute	Description

Name	Pdvws-All-Ac-Entries
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

ACBRN

Attribute	Description
Name	ACBRN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

ACNO

Attribute	Description
Name	ACNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 1

ACCCY

Attribute	**Description**
Name	ACCCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

CODE

Attribute	**Description**
Name	CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

FCYAMT

Attribute	**Description**
Name	FCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

EXCHRATE

Attribute	**Description**
Name	EXCHRATE
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

LCYAMT

Attribute	**Description**
Name	LCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TRNDT

Attribute	**Description**
Name	TRNDT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

VALUEDT

Attribute	**Description**
Name	VALUEDT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

AMTTAG

Attribute	**Description**
Name	AMTTAG
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

OVDRIDES

Attribute	Description
Name	OVDRIDES
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

Master

Attribute	Description
Name	Master
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Detb-Pdc-Linkages

Attribute	Description
Name	Detb-Pdc-Linkages
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

CUSTOMERNO

Attribute	Description
Name	CUSTOMERNO
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / P,C,F

LINKREFNO

Attribute	Description
Name	LINKREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 35

LNKPXNTG

Attribute	Description
Name	LNKPXNTG
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

LINKAMT

Attribute	Description
Name	LINKAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	16

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>X,F,P</td></tr></table>

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>1,2,3,4,5,6,7,8,9</td></tr></table>

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Control

Attribute	Description
Name	Control
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Balance-Trnsfer-Log-Details

Attribute	Description
Name	Balance-Trnsfer-Log-Details
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

PERIOD_CODE

Attribute	**Description**
Name	PERIOD_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

FIN_YEAR

Attribute	**Description**
Name	FIN_YEAR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFERENCE_NO

Attribute	**Description**
Name	REFERENCE_NO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

GL_CODE

Attribute	**Description**

Name	GL_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFERENCE_TYPE

Attribute	**Description**
Name	REFERENCE_TYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TRANSFER_IND

Attribute	**Description**
Name	TRANSFER_IND
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

MIS_CLASS

Attribute	**Description**
Name	MIS_CLASS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TXN_DATE

Attribute	**Description**

Name	TXN_DATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

OLD_MIS_CODE

Attribute	Description
Name	OLD_MIS_CODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

NEW_MIS_CODE

Attribute	Description
Name	NEW_MIS_CODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Decimal
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

EX_RATE

Attribute	Description
Name	EX_RATE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>24</td></tr></table>

Charge

Attribute	Description
Name	Charge
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TRNREF

Attribute	Description
Name	TRNREF
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

EVSEQNO

Attribute	Description
Name	EVSEQNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22

Contract-Charges

Attribute	Description
Name	Contract-Charges
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	15

PICKUP_EVENT_SEQUENCE_NUMBER

Attribute	Description
Name	PICKUP_EVENT_SEQUENCE_NUMBER
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

VALUE_DATE

Attribute	Description
Name	VALUE_DATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TRANSACTION_DATE

Attribute	**Description**
Name	TRANSACTION_DATE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

CHANGE_DURING_AMENDMENT

Attribute	**Description**
Name	CHANGE_DURING_AMENDMENT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

CURRENCY

Attribute	**Description**
Name	CURRENCY
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

AMOUNT

Attribute	**Description**
Name	AMOUNT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	
	Restrictions / **Description**: totalDigits / 22

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

RATE

Attribute	Description
Name	RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	1

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

PARTY

Attribute	Description
Name	PARTY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.7.2.PD-ReversePDContract-Req-IO-MSG.xsd

REVERSEPDCONTRACT_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Pdvws-Pdc-Master-IO

TRNREFNO

REVERSEPDCONTRACT_IOPK_REQ

Attribute	Description
Name	REVERSEPDCONTRACT_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Pdvws-Pdc-Master-IO

Attribute	Description
Name	Pdvws-Pdc-Master-IO
Datatype	
Description	

TRNREFNO

Attribute	Description
Name	TRNREFNO
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

2.7.3.PD-ReversePDContract-Res-Full-MSG.xsd

REVERSEPDCONTRACT_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Pdvws-Pdc-Master-Full

TRNREFNO

EVSEQNO

SCODE

XREF

PRDCD

BRANCH_CODE

REMITTER_ACCOUNT_NO

BENACNO

INSTRNO

CCY

AMT

VALDT

CLEARING_PRODUCT

RTNGNO

ENDPNT

ISSUER_BANK

ISSUER_BRANCH

PURPOSE

ACTIVATION_DT

LOCNOFCHQ

BLKTXNREF

CHARGE_BRANCH

CHG_ACC_NUMBER

CHGCCY

MAKERID

AUTHSTAT

ONCEAUTH

MAKERSTAMP

CHECKERID

CHECKERSTAMP

MODNO

PRODDESC

BRNDESC

CLGPRODDESC

ISRBNKDESC

ISRBRNDESC

ENDPNTDESC

CHGPAYBRNDESC

CLRBNK

PCCLGBRN

SECTORCD

RECSTAT

DUMMY

LOAN_ACCNO

REMARKS

CREDITLINE

LIMTRACKREQD

FRM_DT

TODATE

DOWNPMT

CHQ_INQUIRY

OPERATION

USERREFNO

DRWPARTYID

CHQDATE

TXNSTAT

REMACDESC

BEN_NAME

CHARGE_AC_DESC

SCHEDULEDATE

Pdvws-All-Ac-Entries--Master

- *EVENT*
- *Pdvws-All-Ac-Entries*
  - *EVENT*
  - *ACBRN*
  - *ACNO*
  - *DRCRIND*
  - *ACCCY*
  - *CODE*
  - *FCYAMT*
  - *EXCHRATE*

LCYAMT

TRNDT

VALUEDT

AMTTAG

Csvws-Contract-Ovd

OVDRIDES

Master

Detb-Pdc-Linkages

CUSTOMERNO

LINKAGE_TYPE

LINKREFNO

LNKPXNTG

LINKAMT

Misdetails

CONREFNO

MISGRP

RELACC

RELETED_REFERENCE

MISHEAD

RATEFLG

POOLCD

REFINANCE_RATE

REFRATETYP

PROCALCMTH

REFSPREAD

REFRATECD

COSTCD1

COSTCD2

COSTCD3

COSTCD4

COSTCD5

TXNMIS1

TXNMIS10

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

MISGRPCOMP

MISGRPTXN

COMPMIS1

COMPMIS10

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

FUNDMIS1

FUNDMIS10

FUNDMIS2

FUNDMIS3

FUNDMIS4

FUNDMIS5

FUNDMIS6

FUNDMIS7

FUNDMIS8

FUNDMIS9

MISGRPFUN

TRANMIS1

TRANMIS2

TRANMIS3

TRANMIS4

TRANMIS5

TRANMIS6

TRANMIS7

TRANMIS8

TRANMIS9

TRANMIS10

COMMIS1

COMMIS2

COMMIS3

COMMIS4

COMMIS5

COMMIS6

COMMIS7

COMMIS8

COMMIS9

COMMIS10

FUNMIS1

FUNMIS2

FUNMIS3

FUNMIS4

FUNMIS5

FUNMIS6

FUNMIS7

FUNMIS8

FUNMIS9

FUNMIS10

Txnmisdetails

Compmisdetails

Fundmisdetails

Control

Balance-Trnsfer-Log-Details

BRANCH

PERIOD_CODE

FIN_YEAR

REFERENCE_NO

GL_CODE

REFERENCE_TYPE

TRANSFER_IND

MIS_CLASS

TXN_DATE

OLD_MIS_CODE

NEW_MIS_CODE

CCY

AMOUNT

EX_RATE

Charge

TRNREF

EVSEQNO

Contract-Charges

COMPONENT

PICKUP_EVENT_SEQUENCE_NUMBER

VALUE_DATE

EVENT_SEQ_NO

TRANSACTION_DATE

CHANGE_DURING_AMENDMENT

CURRENCY

AMOUNT

STATUS

WAIVER

RATE

RATE_TYPE

EVENT

PARTY

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

REVERSEPDCONTRACT_FSFS_RES

Attribute	Description
Name	REVERSEPDCONTRACT_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.

Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Pdvws-Pdc-Master-Full
Datatype	
Description	

TRNREFNO

Attribute	Description
Name	TRNREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

EVSEQNO

Attribute	Description
Name	EVSEQNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

SCODE

Attribute	Description
Name	SCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	20

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	4

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

REMITTER_ACCOUNT_NO

Attribute	Description
Name	REMITTER_ACCOUNT_NO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

BENACNO

Attribute	Description
Name	BENACNO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

AMT

Attribute	Description
Name	AMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

VALDT

Attribute	Description
Name	VALDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

CLEARING_PRODUCT

Attribute	Description
Name	CLEARING_PRODUCT

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

RTNGNO

Attribute	Description
Name	RTNGNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>27</td></tr></table>

ENDPNT

Attribute	Description
Name	ENDPNT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

ISSUER_BANK

Attribute	Description
Name	ISSUER_BANK
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

ISSUER_BRANCH

Attribute	Description
Name	ISSUER_BRANCH

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

PURPOSE

Attribute	**Description**
Name	PURPOSE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

ACTIVATION_DT

Attribute	**Description**
Name	ACTIVATION_DT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

LOCNOFCHQ

Attribute	**Description**
Name	LOCNOFCHQ
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

BLKTXNREF

Attribute	**Description**
Name	BLKTXNREF
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

CHARGE_BRANCH

Attribute	**Description**
Name	CHARGE_BRANCH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

CHG_ACC_NUMBER

Attribute	**Description**
Name	CHG_ACC_NUMBER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

CHGCCY

Attribute	**Description**
Name	CHGCCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,A

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

PRODDESC

Attribute	Description
Name	PRODDESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	420

BRNDESC

Attribute	Description
Name	BRNDESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	420

CLGPRODDESC

Attribute	Description
Name	CLGPRODDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

ISRBNKDESC

Attribute	Description
Name	ISRBNKDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

ISRBRNDESC

Attribute	Description
Name	ISRBRNDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

ENDPNTDESC

Attribute	Description
Name	ENDPNTDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 420

CHGPAYBRNDESC

Attribute	Description
Name	CHGPAYBRNDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>420</td></tr></table>

CLRBNK

Attribute	Description
Name	CLRBNK
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>36</td></tr></table>

PCCLGBRN

Attribute	Description
Name	PCCLGBRN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>36</td></tr></table>

SECTORCD

Attribute	Description
Name	SECTORCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>36</td></tr></table>

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

DUMMY

Attribute	Description
Name	DUMMY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>420</td></tr></table>

LOAN_ACCNO

Attribute	Description
Name	LOAN_ACCNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

CREDITLINE

Attribute	Description
Name	CREDITLINE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

LIMTRACKREQD

Attribute	Description
Name	LIMTRACKREQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>N,Y</td></tr></table>

FRM_DT

Attribute	Description
Name	FRM_DT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TODATE

Attribute	Description
Name	TODATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DOWNPMT

Attribute	Description
Name	DOWNPMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22

CHQ_INQUIRY

Attribute	Description
Name	CHQ_INQUIRY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Discounted,Normal,Purchased,Collection,Collection after purchase,Collection after discount,Returned,Passed,Pullback

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	P,,D

USERREFNO

Attribute	Description
Name	USERREFNO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

DRWPARTYID

Attribute	Description
Name	DRWPARTYID
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

CHQDATE

Attribute	**Description**
Name	CHQDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,V,U,L,K,C

REMACDESC

Attribute	**Description**
Name	REMACDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

BEN_NAME

Attribute	**Description**
Name	BEN_NAME
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	255

CHARGE_AC_DESC

Attribute	Description
Name	CHARGE_AC_DESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255

SCHEDULEDATE

Attribute	Description
Name	SCHEDULEDATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Pdvws-All-Ac-Entries--Master

Attribute	Description
Name	Pdvws-All-Ac-Entries--Master
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

Pdvws-All-Ac-Entries

Attribute	Description

Name	Pdvws-All-Ac-Entries
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

EVENT

Attribute	**Description**
Name	EVENT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

ACBRN

Attribute	**Description**
Name	ACBRN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

ACNO

Attribute	**Description**
Name	ACNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

DRCRIND

Attribute	**Description**
Name	DRCRIND
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 1

ACCCY

Attribute	**Description**
Name	ACCCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

CODE

Attribute	**Description**
Name	CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

FCYAMT

Attribute	**Description**
Name	FCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

EXCHRATE

Attribute	**Description**
Name	EXCHRATE
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

LCYAMT

Attribute	**Description**
Name	LCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TRNDT

Attribute	**Description**
Name	TRNDT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

VALUEDT

Attribute	**Description**
Name	VALUEDT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

AMTTAG

Attribute	**Description**
Name	AMTTAG
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

Csvws-Contract-Ovd

Attribute	Description
Name	Csvws-Contract-Ovd
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

OVDRIDES

Attribute	Description
Name	OVDRIDES
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

Master

Attribute	Description
Name	Master
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Detb-Pdc-Linkages

Attribute	Description
Name	Detb-Pdc-Linkages
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

CUSTOMERNO

Attribute	Description
Name	CUSTOMERNO
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / P,C,F

LINKREFNO

Attribute	Description
Name	LINKREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 35

LNKPXNTG

Attribute	Description
Name	LNKPXNTG
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

LINKAMT

Attribute	Description
Name	LINKAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	

Attribute	
	Attribute / **Description** minOccurs / 0

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>X,F,P</td></tr></table>

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>1,2,3,4,5,6,7,8,9</td></tr></table>

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Control

Attribute	Description
Name	Control
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Balance-Trnsfer-Log-Details

Attribute	Description
Name	Balance-Trnsfer-Log-Details
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

PERIOD_CODE

Attribute	**Description**
Name	PERIOD_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

FIN_YEAR

Attribute	**Description**
Name	FIN_YEAR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFERENCE_NO

Attribute	**Description**
Name	REFERENCE_NO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

GL_CODE

Attribute	**Description**

Name	GL_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFERENCE_TYPE

Attribute	**Description**
Name	REFERENCE_TYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TRANSFER_IND

Attribute	**Description**
Name	TRANSFER_IND
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

MIS_CLASS

Attribute	**Description**
Name	MIS_CLASS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TXN_DATE

Attribute	**Description**

Name	TXN_DATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

OLD_MIS_CODE

Attribute	Description
Name	OLD_MIS_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

NEW_MIS_CODE

Attribute	Description
Name	NEW_MIS_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

AMOUNT

Attribute	Description
Name	AMOUNT
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

EX_RATE

Attribute	**Description**
Name	EX_RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 24

Charge

Attribute	**Description**
Name	Charge
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

TRNREF

Attribute	**Description**
Name	TRNREF
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

EVSEQNO

Attribute	**Description**
Name	EVSEQNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22

Contract-Charges

Attribute	Description
Name	Contract-Charges
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

COMPONENT

Attribute	Description
Name	COMPONENT
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	15

PICKUP_EVENT_SEQUENCE_NUMBER

Attribute	Description
Name	PICKUP_EVENT_SEQUENCE_NUMBER
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

VALUE_DATE

Attribute	Description
Name	VALUE_DATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TRANSACTION_DATE

Attribute	**Description**
Name	TRANSACTION_DATE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

CHANGE_DURING_AMENDMENT

Attribute	**Description**
Name	CHANGE_DURING_AMENDMENT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

CURRENCY

Attribute	**Description**
Name	CURRENCY
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

AMOUNT

Attribute	**Description**
Name	AMOUNT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	
	Restrictions / **Description**: totalDigits / 22

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

RATE

Attribute	Description
Name	RATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

RATE_TYPE

Attribute	Description
Name	RATE_TYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	1

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

PARTY

Attribute	Description
Name	PARTY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.7.4.PD-ReversePDContract-Res-PK-MSG.xsd

REVERSEPDCONTRACT_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Pdvws-Pdc-Master-PK

TRNREFNO

Pdvws-Pdc-Master-IO

TRNREFNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

REVERSEPDCONTRACT_IOPK_RES

Attribute	Description
Name	REVERSEPDCONTRACT_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	
	Restrictions / **Description**: pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description**: minOccurs / 0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Pdvws-Pdc-Master-PK

Attribute	Description
Name	Pdvws-Pdc-Master-PK
Datatype	
Description	

TRNREFNO

Attribute	Description
Name	TRNREFNO
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

Pdvws-Pdc-Master-IO

Attribute	Description
Name	Pdvws-Pdc-Master-IO
Datatype	
Description	

TRNREFNO

Attribute	Description
Name	TRNREFNO
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

WCODE

Attribute	Description

Name	WCODE
Datatype	String
Description	

WDESC

Attribute	**Description**
Name	WDESC
Datatype	String
Description	

Gateway Documentation - FCUBSEXTPDService
[Febraury] [2016]

Oracle Financial services Software Limited
Oracle Park
Off western Express Highway
Goregaon(East)
Mumbai,Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax:+91 22 6718 3001
www.oracle.com/financialservices/

Copyright © [2013], [2016], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.