

Gateway Documentation - FCUBSIIService
Oracle FLEXCUBE Universal Banking
Release 12.87.02.0.0
[Febraury][2016]



Table Of Contents

1. Background	1
2. FCUBSIIService	2
2.1.AuthorizeIIGroup	2
2.1.1.II-AuthorizeIIGroup-Req-Full-MSG.xsd	2
2.1.2.II-AuthorizeIIGroup-Req-IO-MSG.xsd	14
2.1.3.II-AuthorizeIIGroup-Res-Full-MSG.xsd	21
2.1.4.II-AuthorizeIIGroup-Res-PK-MSG.xsd	35
2.2.AuthorizeIIGrplink	44
2.2.1.II-AuthorizeIIGrplink-Req-Full-MSG.xsd	44
2.2.2.II-AuthorizeIIGrplink-Req-IO-MSG.xsd	55
2.2.3.II-AuthorizeIIGrplink-Res-Full-MSG.xsd	63
2.2.4.II-AuthorizeIIGrplink-Res-PK-MSG.xsd	75
2.3.AuthorizeIISweep	85
2.3.1.II-AuthorizeIISweep-Req-Full-MSG.xsd	85
2.3.2.II-AuthorizeIISweep-Req-IO-MSG.xsd	100
2.3.3.II-AuthorizeIISweep-Res-Full-MSG.xsd	108
2.3.4.II-AuthorizeIISweep-Res-PK-MSG.xsd	123
2.4.CloseIIGroup	134
2.4.1.II-CloseIIGroup-Req-Full-MSG.xsd	134
2.4.2.II-CloseIIGroup-Req-IO-MSG.xsd	146
2.4.3.II-CloseIIGroup-Res-Full-MSG.xsd	154
2.4.4.II-CloseIIGroup-Res-PK-MSG.xsd	167
2.5.CloseIIGrplink	176
2.5.1.II-CloseIIGrplink-Req-Full-MSG.xsd	176
2.5.2.II-CloseIIGrplink-Req-IO-MSG.xsd	187
2.5.3.II-CloseIIGrplink-Res-Full-MSG.xsd	195
2.5.4.II-CloseIIGrplink-Res-PK-MSG.xsd	207
2.6.CloseIISweep	217
2.6.1.II-CloseIISweep-Req-Full-MSG.xsd	217
2.6.2.II-CloseIISweep-Req-IO-MSG.xsd	232
2.6.3.II-CloseIISweep-Res-Full-MSG.xsd	240
2.6.4.II-CloseIISweep-Res-PK-MSG.xsd	255
2.7.CreateIIGroup	266
2.7.1.II-CreateIIGroup-Req-Full-MSG.xsd	266
2.7.2.II-CreateIIGroup-Req-IO-MSG.xsd	278
2.7.3.II-CreateIIGroup-Res-Full-MSG.xsd	288
2.7.4.II-CreateIIGroup-Res-PK-MSG.xsd	302
2.8.CreateIIGrplink	314
2.8.1.II-CreateIIGrplink-Req-Full-MSG.xsd	314
2.8.2.II-CreateIIGrplink-Req-IO-MSG.xsd	324
2.8.3.II-CreateIIGrplink-Res-Full-MSG.xsd	332
2.8.4.II-CreateIIGrplink-Res-PK-MSG.xsd	344
2.9.CreateIISweep	355
2.9.1.II-CreateIISweep-Req-Full-MSG.xsd	355
2.9.2.II-CreateIISweep-Req-IO-MSG.xsd	369
2.9.3.II-CreateIISweep-Res-Full-MSG.xsd	379
2.9.4.II-CreateIISweep-Res-PK-MSG.xsd	395
2.10.DeleteIIGroup	408

2.10.1.II-DeletelIGroup-Req-Full-MSG.xsd	408
2.10.2.II-DeletelIGroup-Req-IO-MSG.xsd	420
2.10.3.II-DeletelIGroup-Res-Full-MSG.xsd	427
2.10.4.II-DeletelIGroup-Res-PK-MSG.xsd	441
2.11.DeletelIGrplink	449
2.11.1.II-DeletelIGrplink-Req-Full-MSG.xsd	449
2.11.2.II-DeletelIGrplink-Req-IO-MSG.xsd	460
2.11.3.II-DeletelIGrplink-Res-Full-MSG.xsd	467
2.11.4.II-DeletelIGrplink-Res-PK-MSG.xsd	479
2.12.DeletelISweep	489
2.12.1.II-DeletelISweep-Req-Full-MSG.xsd	489
2.12.2.II-DeletelISweep-Req-IO-MSG.xsd	503
2.12.3.II-DeletelISweep-Res-Full-MSG.xsd	510
2.12.4.II-DeletelISweep-Res-PK-MSG.xsd	525
2.13.ModifyIGroup	535
2.13.1.II-ModifyIGroup-Req-Full-MSG.xsd	535
2.13.2.II-ModifyIGroup-Req-IO-MSG.xsd	547
2.13.3.II-ModifyIGroup-Res-Full-MSG.xsd	557
2.13.4.II-ModifyIGroup-Res-PK-MSG.xsd	571
2.14.ModifyISweep	582
2.14.1.II-ModifyISweep-Req-Full-MSG.xsd	582
2.14.2.II-ModifyISweep-Req-IO-MSG.xsd	596
2.14.3.II-ModifyISweep-Res-Full-MSG.xsd	608
2.14.4.II-ModifyISweep-Res-PK-MSG.xsd	624
2.15.QueryIGroup	638
2.15.1.II-QueryIGroup-Req-IO-MSG.xsd	638
2.15.2.II-QueryIGroup-Res-Full-MSG.xsd	645
2.16.QueryIGrplink	659
2.16.1.II-QueryIGrplink-Req-IO-MSG.xsd	659
2.16.2.II-QueryIGrplink-Res-Full-MSG.xsd	666
2.17.QueryISweep	679
2.17.1.II-QueryISweep-Req-IO-MSG.xsd	679
2.17.2.II-QueryISweep-Res-Full-MSG.xsd	686
2.18.ReopenIGroup	703
2.18.1.II-ReopenIGroup-Req-Full-MSG.xsd	703
2.18.2.II-ReopenIGroup-Req-IO-MSG.xsd	715
2.18.3.II-ReopenIGroup-Res-Full-MSG.xsd	722
2.18.4.II-ReopenIGroup-Res-PK-MSG.xsd	736

1. Background

Integration of different applications and solutions is a key area in today's systems. A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data. The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs. The integration needs supported by the Gateway can be broadly categorized from the perspective of Gateway as follows

1. Inbound application integration :

This is used when any external system needs to add, modify or query information within FLEXCUBE UBS

2. Outbound application integration :

This is used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS

The following sections provide detailed XSD documentation of all operations available in FCUBSII Service of II Module

2. FCUBSIIService

2.1.AuthorizeIIGroup

2.1.1.II-AuthorizeIIGroup-Req-Full-MSG.xsd

AUTHORIZEIIGROUP_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Itms-Group-Code-Full

GRPCD

ACCGLDESC

POOL_BENEFIT

SWEEP_BASIS

EFFECTIVE_DATE

INTRADAY_SWEEP_REQD

BVT_INDICATOR

BVT_UNIT

BVT_DURATION

REV_SWEEP_REQD

ACCBRN

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

AUTHORIZEIIGROUP_FSFS_REQ

Attribute	Description
Name	AUTHORIZEIIGROUP_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
-----------	-------------

Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nullable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description
Name	MULTIRIPID

Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Itms-Group-Code-Full

Attribute	Description
Name	Itms-Group-Code-Full
Datatype	
Description	

GRPCD

Attribute	Description				
Name	GRPCD				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

ACGLDESC

Attribute	Description				
Name	ACGLDESC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

POOL_BENEFIT

Attribute	Description				
Name	POOL_BENEFIT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>Y,N</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

SWEEP_BASIS

Attribute	Description
-----------	-------------

Name	SWEEP_BASIS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	B,V

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

INTRADAY_SWEEP_REQD

Attribute	Description	
Name	INTRADAY_SWEEP_REQD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

BVT_INDICATOR

Attribute	Description	
Name	BVT_INDICATOR	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

BVT_UNIT

Attribute	Description	
Name	BVT_UNIT	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	M,D

BVT_DURATION

Attribute	Description	
Name	BVT_DURATION	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

REV_SWEEP_REQD

Attribute	Description	
Name	REV_SWEEP_REQD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	3

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.1.2.II-AuthorizeIIGroup-Req-IO-MSG.xsd

AUTHORIZEIIGROUP_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Itms-Group-Code-IO

GRPCD

CHECKER

CHECKERSTAMP

MODNO

AUTHORIZEIIGROUP_IOPK_REQ

Attribute	Description
Name	AUTHORIZEIIGROUP_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0

PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0
	maxOccurs		unbounded

NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

FCUBS_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description			

Itms-Group-Code-IO

Attribute		Description	
Name		Itms-Group-Code-IO	
Datatype			
Description			

GRPCD

Attribute		Description	
Name		GRPCD	
Datatype		String	
Description			
Restrictions	Restrictions		Description
	maxLength		9

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

2.1.3.II-AuthorizeIIGroup-Res-Full-MSG.xsd

AUTHORIZEIIGROUP_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Itms-Group-Code-Full
GRPCD
ACCGLDESC
POOL_BENEFIT
SWEEP_BASIS
EFFECTIVE_DATE
INTRADAY_SWEEP_REQD
BVT_INDICATOR
BVT_UNIT
BVT_DURATION
REV_SWEEP_REQD
ACCBRN
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZEIIGROUP_FSFS_RES

Attribute	Description
Name	AUTHORIZEIIGROUP_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description					
enumeration	FCUBS,FCIS					

MSGID

Attribute	Description					
Name	MSGID					
Datatype	String					
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	String					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Itms-Group-Code-Full
Datatype	
Description	

GRPCD

Attribute	Description				
Name	GRPCD				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

ACCGLDESC

Attribute	Description				
Name	ACCGLDESC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

POOL_BENEFIT

Attribute	Description				
Name	POOL_BENEFIT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>Y,N</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

SWEEP_BASIS

Attribute	Description				
Name	SWEEP_BASIS				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	enumeration	B,V

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

INTRADAY_SWEEP_REQD

Attribute	Description	
Name	INTRADAY_SWEEP_REQD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

BVT_INDICATOR

Attribute	Description	
Name	BVT_INDICATOR	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

BVT_UNIT

Attribute	Description	
Name	BVT_UNIT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	M,D

BVT_DURATION

Attribute	Description	
Name	BVT_DURATION	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

REV_SWEEP_REQD

Attribute	Description	
Name	REV_SWEEP_REQD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	3

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	

Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	1
	Description	

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	1
	Description	

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	
	maxLength	105
	minLength	1
	Description	

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	
	minOccurs	0
	Description	

Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.1.4.II-AuthorizeIIGroup-Res-PK-MSG.xsd

AUTHORIZEIIGROUP_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Itms-Group-Code-PK

GRPCD

Itms-Group-Code-IO

GRPCD

CHECKER

CHECKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZEIIGROUP_IOPK_RES

Attribute	Description
Name	AUTHORIZEIIGROUP_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Itms-Group-Code-PK

Attribute	Description
Name	Itms-Group-Code-PK
Datatype	
Description	

GRPCD

Attribute	Description				
Name	GRPCD				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

Itms-Group-Code-IO

Attribute	Description
Name	Itms-Group-Code-IO
Datatype	
Description	

GRPCD

Attribute	Description				
Name	GRPCD				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

CHECKER

Attribute	Description
-----------	-------------

Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	12
	Description	

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	35
	Description	

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	totalDigits	4
	Description	

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		

Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.2.AuthorizeIIGrplink

2.2.1.II-AuthorizeIIGrplink-Req-Full-MSG.xsd

[AUTHORIZEIIGRPLINK_FSFS_REQ](#)

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Iltms-Account-Group-Link-Full

ACCBRN

HEADER_ACC

EFFECTIVE_DATE

GROUP_CODE

CCY3

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

AUTHORIZEIIGRPLINK_FSFS_REQ

Attribute	Description
Name	AUTHORIZEIIGRPLINK_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
-----------	-------------

Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Itms-Account-Group-Link-Full

Attribute	Description	
Name	Itms-Account-Group-Link-Full	
Datatype		
Description		

ACCBRN

Attribute	Description	
------------------	--------------------	--

Name	ACCBRN	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

HEADER_ACC

Attribute	Description	
Name	HEADER_ACC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		

GROUP_CODE

Attribute	Description	
Name	GROUP_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

CCY3

Attribute	Description	
Name	CCY3	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	4

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name

Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

2.2.2.II-AuthorizeIIGrplink-Req-IO-MSG.xsd

AUTHORIZEIIGRPLINK_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM
NAME
VALUE
FCUBS_BODY
Itms-Account-Group-Link-IO
ACCBRN
HEADER_ACC
EFFECTIVE_DATE
GROUP_CODE
CHECKER
CHECKERSTAMP
MODNO

AUTHORIZEIIGRPLINK_IOPK_REQ

Attribute	Description
Name	AUTHORIZEIIGRPLINK_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Itms-Account-Group-Link-IO

Attribute		Description
------------------	--	--------------------

Name	Ilrms-Account-Group-Link-IO
Datatype	
Description	

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

HEADER_ACC

Attribute	Description	
Name	HEADER_ACC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		

GROUP_CODE

Attribute	Description	
Name	GROUP_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

2.2.3.II-AuthorizeIIGrplink-Res-Full-MSG.xsd

AUTHORIZEIIGRPLINK_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Iltns-Account-Group-Link-Full

ACCBRN

HEADER_ACC

EFFECTIVE_DATE

GROUP_CODE

CCY3

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

Attribute	Description
Name	AUTHORIZEIIGRPLINK_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	String					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

USERID

Attribute	Description							
Name	USERID							
Datatype	String							
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description							
maxLength	12							
pattern	[A-Z_0-9]*							

BRANCH

Attribute	Description							
Name	BRANCH							
Datatype	String							
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>		Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description							
length	3							
pattern	[a-zA-Z_0-9]{3}							

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	

Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	

Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute			
	Attribute		Description
	minOccurs		0
	maxOccurs		unbounded

NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

FCUBS_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description			

Itms-Account-Group-Link-Full

Attribute		Description	
Name		Itms-Account-Group-Link-Full	
Datatype			
Description			

ACCBRN

Attribute		Description	
Name		ACCBRN	
Datatype		String	
Description			
Restrictions			
	Restrictions		Description
	maxLength		3

HEADER_ACC

Attribute		Description	
Name		HEADER_ACC	
Datatype		String	
Description			
Restrictions			
	Restrictions		Description
	maxLength		20

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

GROUP_CODE

Attribute	Description				
Name	GROUP_CODE				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

CCY3

Attribute	Description				
Name	CCY3				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>4</td></tr></tbody></table>	Restrictions	Description	maxLength	4
Restrictions	Description				
maxLength	4				

MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MAKERSTAMP

Attribute	Description				
Name	MAKERSTAMP				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

Attribute		Description	
Name	FCUBS_ERROR_RESP		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

ERROR

Attribute		Description	
Name	ERROR		
Datatype			
Description			
Attribute	Attribute		Description
	maxOccurs	unbounded	

ECODE

Attribute		Description	
Name	ECODE		
Datatype	String		
Description			

EDESC

Attribute		Description	
Name	EDESC		
Datatype	String		
Description			

FCUBS_WARNING_RESP

Attribute		Description	
Name	FCUBS_WARNING_RESP		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

WARNING

Attribute		Description	
Name	WARNING		
Datatype			
Description			
Attribute	Attribute		Description
	maxOccurs	unbounded	

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.2.4.II-AuthorizeIIGrplink-Res-PK-MSG.xsd

AUTHORIZEIIGRPLINK_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Itms-Account-Group-Link-PK

EFFECTIVE_DATE

GROUP_CODE

ACCBRN

HEADER_ACC

Itms-Account-Group-Link-IO

ACCBRN

HEADER_ACC

EFFECTIVE_DATE

GROUP_CODE

CHECKER

CHECKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZEIIGRPLINK_IOPK_RES

Attribute	Description
Name	AUTHORIZEIIGRPLINK_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Itms-Account-Group-Link-PK

Attribute	Description
Name	Itms-Account-Group-Link-PK
Datatype	
Description	

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

GROUP_CODE

Attribute	Description				
Name	GROUP_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

ACCBRN

Attribute	Description				
Name	ACCBRN				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

HEADER_ACC

Attribute	Description
-----------	-------------

Name	HEADER_ACC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

Itms-Account-Group-Link-IO

Attribute	Description	
Name	Itms-Account-Group-Link-IO	
Datatype		
Description		

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

HEADER_ACC

Attribute	Description	
Name	HEADER_ACC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		

GROUP_CODE

Attribute	Description	
Name	GROUP_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		

Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.3.AuthorizeIISweep

2.3.1.II-AuthorizeIISweep-Req-Full-MSG.xsd

[AUTHORIZEIISWEEP_FSFS_REQ](#)

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Itms-Account-Full

ACCBRN

ACCNT

ACCINDR

EFFECTIVE_DATE

PARENT_ACC_BRN

ACC_NO

SCHEME_1

SWPTYPE

BASE_AMT
REALLOC_REQD
BOOK_ACC_BRN
ACCOPT
EXCHGRRTYP
SPREAD_IND
ACCGLCCY
PARENT_ACC_CCY
BOOK_ACC_CCY
MULTIPLE_AMT
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
UDFDETAILS
FLDNAM
FLDVAL

AUTHORIZEISWEEP_FSFS_REQ

Attribute	Description
Name	AUTHORIZEISWEEP_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
pattern	[A-Z_0-9]*	

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
pattern	[a-zA-Z_0-9]{3}	

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Itms-Account-Full

Attribute	Description
Name	Itms-Account-Full
Datatype	
Description	

ACCBRN

Attribute	Description				
Name	ACCBRN				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

ACCNT

Attribute	Description				
Name	ACCNT				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

ACCINDR

Attribute	Description				
Name	ACCINDR				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>C,P</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	C,P
Restrictions	Description				
enumeration	C,P				

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

PARENT_ACC_BRN

Attribute	Description				
Name	PARENT_ACC_BRN				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

ACC_NO

Attribute	Description				
Name	ACC_NO				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
	Restrictions	Description			
maxLength	20				

SCHEME_1

Attribute	Description				
Name	SCHEME_1				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>S</td></tr></tbody></table>	Restrictions	Description	enumeration	S
	Restrictions	Description			
enumeration	S				

SWPTYPE

Attribute	Description
Name	SWPTYPE
Datatype	String
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,C,T

BASE_AMT

Attribute	Description	
Name	BASE_AMT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22
	minInclusive	0

REALLOC_REQD

Attribute	Description	
Name	REALLOC_REQD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

BOOK_ACC_BRN

Attribute	Description	
Name	BOOK_ACC_BRN	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

ACCOPT

Attribute	Description	
Name	ACCOPT	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

EXCHGRTTYP

Attribute	Description	
Name	EXCHGRTTYP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8

SPREAD_IND

Attribute	Description	
Name	SPREAD_IND	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	M,B

ACCGLCCY

Attribute	Description	
Name	ACCGLCCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

PARENT_ACC_CCY

Attribute	Description	
Name	PARENT_ACC_CCY	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

BOOK_ACC_CCY

Attribute	Description	
Name	BOOK_ACC_CCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

MULTIPLE_AMT

Attribute	Description	
Name	MULTIPLE_AMT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.3.2.II-AuthorizeIISweep-Req-IO-MSG.xsd

AUTHORIZEIISWEEP_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Itms-Account-IO

ACCBRN

ACCNT

ACCINDR

EFFECTIVE_DATE

CHECKER

CHECKERSTAMP

MODNO

AUTHORIZEISWEEP_IOPK_REQ

Attribute	Description
Name	AUTHORIZEISWEEP_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

ADDL

Attribute		Description	
Name	ADDL		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	

PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

FCUBS_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description			

Itms-Account-IO

Attribute		Description	
Name	Itms-Account-IO		
Datatype			
Description			

ACCBRN

Attribute		Description	
Name	ACCBRN		
Datatype	String		
Description			
Restrictions	Restrictions		Description
	maxLength	3	

ACCNT

Attribute	Description				
Name	ACCNT				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

ACCINDR

Attribute	Description				
Name	ACCINDR				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>C,P</td></tr></tbody></table>	Restrictions	Description	enumeration	C,P
Restrictions	Description				
enumeration	C,P				

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

CHECKER

Attribute	Description				
Name	CHECKER				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

CHECKERSTAMP

Attribute	Description				
Name	CHECKERSTAMP				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

2.3.3.II-AuthorizeIISweep-Res-Full-MSG.xsd

AUTHORIZEIISWEEP_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Itms-Account-Full

ACCBRN
ACCNT
ACCINDR
EFFECTIVE_DATE
PARENT_ACC_BRN
ACC_NO
SCHEME_1
SWPTYPE
BASE_AMT
REALLOC_REQD
BOOK_ACC_BRN
ACCOPT
EXCHGRRTYP
SPREAD_IND
ACCGLCCY
PARENT_ACC_CCY
BOOK_ACC_CCY
MULTIPLE_AMT
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZEISWEEP_FSFS_RES

Attribute	Description
Name	AUTHORIZEISWEEP_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0

PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0
	maxOccurs		unbounded

NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

FCUBS_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description			

Itms-Account-Full

Attribute		Description	
Name		Itms-Account-Full	
Datatype			
Description			

ACCBRN

Attribute		Description	
Name		ACCBRN	
Datatype		String	
Description			
Restrictions	Restrictions		Description
	maxLength		3

ACCNT

Attribute	Description	
Name	ACCNT	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

ACCINDR

Attribute	Description	
Name	ACCINDR	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	C,P

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		

PARENT_ACC_BRN

Attribute	Description	
Name	PARENT_ACC_BRN	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

ACC_NO

Attribute	Description	
Name	ACC_NO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	20

SCHEME_1

Attribute	Description	
Name	SCHEME_1	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	S

SWPTYPE

Attribute	Description	
Name	SWPTYPE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,C,T

BASE_AMT

Attribute	Description	
Name	BASE_AMT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22
	minInclusive	0

REALLOC_REQD

Attribute	Description	
Name	REALLOC_REQD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

BOOK_ACC_BRN

Attribute		Description	
Name	BOOK_ACC_BRN		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	3	

ACCOPT

Attribute		Description	
Name	ACCOPT		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	20	

EXCHGRTTYP

Attribute		Description	
Name	EXCHGRTTYP		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	8	

SPREAD_IND

Attribute		Description	
Name	SPREAD_IND		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	enumeration	M,B	

ACGLCCY

Attribute	Description	
Name	ACCGLCCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

PARENT_ACC_CCY

Attribute	Description	
Name	PARENT_ACC_CCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

BOOK_ACC_CCY

Attribute	Description	
Name	BOOK_ACC_CCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

MULTIPLE_AMT

Attribute	Description	
Name	MULTIPLE_AMT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	

Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute		Description	
Name	FCUBS_WARNING_RESP		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

WARNING

Attribute		Description	
Name	WARNING		
Datatype			
Description			
Attribute	Attribute		Description
	maxOccurs	unbounded	

WCODE

Attribute		Description	
Name	WCODE		
Datatype	String		
Description			

WDESC

Attribute		Description	
Name	WDESC		
Datatype	String		
Description			

2.3.4.II-AuthorizeIISweep-Res-PK-MSG.xsd

AUTHORIZEIISWEEP_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION
MULTIRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Ilms-Account-PK
ACCBRN
ACCNT
ACCINDR
EFFECTIVE_DATE
Ilms-Account-IO
ACCBRN
ACCNT
ACCINDR
EFFECTIVE_DATE
CHECKER
CHECKERSTAMP
MODNO
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

AUTHORIZEISWEEP_IOPK_RES

Attribute	Description
Name	AUTHORIZEISWEEP_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute		Description	
Name	SOURCE_USERID		
Datatype	String		
Description	This is the user id in the Source system who is performing the action.		
Attribute	Attribute		Description
	minOccurs	0	

DESTINATION

Attribute		Description	
Name	DESTINATION		
Datatype	String		
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

MULTITRIPID

Attribute		Description	
Name	MULTITRIPID		
Datatype	String		
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

FUNCTIONID

Attribute		Description	
Name	FUNCTIONID		
Datatype	String		
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.		
Attribute	Attribute		Description
	minOccurs	0	

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Itms-Account-PK

Attribute	Description
Name	Itms-Account-PK
Datatype	
Description	

ACCBRN

Attribute	Description				
Name	ACCBRN				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

ACCNT

Attribute	Description
-----------	-------------

Name	ACCNT	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

ACCINDR

Attribute	Description	
Name	ACCINDR	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	1

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		

Itms-Account-IO

Attribute	Description	
Name	Itms-Account-IO	
Datatype		
Description		

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

ACCNT

Attribute	Description	
Name	ACCNT	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

ACCINDR

Attribute	Description	
Name	ACCINDR	
Datatype	String	

Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>C,P</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	C,P
Restrictions	Description				
enumeration	C,P				

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

CHECKER

Attribute	Description				
Name	CHECKER				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

CHECKERSTAMP

Attribute	Description				
Name	CHECKERSTAMP				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

MODNO

Attribute	Description				
Name	MODNO				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>4</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	4
Restrictions	Description				
totalDigits	4				

FCUBS_ERROR_RESP

Attribute	Description
-----------	-------------

Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	
	Description	
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	
	Description	
	maxOccurs	unbounded

WCODE

Attribute	Description
------------------	--------------------

Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.4.ClosellGroup

2.4.1.II-CloseIIGroup-Req-Full-MSG.xsd

CLOSEIIGROUP_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Iltms-Group-Code-Full

GRPCD
ACGLDESC
POOL_BENEFIT
SWEEP_BASIS
EFFECTIVE_DATE
INTRADAY_SWEEP_REQD
BVT_INDICATOR
BVT_UNIT
BVT_DURATION
REV_SWEEP_REQD
ACCBRN
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
UDFDETAILS
FLDNAM
FLDVAL

CLOSEIIGROUP_FSFS_REQ

Attribute	Description
Name	CLOSEIIGROUP_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within EL EXCLUDE UBS. In

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nullable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
pattern	[A-Z_0-9]*	

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Itms-Group-Code-Full

Attribute	Description
Name	Itms-Group-Code-Full
Datatype	
Description	

GRPCD

Attribute	Description				
Name	GRPCD				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

ACCGLDESC

Attribute	Description				
Name	ACCGLDESC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

POOL_BENEFIT

Attribute	Description
Name	POOL_BENEFIT
Datatype	String
Description	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

SWEEP_BASIS

Attribute	Description	
Name	SWEEP_BASIS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	B,V

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

INTRADAY_SWEEP_REQD

Attribute	Description	
Name	INTRADAY_SWEEP_REQD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

BVT_INDICATOR

Attribute	Description	
Name	BVT_INDICATOR	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	enumeration	Y,N

BVT_UNIT

Attribute	Description	
Name	BVT_UNIT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	M,D

BVT_DURATION

Attribute	Description	
Name	BVT_DURATION	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

REV_SWEEP_REQD

Attribute	Description	
Name	REV_SWEEP_REQD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM

Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.4.2.II-CloseIIGroup-Req-IO-MSG.xsd

CLOSEIIGROUP_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Itms-Group-Code-IO

GRPCD

MAKER

MAKERSTAMP

MODNO

CLOSEIIGROUP_IOPK_REQ

Attribute	Description
Name	CLOSEIIGROUP_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Itms-Group-Code-IO

Attribute		Description
------------------	--	--------------------

Name	Illms-Group-Code-IO
Datatype	
Description	

GRPCD

Attribute	Description	
Name	GRPCD	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	9

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

CLOSEIIGROUP_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Iltns-Group-Code-Full

GRPCD

ACCGLDESC

POOL_BENEFIT

SWEEP_BASIS

EFFECTIVE_DATE

INTRADAY_SWEEP_REQD

BVT_INDICATOR

BVT_UNIT

BVT_DURATION

REV_SWEEP_REQD

ACCBRN

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CLOSEIIGROUP_FSFS_RES

Attribute	Description
Name	CLOSEIIGROUP_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Itms-Group-Code-Full

Attribute	Description
Name	Itms-Group-Code-Full
Datatype	
Description	

GRPCD

Attribute	Description				
Name	GRPCD				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

ACCGLDESC

Attribute	Description				
Name	ACCGLDESC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

POOL_BENEFIT

Attribute	Description
Name	POOL_BENEFIT
Datatype	String
Description	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

SWEEP_BASIS

Attribute	Description	
Name	SWEEP_BASIS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	B,V

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

INTRADAY_SWEEP_REQD

Attribute	Description	
Name	INTRADAY_SWEEP_REQD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

BVT_INDICATOR

Attribute	Description	
Name	BVT_INDICATOR	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	enumeration	Y,N

BVT_UNIT

Attribute	Description	
Name	BVT_UNIT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	M,D

BVT_DURATION

Attribute	Description	
Name	BVT_DURATION	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

REV_SWEEP_REQD

Attribute	Description	
Name	REV_SWEEP_REQD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM

Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.4.4.II-CloseIIGroup-Res-PK-MSG.xsd

CLOSEIIGROUP_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Itms-Group-Code-PK

GRPCD

Itms-Group-Code-IO

GRPCD

MAKER

MAKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CLOSEIIGROUP_IOPK_RES

Attribute	Description
Name	CLOSEIIGROUP_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Itms-Group-Code-PK

Attribute	Description
Name	Itms-Group-Code-PK
Datatype	
Description	

GRPCD

Attribute	Description				
Name	GRPCD				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

Itms-Group-Code-IO

Attribute	Description
Name	Itms-Group-Code-IO
Datatype	
Description	

GRPCD

Attribute	Description				
Name	GRPCD				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

MAKER

Attribute	Description
-----------	-------------

Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		

Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.5.CloseIGrplink

2.5.1.II-CloseIGrplink-Req-Full-MSG.xsd

[CLOSEIIGRPLINK_FSFS_REQ](#)

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Iltms-Account-Group-Link-Full

ACCBRN

HEADER_ACC

EFFECTIVE_DATE

GROUP_CODE

CCY3

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

CLOSEIIGRPLINK_FSFS_REQ

Attribute	Description
Name	CLOSEIIGRPLINK_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
-----------	-------------

Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
pattern	[a-zA-Z_0-9]*	

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	

Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Itms-Account-Group-Link-Full

Attribute	Description	
Name	Itms-Account-Group-Link-Full	
Datatype		
Description		

ACCBRN

Attribute	Description	
------------------	--------------------	--

Name	ACCBRN	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

HEADER_ACC

Attribute	Description	
Name	HEADER_ACC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		

GROUP_CODE

Attribute	Description	
Name	GROUP_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

CCY3

Attribute	Description	
Name	CCY3	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	4

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	

Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

2.5.2.II-CloseIIGrplink-Req-IO-MSG.xsd

CLOSEIIGRPLINK_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM
NAME
VALUE
FCUBS_BODY
Iltns-Account-Group-Link-IO
ACCBRN
HEADER_ACC
EFFECTIVE_DATE
GROUP_CODE
MAKER
MAKERSTAMP
MODNO

CLOSEIIGRPLINK_IOPK_REQ

Attribute	Description
Name	CLOSEIIGRPLINK_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Itms-Account-Group-Link-IO

Attribute		Description
------------------	--	--------------------

Name	Illms-Account-Group-Link-IO
Datatype	
Description	

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

HEADER_ACC

Attribute	Description	
Name	HEADER_ACC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		

GROUP_CODE

Attribute	Description	
Name	GROUP_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

2.5.3.II-CloseIIGrplink-Res-Full-MSG.xsd

CLOSEIIGRPLINK_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Iltns-Account-Group-Link-Full

ACCBRN

HEADER_ACC

EFFECTIVE_DATE

GROUP_CODE

CCY3

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

Attribute	Description
Name	CLOSEIIGRPLINK_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	

Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Itms-Account-Group-Link-Full

Attribute	Description	
Name	Itms-Account-Group-Link-Full	
Datatype		
Description		

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

HEADER_ACC

Attribute	Description	
Name	HEADER_ACC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

GROUP_CODE

Attribute	Description				
Name	GROUP_CODE				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

CCY3

Attribute	Description				
Name	CCY3				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>4</td></tr></tbody></table>	Restrictions	Description	maxLength	4
Restrictions	Description				
maxLength	4				

MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MAKERSTAMP

Attribute	Description				
Name	MAKERSTAMP				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

Attribute		Description	
Name	FCUBS_ERROR_RESP		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

ERROR

Attribute		Description	
Name	ERROR		
Datatype			
Description			
Attribute	Attribute		Description
	maxOccurs	unbounded	

ECODE

Attribute		Description	
Name	ECODE		
Datatype	String		
Description			

EDESC

Attribute		Description	
Name	EDESC		
Datatype	String		
Description			

FCUBS_WARNING_RESP

Attribute		Description	
Name	FCUBS_WARNING_RESP		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

WARNING

Attribute		Description	
Name	WARNING		
Datatype			
Description			
Attribute	Attribute		Description
	maxOccurs	unbounded	

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.5.4.II-CloseIIGrplink-Res-PK-MSG.xsd

CLOSEIIGRPLINK_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Itms-Account-Group-Link-PK

EFFECTIVE_DATE

GROUP_CODE

ACCBRN

HEADER_ACC

Iltns-Account-Group-Link-IO

ACCBRN

HEADER_ACC

EFFECTIVE_DATE

GROUP_CODE

MAKER

MAKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CLOSEIIGRPLINK_IOPK_RES

Attribute	Description
Name	CLOSEIIGRPLINK_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Itms-Account-Group-Link-PK

Attribute	Description
Name	Itms-Account-Group-Link-PK
Datatype	
Description	

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

GROUP_CODE

Attribute	Description				
Name	GROUP_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

ACCBRN

Attribute	Description				
Name	ACCBRN				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

HEADER_ACC

Attribute	Description
-----------	-------------

Name	HEADER_ACC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

Itms-Account-Group-Link-IO

Attribute	Description	
Name	Itms-Account-Group-Link-IO	
Datatype		
Description		

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

HEADER_ACC

Attribute	Description	
Name	HEADER_ACC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		

GROUP_CODE

Attribute	Description	
Name	GROUP_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		

Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.6.CloseISweep

2.6.1.II-CloseISweep-Req-Full-MSG.xsd

CLOSEIISWEEP_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Itms-Account-Full

ACCBRN

ACCNT

ACCINDR

EFFECTIVE_DATE

PARENT_ACC_BRN

ACC_NO

SCHEME_1

SWPTYPE

BASE_AMT
REALLOC_REQD
BOOK_ACC_BRN
ACCOPT
EXCHGRRTYP
SPREAD_IND
ACCGLCCY
PARENT_ACC_CCY
BOOK_ACC_CCY
MULTIPLE_AMT
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
UDFDETAILS
FLDNAM
FLDVAL

CLOSEIISWEEP_FSFS_REQ

Attribute	Description
Name	CLOSEIISWEEP_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Itms-Account-Full

Attribute	Description
Name	Itms-Account-Full
Datatype	
Description	

ACCBRN

Attribute	Description				
Name	ACCBRN				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

ACCNT

Attribute	Description				
Name	ACCNT				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

ACCINDR

Attribute	Description				
Name	ACCINDR				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>C,P</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	C,P
Restrictions	Description				
enumeration	C,P				

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

PARENT_ACC_BRN

Attribute	Description				
Name	PARENT_ACC_BRN				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

ACC_NO

Attribute	Description				
Name	ACC_NO				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

SCHEME_1

Attribute	Description				
Name	SCHEME_1				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>S</td></tr></tbody></table>	Restrictions	Description	enumeration	S
Restrictions	Description				
enumeration	S				

SWPTYPE

Attribute	Description
Name	SWPTYPE
Datatype	String
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,C,T

BASE_AMT

Attribute	Description	
Name	BASE_AMT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22
	minInclusive	0

REALLOC_REQD

Attribute	Description	
Name	REALLOC_REQD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

BOOK_ACC_BRN

Attribute	Description	
Name	BOOK_ACC_BRN	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

ACCOPT

Attribute	Description	
Name	ACCOPT	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

EXCHGRTTYP

Attribute	Description	
Name	EXCHGRTTYP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8

SPREAD_IND

Attribute	Description	
Name	SPREAD_IND	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	M,B

ACCGLCCY

Attribute	Description	
Name	ACCGLCCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

PARENT_ACC_CCY

Attribute	Description	
Name	PARENT_ACC_CCY	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

BOOK_ACC_CCY

Attribute	Description	
Name	BOOK_ACC_CCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

MULTIPLE_AMT

Attribute	Description	
Name	MULTIPLE_AMT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

2.6.2.II-CloseIISweep-Req-IO-MSG.xsd

CLOSEIISWEEP_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Itms-Account-IO

ACCBRN

ACCNT

ACCINDR

EFFECTIVE_DATE

MAKER

MAKERSTAMP

MODNO

CLOSEIISWEEP_IOPK_REQ

Attribute	Description
Name	CLOSEIISWEEP_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0

PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0
	maxOccurs		unbounded

NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

FCUBS_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description			

Itms-Account-IO

Attribute		Description	
Name		Itms-Account-IO	
Datatype			
Description			

ACCBRN

Attribute		Description	
Name		ACCBRN	
Datatype		String	
Description			
Restrictions	Restrictions		Description
	maxLength		3

ACCNT

Attribute	Description	
Name	ACCNT	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

ACCINDR

Attribute	Description	
Name	ACCINDR	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	C,P

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

2.6.3.II-CloseIISweep-Res-Full-MSG.xsd

CLOSEIISWEEP_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Itms-Account-Full

ACCBRN
ACCNT
ACCINDR
EFFECTIVE_DATE
PARENT_ACC_BRN
ACC_NO
SCHEME_1
SWPTYPE
BASE_AMT
REALLOC_REQD
BOOK_ACC_BRN
ACCOPT
EXCHGRRTYP
SPREAD_IND
ACCGLCCY
PARENT_ACC_CCY
BOOK_ACC_CCY
MULTIPLE_AMT
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CLOSEIISWEEP_FSFS_RES

Attribute	Description
Name	CLOSEIISWEEP_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field. 242

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

ADDL

Attribute		Description	
Name	ADDL		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	

PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

FCUBS_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description			

Itms-Account-Full

Attribute		Description	
Name	Itms-Account-Full		
Datatype			
Description			

ACCBRN

Attribute		Description	
Name	ACCBRN		
Datatype	String		
Description			
Restrictions	Restrictions		Description
	maxLength	3	

ACCNT

Attribute	Description	
Name	ACCNT	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

ACCINDR

Attribute	Description	
Name	ACCINDR	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	C,P

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		

PARENT_ACC_BRN

Attribute	Description	
Name	PARENT_ACC_BRN	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

ACC_NO

Attribute	Description	
Name	ACC_NO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	20

SCHEME_1

Attribute	Description	
Name	SCHEME_1	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	S

SWPTYPE

Attribute	Description	
Name	SWPTYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	D,C,T

BASE_AMT

Attribute	Description	
Name	BASE_AMT	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22
	minInclusive	0

REALLOC_REQD

Attribute	Description	
Name	REALLOC_REQD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

BOOK_ACC_BRN

Attribute	Description	
Name	BOOK_ACC_BRN	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

ACCOPT

Attribute	Description	
Name	ACCOPT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

EXCHGRTTYP

Attribute	Description	
Name	EXCHGRTTYP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8

SPREAD_IND

Attribute	Description	
Name	SPREAD_IND	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	M,B

ACGLCCY

Attribute	Description	
Name	ACCGLCCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

PARENT_ACC_CCY

Attribute	Description	
Name	PARENT_ACC_CCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

BOOK_ACC_CCY

Attribute	Description	
Name	BOOK_ACC_CCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

MULTIPLE_AMT

Attribute	Description	
Name	MULTIPLE_AMT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	

Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute		Description	
Name	FCUBS_WARNING_RESP		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

WARNING

Attribute		Description	
Name	WARNING		
Datatype			
Description			
Attribute	Attribute		Description
	maxOccurs	unbounded	

WCODE

Attribute		Description	
Name	WCODE		
Datatype	String		
Description			

WDESC

Attribute		Description	
Name	WDESC		
Datatype	String		
Description			

2.6.4.II-CloseIISweep-Res-PK-MSG.xsd

CLOSEIISWEEP_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION
MULTIRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Ilms-Account-PK
ACCBRN
ACCNT
ACCINDR
EFFECTIVE_DATE
Ilms-Account-IO
ACCBRN
ACCNT
ACCINDR
EFFECTIVE_DATE
MAKER
MAKERSTAMP
MODNO
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

CLOSEIISWEEP_IOPK_RES

Attribute	Description
Name	CLOSEIISWEEP_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute		Description	
Name	SOURCE_USERID		
Datatype	String		
Description	This is the user id in the Source system who is performing the action.		
Attribute	Attribute		Description
	minOccurs	0	

DESTINATION

Attribute		Description	
Name	DESTINATION		
Datatype	String		
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

MULTITRIPID

Attribute		Description	
Name	MULTITRIPID		
Datatype	String		
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

FUNCTIONID

Attribute		Description	
Name	FUNCTIONID		
Datatype	String		
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.		
Attribute	Attribute		Description
	minOccurs	0	

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Itms-Account-PK

Attribute	Description
Name	Itms-Account-PK
Datatype	
Description	

ACCBRN

Attribute	Description				
Name	ACCBRN				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

ACCNT

Attribute	Description
-----------	-------------

Name	ACCNT	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

ACCINDR

Attribute	Description	
Name	ACCINDR	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	1

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		

Itms-Account-IO

Attribute	Description	
Name	Itms-Account-IO	
Datatype		
Description		

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

ACCNT

Attribute	Description	
Name	ACCNT	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

ACCINDR

Attribute	Description	
Name	ACCINDR	
Datatype	String	

Description					
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>enumeration</td> <td>C,P</td> </tr> </table>	Restrictions	Description	enumeration	C,P
Restrictions	Description				
enumeration	C,P				

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attribute	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>maxLength</td> <td>12</td> </tr> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MAKERSTAMP

Attribute	Description				
Name	MAKERSTAMP				
Datatype	String				
Description					
Attribute	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>maxLength</td> <td>35</td> </tr> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

MODNO

Attribute	Description				
Name	MODNO				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>totalDigits</td> <td>4</td> </tr> </table>	Restrictions	Description	totalDigits	4
Restrictions	Description				
totalDigits	4				

FCUBS_ERROR_RESP

Attribute	Description
-----------	-------------

Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	
	Description	
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	
	Description	
	maxOccurs	unbounded

WCODE

Attribute	Description
------------------	--------------------

Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.7.CreateIIGroup

2.7.1.II-CreateIIGroup-Req-Full-MSG.xsd

CREATEIIGROUP_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Iltms-Group-Code-Full

GRPCD
ACCGLDESC
POOL_BENEFIT
SWEEP_BASIS
EFFECTIVE_DATE
INTRADAY_SWEEP_REQD
BVT_INDICATOR
BVT_UNIT
BVT_DURATION
REV_SWEEP_REQD
ACCBRN
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
UDFDETAILS
FLDNAM
FLDVAL

CREATEIIGROUP_FSFS_REQ

Attribute	Description
Name	CREATEIIGROUP_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within EL EXCLUDE UBS. In

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Itms-Group-Code-Full

Attribute	Description
Name	Itms-Group-Code-Full
Datatype	
Description	

GRPCD

Attribute	Description				
Name	GRPCD				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

ACCGLDESC

Attribute	Description				
Name	ACCGLDESC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

POOL_BENEFIT

Attribute	Description
Name	POOL_BENEFIT
Datatype	String
Description	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

SWEEP_BASIS

Attribute	Description	
Name	SWEEP_BASIS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	B,V

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

INTRADAY_SWEEP_REQD

Attribute	Description	
Name	INTRADAY_SWEEP_REQD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

BVT_INDICATOR

Attribute	Description	
Name	BVT_INDICATOR	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	enumeration	Y,N

BVT_UNIT

Attribute	Description	
Name	BVT_UNIT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	M,D

BVT_DURATION

Attribute	Description	
Name	BVT_DURATION	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

REV_SWEEP_REQD

Attribute	Description	
Name	REV_SWEEP_REQD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM

Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.7.2.II-CreateIIGroup-Req-IO-MSG.xsd

CREATEIIGROUP_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Itms-Group-Code-IO

GRPCD

ACCGLDESC

POOL_BENEFIT

SWEEP_BASIS

EFFECTIVE_DATE

INTRADAY_SWEEP_REQD

BVT_INDICATOR

BVT_UNIT

BVT_DURATION

REV_SWEEP_REQD

ACCBRN

UDFDETAILS

FLDNAM

FLDVAL

CREATEIIGROUP_IOPK_REQ

Attribute	Description
Name	CREATEIIGROUP_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Itms-Group-Code-IO

Attribute	Description
Name	Itms-Group-Code-IO
Datatype	
Description	

GRPCD

Attribute	Description				
Name	GRPCD				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

ACCGLDESC

Attribute	Description				
Name	ACCGLDESC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

POOL_BENEFIT

Attribute	Description
Name	POOL_BENEFIT
Datatype	String
Description	

Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	enumeration	Y,N
	Description	

SWEEP_BASIS

Attribute		Description
Name	SWEEP_BASIS	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	enumeration	B,V
	Description	

EFFECTIVE_DATE

Attribute		Description
Name	EFFECTIVE_DATE	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	enumeration	Y,N
	Description	

INTRADAY_SWEEP_REQD

Attribute		Description
Name	INTRADAY_SWEEP_REQD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	enumeration	Y,N
	Description	

BVT_INDICATOR

Attribute		Description
Name	BVT_INDICATOR	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	enumeration	Y,N
	Description	

Restrictions		
	Restrictions	Description
	enumeration	Y,N

BVT_UNIT

Attribute	Description	
Name	BVT_UNIT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	M,D

BVT_DURATION

Attribute	Description	
Name	BVT_DURATION	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

REV_SWEEP_REQD

Attribute	Description	
Name	REV_SWEEP_REQD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

UDFDETAILS

Attribute	Description						
Name	UDFDETAILS						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

FLDNAM

Attribute	Description						
Name	FLDNAM						
Datatype	String						
Description	Indicates Field Name						
Restrictions							
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	105	minLength	1
Restrictions	Description						
maxLength	105						
minLength	1						

FLDVAL

Attribute	Description						
Name	FLDVAL						
Datatype	String						
Description	Indicates Field Value						
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions							
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></tbody></table>	Restrictions	Description	maxLength	150	minLength	0
Restrictions	Description						
maxLength	150						
minLength	0						

2.7.3.II-CreateIIGroup-Res-Full-MSG.xsd

CREATEIIGROUP_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTIRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Itms-Group-Code-Full
GRPCD
ACCGLDESC
POOL_BENEFIT
SWEEP_BASIS
EFFECTIVE_DATE
INTRADAY_SWEEP_REQD
BVT_INDICATOR
BVT_UNIT
BVT_DURATION
REV_SWEEP_REQD
ACCBRN
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATEIIGROUP_FSFS_RES

Attribute	Description
Name	CREATEIIGROUP_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Itms-Group-Code-Full

Attribute	Description	
------------------	--------------------	--

Name	Illms-Group-Code-Full
Datatype	
Description	

GRPCD

Attribute	Description	
Name	GRPCD	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	9

ACCGLDESC

Attribute	Description	
Name	ACCGLDESC	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

POOL_BENEFIT

Attribute	Description	
Name	POOL_BENEFIT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

SWEEP_BASIS

Attribute	Description	
Name	SWEEP_BASIS	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	B,V

EFFECTIVE_DATE

Attribute		Description	
Name	EFFECTIVE_DATE		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	

INTRADAY_SWEEP_REQD

Attribute		Description	
Name	INTRADAY_SWEEP_REQD		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	enumeration	Y,N	

BVT_INDICATOR

Attribute		Description	
Name	BVT_INDICATOR		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	enumeration	Y,N	

BVT_UNIT

Attribute		Description	
Name	BVT_UNIT		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	enumeration	M,D	

BVT_DURATION

Attribute		Description	
Name	BVT_DURATION		
Datatype	Decimal		

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

REV_SWEEP_REQD

Attribute	Description	
Name	REV_SWEEP_REQD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	3

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		

Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.7.4.II-CreateIIGroup-Res-PK-MSG.xsd

CREATEIIGROUP_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME
VALUE
FCUBS_BODY
Itms-Group-Code-PK
GRPCD
Itms-Group-Code-IO
GRPCD
ACCGLDESC
POOL_BENEFIT
SWEEP_BASIS
EFFECTIVE_DATE
INTRADAY_SWEEP_REQD
BVT_INDICATOR
BVT_UNIT
BVT_DURATION
REV_SWEEP_REQD
ACCBRN
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

CREATEIIGROUP_IOPK_RES

Attribute	Description
Name	CREATEIIGROUP_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Itms-Group-Code-PK

Attribute	Description
Name	Itms-Group-Code-PK
Datatype	
Description	

GRPCD

Attribute	Description	
Name	GRPCD	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	9

Itms-Group-Code-IO

Attribute	Description
Name	Itms-Group-Code-IO
Datatype	
Description	

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	

Restrictions		
	Restrictions	Description
	maxLength	9

ACCGLDESC

Attribute	Description	
Name	ACCGLDESC	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

POOL_BENEFIT

Attribute	Description	
Name	POOL_BENEFIT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

SWEEP_BASIS

Attribute	Description	
Name	SWEEP_BASIS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	B,V

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

INTRADAY_SWEEP_REQD

Attribute	Description				
Name	INTRADAY_SWEEP_REQD				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>Y,N</td></tr></tbody></table>	Restrictions	Description	enumeration	Y,N
	Restrictions	Description			
enumeration	Y,N				

BVT_INDICATOR

Attribute	Description				
Name	BVT_INDICATOR				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>Y,N</td></tr></tbody></table>	Restrictions	Description	enumeration	Y,N
	Restrictions	Description			
enumeration	Y,N				

BVT_UNIT

Attribute	Description				
Name	BVT_UNIT				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>M,D</td></tr></tbody></table>	Restrictions	Description	enumeration	M,D
	Restrictions	Description			
enumeration	M,D				

BVT_DURATION

Attribute	Description				
Name	BVT_DURATION				
Datatype	Decimal				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
	Restrictions	Description			
totalDigits	22				

REV_SWEEP_REQD

Attribute		Description	
Name	REV_SWEEP_REQD		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	enumeration	Y,N	

ACCBRN

Attribute		Description	
Name	ACCBRN		
Datatype	String		
Description			
Restrictions	Restrictions		Description
	maxLength	3	

UDFDETAILS

Attribute		Description	
Name	UDFDETAILS		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

FLDNAM

Attribute		Description	
Name	FLDNAM		
Datatype	String		
Description	Indicates Field Name		
Restrictions	Restrictions		Description
	maxLength	105	
	minLength	1	

FLDVAL

Attribute		Description	
Name	FLDVAL		
Datatype	String		
Description	Indicates Field Value		
Attribute	Attribute		Description
	minOccurs	0	

Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		

Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.8.CreateIIGrplink

2.8.1.II-CreateIIGrplink-Req-Full-MSG.xsd

CREATEIIGRPLINK_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM
NAME
VALUE
FCUBS_BODY
Iltns-Account-Group-Link-Full
ACCBRN
HEADER_ACC
EFFECTIVE_DATE
GROUP_CODE
CCY3
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
UDFDETAILS
FLDNAM
FLDVAL

CREATEIIGRPLINK_FSFS_REQ

Attribute	Description
Name	CREATEIIGRPLINK_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Itms-Account-Group-Link-Full

Attribute	Description
Name	Itms-Account-Group-Link-Full
Datatype	
Description	

ACCBRN

Attribute	Description				
Name	ACCBRN				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

HEADER_ACC

Attribute	Description				
Name	HEADER_ACC				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

GROUP_CODE

Attribute	Description
-----------	-------------

Name	GROUP_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

CCY3

Attribute	Description	
Name	CCY3	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	4

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
Restrictions	Restrictions	Description
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
Restrictions	Restrictions	Description
	minLength	0

2.8.2.II-CreateIIGrplink-Req-IO-MSG.xsd

CREATEIIGRPLINK_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
 NAME
 VALUE
FCUBS_BODY
 Ilms-Account-Group-Link-IO
 ACCBRN
 HEADER_ACC
 EFFECTIVE_DATE
 GROUP_CODE
 UDFDETAILS
 FLDNAM
 FLDVAL

CREATEIIGRPLINK_IOPK_REQ

Attribute	Description
Name	CREATEIIGRPLINK_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
-----------	-------------

Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Itms-Account-Group-Link-IO

Attribute	Description
Name	Itms-Account-Group-Link-IO
Datatype	
Description	

ACCBRN

Attribute	Description				
Name	ACCBRN				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

HEADER_ACC

Attribute	Description				
Name	HEADER_ACC				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

GROUP_CODE

Attribute	Description

Name	GROUP_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.8.3.II-CreateIIGrplink-Res-Full-MSG.xsd

CREATEIIGRPLINK_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Iltns-Account-Group-Link-Full
ACCBRN
HEADER_ACC
EFFECTIVE_DATE
GROUP_CODE
CCY3
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATEIIGRPLINK_FSFS_RES

Attribute	Description
Name	CREATEIIGRPLINK_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Itms-Account-Group-Link-Full

Attribute		Description
------------------	--	--------------------

Name	Ilrms-Account-Group-Link-Full
Datatype	
Description	

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

HEADER_ACC

Attribute	Description	
Name	HEADER_ACC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		

GROUP_CODE

Attribute	Description	
Name	GROUP_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

CCY3

Attribute	Description	
Name	CCY3	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	4

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	

Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute		Description	
Name	FCUBS_WARNING_RESP		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

WARNING

Attribute		Description	
Name	WARNING		
Datatype			
Description			
Attribute	Attribute		Description
	maxOccurs	unbounded	

WCODE

Attribute		Description	
Name	WCODE		
Datatype	String		
Description			

WDESC

Attribute		Description	
Name	WDESC		
Datatype	String		
Description			

2.8.4.II-CreateIIGrplink-Res-PK-MSG.xsd

CREATEIIGRPLINK_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Iltns-Account-Group-Link-PK
EFFECTIVE_DATE
GROUP_CODE
ACCBRN
HEADER_ACC
Iltns-Account-Group-Link-IO
ACCBRN
HEADER_ACC
EFFECTIVE_DATE
GROUP_CODE
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

CREATEIIGRPLINK_IOPK_RES

Attribute	Description
Name	CREATEIIGRPLINK_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute		Description	
Name	SOURCE_USERID		
Datatype	String		
Description	This is the user id in the Source system who is performing the action.		
Attribute	Attribute		Description
	minOccurs	0	

DESTINATION

Attribute		Description	
Name	DESTINATION		
Datatype	String		
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

MULTITRIPID

Attribute		Description	
Name	MULTITRIPID		
Datatype	String		
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

FUNCTIONID

Attribute		Description	
Name	FUNCTIONID		
Datatype	String		
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.		
Attribute	Attribute		Description
	minOccurs	0	

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Itms-Account-Group-Link-PK

Attribute	Description
Name	Itms-Account-Group-Link-PK
Datatype	
Description	

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

GROUP_CODE

Attribute	Description
Name	GROUP_CODE
Datatype	String
Description	

Restrictions		
	Restrictions	Description
	maxLength	9

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

HEADER_ACC

Attribute	Description	
Name	HEADER_ACC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

Itms-Account-Group-Link-IO

Attribute	Description	
Name	Itms-Account-Group-Link-IO	
Datatype		
Description		

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

HEADER_ACC

Attribute	Description	
Name	HEADER_ACC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	

Datatype	String
Description	

GROUP_CODE

Attribute	Description	
Name	GROUP_CODE	
Datatype	String	
Description		
Restrictions	Restrictions	
	maxLength	9
	Description	

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	
	maxLength	105
	minLength	1
	Description	

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	150
	minLength	0
	Description	

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		

Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.9.CreateIISweep

2.9.1.II-CreateIISweep-Req-Full-MSG.xsd

CREATEIISWEEP_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Itms-Account-Full

ACCBRN

ACCNT

ACCINDR
EFFECTIVE_DATE
PARENT_ACC_BRN
ACC_NO
SCHEME_1
SWPTYPE
BASE_AMT
REALLOC_REQD
BOOK_ACC_BRN
ACCOPT
EXCHGRRTYP
SPREAD_IND
ACGLCCY
PARENT_ACC_CCY
BOOK_ACC_CCY
MULTIPLE_AMT
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
UDFDETAILS
FLDNAM
FLDVAL

CREATEIISWEEP_FSFS_REQ

Attribute	Description
Name	CREATEIISWEEP_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
------------------	--------------------

Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Itms-Account-Full

Attribute	Description
Name	Itms-Account-Full
Datatype	
Description	

ACCBRN

Attribute	Description				
Name	ACCBRN				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

ACCNT

Attribute	Description				
Name	ACCNT				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

ACCINDR

Attribute	Description				
Name	ACCINDR				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>C,P</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	C,P
Restrictions	Description				
enumeration	C,P				

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

PARENT_ACC_BRN

Attribute	Description				
Name	PARENT_ACC_BRN				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

ACC_NO

Attribute	Description				
Name	ACC_NO				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

SCHEME_1

Attribute	Description				
Name	SCHEME_1				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>S</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	S
Restrictions	Description				
enumeration	S				

SWPTYPE

Attribute	Description
Name	SWPTYPE
Datatype	String
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,C,T

BASE_AMT

Attribute	Description	
Name	BASE_AMT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22
	minInclusive	0

REALLOC_REQD

Attribute	Description	
Name	REALLOC_REQD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

BOOK_ACC_BRN

Attribute	Description	
Name	BOOK_ACC_BRN	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

ACCOPT

Attribute	Description	
Name	ACCOPT	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

EXCHGRTTYP

Attribute	Description	
Name	EXCHGRTTYP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8

SPREAD_IND

Attribute	Description	
Name	SPREAD_IND	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	M,B

ACCGLCCY

Attribute	Description	
Name	ACCGLCCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

PARENT_ACC_CCY

Attribute	Description	
Name	PARENT_ACC_CCY	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

BOOK_ACC_CCY

Attribute	Description	
Name	BOOK_ACC_CCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

MULTIPLE_AMT

Attribute	Description	
Name	MULTIPLE_AMT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

2.9.2.II-CreateIISweep-Req-IO-MSG.xsd

CREATEIISWEEP_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Itms-Account-IO

ACCBRN

ACCNT

ACCINDR

EFFECTIVE_DATE

PARENT_ACC_BRN

ACC_NO

SWPTYPE

BASE_AMT

REALLOC_REQD

BOOK_ACC_BRN

ACCOPT

EXCHGRRTYP

SPREAD_IND

MULTIPLE_AMT

UDFDETAILS

FLDNAM

FLDVAL

CREATEIISWEEP_IOPK_REQ

Attribute	Description
Name	CREATEIISWEEP_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description					
Name	SOURCE_OPERATION					
Datatype	String					
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

SOURCE_USERID

Attribute	Description					
Name	SOURCE_USERID					
Datatype	String					
Description	This is the user id in the Source system who is performing the action.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

DESTINATION

Attribute	Description					
Name	DESTINATION					
Datatype	String					
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

MULTIRIPID

Attribute	Description					
Name	MULTIRIPID					
Datatype	String					
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Itms-Account-IO

Attribute		Description
------------------	--	--------------------

Name	Illms-Account-IO
Datatype	
Description	

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

ACCNT

Attribute	Description	
Name	ACCNT	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

ACCINDR

Attribute	Description	
Name	ACCINDR	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	C,P

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		

PARENT_ACC_BRN

Attribute	Description	
Name	PARENT_ACC_BRN	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

ACC_NO

Attribute	Description	
Name	ACC_NO	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

SWPTYPE

Attribute	Description	
Name	SWPTYPE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,C,T

BASE_AMT

Attribute	Description	
Name	BASE_AMT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22
	minInclusive	0

REALLOC_REQD

Attribute	Description	
Name	REALLOC_REQD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

BOOK_ACC_BRN

Attribute		Description	
Name	BOOK_ACC_BRN		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	3	

ACCOPT

Attribute		Description	
Name	ACCOPT		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	20	

EXCHGRTTYP

Attribute		Description	
Name	EXCHGRTTYP		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	8	

SPREAD_IND

Attribute		Description	
Name	SPREAD_IND		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	enumeration	M,B	

MULTIPLE_AMT

Attribute	Description	
Name	MULTIPLE_AMT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

2.9.3.II-CreateIISweep-Res-Full-MSG.xsd

CREATEIISWEEP_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Iltns-Account-Full
ACCBRN
ACCNT
ACCINDR
EFFECTIVE_DATE
PARENT_ACC_BRN
ACC_NO
SCHEME_1
SWPTYPE
BASE_AMT
REALLOC_REQD
BOOK_ACC_BRN

ACCOPT

EXCHGRRTYP

SPREAD_IND

ACCGLCCY

PARENT_ACC_CCY

BOOK_ACC_CCY

MULTIPLE_AMT

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATEIISWEEP_FSFS_RES

Attribute	Description
Name	CREATEIISWEEP_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	
-------------	--

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Itms-Account-Full

Attribute	Description
Name	Itms-Account-Full
Datatype	
Description	

ACCBRN

Attribute	Description				
Name	ACCBRN				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

ACCNT

Attribute	Description				
Name	ACCNT				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

ACCINDR

Attribute	Description				
Name	ACCINDR				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>C,P</td></tr></tbody></table>	Restrictions	Description	enumeration	C,P
Restrictions	Description				
enumeration	C,P				

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

PARENT_ACC_BRN

Attribute	Description				
Name	PARENT_ACC_BRN				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

ACC_NO

Attribute	Description				
Name	ACC_NO				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
	Restrictions	Description			
maxLength	20				

SCHEME_1

Attribute	Description				
Name	SCHEME_1				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>S</td></tr></tbody></table>	Restrictions	Description	enumeration	S
	Restrictions	Description			
enumeration	S				

SWPTYPE

Attribute	Description
Name	SWPTYPE
Datatype	String
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,C,T

BASE_AMT

Attribute	Description	
Name	BASE_AMT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22
	minInclusive	0

REALLOC_REQD

Attribute	Description	
Name	REALLOC_REQD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

BOOK_ACC_BRN

Attribute	Description	
Name	BOOK_ACC_BRN	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

ACCOPT

Attribute	Description	
Name	ACCOPT	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

EXCHGRTTYP

Attribute	Description	
Name	EXCHGRTTYP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8

SPREAD_IND

Attribute	Description	
Name	SPREAD_IND	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	M,B

ACCGLCCY

Attribute	Description	
Name	ACCGLCCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

PARENT_ACC_CCY

Attribute	Description	
Name	PARENT_ACC_CCY	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

BOOK_ACC_CCY

Attribute	Description	
Name	BOOK_ACC_CCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

MULTIPLE_AMT

Attribute	Description	
Name	MULTIPLE_AMT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		

Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.9.4.II-CreateIISweep-Res-PK-MSG.xsd

CREATEIISWEEP_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME
VALUE
FCUBS_BODY
Ilms-Account-PK
ACCBRN
ACCNT
ACCINDR
EFFECTIVE_DATE
Ilms-Account-IO
ACCBRN
ACCNT
ACCINDR
EFFECTIVE_DATE
PARENT_ACC_BRN
ACC_NO
SWPTYPE
BASE_AMT
REALLOC_REQD
BOOK_ACC_BRN
ACCOPT
EXCHGRRTYP
SPREAD_IND
MULTIPLE_AMT
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING

WCODE

WDESC

CREATEIISWEEP_IOPK_RES

Attribute	Description
Name	CREATEIISWEEP_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0

PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0
	maxOccurs		unbounded

NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

FCUBS_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description			

Itms-Account-PK

Attribute		Description	
Name		Itms-Account-PK	
Datatype			
Description			

ACCBRN

Attribute		Description	
Name		ACCBRN	
Datatype		String	
Description			
Restrictions	Restrictions		Description
	maxLength		3

ACCNT

Attribute	Description				
Name	ACCNT				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

ACCINDR

Attribute	Description				
Name	ACCINDR				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

Itms-Account-IO

Attribute	Description
Name	Itms-Account-IO
Datatype	
Description	

ACCBRN

Attribute	Description				
Name	ACCBRN				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

ACCNT

Attribute	Description				
Name	ACCNT				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

ACCINDR

Attribute	Description
-----------	-------------

Name	ACCINDR	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	C,P

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		

PARENT_ACC_BRN

Attribute	Description	
Name	PARENT_ACC_BRN	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

ACC_NO

Attribute	Description	
Name	ACC_NO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	20

SWPTYPE

Attribute	Description	
Name	SWPTYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	D,C,T

BASE_AMT

Attribute		Description	
Name	BASE_AMT		
Datatype	Decimal		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	totalDigits	22	
	minInclusive	0	

REALLOC_REQD

Attribute		Description	
Name	REALLOC_REQD		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	enumeration	Y,N	

BOOK_ACC_BRN

Attribute		Description	
Name	BOOK_ACC_BRN		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	3	

ACCOPT

Attribute		Description	
Name	ACCOPT		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	20	

EXCHGRTTYP

Attribute		Description	
Name	EXCHGRTTYP		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	8	

SPREAD_IND

Attribute		Description	
Name	SPREAD_IND		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	enumeration	M,B	

MULTIPLE_AMT

Attribute		Description	
Name	MULTIPLE_AMT		
Datatype	Decimal		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	totalDigits	22	

UDFDETAILS

Attribute		Description	
Name	UDFDETAILS		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

FLDNAM

Attribute		Description	
Name	FLDNAM		

Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.10.DeleteIIGroup

2.10.1.II-DeleteIIGroup-Req-Full-MSG.xsd

DELETEIIGROUP_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTIRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Itms-Group-Code-Full
GRPCD
ACCGLDESC
POOL_BENEFIT
SWEEP_BASIS
EFFECTIVE_DATE
INTRADAY_SWEEP_REQD
BVT_INDICATOR
BVT_UNIT
BVT_DURATION
REV_SWEEP_REQD
ACCBRN
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

DELETEIIGROUP_FSFS_REQ

Attribute	Description
Name	DELETEIIGROUP_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*
	Description	

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*
	Description	

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	enumeration	SUCCESS,WARNING,FAILURE
	Description	

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*
	Description	

ADDL

Attribute		Description	
Name	ADDL		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	

PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

FCUBS_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description			

Itms-Group-Code-Full

Attribute		Description	
Name	Itms-Group-Code-Full		
Datatype			
Description			

GRPCD

Attribute		Description	
Name	GRPCD		
Datatype	String		
Description			
Restrictions	Restrictions		Description
	maxLength	9	

ACCGLDESC

Attribute	Description	
Name	ACCGLDESC	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

POOL_BENEFIT

Attribute	Description	
Name	POOL_BENEFIT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

SWEEP_BASIS

Attribute	Description	
Name	SWEEP_BASIS	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	B,V

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

INTRADAY_SWEEP_REQD

Attribute	Description	
Name	INTRADAY_SWEEP_REQD	

Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	enumeration	Y,N
	Description	

BVT_INDICATOR

Attribute	Description	
Name	BVT_INDICATOR	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	enumeration	Y,N
	Description	

BVT_UNIT

Attribute	Description	
Name	BVT_UNIT	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	enumeration	M,D
	Description	

BVT_DURATION

Attribute	Description	
Name	BVT_DURATION	
Datatype	Decimal	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	totalDigits	22
	Description	

REV_SWEEP_REQD

Attribute	Description	
Name	REV_SWEEP_REQD	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

2.10.2.II-DeleteIIGroup-Req-IO-MSG.xsd

DELETEIIGROUP_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Iltns-Group-Code-IO
GRPCD

DELETEIIGROUP_IOPK_REQ

Attribute	Description
Name	DELETEIIGROUP_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
pattern	[A-Z_0-9]*	

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Itms-Group-Code-IO

Attribute	Description
Name	Itms-Group-Code-IO
Datatype	
Description	

GRPCD

Attribute	Description				
Name	GRPCD				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

*2.10.3.II-DeleteIIGroup-Res-Full-MSG.xsd**DELETEIIGROUP_FSFS_RES**FCUBS_HEADER**SOURCE**UBSCOMP**MSGID**CORRELID**USERID**BRANCH**MODULEID**SERVICE**OPERATION*

SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTIRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Itms-Group-Code-Full
GRPCD
ACCGLDESC
POOL_BENEFIT
SWEEP_BASIS
EFFECTIVE_DATE
INTRADAY_SWEEP_REQD
BVT_INDICATOR
BVT_UNIT
BVT_DURATION
REV_SWEEP_REQD
ACCBRN
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETEIIGROUP_FSFS_RES

Attribute	Description
Name	DELETEIIGROUP_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Itms-Group-Code-Full

Attribute		Description
------------------	--	--------------------

Name	Ilrms-Group-Code-Full
Datatype	
Description	

GRPCD

Attribute	Description	
Name	GRPCD	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	9

ACCGLDESC

Attribute	Description	
Name	ACCGLDESC	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

POOL_BENEFIT

Attribute	Description	
Name	POOL_BENEFIT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

SWEEP_BASIS

Attribute	Description	
Name	SWEEP_BASIS	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	B,V

EFFECTIVE_DATE

Attribute		Description	
Name	EFFECTIVE_DATE		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	

INTRADAY_SWEEP_REQD

Attribute		Description	
Name	INTRADAY_SWEEP_REQD		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	enumeration	Y,N	

BVT_INDICATOR

Attribute		Description	
Name	BVT_INDICATOR		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	enumeration	Y,N	

BVT_UNIT

Attribute		Description	
Name	BVT_UNIT		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	enumeration	M,D	

BVT_DURATION

Attribute		Description	
Name	BVT_DURATION		
Datatype	Decimal		

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

REV_SWEEP_REQD

Attribute	Description	
Name	REV_SWEEP_REQD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	3

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.10.4.II-DeleteIIGroup-Res-PK-MSG.xsd

DELETEIIGROUP_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Itms-Group-Code-PK

GRPCD

Itms-Group-Code-IO

GRPCD

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETEIIGROUP_IOPK_RES

Attribute	Description
Name	DELETEIIGROUP_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
-----------	-------------

Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE. ⁴⁴³	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Itms-Group-Code-PK
Datatype	
Description	

GRPCD

Attribute	Description				
Name	GRPCD				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

Itms-Group-Code-IO

Attribute	Description
Name	Itms-Group-Code-IO
Datatype	
Description	

GRPCD

Attribute	Description				
Name	GRPCD				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

FCUBS_ERROR_RESP

Attribute	Description						
Name	FCUBS_ERROR_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

ECODE

Attribute	Description
-----------	-------------

Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.11.DeleteIIGrplink

2.11.1.II-DeleteIIGrplink-Req-Full-MSG.xsd

DELETEIIGRPLINK_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Iltns-Account-Group-Link-Full
ACCBRN
HEADER_ACC
EFFECTIVE_DATE
GROUP_CODE
CCY3
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

DELETEIIGRPLINK_FSFS_REQ

Attribute	Description
Name	DELETEIIGRPLINK_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

ADDL

Attribute		Description	
Name	ADDL		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	

PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

FCUBS_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description			

Itms-Account-Group-Link-Full

Attribute		Description	
Name	Itms-Account-Group-Link-Full		
Datatype			
Description			

ACCBRN

Attribute		Description	
Name	ACCBRN		
Datatype	String		
Description			
Restrictions	Restrictions		Description
	maxLength	3	

HEADER_ACC

Attribute	Description	
Name	HEADER_ACC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		

GROUP_CODE

Attribute	Description	
Name	GROUP_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

CCY3

Attribute	Description	
Name	CCY3	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	4

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	1
	Description	

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	1
	Description	

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	
	maxLength	105
	minLength	1
	Description	

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

2.11.2.II-DeleteIIGrplink-Req-IO-MSG.xsd

DELETEIIGRPLINK_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Itms-Account-Group-Link-IO

ACCBRN

HEADER_ACC

EFFECTIVE_DATE

GROUP_CODE

DELETEIIGRPLINK_IOPK_REQ

Attribute	Description
Name	DELETEIIGRPLINK_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute		Description			
Name		ADDL			
Datatype					
Description					
Attribute					
		Attribute		Description	
		minOccurs		0	

PARAM

Attribute		Description			
Name		PARAM			
Datatype					
Description					
Attribute					
		Attribute		Description	
		minOccurs		0	
		maxOccurs		unbounded	

NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

FCUBS_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description			

Itms-Account-Group-Link-IO

Attribute		Description	
Name		Itms-Account-Group-Link-IO	
Datatype			
Description			

ACCBRN

Attribute		Description			
Name		ACCBRN			
Datatype		String			
Description					
Restrictions					
		Restrictions		Description	
		maxLength		3	

HEADER_ACC

Attribute	Description				
Name	HEADER_ACC				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
	Restrictions	Description			
maxLength	20				

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

GROUP_CODE

Attribute	Description				
Name	GROUP_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
	Restrictions	Description			
maxLength	9				

2.11.3.II-DeleteIIGrplink-Res-Full-MSG.xsd

DELETEIIGRPLINK_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Ilrms-Account-Group-Link-Full

ACCBRN

HEADER_ACC

EFFECTIVE_DATE

GROUP_CODE

CCY3

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETEIIGRPLINK_FSFS_RES

Attribute	Description
Name	DELETEIIGRPLINK_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description	This is the user id in the Source system who is performing the action.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

FUNCTIONID

Attribute	Description				
Name	FUNCTIONID				
Datatype	String				
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Itms-Account-Group-Link-Full

Attribute	Description
Name	Itms-Account-Group-Link-Full
Datatype	
Description	

ACCBRN

Attribute	Description				
Name	ACCBRN				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

HEADER_ACC

Attribute	Description
-----------	-------------

Name	HEADER_ACC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		

GROUP_CODE

Attribute	Description	
Name	GROUP_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

CCY3

Attribute	Description	
Name	CCY3	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	4

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		

Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.11.4.II-DeleteIIGrplink-Res-PK-MSG.xsd

DELETEIIGRPLINK_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Ilrms-Account-Group-Link-PK

EFFECTIVE_DATE

GROUP_CODE

ACCBRN

HEADER_ACC

Ilrms-Account-Group-Link-IO

ACCBRN

HEADER_ACC

EFFECTIVE_DATE

GROUP_CODE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETEIIGRPLINK_IOPK_RES

Attribute	Description
Name	DELETEIIGRPLINK_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within EL EXCLUDE LIBS. In

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
pattern	[A-Z_0-9]*	

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Itms-Account-Group-Link-PK

Attribute	Description
Name	Itms-Account-Group-Link-PK
Datatype	
Description	

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

GROUP_CODE

Attribute	Description				
Name	GROUP_CODE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

ACCBRN

Attribute	Description				
Name	ACCBRN				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

HEADER_ACC

Attribute	Description
-----------	-------------

Name	HEADER_ACC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

Itms-Account-Group-Link-IO

Attribute	Description	
Name	Itms-Account-Group-Link-IO	
Datatype		
Description		

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

HEADER_ACC

Attribute	Description	
Name	HEADER_ACC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		

GROUP_CODE

Attribute	Description	
Name	GROUP_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		

Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String

Description	
-------------	--

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.12.DeleteIISweep

2.12.1.II-DeleteIISweep-Req-Full-MSG.xsd

DELETEIISWEEP_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Itms-Account-Full

ACCBRN

ACCNT
ACCINDR
EFFECTIVE_DATE
PARENT_ACC_BRN
ACC_NO
SCHEME_1
SWPTYPE
BASE_AMT
REALLOC_REQD
BOOK_ACC_BRN
ACCOPT
EXCHGRRTYP
SPREAD_IND
ACGLCCY
PARENT_ACC_CCY
BOOK_ACC_CCY
MULTIPLE_AMT
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
UDFDETAILS
FLDNAM
FLDVAL

DELETEIISWEEP_FSFS_REQ

Attribute	Description
Name	DELETEIISWEEP_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
pattern	[A-Z_0-9]*	

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Itms-Account-Full

Attribute	Description
Name	Itms-Account-Full
Datatype	
Description	

ACCBRN

Attribute	Description				
Name	ACCBRN				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

ACCNT

Attribute	Description				
Name	ACCNT				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

ACCINDR

Attribute	Description				
Name	ACCINDR				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>C,P</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	C,P
Restrictions	Description				
enumeration	C,P				

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

PARENT_ACC_BRN

Attribute	Description				
Name	PARENT_ACC_BRN				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

ACC_NO

Attribute	Description				
Name	ACC_NO				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

SCHEME_1

Attribute	Description				
Name	SCHEME_1				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>S</td></tr></tbody></table>	Restrictions	Description	enumeration	S
Restrictions	Description				
enumeration	S				

SWPTYPE

Attribute	Description
Name	SWPTYPE
Datatype	String
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,C,T

BASE_AMT

Attribute	Description	
Name	BASE_AMT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22
	minInclusive	0

REALLOC_REQD

Attribute	Description	
Name	REALLOC_REQD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

BOOK_ACC_BRN

Attribute	Description	
Name	BOOK_ACC_BRN	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

ACCOPT

Attribute	Description	
Name	ACCOPT	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

EXCHGRTTYP

Attribute	Description	
Name	EXCHGRTTYP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8

SPREAD_IND

Attribute	Description	
Name	SPREAD_IND	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	M,B

ACCGLCCY

Attribute	Description	
Name	ACCGLCCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

PARENT_ACC_CCY

Attribute	Description	
Name	PARENT_ACC_CCY	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

BOOK_ACC_CCY

Attribute	Description	
Name	BOOK_ACC_CCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

MULTIPLE_AMT

Attribute	Description	
Name	MULTIPLE_AMT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.12.2.II-DeleteIISweep-Req-IO-MSG.xsd

DELETEIISWEEP_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Itms-Account-IO

ACCBRN

ACCNT

ACCINDR

DELETEIISWEEP_IOPK_REQ

Attribute	Description
Name	DELETEIISWEEP_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute		Description	
Name	SOURCE_USERID		
Datatype	String		
Description	This is the user id in the Source system who is performing the action.		
Attribute	Attribute		Description
	minOccurs	0	

DESTINATION

Attribute		Description	
Name	DESTINATION		
Datatype	String		
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

MULTITRIPID

Attribute		Description	
Name	MULTITRIPID		
Datatype	String		
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

FUNCTIONID

Attribute		Description	
Name	FUNCTIONID		
Datatype	String		
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.		
Attribute	Attribute		Description
	minOccurs	0	

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Itms-Account-IO

Attribute	Description
Name	Itms-Account-IO
Datatype	
Description	

ACCBRN

Attribute	Description				
Name	ACCBRN				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

ACCNT

Attribute	Description
-----------	-------------

Name	ACCNT	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

ACCINDR

Attribute	Description	
Name	ACCINDR	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	C,P

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		

2.12.3.II-DeleteIISweep-Res-Full-MSG.xsd

DELETEIISWEEP_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Itms-Account-Full

ACCBRN

ACCNT

ACCINDR

EFFECTIVE_DATE

PARENT_ACC_BRN

ACC_NO

SCHEME_1

SWPTYPE

BASE_AMT

REALLOC_REQD

BOOK_ACC_BRN

ACCOPT

EXCHGRRTYP

SPREAD_IND

ACCGLCCY

PARENT_ACC_CCY

BOOK_ACC_CCY

MULTIPLE_AMT

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETEIISWEEP_FSFS_RES

Attribute	Description
Name	DELETEIISWEEP_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	Description	

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded
	Description	

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Itms-Account-Full

Attribute		Description
------------------	--	--------------------

Name	Illms-Account-Full
Datatype	
Description	

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

ACCNT

Attribute	Description	
Name	ACCNT	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

ACCINDR

Attribute	Description	
Name	ACCINDR	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	C,P

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		

PARENT_ACC_BRN

Attribute	Description	
Name	PARENT_ACC_BRN	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

ACC_NO

Attribute	Description	
Name	ACC_NO	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

SCHEME_1

Attribute	Description	
Name	SCHEME_1	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	S

SWPTYPE

Attribute	Description	
Name	SWPTYPE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,C,T

BASE_AMT

Attribute	Description	
Name	BASE_AMT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22
	minInclusive	0

REALLOC_REQD

Attribute		Description	
Name	REALLOC_REQD		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	enumeration	Y,N	

BOOK_ACC_BRN

Attribute		Description	
Name	BOOK_ACC_BRN		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	3	

ACCOPT

Attribute		Description	
Name	ACCOPT		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	20	

EXCHGRTTYP

Attribute		Description	
Name	EXCHGRTTYP		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	8	

SPREAD_IND

Attribute	Description	
Name	SPREAD_IND	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	M,B

ACCGLCCY

Attribute	Description	
Name	ACCGLCCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

PARENT_ACC_CCY

Attribute	Description	
Name	PARENT_ACC_CCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

BOOK_ACC_CCY

Attribute	Description	
Name	BOOK_ACC_CCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

MULTIPLE_AMT

Attribute	Description	
Name	MULTIPLE_AMT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

*2.12.4.II-DeleteIISweep-Res-PK-MSG.xsd**DELETEIISWEEP_IOPK_RES**FCUBS_HEADER**SOURCE**UBSCOMP**MSGID*

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Iltns-Account-PK
ACCBRN
ACCNT
ACCINDR
EFFECTIVE_DATE
Iltns-Account-IO
ACCBRN
ACCNT
ACCINDR
EFFECTIVE_DATE
FCUBS_ERROR_RESP
ERROR
ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETEIISWEEP_IOPK_RES

Attribute	Description
Name	DELETEIISWEEP_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0

PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0
	maxOccurs		unbounded

NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

FCUBS_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description			

Itms-Account-PK

Attribute		Description	
Name		Itms-Account-PK	
Datatype			
Description			

ACCBRN

Attribute		Description	
Name		ACCBRN	
Datatype		String	
Description			
Restrictions	Restrictions		Description
	maxLength		3

ACCNT

Attribute	Description				
Name	ACCNT				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

ACCINDR

Attribute	Description				
Name	ACCINDR				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

Itms-Account-IO

Attribute	Description
Name	Itms-Account-IO
Datatype	
Description	

ACCBRN

Attribute	Description				
Name	ACCBRN				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

ACCNT

Attribute	Description				
Name	ACCNT				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

ACCINDR

Attribute	Description
-----------	-------------

Name	ACCINDR	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	C,P

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.13.ModifyIIGroup

2.13.1.II-ModifyIIGroup-Req-Full-MSG.xsd

MODIFYIIGROUP_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Iltns-Group-Code-Full
GRPCD
ACGLDESC
POOL_BENEFIT
SWEEP_BASIS
EFFECTIVE_DATE
INTRADAY_SWEEP_REQD
BVT_INDICATOR
BVT_UNIT
BVT_DURATION
REV_SWEEP_REQD
ACCBRN
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
UDFDETAILS
FLDNAM
FLDVAL

MODIFYIIGROUP_FSFS_REQ

Attribute	Description
Name	MODIFYIIGROUP_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute		Description	
Name	SOURCE_USERID		
Datatype	String		
Description	This is the user id in the Source system who is performing the action.		
Attribute	Attribute		Description
	minOccurs	0	

DESTINATION

Attribute		Description	
Name	DESTINATION		
Datatype	String		
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

MULTITRIPID

Attribute		Description	
Name	MULTITRIPID		
Datatype	String		
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

FUNCTIONID

Attribute		Description	
Name	FUNCTIONID		
Datatype	String		
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.		
Attribute	Attribute		Description
	minOccurs	0	

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Itms-Group-Code-Full

Attribute	Description
Name	Itms-Group-Code-Full
Datatype	
Description	

GRPCD

Attribute	Description				
Name	GRPCD				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

ACCGLDESC

Attribute	Description
------------------	--------------------

Name	ACCGLDESC	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

POOL_BENEFIT

Attribute	Description	
Name	POOL_BENEFIT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

SWEEP_BASIS

Attribute	Description	
Name	SWEEP_BASIS	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	B,V

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

INTRADAY_SWEEP_REQD

Attribute	Description	
Name	INTRADAY_SWEEP_REQD	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

BVT_INDICATOR

Attribute	Description	
Name	BVT_INDICATOR	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

BVT_UNIT

Attribute	Description	
Name	BVT_UNIT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	M,D

BVT_DURATION

Attribute	Description	
Name	BVT_DURATION	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

REV_SWEEP_REQD

Attribute	Description	
Name	REV_SWEEP_REQD	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	3

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.13.2.II-ModifyIIGroup-Req-IO-MSG.xsd

MODIFYIIGROUP_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
 PARAM
 NAME
 VALUE
FCUBS_BODY
 Itms-Group-Code-IO
 GRPCD
 ACCGLDESC
 INTRADAY_SWEEP_REQD
 BVT_INDICATOR
 BVT_UNIT
 BVT_DURATION
 REV_SWEEP_REQD
 MAKER
 MAKERSTAMP
 UDFDETAILS
 FLDNAM
 FLDVAL

MODIFYIIGROUP_IOPK_REQ

Attribute	Description
Name	MODIFYIIGROUP_IOPK_REQ

Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	

Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	

Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

FCUBS_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description			

Itms-Group-Code-IO

Attribute		Description	
Name	Itms-Group-Code-IO		
Datatype			
Description			

GRPCD

Attribute		Description	
Name	GRPCD		
Datatype	String		
Description			
Restrictions	Restrictions		Description
	maxLength	9	

ACCGLDESC

Attribute		Description	
Name	ACCGLDESC		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	

Restrictions		
	Restrictions	Description
	maxLength	35

INTRADAY_SWEEP_REQD

Attribute	Description	
Name	INTRADAY_SWEEP_REQD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

BVT_INDICATOR

Attribute	Description	
Name	BVT_INDICATOR	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

BVT_UNIT

Attribute	Description	
Name	BVT_UNIT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	M,D

BVT_DURATION

Attribute	Description	
Name	BVT_DURATION	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	totalDigits	22

REV_SWEEP_REQD

Attribute	Description	
Name	REV_SWEEP_REQD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.13.3.II-ModifyIIGroup-Res-Full-MSG.xsd

MODIFYIIGROUP_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Iltns-Group-Code-Full
GRPCD
ACCGLDESC
POOL_BENEFIT
SWEEP_BASIS
EFFECTIVE_DATE
INTRADAY_SWEEP_REQD
BVT_INDICATOR
BVT_UNIT
BVT_DURATION
REV_SWEEP_REQD
ACCBRN
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYIIGROUP_FSFS_RES

Attribute	Description
Name	MODIFYIIGROUP_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*
	Description	

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*
	Description	

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	enumeration	SUCCESS,WARNING,FAILURE
	Description	

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*
	Description	

ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute			
		Attribute	Description
		minOccurs	0

PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute			
		Attribute	Description
		minOccurs	0
		maxOccurs	unbounded

NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

FCUBS_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description			

Itms-Group-Code-Full

Attribute		Description	
Name		Itms-Group-Code-Full	
Datatype			
Description			

GRPCD

Attribute		Description	
Name		GRPCD	
Datatype		String	
Description			
Restrictions			
		Restrictions	Description
		maxLength	9

ACCGLDESC

Attribute	Description	
Name	ACCGLDESC	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

POOL_BENEFIT

Attribute	Description	
Name	POOL_BENEFIT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

SWEEP_BASIS

Attribute	Description	
Name	SWEEP_BASIS	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	B,V

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

INTRADAY_SWEEP_REQD

Attribute	Description	
Name	INTRADAY_SWEEP_REQD	

Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	enumeration	Y,N
	Description	

BVT_INDICATOR

Attribute	Description	
Name	BVT_INDICATOR	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	enumeration	Y,N
	Description	

BVT_UNIT

Attribute	Description	
Name	BVT_UNIT	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	enumeration	M,D
	Description	

BVT_DURATION

Attribute	Description	
Name	BVT_DURATION	
Datatype	Decimal	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	totalDigits	22
	Description	

REV_SWEEP_REQD

Attribute	Description	
Name	REV_SWEEP_REQD	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String

*2.13.4.II-ModifyIIGroup-Res-PK-MSG.xsd**MODIFYIIGROUP_IOPK_RES**FCUBS_HEADER**SOURCE**UBSCOMP**MSGID**CORRELID**USERID**BRANCH**MODULEID**SERVICE**OPERATION**SOURCE_OPERATION**SOURCE_USERID**DESTINATION**MULTITRIPID**FUNCTIONID**ACTION**MSGSTAT**PASSWORD**ADDL**PARAM**NAME**VALUE**FCUBS_BODY**Itms-Group-Code-PK**GRPCD**Itms-Group-Code-IO**GRPCD**ACCGLDESC**INTRADAY_SWEEP_REQD**BVT_INDICATOR*

BVT_UNIT

BVT_DURATION

REV_SWEEP_REQD

MAKER

MAKERSTAMP

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYIIGROUP_IOPK_RES

Attribute	Description
Name	MODIFYIIGROUP_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description
Name	USERID

Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description
Name	MULTIRIPID

Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Itms-Group-Code-PK

Attribute	Description
Name	Itms-Group-Code-PK
Datatype	
Description	

GRPCD

Attribute	Description				
Name	GRPCD				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

Itms-Group-Code-IO

Attribute	Description
Name	Itms-Group-Code-IO
Datatype	
Description	

GRPCD

Attribute	Description				
Name	GRPCD				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

ACCGLDESC

Attribute	Description				
Name	ACCGLDESC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

INTRADAY_SWEEP_REQD

Attribute		Description	
Name	INTRADAY_SWEEP_REQD		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	enumeration	Y,N	

BVT_INDICATOR

Attribute		Description	
Name	BVT_INDICATOR		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	enumeration	Y,N	

BVT_UNIT

Attribute		Description	
Name	BVT_UNIT		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	enumeration	M,D	

BVT_DURATION

Attribute		Description	
Name	BVT_DURATION		
Datatype	Decimal		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	totalDigits	22	

REV_SWEEP_REQD

Attribute	Description	
Name	REV_SWEEP_REQD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	

Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute		Description	
Name	FCUBS_WARNING_RESP		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

WARNING

Attribute		Description	
Name	WARNING		
Datatype			
Description			
Attribute	Attribute		Description
	maxOccurs	unbounded	

WCODE

Attribute		Description	
Name	WCODE		
Datatype	String		
Description			

WDESC

Attribute		Description	
Name	WDESC		
Datatype	String		
Description			

2.14.ModifyIISweep

2.14.1.II-ModifyIISweep-Req-Full-MSG.xsd

MODIFYIISWEEP_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Iltns-Account-Full
ACCBRN
ACCNT
ACCINDR
EFFECTIVE_DATE
PARENT_ACC_BRN
ACC_NO
SCHEME_1
SWPTYPE
BASE_AMT
REALLOC_REQD
BOOK_ACC_BRN
ACCOPT
EXCHGRTTYP
SPREAD_IND
ACGLCCY
PARENT_ACC_CCY
BOOK_ACC_CCY
MULTIPLE_AMT
MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

MODIFYIISWEEP_FSFS_REQ

Attribute	Description
Name	MODIFYIISWEEP_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	12					
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description
Name	BRANCH

Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		

Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Itms-Account-Full

Attribute		Description
Name	Itms-Account-Full	
Datatype		
Description		

ACCBRN

Attribute	Description				
Name	ACCBRN				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

ACCNT

Attribute	Description				
Name	ACCNT				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

ACCINDR

Attribute	Description				
Name	ACCINDR				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>C,P</td></tr></tbody></table>	Restrictions	Description	enumeration	C,P
Restrictions	Description				
enumeration	C,P				

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

PARENT_ACC_BRN

Attribute	Description				
Name	PARENT_ACC_BRN				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

ACC_NO

Attribute	Description
Name	ACC_NO
Datatype	String

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

SCHEME_1

Attribute	Description	
Name	SCHEME_1	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	S

SWPTYPE

Attribute	Description	
Name	SWPTYPE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,C,T

BASE_AMT

Attribute	Description	
Name	BASE_AMT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22
	minInclusive	0

REALLOC_REQD

Attribute	Description	
Name	REALLOC_REQD	

Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

BOOK_ACC_BRN

Attribute	Description	
Name	BOOK_ACC_BRN	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

ACCOPT

Attribute	Description	
Name	ACCOPT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

EXCHGRTTYP

Attribute	Description	
Name	EXCHGRTTYP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8

SPREAD_IND

Attribute	Description	
Name	SPREAD_IND	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	M,B

ACCGLCCY

Attribute	Description	
Name	ACCGLCCY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

PARENT_ACC_CCY

Attribute	Description	
Name	PARENT_ACC_CCY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

BOOK_ACC_CCY

Attribute	Description	
Name	BOOK_ACC_CCY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

MULTIPLE_AMT

Attribute	Description
Name	MULTIPLE_AMT

Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description
Name	UDFDETAILS

Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.14.2.II-ModifyIISweep-Req-IO-MSG.xsd

MODIFYIISWEEP_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Iltns-Account-IO
ACCBRN
ACCNT
ACCINDR
EFFECTIVE_DATE
PARENT_ACC_BRN
ACC_NO
SCHEME_1
SWPTYPE
BASE_AMT
BOOK_ACC_BRN
ACCOPT
EXCHGRRTYP
SPREAD_IND
PARENT_ACC_CCY
BOOK_ACC_CCY
MULTIPLE_AMT
MAKER
MAKERSTAMP
UDFDETAILS
FLDNAM

MODIFYIISWEEP_IOPK_REQ

Attribute	Description
Name	MODIFYIISWEEP_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute		Description	
Name	SOURCE_USERID		
Datatype	String		
Description	This is the user id in the Source system who is performing the action.		
Attribute	Attribute		Description
	minOccurs	0	

DESTINATION

Attribute		Description	
Name	DESTINATION		
Datatype	String		
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

MULTITRIPID

Attribute		Description	
Name	MULTITRIPID		
Datatype	String		
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

FUNCTIONID

Attribute		Description	
Name	FUNCTIONID		
Datatype	String		
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.		
Attribute	Attribute		Description
	minOccurs	0	

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Itms-Account-IO

Attribute	Description
Name	Itms-Account-IO
Datatype	
Description	

ACCBRN

Attribute	Description				
Name	ACCBRN				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

ACCNT

Attribute	Description
-----------	-------------

Name	ACCNT	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

ACCINDR

Attribute	Description	
Name	ACCINDR	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	C,P

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		

PARENT_ACC_BRN

Attribute	Description	
Name	PARENT_ACC_BRN	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

ACC_NO

Attribute	Description	
Name	ACC_NO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	20

SCHEME_1

Attribute	Description	
Name	SCHEME_1	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	S

SWPTYPE

Attribute	Description	
Name	SWPTYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	D,C,T

BASE_AMT

Attribute	Description	
Name	BASE_AMT	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22
	minInclusive	0

BOOK_ACC_BRN

Attribute	Description	
Name	BOOK_ACC_BRN	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

ACCOPT

Attribute	Description
------------------	--------------------

Name	ACCOPT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

EXCHGRTTYP

Attribute	Description	
Name	EXCHGRTTYP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8

SPREAD_IND

Attribute	Description	
Name	SPREAD_IND	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	M,B

PARENT_ACC_CCY

Attribute	Description	
Name	PARENT_ACC_CCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

BOOK_ACC_CCY

Attribute	Description
------------------	--------------------

Name	BOOK_ACC_CCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

MULTIPLE_AMT

Attribute	Description	
Name	MULTIPLE_AMT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

UDFDETAILS

Attribute	Description
------------------	--------------------

Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.14.3.II-ModifyIISweep-Res-Full-MSG.xsd

MODIFYIISWEEP_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID
DESTINATION
MULTIRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Iltns-Account-Full
ACCBRN
ACCNT
ACCINDR
EFFECTIVE_DATE
PARENT_ACC_BRN
ACC_NO
SCHEME_1
SWPTYPE
BASE_AMT
REALLOC_REQD
BOOK_ACC_BRN
ACCOPT
EXCHGRTTYP
SPREAD_IND
ACGLCCY
PARENT_ACC_CCY
BOOK_ACC_CCY
MULTIPLE_AMT
MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYIISWEEP_FSFS_RES

Attribute	Description
Name	MODIFYIISWEEP_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description

Name	USERID						
Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description
Name	MULTIRIPID

Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Itms-Account-Full

Attribute	Description
Name	Itms-Account-Full
Datatype	
Description	

ACCBRN

Attribute	Description				
Name	ACCBRN				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

ACCNT

Attribute	Description				
Name	ACCNT				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

ACCINDR

Attribute	Description				
Name	ACCINDR				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>C,P</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	C,P
Restrictions	Description				
enumeration	C,P				

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

PARENT_ACC_BRN

Attribute	Description
Name	PARENT_ACC_BRN

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

ACC_NO

Attribute	Description	
Name	ACC_NO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	20

SCHEME_1

Attribute	Description	
Name	SCHEME_1	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	S

SWPTYPE

Attribute	Description	
Name	SWPTYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	D,C,T

BASE_AMT

Attribute	Description
Name	BASE_AMT

Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22
	minInclusive	0

REALLOC_REQD

Attribute	Description	
Name	REALLOC_REQD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

BOOK_ACC_BRN

Attribute	Description	
Name	BOOK_ACC_BRN	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

ACCOPT

Attribute	Description	
Name	ACCOPT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	20

EXCHGRTTYP

Attribute	Description
------------------	--------------------

Name	EXCHGRTTYP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8

SPREAD_IND

Attribute	Description	
Name	SPREAD_IND	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	M,B

ACCGLCCY

Attribute	Description	
Name	ACCGLCCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

PARENT_ACC_CCY

Attribute	Description	
Name	PARENT_ACC_CCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

BOOK_ACC_CCY

Attribute	Description
------------------	--------------------

Name	BOOK_ACC_CCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

MULTIPLE_AMT

Attribute	Description	
Name	MULTIPLE_AMT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description
------------------	--------------------

Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description
------------------	--------------------

Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		

Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.14.4.II-ModifyIISweep-Res-PK-MSG.xsd

MODIFYIISWEEP_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Itms-Account-PK

ACCBRN

ACCNT

ACCINDR

EFFECTIVE_DATE
Itms-Account-IO
ACCBRN
ACCNT
ACCINDR
EFFECTIVE_DATE
PARENT_ACC_BRN
ACC_NO
SCHEME_1
SWPTYPE
BASE_AMT
BOOK_ACC_BRN
ACCOPT
EXCHGRTTYP
SPREAD_IND
PARENT_ACC_CCY
BOOK_ACC_CCY
MULTIPLE_AMT
MAKER
MAKERSTAMP
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

Attribute	Description
Name	MODIFYIISWEEP_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	

Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Itms-Account-PK

Attribute	Description	
Name	Itms-Account-PK	
Datatype		
Description		

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

ACCNT

Attribute	Description	
Name	ACCNT	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

ACCINDR

Attribute	Description				
Name	ACCINDR				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
	Restrictions	Description			
maxLength	1				

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

Itms-Account-IO

Attribute	Description
Name	Itms-Account-IO
Datatype	
Description	

ACCBRN

Attribute	Description				
Name	ACCBRN				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

ACCNT

Attribute	Description				
Name	ACCNT				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
	Restrictions	Description			
maxLength	20				

ACCINDR

Attribute	Description				
Name	ACCINDR				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>C,P</td></tr></tbody></table>	Restrictions	Description	enumeration	C,P
	Restrictions	Description			
enumeration	C,P				

EFFECTIVE_DATE

Attribute	Description
-----------	-------------

Name	EFFECTIVE_DATE
Datatype	String
Description	

PARENT_ACC_BRN

Attribute	Description	
Name	PARENT_ACC_BRN	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

ACC_NO

Attribute	Description	
Name	ACC_NO	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

SCHEME_1

Attribute	Description	
Name	SCHEME_1	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	S

SWPTYPE

Attribute	Description	
Name	SWPTYPE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	enumeration	D,C,T

BASE_AMT

Attribute	Description	
Name	BASE_AMT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22
	minInclusive	0

BOOK_ACC_BRN

Attribute	Description	
Name	BOOK_ACC_BRN	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

ACCOPT

Attribute	Description	
Name	ACCOPT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

EXCHGRTTYP

Attribute	Description	
Name	EXCHGRTTYP	
Datatype	String	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8

SPREAD_IND

Attribute	Description	
Name	SPREAD_IND	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	M,B

PARENT_ACC_CCY

Attribute	Description	
Name	PARENT_ACC_CCY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

BOOK_ACC_CCY

Attribute	Description	
Name	BOOK_ACC_CCY	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

MULTIPLE_AMT

Attribute	Description	
Name	MULTIPLE_AMT	
Datatype	Decimal	
Description		

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name

Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.15.QueryIIGroup

2.15.1.II-QueryIIGroup-Req-IO-MSG.xsd

QUERYIIGROUP_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Itms-Group-Code-IO

GRPCD

QUERYIIGROUP_IOFS_REQ

Attribute	Description
Name	QUERYIIGROUP_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description					
enumeration	FCUBS,FCIS					

MSGID

Attribute	Description					
Name	MSGID					
Datatype	String					
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	String					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Iltns-Group-Code-IO
Datatype	
Description	

GRPCD

Attribute	Description				
Name	GRPCD				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

2.15.2.II-QueryIIGroup-Res-Full-MSG.xsd

QUERYIIGROUP_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Itms-Group-Code-IO

GRPCD

Itms-Group-Code-Full

GRPCD

ACCGLDESC

POOL_BENEFIT

SWEEP_BASIS

EFFECTIVE_DATE

INTRADAY_SWEEP_REQD

BVT_INDICATOR

BVT_UNIT

BVT_DURATION

REV_SWEEP_REQD

ACCBRN

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

QUERYIIGROUP_IOFS_RES

Attribute	Description
Name	QUERYIIGROUP_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute		Description	
Name	SOURCE_USERID		
Datatype	String		
Description	This is the user id in the Source system who is performing the action.		
Attribute	Attribute		Description
	minOccurs	0	

DESTINATION

Attribute		Description	
Name	DESTINATION		
Datatype	String		
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

MULTITRIPID

Attribute		Description	
Name	MULTITRIPID		
Datatype	String		
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.		
Attribute	Attribute		Description
	minOccurs	0	
	Restrictions		Description
Restrictions	pattern	[a-zA-Z_0-9]*	

FUNCTIONID

Attribute		Description	
Name	FUNCTIONID		
Datatype	String		
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.		
Attribute	Attribute		Description
	minOccurs	0	

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Itms-Group-Code-IO

Attribute	Description
Name	Itms-Group-Code-IO
Datatype	
Description	

GRPCD

Attribute	Description				
Name	GRPCD				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

Itms-Group-Code-Full

Attribute	Description
-----------	-------------

Name	Illms-Group-Code-Full
Datatype	
Description	

GRPCD

Attribute	Description	
Name	GRPCD	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	9

ACCGLDESC

Attribute	Description	
Name	ACCGLDESC	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

POOL_BENEFIT

Attribute	Description	
Name	POOL_BENEFIT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

SWEEP_BASIS

Attribute	Description	
Name	SWEEP_BASIS	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	B,V

EFFECTIVE_DATE

Attribute		Description	
Name	EFFECTIVE_DATE		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	

INTRADAY_SWEEP_REQD

Attribute		Description	
Name	INTRADAY_SWEEP_REQD		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	enumeration	Y,N	

BVT_INDICATOR

Attribute		Description	
Name	BVT_INDICATOR		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	enumeration	Y,N	

BVT_UNIT

Attribute		Description	
Name	BVT_UNIT		
Datatype	String		
Description			
Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	enumeration	M,D	

BVT_DURATION

Attribute		Description	
Name	BVT_DURATION		
Datatype	Decimal		

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

REV_SWEEP_REQD

Attribute	Description	
Name	REV_SWEEP_REQD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	3

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.16.QueryIIGrplink

2.16.1.II-QueryIIGrplink-Req-IO-MSG.xsd

QUERYIIGRPLINK_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Itms-Account-Group-Link-IO

ACCBRN

HEADER_ACC

EFFECTIVE_DATE

GROUP_CODE

QUERYIIGRPLINK_IOFS_REQ

Attribute	Description
Name	QUERYIIGRPLINK_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description
Name	BRANCH

Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	

Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Itms-Account-Group-Link-IO

Attribute	Description	
Name	Itms-Account-Group-Link-IO	
Datatype		
Description		

ACCBRN

Attribute	Description				
Name	ACCBRN				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

HEADER_ACC

Attribute	Description				
Name	HEADER_ACC				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

GROUP_CODE

Attribute	Description				
Name	GROUP_CODE				
Datatype	String				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

2.16.2.II-QueryIIGrplink-Res-Full-MSG.xsd

QUERYIIGRPLINK_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTIRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Ilms-Account-Group-Link-IO
ACCBRN
HEADER_ACC
EFFECTIVE_DATE
GROUP_CODE
Ilms-Account-Group-Link-Full
ACCBRN
HEADER_ACC
EFFECTIVE_DATE
GROUP_CODE
CCY3
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYIIGRPLINK_IOFS_RES

Attribute	Description
Name	QUERYIIGRPLINK_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0

PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute		Description
Name	FCUBS_BODY	
Datatype		
Description		

Itms-Account-Group-Link-IO

Attribute		Description
------------------	--	--------------------

Name	Ilrms-Account-Group-Link-IO
Datatype	
Description	

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	3

HEADER_ACC

Attribute	Description	
Name	HEADER_ACC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		

GROUP_CODE

Attribute	Description	
Name	GROUP_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

Ilrms-Account-Group-Link-Full

Attribute	Description	
Name	Ilrms-Account-Group-Link-Full	
Datatype		
Description		

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		

Restrictions		
	Restrictions	Description
	maxLength	3

HEADER_ACC

Attribute	Description	
Name	HEADER_ACC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		

GROUP_CODE

Attribute	Description	
Name	GROUP_CODE	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

CCY3

Attribute	Description	
Name	CCY3	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	4

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		

Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.17.QueryISweep

2.17.1.II-QueryISweep-Req-IO-MSG.xsd

QUERYISWEEP_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTIRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Itms-Account-IO

ACCBRN

ACCNT

ACCINDR

EFFECTIVE_DATE

QUERYISWEEP_IOFS_REQ

Attribute	Description
Name	QUERYISWEEP_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
-----------	-------------

Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Ilrms-Account-IO
Datatype	
Description	

ACCBRN

Attribute	Description				
Name	ACCBRN				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

ACCNT

Attribute	Description				
Name	ACCNT				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

ACCINDR

Attribute	Description				
Name	ACCINDR				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>C,P</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	C,P
Restrictions	Description				
enumeration	C,P				

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

2.17.2.II-QueryIISweep-Res-Full-MSG.xsd

QUERYIISWEEP_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Itms-Account-IO
ACCBRN
ACCNT
ACCINDR
EFFECTIVE_DATE
Itms-Account-Full
ACCBRN
ACCNT
ACCINDR
EFFECTIVE_DATE
PARENT_ACC_BRN
ACC_NO
SCHEME_1
SWPTYPE
BASE_AMT

REALLOC_REQD
BOOK_ACC_BRN
ACCOPT
EXCHGRRTYP
SPREAD_IND
ACCGLCCY
PARENT_ACC_CCY
BOOK_ACC_CCY
MULTIPLE_AMT
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
UDFDETAILS
 FLDNAM
 FLDVAL
FCUBS_ERROR_RESP
 ERROR
 ECODE
 EDESC
FCUBS_WARNING_RESP
 WARNING
 WCODE
 WDESC

QUERYIISWEEP_IOFS_RES

Attribute	Description
Name	QUERYIISWEEP_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Itms-Account-IO

Attribute	Description
Name	Itms-Account-IO
Datatype	
Description	

ACCBRN

Attribute	Description				
Name	ACCBRN				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

ACCNT

Attribute	Description				
Name	ACCNT				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

ACCINDR

Attribute	Description				
Name	ACCINDR				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>C,P</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	C,P
Restrictions	Description				
enumeration	C,P				

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

Itms-Account-Full

Attribute	Description
Name	Itms-Account-Full
Datatype	
Description	

ACCBRN

Attribute	Description				
Name	ACCBRN				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

ACCNT

Attribute	Description				
Name	ACCNT				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

ACCINDR

Attribute	Description				
Name	ACCINDR				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>C,P</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	C,P
Restrictions	Description				
enumeration	C,P				

EFFECTIVE_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	String
Description	

PARENT_ACC_BRN

Attribute	Description
Name	PARENT_ACC_BRN
Datatype	String
Description	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

ACC_NO

Attribute	Description	
Name	ACC_NO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	20

SCHEME_1

Attribute	Description	
Name	SCHEME_1	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	S

SWPTYPE

Attribute	Description	
Name	SWPTYPE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	D,C,T

BASE_AMT

Attribute	Description	
Name	BASE_AMT	
Datatype	Decimal	
Description		

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22
	minInclusive	0

REALLOC_REQD

Attribute	Description	
Name	REALLOC_REQD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

BOOK_ACC_BRN

Attribute	Description	
Name	BOOK_ACC_BRN	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

ACCOPT

Attribute	Description	
Name	ACCOPT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

EXCHGRTTYP

Attribute	Description	
Name	EXCHGRTTYP	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8

SPREAD_IND

Attribute	Description	
Name	SPREAD_IND	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	M,B

ACCGLCCY

Attribute	Description	
Name	ACCGLCCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

PARENT_ACC_CCY

Attribute	Description	
Name	PARENT_ACC_CCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

BOOK_ACC_CCY

Attribute	Description	
Name	BOOK_ACC_CCY	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

MULTIPLE_AMT

Attribute	Description	
Name	MULTIPLE_AMT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String

2.18.ReopenIIGroup

2.18.1.II-ReopenIIGroup-Req-Full-MSG.xsd

REOPENIIGROUP_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Ilrms-Group-Code-Full

GRPCD

ACCGLDESC

POOL_BENEFIT

SWEEP_BASIS

EFFECTIVE_DATE

INTRADAY_SWEEP_REQD

BVT_INDICATOR

BVT_UNIT

BVT_DURATION

REV_SWEEP_REQD

ACCBRN

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

REOPENIIGROUP_FSFS_REQ

Attribute	Description
Name	REOPENIIGROUP_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description
Name	USERID

Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	12					
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
	Restrictions	Description					
	length	3					
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
	Attribute	Description			
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description
Name	MULTIRIPID

Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Itms-Group-Code-Full

Attribute	Description
Name	Itms-Group-Code-Full
Datatype	
Description	

GRPCD

Attribute	Description				
Name	GRPCD				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

ACGLDESC

Attribute	Description				
Name	ACGLDESC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

POOL_BENEFIT

Attribute	Description				
Name	POOL_BENEFIT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>Y,N</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

SWEEP_BASIS

Attribute	Description
-----------	-------------

Name	SWEEP_BASIS	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	B,V

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

INTRADAY_SWEEP_REQD

Attribute	Description	
Name	INTRADAY_SWEEP_REQD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

BVT_INDICATOR

Attribute	Description	
Name	BVT_INDICATOR	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

BVT_UNIT

Attribute	Description	
Name	BVT_UNIT	
Datatype	String	
Description		

Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	enumeration	M,D
	Description	

BVT_DURATION

Attribute	Description	
Name	BVT_DURATION	
Datatype	Decimal	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	totalDigits	22
	Description	

REV_SWEEP_REQD

Attribute	Description	
Name	REV_SWEEP_REQD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	enumeration	Y,N
	Description	

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Restrictions	Restrictions	
	maxLength	3
	Description	

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	

Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.18.2.II-ReopenIIGroup-Req-IO-MSG.xsd

REOPENIIGROUP_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Itms-Group-Code-IO

GRPCD

MAKER

MAKERSTAMP

MODNO

REOPENIIGROUP_IOPK_REQ

Attribute	Description
Name	REOPENIIGROUP_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*
	Description	

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*
	Description	

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	enumeration	SUCCESS,WARNING,FAILURE
	Description	

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	
	minOccurs	0
	Description	
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*
	Description	

ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute		Attribute	
		Description	
		minOccurs	0

PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute		Attribute	
		Description	
		minOccurs	0
		maxOccurs	unbounded

NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

FCUBS_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description			

Itms-Group-Code-IO

Attribute		Description	
Name		Itms-Group-Code-IO	
Datatype			
Description			

GRPCD

Attribute		Description	
Name		GRPCD	
Datatype		String	
Description			
Restrictions		Restrictions	
		Description	
		maxLength	9

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

2.18.3.II-ReopenIIGroup-Res-Full-MSG.xsd

REOPENIIGROUP_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Itms-Group-Code-Full
GRPCD
ACCGLDESC
POOL_BENEFIT
SWEEP_BASIS
EFFECTIVE_DATE
INTRADAY_SWEEP_REQD
BVT_INDICATOR
BVT_UNIT
BVT_DURATION
REV_SWEEP_REQD
ACCBRN
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

REOPENIIGROUP_FSFS_RES

Attribute	Description
Name	REOPENIIGROUP_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description					
enumeration	FCUBS,FCIS					

MSGID

Attribute	Description					
Name	MSGID					
Datatype	String					
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	String					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
	Restrictions	Description
Restrictions	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Ilrms-Group-Code-Full
Datatype	
Description	

GRPCD

Attribute	Description				
Name	GRPCD				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

ACCGLDESC

Attribute	Description				
Name	ACCGLDESC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

POOL_BENEFIT

Attribute	Description				
Name	POOL_BENEFIT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>Y,N</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

SWEEP_BASIS

Attribute	Description				
Name	SWEEP_BASIS				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	enumeration	B,V

EFFECTIVE_DATE

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

INTRADAY_SWEEP_REQD

Attribute	Description	
Name	INTRADAY_SWEEP_REQD	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

BVT_INDICATOR

Attribute	Description	
Name	BVT_INDICATOR	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	Y,N

BVT_UNIT

Attribute	Description	
Name	BVT_UNIT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	M,D

BVT_DURATION

Attribute	Description	
Name	BVT_DURATION	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

REV_SWEEP_REQD

Attribute	Description	
Name	REV_SWEEP_REQD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	3

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	

Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	150
	minLength	0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		

Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.18.4.II-ReopenIIGroup-Res-PK-MSG.xsd

REOPENIIGROUP_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Itms-Group-Code-PK

GRPCD

Itms-Group-Code-IO

GRPCD

MAKER

MAKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

REOPENIIGROUP_IOPK_RES

Attribute	Description
Name	REOPENIIGROUP_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	Attribute	Description
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Itms-Group-Code-PK

Attribute	Description
Name	Itms-Group-Code-PK
Datatype	
Description	

GRPCD

Attribute	Description				
Name	GRPCD				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

Itms-Group-Code-IO

Attribute	Description
Name	Itms-Group-Code-IO
Datatype	
Description	

GRPCD

Attribute	Description				
Name	GRPCD				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

MAKER

Attribute	Description
-----------	-------------

Name	MAKER	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		

Attribute		
	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	



FINANCIAL SERVICES

Gateway Documentation - FCUBSIIService
[February] [2016]

Oracle Financial services Software Limited
Oracle Park
Off western Express Highway
Goregaon(East)
Mumbai,Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax:+91 22 6718 3001
www.oracle.com/financialservices/

Copyright © [2013], [2016], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.