Gateway Documentation - FCUBSINService
Oracle FLEXCUBE Universal Banking
Release 12.87.02.0.0
[Febraury][2016]

Table Of Contents

1. Background **1**

2. FCUBSINService **2**

2.1.AuthorizeINextudval **2**

2.1.1.IN-AuthorizeINextudval-Req-Full-MSG.xsd 2

2.1.2.IN-AuthorizeINextudval-Req-IO-MSG.xsd 13

2.1.3.IN-AuthorizeINextudval-Res-Full-MSG.xsd 21

2.1.4.IN-AuthorizeINextudval-Res-PK-MSG.xsd 34

2.2.AuthorizeINGroup **44**

2.2.1.IN-AuthorizeINGroup-Req-Full-MSG.xsd 44

2.2.2.IN-AuthorizeINGroup-Req-IO-MSG.xsd 53

2.2.3.IN-AuthorizeINGroup-Res-Full-MSG.xsd 61

2.2.4.IN-AuthorizeINGroup-Res-PK-MSG.xsd 71

2.3.AuthorizeInIntermedMaint **81**

2.3.1.IN-AuthorizeInIntermedMaint-Req-Full-MSG.xsd 81

2.3.2.IN-AuthorizeInIntermedMaint-Req-IO-MSG.xsd 138

2.3.3.IN-AuthorizeInIntermedMaint-Res-Full-MSG.xsd 146

2.3.4.IN-AuthorizeInIntermedMaint-Res-PK-MSG.xsd 205

2.4.CreateINextudval **215**

2.4.1.IN-CreateINextudval-Req-Full-MSG.xsd 215

2.4.2.IN-CreateINextudval-Req-IO-MSG.xsd 226

2.4.3.IN-CreateINextudval-Res-Full-MSG.xsd 235

2.4.4.IN-CreateINextudval-Res-PK-MSG.xsd 248

2.5.CreateINGroup **259**

2.5.1.IN-CreateINGroup-Req-Full-MSG.xsd 259

2.5.2.IN-CreateINGroup-Req-IO-MSG.xsd 268

2.5.3.IN-CreateINGroup-Res-Full-MSG.xsd 275

2.5.4.IN-CreateINGroup-Res-PK-MSG.xsd 286

2.6.CreateInIntermedMaint **295**

2.6.1.IN-CreateInIntermedMaint-Req-Full-MSG.xsd 295

2.6.2.IN-CreateInIntermedMaint-Req-IO-MSG.xsd 352

2.6.3.IN-CreateInIntermedMaint-Res-Full-MSG.xsd 394

2.6.4.IN-CreateInIntermedMaint-Res-PK-MSG.xsd 453

2.7.DeleteINextudval **496**

2.7.1.IN-DeleteINextudval-Req-Full-MSG.xsd 496

2.7.2.IN-DeleteINextudval-Req-IO-MSG.xsd 508

2.7.3.IN-DeleteINextudval-Res-Full-MSG.xsd 515

2.7.4.IN-DeleteINextudval-Res-PK-MSG.xsd 528

2.8.DeleteINGroup **537**

2.8.1.IN-DeleteINGroup-Req-Full-MSG.xsd 537

2.8.2.IN-DeleteINGroup-Req-IO-MSG.xsd 546

2.8.3.IN-DeleteINGroup-Res-Full-MSG.xsd 553

2.8.4.IN-DeleteINGroup-Res-PK-MSG.xsd 563

2.9.DeleteInIntermedMaint **572**

2.9.1.IN-DeleteInIntermedMaint-Req-Full-MSG.xsd 572

2.9.2.IN-DeleteInIntermedMaint-Req-IO-MSG.xsd 629

2.9.3.IN-DeleteInIntermedMaint-Res-Full-MSG.xsd 636

2.9.4.IN-DeleteInIntermedMaint-Res-PK-MSG.xsd 695

2.10.ModifyINextudval **704**

ORACLE

2.10.1.IN-ModifyINextudval-Req-Full-MSG.xsd 704
2.10.2.IN-ModifyINextudval-Req-IO-MSG.xsd 715
2.10.3.IN-ModifyINextudval-Res-Full-MSG.xsd 723
2.10.4.IN-ModifyINextudval-Res-PK-MSG.xsd 736
2.11.ModifyINGroup 746
2.11.1.IN-ModifyINGroup-Req-Full-MSG.xsd 746
2.11.2.IN-ModifyINGroup-Req-IO-MSG.xsd 755
2.11.3.IN-ModifyINGroup-Res-Full-MSG.xsd 762
2.11.4.IN-ModifyINGroup-Res-PK-MSG.xsd 772
2.12.ModifyInIntermedMaint 782
2.12.1.IN-ModifyInIntermedMaint-Req-Full-MSG.xsd 782
2.12.2.IN-ModifyInIntermedMaint-Req-IO-MSG.xsd 839
2.12.3.IN-ModifyInIntermedMaint-Res-Full-MSG.xsd 872
2.12.4.IN-ModifyInIntermedMaint-Res-PK-MSG.xsd 931
2.13.QueryINbrnmaint 965
2.13.1.IN-QueryINbrnmaint-Req-IO-MSG.xsd 965
2.13.2.IN-QueryINbrnmaint-Res-Full-MSG.xsd 972
2.14.QueryINextudval 984
2.14.1.IN-QueryINextudval-Req-IO-MSG.xsd 984
2.14.2.IN-QueryINextudval-Res-Full-MSG.xsd 991
2.15.QueryINGroup 1005
2.15.1.IN-QueryINGroup-Req-IO-MSG.xsd 1005
2.15.2.IN-QueryINGroup-Res-Full-MSG.xsd 1011
2.16.QueryInIntermedMaint 1022
2.16.1.IN-QueryInIntermedMaint-Req-IO-MSG.xsd 1022
2.16.2.IN-QueryInIntermedMaint-Res-Full-MSG.xsd 1029
2.17.QueryInProdMaint 1089
2.17.1.IN-QueryInProdMaint-Req-IO-MSG.xsd 1089
2.17.2.IN-QueryInProdMaint-Res-Full-MSG.xsd 1095
2.18.QueryInRuleMaint 1124
2.18.1.IN-QueryInRuleMaint-Req-IO-MSG.xsd 1124
2.18.2.IN-QueryInRuleMaint-Res-Full-MSG.xsd 1131
2.19.QueryInSdeMaint 1146
2.19.1.IN-QueryInSdeMaint-Req-IO-MSG.xsd 1146
2.19.2.IN-QueryInSdeMaint-Res-Full-MSG.xsd 1153
2.20.QueryInSdeView 1162
2.20.1.IN-QueryInSdeView-Req-IO-MSG.xsd 1162
2.20.2.IN-QueryInSdeView-Res-Full-MSG.xsd 1169
2.21.QueryInUdeMaint 1179
2.21.1.IN-QueryInUdeMaint-Req-IO-MSG.xsd 1179
2.21.2.IN-QueryInUdeMaint-Res-Full-MSG.xsd 1186
2.22.QueryInViewMaint 1197
2.22.1.IN-QueryInViewMaint-Req-IO-MSG.xsd 1197
2.22.2.IN-QueryInViewMaint-Res-Full-MSG.xsd 1205

1. Background

Integration of different applications and solutions is a key area in today's systems.A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data.The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs.The integration needs supported by the Gateway can be broadly categorized from the perspective of Gateway as follows

1. Inbound application integration :

This is used when any external system needs to add, modify or query information within FLEXCUBE UBS

2. Outbound application integration :

This is used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS

The following sections provide detailed XSD documentation of all operations available in FCUBSINService of IN Module

2. FCUBSINService

2.1.AuthorizeINextudval

2.1.1.IN-AuthorizeINextudval-Req-Full-MSG.xsd

- *AUTHORIZEINEXTUDVAL_FSFS_REQ*
  - *FCUBS_HEADER*
    - *SOURCE*
    - *UBSCOMP*
    - *MSGID*
    - *CORRELID*
    - *USERID*
    - *BRANCH*
    - *MODULEID*
    - *SERVICE*
    - *OPERATION*
    - *SOURCE_OPERATION*
    - *SOURCE_USERID*
    - *DESTINATION*
    - *MULTITRIPID*
    - *FUNCTIONID*
    - *ACTION*
    - *MSGSTAT*
    - *PASSWORD*
    - *ADDL*
      - *PARAM*
        - *NAME*
        - *VALUE*
  - *FCUBS_BODY*
    - *Intms-Inter-Ext-Ude-Full*
      - *INTERMEDIARYCODE*
      - *UDEFFDT*
      - *MAKER*
      - *MAKERSTAMP*

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Intms-Inter-Ext-Prdlink

PRODUCTCODE

PRODUCT_DESC

UDEEFFDT

Intms-Inter-Ext-Ude-Values

UDEID

UDEVALUE

RULEID

UDETYPE

UDECCY

AUTHORIZEINEXTUDVAL_FSFS_REQ

Attribute	Description
Name	AUTHORIZEINEXTUDVAL_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description

Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.

Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	
	Restrictions / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description**: minOccurs / 0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Intms-Inter-Ext-Ude-Full
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

UDEFFDT

Attribute	Description
Name	UDEFFDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	4

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

Intms-Inter-Ext-Prdlink

Attribute	Description
Name	Intms-Inter-Ext-Prdlink
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PRODUCTCODE

Attribute	Description
Name	PRODUCTCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

PRODUCT_DESC

Attribute	Description
Name	PRODUCT_DESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	50

UDEEFFDT

Attribute	Description
Name	UDEEFFDT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Intms-Inter-Ext-Ude-Values

Attribute	Description
Name	Intms-Inter-Ext-Ude-Values
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

UDEVALUE

Attribute	Description
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

RULEID

Attribute	Description

Name	RULEID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

UDETYPE

Attribute	**Description**
Name	UDETYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / R,A,N,

UDECCY

Attribute	**Description**
Name	UDECCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

2.1.2.IN-AuthorizeINextudval-Req-IO-MSG.xsd

AUTHORIZEINEXTUDVAL_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Inter-Ext-Ude-IO

INTERMEDIARYCODE

UDEFFDT

CHECKER

CHECKERSTAMP

MODNO

AUTHORIZEINEXTUDVAL_IOPK_REQ

Attribute	Description
Name	AUTHORIZEINEXTUDVAL_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Inter-Ext-Ude-IO

Attribute	Description
Name	Intms-Inter-Ext-Ude-IO
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

UDEFFDT

Attribute	Description
Name	UDEFFDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

2.1.3.IN-AuthorizeINextudval-Res-Full-MSG.xsd

AUTHORIZEINEXTUDVAL_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Inter-Ext-Ude-Full

INTERMEDIARYCODE

UDEFFDT

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Intms-Inter-Ext-Prdlink

PRODUCTCODE

PRODUCT_DESC

UDEEFFDT

Intms-Inter-Ext-Ude-Values

UDEID

UDEVALUE

RULEID

UDETYPE

UDECCY

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZEINEXTUDVAL_FSFS_RES

Attribute	Description
Name	AUTHORIZEINEXTUDVAL_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH

Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String

Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Inter-Ext-Ude-Full

Attribute	Description
Name	Intms-Inter-Ext-Ude-Full
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

UDEFFDT

Attribute	Description
Name	UDEFFDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Intms-Inter-Ext-Prdlink

Attribute	Description
Name	Intms-Inter-Ext-Prdlink
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PRODUCTCODE

Attribute	Description
Name	PRODUCTCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

PRODUCT_DESC

Attribute	Description
Name	PRODUCT_DESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

UDEEFFDT

Attribute	Description
Name	UDEEFFDT
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0

Intms-Inter-Ext-Ude-Values

Attribute	Description
Name	Intms-Inter-Ext-Ude-Values
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

UDEVALUE

Attribute	Description
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

RULEID

Attribute	Description
Name	RULEID
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	16

UDETYPE

Attribute	Description
Name	UDETYPE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	R,A,N,

UDECCY

Attribute	Description
Name	UDECCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description

Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.1.4.IN-AuthorizeINextudval-Res-PK-MSG.xsd

AUTHORIZEINEXTUDVAL_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Inter-Ext-Ude-PK

INTERMEDIARYCODE

UDEFFDT

Intms-Inter-Ext-Ude-IO

INTERMEDIARYCODE

UDEFFDT

CHECKER

CHECKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZEINEXTUDVAL_IOPK_RES

Attribute	Description
Name	AUTHORIZEINEXTUDVAL_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Inter-Ext-Ude-PK

Attribute	Description
Name	Intms-Inter-Ext-Ude-PK
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	16

UDEFFDT

Attribute	Description
Name	UDEFFDT
Datatype	String
Description	

Intms-Inter-Ext-Ude-IO

Attribute	Description
Name	Intms-Inter-Ext-Ude-IO
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

UDEFFDT

Attribute	Description
Name	UDEFFDT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.2.AuthorizeINGroup

2.2.1.IN-AuthorizeINGroup-Req-Full-MSG.xsd

AUTHORIZEINGROUP_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-Group-Full

GRPCD

GROUPDESC

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

AUTHORIZEINGROUP_FSFS_REQ

Attribute	Description
Name	AUTHORIZEINGROUP_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description

Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-Group-Full

Attribute	Description
Name	Intms-Intermediary-Group-Full
Datatype	
Description	

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

GROUPDESC

Attribute	Description
Name	GROUPDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

2.2.2.IN-AuthorizeINGroup-Req-IO-MSG.xsd

AUTHORIZEINGROUP_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-Group-IO

GRPCD

CHECKER

CHECKERSTAMP

MODNO

AUTHORIZEINGROUP_IOPK_REQ

Attribute	Description
Name	AUTHORIZEINGROUP_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-Group-IO

Attribute	Description
Name	Intms-Intermediary-Group-IO
Datatype	
Description	

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

2.2.3.IN-AuthorizeINGroup-Res-Full-MSG.xsd

AUTHORIZEINGROUP_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-Group-Full

GRPCD

GROUPDESC

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZEINGROUP_FSFS_RES

Attribute	Description
Name	AUTHORIZEINGROUP_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-Group-Full

Attribute	Description
Name	Intms-Intermediary-Group-Full
Datatype	
Description	

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

GROUPDESC

Attribute	Description
Name	GROUPDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	

Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.2.4.IN-AuthorizeINGroup-Res-PK-MSG.xsd

AUTHORIZEINGROUP_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-Group-PK

GRPCD

Intms-Intermediary-Group-IO

GRPCD

CHECKER

CHECKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZEINGROUP_IOPK_RES

Attribute	Description
Name	AUTHORIZEINGROUP_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-Group-PK

Attribute	Description
Name	Intms-Intermediary-Group-PK
Datatype	
Description	

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

Intms-Intermediary-Group-IO

Attribute	Description
Name	Intms-Intermediary-Group-IO
Datatype	
Description	

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attribute	

Attribute	Description
maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.3.AuthorizeInIntermedMaint

2.3.1.IN-AuthorizeInIntermedMaint-Req-Full-MSG.xsd

AUTHORIZEININTERMEDMAINT_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-Full

INTERMEDIARYCODE

INTERMEDIARYSTATUS

INTERMEDIARYCATEGORY

LEVELNUMBER

PARENTINTERMEDIARYCODE

PARENTINTERMEDIARYNAME

ADDRESS1

ADDRESS2

ADDRESS3

COUNTRY

TELEPHONE

EMAILID

ZIP

FAX

MOBILE

INTERMEDIARYCUSTNO

TYPE

CLCTAGENTID

STATEMENTFREQUENCY

STATEMENTSTARTMONTH

STATEMENTSTARTDATE

STATEMENTFREQUENCYUNIT

LASTSTATEMENTDATE

NEXTSTATEMENTDATE

INTERMEDIARYNAME

PRIMARYCONTACT

EFFECTIVEDATE

BRANCHCODE

LIQUIDATIONMODE

MINIMUMLIQAMT

CASCADETILL

ROOTINTM

CASCADE_CHILDS

GRPCD

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Intms-Inter-Settlement

- *SETTLE_MODE*
- *UPLDSRC*
- *CLGPRODDR*
- *ENDPOINT*
- *ROUTINGNO*
- *EXTACCBNK2*
- *EXT_BRN_CODE*
- *INSTRUMENTNO*
- *SECTORCODE*
- *EXTACCNAME*
- *EXTACCNUMBER*
- *CTG_PROD_CAT*
- *PAYABLEBANK*
- *PAYABLEBRANCH*
- *SETTLEPRD*
- *SETLCCY*
- *SETLACCBRN*
- *STTLACC*

Intms-Inter-Prd-Linkage

PRODUCTCODE

PRODUCT_DESC

LASTSETTLEMENTDT

LASTPROCESSINGDATE

NEXTPROCESSINGDATE

MIN_HIERARCHY_COMM

HERRCOMM

Intbs-Inter-Ude-Values

UDEID

UDETYPE

UDEVALUE

INTERMEDIARYPRODUCTCODE

INTERMEDIARYCODE

RULEID

Invws-Inter-Prd-Rule-Ude

RULEID

UDEID

UDEVALUE

Intbs-Inter-Event-Log

INTERMEDIARYCODE

BRANCHCODE

EVENTCODE

EVENT_DATE

EVENTNO

Invws-Event-Ac-Entries

FCCREF

ESN

BRANCHCODE

ACCOUNTNUMBER

BRNLCY

DRCRIND

CODE

FCYAMT

EXRATE

LCYAMT

DATE

VALDT

AMTTAG

EVENT

Intbs-Inter-Event-Adv

EVENTCODE

INTERMEDIARYCODE

BRANCHCODE

EVENTNO

MSGTYPE

SUPPRESS

PRIORITY

PRTYID

CustAcc

BRN

ACC

Misdetails

MISGRP

POOLCD

REFRATE

REFRTTYPE

MISGRPTXN

REFRTCD

REFRTSPRD

CALCMETH

TXNMIS1

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

TXNMIS10

MISGRPCOMP

COMPMIS1

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

COMPMIS10

COSTCOD1

COSTCOD2

COSTCOD3

COSTCOD4

COSTCOD5

RTFLAG

LINKGRP

MisAccLog

- *MISCLS*
- *TXNDT*
- *OLDMISCD*
- *NWMISCD*

MisBalLog

- *BRN*

PRDCD

FINYR

TXNDT

GLCODE

MISCLS

OLDMISCD

NWMISCD

TRNIND

CCY

XRATE

AMT

Chglog

Classname

C2

C3

C4

C6

C7

C8

C9

C10

T1

T3

T5

T6

T7

T8

T9

T10

UDFDETAILS

FLDNAM

FLDVAL

AUTHORIZEININTERMEDMAINT_FSFS_REQ

Attribute	Description
Name	AUTHORIZEININTERMEDMAINT_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description**: minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL

Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-Full

Attribute	Description
Name	Intms-Intermediary-Full
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	16

INTERMEDIARYSTATUS

Attribute	Description
Name	INTERMEDIARYSTATUS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	A,I

INTERMEDIARYCATEGORY

Attribute	Description
Name	INTERMEDIARYCATEGORY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	I,G,

LEVELNUMBER

Attribute	Description
Name	LEVELNUMBER
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

PARENTINTERMEDIARYCODE

Attribute	Description
Name	PARENTINTERMEDIARYCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

PARENTINTERMEDIARYNAME

Attribute	Description
Name	PARENTINTERMEDIARYNAME
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	32

ADDRESS1

Attribute	Description
Name	ADDRESS1
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	100

ADDRESS2

Attribute	Description
Name	ADDRESS2
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	100

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 100

COUNTRY

Attribute	**Description**
Name	COUNTRY
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TELEPHONE

Attribute	**Description**
Name	TELEPHONE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 16

EMAILID

Attribute	**Description**
Name	EMAILID
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

ZIP

Attribute	**Description**
Name	ZIP
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	14

FAX

Attribute	Description
Name	FAX
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	16

MOBILE

Attribute	Description
Name	MOBILE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	10

INTERMEDIARYCUSTNO

Attribute	Description
Name	INTERMEDIARYCUSTNO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

TYPE

Attribute	Description
Name	TYPE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: enumeration / I,E

CLCTAGENTID

Attribute	**Description**
Name	CLCTAGENTID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

STATEMENTFREQUENCY

Attribute	**Description**
Name	STATEMENTFREQUENCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Y,

STATEMENTSTARTMONTH

Attribute	**Description**
Name	STATEMENTSTARTMONTH
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

STATEMENTSTARTDATE

Attribute	**Description**
Name	STATEMENTSTARTDATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description** totalDigits / 22

STATEMENTFREQUENCYUNIT

Attribute	Description
Name	STATEMENTFREQUENCYUNIT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

LASTSTATEMENTDATE

Attribute	Description
Name	LASTSTATEMENTDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

NEXTSTATEMENTDATE

Attribute	Description
Name	NEXTSTATEMENTDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

INTERMEDIARYNAME

Attribute	Description
Name	INTERMEDIARYNAME
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

PRIMARYCONTACT

Attribute	Description

Name	PRIMARYCONTACT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

EFFECTIVEDATE

Attribute	**Description**
Name	EFFECTIVEDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

BRANCHCODE

Attribute	**Description**
Name	BRANCHCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

LIQUIDATIONMODE

Attribute	**Description**
Name	LIQUIDATIONMODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M,

MINIMUMLIQAMT

Attribute	**Description**
Name	MINIMUMLIQAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: totalDigits / 22

CASCADETILL

Attribute	Description
Name	CASCADETILL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,R,

ROOTINTM

Attribute	Description
Name	ROOTINTM
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CASCADE_CHILDS

Attribute	Description
Name	CASCADE_CHILDS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	4

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	4

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

Intms-Inter-Settlement

Attribute	Description
Name	Intms-Inter-Settlement
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

SETTLE_MODE

Attribute	Description
Name	SETTLE_MODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ACC,EAC,

UPLDSRC

Attribute	Description
Name	UPLDSRC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

CLGPRODDR

Attribute	Description
Name	CLGPRODDR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

EXTACCBNK2

Attribute	Description
Name	EXTACCBNK2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

EXT_BRN_CODE

Attribute	Description
Name	EXT_BRN_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

INSTRUMENTNO

Attribute	Description
Name	INSTRUMENTNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

SECTORCODE

Attribute	Description
Name	SECTORCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

EXTACCNAME

Attribute	Description
Name	EXTACCNAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

EXTACCNUMBER

Attribute	Description
Name	EXTACCNUMBER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

CTG_PROD_CAT

Attribute	Description
Name	CTG_PROD_CAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

PAYABLEBANK

Attribute	Description
Name	PAYABLEBANK
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

PAYABLEBRANCH

Attribute	Description
Name	PAYABLEBRANCH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

SETTLEPRD

Attribute	Description
Name	SETTLEPRD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

SETLCCY

Attribute	Description
Name	SETLCCY
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

SETLACCBRN

Attribute	Description
Name	SETLACCBRN
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	4

STTLACC

Attribute	Description
Name	STTLACC
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	20

Intms-Inter-Prd-Linkage

Attribute	Description
Name	Intms-Inter-Prd-Linkage
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PRODUCTCODE

Attribute	Description
Name	PRODUCTCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

PRODUCT_DESC

Attribute	Description
Name	PRODUCT_DESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	50

LASTSETTLEMENTDT

Attribute	Description

Name	LASTSETTLEMENTDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

LASTPROCESSINGDATE

Attribute	Description
Name	LASTPROCESSINGDATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

NEXTPROCESSINGDATE

Attribute	Description
Name	NEXTPROCESSINGDATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

MIN_HIERARCHY_COMM

Attribute	Description
Name	MIN_HIERARCHY_COMM
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

HERRCOMM

Attribute	Description
Name	HERRCOMM
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>100</td></tr></table>

Intbs-Inter-Ude-Values

Attribute	Description
Name	Intbs-Inter-Ude-Values
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

UDETYPE

Attribute	Description
Name	UDETYPE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

UDEVALUE

Attribute	Description
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

INTERMEDIARYPRODUCTCODE

Attribute	Description

Name	INTERMEDIARYPRODUCTCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

INTERMEDIARYCODE

Attribute	**Description**
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

RULEID

Attribute	**Description**
Name	RULEID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

Invws-Inter-Prd-Rule-Ude

Attribute	**Description**
Name	Invws-Inter-Prd-Rule-Ude
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

RULEID

Attribute	**Description**
Name	RULEID
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

UDEID

Attribute	**Description**
Name	UDEID
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

UDEVALUE

Attribute	**Description**
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

Intbs-Inter-Event-Log

Attribute	**Description**
Name	Intbs-Inter-Event-Log
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

INTERMEDIARYCODE

Attribute	**Description**
Name	INTERMEDIARYCODE
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

BRANCHCODE

Attribute	**Description**
Name	BRANCHCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

EVENTCODE

Attribute	**Description**
Name	EVENTCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

EVENT_DATE

Attribute	**Description**
Name	EVENT_DATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

EVENTNO

Attribute	**Description**
Name	EVENTNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22

Invws-Event-Ac-Entries

Attribute	Description
Name	Invws-Event-Ac-Entries
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

ESN

Attribute	Description
Name	ESN
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

ACCOUNTNUMBER

Attribute	Description
Name	ACCOUNTNUMBER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

BRNLCY

Attribute	Description
Name	BRNLCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: maxLength / 3

FCYAMT

Attribute	Description
Name	FCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

DATE

Attribute	Description
Name	DATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

VALDT

Attribute	Description
Name	VALDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

Intbs-Inter-Event-Adv

Attribute	Description
Name	Intbs-Inter-Event-Adv
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

INTERMEDIARYCODE

Attribute	**Description**
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

BRANCHCODE

Attribute	**Description**
Name	BRANCHCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

EVENTNO

Attribute	**Description**
Name	EVENTNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

MSGTYPE

Attribute	**Description**
Name	MSGTYPE
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 25

SUPPRESS

Attribute	**Description**
Name	SUPPRESS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

PRTYID

Attribute	**Description**
Name	PRTYID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

CustAcc

Attribute	**Description**
Name	CustAcc
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFRATE

Attribute	Description
Name	REFRATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>1,2,3,4,5,6,7,8,9,</td></tr></table>

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

MisAccLog

Attribute	Description
Name	MisAccLog
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String

Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

MisBalLog

Attribute	Description
Name	MisBalLog
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRN

Attribute	Description
Name	BRN
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

MISCLS

Attribute	**Description**
Name	MISCLS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

OLDMISCD

Attribute	**Description**
Name	OLDMISCD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

NWMISCD

Attribute	**Description**
Name	NWMISCD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TRNIND

Attribute	**Description**
Name	TRNIND
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 1

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

XRATE

Attribute	**Description**
Name	XRATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

AMT

Attribute	**Description**
Name	AMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

Chglog

Attribute	**Description**
Name	Chglog
Datatype	
Description	

Attribute	
	Attribute / **Description** minOccurs / 0

Classname

Attribute	Description
Name	Classname
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

C2

Attribute	Description
Name	C2
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

C3

Attribute	Description
Name	C3
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

C4

Attribute	Description
Name	C4
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

C6

Attribute	Description
Name	C6
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C7

Attribute	Description
Name	C7
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C8

Attribute	Description
Name	C8
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C9

Attribute	Description
Name	C9
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C10

Attribute	Description
Name	C10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T1

Attribute	Description
Name	T1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T3

Attribute	Description
Name	T3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T5

Attribute	Description
Name	T5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T6

Attribute	Description
Name	T6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T7

Attribute	Description
Name	T7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T8

Attribute	Description
Name	T8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T9

Attribute	Description
Name	T9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T10

Attribute	Description
Name	T10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.3.2.IN-AuthorizeInIntermedMaint-Req-IO-MSG.xsd

AUTHORIZEININTERMEDMAINT_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-IO

INTERMEDIARYCODE

CHECKER

CHECKERSTAMP

MODNO

AUTHORIZEININTERMEDMAINT_IOPK_REQ

Attribute	Description
Name	AUTHORIZEININTERMEDMAINT_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-IO

Attribute	Description
Name	Intms-Intermediary-IO
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	Description

Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

2.3.3.IN-AuthorizeInIntermedMaint-Res-Full-MSG.xsd

AUTHORIZEININTERMEDMAINT_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-Full

INTERMEDIARYCODE

INTERMEDIARYSTATUS

INTERMEDIARYCATEGORY

LEVELNUMBER

PARENTINTERMEDIARYCODE

PARENTINTERMEDIARYNAME

ADDRESS1

ADDRESS2

ADDRESS3

COUNTRY

TELEPHONE

EMAILID

ZIP

FAX

MOBILE

INTERMEDIARYCUSTNO

TYPE

CLCTAGENTID

STATEMENTFREQUENCY

STATEMENTSTARTMONTH

STATEMENTSTARTDATE

STATEMENTFREQUENCYUNIT

LASTSTATEMENTDATE

NEXTSTATEMENTDATE

INTERMEDIARYNAME

PRIMARYCONTACT

EFFECTIVEDATE

BRANCHCODE

LIQUIDATIONMODE

MINIMUMLIQAMT

CASCADETILL

ROOTINTM

CASCADE_CHILDS

GRPCD

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Intms-Inter-Settlement

- *SETTLE_MODE*
- *UPLDSRC*
- *CLGPRODDR*
- *ENDPOINT*
- *ROUTINGNO*
- *EXTACCBNK2*
- *EXT_BRN_CODE*
- *INSTRUMENTNO*
- *SECTORCODE*
- *EXTACCNAME*
- *EXTACCNUMBER*
- *CTG_PROD_CAT*
- *PAYABLEBANK*
- *PAYABLEBRANCH*

SETTLEPRD

SETLCCY

SETLACCBRN

STTLACC

Intms-Inter-Prd-Linkage

PRODUCTCODE

PRODUCT_DESC

LASTSETTLEMENTDT

LASTPROCESSINGDATE

NEXTPROCESSINGDATE

MIN_HIERARCHY_COMM

HERRCOMM

Intbs-Inter-Ude-Values

UDEID

UDETYPE

UDEVALUE

INTERMEDIARYPRODUCTCODE

INTERMEDIARYCODE

RULEID

Invws-Inter-Prd-Rule-Ude

RULEID

UDEID

UDEVALUE

Intbs-Inter-Event-Log

INTERMEDIARYCODE

BRANCHCODE

EVENTCODE

EVENT_DATE

EVENTNO

Invws-Event-Ac-Entries

FCCREF

ESN

BRANCHCODE

ACCOUNTNUMBER

BRNLCY

DRCRIND

CODE

FCYAMT

EXRATE

LCYAMT

DATE

VALDT

AMTTAG

EVENT

Intbs-Inter-Event-Adv

EVENTCODE

INTERMEDIARYCODE

BRANCHCODE

EVENTNO

MSGTYPE

SUPPRESS

PRIORITY

PRTYID

CustAcc

BRN

ACC

Misdetails

MISGRP

POOLCD

REFRATE

REFRTTYPE

MISGRPTXN

REFRTCD

REFRTSPRD

CALCMETH

TXNMIS1

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

TXNMIS10

MISGRPCOMP

COMPMIS1

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

COMPMIS10

COSTCOD1

COSTCOD2

COSTCOD3

COSTCOD4

COSTCOD5

RTFLAG

LINKGRP

MisAccLog

- *MISCLS*
- *TXNDT*

OLDMISCD

NWMISCD

MisBalLog

BRN

PRDCD

FINYR

TXNDT

GLCODE

MISCLS

OLDMISCD

NWMISCD

TRNIND

CCY

XRATE

AMT

Chglog

Classname

C2

C3

C4

C6

C7

C8

C9

C10

T1

T3

T5

T6

T7

T8

T9

T10

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZEININTERMEDMAINT_FSFS_RES

Attribute	Description
Name	AUTHORIZEININTERMEDMAINT_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-Full

Attribute	Description

Name	Intms-Intermediary-Full
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

INTERMEDIARYSTATUS

Attribute	Description
Name	INTERMEDIARYSTATUS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

INTERMEDIARYCATEGORY

Attribute	Description
Name	INTERMEDIARYCATEGORY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,G,

LEVELNUMBER

Attribute	Description
Name	LEVELNUMBER
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22

PARENTINTERMEDIARYCODE

Attribute	Description
Name	PARENTINTERMEDIARYCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

PARENTINTERMEDIARYNAME

Attribute	Description
Name	PARENTINTERMEDIARYNAME
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	32

ADDRESS1

Attribute	Description
Name	ADDRESS1
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	100

ADDRESS2

Attribute	Description
Name	ADDRESS2
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	100

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	100

COUNTRY

Attribute	Description
Name	COUNTRY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

TELEPHONE

Attribute	Description
Name	TELEPHONE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	16

EMAILID

Attribute	Description
Name	EMAILID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	30

ZIP

Attribute	Description
Name	ZIP
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	14

FAX

Attribute	Description
Name	FAX
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	16

MOBILE

Attribute	Description
Name	MOBILE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	10

INTERMEDIARYCUSTNO

Attribute	Description
Name	INTERMEDIARYCUSTNO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

TYPE

Attribute	Description
Name	TYPE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	I,E

CLCTAGENTID

Attribute	Description
Name	CLCTAGENTID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

STATEMENTFREQUENCY

Attribute	Description
Name	STATEMENTFREQUENCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	D,W,M,Y,

STATEMENTSTARTMONTH

Attribute	Description
Name	STATEMENTSTARTMONTH
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

STATEMENTSTARTDATE

Attribute	Description
Name	STATEMENTSTARTDATE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

STATEMENTFREQUENCYUNIT

Attribute	Description
Name	STATEMENTFREQUENCYUNIT
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

LASTSTATEMENTDATE

Attribute	Description
Name	LASTSTATEMENTDATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

NEXTSTATEMENTDATE

Attribute	Description
Name	NEXTSTATEMENTDATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

INTERMEDIARYNAME

Attribute	Description

Name	INTERMEDIARYNAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

PRIMARYCONTACT

Attribute	**Description**
Name	PRIMARYCONTACT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

EFFECTIVEDATE

Attribute	**Description**
Name	EFFECTIVEDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

BRANCHCODE

Attribute	**Description**
Name	BRANCHCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

LIQUIDATIONMODE

Attribute	**Description**
Name	LIQUIDATIONMODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	A,M,

MINIMUMLIQAMT

Attribute	Description
Name	MINIMUMLIQAMT
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CASCADETILL

Attribute	Description
Name	CASCADETILL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	I,R,

ROOTINTM

Attribute	Description
Name	ROOTINTM
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CASCADE_CHILDS

Attribute	Description
Name	CASCADE_CHILDS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: enumeration / Y,N

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	4

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

Intms-Inter-Settlement

Attribute	Description
Name	Intms-Inter-Settlement
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

SETTLE_MODE

Attribute	Description
Name	SETTLE_MODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	ACC,EAC,

UPLDSRC

Attribute	Description
Name	UPLDSRC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

CLGPRODDR

Attribute	Description
Name	CLGPRODDR
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

EXTACCBNK2

Attribute	Description
Name	EXTACCBNK2
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

EXT_BRN_CODE

Attribute	Description
Name	EXT_BRN_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

INSTRUMENTNO

Attribute	Description
Name	INSTRUMENTNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

SECTORCODE

Attribute	Description
Name	SECTORCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

EXTACCNAME

Attribute	Description
Name	EXTACCNAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

EXTACCNUMBER

Attribute	Description
Name	EXTACCNUMBER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

CTG_PROD_CAT

Attribute	Description
Name	CTG_PROD_CAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

PAYABLEBANK

Attribute	Description
Name	PAYABLEBANK
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

PAYABLEBRANCH

Attribute	Description
Name	PAYABLEBRANCH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

SETTLEPRD

Attribute	Description
Name	SETTLEPRD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

SETLCCY

Attribute	Description
Name	SETLCCY
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

SETLACCBRN

Attribute	Description
Name	SETLACCBRN
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

STTLACC

Attribute	Description
Name	STTLACC
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

Intms-Inter-Prd-Linkage

Attribute	Description
Name	Intms-Inter-Prd-Linkage
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PRODUCTCODE

Attribute	Description
Name	PRODUCTCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

PRODUCT_DESC

Attribute	Description
Name	PRODUCT_DESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

LASTSETTLEMENTDT

Attribute	Description
Name	LASTSETTLEMENTDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

LASTPROCESSINGDATE

Attribute	Description
Name	LASTPROCESSINGDATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

NEXTPROCESSINGDATE

Attribute	Description
Name	NEXTPROCESSINGDATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

MIN_HIERARCHY_COMM

Attribute	Description
Name	MIN_HIERARCHY_COMM
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

HERRCOMM

Attribute	Description
Name	HERRCOMM
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>100</td></tr></table>

Intbs-Inter-Ude-Values

Attribute	Description
Name	Intbs-Inter-Ude-Values
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

UDETYPE

Attribute	Description
Name	UDETYPE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

UDEVALUE

Attribute	Description
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

INTERMEDIARYPRODUCTCODE

Attribute	Description
Name	INTERMEDIARYPRODUCTCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

RULEID

Attribute	Description
Name	RULEID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

Invws-Inter-Prd-Rule-Ude

Attribute	Description
Name	Invws-Inter-Prd-Rule-Ude
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

RULEID

Attribute	Description
Name	RULEID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

UDEVALUE

Attribute	Description
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

Intbs-Inter-Event-Log

Attribute	Description
Name	Intbs-Inter-Event-Log
Datatype	

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	String
Description	

Attribute	

Attribute	Description
minOccurs	0

EVENTNO

Attribute	Description
Name	EVENTNO
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

Invws-Event-Ac-Entries

Attribute	Description
Name	Invws-Event-Ac-Entries
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

ESN

Attribute	Description
Name	ESN
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

ACCOUNTNUMBER

Attribute	Description
Name	ACCOUNTNUMBER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

BRNLCY

Attribute	Description
Name	BRNLCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: maxLength / 1

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

FCYAMT

Attribute	Description
Name	FCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22

DATE

Attribute	Description
Name	DATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

VALDT

Attribute	Description
Name	VALDT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

Intbs-Inter-Event-Adv

Attribute	Description

Name	Intbs-Inter-Event-Adv
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

EVENTCODE

Attribute	**Description**
Name	EVENTCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

INTERMEDIARYCODE

Attribute	**Description**
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

BRANCHCODE

Attribute	**Description**
Name	BRANCHCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

EVENTNO

Attribute	**Description**
Name	EVENTNO
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** totalDigits / 22

MSGTYPE

Attribute	**Description**
Name	MSGTYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

SUPPRESS

Attribute	**Description**
Name	SUPPRESS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

PRTYID

Attribute	**Description**
Name	PRTYID
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

CustAcc

Attribute	Description
Name	CustAcc
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFRATE

Attribute	Description
Name	REFRATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>1,2,3,4,5,6,7,8,9,</td></tr></table>

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

MisAccLog

Attribute	Description
Name	MisAccLog
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

MisBalLog

Attribute	Description
Name	MisBalLog
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TRNIND

Attribute	Description
Name	TRNIND
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

XRATE

Attribute	Description
Name	XRATE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

AMT

Attribute	Description
Name	AMT
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

Chglog

Attribute	**Description**
Name	Chglog
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Classname

Attribute	**Description**
Name	Classname
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

C2

Attribute	**Description**
Name	C2
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

C3

Attribute	**Description**
Name	C3
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

C4

Attribute	Description
Name	C4
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C6

Attribute	Description
Name	C6
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C7

Attribute	Description
Name	C7
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C8

Attribute	Description
Name	C8
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C9

Attribute	Description
Name	C9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

C10

Attribute	Description
Name	C10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T1

Attribute	Description
Name	T1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T3

Attribute	Description
Name	T3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T5

Attribute	Description
Name	T5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T6

Attribute	Description
Name	T6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T7

Attribute	Description
Name	T7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T8

Attribute	Description
Name	T8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T9

Attribute	Description
Name	T9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T10

Attribute	Description
Name	T10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.3.4.IN-AuthorizeInIntermedMaint-Res-PK-MSG.xsd

AUTHORIZEININTERMEDMAINT_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-PK

INTERMEDIARYCODE

Intms-Intermediary-IO

INTERMEDIARYCODE

CHECKER

CHECKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZEININTERMEDMAINT_IOPK_RES

Attribute	Description
Name	AUTHORIZEININTERMEDMAINT_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-PK

Attribute	Description
Name	Intms-Intermediary-PK
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

Intms-Intermediary-IO

Attribute	Description
Name	Intms-Intermediary-IO
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	16

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String

Description	

2.4.CreateINextudval

2.4.1.IN-CreateINextudval-Req-Full-MSG.xsd

- *CREATEINEXTUDVAL_FSFS_REQ*
  - *FCUBS_HEADER*
    - *SOURCE*
    - *UBSCOMP*
    - *MSGID*
    - *CORRELID*
    - *USERID*
    - *BRANCH*
    - *MODULEID*
    - *SERVICE*
    - *OPERATION*
    - *SOURCE_OPERATION*
    - *SOURCE_USERID*
    - *DESTINATION*
    - *MULTITRIPID*
    - *FUNCTIONID*
    - *ACTION*
    - *MSGSTAT*
    - *PASSWORD*
    - *ADDL*
      - *PARAM*
        - *NAME*
        - *VALUE*
  - *FCUBS_BODY*
    - *Intms-Inter-Ext-Ude-Full*
      - *INTERMEDIARYCODE*
      - *UDEFFDT*
      - *MAKER*
      - *MAKERSTAMP*

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Intms-Inter-Ext-Prdlink

PRODUCTCODE

PRODUCT_DESC

UDEEFFDT

Intms-Inter-Ext-Ude-Values

UDEID

UDEVALUE

RULEID

UDETYPE

UDECCY

CREATEINEXTUDVAL_FSFS_REQ

Attribute	Description
Name	CREATEINEXTUDVAL_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	**Description**
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.

Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Intms-Inter-Ext-Ude-Full
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

UDEFFDT

Attribute	Description
Name	UDEFFDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	4

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: maxLength / 1

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

Intms-Inter-Ext-Prdlink

Attribute	Description
Name	Intms-Inter-Ext-Prdlink
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

PRODUCTCODE

Attribute	Description
Name	PRODUCTCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

PRODUCT_DESC

Attribute	Description
Name	PRODUCT_DESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: maxLength / 50

UDEEFFDT

Attribute	Description
Name	UDEEFFDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Intms-Inter-Ext-Ude-Values

Attribute	Description
Name	Intms-Inter-Ext-Ude-Values
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

UDEVALUE

Attribute	Description
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

RULEID

Attribute	Description

Name	RULEID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

UDETYPE

Attribute	**Description**
Name	UDETYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / R,A,N,

UDECCY

Attribute	**Description**
Name	UDECCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

2.4.2.IN-CreateINextudval-Req-IO-MSG.xsd

CREATEINEXTUDVAL_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Inter-Ext-Ude-IO

INTERMEDIARYCODE

UDEFFDT

Intms-Inter-Ext-Prdlink

PRODUCTCODE

PRODUCT_DESC

UDEEFFDT

Intms-Inter-Ext-Ude-Values

UDEID

UDEVALUE

RULEID

CREATEINEXTUDVAL_IOPK_REQ

Attribute	Description
Name	CREATEINEXTUDVAL_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Inter-Ext-Ude-IO

Attribute	Description
Name	Intms-Inter-Ext-Ude-IO
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

UDEFFDT

Attribute	Description
Name	UDEFFDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Intms-Inter-Ext-Prdlink

Attribute	Description
Name	Intms-Inter-Ext-Prdlink
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PRODUCTCODE

Attribute	Description
Name	PRODUCTCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

PRODUCT_DESC

Attribute	Description
Name	PRODUCT_DESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	50

UDEEFFDT

Attribute	Description
Name	UDEEFFDT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Intms-Inter-Ext-Ude-Values

Attribute	Description
Name	Intms-Inter-Ext-Ude-Values
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

UDEVALUE

Attribute	Description
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

RULEID

Attribute	Description
Name	RULEID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

2.4.3.IN-CreateINextudval-Res-Full-MSG.xsd

CREATEINEXTUDVAL_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Inter-Ext-Ude-Full

INTERMEDIARYCODE

UDEFFDT

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Intms-Inter-Ext-Prdlink

PRODUCTCODE

PRODUCT_DESC

UDEEFFDT

Intms-Inter-Ext-Ude-Values

UDEID

UDEVALUE

RULEID

UDETYPE

UDECCY

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATEINEXTUDVAL_FSFS_RES

Attribute	Description
Name	CREATEINEXTUDVAL_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	

Intms-Inter-Ext-Ude-Full

Attribute	**Description**

Name	Intms-Inter-Ext-Ude-Full
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

UDEFFDT

Attribute	Description
Name	UDEFFDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Intms-Inter-Ext-Prdlink

Attribute	Description
Name	Intms-Inter-Ext-Prdlink
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PRODUCTCODE

Attribute	Description
Name	PRODUCTCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

PRODUCT_DESC

Attribute	Description
Name	PRODUCT_DESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

UDEEFFDT

Attribute	Description
Name	UDEEFFDT
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Intms-Inter-Ext-Ude-Values

Attribute	Description
Name	Intms-Inter-Ext-Ude-Values
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

UDEVALUE

Attribute	Description
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

RULEID

Attribute	Description
Name	RULEID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	16

UDETYPE

Attribute	Description
Name	UDETYPE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	R,A,N,

UDECCY

Attribute	Description
Name	UDECCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description

Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.4.4.IN-CreateINextudval-Res-PK-MSG.xsd

CREATEINEXTUDVAL_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Inter-Ext-Ude-PK

INTERMEDIARYCODE

UDEFFDT

Intms-Inter-Ext-Ude-IO

INTERMEDIARYCODE

UDEFFDT

Intms-Inter-Ext-Prdlink

PRODUCTCODE

PRODUCT_DESC

UDEEFFDT

Intms-Inter-Ext-Ude-Values

UDEID

UDEVALUE

RULEID

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATEINEXTUDVAL_IOPK_RES

Attribute	Description
Name	CREATEINEXTUDVAL_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Inter-Ext-Ude-PK

Attribute	Description
Name	Intms-Inter-Ext-Ude-PK
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description

Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

UDEFFDT

Attribute	Description
Name	UDEFFDT
Datatype	String
Description	

Intms-Inter-Ext-Ude-IO

Attribute	Description
Name	Intms-Inter-Ext-Ude-IO
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

UDEFFDT

Attribute	Description
Name	UDEFFDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Intms-Inter-Ext-Prdlink

Attribute	Description
Name	Intms-Inter-Ext-Prdlink
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PRODUCTCODE

Attribute	Description
Name	PRODUCTCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

PRODUCT_DESC

Attribute	Description
Name	PRODUCT_DESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	50

UDEEFFDT

Attribute	Description
Name	UDEEFFDT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Intms-Inter-Ext-Ude-Values

Attribute	Description
Name	Intms-Inter-Ext-Ude-Values
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

UDEVALUE

Attribute	Description
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

RULEID

Attribute	Description
Name	RULEID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.5.CreateINGroup

2.5.1.IN-CreateINGroup-Req-Full-MSG.xsd

CREATEINGROUP_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-Group-Full

GRPCD

GROUPDESC

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

CREATEINGROUP_FSFS_REQ

Attribute	Description
Name	CREATEINGROUP_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description**: minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL

Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-Group-Full

Attribute	Description
Name	Intms-Intermediary-Group-Full
Datatype	
Description	

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

GROUPDESC

Attribute	Description

Name	GROUPDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	**Description**

Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

2.5.2.IN-CreateINGroup-Req-IO-MSG.xsd

CREATEINGROUP_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-Group-IO

GRPCD

GROUPDESC

CREATEINGROUP_IOPK_REQ

Attribute	Description
Name	CREATEINGROUP_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-Group-IO

Attribute	Description
Name	Intms-Intermediary-Group-IO
Datatype	
Description	

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

GROUPDESC

Attribute	Description
Name	GROUPDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

2.5.3.IN-CreateINGroup-Res-Full-MSG.xsd

CREATEINGROUP_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-Group-Full

GRPCD

GROUPDESC

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATEINGROUP_FSFS_RES

Attribute	Description
Name	CREATEINGROUP_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.

Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-Group-Full

Attribute	Description
Name	Intms-Intermediary-Group-Full
Datatype	
Description	

GRPCD

Attribute	Description

Name	GRPCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

GROUPDESC

Attribute	**Description**
Name	GROUPDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.5.4.IN-CreateINGroup-Res-PK-MSG.xsd

CREATEINGROUP_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-Group-PK

GRPCD

Intms-Intermediary-Group-IO

GRPCD

GROUPDESC

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATEINGROUP_IOPK_RES

Attribute	Description
Name	CREATEINGROUP_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description

Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String

Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-Group-PK

Attribute	Description
Name	Intms-Intermediary-Group-PK
Datatype	
Description	

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	4

Intms-Intermediary-Group-IO

Attribute	Description
Name	Intms-Intermediary-Group-IO
Datatype	
Description	

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	4

GROUPDESC

Attribute	Description
Name	GROUPDESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	50

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.6.CreateInIntermedMaint

2.6.1.IN-CreateInIntermedMaint-Req-Full-MSG.xsd

CREATEININTERMEDMAINT_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-Full

INTERMEDIARYCODE

INTERMEDIARYSTATUS

INTERMEDIARYCATEGORY

LEVELNUMBER

PARENTINTERMEDIARYCODE

PARENTINTERMEDIARYNAME

ADDRESS1

ADDRESS2

ADDRESS3

COUNTRY

TELEPHONE

EMAILID

ZIP

FAX

MOBILE

INTERMEDIARYCUSTNO

TYPE

CLCTAGENTID

STATEMENTFREQUENCY

STATEMENTSTARTMONTH

STATEMENTSTARTDATE

STATEMENTFREQUENCYUNIT

LASTSTATEMENTDATE

NEXTSTATEMENTDATE

INTERMEDIARYNAME

PRIMARYCONTACT

EFFECTIVEDATE

BRANCHCODE

LIQUIDATIONMODE

MINIMUMLIQAMT

CASCADETILL

ROOTINTM

CASCADE_CHILDS

GRPCD

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Intms-Inter-Settlement

- *SETTLE_MODE*
- *UPLDSRC*
- *CLGPRODDR*
- *ENDPOINT*
- *ROUTINGNO*
- *EXTACCBNK2*
- *EXT_BRN_CODE*
- *INSTRUMENTNO*
- *SECTORCODE*
- *EXTACCNAME*
- *EXTACCNUMBER*
- *CTG_PROD_CAT*
- *PAYABLEBANK*
- *PAYABLEBRANCH*
- *SETTLEPRD*
- *SETLCCY*
- *SETLACCBRN*
- *STTLACC*

Intms-Inter-Prd-Linkage

- *PRODUCTCODE*
- *PRODUCT_DESC*

LASTSETTLEMENTDT

LASTPROCESSINGDATE

NEXTPROCESSINGDATE

MIN_HIERARCHY_COMM

HERRCOMM

Intbs-Inter-Ude-Values

UDEID

UDETYPE

UDEVALUE

INTERMEDIARYPRODUCTCODE

INTERMEDIARYCODE

RULEID

Invws-Inter-Prd-Rule-Ude

RULEID

UDEID

UDEVALUE

Intbs-Inter-Event-Log

INTERMEDIARYCODE

BRANCHCODE

EVENTCODE

EVENT_DATE

EVENTNO

Invws-Event-Ac-Entries

FCCREF

ESN

BRANCHCODE

ACCOUNTNUMBER

BRNLCY

DRCRIND

CODE

FCYAMT

EXRATE

LCYAMT

DATE

VALDT

AMTTAG

EVENT

Intbs-Inter-Event-Adv

EVENTCODE

INTERMEDIARYCODE

BRANCHCODE

EVENTNO

MSGTYPE

SUPPRESS

PRIORITY

PRTYID

CustAcc

BRN

ACC

Misdetails

MISGRP

POOLCD

REFRATE

REFRTTYPE

MISGRPTXN

REFRTCD

REFRTSPRD

CALCMETH

TXNMIS1

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

TXNMIS10

MISGRPCOMP

COMPMIS1

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

COMPMIS10

COSTCOD1

COSTCOD2

COSTCOD3

COSTCOD4

COSTCOD5

RTFLAG

LINKGRP

MisAccLog

- *MISCLS*
- *TXNDT*
- *OLDMISCD*
- *NWMISCD*

MisBalLog

- *BRN*
- *PRDCD*
- *FINYR*
- *TXNDT*

GLCODE

MISCLS

OLDMISCD

NWMISCD

TRNIND

CCY

XRATE

AMT

Chglog

Classname

C2

C3

C4

C6

C7

C8

C9

C10

T1

T3

T5

T6

T7

T8

T9

T10

UDFDETAILS

FLDNAM

FLDVAL

CREATEININTERMEDMAINT_FSFS_REQ

Attribute	Description
Name	CREATEININTERMEDMAINT_FSFS_REQ

Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-Full

Attribute	Description
Name	Intms-Intermediary-Full
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

INTERMEDIARYSTATUS

Attribute	Description
Name	INTERMEDIARYSTATUS
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

INTERMEDIARYCATEGORY

Attribute	**Description**
Name	INTERMEDIARYCATEGORY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,G,

LEVELNUMBER

Attribute	**Description**
Name	LEVELNUMBER
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

PARENTINTERMEDIARYCODE

Attribute	**Description**
Name	PARENTINTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

PARENTINTERMEDIARYNAME

Attribute	**Description**
Name	PARENTINTERMEDIARYNAME
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

ADDRESS1

Attribute	**Description**
Name	ADDRESS1
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

ADDRESS2

Attribute	**Description**
Name	ADDRESS2
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

ADDRESS3

Attribute	**Description**
Name	ADDRESS3
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

COUNTRY

Attribute	**Description**
Name	COUNTRY
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

TELEPHONE

Attribute	Description
Name	TELEPHONE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>16</td></tr></table>

EMAILID

Attribute	Description
Name	EMAILID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

ZIP

Attribute	Description
Name	ZIP
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>14</td></tr></table>

FAX

Attribute	Description
Name	FAX
Datatype	Decimal
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>16</td></tr></table>

MOBILE

Attribute	Description
Name	MOBILE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>10</td></tr></table>

INTERMEDIARYCUSTNO

Attribute	Description
Name	INTERMEDIARYCUSTNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

TYPE

Attribute	Description
Name	TYPE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>I,E</td></tr></table>

CLCTAGENTID

Attribute	Description
Name	CLCTAGENTID
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

STATEMENTFREQUENCY

Attribute	**Description**
Name	STATEMENTFREQUENCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Y,

STATEMENTSTARTMONTH

Attribute	**Description**
Name	STATEMENTSTARTMONTH
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

STATEMENTSTARTDATE

Attribute	**Description**
Name	STATEMENTSTARTDATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

STATEMENTFREQUENCYUNIT

Attribute	**Description**
Name	STATEMENTFREQUENCYUNIT
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

LASTSTATEMENTDATE

Attribute	**Description**
Name	LASTSTATEMENTDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

NEXTSTATEMENTDATE

Attribute	**Description**
Name	NEXTSTATEMENTDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

INTERMEDIARYNAME

Attribute	**Description**
Name	INTERMEDIARYNAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

PRIMARYCONTACT

Attribute	**Description**
Name	PRIMARYCONTACT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

EFFECTIVEDATE

Attribute	Description
Name	EFFECTIVEDATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

LIQUIDATIONMODE

Attribute	Description
Name	LIQUIDATIONMODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,M,</td></tr></table>

MINIMUMLIQAMT

Attribute	Description
Name	MINIMUMLIQAMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CASCADETILL

Attribute	Description
Name	CASCADETILL
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,R,

ROOTINTM

Attribute	**Description**
Name	ROOTINTM
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CASCADE_CHILDS

Attribute	**Description**
Name	CASCADE_CHILDS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

GRPCD

Attribute	**Description**
Name	GRPCD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

Intms-Inter-Settlement

Attribute	**Description**
Name	Intms-Inter-Settlement
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

SETTLE_MODE

Attribute	**Description**
Name	SETTLE_MODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	ACC,EAC,

UPLDSRC

Attribute	Description
Name	UPLDSRC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

CLGPRODDR

Attribute	Description
Name	CLGPRODDR
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

EXTACCBNK2

Attribute	Description
Name	EXTACCBNK2
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

EXT_BRN_CODE

Attribute	Description
Name	EXT_BRN_CODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

INSTRUMENTNO

Attribute	Description
Name	INSTRUMENTNO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

SECTORCODE

Attribute	Description
Name	SECTORCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

EXTACCNAME

Attribute	Description
Name	EXTACCNAME
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

EXTACCNUMBER

Attribute	Description
Name	EXTACCNUMBER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

CTG_PROD_CAT

Attribute	Description
Name	CTG_PROD_CAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

PAYABLEBANK

Attribute	Description
Name	PAYABLEBANK
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 4

PAYABLEBRANCH

Attribute	**Description**
Name	PAYABLEBRANCH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

SETTLEPRD

Attribute	**Description**
Name	SETTLEPRD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

SETLCCY

Attribute	**Description**
Name	SETLCCY
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 3

SETLACCBRN

Attribute	**Description**
Name	SETLACCBRN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 4

STTLACC

Attribute	**Description**

Name	STTLACC
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 20

Intms-Inter-Prd-Linkage

Attribute	**Description**
Name	Intms-Inter-Prd-Linkage
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

PRODUCTCODE

Attribute	**Description**
Name	PRODUCTCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

PRODUCT_DESC

Attribute	**Description**
Name	PRODUCT_DESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

LASTSETTLEMENTDT

Attribute	**Description**
Name	LASTSETTLEMENTDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

LASTPROCESSINGDATE

Attribute	Description
Name	LASTPROCESSINGDATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

NEXTPROCESSINGDATE

Attribute	Description
Name	NEXTPROCESSINGDATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

MIN_HIERARCHY_COMM

Attribute	Description
Name	MIN_HIERARCHY_COMM
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

HERRCOMM

Attribute	Description
Name	HERRCOMM
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>100</td></tr></table>

Intbs-Inter-Ude-Values

Attribute	Description
Name	Intbs-Inter-Ude-Values
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

UDETYPE

Attribute	Description
Name	UDETYPE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

UDEVALUE

Attribute	Description
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

INTERMEDIARYPRODUCTCODE

Attribute	Description
Name	INTERMEDIARYPRODUCTCODE
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

INTERMEDIARYCODE

Attribute	**Description**
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

RULEID

Attribute	**Description**
Name	RULEID
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

Invws-Inter-Prd-Rule-Ude

Attribute	**Description**
Name	Invws-Inter-Prd-Rule-Ude
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

RULEID

Attribute	**Description**
Name	RULEID
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

UDEID

Attribute	**Description**
Name	UDEID
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

UDEVALUE

Attribute	**Description**
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

Intbs-Inter-Event-Log

Attribute	**Description**
Name	Intbs-Inter-Event-Log
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

INTERMEDIARYCODE

Attribute	**Description**
Name	INTERMEDIARYCODE
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

BRANCHCODE

Attribute	**Description**
Name	BRANCHCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

EVENTCODE

Attribute	**Description**
Name	EVENTCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

EVENT_DATE

Attribute	**Description**
Name	EVENT_DATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

EVENTNO

Attribute	**Description**
Name	EVENTNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22

Invws-Event-Ac-Entries

Attribute	Description
Name	Invws-Event-Ac-Entries
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

ESN

Attribute	Description
Name	ESN
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: maxLength / 3

ACCOUNTNUMBER

Attribute	Description
Name	ACCOUNTNUMBER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

BRNLCY

Attribute	Description
Name	BRNLCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	3

FCYAMT

Attribute	Description
Name	FCYAMT
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

DATE

Attribute	Description
Name	DATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

VALDT

Attribute	Description
Name	VALDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

Intbs-Inter-Event-Adv

Attribute	Description
Name	Intbs-Inter-Event-Adv
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	

Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

INTERMEDIARYCODE

Attribute	**Description**
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

BRANCHCODE

Attribute	**Description**
Name	BRANCHCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

EVENTNO

Attribute	**Description**
Name	EVENTNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

MSGTYPE

Attribute	**Description**
Name	MSGTYPE
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** maxLength / 25

SUPPRESS

Attribute	**Description**
Name	SUPPRESS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

PRTYID

Attribute	**Description**
Name	PRTYID
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

CustAcc

Attribute	**Description**
Name	CustAcc
Datatype	
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFRATE

Attribute	Description
Name	REFRATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>1,2,3,4,5,6,7,8,9,</td></tr></table>

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

MisAccLog

Attribute	Description
Name	MisAccLog
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String

Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

MisBalLog

Attribute	Description
Name	MisBalLog
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRN

Attribute	Description
Name	BRN
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TRNIND

Attribute	Description
Name	TRNIND
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

XRATE

Attribute	Description
Name	XRATE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

AMT

Attribute	Description
Name	AMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

Chglog

Attribute	Description
Name	Chglog
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0

Classname

Attribute	Description
Name	Classname
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

C2

Attribute	Description
Name	C2
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

C3

Attribute	Description
Name	C3
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

C4

Attribute	Description
Name	C4
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

C6

Attribute	Description
Name	C6
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C7

Attribute	Description
Name	C7
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C8

Attribute	Description
Name	C8
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C9

Attribute	Description
Name	C9
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C10

Attribute	Description
Name	C10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T1

Attribute	Description
Name	T1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T3

Attribute	Description
Name	T3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T5

Attribute	Description
Name	T5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T6

Attribute	Description
Name	T6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T7

Attribute	Description
Name	T7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T8

Attribute	Description
Name	T8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T9

Attribute	Description
Name	T9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T10

Attribute	Description
Name	T10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.6.2.IN-CreateInIntermedMaint-Req-IO-MSG.xsd

CREATEININTERMEDMAINT_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-IO

INTERMEDIARYCODE

INTERMEDIARYSTATUS

INTERMEDIARYCATEGORY

ADDRESS1

ADDRESS2

ADDRESS3

TELEPHONE

EMAILID

ZIP

FAX

MOBILE

TYPE

CLCTAGENTID

STATEMENTFREQUENCY

STATEMENTSTARTMONTH

STATEMENTSTARTDATE

STATEMENTFREQUENCYUNIT

INTERMEDIARYNAME

PRIMARYCONTACT

LIQUIDATIONMODE

MINIMUMLIQAMT

CASCADETILL

ROOTINTM

CASCADE_CHILDS

GRPCD

Intms-Inter-Settlement

- *SETTLE_MODE*
- *UPLDSRC*
- *ENDPOINT*
- *ROUTINGNO*
- *INSTRUMENTNO*
- *SECTORCODE*
- *EXTACCNAME*
- *EXTACCNUMBER*
- *PAYABLEBANK*
- *PAYABLEBRANCH*
- *SETTLEPRD*

Intms-Inter-Prd-Linkage

- *MIN_HIERARCHY_COMM*
- *HERRCOMM*
- *Intbs-Inter-Ude-Values*
  - *UDETYPE*
  - *UDEVALUE*

INTERMEDIARYPRODUCTCODE

INTERMEDIARYCODE

Invws-Inter-Prd-Rule-Ude

RULEID

UDEID

UDEVALUE

Intbs-Inter-Event-Log

INTERMEDIARYCODE

BRANCHCODE

EVENTCODE

EVENT_DATE

EVENTNO

Invws-Event-Ac-Entries

FCCREF

ESN

BRANCHCODE

ACCOUNTNUMBER

BRNLCY

DRCRIND

CODE

FCYAMT

EXRATE

LCYAMT

DATE

VALDT

AMTTAG

EVENT

Intbs-Inter-Event-Adv

EVENTCODE

INTERMEDIARYCODE

BRANCHCODE

EVENTNO

MSGTYPE

SUPPRESS

PRIORITY

PRTYID

CustAcc

BRN

ACC

Misdetails

MISGRP

POOLCD

REFRATE

REFRTTYPE

REFRTCD

REFRTSPRD

CALCMETH

TXNMIS1

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

TXNMIS10

COMPMIS1

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

COMPMIS10

COSTCOD1

COSTCOD2

COSTCOD3

COSTCOD4

COSTCOD5

RTFLAG

LINKGRP

MisAccLog

MISCLS

TXNDT

OLDMISCD

NWMISCD

MisBalLog

Classname

UDFDETAILS

FLDNAM

FLDVAL

CREATEININTERMEDMAINT_IOPK_REQ

Attribute	Description
Name	CREATEININTERMEDMAINT_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-IO

Attribute	Description
Name	Intms-Intermediary-IO
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

INTERMEDIARYSTATUS

Attribute	Description
Name	INTERMEDIARYSTATUS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

INTERMEDIARYCATEGORY

Attribute	Description

Name	INTERMEDIARYCATEGORY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,G,

ADDRESS1

Attribute	**Description**
Name	ADDRESS1
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

ADDRESS2

Attribute	**Description**
Name	ADDRESS2
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

ADDRESS3

Attribute	**Description**
Name	ADDRESS3
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TELEPHONE

Attribute	**Description**

Name	TELEPHONE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 16

EMAILID

Attribute	**Description**
Name	EMAILID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

ZIP

Attribute	**Description**
Name	ZIP
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 14

FAX

Attribute	**Description**
Name	FAX
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 16

MOBILE

Attribute	**Description**

Name	MOBILE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 10

TYPE

Attribute	**Description**
Name	TYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,E

CLCTAGENTID

Attribute	**Description**
Name	CLCTAGENTID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

STATEMENTFREQUENCY

Attribute	**Description**
Name	STATEMENTFREQUENCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Y,

STATEMENTSTARTMONTH

Attribute	**Description**

Name	STATEMENTSTARTMONTH
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

STATEMENTSTARTDATE

Attribute	**Description**
Name	STATEMENTSTARTDATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

STATEMENTFREQUENCYUNIT

Attribute	**Description**
Name	STATEMENTFREQUENCYUNIT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

INTERMEDIARYNAME

Attribute	**Description**
Name	INTERMEDIARYNAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

PRIMARYCONTACT

Attribute	**Description**

Name	PRIMARYCONTACT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

LIQUIDATIONMODE

Attribute	**Description**
Name	LIQUIDATIONMODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M,

MINIMUMLIQAMT

Attribute	**Description**
Name	MINIMUMLIQAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CASCADETILL

Attribute	**Description**
Name	CASCADETILL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,R,

ROOTINTM

Attribute	**Description**

Name	ROOTINTM
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CASCADE_CHILDS

Attribute	**Description**
Name	CASCADE_CHILDS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

GRPCD

Attribute	**Description**
Name	GRPCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

Intms-Inter-Settlement

Attribute	**Description**
Name	Intms-Inter-Settlement
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

SETTLE_MODE

Attribute	**Description**
Name	SETTLE_MODE
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ACC,EAC,

UPLDSRC

Attribute	**Description**
Name	UPLDSRC
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

ENDPOINT

Attribute	**Description**
Name	ENDPOINT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

ROUTINGNO

Attribute	**Description**
Name	ROUTINGNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

INSTRUMENTNO

Attribute	**Description**
Name	INSTRUMENTNO
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

SECTORCODE

Attribute	Description
Name	SECTORCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

EXTACCNAME

Attribute	Description
Name	EXTACCNAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

EXTACCNUMBER

Attribute	Description
Name	EXTACCNUMBER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

PAYABLEBANK

Attribute	Description
Name	PAYABLEBANK
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

PAYABLEBRANCH

Attribute	**Description**
Name	PAYABLEBRANCH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

SETTLEPRD

Attribute	**Description**
Name	SETTLEPRD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

Intms-Inter-Prd-Linkage

Attribute	**Description**
Name	Intms-Inter-Prd-Linkage
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

MIN_HIERARCHY_COMM

Attribute	**Description**
Name	MIN_HIERARCHY_COMM
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

HERRCOMM

Attribute	**Description**
Name	HERRCOMM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 100

Intbs-Inter-Ude-Values

Attribute	**Description**
Name	Intbs-Inter-Ude-Values
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

UDETYPE

Attribute	**Description**
Name	UDETYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

UDEVALUE

Attribute	**Description**
Name	UDEVALUE
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

INTERMEDIARYPRODUCTCODE

Attribute	**Description**
Name	INTERMEDIARYPRODUCTCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

INTERMEDIARYCODE

Attribute	**Description**
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

Invws-Inter-Prd-Rule-Ude

Attribute	**Description**
Name	Invws-Inter-Prd-Rule-Ude
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

RULEID

Attribute	**Description**
Name	RULEID
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

UDEID

Attribute	**Description**
Name	UDEID
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

UDEVALUE

Attribute	**Description**
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

Intbs-Inter-Event-Log

Attribute	**Description**
Name	Intbs-Inter-Event-Log
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

INTERMEDIARYCODE

Attribute	**Description**
Name	INTERMEDIARYCODE
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

BRANCHCODE

Attribute	**Description**
Name	BRANCHCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

EVENTCODE

Attribute	**Description**
Name	EVENTCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

EVENT_DATE

Attribute	**Description**
Name	EVENT_DATE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

EVENTNO

Attribute	**Description**
Name	EVENTNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22

Invws-Event-Ac-Entries

Attribute	Description
Name	Invws-Event-Ac-Entries
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

ESN

Attribute	Description
Name	ESN
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

ACCOUNTNUMBER

Attribute	Description
Name	ACCOUNTNUMBER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

BRNLCY

Attribute	Description
Name	BRNLCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: maxLength / 3

FCYAMT

Attribute	Description
Name	FCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

DATE

Attribute	Description
Name	DATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

VALDT

Attribute	Description
Name	VALDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

Intbs-Inter-Event-Adv

Attribute	Description
Name	Intbs-Inter-Event-Adv
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 4

INTERMEDIARYCODE

Attribute	**Description**
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

BRANCHCODE

Attribute	**Description**
Name	BRANCHCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

EVENTNO

Attribute	**Description**
Name	EVENTNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

MSGTYPE

Attribute	**Description**
Name	MSGTYPE
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

SUPPRESS

Attribute	**Description**
Name	SUPPRESS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

PRTYID

Attribute	**Description**
Name	PRTYID
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

CustAcc

Attribute	**Description**
Name	CustAcc
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFRATE

Attribute	Description
Name	REFRATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>1,2,3,4,5,6,7,8,9,</td></tr></table>

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

MisAccLog

Attribute	Description
Name	MisAccLog
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

MisBalLog

Attribute	Description
Name	MisBalLog
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

Classname

Attribute	Description
Name	Classname
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.6.3.IN-CreateInIntermedMaint-Res-Full-MSG.xsd

CREATEININTERMEDMAINT_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-Full

- *INTERMEDIARYCODE*
- *INTERMEDIARYSTATUS*
- *INTERMEDIARYCATEGORY*
- *LEVELNUMBER*
- *PARENTINTERMEDIARYCODE*
- *PARENTINTERMEDIARYNAME*
- *ADDRESS1*
- *ADDRESS2*
- *ADDRESS3*
- *COUNTRY*
- *TELEPHONE*
- *EMAILID*
- *ZIP*
- *FAX*
- *MOBILE*
- *INTERMEDIARYCUSTNO*
- *TYPE*
- *CLCTAGENTID*
- *STATEMENTFREQUENCY*
- *STATEMENTSTARTMONTH*
- *STATEMENTSTARTDATE*
- *STATEMENTFREQUENCYUNIT*
- *LASTSTATEMENTDATE*
- *NEXTSTATEMENTDATE*
- *INTERMEDIARYNAME*
- *PRIMARYCONTACT*
- *EFFECTIVEDATE*
- *BRANCHCODE*
- *LIQUIDATIONMODE*
- *MINIMUMLIQAMT*
- *CASCADETILL*

ROOTINTM

CASCADE_CHILDS

GRPCD

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Intms-Inter-Settlement

- *SETTLE_MODE*
- *UPLDSRC*
- *CLGPRODDR*
- *ENDPOINT*
- *ROUTINGNO*
- *EXTACCBNK2*
- *EXT_BRN_CODE*
- *INSTRUMENTNO*
- *SECTORCODE*
- *EXTACCNAME*
- *EXTACCNUMBER*
- *CTG_PROD_CAT*
- *PAYABLEBANK*
- *PAYABLEBRANCH*
- *SETTLEPRD*
- *SETLCCY*
- *SETLACCBRN*
- *STTLACC*

Intms-Inter-Prd-Linkage

- *PRODUCTCODE*
- *PRODUCT_DESC*

LASTSETTLEMENTDT

LASTPROCESSINGDATE

NEXTPROCESSINGDATE

MIN_HIERARCHY_COMM

HERRCOMM

Intbs-Inter-Ude-Values

UDEID

UDETYPE

UDEVALUE

INTERMEDIARYPRODUCTCODE

INTERMEDIARYCODE

RULEID

Invws-Inter-Prd-Rule-Ude

RULEID

UDEID

UDEVALUE

Intbs-Inter-Event-Log

INTERMEDIARYCODE

BRANCHCODE

EVENTCODE

EVENT_DATE

EVENTNO

Invws-Event-Ac-Entries

FCCREF

ESN

BRANCHCODE

ACCOUNTNUMBER

BRNLCY

DRCRIND

CODE

FCYAMT

EXRATE

LCYAMT

DATE

VALDT

AMTTAG

EVENT

Intbs-Inter-Event-Adv

EVENTCODE

INTERMEDIARYCODE

BRANCHCODE

EVENTNO

MSGTYPE

SUPPRESS

PRIORITY

PRTYID

CustAcc

BRN

ACC

Misdetails

MISGRP

POOLCD

REFRATE

REFRTTYPE

MISGRPTXN

REFRTCD

REFRTSPRD

CALCMETH

TXNMIS1

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

TXNMIS10

MISGRPCOMP

COMPMIS1

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

COMPMIS10

COSTCOD1

COSTCOD2

COSTCOD3

COSTCOD4

COSTCOD5

RTFLAG

LINKGRP

MisAccLog

- *MISCLS*
- *TXNDT*
- *OLDMISCD*
- *NWMISCD*

MisBalLog

- *BRN*
- *PRDCD*
- *FINYR*
- *TXNDT*

GLCODE

MISCLS

OLDMISCD

NWMISCD

TRNIND

CCY

XRATE

AMT

Chglog

Classname

C2

C3

C4

C6

C7

C8

C9

C10

T1

T3

T5

T6

T7

T8

T9

T10

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATEININTERMEDMAINT_FSFS_RES

Attribute	Description
Name	CREATEININTERMEDMAINT_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-Full

Attribute	Description
Name	Intms-Intermediary-Full
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	
	Restrictions / **Description**: maxLength / 16

INTERMEDIARYSTATUS

Attribute	**Description**
Name	INTERMEDIARYSTATUS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

INTERMEDIARYCATEGORY

Attribute	**Description**
Name	INTERMEDIARYCATEGORY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,G,

LEVELNUMBER

Attribute	**Description**
Name	LEVELNUMBER
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

PARENTINTERMEDIARYCODE

Attribute	**Description**
Name	PARENTINTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	16

PARENTINTERMEDIARYNAME

Attribute	Description
Name	PARENTINTERMEDIARYNAME
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	32

ADDRESS1

Attribute	Description
Name	ADDRESS1
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	100

ADDRESS2

Attribute	Description
Name	ADDRESS2
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	100

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	100

COUNTRY

Attribute	Description
Name	COUNTRY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

TELEPHONE

Attribute	Description
Name	TELEPHONE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	16

EMAILID

Attribute	Description
Name	EMAILID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	30

ZIP

Attribute	Description
Name	ZIP
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	14

FAX

Attribute	Description
Name	FAX
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	16

MOBILE

Attribute	Description
Name	MOBILE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	10

INTERMEDIARYCUSTNO

Attribute	Description
Name	INTERMEDIARYCUSTNO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

TYPE

Attribute	Description
Name	TYPE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: enumeration / I,E

CLCTAGENTID

Attribute	**Description**
Name	CLCTAGENTID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

STATEMENTFREQUENCY

Attribute	**Description**
Name	STATEMENTFREQUENCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Y,

STATEMENTSTARTMONTH

Attribute	**Description**
Name	STATEMENTSTARTMONTH
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

STATEMENTSTARTDATE

Attribute	**Description**
Name	STATEMENTSTARTDATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22

STATEMENTFREQUENCYUNIT

Attribute	Description
Name	STATEMENTFREQUENCYUNIT
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

LASTSTATEMENTDATE

Attribute	Description
Name	LASTSTATEMENTDATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

NEXTSTATEMENTDATE

Attribute	Description
Name	NEXTSTATEMENTDATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

INTERMEDIARYNAME

Attribute	Description
Name	INTERMEDIARYNAME
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	32

PRIMARYCONTACT

Attribute	Description

Name	PRIMARYCONTACT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

EFFECTIVEDATE

Attribute	**Description**
Name	EFFECTIVEDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

BRANCHCODE

Attribute	**Description**
Name	BRANCHCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

LIQUIDATIONMODE

Attribute	**Description**
Name	LIQUIDATIONMODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M,

MINIMUMLIQAMT

Attribute	**Description**
Name	MINIMUMLIQAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22

CASCADETILL

Attribute	Description
Name	CASCADETILL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	I,R,

ROOTINTM

Attribute	Description
Name	ROOTINTM
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CASCADE_CHILDS

Attribute	Description
Name	CASCADE_CHILDS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 4

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	4

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

Intms-Inter-Settlement

Attribute	Description
Name	Intms-Inter-Settlement
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

SETTLE_MODE

Attribute	Description
Name	SETTLE_MODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ACC,EAC,

UPLDSRC

Attribute	Description
Name	UPLDSRC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

CLGPRODDR

Attribute	Description
Name	CLGPRODDR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

EXTACCBNK2

Attribute	Description
Name	EXTACCBNK2
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

EXT_BRN_CODE

Attribute	Description
Name	EXT_BRN_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

INSTRUMENTNO

Attribute	Description
Name	INSTRUMENTNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

SECTORCODE

Attribute	Description
Name	SECTORCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

EXTACCNAME

Attribute	Description
Name	EXTACCNAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

EXTACCNUMBER

Attribute	Description
Name	EXTACCNUMBER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

CTG_PROD_CAT

Attribute	Description
Name	CTG_PROD_CAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

PAYABLEBANK

Attribute	Description
Name	PAYABLEBANK
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

PAYABLEBRANCH

Attribute	Description
Name	PAYABLEBRANCH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

SETTLEPRD

Attribute	Description
Name	SETTLEPRD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

SETLCCY

Attribute	Description
Name	SETLCCY
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

SETLACCBRN

Attribute	Description
Name	SETLACCBRN
Datatype	String
Description	

Restrictions	
	Restrictions / **Description**: maxLength / 4

STTLACC

Attribute	Description
Name	STTLACC
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 20

Intms-Inter-Prd-Linkage

Attribute	Description
Name	Intms-Inter-Prd-Linkage
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

PRODUCTCODE

Attribute	Description
Name	PRODUCTCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

PRODUCT_DESC

Attribute	Description
Name	PRODUCT_DESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

LASTSETTLEMENTDT

Attribute	Description

Name	LASTSETTLEMENTDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

LASTPROCESSINGDATE

Attribute	**Description**
Name	LASTPROCESSINGDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

NEXTPROCESSINGDATE

Attribute	**Description**
Name	NEXTPROCESSINGDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

MIN_HIERARCHY_COMM

Attribute	**Description**
Name	MIN_HIERARCHY_COMM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

HERRCOMM

Attribute	**Description**
Name	HERRCOMM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 100

Intbs-Inter-Ude-Values

Attribute	Description
Name	Intbs-Inter-Ude-Values
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

UDETYPE

Attribute	Description
Name	UDETYPE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

UDEVALUE

Attribute	Description
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

INTERMEDIARYPRODUCTCODE

Attribute	Description

Name	INTERMEDIARYPRODUCTCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

INTERMEDIARYCODE

Attribute	**Description**
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

RULEID

Attribute	**Description**
Name	RULEID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

Invws-Inter-Prd-Rule-Ude

Attribute	**Description**
Name	Invws-Inter-Prd-Rule-Ude
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

RULEID

Attribute	**Description**
Name	RULEID
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 16

UDEID

Attribute	**Description**
Name	UDEID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

UDEVALUE

Attribute	**Description**
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

Intbs-Inter-Event-Log

Attribute	**Description**
Name	Intbs-Inter-Event-Log
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

INTERMEDIARYCODE

Attribute	**Description**
Name	INTERMEDIARYCODE
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

BRANCHCODE

Attribute	**Description**
Name	BRANCHCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

EVENTCODE

Attribute	**Description**
Name	EVENTCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

EVENT_DATE

Attribute	**Description**
Name	EVENT_DATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

EVENTNO

Attribute	**Description**
Name	EVENTNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: totalDigits / 22

Invws-Event-Ac-Entries

Attribute	Description
Name	Invws-Event-Ac-Entries
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

ESN

Attribute	Description
Name	ESN
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	3

ACCOUNTNUMBER

Attribute	Description
Name	ACCOUNTNUMBER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

BRNLCY

Attribute	Description
Name	BRNLCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: maxLength / 3

FCYAMT

Attribute	Description
Name	FCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

DATE

Attribute	Description
Name	DATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

VALDT

Attribute	Description
Name	VALDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

Intbs-Inter-Event-Adv

Attribute	Description
Name	Intbs-Inter-Event-Adv
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 4

INTERMEDIARYCODE

Attribute	**Description**
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

BRANCHCODE

Attribute	**Description**
Name	BRANCHCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

EVENTNO

Attribute	**Description**
Name	EVENTNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

MSGTYPE

Attribute	**Description**
Name	MSGTYPE
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 25

SUPPRESS

Attribute	**Description**
Name	SUPPRESS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

PRTYID

Attribute	**Description**
Name	PRTYID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

CustAcc

Attribute	**Description**
Name	CustAcc
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFRATE

Attribute	Description
Name	REFRATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>1,2,3,4,5,6,7,8,9,</td></tr></table>

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

MisAccLog

Attribute	Description
Name	MisAccLog
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String

Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

MisBalLog

Attribute	Description
Name	MisBalLog
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRN

Attribute	Description
Name	BRN
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TRNIND

Attribute	Description
Name	TRNIND
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** maxLength / 1

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

XRATE

Attribute	**Description**
Name	XRATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

AMT

Attribute	**Description**
Name	AMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

Chglog

Attribute	**Description**
Name	Chglog
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0

Classname

Attribute	Description
Name	Classname
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

C2

Attribute	Description
Name	C2
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

C3

Attribute	Description
Name	C3
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

C4

Attribute	Description
Name	C4
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

C6

Attribute	Description
Name	C6
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C7

Attribute	Description
Name	C7
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C8

Attribute	Description
Name	C8
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C9

Attribute	Description
Name	C9
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C10

Attribute	Description
Name	C10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T1

Attribute	Description
Name	T1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T3

Attribute	Description
Name	T3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T5

Attribute	Description
Name	T5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T6

Attribute	Description
Name	T6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T7

Attribute	Description
Name	T7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T8

Attribute	Description
Name	T8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T9

Attribute	Description
Name	T9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T10

Attribute	Description
Name	T10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.6.4.IN-CreateInIntermedMaint-Res-PK-MSG.xsd

CREATEININTERMEDMAINT_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-PK

INTERMEDIARYCODE

Intms-Intermediary-IO

INTERMEDIARYCODE

INTERMEDIARYSTATUS

INTERMEDIARYCATEGORY

ADDRESS1

ADDRESS2

ADDRESS3

TELEPHONE

EMAILID

ZIP

FAX

MOBILE

TYPE

CLCTAGENTID

STATEMENTFREQUENCY

STATEMENTSTARTMONTH

STATEMENTSTARTDATE

STATEMENTFREQUENCYUNIT

INTERMEDIARYNAME

PRIMARYCONTACT

LIQUIDATIONMODE

MINIMUMLIQAMT

CASCADETILL

ROOTINTM

CASCADE_CHILDS

GRPCD

Intms-Inter-Settlement

- *SETTLE_MODE*
- *UPLDSRC*
- *ENDPOINT*
- *ROUTINGNO*
- *INSTRUMENTNO*
- *SECTORCODE*
- *EXTACCNAME*

EXTACCNUMBER

PAYABLEBANK

PAYABLEBRANCH

SETTLEPRD

Intms-Inter-Prd-Linkage

MIN_HIERARCHY_COMM

HERRCOMM

Intbs-Inter-Ude-Values

UDETYPE

UDEVALUE

INTERMEDIARYPRODUCTCODE

INTERMEDIARYCODE

Invws-Inter-Prd-Rule-Ude

RULEID

UDEID

UDEVALUE

Intbs-Inter-Event-Log

INTERMEDIARYCODE

BRANCHCODE

EVENTCODE

EVENT_DATE

EVENTNO

Invws-Event-Ac-Entries

FCCREF

ESN

BRANCHCODE

ACCOUNTNUMBER

BRNLCY

DRCRIND

CODE

FCYAMT

EXRATE

LCYAMT

DATE

VALDT

AMTTAG

EVENT

Intbs-Inter-Event-Adv

EVENTCODE

INTERMEDIARYCODE

BRANCHCODE

EVENTNO

MSGTYPE

SUPPRESS

PRIORITY

PRTYID

CustAcc

BRN

ACC

Misdetails

MISGRP

POOLCD

REFRATE

REFRTTYPE

REFRTCD

REFRTSPRD

CALCMETH

TXNMIS1

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

TXNMIS10

COMPMIS1

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

COMPMIS10

COSTCOD1

COSTCOD2

COSTCOD3

COSTCOD4

COSTCOD5

RTFLAG

LINKGRP

MisAccLog

MISCLS

TXNDT

OLDMISCD

NWMISCD

MisBalLog

Classname

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATEININTERMEDMAINT_IOPK_RES

Attribute	Description
Name	CREATEININTERMEDMAINT_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String

Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.

Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-PK

Attribute	Description
Name	Intms-Intermediary-PK
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description

Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

Intms-Intermediary-IO

Attribute	**Description**
Name	Intms-Intermediary-IO
Datatype	
Description	

INTERMEDIARYCODE

Attribute	**Description**
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

INTERMEDIARYSTATUS

Attribute	**Description**
Name	INTERMEDIARYSTATUS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

INTERMEDIARYCATEGORY

Attribute	**Description**
Name	INTERMEDIARYCATEGORY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	I,G,

ADDRESS1

Attribute	Description
Name	ADDRESS1
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	100

ADDRESS2

Attribute	Description
Name	ADDRESS2
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	100

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	100

TELEPHONE

Attribute	Description
Name	TELEPHONE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: totalDigits / 16

EMAILID

Attribute	Description
Name	EMAILID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

ZIP

Attribute	Description
Name	ZIP
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 14

FAX

Attribute	Description
Name	FAX
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 16

MOBILE

Attribute	Description
Name	MOBILE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	10

TYPE

Attribute	Description
Name	TYPE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	I,E

CLCTAGENTID

Attribute	Description
Name	CLCTAGENTID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

STATEMENTFREQUENCY

Attribute	Description
Name	STATEMENTFREQUENCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	D,W,M,Y,

STATEMENTSTARTMONTH

Attribute	Description
Name	STATEMENTSTARTMONTH
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: totalDigits / 22

STATEMENTSTARTDATE

Attribute	Description
Name	STATEMENTSTARTDATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

STATEMENTFREQUENCYUNIT

Attribute	Description
Name	STATEMENTFREQUENCYUNIT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

INTERMEDIARYNAME

Attribute	Description
Name	INTERMEDIARYNAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

PRIMARYCONTACT

Attribute	Description
Name	PRIMARYCONTACT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: maxLength / 32

LIQUIDATIONMODE

Attribute	**Description**
Name	LIQUIDATIONMODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M,

MINIMUMLIQAMT

Attribute	**Description**
Name	MINIMUMLIQAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CASCADETILL

Attribute	**Description**
Name	CASCADETILL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,R,

ROOTINTM

Attribute	**Description**
Name	ROOTINTM
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	Y,N

CASCADE_CHILDS

Attribute	Description
Name	CASCADE_CHILDS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

Intms-Inter-Settlement

Attribute	Description
Name	Intms-Inter-Settlement
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

SETTLE_MODE

Attribute	Description
Name	SETTLE_MODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	ACC,EAC,

UPLDSRC

Attribute	Description
Name	UPLDSRC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

INSTRUMENTNO

Attribute	Description
Name	INSTRUMENTNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

SECTORCODE

Attribute	Description
Name	SECTORCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

EXTACCNAME

Attribute	Description
Name	EXTACCNAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

EXTACCNUMBER

Attribute	Description
Name	EXTACCNUMBER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

PAYABLEBANK

Attribute	Description
Name	PAYABLEBANK
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

PAYABLEBRANCH

Attribute	Description
Name	PAYABLEBRANCH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

SETTLEPRD

Attribute	Description
Name	SETTLEPRD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

Intms-Inter-Prd-Linkage

Attribute	Description
Name	Intms-Inter-Prd-Linkage
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

MIN_HIERARCHY_COMM

Attribute	Description
Name	MIN_HIERARCHY_COMM
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

HERRCOMM

Attribute	Description
Name	HERRCOMM
Datatype	Decimal

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>100</td></tr></table>

Intbs-Inter-Ude-Values

Attribute	Description
Name	Intbs-Inter-Ude-Values
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

UDETYPE

Attribute	Description
Name	UDETYPE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

UDEVALUE

Attribute	Description
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

INTERMEDIARYPRODUCTCODE

Attribute	Description
Name	INTERMEDIARYPRODUCTCODE
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** maxLength / 4

INTERMEDIARYCODE

Attribute	**Description**
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

Invws-Inter-Prd-Rule-Ude

Attribute	**Description**
Name	Invws-Inter-Prd-Rule-Ude
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

RULEID

Attribute	**Description**
Name	RULEID
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

UDEID

Attribute	**Description**
Name	UDEID
Datatype	String
Description	

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

UDEVALUE

Attribute	Description
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

Intbs-Inter-Event-Log

Attribute	Description
Name	Intbs-Inter-Event-Log
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

EVENTCODE

Attribute	**Description**
Name	EVENTCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

EVENT_DATE

Attribute	**Description**
Name	EVENT_DATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

EVENTNO

Attribute	**Description**
Name	EVENTNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

Invws-Event-Ac-Entries

Attribute	**Description**
Name	Invws-Event-Ac-Entries
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

ESN

Attribute	Description
Name	ESN
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

ACCOUNTNUMBER

Attribute	Description
Name	ACCOUNTNUMBER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

BRNLCY

Attribute	Description
Name	BRNLCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

FCYAMT

Attribute	Description
Name	FCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

DATE

Attribute	Description
Name	DATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

VALDT

Attribute	Description
Name	VALDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	35

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

Intbs-Inter-Event-Adv

Attribute	Description
Name	Intbs-Inter-Event-Adv
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

EVENTNO

Attribute	Description
Name	EVENTNO
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	25

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	**Restrictions** / **Description**: maxLength / 1

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

PRTYID

Attribute	**Description**
Name	PRTYID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

CustAcc

Attribute	**Description**
Name	CustAcc
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

BRN

Attribute	**Description**
Name	BRN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFRATE

Attribute	Description
Name	REFRATE

Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

REFRTTYPE

Attribute	**Description**
Name	REFRTTYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F

REFRTCD

Attribute	**Description**
Name	REFRTCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

REFRTSPRD

Attribute	**Description**
Name	REFRTSPRD
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CALCMETH

Attribute	**Description**
Name	CALCMETH

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>1,2,3,4,5,6,7,8,9,</td></tr></table>

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS8

Attribute	Description
Name	TXNMIS8

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS2

Attribute	Description
Name	COMPMIS2

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS6

Attribute	Description
Name	COMPMIS6

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS10

Attribute	Description
Name	COMPMIS10

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD4

Attribute	Description
Name	COSTCOD4

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

COSTCOD5

Attribute	**Description**
Name	COSTCOD5
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

RTFLAG

Attribute	**Description**
Name	RTFLAG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

LINKGRP

Attribute	**Description**
Name	LINKGRP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

MisAccLog

Attribute	**Description**
Name	MisAccLog

Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

MisBalLog

Attribute	Description
Name	MisBalLog

Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

Classname

Attribute	Description
Name	Classname
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions

Restrictions	Description
maxLength	150
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.7.DeleteINextudval

2.7.1.IN-DeleteINextudval-Req-Full-MSG.xsd

DELETEINEXTUDVAL_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Inter-Ext-Ude-Full

INTERMEDIARYCODE

UDEFFDT

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Intms-Inter-Ext-Prdlink

PRODUCTCODE

PRODUCT_DESC

UDEEFFDT

Intms-Inter-Ext-Ude-Values

UDEID

UDEVALUE

RULEID

UDETYPE

UDECCY

DELETEINEXTUDVAL_FSFS_REQ

Attribute	Description
Name	DELETEINEXTUDVAL_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Inter-Ext-Ude-Full

Attribute	Description
Name	Intms-Inter-Ext-Ude-Full
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

UDEFFDT

Attribute	Description
Name	UDEFFDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

Intms-Inter-Ext-Prdlink

Attribute	**Description**
Name	Intms-Inter-Ext-Prdlink
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

PRODUCTCODE

Attribute	**Description**
Name	PRODUCTCODE
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** maxLength / 4

PRODUCT_DESC

Attribute	**Description**
Name	PRODUCT_DESC
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

UDEEFFDT

Attribute	**Description**
Name	UDEEFFDT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Intms-Inter-Ext-Ude-Values

Attribute	**Description**
Name	Intms-Inter-Ext-Ude-Values
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

UDEID

Attribute	**Description**
Name	UDEID
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	16

UDEVALUE

Attribute	Description
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

RULEID

Attribute	Description
Name	RULEID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

UDETYPE

Attribute	Description
Name	UDETYPE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	R,A,N,

UDECCY

Attribute	Description
Name	UDECCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

2.7.2.IN-DeleteINextudval-Req-IO-MSG.xsd

DELETEINEXTUDVAL_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Inter-Ext-Ude-IO

INTERMEDIARYCODE

UDEFFDT

DELETEINEXTUDVAL_IOPK_REQ

Attribute	Description
Name	DELETEINEXTUDVAL_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Inter-Ext-Ude-IO

Attribute	Description
Name	Intms-Inter-Ext-Ude-IO
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

UDEFFDT

Attribute	Description
Name	UDEFFDT
Datatype	String
Description	

Attribute	

Attribute	Description
minOccurs	0

2.7.3.IN-DeleteINextudval-Res-Full-MSG.xsd

DELETEINEXTUDVAL_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Inter-Ext-Ude-Full

INTERMEDIARYCODE

UDEFFDT

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Intms-Inter-Ext-Prdlink

PRODUCTCODE

PRODUCT_DESC

UDEEFFDT

Intms-Inter-Ext-Ude-Values

UDEID

UDEVALUE

RULEID

UDETYPE

UDECCY

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETEINEXTUDVAL_FSFS_RES

Attribute	Description
Name	DELETEINEXTUDVAL_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Inter-Ext-Ude-Full

Attribute	Description
Name	Intms-Inter-Ext-Ude-Full
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

UDEFFDT

Attribute	Description
Name	UDEFFDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Intms-Inter-Ext-Prdlink

Attribute	Description
Name	Intms-Inter-Ext-Prdlink
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PRODUCTCODE

Attribute	Description
Name	PRODUCTCODE
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

PRODUCT_DESC

Attribute	**Description**
Name	PRODUCT_DESC
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

UDEEFFDT

Attribute	**Description**
Name	UDEEFFDT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Intms-Inter-Ext-Ude-Values

Attribute	**Description**
Name	Intms-Inter-Ext-Ude-Values
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

UDEID

Attribute	**Description**
Name	UDEID
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	
	Restrictions / **Description**: maxLength / 16

UDEVALUE

Attribute	Description
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

RULEID

Attribute	Description
Name	RULEID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

UDETYPE

Attribute	Description
Name	UDETYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / R,A,N,

UDECCY

Attribute	Description
Name	UDECCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	3

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.7.4.IN-DeleteINextudval-Res-PK-MSG.xsd

DELETEINEXTUDVAL_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Inter-Ext-Ude-PK

INTERMEDIARYCODE

UDEFFDT

Intms-Inter-Ext-Ude-IO

INTERMEDIARYCODE

UDEFFDT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETEINEXTUDVAL_IOPK_RES

Attribute	Description
Name	DELETEINEXTUDVAL_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID

Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String

Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Inter-Ext-Ude-PK

Attribute	Description
Name	Intms-Inter-Ext-Ude-PK
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

UDEFFDT

Attribute	Description
Name	UDEFFDT
Datatype	String
Description	

Intms-Inter-Ext-Ude-IO

Attribute	Description
Name	Intms-Inter-Ext-Ude-IO
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

UDEFFDT

Attribute	Description
Name	UDEFFDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.8.DeleteINGroup

2.8.1.IN-DeleteINGroup-Req-Full-MSG.xsd

DELETEINGROUP_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-Group-Full

GRPCD

GROUPDESC

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

DELETEINGROUP_FSFS_REQ

Attribute	Description
Name	DELETEINGROUP_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String

Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-Group-Full

Attribute	Description
Name	Intms-Intermediary-Group-Full
Datatype	
Description	

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

GROUPDESC

Attribute	Description
Name	GROUPDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description

Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	**Description**

Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

2.8.2.IN-DeleteINGroup-Req-IO-MSG.xsd

DELETEINGROUP_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-Group-IO

GRPCD

DELETEINGROUP_IOPK_REQ

Attribute	Description
Name	DELETEINGROUP_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH

Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String

Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-Group-IO

Attribute	Description
Name	Intms-Intermediary-Group-IO
Datatype	
Description	

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

2.8.3.IN-DeleteINGroup-Res-Full-MSG.xsd

DELETEINGROUP_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-Group-Full

GRPCD

GROUPDESC

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETEINGROUP_FSFS_RES

Attribute	Description
Name	DELETEINGROUP_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String

Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-Group-Full

Attribute	Description
Name	Intms-Intermediary-Group-Full
Datatype	
Description	

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

GROUPDESC

Attribute	Description
Name	GROUPDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description

Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	**Description**

Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attribute	**Attribute** / **Description**: maxOccurs / unbounded

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	**Description**

Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.8.4.IN-DeleteINGroup-Res-PK-MSG.xsd

DELETEINGROUP_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-Group-PK

GRPCD

Intms-Intermediary-Group-IO

GRPCD

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETEINGROUP_IOPK_RES

Attribute	Description
Name	DELETEINGROUP_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description

Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-Group-PK

Attribute	Description
Name	Intms-Intermediary-Group-PK
Datatype	
Description	

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

Intms-Intermediary-Group-IO

Attribute	Description
Name	Intms-Intermediary-Group-IO
Datatype	
Description	

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

WCODE

Attribute	Description

Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.9.DeleteInIntermedMaint

2.9.1.IN-DeleteInIntermedMaint-Req-Full-MSG.xsd

DELETEININTERMEDMAINT_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-Full

INTERMEDIARYCODE

INTERMEDIARYSTATUS

INTERMEDIARYCATEGORY

LEVELNUMBER

PARENTINTERMEDIARYCODE

PARENTINTERMEDIARYNAME

ADDRESS1

ADDRESS2

ADDRESS3

COUNTRY

TELEPHONE

EMAILID

ZIP

FAX

MOBILE

INTERMEDIARYCUSTNO

TYPE

CLCTAGENTID

STATEMENTFREQUENCY

STATEMENTSTARTMONTH

STATEMENTSTARTDATE

STATEMENTFREQUENCYUNIT

LASTSTATEMENTDATE

NEXTSTATEMENTDATE

INTERMEDIARYNAME

PRIMARYCONTACT

EFFECTIVEDATE

BRANCHCODE

LIQUIDATIONMODE

MINIMUMLIQAMT

CASCADETILL

ROOTINTM

CASCADE_CHILDS

GRPCD

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Intms-Inter-Settlement

- *SETTLE_MODE*
- *UPLDSRC*
- *CLGPRODDR*
- *ENDPOINT*
- *ROUTINGNO*
- *EXTACCBNK2*
- *EXT_BRN_CODE*
- *INSTRUMENTNO*
- *SECTORCODE*
- *EXTACCNAME*
- *EXTACCNUMBER*
- *CTG_PROD_CAT*
- *PAYABLEBANK*
- *PAYABLEBRANCH*
- *SETTLEPRD*
- *SETLCCY*
- *SETLACCBRN*
- *STTLACC*

Intms-Inter-Prd-Linkage

- *PRODUCTCODE*
- *PRODUCT_DESC*
- *LASTSETTLEMENTDT*

LASTPROCESSINGDATE

NEXTPROCESSINGDATE

MIN_HIERARCHY_COMM

HERRCOMM

Intbs-Inter-Ude-Values

UDEID

UDETYPE

UDEVALUE

INTERMEDIARYPRODUCTCODE

INTERMEDIARYCODE

RULEID

Invws-Inter-Prd-Rule-Ude

RULEID

UDEID

UDEVALUE

Intbs-Inter-Event-Log

INTERMEDIARYCODE

BRANCHCODE

EVENTCODE

EVENT_DATE

EVENTNO

Invws-Event-Ac-Entries

FCCREF

ESN

BRANCHCODE

ACCOUNTNUMBER

BRNLCY

DRCRIND

CODE

FCYAMT

EXRATE

LCYAMT

DATE

VALDT

AMTTAG

EVENT

Intbs-Inter-Event-Adv

EVENTCODE

INTERMEDIARYCODE

BRANCHCODE

EVENTNO

MSGTYPE

SUPPRESS

PRIORITY

PRTYID

CustAcc

BRN

ACC

Misdetails

MISGRP

POOLCD

REFRATE

REFRTTYPE

MISGRPTXN

REFRTCD

REFRTSPRD

CALCMETH

TXNMIS1

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

TXNMIS10

MISGRPCOMP

COMPMIS1

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

COMPMIS10

COSTCOD1

COSTCOD2

COSTCOD3

COSTCOD4

COSTCOD5

RTFLAG

LINKGRP

MisAccLog

- *MISCLS*
- *TXNDT*
- *OLDMISCD*
- *NWMISCD*

MisBalLog

- *BRN*
- *PRDCD*
- *FINYR*
- *TXNDT*
- *GLCODE*

MISCLS

OLDMISCD

NWMISCD

TRNIND

CCY

XRATE

AMT

Chglog

Classname

C2

C3

C4

C6

C7

C8

C9

C10

T1

T3

T5

T6

T7

T8

T9

T10

UDFDETAILS

FLDNAM

FLDVAL

DELETEININTERMEDMAINT_FSFS_REQ

Attribute	Description
Name	DELETEININTERMEDMAINT_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-Full

Attribute	Description
Name	Intms-Intermediary-Full
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	16

INTERMEDIARYSTATUS

Attribute	Description
Name	INTERMEDIARYSTATUS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	A,I

INTERMEDIARYCATEGORY

Attribute	Description
Name	INTERMEDIARYCATEGORY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	I,G,

LEVELNUMBER

Attribute	Description
Name	LEVELNUMBER
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

PARENTINTERMEDIARYCODE

Attribute	Description
Name	PARENTINTERMEDIARYCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

PARENTINTERMEDIARYNAME

Attribute	Description
Name	PARENTINTERMEDIARYNAME
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	32

ADDRESS1

Attribute	Description
Name	ADDRESS1
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	100

ADDRESS2

Attribute	Description
Name	ADDRESS2
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	100

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	100

COUNTRY

Attribute	Description
Name	COUNTRY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: maxLength / 3

TELEPHONE

Attribute	Description
Name	TELEPHONE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 16

EMAILID

Attribute	Description
Name	EMAILID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

ZIP

Attribute	Description
Name	ZIP
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 14

FAX

Attribute	Description
Name	FAX
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	16

MOBILE

Attribute	Description
Name	MOBILE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	10

INTERMEDIARYCUSTNO

Attribute	Description
Name	INTERMEDIARYCUSTNO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

TYPE

Attribute	Description
Name	TYPE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	I,E

CLCTAGENTID

Attribute	Description
Name	CLCTAGENTID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: enumeration / Y,N

STATEMENTFREQUENCY

Attribute	**Description**
Name	STATEMENTFREQUENCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Y,

STATEMENTSTARTMONTH

Attribute	**Description**
Name	STATEMENTSTARTMONTH
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

STATEMENTSTARTDATE

Attribute	**Description**
Name	STATEMENTSTARTDATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

STATEMENTFREQUENCYUNIT

Attribute	**Description**
Name	STATEMENTFREQUENCYUNIT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22

LASTSTATEMENTDATE

Attribute	Description
Name	LASTSTATEMENTDATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

NEXTSTATEMENTDATE

Attribute	Description
Name	NEXTSTATEMENTDATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

INTERMEDIARYNAME

Attribute	Description
Name	INTERMEDIARYNAME
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	32

PRIMARYCONTACT

Attribute	Description
Name	PRIMARYCONTACT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	32

EFFECTIVEDATE

Attribute	Description

Name	EFFECTIVEDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

BRANCHCODE

Attribute	**Description**
Name	BRANCHCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

LIQUIDATIONMODE

Attribute	**Description**
Name	LIQUIDATIONMODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M,

MINIMUMLIQAMT

Attribute	**Description**
Name	MINIMUMLIQAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CASCADETILL

Attribute	**Description**
Name	CASCADETILL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: enumeration / I,R,

ROOTINTM

Attribute	Description
Name	ROOTINTM
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CASCADE_CHILDS

Attribute	Description
Name	CASCADE_CHILDS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	4

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

Intms-Inter-Settlement

Attribute	Description
Name	Intms-Inter-Settlement
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

SETTLE_MODE

Attribute	Description
Name	SETTLE_MODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	ACC,EAC,

UPLDSRC

Attribute	Description
Name	UPLDSRC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

CLGPRODDR

Attribute	Description
Name	CLGPRODDR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

EXTACCBNK2

Attribute	Description
Name	EXTACCBNK2
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

EXT_BRN_CODE

Attribute	Description
Name	EXT_BRN_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

INSTRUMENTNO

Attribute	Description
Name	INSTRUMENTNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

SECTORCODE

Attribute	Description
Name	SECTORCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

EXTACCNAME

Attribute	Description
Name	EXTACCNAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

EXTACCNUMBER

Attribute	Description
Name	EXTACCNUMBER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

CTG_PROD_CAT

Attribute	Description
Name	CTG_PROD_CAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

PAYABLEBANK

Attribute	Description
Name	PAYABLEBANK
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

PAYABLEBRANCH

Attribute	Description
Name	PAYABLEBRANCH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

SETTLEPRD

Attribute	Description
Name	SETTLEPRD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

SETLCCY

Attribute	Description
Name	SETLCCY
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

SETLACCBRN

Attribute	Description
Name	SETLACCBRN
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

STTLACC

Attribute	Description
Name	STTLACC
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

Intms-Inter-Prd-Linkage

Attribute	Description
Name	Intms-Inter-Prd-Linkage
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PRODUCTCODE

Attribute	Description
Name	PRODUCTCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

PRODUCT_DESC

Attribute	Description
Name	PRODUCT_DESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

LASTSETTLEMENTDT

Attribute	Description
Name	LASTSETTLEMENTDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

LASTPROCESSINGDATE

Attribute	Description
Name	LASTPROCESSINGDATE
Datatype	String
Description	

Attribute	

Attribute	Description
minOccurs	0

NEXTPROCESSINGDATE

Attribute	Description
Name	NEXTPROCESSINGDATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

MIN_HIERARCHY_COMM

Attribute	Description
Name	MIN_HIERARCHY_COMM
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

HERRCOMM

Attribute	Description
Name	HERRCOMM
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	100

Intbs-Inter-Ude-Values

Attribute	Description
Name	Intbs-Inter-Ude-Values
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

UDETYPE

Attribute	Description
Name	UDETYPE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

UDEVALUE

Attribute	Description
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

INTERMEDIARYPRODUCTCODE

Attribute	Description
Name	INTERMEDIARYPRODUCTCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

RULEID

Attribute	Description
Name	RULEID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

Invws-Inter-Prd-Rule-Ude

Attribute	Description
Name	Invws-Inter-Prd-Rule-Ude
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

RULEID

Attribute	Description
Name	RULEID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

UDEID

Attribute	Description
Name	UDEID
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

UDEVALUE

Attribute	Description
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

Intbs-Inter-Event-Log

Attribute	Description
Name	Intbs-Inter-Event-Log
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	

Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

EVENTCODE

Attribute	**Description**
Name	EVENTCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

EVENT_DATE

Attribute	**Description**
Name	EVENT_DATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

EVENTNO

Attribute	**Description**
Name	EVENTNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

Invws-Event-Ac-Entries

Attribute	**Description**
Name	Invws-Event-Ac-Entries
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

ESN

Attribute	Description
Name	ESN
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

ACCOUNTNUMBER

Attribute	Description
Name	ACCOUNTNUMBER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

BRNLCY

Attribute	Description
Name	BRNLCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

FCYAMT

Attribute	Description
Name	FCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

DATE

Attribute	Description
Name	DATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

VALDT

Attribute	Description
Name	VALDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	35

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

Intbs-Inter-Event-Adv

Attribute	Description
Name	Intbs-Inter-Event-Adv
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

EVENTNO

Attribute	Description
Name	EVENTNO
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	25

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

CustAcc

Attribute	Description
Name	CustAcc
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFRATE

Attribute	Description
Name	REFRATE

Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

REFRTTYPE

Attribute	**Description**
Name	REFRTTYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F

MISGRPTXN

Attribute	**Description**
Name	MISGRPTXN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

REFRTCD

Attribute	**Description**
Name	REFRTCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

REFRTSPRD

Attribute	**Description**
Name	REFRTSPRD

Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CALCMETH

Attribute	**Description**
Name	CALCMETH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,8,9,

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TXNMIS2

Attribute	**Description**
Name	TXNMIS2
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TXNMIS3

Attribute	**Description**
Name	TXNMIS3

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS7

Attribute	Description
Name	TXNMIS7

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS4

Attribute	Description
Name	COMPMIS4

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS8

Attribute	Description
Name	COMPMIS8

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD2

Attribute	Description
Name	COSTCOD2

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

RTFLAG

Attribute	Description
Name	RTFLAG

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

MisAccLog

Attribute	Description
Name	MisAccLog
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	

OLDMISCD

Attribute	Description
Name	OLDMISCD

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

MisBalLog

Attribute	Description
Name	MisBalLog
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

FINYR

Attribute	**Description**
Name	FINYR
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TXNDT

Attribute	**Description**
Name	TXNDT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

GLCODE

Attribute	**Description**
Name	GLCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

MISCLS

Attribute	**Description**
Name	MISCLS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

OLDMISCD

Attribute	**Description**
Name	OLDMISCD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

NWMISCD

Attribute	**Description**
Name	NWMISCD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TRNIND

Attribute	**Description**
Name	TRNIND
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	3

XRATE

Attribute	Description
Name	XRATE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

AMT

Attribute	Description
Name	AMT
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

Chglog

Attribute	Description
Name	Chglog
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

Classname

Attribute	Description
Name	Classname
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

C2

Attribute	Description

Name	C2
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C3

Attribute	**Description**
Name	C3
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C4

Attribute	**Description**
Name	C4
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C6

Attribute	**Description**
Name	C6
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C7

Attribute	**Description**

Name	C7
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C8

Attribute	**Description**
Name	C8
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C9

Attribute	**Description**
Name	C9
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C10

Attribute	**Description**
Name	C10
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

T1

Attribute	**Description**

Name	T1
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

T3

Attribute	**Description**
Name	T3
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

T5

Attribute	**Description**
Name	T5
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

T6

Attribute	**Description**
Name	T6
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

T7

Attribute	**Description**

Name	T7
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

T8

Attribute	**Description**
Name	T8
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

T9

Attribute	**Description**
Name	T9
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

T10

Attribute	**Description**
Name	T10
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

UDFDETAILS

Attribute	**Description**

Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.9.2.IN-DeleteInIntermedMaint-Req-IO-MSG.xsd

DELETEININTERMEDMAINT_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-IO

INTERMEDIARYCODE

DELETEININTERMEDMAINT_IOPK_REQ

Attribute	Description
Name	DELETEININTERMEDMAINT_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.

Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-IO

Attribute	Description
Name	Intms-Intermediary-IO
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

2.9.3.IN-DeleteInIntermedMaint-Res-Full-MSG.xsd

DELETEININTERMEDMAINT_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-Full

INTERMEDIARYCODE

INTERMEDIARYSTATUS

INTERMEDIARYCATEGORY

LEVELNUMBER

PARENTINTERMEDIARYCODE

PARENTINTERMEDIARYNAME

ADDRESS1

ADDRESS2

ADDRESS3

COUNTRY

TELEPHONE

EMAILID

ZIP

FAX

MOBILE

INTERMEDIARYCUSTNO

TYPE

CLCTAGENTID

STATEMENTFREQUENCY

STATEMENTSTARTMONTH

STATEMENTSTARTDATE

STATEMENTFREQUENCYUNIT

LASTSTATEMENTDATE

NEXTSTATEMENTDATE

INTERMEDIARYNAME

PRIMARYCONTACT

EFFECTIVEDATE

BRANCHCODE

LIQUIDATIONMODE

MINIMUMLIQAMT

CASCADETILL

ROOTINTM

CASCADE_CHILDS

GRPCD

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Intms-Inter-Settlement

- *SETTLE_MODE*
- *UPLDSRC*
- *CLGPRODDR*
- *ENDPOINT*
- *ROUTINGNO*
- *EXTACCBNK2*
- *EXT_BRN_CODE*
- *INSTRUMENTNO*
- *SECTORCODE*
- *EXTACCNAME*
- *EXTACCNUMBER*
- *CTG_PROD_CAT*
- *PAYABLEBANK*
- *PAYABLEBRANCH*
- *SETTLEPRD*
- *SETLCCY*
- *SETLACCBRN*
- *STTLACC*

Intms-Inter-Prd-Linkage

PRODUCTCODE

PRODUCT_DESC

LASTSETTLEMENTDT

LASTPROCESSINGDATE

NEXTPROCESSINGDATE

MIN_HIERARCHY_COMM

HERRCOMM

Intbs-Inter-Ude-Values

UDEID

UDETYPE

UDEVALUE

INTERMEDIARYPRODUCTCODE

INTERMEDIARYCODE

RULEID

Invws-Inter-Prd-Rule-Ude

RULEID

UDEID

UDEVALUE

Intbs-Inter-Event-Log

INTERMEDIARYCODE

BRANCHCODE

EVENTCODE

EVENT_DATE

EVENTNO

Invws-Event-Ac-Entries

FCCREF

ESN

BRANCHCODE

ACCOUNTNUMBER

BRNLCY

DRCRIND

CODE

FCYAMT

EXRATE

LCYAMT

DATE

VALDT

AMTTAG

EVENT

Intbs-Inter-Event-Adv

EVENTCODE

INTERMEDIARYCODE

BRANCHCODE

EVENTNO

MSGTYPE

SUPPRESS

PRIORITY

PRTYID

CustAcc

BRN

ACC

Misdetails

MISGRP

POOLCD

REFRATE

REFRTTYPE

MISGRPTXN

REFRTCD

REFRTSPRD

CALCMETH

TXNMIS1

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

TXNMIS10

MISGRPCOMP

COMPMIS1

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

COMPMIS10

COSTCOD1

COSTCOD2

COSTCOD3

COSTCOD4

COSTCOD5

RTFLAG

LINKGRP

MisAccLog

- *MISCLS*
- *TXNDT*
- *OLDMISCD*
- *NWMISCD*

MisBalLog

- *BRN*

PRDCD

FINYR

TXNDT

GLCODE

MISCLS

OLDMISCD

NWMISCD

TRNIND

CCY

XRATE

AMT

Chglog

Classname

C2

C3

C4

C6

C7

C8

C9

C10

T1

T3

T5

T6

T7

T8

T9

T10

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETEININTERMEDMAINT_FSFS_RES

Attribute	Description
Name	DELETEININTERMEDMAINT_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID

Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-Full

Attribute	Description
Name	Intms-Intermediary-Full
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description

Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

INTERMEDIARYSTATUS

Attribute	**Description**
Name	INTERMEDIARYSTATUS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

INTERMEDIARYCATEGORY

Attribute	**Description**
Name	INTERMEDIARYCATEGORY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,G,

LEVELNUMBER

Attribute	**Description**
Name	LEVELNUMBER
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

PARENTINTERMEDIARYCODE

Attribute	**Description**

Name	PARENTINTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

PARENTINTERMEDIARYNAME

Attribute	**Description**
Name	PARENTINTERMEDIARYNAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

ADDRESS1

Attribute	**Description**
Name	ADDRESS1
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

ADDRESS2

Attribute	**Description**
Name	ADDRESS2
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

ADDRESS3

Attribute	**Description**

Name	ADDRESS3
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

COUNTRY

Attribute	**Description**
Name	COUNTRY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TELEPHONE

Attribute	**Description**
Name	TELEPHONE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 16

EMAILID

Attribute	**Description**
Name	EMAILID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

ZIP

Attribute	**Description**

Name	ZIP
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 14

FAX

Attribute	**Description**
Name	FAX
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 16

MOBILE

Attribute	**Description**
Name	MOBILE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 10

INTERMEDIARYCUSTNO

Attribute	**Description**
Name	INTERMEDIARYCUSTNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TYPE

Attribute	**Description**

Name	TYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,E

CLCTAGENTID

Attribute	**Description**
Name	CLCTAGENTID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

STATEMENTFREQUENCY

Attribute	**Description**
Name	STATEMENTFREQUENCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Y,

STATEMENTSTARTMONTH

Attribute	**Description**
Name	STATEMENTSTARTMONTH
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

STATEMENTSTARTDATE

Attribute	**Description**

Name	STATEMENTSTARTDATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

STATEMENTFREQUENCYUNIT

Attribute	**Description**
Name	STATEMENTFREQUENCYUNIT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

LASTSTATEMENTDATE

Attribute	**Description**
Name	LASTSTATEMENTDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

NEXTSTATEMENTDATE

Attribute	**Description**
Name	NEXTSTATEMENTDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

INTERMEDIARYNAME

Attribute	**Description**
Name	INTERMEDIARYNAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	32

PRIMARYCONTACT

Attribute	Description
Name	PRIMARYCONTACT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	32

EFFECTIVEDATE

Attribute	Description
Name	EFFECTIVEDATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	4

LIQUIDATIONMODE

Attribute	Description
Name	LIQUIDATIONMODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	A,M,

MINIMUMLIQAMT

Attribute	Description

Name	MINIMUMLIQAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CASCADETILL

Attribute	**Description**
Name	CASCADETILL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,R,

ROOTINTM

Attribute	**Description**
Name	ROOTINTM
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CASCADE_CHILDS

Attribute	**Description**
Name	CASCADE_CHILDS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

GRPCD

Attribute	**Description**

Name	GRPCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	**Description**

Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

Intms-Inter-Settlement

Attribute	**Description**

Name	Intms-Inter-Settlement
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

SETTLE_MODE

Attribute	**Description**
Name	SETTLE_MODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ACC,EAC,

UPLDSRC

Attribute	**Description**
Name	UPLDSRC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

CLGPRODDR

Attribute	**Description**
Name	CLGPRODDR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

ENDPOINT

Attribute	**Description**
Name	ENDPOINT
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

ROUTINGNO

Attribute	**Description**
Name	ROUTINGNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

EXTACCBNK2

Attribute	**Description**
Name	EXTACCBNK2
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

EXT_BRN_CODE

Attribute	**Description**
Name	EXT_BRN_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

INSTRUMENTNO

Attribute	**Description**
Name	INSTRUMENTNO
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

SECTORCODE

Attribute	**Description**
Name	SECTORCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

EXTACCNAME

Attribute	**Description**
Name	EXTACCNAME
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

EXTACCNUMBER

Attribute	**Description**
Name	EXTACCNUMBER
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

CTG_PROD_CAT

Attribute	**Description**
Name	CTG_PROD_CAT
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

PAYABLEBANK

Attribute	**Description**
Name	PAYABLEBANK
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

PAYABLEBRANCH

Attribute	**Description**
Name	PAYABLEBRANCH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

SETTLEPRD

Attribute	**Description**
Name	SETTLEPRD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

SETLCCY

Attribute	**Description**
Name	SETLCCY
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	3

SETLACCBRN

Attribute	Description
Name	SETLACCBRN
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	4

STTLACC

Attribute	Description
Name	STTLACC
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	20

Intms-Inter-Prd-Linkage

Attribute	Description
Name	Intms-Inter-Prd-Linkage
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PRODUCTCODE

Attribute	Description
Name	PRODUCTCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

PRODUCT_DESC

Attribute	Description
Name	PRODUCT_DESC
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

LASTSETTLEMENTDT

Attribute	**Description**
Name	LASTSETTLEMENTDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

LASTPROCESSINGDATE

Attribute	**Description**
Name	LASTPROCESSINGDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

NEXTPROCESSINGDATE

Attribute	**Description**
Name	NEXTPROCESSINGDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

MIN_HIERARCHY_COMM

Attribute	**Description**
Name	MIN_HIERARCHY_COMM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

HERRCOMM

Attribute	**Description**

Name	HERRCOMM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 100

Intbs-Inter-Ude-Values

Attribute	**Description**
Name	Intbs-Inter-Ude-Values
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

UDEID

Attribute	**Description**
Name	UDEID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

UDETYPE

Attribute	**Description**
Name	UDETYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

UDEVALUE

Attribute	**Description**
Name	UDEVALUE

Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

INTERMEDIARYPRODUCTCODE

Attribute	**Description**
Name	INTERMEDIARYPRODUCTCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

INTERMEDIARYCODE

Attribute	**Description**
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

RULEID

Attribute	**Description**
Name	RULEID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

Invws-Inter-Prd-Rule-Ude

Attribute	**Description**
Name	Invws-Inter-Prd-Rule-Ude

Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

RULEID

Attribute	Description
Name	RULEID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

UDEVALUE

Attribute	Description
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

Intbs-Inter-Event-Log

Attribute	Description
Name	Intbs-Inter-Event-Log
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

EVENT_DATE

Attribute	Description
Name	EVENT_DATE
Datatype	String
Description	

Attribute	

Attribute	Description
minOccurs	0

EVENTNO

Attribute	Description
Name	EVENTNO
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

Invws-Event-Ac-Entries

Attribute	Description
Name	Invws-Event-Ac-Entries
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

ESN

Attribute	Description
Name	ESN
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: totalDigits / 22

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

ACCOUNTNUMBER

Attribute	Description
Name	ACCOUNTNUMBER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

BRNLCY

Attribute	Description
Name	BRNLCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: maxLength / 1

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

FCYAMT

Attribute	Description
Name	FCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22

DATE

Attribute	Description
Name	DATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

VALDT

Attribute	Description
Name	VALDT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

Intbs-Inter-Event-Adv

Attribute	Description

Name	Intbs-Inter-Event-Adv
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

EVENTCODE

Attribute	**Description**
Name	EVENTCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

INTERMEDIARYCODE

Attribute	**Description**
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

BRANCHCODE

Attribute	**Description**
Name	BRANCHCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

EVENTNO

Attribute	**Description**
Name	EVENTNO
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

MSGTYPE

Attribute	**Description**
Name	MSGTYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

SUPPRESS

Attribute	**Description**
Name	SUPPRESS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

PRTYID

Attribute	**Description**
Name	PRTYID
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

CustAcc

Attribute	**Description**
Name	CustAcc
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

BRN

Attribute	**Description**
Name	BRN
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

ACC

Attribute	**Description**
Name	ACC
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

Misdetails

Attribute	**Description**
Name	Misdetails
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFRATE

Attribute	Description
Name	REFRATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>1,2,3,4,5,6,7,8,9,</td></tr></table>

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

MisAccLog

Attribute	Description
Name	MisAccLog
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

MisBalLog

Attribute	Description
Name	MisBalLog
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 9

TRNIND

Attribute	**Description**
Name	TRNIND
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

XRATE

Attribute	**Description**
Name	XRATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

AMT

Attribute	**Description**
Name	AMT
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

Chglog

Attribute	**Description**
Name	Chglog
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Classname

Attribute	**Description**
Name	Classname
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

C2

Attribute	**Description**
Name	C2
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

C3

Attribute	**Description**
Name	C3
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

C4

Attribute	Description
Name	C4
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C6

Attribute	Description
Name	C6
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C7

Attribute	Description
Name	C7
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C8

Attribute	Description
Name	C8
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C9

Attribute	Description
Name	C9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

C10

Attribute	Description
Name	C10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T1

Attribute	Description
Name	T1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T3

Attribute	Description
Name	T3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T5

Attribute	Description
Name	T5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T6

Attribute	Description
Name	T6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T7

Attribute	Description
Name	T7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T8

Attribute	Description
Name	T8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T9

Attribute	Description
Name	T9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T10

Attribute	Description
Name	T10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attribute	**Attribute** / **Description** maxOccurs / unbounded

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	**Description**
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.9.4.IN-DeleteInIntermedMaint-Res-PK-MSG.xsd

DELETEININTERMEDMAINT_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-PK

INTERMEDIARYCODE

Intms-Intermediary-IO

INTERMEDIARYCODE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETEININTERMEDMAINT_IOPK_RES

Attribute	Description
Name	DELETEININTERMEDMAINT_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description

Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String

Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-PK

Attribute	Description
Name	Intms-Intermediary-PK
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

Intms-Intermediary-IO

Attribute	Description
Name	Intms-Intermediary-IO
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.10.ModifyINextudval

2.10.1.IN-ModifyINextudval-Req-Full-MSG.xsd

MODIFYINEXTUDVAL_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Inter-Ext-Ude-Full

INTERMEDIARYCODE

UDEFFDT

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Intms-Inter-Ext-Prdlink

PRODUCTCODE

PRODUCT_DESC

UDEEFFDT

Intms-Inter-Ext-Ude-Values

UDEID

UDEVALUE

RULEID

UDETYPE

UDECCY

MODIFYINEXTUDVAL_FSFS_REQ

Attribute	Description
Name	MODIFYINEXTUDVAL_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description

Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String

Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Inter-Ext-Ude-Full

Attribute	Description
Name	Intms-Inter-Ext-Ude-Full
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

UDEFFDT

Attribute	Description
Name	UDEFFDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description

Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	**Description**

Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

Intms-Inter-Ext-Prdlink

Attribute	**Description**
Name	Intms-Inter-Ext-Prdlink
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

PRODUCTCODE

Attribute	**Description**
Name	PRODUCTCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

PRODUCT_DESC

Attribute	**Description**
Name	PRODUCT_DESC
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

UDEEFFDT

Attribute	**Description**
Name	UDEEFFDT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Intms-Inter-Ext-Ude-Values

Attribute	**Description**
Name	Intms-Inter-Ext-Ude-Values
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

UDEID

Attribute	**Description**
Name	UDEID
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

UDEVALUE

Attribute	**Description**
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22

RULEID

Attribute	Description
Name	RULEID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

UDETYPE

Attribute	Description
Name	UDETYPE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	R,A,N,

UDECCY

Attribute	Description
Name	UDECCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

2.10.2.IN-ModifyINextudval-Req-IO-MSG.xsd

MODIFYINEXTUDVAL_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Inter-Ext-Ude-IO

INTERMEDIARYCODE

UDEFFDT

MAKER

MAKERSTAMP

MODIFYINEXTUDVAL_IOPK_REQ

Attribute	Description
Name	MODIFYINEXTUDVAL_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Inter-Ext-Ude-IO

Attribute	Description
Name	Intms-Inter-Ext-Ude-IO
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

UDEFFDT

Attribute	Description
Name	UDEFFDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

2.10.3.IN-ModifyINextudval-Res-Full-MSG.xsd

MODIFYINEXTUDVAL_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Inter-Ext-Ude-Full

INTERMEDIARYCODE

UDEFFDT

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Intms-Inter-Ext-Prdlink

PRODUCTCODE

PRODUCT_DESC

UDEEFFDT

Intms-Inter-Ext-Ude-Values

UDEID

UDEVALUE

RULEID

UDETYPE

UDECCY

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYINEXTUDVAL_FSFS_RES

Attribute	Description
Name	MODIFYINEXTUDVAL_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description**: minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL

Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Inter-Ext-Ude-Full

Attribute	Description
Name	Intms-Inter-Ext-Ude-Full
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	
	Restrictions / **Description**: maxLength / 16

UDEFFDT

Attribute	Description
Name	UDEFFDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

Intms-Inter-Ext-Prdlink

Attribute	Description
Name	Intms-Inter-Ext-Prdlink
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PRODUCTCODE

Attribute	Description
Name	PRODUCTCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

PRODUCT_DESC

Attribute	Description
Name	PRODUCT_DESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

UDEEFFDT

Attribute	Description
Name	UDEEFFDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Intms-Inter-Ext-Ude-Values

Attribute	Description
Name	Intms-Inter-Ext-Ude-Values
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

UDEVALUE

Attribute	Description
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

RULEID

Attribute	Description
Name	RULEID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

UDETYPE

Attribute	Description
Name	UDETYPE
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>R,A,N,</td></tr></table>

UDECCY

Attribute	Description
Name	UDECCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.10.4.IN-ModifyINextudval-Res-PK-MSG.xsd

MODIFYINEXTUDVAL_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Inter-Ext-Ude-PK

INTERMEDIARYCODE

UDEFFDT

Intms-Inter-Ext-Ude-IO

INTERMEDIARYCODE

UDEFFDT

MAKER

MAKERSTAMP

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYINEXTUDVAL_IOPK_RES

Attribute	Description
Name	MODIFYINEXTUDVAL_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Inter-Ext-Ude-PK

Attribute	Description
Name	Intms-Inter-Ext-Ude-PK
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

UDEFFDT

Attribute	Description
Name	UDEFFDT
Datatype	String
Description	

Intms-Inter-Ext-Ude-IO

Attribute	Description
Name	Intms-Inter-Ext-Ude-IO

Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

UDEFFDT

Attribute	Description
Name	UDEFFDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.11.ModifyINGroup

2.11.1.IN-ModifyINGroup-Req-Full-MSG.xsd

MODIFYINGROUP_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-Group-Full

GRPCD

GROUPDESC

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

MODIFYINGROUP_FSFS_REQ

Attribute	Description
Name	MODIFYINGROUP_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-Group-Full

Attribute	Description

Name	Intms-Intermediary-Group-Full
Datatype	
Description	

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	4

GROUPDESC

Attribute	Description
Name	GROUPDESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	50

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

2.11.2.IN-ModifyINGroup-Req-IO-MSG.xsd

MODIFYINGROUP_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-Group-IO

GRPCD

MAKER

MAKERSTAMP

MODIFYINGROUP_IOPK_REQ

Attribute	Description
Name	MODIFYINGROUP_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-Group-IO

Attribute	Description
Name	Intms-Intermediary-Group-IO
Datatype	
Description	

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

2.11.3.IN-ModifyINGroup-Res-Full-MSG.xsd

MODIFYINGROUP_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-Group-Full

GRPCD

GROUPDESC

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYINGROUP_FSFS_RES

Attribute	Description
Name	MODIFYINGROUP_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description

Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-Group-Full

Attribute	Description
Name	Intms-Intermediary-Group-Full
Datatype	
Description	

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

GROUPDESC

Attribute	Description
Name	GROUPDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	

Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.11.4.IN-ModifyINGroup-Res-PK-MSG.xsd

MODIFYINGROUP_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-Group-PK

GRPCD

Intms-Intermediary-Group-IO

GRPCD

MAKER

MAKERSTAMP

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYINGROUP_IOPK_RES

Attribute	Description
Name	MODIFYINGROUP_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-Group-PK

Attribute	Description
Name	Intms-Intermediary-Group-PK
Datatype	
Description	

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

Intms-Intermediary-Group-IO

Attribute	Description
Name	Intms-Intermediary-Group-IO
Datatype	
Description	

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.12.ModifyInIntermedMaint

2.12.1.IN-ModifyInIntermedMaint-Req-Full-MSG.xsd

- *MODIFYININTERMEDMAINT_FSFS_REQ*
  - *FCUBS_HEADER*
    - *SOURCE*
    - *UBSCOMP*
    - *MSGID*
    - *CORRELID*
    - *USERID*
    - *BRANCH*
    - *MODULEID*
    - *SERVICE*
    - *OPERATION*
    - *SOURCE_OPERATION*
    - *SOURCE_USERID*
    - *DESTINATION*
    - *MULTITRIPID*
    - *FUNCTIONID*
    - *ACTION*
    - *MSGSTAT*
    - *PASSWORD*
    - *ADDL*
      - *PARAM*
        - *NAME*
        - *VALUE*
  - *FCUBS_BODY*
    - *Intms-Intermediary-Full*
      - *INTERMEDIARYCODE*
      - *INTERMEDIARYSTATUS*
      - *INTERMEDIARYCATEGORY*
      - *LEVELNUMBER*
      - *PARENTINTERMEDIARYCODE*

PARENTINTERMEDIARYNAME

ADDRESS1

ADDRESS2

ADDRESS3

COUNTRY

TELEPHONE

EMAILID

ZIP

FAX

MOBILE

INTERMEDIARYCUSTNO

TYPE

CLCTAGENTID

STATEMENTFREQUENCY

STATEMENTSTARTMONTH

STATEMENTSTARTDATE

STATEMENTFREQUENCYUNIT

LASTSTATEMENTDATE

NEXTSTATEMENTDATE

INTERMEDIARYNAME

PRIMARYCONTACT

EFFECTIVEDATE

BRANCHCODE

LIQUIDATIONMODE

MINIMUMLIQAMT

CASCADETILL

ROOTINTM

CASCADE_CHILDS

GRPCD

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Intms-Inter-Settlement

SETTLE_MODE

UPLDSRC

CLGPRODDR

ENDPOINT

ROUTINGNO

EXTACCBNK2

EXT_BRN_CODE

INSTRUMENTNO

SECTORCODE

EXTACCNAME

EXTACCNUMBER

CTG_PROD_CAT

PAYABLEBANK

PAYABLEBRANCH

SETTLEPRD

SETLCCY

SETLACCBRN

STTLACC

Intms-Inter-Prd-Linkage

PRODUCTCODE

PRODUCT_DESC

LASTSETTLEMENTDT

LASTPROCESSINGDATE

NEXTPROCESSINGDATE

MIN_HIERARCHY_COMM

HERRCOMM

Intbs-Inter-Ude-Values

UDEID

UDETYPE

UDEVALUE

INTERMEDIARYPRODUCTCODE

INTERMEDIARYCODE

RULEID

Invws-Inter-Prd-Rule-Ude

RULEID

UDEID

UDEVALUE

Intbs-Inter-Event-Log

INTERMEDIARYCODE

BRANCHCODE

EVENTCODE

EVENT_DATE

EVENTNO

Invws-Event-Ac-Entries

FCCREF

ESN

BRANCHCODE

ACCOUNTNUMBER

BRNLCY

DRCRIND

CODE

FCYAMT

EXRATE

LCYAMT

DATE

VALDT

AMTTAG

EVENT

Intbs-Inter-Event-Adv

EVENTCODE

INTERMEDIARYCODE

BRANCHCODE

EVENTNO

MSGTYPE

SUPPRESS

PRIORITY

PRTYID

CustAcc

BRN

ACC

Misdetails

MISGRP

POOLCD

REFRATE

REFRTTYPE

MISGRPTXN

REFRTCD

REFRTSPRD

CALCMETH

TXNMIS1

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

TXNMIS10

MISGRPCOMP

COMPMIS1

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

COMPMIS10

COSTCOD1

COSTCOD2

COSTCOD3

COSTCOD4

COSTCOD5

RTFLAG

LINKGRP

MisAccLog

- *MISCLS*
- *TXNDT*
- *OLDMISCD*
- *NWMISCD*

MisBalLog

- *BRN*
- *PRDCD*
- *FINYR*
- *TXNDT*
- *GLCODE*
- *MISCLS*
- *OLDMISCD*
- *NWMISCD*
- *TRNIND*
- *CCY*
- *XRATE*

AMT

Chglog

Classname

C2

C3

C4

C6

C7

C8

C9

C10

T1

T3

T5

T6

T7

T8

T9

T10

UDFDETAILS

FLDNAM

FLDVAL

MODIFYININTERMEDMAINT_FSFS_REQ

Attribute	Description
Name	MODIFYININTERMEDMAINT_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-Full

Attribute	Description
Name	Intms-Intermediary-Full
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

INTERMEDIARYSTATUS

Attribute	Description
Name	INTERMEDIARYSTATUS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

INTERMEDIARYCATEGORY

Attribute	Description

Name	INTERMEDIARYCATEGORY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,G,

LEVELNUMBER

Attribute	**Description**
Name	LEVELNUMBER
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

PARENTINTERMEDIARYCODE

Attribute	**Description**
Name	PARENTINTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

PARENTINTERMEDIARYNAME

Attribute	**Description**
Name	PARENTINTERMEDIARYNAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

ADDRESS1

Attribute	**Description**

Name	ADDRESS1
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

ADDRESS2

Attribute	**Description**
Name	ADDRESS2
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

ADDRESS3

Attribute	**Description**
Name	ADDRESS3
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

COUNTRY

Attribute	**Description**
Name	COUNTRY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TELEPHONE

Attribute	**Description**

Name	TELEPHONE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 16

EMAILID

Attribute	**Description**
Name	EMAILID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

ZIP

Attribute	**Description**
Name	ZIP
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 14

FAX

Attribute	**Description**
Name	FAX
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 16

MOBILE

Attribute	**Description**

Name	MOBILE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 10

INTERMEDIARYCUSTNO

Attribute	**Description**
Name	INTERMEDIARYCUSTNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TYPE

Attribute	**Description**
Name	TYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,E

CLCTAGENTID

Attribute	**Description**
Name	CLCTAGENTID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

STATEMENTFREQUENCY

Attribute	**Description**

Name	STATEMENTFREQUENCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Y,

STATEMENTSTARTMONTH

Attribute	**Description**
Name	STATEMENTSTARTMONTH
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

STATEMENTSTARTDATE

Attribute	**Description**
Name	STATEMENTSTARTDATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

STATEMENTFREQUENCYUNIT

Attribute	**Description**
Name	STATEMENTFREQUENCYUNIT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

LASTSTATEMENTDATE

Attribute	**Description**

Name	LASTSTATEMENTDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

NEXTSTATEMENTDATE

Attribute	**Description**
Name	NEXTSTATEMENTDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

INTERMEDIARYNAME

Attribute	**Description**
Name	INTERMEDIARYNAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

PRIMARYCONTACT

Attribute	**Description**
Name	PRIMARYCONTACT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

EFFECTIVEDATE

Attribute	**Description**
Name	EFFECTIVEDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

LIQUIDATIONMODE

Attribute	Description
Name	LIQUIDATIONMODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M,

MINIMUMLIQAMT

Attribute	Description
Name	MINIMUMLIQAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CASCADETILL

Attribute	Description
Name	CASCADETILL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,R,

ROOTINTM

Attribute	Description
Name	ROOTINTM
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CASCADE_CHILDS

Attribute	Description
Name	CASCADE_CHILDS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Intms-Inter-Settlement

Attribute	Description
Name	Intms-Inter-Settlement
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SETTLE_MODE

Attribute	Description
Name	SETTLE_MODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>ACC,EAC,</td></tr></table>

UPLDSRC

Attribute	Description
Name	UPLDSRC
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** maxLength / 20

CLGPRODDR

Attribute	**Description**
Name	CLGPRODDR
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

ENDPOINT

Attribute	**Description**
Name	ENDPOINT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

ROUTINGNO

Attribute	**Description**
Name	ROUTINGNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

EXTACCBNK2

Attribute	**Description**
Name	EXTACCBNK2
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

EXT_BRN_CODE

Attribute	**Description**
Name	EXT_BRN_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

INSTRUMENTNO

Attribute	**Description**
Name	INSTRUMENTNO
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

SECTORCODE

Attribute	**Description**
Name	SECTORCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

EXTACCNAME

Attribute	**Description**
Name	EXTACCNAME
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

EXTACCNUMBER

Attribute	**Description**
Name	EXTACCNUMBER
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

CTG_PROD_CAT

Attribute	**Description**
Name	CTG_PROD_CAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

PAYABLEBANK

Attribute	**Description**
Name	PAYABLEBANK
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

PAYABLEBRANCH

Attribute	**Description**
Name	PAYABLEBRANCH
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

SETTLEPRD

Attribute	**Description**
Name	SETTLEPRD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

SETLCCY

Attribute	**Description**
Name	SETLCCY
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 3

SETLACCBRN

Attribute	**Description**
Name	SETLACCBRN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 4

STTLACC

Attribute	**Description**
Name	STTLACC
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 20

Intms-Inter-Prd-Linkage

Attribute	**Description**

Name	Intms-Inter-Prd-Linkage
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PRODUCTCODE

Attribute	Description
Name	PRODUCTCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	4

PRODUCT_DESC

Attribute	Description
Name	PRODUCT_DESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	50

LASTSETTLEMENTDT

Attribute	Description
Name	LASTSETTLEMENTDT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

LASTPROCESSINGDATE

Attribute	Description
Name	LASTPROCESSINGDATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

NEXTPROCESSINGDATE

Attribute	Description
Name	NEXTPROCESSINGDATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

MIN_HIERARCHY_COMM

Attribute	Description
Name	MIN_HIERARCHY_COMM
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

HERRCOMM

Attribute	Description
Name	HERRCOMM
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>100</td></tr></table>

Intbs-Inter-Ude-Values

Attribute	Description
Name	Intbs-Inter-Ude-Values
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

UDEID

Attribute	Description
Name	UDEID
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

UDETYPE

Attribute	Description
Name	UDETYPE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

UDEVALUE

Attribute	Description
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

INTERMEDIARYPRODUCTCODE

Attribute	Description
Name	INTERMEDIARYPRODUCTCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

RULEID

Attribute	Description
Name	RULEID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

Invws-Inter-Prd-Rule-Ude

Attribute	Description
Name	Invws-Inter-Prd-Rule-Ude
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

RULEID

Attribute	Description
Name	RULEID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

UDEVALUE

Attribute	**Description**
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

Intbs-Inter-Event-Log

Attribute	**Description**
Name	Intbs-Inter-Event-Log
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

INTERMEDIARYCODE

Attribute	**Description**
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

BRANCHCODE

Attribute	**Description**
Name	BRANCHCODE
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

EVENTCODE

Attribute	**Description**
Name	EVENTCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

EVENT_DATE

Attribute	**Description**
Name	EVENT_DATE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

EVENTNO

Attribute	**Description**
Name	EVENTNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

Invws-Event-Ac-Entries

Attribute	**Description**
Name	Invws-Event-Ac-Entries
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

ESN

Attribute	Description
Name	ESN
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

ACCOUNTNUMBER

Attribute	Description
Name	ACCOUNTNUMBER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

BRNLCY

Attribute	Description
Name	BRNLCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

FCYAMT

Attribute	Description
Name	FCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

DATE

Attribute	Description
Name	DATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

VALDT

Attribute	Description
Name	VALDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	35

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

Intbs-Inter-Event-Adv

Attribute	Description
Name	Intbs-Inter-Event-Adv
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

EVENTNO

Attribute	Description
Name	EVENTNO
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	25

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

CustAcc

Attribute	Description
Name	CustAcc
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFRATE

Attribute	Description
Name	REFRATE

Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

REFRTTYPE

Attribute	**Description**
Name	REFRTTYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F

MISGRPTXN

Attribute	**Description**
Name	MISGRPTXN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

REFRTCD

Attribute	**Description**
Name	REFRTCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

REFRTSPRD

Attribute	**Description**
Name	REFRTSPRD

Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CALCMETH

Attribute	**Description**
Name	CALCMETH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,8,9,

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TXNMIS2

Attribute	**Description**
Name	TXNMIS2
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TXNMIS3

Attribute	**Description**
Name	TXNMIS3

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS7

Attribute	Description
Name	TXNMIS7

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS4

Attribute	Description
Name	COMPMIS4

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS8

Attribute	Description
Name	COMPMIS8

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD2

Attribute	Description
Name	COSTCOD2

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

COSTCOD3

Attribute	**Description**
Name	COSTCOD3
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

COSTCOD4

Attribute	**Description**
Name	COSTCOD4
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

COSTCOD5

Attribute	**Description**
Name	COSTCOD5
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

RTFLAG

Attribute	**Description**
Name	RTFLAG

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

MisAccLog

Attribute	Description
Name	MisAccLog
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	

OLDMISCD

Attribute	Description
Name	OLDMISCD

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

MisBalLog

Attribute	Description
Name	MisBalLog
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

FINYR

Attribute	**Description**
Name	FINYR
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TXNDT

Attribute	**Description**
Name	TXNDT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

GLCODE

Attribute	**Description**
Name	GLCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

MISCLS

Attribute	**Description**
Name	MISCLS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	9

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

TRNIND

Attribute	Description
Name	TRNIND
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

XRATE

Attribute	Description
Name	XRATE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

AMT

Attribute	Description
Name	AMT
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

Chglog

Attribute	Description
Name	Chglog
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

Classname

Attribute	Description
Name	Classname
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

C2

Attribute	Description

Name	C2
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C3

Attribute	**Description**
Name	C3
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C4

Attribute	**Description**
Name	C4
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C6

Attribute	**Description**
Name	C6
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C7

Attribute	**Description**

Name	C7
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C8

Attribute	**Description**
Name	C8
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C9

Attribute	**Description**
Name	C9
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C10

Attribute	**Description**
Name	C10
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

T1

Attribute	**Description**

Name	T1
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

T3

Attribute	**Description**
Name	T3
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

T5

Attribute	**Description**
Name	T5
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

T6

Attribute	**Description**
Name	T6
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

T7

Attribute	**Description**

Name	T7
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

T8

Attribute	**Description**
Name	T8
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

T9

Attribute	**Description**
Name	T9
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

T10

Attribute	**Description**
Name	T10
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

UDFDETAILS

Attribute	**Description**

Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.12.2.IN-ModifyInIntermedMaint-Req-IO-MSG.xsd

MODIFYININTERMEDMAINT_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-IO

INTERMEDIARYCODE

INTERMEDIARYSTATUS

INTERMEDIARYCATEGORY

LEVELNUMBER

PARENTINTERMEDIARYCODE

PARENTINTERMEDIARYNAME

ADDRESS1

ADDRESS2

ADDRESS3

COUNTRY

TELEPHONE

EMAILID

ZIP

FAX

MOBILE

INTERMEDIARYCUSTNO

TYPE

CLCTAGENTID

STATEMENTFREQUENCY

STATEMENTSTARTMONTH

STATEMENTSTARTDATE

STATEMENTFREQUENCYUNIT

LASTSTATEMENTDATE

NEXTSTATEMENTDATE

INTERMEDIARYNAME

PRIMARYCONTACT

EFFECTIVEDATE

LIQUIDATIONMODE

MINIMUMLIQAMT

CASCADETILL

ROOTINTM

GRPCD

MAKER

MAKERSTAMP

Intms-Inter-Settlement

- *SETTLE_MODE*
- *EXTACCBNK2*
- *EXTACCNAME*
- *EXTACCNUMBER*
- *SETLCCY*
- *SETLACCBRN*
- *STTLACC*

Intms-Inter-Prd-Linkage

- *PRODUCTCODE*
- *MIN_HIERARCHY_COMM*
- *HERRCOMM*
- *Intbs-Inter-Ude-Values*
  - *UDEID*
  - *UDETYPE*
  - *UDEVALUE*

CustAcc

BRN

ACC

Misdetails

- *UNTREF*
- *MISGRP*
- *POOLCD*
- *REFRATE*
- *REFRTTYPE*
- *MISGRPTXN*
- *REFRTCD*
- *REFRTSPRD*
- *CALCMETH*
- *TXNMIS1*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*
- *TXNMIS10*
- *MISGRPCOMP*
- *COMPMIS1*
- *COMPMIS2*
- *COMPMIS3*
- *COMPMIS4*
- *COMPMIS5*
- *COMPMIS6*
- *COMPMIS7*
- *COMPMIS8*
- *COMPMIS9*

COMPMIS10

COSTCOD1

COSTCOD2

COSTCOD3

COSTCOD4

COSTCOD5

RTFLAG

MisAccLog

MisBalLog

UDFDETAILS

FLDNAM

FLDVAL

MODIFYININTERMEDMAINT_IOPK_REQ

Attribute	Description
Name	MODIFYININTERMEDMAINT_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-IO

Attribute	Description

Name	Intms-Intermediary-IO
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

INTERMEDIARYSTATUS

Attribute	Description
Name	INTERMEDIARYSTATUS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

INTERMEDIARYCATEGORY

Attribute	Description
Name	INTERMEDIARYCATEGORY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,G,

LEVELNUMBER

Attribute	Description
Name	LEVELNUMBER
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22

PARENTINTERMEDIARYCODE

Attribute	Description
Name	PARENTINTERMEDIARYCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

PARENTINTERMEDIARYNAME

Attribute	Description
Name	PARENTINTERMEDIARYNAME
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	32

ADDRESS1

Attribute	Description
Name	ADDRESS1
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	100

ADDRESS2

Attribute	Description
Name	ADDRESS2
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	100

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	100

COUNTRY

Attribute	Description
Name	COUNTRY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

TELEPHONE

Attribute	Description
Name	TELEPHONE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	16

EMAILID

Attribute	Description
Name	EMAILID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: maxLength / 30

ZIP

Attribute	Description
Name	ZIP
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 14

FAX

Attribute	Description
Name	FAX
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 16

MOBILE

Attribute	Description
Name	MOBILE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 10

INTERMEDIARYCUSTNO

Attribute	Description
Name	INTERMEDIARYCUSTNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: maxLength / 16

TYPE

Attribute	Description
Name	TYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,E

CLCTAGENTID

Attribute	Description
Name	CLCTAGENTID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

STATEMENTFREQUENCY

Attribute	Description
Name	STATEMENTFREQUENCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Y,

STATEMENTSTARTMONTH

Attribute	Description
Name	STATEMENTSTARTMONTH
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22

STATEMENTSTARTDATE

Attribute	Description
Name	STATEMENTSTARTDATE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

STATEMENTFREQUENCYUNIT

Attribute	Description
Name	STATEMENTFREQUENCYUNIT
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

LASTSTATEMENTDATE

Attribute	Description
Name	LASTSTATEMENTDATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

NEXTSTATEMENTDATE

Attribute	Description
Name	NEXTSTATEMENTDATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

INTERMEDIARYNAME

Attribute	Description

Name	INTERMEDIARYNAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

PRIMARYCONTACT

Attribute	**Description**
Name	PRIMARYCONTACT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

EFFECTIVEDATE

Attribute	**Description**
Name	EFFECTIVEDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

LIQUIDATIONMODE

Attribute	**Description**
Name	LIQUIDATIONMODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M,

MINIMUMLIQAMT

Attribute	**Description**
Name	MINIMUMLIQAMT
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CASCADETILL

Attribute	**Description**
Name	CASCADETILL
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,R,

ROOTINTM

Attribute	**Description**
Name	ROOTINTM
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

GRPCD

Attribute	**Description**
Name	GRPCD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

Intms-Inter-Settlement

Attribute	**Description**
Name	Intms-Inter-Settlement
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

SETTLE_MODE

Attribute	**Description**
Name	SETTLE_MODE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ACC,EAC,

EXTACCBNK2

Attribute	**Description**
Name	EXTACCBNK2
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	20

EXTACCNAME

Attribute	Description
Name	EXTACCNAME
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

EXTACCNUMBER

Attribute	Description
Name	EXTACCNUMBER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

SETLCCY

Attribute	Description
Name	SETLCCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

SETLACCBRN

Attribute	Description
Name	SETLACCBRN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

STTLACC

Attribute	Description
Name	STTLACC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

Intms-Inter-Prd-Linkage

Attribute	Description
Name	Intms-Inter-Prd-Linkage
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PRODUCTCODE

Attribute	Description
Name	PRODUCTCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

MIN_HIERARCHY_COMM

Attribute	Description
Name	MIN_HIERARCHY_COMM
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

HERRCOMM

Attribute	Description
Name	HERRCOMM
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	100

Intbs-Inter-Ude-Values

Attribute	Description
Name	Intbs-Inter-Ude-Values
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

UDETYPE

Attribute	Description
Name	UDETYPE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

UDEVALUE

Attribute	Description
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CustAcc

Attribute	Description
Name	CustAcc
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

UNTREF

Attribute	Description
Name	UNTREF
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

REFRATE

Attribute	Description
Name	REFRATE

Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

REFRTTYPE

Attribute	**Description**
Name	REFRTTYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F

MISGRPTXN

Attribute	**Description**
Name	MISGRPTXN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

REFRTCD

Attribute	**Description**
Name	REFRTCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

REFRTSPRD

Attribute	**Description**
Name	REFRTSPRD

Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CALCMETH

Attribute	**Description**
Name	CALCMETH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / 1,2,3,4,5,6,7,8,9,

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TXNMIS2

Attribute	**Description**
Name	TXNMIS2
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TXNMIS3

Attribute	**Description**
Name	TXNMIS3

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS7

Attribute	Description
Name	TXNMIS7

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS4

Attribute	Description
Name	COMPMIS4

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS8

Attribute	Description
Name	COMPMIS8

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD2

Attribute	Description
Name	COSTCOD2

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

COSTCOD3

Attribute	**Description**
Name	COSTCOD3
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

COSTCOD4

Attribute	**Description**
Name	COSTCOD4
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

COSTCOD5

Attribute	**Description**
Name	COSTCOD5
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

RTFLAG

Attribute	**Description**
Name	RTFLAG

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

MisAccLog

Attribute	Description
Name	MisAccLog
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

MisBalLog

Attribute	Description
Name	MisBalLog
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description

Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150; minLength / 0

2.12.3.IN-ModifyInIntermedMaint-Res-Full-MSG.xsd

MODIFYININTERMEDMAINT_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-Full

INTERMEDIARYCODE

INTERMEDIARYSTATUS

INTERMEDIARYCATEGORY

LEVELNUMBER

PARENTINTERMEDIARYCODE

PARENTINTERMEDIARYNAME

ADDRESS1

ADDRESS2

ADDRESS3

COUNTRY

TELEPHONE

EMAILID

ZIP

FAX

MOBILE

INTERMEDIARYCUSTNO

TYPE

CLCTAGENTID

STATEMENTFREQUENCY

STATEMENTSTARTMONTH

STATEMENTSTARTDATE

STATEMENTFREQUENCYUNIT

LASTSTATEMENTDATE

NEXTSTATEMENTDATE

INTERMEDIARYNAME

PRIMARYCONTACT

EFFECTIVEDATE

BRANCHCODE

LIQUIDATIONMODE

MINIMUMLIQAMT

CASCADETILL

ROOTINTM

CASCADE_CHILDS

GRPCD

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Intms-Inter-Settlement

- *SETTLE_MODE*
- *UPLDSRC*
- *CLGPRODDR*
- *ENDPOINT*
- *ROUTINGNO*
- *EXTACCBNK2*
- *EXT_BRN_CODE*
- *INSTRUMENTNO*
- *SECTORCODE*
- *EXTACCNAME*
- *EXTACCNUMBER*
- *CTG_PROD_CAT*
- *PAYABLEBANK*
- *PAYABLEBRANCH*
- *SETTLEPRD*
- *SETLCCY*
- *SETLACCBRN*
- *STTLACC*

Intms-Inter-Prd-Linkage

- *PRODUCTCODE*
- *PRODUCT_DESC*
- *LASTSETTLEMENTDT*

LASTPROCESSINGDATE

NEXTPROCESSINGDATE

MIN_HIERARCHY_COMM

HERRCOMM

Intbs-Inter-Ude-Values

UDEID

UDETYPE

UDEVALUE

INTERMEDIARYPRODUCTCODE

INTERMEDIARYCODE

RULEID

Invws-Inter-Prd-Rule-Ude

RULEID

UDEID

UDEVALUE

Intbs-Inter-Event-Log

INTERMEDIARYCODE

BRANCHCODE

EVENTCODE

EVENT_DATE

EVENTNO

Invws-Event-Ac-Entries

FCCREF

ESN

BRANCHCODE

ACCOUNTNUMBER

BRNLCY

DRCRIND

CODE

FCYAMT

EXRATE

LCYAMT

DATE

VALDT

AMTTAG

EVENT

Intbs-Inter-Event-Adv

EVENTCODE

INTERMEDIARYCODE

BRANCHCODE

EVENTNO

MSGTYPE

SUPPRESS

PRIORITY

PRTYID

CustAcc

BRN

ACC

Misdetails

MISGRP

POOLCD

REFRATE

REFRTTYPE

MISGRPTXN

REFRTCD

REFRTSPRD

CALCMETH

TXNMIS1

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

TXNMIS10

MISGRPCOMP

COMPMIS1

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

COMPMIS10

COSTCOD1

COSTCOD2

COSTCOD3

COSTCOD4

COSTCOD5

RTFLAG

LINKGRP

MisAccLog

- *MISCLS*
- *TXNDT*
- *OLDMISCD*
- *NWMISCD*

MisBalLog

- *BRN*
- *PRDCD*
- *FINYR*
- *TXNDT*
- *GLCODE*

MISCLS

OLDMISCD

NWMISCD

TRNIND

CCY

XRATE

AMT

Chglog

Classname

C2

C3

C4

C6

C7

C8

C9

C10

T1

T3

T5

T6

T7

T8

T9

T10

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYININTERMEDMAINT_FSFS_RES

Attribute	Description
Name	MODIFYININTERMEDMAINT_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-Full

Attribute	Description
Name	Intms-Intermediary-Full
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	
	Restrictions / **Description**: maxLength / 16

INTERMEDIARYSTATUS

Attribute	**Description**
Name	INTERMEDIARYSTATUS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

INTERMEDIARYCATEGORY

Attribute	**Description**
Name	INTERMEDIARYCATEGORY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,G,

LEVELNUMBER

Attribute	**Description**
Name	LEVELNUMBER
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

PARENTINTERMEDIARYCODE

Attribute	**Description**
Name	PARENTINTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	16

PARENTINTERMEDIARYNAME

Attribute	Description
Name	PARENTINTERMEDIARYNAME
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	32

ADDRESS1

Attribute	Description
Name	ADDRESS1
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	100

ADDRESS2

Attribute	Description
Name	ADDRESS2
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	100

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: maxLength / 100

COUNTRY

Attribute	Description
Name	COUNTRY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TELEPHONE

Attribute	Description
Name	TELEPHONE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 16

EMAILID

Attribute	Description
Name	EMAILID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

ZIP

Attribute	Description
Name	ZIP
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	14

FAX

Attribute	Description
Name	FAX
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	16

MOBILE

Attribute	Description
Name	MOBILE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	10

INTERMEDIARYCUSTNO

Attribute	Description
Name	INTERMEDIARYCUSTNO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

TYPE

Attribute	Description
Name	TYPE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: enumeration / I,E

CLCTAGENTID

Attribute	**Description**
Name	CLCTAGENTID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

STATEMENTFREQUENCY

Attribute	**Description**
Name	STATEMENTFREQUENCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Y,

STATEMENTSTARTMONTH

Attribute	**Description**
Name	STATEMENTSTARTMONTH
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

STATEMENTSTARTDATE

Attribute	**Description**
Name	STATEMENTSTARTDATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22

STATEMENTFREQUENCYUNIT

Attribute	Description
Name	STATEMENTFREQUENCYUNIT
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

LASTSTATEMENTDATE

Attribute	Description
Name	LASTSTATEMENTDATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

NEXTSTATEMENTDATE

Attribute	Description
Name	NEXTSTATEMENTDATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

INTERMEDIARYNAME

Attribute	Description
Name	INTERMEDIARYNAME
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	32

PRIMARYCONTACT

Attribute	Description

Name	PRIMARYCONTACT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

EFFECTIVEDATE

Attribute	**Description**
Name	EFFECTIVEDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

BRANCHCODE

Attribute	**Description**
Name	BRANCHCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

LIQUIDATIONMODE

Attribute	**Description**
Name	LIQUIDATIONMODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M,

MINIMUMLIQAMT

Attribute	**Description**
Name	MINIMUMLIQAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: totalDigits / 22

CASCADETILL

Attribute	Description
Name	CASCADETILL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,R,

ROOTINTM

Attribute	Description
Name	ROOTINTM
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CASCADE_CHILDS

Attribute	Description
Name	CASCADE_CHILDS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: maxLength / 4

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	4

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

Intms-Inter-Settlement

Attribute	Description
Name	Intms-Inter-Settlement
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

SETTLE_MODE

Attribute	Description
Name	SETTLE_MODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ACC,EAC,

UPLDSRC

Attribute	Description
Name	UPLDSRC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

CLGPRODDR

Attribute	Description
Name	CLGPRODDR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

EXTACCBNK2

Attribute	Description
Name	EXTACCBNK2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

EXT_BRN_CODE

Attribute	Description
Name	EXT_BRN_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

INSTRUMENTNO

Attribute	Description
Name	INSTRUMENTNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

SECTORCODE

Attribute	Description
Name	SECTORCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

EXTACCNAME

Attribute	Description
Name	EXTACCNAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

EXTACCNUMBER

Attribute	Description
Name	EXTACCNUMBER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

CTG_PROD_CAT

Attribute	Description
Name	CTG_PROD_CAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

PAYABLEBANK

Attribute	Description
Name	PAYABLEBANK
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

PAYABLEBRANCH

Attribute	Description
Name	PAYABLEBRANCH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

SETTLEPRD

Attribute	Description
Name	SETTLEPRD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

SETLCCY

Attribute	Description
Name	SETLCCY
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

SETLACCBRN

Attribute	Description
Name	SETLACCBRN
Datatype	String
Description	

Restrictions	
	Restrictions / **Description**: maxLength / 4

STTLACC

Attribute	Description
Name	STTLACC
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 20

Intms-Inter-Prd-Linkage

Attribute	Description
Name	Intms-Inter-Prd-Linkage
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

PRODUCTCODE

Attribute	Description
Name	PRODUCTCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

PRODUCT_DESC

Attribute	Description
Name	PRODUCT_DESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

LASTSETTLEMENTDT

Attribute	Description

Name	LASTSETTLEMENTDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

LASTPROCESSINGDATE

Attribute	Description
Name	LASTPROCESSINGDATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

NEXTPROCESSINGDATE

Attribute	Description
Name	NEXTPROCESSINGDATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

MIN_HIERARCHY_COMM

Attribute	Description
Name	MIN_HIERARCHY_COMM
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

HERRCOMM

Attribute	Description
Name	HERRCOMM
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>100</td></tr></table>

Intbs-Inter-Ude-Values

Attribute	Description
Name	Intbs-Inter-Ude-Values
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

UDETYPE

Attribute	Description
Name	UDETYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

UDEVALUE

Attribute	Description
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

INTERMEDIARYPRODUCTCODE

Attribute	Description

Name	INTERMEDIARYPRODUCTCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

INTERMEDIARYCODE

Attribute	**Description**
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

RULEID

Attribute	**Description**
Name	RULEID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

Invws-Inter-Prd-Rule-Ude

Attribute	**Description**
Name	Invws-Inter-Prd-Rule-Ude
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

RULEID

Attribute	**Description**
Name	RULEID
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

UDEID

Attribute	**Description**
Name	UDEID
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

UDEVALUE

Attribute	**Description**
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

Intbs-Inter-Event-Log

Attribute	**Description**
Name	Intbs-Inter-Event-Log
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

INTERMEDIARYCODE

Attribute	**Description**
Name	INTERMEDIARYCODE
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

BRANCHCODE

Attribute	**Description**
Name	BRANCHCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

EVENTCODE

Attribute	**Description**
Name	EVENTCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

EVENT_DATE

Attribute	**Description**
Name	EVENT_DATE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

EVENTNO

Attribute	**Description**
Name	EVENTNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22

Invws-Event-Ac-Entries

Attribute	Description
Name	Invws-Event-Ac-Entries
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

ESN

Attribute	Description
Name	ESN
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

ACCOUNTNUMBER

Attribute	Description
Name	ACCOUNTNUMBER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

BRNLCY

Attribute	Description
Name	BRNLCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: maxLength / 3

FCYAMT

Attribute	Description
Name	FCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

DATE

Attribute	Description
Name	DATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

VALDT

Attribute	Description
Name	VALDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

Intbs-Inter-Event-Adv

Attribute	Description
Name	Intbs-Inter-Event-Adv
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

INTERMEDIARYCODE

Attribute	**Description**
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

BRANCHCODE

Attribute	**Description**
Name	BRANCHCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

EVENTNO

Attribute	**Description**
Name	EVENTNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

MSGTYPE

Attribute	**Description**
Name	MSGTYPE
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** maxLength / 25

SUPPRESS

Attribute	**Description**
Name	SUPPRESS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

PRTYID

Attribute	**Description**
Name	PRTYID
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

CustAcc

Attribute	**Description**
Name	CustAcc
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFRATE

Attribute	Description
Name	REFRATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>1,2,3,4,5,6,7,8,9,</td></tr></table>

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

MisAccLog

Attribute	Description
Name	MisAccLog
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String

Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

MisBalLog

Attribute	Description
Name	MisBalLog
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRN

Attribute	Description
Name	BRN
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TRNIND

Attribute	Description
Name	TRNIND
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

XRATE

Attribute	Description
Name	XRATE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

AMT

Attribute	Description
Name	AMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

Chglog

Attribute	Description
Name	Chglog
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0

Classname

Attribute	Description
Name	Classname
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

C2

Attribute	Description
Name	C2
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

C3

Attribute	Description
Name	C3
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

C4

Attribute	Description
Name	C4
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

C6

Attribute	Description
Name	C6
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C7

Attribute	Description
Name	C7
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C8

Attribute	Description
Name	C8
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C9

Attribute	Description
Name	C9
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C10

Attribute	Description
Name	C10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T1

Attribute	Description
Name	T1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T3

Attribute	Description
Name	T3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T5

Attribute	Description
Name	T5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T6

Attribute	Description
Name	T6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T7

Attribute	Description
Name	T7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T8

Attribute	Description
Name	T8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T9

Attribute	Description
Name	T9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T10

Attribute	Description
Name	T10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.12.4.IN-ModifyInIntermedMaint-Res-PK-MSG.xsd

MODIFYININTERMEDMAINT_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-PK

INTERMEDIARYCODE

Intms-Intermediary-IO

INTERMEDIARYCODE

INTERMEDIARYSTATUS

INTERMEDIARYCATEGORY

LEVELNUMBER

PARENTINTERMEDIARYCODE

PARENTINTERMEDIARYNAME

ADDRESS1

ADDRESS2

ADDRESS3

COUNTRY

TELEPHONE

EMAILID

ZIP

FAX

MOBILE

INTERMEDIARYCUSTNO

TYPE

CLCTAGENTID

STATEMENTFREQUENCY

STATEMENTSTARTMONTH

STATEMENTSTARTDATE

STATEMENTFREQUENCYUNIT

LASTSTATEMENTDATE

NEXTSTATEMENTDATE

INTERMEDIARYNAME

PRIMARYCONTACT

EFFECTIVEDATE

LIQUIDATIONMODE

MINIMUMLIQAMT

CASCADETILL

ROOTINTM

GRPCD

MAKER

MAKERSTAMP

Intms-Inter-Settlement

SETTLE_MODE

EXTACCBNK2

EXTACCNAME

EXTACCNUMBER

SETLCCY

SETLACCBRN

STTLACC

Intms-Inter-Prd-Linkage

PRODUCTCODE

MIN_HIERARCHY_COMM

HERRCOMM

Intbs-Inter-Ude-Values

UDEID

UDETYPE

UDEVALUE

CustAcc

BRN

ACC

Misdetails

UNTREF

MISGRP

POOLCD

REFRATE

REFRTTYPE

MISGRPTXN

REFRTCD

REFRTSPRD

CALCMETH

TXNMIS1

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

TXNMIS10

MISGRPCOMP

COMPMIS1

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

COMPMIS10

COSTCOD1

COSTCOD2

COSTCOD3

COSTCOD4

COSTCOD5

RTFLAG

MisAccLog

MisBalLog

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYININTERMEDMAINT_IOPK_RES

Attribute	Description
Name	MODIFYININTERMEDMAINT_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String

Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.

Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-PK

Attribute	Description
Name	Intms-Intermediary-PK
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description

Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

Intms-Intermediary-IO

Attribute	**Description**
Name	Intms-Intermediary-IO
Datatype	
Description	

INTERMEDIARYCODE

Attribute	**Description**
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

INTERMEDIARYSTATUS

Attribute	**Description**
Name	INTERMEDIARYSTATUS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,I

INTERMEDIARYCATEGORY

Attribute	**Description**
Name	INTERMEDIARYCATEGORY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	I,G,

LEVELNUMBER

Attribute	Description
Name	LEVELNUMBER
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

PARENTINTERMEDIARYCODE

Attribute	Description
Name	PARENTINTERMEDIARYCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

PARENTINTERMEDIARYNAME

Attribute	Description
Name	PARENTINTERMEDIARYNAME
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	32

ADDRESS1

Attribute	Description
Name	ADDRESS1
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	100

ADDRESS2

Attribute	Description
Name	ADDRESS2
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	100

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	100

COUNTRY

Attribute	Description
Name	COUNTRY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

TELEPHONE

Attribute	Description
Name	TELEPHONE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	16

EMAILID

Attribute	Description
Name	EMAILID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	30

ZIP

Attribute	Description
Name	ZIP
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	14

FAX

Attribute	Description
Name	FAX
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	16

MOBILE

Attribute	Description
Name	MOBILE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	10

INTERMEDIARYCUSTNO

Attribute	Description
Name	INTERMEDIARYCUSTNO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

TYPE

Attribute	Description
Name	TYPE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	I,E

CLCTAGENTID

Attribute	Description
Name	CLCTAGENTID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

STATEMENTFREQUENCY

Attribute	Description
Name	STATEMENTFREQUENCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	D,W,M,Y,

STATEMENTSTARTMONTH

Attribute	Description
Name	STATEMENTSTARTMONTH
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

STATEMENTSTARTDATE

Attribute	Description
Name	STATEMENTSTARTDATE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

STATEMENTFREQUENCYUNIT

Attribute	Description
Name	STATEMENTFREQUENCYUNIT
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

LASTSTATEMENTDATE

Attribute	Description
Name	LASTSTATEMENTDATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

NEXTSTATEMENTDATE

Attribute	Description
Name	NEXTSTATEMENTDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

INTERMEDIARYNAME

Attribute	Description
Name	INTERMEDIARYNAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

PRIMARYCONTACT

Attribute	Description
Name	PRIMARYCONTACT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

EFFECTIVEDATE

Attribute	Description
Name	EFFECTIVEDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

LIQUIDATIONMODE

Attribute	Description
Name	LIQUIDATIONMODE
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M,

MINIMUMLIQAMT

Attribute	**Description**
Name	MINIMUMLIQAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CASCADETILL

Attribute	**Description**
Name	CASCADETILL
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,R,

ROOTINTM

Attribute	**Description**
Name	ROOTINTM
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

GRPCD

Attribute	**Description**
Name	GRPCD
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

Intms-Inter-Settlement

Attribute	**Description**
Name	Intms-Inter-Settlement
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

SETTLE_MODE

Attribute	**Description**
Name	SETTLE_MODE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	ACC,EAC,

EXTACCBNK2

Attribute	Description
Name	EXTACCBNK2
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

EXTACCNAME

Attribute	Description
Name	EXTACCNAME
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

EXTACCNUMBER

Attribute	Description
Name	EXTACCNUMBER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

SETLCCY

Attribute	Description
Name	SETLCCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

SETLACCBRN

Attribute	Description
Name	SETLACCBRN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

STTLACC

Attribute	Description
Name	STTLACC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

Intms-Inter-Prd-Linkage

Attribute	Description
Name	Intms-Inter-Prd-Linkage
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PRODUCTCODE

Attribute	Description
Name	PRODUCTCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

MIN_HIERARCHY_COMM

Attribute	Description
Name	MIN_HIERARCHY_COMM
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

HERRCOMM

Attribute	Description
Name	HERRCOMM
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	100

Intbs-Inter-Ude-Values

Attribute	Description
Name	Intbs-Inter-Ude-Values
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

UDETYPE

Attribute	Description
Name	UDETYPE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

UDEVALUE

Attribute	Description
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CustAcc

Attribute	Description
Name	CustAcc
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

UNTREF

Attribute	Description
Name	UNTREF
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFRATE

Attribute	**Description**
Name	REFRATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

REFRTTYPE

Attribute	**Description**
Name	REFRTTYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F

MISGRPTXN

Attribute	**Description**
Name	MISGRPTXN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

REFRTCD

Attribute	**Description**
Name	REFRTCD

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>1,2,3,4,5,6,7,8,9,</td></tr></table>

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS6

Attribute	Description
Name	TXNMIS6

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS10

Attribute	Description
Name	TXNMIS10

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS7

Attribute	Description
Name	COMPMIS7

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD1

Attribute	Description
Name	COSTCOD1

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

COSTCOD2

Attribute	**Description**
Name	COSTCOD2
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

COSTCOD3

Attribute	**Description**
Name	COSTCOD3
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

COSTCOD4

Attribute	**Description**
Name	COSTCOD4
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

COSTCOD5

Attribute	**Description**
Name	COSTCOD5

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

MisAccLog

Attribute	Description
Name	MisAccLog
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

MisBalLog

Attribute	Description
Name	MisBalLog
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description

Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.13.QueryINbrnmaint

2.13.1.IN-QueryINbrnmaint-Req-IO-MSG.xsd

QUERYINBRNMAINT_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Branch-Parameter-IO

BRANCHCODE

QUERYINBRNMAINT_IOFS_REQ

Attribute	Description
Name	QUERYINBRNMAINT_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description

Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID

Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".

Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String

Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Branch-Parameter-IO

Attribute	Description
Name	Intms-Branch-Parameter-IO
Datatype	
Description	

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

2.13.2.IN-QueryINbrnmaint-Res-Full-MSG.xsd

QUERYINBRNMAINT_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Branch-Parameter-IO

BRANCHCODE

Intms-Branch-Parameter-Full

BRANCHCODE

BRNAM

PROCESSTILL

INTERMEDIARYDLYCOMP

PRDCATPC

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYINBRNMAINT_IOFS_RES

Attribute	Description

Name	QUERYINBRNMAINT_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Branch-Parameter-IO

Attribute	Description
Name	Intms-Branch-Parameter-IO
Datatype	
Description	

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

Intms-Branch-Parameter-Full

Attribute	Description
Name	Intms-Branch-Parameter-Full
Datatype	
Description	

BRANCHCODE

Attribute	Description

Name	BRANCHCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

BRNAM

Attribute	**Description**
Name	BRNAM
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

PROCESSTILL

Attribute	**Description**
Name	PROCESSTILL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,N

INTERMEDIARYDLYCOMP

Attribute	**Description**
Name	INTERMEDIARYDLYCOMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

PRDCATPC

Attribute	**Description**
Name	PRDCATPC
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.14.QueryINextudval

2.14.1.IN-QueryINextudval-Req-IO-MSG.xsd

QUERYINEXTUDVAL_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Inter-Ext-Ude-IO

INTERMEDIARYCODE

UDEFFDT

QUERYINEXTUDVAL_IOFS_REQ

Attribute	Description
Name	QUERYINEXTUDVAL_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description**: minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL

Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Inter-Ext-Ude-IO

Attribute	Description
Name	Intms-Inter-Ext-Ude-IO
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

UDEFFDT

Attribute	Description
Name	UDEFFDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

2.14.2.IN-QueryINextudval-Res-Full-MSG.xsd

QUERYINEXTUDVAL_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Inter-Ext-Ude-IO

INTERMEDIARYCODE

UDEFFDT

Intms-Inter-Ext-Ude-Full

INTERMEDIARYCODE

UDEFFDT

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Intms-Inter-Ext-Prdlink

PRODUCTCODE

PRODUCT_DESC

UDEEFFDT

Intms-Inter-Ext-Ude-Values

UDEID

UDEVALUE

RULEID

UDETYPE

UDECCY

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYINEXTUDVAL_IOFS_RES

Attribute	Description
Name	QUERYINEXTUDVAL_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description**: minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL

Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Inter-Ext-Ude-IO

Attribute	Description
Name	Intms-Inter-Ext-Ude-IO
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	16

UDEFFDT

Attribute	Description
Name	UDEFFDT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Intms-Inter-Ext-Ude-Full

Attribute	Description
Name	Intms-Inter-Ext-Ude-Full
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

UDEFFDT

Attribute	Description
Name	UDEFFDT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	4

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

Intms-Inter-Ext-Prdlink

Attribute	Description
Name	Intms-Inter-Ext-Prdlink
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PRODUCTCODE

Attribute	Description
Name	PRODUCTCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

PRODUCT_DESC

Attribute	Description
Name	PRODUCT_DESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	50

UDEEFFDT

Attribute	Description
Name	UDEEFFDT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Intms-Inter-Ext-Ude-Values

Attribute	Description
Name	Intms-Inter-Ext-Ude-Values
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

UDEVALUE

Attribute	Description

Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

RULEID

Attribute	**Description**
Name	RULEID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

UDETYPE

Attribute	**Description**
Name	UDETYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / R,A,N,

UDECCY

Attribute	**Description**
Name	UDECCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

FCUBS_ERROR_RESP

Attribute	**Description**

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

WCODE

Attribute	Description

Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.15.QueryINGroup

2.15.1.IN-QueryINGroup-Req-IO-MSG.xsd

QUERYINGROUP_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-Group-IO

GRPCD

QUERYINGROUP_IOFS_REQ

Attribute	Description
Name	QUERYINGROUP_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description**: minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL

Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-Group-IO

Attribute	Description
Name	Intms-Intermediary-Group-IO
Datatype	
Description	

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

2.15.2.IN-QueryINGroup-Res-Full-MSG.xsd

QUERYINGROUP_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-Group-IO

GRPCD

Intms-Intermediary-Group-Full

GRPCD

GROUPDESC

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYINGROUP_IOFS_RES

Attribute	Description
Name	QUERYINGROUP_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-Group-IO

Attribute	Description

Name	Intms-Intermediary-Group-IO
Datatype	
Description	

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	4

Intms-Intermediary-Group-Full

Attribute	Description
Name	Intms-Intermediary-Group-Full
Datatype	
Description	

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	4

GROUPDESC

Attribute	Description
Name	GROUPDESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	50

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description** maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	4

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description

Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.16.QueryInIntermedMaint

2.16.1.IN-QueryInIntermedMaint-Req-IO-MSG.xsd

QUERYININTERMEDMAINT_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-IO

INTERMEDIARYCODE

QUERYININTERMEDMAINT_IOFS_REQ

Attribute	Description
Name	QUERYININTERMEDMAINT_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-IO

Attribute	Description
Name	Intms-Intermediary-IO
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

2.16.2.IN-QueryInIntermedMaint-Res-Full-MSG.xsd

QUERYININTERMEDMAINT_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-IO

INTERMEDIARYCODE

Intms-Intermediary-Full

INTERMEDIARYCODE

INTERMEDIARYSTATUS

INTERMEDIARYCATEGORY

LEVELNUMBER

PARENTINTERMEDIARYCODE

PARENTINTERMEDIARYNAME

ADDRESS1

ADDRESS2

ADDRESS3

COUNTRY

TELEPHONE

EMAILID

ZIP

FAX

MOBILE

INTERMEDIARYCUSTNO

TYPE

CLCTAGENTID

STATEMENTFREQUENCY

STATEMENTSTARTMONTH

STATEMENTSTARTDATE

STATEMENTFREQUENCYUNIT

LASTSTATEMENTDATE

NEXTSTATEMENTDATE

INTERMEDIARYNAME

PRIMARYCONTACT

EFFECTIVEDATE

BRANCHCODE

LIQUIDATIONMODE

MINIMUMLIQAMT

CASCADETILL

ROOTINTM

CASCADE_CHILDS

GRPCD

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Intms-Inter-Settlement

- *SETTLE_MODE*
- *UPLDSRC*
- *CLGPRODDR*
- *ENDPOINT*

ROUTINGNO

EXTACCBNK2

EXT_BRN_CODE

INSTRUMENTNO

SECTORCODE

EXTACCNAME

EXTACCNUMBER

CTG_PROD_CAT

PAYABLEBANK

PAYABLEBRANCH

SETTLEPRD

SETLCCY

SETLACCBRN

STTLACC

Intms-Inter-Prd-Linkage

PRODUCTCODE

PRODUCT_DESC

LASTSETTLEMENTDT

LASTPROCESSINGDATE

NEXTPROCESSINGDATE

MIN_HIERARCHY_COMM

HERRCOMM

Intbs-Inter-Ude-Values

UDEID

UDETYPE

UDEVALUE

INTERMEDIARYPRODUCTCODE

INTERMEDIARYCODE

RULEID

Invws-Inter-Prd-Rule-Ude

RULEID

UDEID

UDEVALUE

Intbs-Inter-Event-Log

INTERMEDIARYCODE

BRANCHCODE

EVENTCODE

EVENT_DATE

EVENTNO

Invws-Event-Ac-Entries

FCCREF

ESN

BRANCHCODE

ACCOUNTNUMBER

BRNLCY

DRCRIND

CODE

FCYAMT

EXRATE

LCYAMT

DATE

VALDT

AMTTAG

EVENT

Intbs-Inter-Event-Adv

EVENTCODE

INTERMEDIARYCODE

BRANCHCODE

EVENTNO

MSGTYPE

SUPPRESS

PRIORITY

PRTYID

CustAcc

BRN

ACC

Misdetails

- *MISGRP*
- *POOLCD*
- *REFRATE*
- *REFRTTYPE*
- *MISGRPTXN*
- *REFRTCD*
- *REFRTSPRD*
- *CALCMETH*
- *TXNMIS1*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*
- *TXNMIS10*
- *MISGRPCOMP*
- *COMPMIS1*
- *COMPMIS2*
- *COMPMIS3*
- *COMPMIS4*
- *COMPMIS5*
- *COMPMIS6*
- *COMPMIS7*
- *COMPMIS8*
- *COMPMIS9*
- *COMPMIS10*

COSTCOD1

COSTCOD2

COSTCOD3

COSTCOD4

COSTCOD5

RTFLAG

LINKGRP

MisAccLog

MISCLS

TXNDT

OLDMISCD

NWMISCD

MisBalLog

BRN

PRDCD

FINYR

TXNDT

GLCODE

MISCLS

OLDMISCD

NWMISCD

TRNIND

CCY

XRATE

AMT

Chglog

Classname

C2

C3

C4

C6

C7

C8

C9

C10

T1

T3

T5

T6

T7

T8

T9

T10

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYININTERMEDMAINT_IOFS_RES

Attribute	Description
Name	QUERYININTERMEDMAINT_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-IO

Attribute	Description
Name	Intms-Intermediary-IO
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

Intms-Intermediary-Full

Attribute	Description
Name	Intms-Intermediary-Full
Datatype	
Description	

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	16

INTERMEDIARYSTATUS

Attribute	Description
Name	INTERMEDIARYSTATUS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	A,I

INTERMEDIARYCATEGORY

Attribute	Description
Name	INTERMEDIARYCATEGORY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	I,G,

LEVELNUMBER

Attribute	Description
Name	LEVELNUMBER
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

PARENTINTERMEDIARYCODE

Attribute	Description
Name	PARENTINTERMEDIARYCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

PARENTINTERMEDIARYNAME

Attribute	Description
Name	PARENTINTERMEDIARYNAME
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	32

ADDRESS1

Attribute	Description
Name	ADDRESS1
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	100

ADDRESS2

Attribute	Description
Name	ADDRESS2
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	100

ADDRESS3

Attribute	Description
Name	ADDRESS3
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	100

COUNTRY

Attribute	Description
Name	COUNTRY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

TELEPHONE

Attribute	Description
Name	TELEPHONE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	16

EMAILID

Attribute	Description
Name	EMAILID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	30

ZIP

Attribute	Description
Name	ZIP
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	14

FAX

Attribute	Description
Name	FAX
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	16

MOBILE

Attribute	Description
Name	MOBILE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	10

INTERMEDIARYCUSTNO

Attribute	Description
Name	INTERMEDIARYCUSTNO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

TYPE

Attribute	Description
Name	TYPE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: enumeration / I,E

CLCTAGENTID

Attribute	**Description**
Name	CLCTAGENTID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

STATEMENTFREQUENCY

Attribute	**Description**
Name	STATEMENTFREQUENCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,W,M,Y,

STATEMENTSTARTMONTH

Attribute	**Description**
Name	STATEMENTSTARTMONTH
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

STATEMENTSTARTDATE

Attribute	**Description**
Name	STATEMENTSTARTDATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description** totalDigits / 22

STATEMENTFREQUENCYUNIT

Attribute	Description
Name	STATEMENTFREQUENCYUNIT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

LASTSTATEMENTDATE

Attribute	Description
Name	LASTSTATEMENTDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

NEXTSTATEMENTDATE

Attribute	Description
Name	NEXTSTATEMENTDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

INTERMEDIARYNAME

Attribute	Description
Name	INTERMEDIARYNAME
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

PRIMARYCONTACT

Attribute	Description

Name	PRIMARYCONTACT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

EFFECTIVEDATE

Attribute	**Description**
Name	EFFECTIVEDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

BRANCHCODE

Attribute	**Description**
Name	BRANCHCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

LIQUIDATIONMODE

Attribute	**Description**
Name	LIQUIDATIONMODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M,

MINIMUMLIQAMT

Attribute	**Description**
Name	MINIMUMLIQAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: totalDigits / 22

CASCADETILL

Attribute	Description
Name	CASCADETILL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,R,

ROOTINTM

Attribute	Description
Name	ROOTINTM
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CASCADE_CHILDS

Attribute	Description
Name	CASCADE_CHILDS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	4

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	4

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

Intms-Inter-Settlement

Attribute	Description
Name	Intms-Inter-Settlement
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

SETTLE_MODE

Attribute	Description
Name	SETTLE_MODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ACC,EAC,

UPLDSRC

Attribute	Description
Name	UPLDSRC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

CLGPRODDR

Attribute	Description
Name	CLGPRODDR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

EXTACCBNK2

Attribute	Description
Name	EXTACCBNK2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

EXT_BRN_CODE

Attribute	Description
Name	EXT_BRN_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

INSTRUMENTNO

Attribute	Description
Name	INSTRUMENTNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

SECTORCODE

Attribute	Description
Name	SECTORCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

EXTACCNAME

Attribute	Description
Name	EXTACCNAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

EXTACCNUMBER

Attribute	Description
Name	EXTACCNUMBER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

CTG_PROD_CAT

Attribute	Description
Name	CTG_PROD_CAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

PAYABLEBANK

Attribute	Description
Name	PAYABLEBANK
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

PAYABLEBRANCH

Attribute	Description
Name	PAYABLEBRANCH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

SETTLEPRD

Attribute	Description
Name	SETTLEPRD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

SETLCCY

Attribute	Description
Name	SETLCCY
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

SETLACCBRN

Attribute	Description
Name	SETLACCBRN
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	4

STTLACC

Attribute	Description
Name	STTLACC
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	20

Intms-Inter-Prd-Linkage

Attribute	Description
Name	Intms-Inter-Prd-Linkage
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PRODUCTCODE

Attribute	Description
Name	PRODUCTCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

PRODUCT_DESC

Attribute	Description
Name	PRODUCT_DESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	50

LASTSETTLEMENTDT

Attribute	Description

Name	LASTSETTLEMENTDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

LASTPROCESSINGDATE

Attribute	**Description**
Name	LASTPROCESSINGDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

NEXTPROCESSINGDATE

Attribute	**Description**
Name	NEXTPROCESSINGDATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

MIN_HIERARCHY_COMM

Attribute	**Description**
Name	MIN_HIERARCHY_COMM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

HERRCOMM

Attribute	**Description**
Name	HERRCOMM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 100

Intbs-Inter-Ude-Values

Attribute	Description
Name	Intbs-Inter-Ude-Values
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

UDETYPE

Attribute	Description
Name	UDETYPE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

UDEVALUE

Attribute	Description
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

INTERMEDIARYPRODUCTCODE

Attribute	Description

Name	INTERMEDIARYPRODUCTCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

INTERMEDIARYCODE

Attribute	**Description**
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

RULEID

Attribute	**Description**
Name	RULEID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

Invws-Inter-Prd-Rule-Ude

Attribute	**Description**
Name	Invws-Inter-Prd-Rule-Ude
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

RULEID

Attribute	**Description**
Name	RULEID
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

UDEID

Attribute	**Description**
Name	UDEID
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

UDEVALUE

Attribute	**Description**
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

Intbs-Inter-Event-Log

Attribute	**Description**
Name	Intbs-Inter-Event-Log
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

INTERMEDIARYCODE

Attribute	**Description**
Name	INTERMEDIARYCODE
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

BRANCHCODE

Attribute	**Description**
Name	BRANCHCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

EVENTCODE

Attribute	**Description**
Name	EVENTCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

EVENT_DATE

Attribute	**Description**
Name	EVENT_DATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

EVENTNO

Attribute	**Description**
Name	EVENTNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22

Invws-Event-Ac-Entries

Attribute	Description
Name	Invws-Event-Ac-Entries
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

ESN

Attribute	Description
Name	ESN
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

ACCOUNTNUMBER

Attribute	Description
Name	ACCOUNTNUMBER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

BRNLCY

Attribute	Description
Name	BRNLCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: maxLength / 3

FCYAMT

Attribute	Description
Name	FCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

DATE

Attribute	Description
Name	DATE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

VALDT

Attribute	Description
Name	VALDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

Intbs-Inter-Event-Adv

Attribute	Description
Name	Intbs-Inter-Event-Adv
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 4

INTERMEDIARYCODE

Attribute	**Description**
Name	INTERMEDIARYCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

BRANCHCODE

Attribute	**Description**
Name	BRANCHCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

EVENTNO

Attribute	**Description**
Name	EVENTNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

MSGTYPE

Attribute	**Description**
Name	MSGTYPE
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** maxLength / 25

SUPPRESS

Attribute	**Description**
Name	SUPPRESS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

PRTYID

Attribute	**Description**
Name	PRTYID
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

CustAcc

Attribute	**Description**
Name	CustAcc
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REFRATE

Attribute	Description
Name	REFRATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>1,2,3,4,5,6,7,8,9,</td></tr></table>

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,R</td></tr></table>

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

MisAccLog

Attribute	Description
Name	MisAccLog
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String

Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

MisBalLog

Attribute	Description
Name	MisBalLog
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRN

Attribute	Description
Name	BRN
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TXNDT

Attribute	Description
Name	TXNDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

TRNIND

Attribute	Description
Name	TRNIND
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

XRATE

Attribute	**Description**
Name	XRATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

AMT

Attribute	**Description**
Name	AMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

Chglog

Attribute	**Description**
Name	Chglog
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0

Classname

Attribute	Description
Name	Classname
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

C2

Attribute	Description
Name	C2
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

C3

Attribute	Description
Name	C3
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

C4

Attribute	Description
Name	C4
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

C6

Attribute	Description
Name	C6
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C7

Attribute	Description
Name	C7
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C8

Attribute	Description
Name	C8
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C9

Attribute	Description
Name	C9
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

C10

Attribute	Description
Name	C10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T1

Attribute	Description
Name	T1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T3

Attribute	Description
Name	T3
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T5

Attribute	Description
Name	T5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T6

Attribute	Description
Name	T6
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T7

Attribute	Description
Name	T7
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T8

Attribute	Description
Name	T8
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T9

Attribute	Description
Name	T9
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

T10

Attribute	Description
Name	T10
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.17.QueryInProdMaint

2.17.1.IN-QueryInProdMaint-Req-IO-MSG.xsd

QUERYINPRODMAINT_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-Product-IO

INTERMEDIARYPRODUCTCODE

QUERYINPRODMAINT_IOFS_REQ

Attribute	Description
Name	QUERYINPRODMAINT_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-Product-IO

Attribute	Description
Name	Intms-Intermediary-Product-IO
Datatype	
Description	

INTERMEDIARYPRODUCTCODE

Attribute	Description
Name	INTERMEDIARYPRODUCTCODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

2.17.2.IN-QueryInProdMaint-Res-Full-MSG.xsd

QUERYINPRODMAINT_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Intermediary-Product-IO

INTERMEDIARYPRODUCTCODE

Intms-Intermediary-Product-Full

INTERMEDIARYPRODUCTCODE

PRODUCT_DESC

STARTDT

ENDDT

SETTLEMENTFREQ

SETTLEMENTFREQUT

REMARKS

BRANCH_RESTRICTION

CURRENCY_RESTRICTION

LOAN_RESTRICTION

SETTLESTARTMONTH

SETTLESTARTDATE

CHARGEBACKUNIT

CHARGEBACKPERIOD

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Intms-Interm-Brn-Restrict

- *BRANCHCODE*
- *BRNDESC*

Intms-Interm-Ccy-Restrict

- *CCYCODE*
- *CCYDESC*

Intms-Interm-Loan-Restrictn

- *PRDPRDCD*
- *PRODUCT_DESC*

Intms-Inter-Prd-Rule

- *RULEID*
- *RULEDESC*

Product-Events

- *CLASCD*
- *CLASDESC*
- *Event-Details*
  - *EVNTCD*
  - *EVENTDESC*
  - *Accounting-Entries*
    - *ACCRLCD*
    - *AMTTAG*

DRCRINDICTR

TRNCD

NETINDICTR

MISHD

REVALPRGL

REVALLSGL

REVALRTCD

REVALTXNCD

HOLTREAT

REVALREQD

RATE_TYPE_INDICATOR

Advices

MSGTYP

DESC

GENTIME

SUPRS

PRIOR

CHGREQD

Role-To-Head-Mapping

CLASCD

CLASDESC

Mapping-Details

ACCTRL

ROLDESC

ACCTHD

GLDESC

Product-Mis-Details

MISGRP

POOLCD

CSTCD1

CSTCD2

CSTCD4

CSTCD5

Default-Mis-Codes

MISCLS

MISCD

Dummy-Prd

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYINPRODMAINT_IOFS_RES

Attribute	Description
Name	QUERYINPRODMAINT_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE

Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Intermediary-Product-IO

Attribute	Description

Name	Intms-Intermediary-Product-IO
Datatype	
Description	

INTERMEDIARYPRODUCTCODE

Attribute	Description
Name	INTERMEDIARYPRODUCTCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

Intms-Intermediary-Product-Full

Attribute	Description
Name	Intms-Intermediary-Product-Full
Datatype	
Description	

INTERMEDIARYPRODUCTCODE

Attribute	Description
Name	INTERMEDIARYPRODUCTCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

PRODUCT_DESC

Attribute	Description
Name	PRODUCT_DESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

STARTDT

Attribute	Description
Name	STARTDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

ENDDT

Attribute	Description
Name	ENDDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SETTLEMENTFREQ

Attribute	Description
Name	SETTLEMENTFREQ
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>D,W,M,Y,</td></tr></table>

SETTLEMENTFREQUT

Attribute	Description
Name	SETTLEMENTFREQUT
Datatype	Decimal
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>1</td></tr></table>

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>100</td></tr></table>

BRANCH_RESTRICTION

Attribute	Description
Name	BRANCH_RESTRICTION
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
enumeration	A,D

CURRENCY_RESTRICTION

Attribute	Description
Name	CURRENCY_RESTRICTION
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	A,D

LOAN_RESTRICTION

Attribute	Description
Name	LOAN_RESTRICTION
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	A,D

SETTLESTARTMONTH

Attribute	Description
Name	SETTLESTARTMONTH
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

SETTLESTARTDATE

Attribute	Description
Name	SETTLESTARTDATE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1
maxInclusive	31

CHARGEBACKUNIT

Attribute	Description
Name	CHARGEBACKUNIT
Datatype	String
Description	
Restrictions	

Restrictions	Description
enumeration	D,W,M,Y,

CHARGEBACKPERIOD

Attribute	Description
Name	CHARGEBACKPERIOD
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	22

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Intms-Interm-Brn-Restrict

Attribute	Description
Name	Intms-Interm-Brn-Restrict
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

BRNDESC

Attribute	Description
Name	BRNDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

Intms-Interm-Ccy-Restrict

Attribute	Description
Name	Intms-Interm-Ccy-Restrict
Datatype	

Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

CCYCODE

Attribute	Description
Name	CCYCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

CCYDESC

Attribute	Description
Name	CCYDESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	50

Intms-Interm-Loan-Restrictn

Attribute	Description
Name	Intms-Interm-Loan-Restrictn
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PRDPRDCD

Attribute	Description
Name	PRDPRDCD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4

PRODUCT_DESC

Attribute	Description
Name	PRODUCT_DESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	50

Intms-Inter-Prd-Rule

Attribute	Description
Name	Intms-Inter-Prd-Rule
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

RULEID

Attribute	Description
Name	RULEID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	10

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

EVNTCD

Attribute	Description

Name	EVNTCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 6

EVENTDESC

Attribute	**Description**
Name	EVENTDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

Accounting-Entries

Attribute	**Description**
Name	Accounting-Entries
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ACCRLCD

Attribute	**Description**
Name	ACCRLCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 20

AMTTAG

Attribute	**Description**
Name	AMTTAG
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 35

DRCRINDICTR

Attribute	**Description**

Name	DRCRINDICTR
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / D,C

TRNCD

Attribute	**Description**
Name	TRNCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

NETINDICTR

Attribute	**Description**
Name	NETINDICTR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

MISHD

Attribute	**Description**
Name	MISHD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

REVALPRGL

Attribute	**Description**
Name	REVALPRGL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	9

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

REVALRTCD

Attribute	Description
Name	REVALRTCD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	M,B,S,

Advices

Attribute	Description
Name	Advices
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	15

DESC

Attribute	Description

Name	DESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

GENTIME

Attribute	**Description**
Name	GENTIME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

SUPRS

Attribute	**Description**
Name	SUPRS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

PRIOR

Attribute	**Description**
Name	PRIOR
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CHGREQD

Attribute	**Description**
Name	CHGREQD
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

MISCD

Attribute	**Description**
Name	MISCD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

Dummy-Prd

Attribute	**Description**
Name	Dummy-Prd
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attribute	**Attribute** / **Description** maxOccurs / unbounded

ECODE

Attribute	**Description**

Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.18.QueryInRuleMaint

2.18.1.IN-QueryInRuleMaint-Req-IO-MSG.xsd

QUERYINRULEMAINT_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Rule-IO

RULEID

QUERYINRULEMAINT_IOFS_REQ

Attribute	Description
Name	QUERYINRULEMAINT_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Rule-IO

Attribute	Description
Name	Intms-Rule-IO
Datatype	
Description	

RULEID

Attribute	Description
Name	RULEID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

2.18.2.IN-QueryInRuleMaint-Res-Full-MSG.xsd

QUERYINRULEMAINT_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Rule-IO

RULEID

Intms-Rule-Full

RULEID

RULEDESC

CCY

RATECODETYPE

RULETYPE

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Intms-Rule-Sde

SDEID

Intms-Rule-Ude

UDEID

UDETYPE

UDEBASIS

UDECCY

Intms-Rule-Frm

Intms-Expr

EXPRLINE

COND

RESULT

Condition

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYINRULEMAINT_IOFS_RES

Attribute	Description
Name	QUERYINRULEMAINT_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description

Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID

Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String

Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Rule-IO

Attribute	Description
Name	Intms-Rule-IO
Datatype	
Description	

RULEID

Attribute	Description
Name	RULEID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	4

Intms-Rule-Full

Attribute	Description
Name	Intms-Rule-Full
Datatype	
Description	

RULEID

Attribute	Description
Name	RULEID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	4

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

RATECODETYPE

Attribute	Description
Name	RATECODETYPE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

RULETYPE

Attribute	Description
Name	RULETYPE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,C</td></tr></table>

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Intms-Rule-Sde

Attribute	Description
Name	Intms-Rule-Sde
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

SDEID

Attribute	Description
Name	SDEID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

Intms-Rule-Ude

Attribute	Description
Name	Intms-Rule-Ude
Datatype	

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

UDETYPE

Attribute	Description
Name	UDETYPE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,R,N</td></tr></table>

UDEBASIS

Attribute	Description
Name	UDEBASIS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>I,E</td></tr></table>

UDECCY

Attribute	Description
Name	UDECCY
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

Intms-Rule-Frm

Attribute	**Description**
Name	Intms-Rule-Frm
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Intms-Expr

Attribute	**Description**
Name	Intms-Expr
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

EXPRLINE

Attribute	**Description**
Name	EXPRLINE
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description** totalDigits / 22

COND

Attribute	**Description**
Name	COND
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

RESULT

Attribute	**Description**

Name	RESULT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

Condition

Attribute	Description
Name	Condition
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.19.QueryInSdeMaint

2.19.1.IN-QueryInSdeMaint-Req-IO-MSG.xsd

QUERYINSDEMAINT_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Sde-IO

ELEMENT

QUERYINSDEMAINT_IOFS_REQ

Attribute	Description
Name	QUERYINSDEMAINT_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.

Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	
	Restrictions / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description**: minOccurs / 0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Sde-IO

Attribute	Description
Name	Intms-Sde-IO
Datatype	
Description	

ELEMENT

Attribute	Description
Name	ELEMENT
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

2.19.2.IN-QueryInSdeMaint-Res-Full-MSG.xsd

QUERYINSDEMAINT_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Sde-IO

ELEMENT

Intms-Sde-Full

ELEMENT

SDEDESC

CALCMETHOD

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYINSDEMAINT_IOFS_RES

Attribute	Description
Name	QUERYINSDEMAINT_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description

Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.

Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Sde-IO

Attribute	Description
Name	Intms-Sde-IO
Datatype	
Description	

ELEMENT

Attribute	Description
Name	ELEMENT
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

Intms-Sde-Full

Attribute	Description
Name	Intms-Sde-Full
Datatype	
Description	

ELEMENT

Attribute	Description
Name	ELEMENT
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

SDEDESC

Attribute	Description
Name	SDEDESC
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

CALCMETHOD

Attribute	Description
Name	CALCMETHOD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>P,A</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.20.QueryInSdeView

2.20.1.IN-QueryInSdeView-Req-IO-MSG.xsd

QUERYINSDEVIEW_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Invws-Inter-Product-IO

PRODUCTCODE

INTERMEDIARYCODE

RULEID

QUERYINSDEVIEW_IOFS_REQ

Attribute	Description
Name	QUERYINSDEVIEW_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Invws-Inter-Product-IO

Attribute	Description
Name	Invws-Inter-Product-IO
Datatype	
Description	

PRODUCTCODE

Attribute	Description
Name	PRODUCTCODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

RULEID

Attribute	Description
Name	RULEID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

2.20.2.IN-QueryInSdeView-Res-Full-MSG.xsd

QUERYINSDEVIEW_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Invws-Inter-Product-IO

PRODUCTCODE

INTERMEDIARYCODE

RULEID

Invws-Inter-Product-Full

PRODUCTCODE

INTERMEDIARYCODE

RULEID

Invws-Sde-Details

SDEID

SDEVALUES

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYINSDEVIEW_IOFS_RES

Attribute	Description
Name	QUERYINSDEVIEW_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Invws-Inter-Product-IO

Attribute	Description
Name	Invws-Inter-Product-IO
Datatype	
Description	

PRODUCTCODE

Attribute	Description
Name	PRODUCTCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

RULEID

Attribute	Description
Name	RULEID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

Invws-Inter-Product-Full

Attribute	Description
Name	Invws-Inter-Product-Full
Datatype	
Description	

PRODUCTCODE

Attribute	Description
Name	PRODUCTCODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

RULEID

Attribute	Description
Name	RULEID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

Invws-Sde-Details

Attribute	Description
Name	Invws-Sde-Details
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

SDEID

Attribute	Description
Name	SDEID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength / 16

SDEVALUES

Attribute	**Description**
Name	SDEVALUES
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attribute	**Attribute** / **Description** maxOccurs / unbounded

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	**Description**

Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.21.QueryInUdeMaint

2.21.1.IN-QueryInUdeMaint-Req-IO-MSG.xsd

QUERYINUDEMAINT_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Inter-Prd-Ude-IO

PRODUCTCODE

QUERYINUDEMAINT_IOFS_REQ

Attribute	Description
Name	QUERYINUDEMAINT_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE

Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	

Intms-Inter-Prd-Ude-IO

Attribute	**Description**

Name	Intms-Inter-Prd-Ude-IO
Datatype	
Description	

PRODUCTCODE

Attribute	Description
Name	PRODUCTCODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

2.21.2.IN-QueryInUdeMaint-Res-Full-MSG.xsd

QUERYINUDEMAINT_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Inter-Prd-Ude-IO

PRODUCTCODE

Intms-Inter-Prd-Ude-Full

PRODUCTCODE

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Intms-Inter-Prd-Ude-Values

RULEID

UDEID

UDEVALUE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYINUDEMAINT_IOFS_RES

Attribute	Description
Name	QUERYINUDEMAINT_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Inter-Prd-Ude-IO

Attribute	Description
Name	Intms-Inter-Prd-Ude-IO
Datatype	
Description	

PRODUCTCODE

Attribute	Description
Name	PRODUCTCODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

Intms-Inter-Prd-Ude-Full

Attribute	Description
Name	Intms-Inter-Prd-Ude-Full
Datatype	
Description	

PRODUCTCODE

Attribute	Description
Name	PRODUCTCODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

MAKER

Attribute	Description

Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	**Description**

Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

Intms-Inter-Prd-Ude-Values

Attribute	**Description**
Name	Intms-Inter-Prd-Ude-Values
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

RULEID

Attribute	**Description**
Name	RULEID
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	4

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	16

UDEVALUE

Attribute	Description
Name	UDEVALUE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.22.QueryInViewMaint

2.22.1.IN-QueryInViewMaint-Req-IO-MSG.xsd

QUERYINVIEWMAINT_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Inter-Processed-IO

PRODUCTCODE

INTERMEDIARYCODE

BRANCHCODE

REFERENCENO

EVENTCODE

EXECUTIONDATE

RULEID

QUERYINVIEWMAINT_IOFS_REQ

Attribute	Description
Name	QUERYINVIEWMAINT_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Inter-Processed-IO

Attribute	Description
Name	Intms-Inter-Processed-IO
Datatype	
Description	

PRODUCTCODE

Attribute	Description
Name	PRODUCTCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

EXECUTIONDATE

Attribute	Description
Name	EXECUTIONDATE
Datatype	String
Description	

RULEID

Attribute	Description
Name	RULEID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

2.22.2.IN-QueryInViewMaint-Res-Full-MSG.xsd

QUERYINVIEWMAINT_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Intms-Inter-Processed-IO

PRODUCTCODE

INTERMEDIARYCODE

BRANCHCODE

REFERENCENO

EVENTCODE

EXECUTIONDATE

RULEID

Intms-Inter-Processed-Full

PRODUCTCODE

INTERMEDIARYCODE

BRANCHCODE

REFERENCENO

EVENTCODE

EXECUTIONDATE

AMOUNT

CURRENCY

SDEID

SDEVALUE

SETTLEBRANCH

SETTLEACCOUNT

MANUALEXECUTIONDT

HIERARCHYCOMMPROCESSED

RULEID

Intms-Inter-Processed-Det

ACCOUNTNO

BRANCHCODE

CUSTOMERID

BOOKDATE

MODULECODE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYINVIEWMAINT_IOFS_RES

Attribute	Description
Name	QUERYINVIEWMAINT_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Intms-Inter-Processed-IO

Attribute	Description
Name	Intms-Inter-Processed-IO
Datatype	
Description	

PRODUCTCODE

Attribute	Description
Name	PRODUCTCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

INTERMEDIARYCODE

Attribute	Description
Name	INTERMEDIARYCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

EVENTCODE

Attribute	Description
Name	EVENTCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

EXECUTIONDATE

Attribute	Description
Name	EXECUTIONDATE
Datatype	String
Description	

RULEID

Attribute	Description
Name	RULEID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 10

Intms-Inter-Processed-Full

Attribute	Description
Name	Intms-Inter-Processed-Full
Datatype	
Description	

PRODUCTCODE

Attribute	Description
Name	PRODUCTCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

INTERMEDIARYCODE

Attribute	Description

Name	INTERMEDIARYCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

BRANCHCODE

Attribute	**Description**
Name	BRANCHCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

REFERENCENO

Attribute	**Description**
Name	REFERENCENO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

EVENTCODE

Attribute	**Description**
Name	EVENTCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

EXECUTIONDATE

Attribute	**Description**
Name	EXECUTIONDATE
Datatype	String
Description	

AMOUNT

Attribute	**Description**
Name	AMOUNT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: totalDigits / 22

CURRENCY

Attribute	Description
Name	CURRENCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

SDEID

Attribute	Description
Name	SDEID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 200

SDEVALUE

Attribute	Description
Name	SDEVALUE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 200

SETTLEBRANCH

Attribute	Description
Name	SETTLEBRANCH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	3

SETTLEACCOUNT

Attribute	Description
Name	SETTLEACCOUNT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

MANUALEXECUTIONDT

Attribute	Description
Name	MANUALEXECUTIONDT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

HIERARCHYCOMMPROCESSED

Attribute	Description
Name	HIERARCHYCOMMPROCESSED
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

RULEID

Attribute	Description
Name	RULEID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	10

Intms-Inter-Processed-Det

Attribute	Description

Name	Intms-Inter-Processed-Det
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ACCOUNTNO

Attribute	Description
Name	ACCOUNTNO
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

CUSTOMERID

Attribute	Description
Name	CUSTOMERID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

BOOKDATE

Attribute	Description
Name	BOOKDATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

MODULECODE

Attribute	Description

Name	MODULECODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

Gateway Documentation - FCUBSINService
[Febraury] [2016]

Oracle Financial services Software Limited
Oracle Park
Off western Express Highway
Goregaon(East)
Mumbai,Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax:+91 22 6718 3001
www.oracle.com/financialservices/

Copyright © [2013], [2016], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.