Gateway Documentation - FCUBSSMService
Oracle FLEXCUBE Universal Banking
Release 12.87.02.0.0
[Febraury][2016]

Table Of Contents

1. Background **1**

2. FCUBSSMService **2**

2.1.AuthorizeSMDBANKP **2**

2.1.1.SM-AuthorizeSMDBANKP-Req-Full-MSG.xsd 2

2.1.2.SM-AuthorizeSMDBANKP-Req-IO-MSG.xsd 19

2.1.3.SM-AuthorizeSMDBANKP-Res-Full-MSG.xsd 27

2.1.4.SM-AuthorizeSMDBANKP-Res-PK-MSG.xsd 46

2.2.AuthorizeSMDRLMNE **55**

2.2.1.SM-AuthorizeSMDRLMNE-Req-Full-MSG.xsd 55

2.2.2.SM-AuthorizeSMDRLMNE-Req-IO-MSG.xsd 66

2.2.3.SM-AuthorizeSMDRLMNE-Res-Full-MSG.xsd 73

2.2.4.SM-AuthorizeSMDRLMNE-Res-PK-MSG.xsd 85

2.3.AuthorizeUserMaint **95**

2.3.1.SM-AuthorizeUserMaint-Req-Full-MSG.xsd 95

2.3.2.SM-AuthorizeUserMaint-Req-IO-MSG.xsd 145

2.3.3.SM-AuthorizeUserMaint-Res-Full-MSG.xsd 153

2.3.4.SM-AuthorizeUserMaint-Res-PK-MSG.xsd 205

2.4.CloseSMDBANKP **214**

2.4.1.SM-CloseSMDBANKP-Req-Full-MSG.xsd 214

2.4.2.SM-CloseSMDBANKP-Req-IO-MSG.xsd 232

2.4.3.SM-CloseSMDBANKP-Res-Full-MSG.xsd 240

2.4.4.SM-CloseSMDBANKP-Res-PK-MSG.xsd 258

2.5.CloseSMDRLMNE **268**

2.5.1.SM-CloseSMDRLMNE-Req-Full-MSG.xsd 268

2.5.2.SM-CloseSMDRLMNE-Req-IO-MSG.xsd 278

2.5.3.SM-CloseSMDRLMNE-Res-Full-MSG.xsd 286

2.5.4.SM-CloseSMDRLMNE-Res-PK-MSG.xsd 298

2.6.CloseUserMaint **307**

2.6.1.SM-CloseUserMaint-Req-Full-MSG.xsd 307

2.6.2.SM-CloseUserMaint-Req-IO-MSG.xsd 358

2.6.3.SM-CloseUserMaint-Res-Full-MSG.xsd 365

2.6.4.SM-CloseUserMaint-Res-PK-MSG.xsd 417

2.7.CreateSMDBANKP **426**

2.7.1.SM-CreateSMDBANKP-Req-Full-MSG.xsd 426

2.7.2.SM-CreateSMDBANKP-Req-IO-MSG.xsd 444

2.7.3.SM-CreateSMDBANKP-Res-Full-MSG.xsd 459

2.7.4.SM-CreateSMDBANKP-Res-PK-MSG.xsd 478

2.8.CreateSMDRLMNE **495**

2.8.1.SM-CreateSMDRLMNE-Req-Full-MSG.xsd 496

2.8.2.SM-CreateSMDRLMNE-Req-IO-MSG.xsd 506

2.8.3.SM-CreateSMDRLMNE-Res-Full-MSG.xsd 514

2.8.4.SM-CreateSMDRLMNE-Res-PK-MSG.xsd 526

2.9.CreateSMRole **536**

2.9.1.SM-CreateSMRole-Req-Full-MSG.xsd 536

2.9.2.SM-CreateSMRole-Req-IO-MSG.xsd 591

2.9.3.SM-CreateSMRole-Res-Full-MSG.xsd 642

2.9.4.SM-CreateSMRole-Res-PK-MSG.xsd 698

2.10.CreateUserMaint **752**

ORACLE

2.10.1.SM-CreateUserMaint-Req-Full-MSG.xsd 752
2.10.2.SM-CreateUserMaint-Req-IO-MSG.xsd 802
2.10.3.SM-CreateUserMaint-Res-Full-MSG.xsd 846
2.10.4.SM-CreateUserMaint-Res-PK-MSG.xsd 898
2.11.DeleteSMDBANKP 944
2.11.1.SM-DeleteSMDBANKP-Req-Full-MSG.xsd 944
2.11.2.SM-DeleteSMDBANKP-Req-IO-MSG.xsd 961
2.11.3.SM-DeleteSMDBANKP-Res-Full-MSG.xsd 968
2.11.4.SM-DeleteSMDBANKP-Res-PK-MSG.xsd 987
2.12.DeleteSMDRLMNE 996
2.12.1.SM-DeleteSMDRLMNE-Req-Full-MSG.xsd 996
2.12.2.SM-DeleteSMDRLMNE-Req-IO-MSG.xsd 1006
2.12.3.SM-DeleteSMDRLMNE-Res-Full-MSG.xsd 1013
2.12.4.SM-DeleteSMDRLMNE-Res-PK-MSG.xsd 1025
2.13.DeleteSMRole 1033
2.13.1.SM-DeleteSMRole-Req-Full-MSG.xsd 1033
2.13.2.SM-DeleteSMRole-Req-IO-MSG.xsd 1088
2.13.3.SM-DeleteSMRole-Res-Full-MSG.xsd 1095
2.13.4.SM-DeleteSMRole-Res-PK-MSG.xsd 1151
2.14.DeleteUserMaint 1159
2.14.1.SM-DeleteUserMaint-Req-Full-MSG.xsd 1159
2.14.2.SM-DeleteUserMaint-Req-IO-MSG.xsd 1210
2.14.3.SM-DeleteUserMaint-Res-Full-MSG.xsd 1217
2.14.4.SM-DeleteUserMaint-Res-PK-MSG.xsd 1269
2.15.ModifySMDBANKP 1277
2.15.1.SM-ModifySMDBANKP-Req-Full-MSG.xsd 1277
2.15.2.SM-ModifySMDBANKP-Req-IO-MSG.xsd 1295
2.15.3.SM-ModifySMDBANKP-Res-Full-MSG.xsd 1310
2.15.4.SM-ModifySMDBANKP-Res-PK-MSG.xsd 1329
2.16.ModifySMDRLMNE 1347
2.16.1.SM-ModifySMDRLMNE-Req-Full-MSG.xsd 1347
2.16.2.SM-ModifySMDRLMNE-Req-IO-MSG.xsd 1357
2.16.3.SM-ModifySMDRLMNE-Res-Full-MSG.xsd 1367
2.16.4.SM-ModifySMDRLMNE-Res-PK-MSG.xsd 1379
2.17.ModifySMRole 1390
2.17.1.SM-ModifySMRole-Req-Full-MSG.xsd 1390
2.17.2.SM-ModifySMRole-Req-IO-MSG.xsd 1444
2.17.3.SM-ModifySMRole-Res-Full-MSG.xsd 1504
2.17.4.SM-ModifySMRole-Res-PK-MSG.xsd 1560
2.18.ModifyUserMaint 1621
2.18.1.SM-ModifyUserMaint-Req-Full-MSG.xsd 1621
2.18.2.SM-ModifyUserMaint-Req-IO-MSG.xsd 1672
2.18.3.SM-ModifyUserMaint-Res-Full-MSG.xsd 1714
2.18.4.SM-ModifyUserMaint-Res-PK-MSG.xsd 1766
2.19.QuerySMDBANKP 1809
2.19.1.SM-QuerySMDBANKP-Req-IO-MSG.xsd 1809
2.19.2.SM-QuerySMDBANKP-Res-Full-MSG.xsd 1816
2.20.QuerySMDRLMNE 1835
2.20.1.SM-QuerySMDRLMNE-Req-IO-MSG.xsd 1835
2.20.2.SM-QuerySMDRLMNE-Res-Full-MSG.xsd 1842
2.21.QuerySMRole 1854
2.21.1.SM-QuerySMRole-Req-IO-MSG.xsd 1854

2.21.2.SM-QuerySMRole-Res-Full-MSG.xsd 1861
2.22.QueryUserMaint 1918
2.22.1.SM-QueryUserMaint-Req-IO-MSG.xsd 1918
2.22.2.SM-QueryUserMaint-Res-Full-MSG.xsd 1925
2.23.ReopenSMDBANKP 1978
2.23.1.SM-ReopenSMDBANKP-Req-Full-MSG.xsd 1978
2.23.2.SM-ReopenSMDBANKP-Req-IO-MSG.xsd 1996
2.23.3.SM-ReopenSMDBANKP-Res-Full-MSG.xsd 2003
2.23.4.SM-ReopenSMDBANKP-Res-PK-MSG.xsd 2022
2.24.ReopenSMDRLMNE 2032
2.24.1.SM-ReopenSMDRLMNE-Req-Full-MSG.xsd 2032
2.24.2.SM-ReopenSMDRLMNE-Req-IO-MSG.xsd 2042
2.24.3.SM-ReopenSMDRLMNE-Res-Full-MSG.xsd 2050
2.24.4.SM-ReopenSMDRLMNE-Res-PK-MSG.xsd 2062
2.25.ReopenUserMaint 2071
2.25.1.SM-ReopenUserMaint-Req-Full-MSG.xsd 2071
2.25.2.SM-ReopenUserMaint-Req-IO-MSG.xsd 2122
2.25.3.SM-ReopenUserMaint-Res-Full-MSG.xsd 2129
2.25.4.SM-ReopenUserMaint-Res-PK-MSG.xsd 2181

1. Background

Integration of different applications and solutions is a key area in today's systems.A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data.The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs.The integration needs supported by the Gateway can be broadly categorized from the perspective of Gateway as follows

1. Inbound application integration :

This is used when any external system needs to add, modify or query information within FLEXCUBE UBS

2. Outbound application integration :

This is used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS

The following sections provide detailed XSD documentation of all operations available in FCUBSSMService of SMS Module

2. FCUBSSMService

2.1.AuthorizeSMDBANKP

2.1.1.SM-AuthorizeSMDBANKP-Req-Full-MSG.xsd

- *AUTHORIZESMDBANKP_FSFS_REQ*
  - *FCUBS_HEADER*
    - *SOURCE*
    - *UBSCOMP*
    - *MSGID*
    - *CORRELID*
    - *USERID*
    - *BRANCH*
    - *MODULEID*
    - *SERVICE*
    - *OPERATION*
    - *SOURCE_OPERATION*
    - *SOURCE_USERID*
    - *DESTINATION*
    - *MULTITRIPID*
    - *FUNCTIONID*
    - *ACTION*
    - *MSGSTAT*
    - *PASSWORD*
    - *ADDL*
      - *PARAM*
        - *NAME*
        - *VALUE*
  - *FCUBS_BODY*
    - *Smtbs-Parameters-Full*
      - *HEAD_OFFICE*
      - *SITE_CODE*
      - *ACTIVATION_KEY*
      - *INVALID_LOGINS_CUM*

INVALID_LOGINS_SUC

PWD_PREVENT_REUSE

PWD_CHANGE_AFTER

MAXIMUM

MINIMUM

PWD_EXPIRY_MSG_DAYS

ARCHIVAL_PERIOD

CONCHAR_PWD_NUM

FREQ_PWD_CHG

MIN_PWD_NUMERIC_LENGTH

LEGAL_NOTICE

DORMANCY_DAYS

DISPLAY_LEGAL_NOTICE

MIN_SPECIALCHAR_LENGTH

MIN_LOWERCASE_CHAR

MIN_UPPERCASE_CHAR

SCREENSAVERREQUIRED

SCREENSAVERTIMEOUTINSECONDS

SCREENSAVERMODIFIABLEBYUSER

PASSWORDEXTERNAL

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Smtbs-Branch-Restr

- *RESTR_TYPE*
- *DESCRIPTION*

Smtbs-Restrictive-Passwd

- *PASSWORD*

UDFDETAILS

FLDNAM

FLDVAL

AUTHORIZESMDBANKP_FSFS_REQ

Attribute	Description
Name	AUTHORIZESMDBANKP_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Parameters-Full

Attribute	Description
Name	Smtbs-Parameters-Full
Datatype	
Description	

HEAD_OFFICE

Attribute	Description
Name	HEAD_OFFICE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	3

SITE_CODE

Attribute	Description
Name	SITE_CODE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	4

ACTIVATION_KEY

Attribute	Description
Name	ACTIVATION_KEY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	24

INVALID_LOGINS_CUM

Attribute	Description
Name	INVALID_LOGINS_CUM
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	6
maxInclusive	99

INVALID_LOGINS_SUC

Attribute	Description
Name	INVALID_LOGINS_SUC
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	1
minInclusive	3
maxInclusive	5

PWD_PREVENT_REUSE

Attribute	Description
Name	PWD_PREVENT_REUSE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1

PWD_CHANGE_AFTER

Attribute	Description
Name	PWD_CHANGE_AFTER
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	3
minInclusive	15
maxInclusive	180

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	12
maxInclusive	30

MINIMUM

Attribute	Description

Name	MINIMUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 6; maxInclusive / 11

PWD_EXPIRY_MSG_DAYS

Attribute	**Description**
Name	PWD_EXPIRY_MSG_DAYS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1; maxInclusive / 5

ARCHIVAL_PERIOD

Attribute	**Description**
Name	ARCHIVAL_PERIOD
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

CONCHAR_PWD_NUM

Attribute	**Description**
Name	CONCHAR_PWD_NUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2

FREQ_PWD_CHG

Attribute	Description
Name	FREQ_PWD_CHG
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 0

MIN_PWD_NUMERIC_LENGTH

Attribute	Description
Name	MIN_PWD_NUMERIC_LENGTH
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

LEGAL_NOTICE

Attribute	Description
Name	LEGAL_NOTICE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

DORMANCY_DAYS

Attribute	Description
Name	DORMANCY_DAYS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1

DISPLAY_LEGAL_NOTICE

Attribute	Description
Name	DISPLAY_LEGAL_NOTICE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

MIN_SPECIALCHAR_LENGTH

Attribute	Description
Name	MIN_SPECIALCHAR_LENGTH
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1

MIN_LOWERCASE_CHAR

Attribute	Description
Name	MIN_LOWERCASE_CHAR
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1

MIN_UPPERCASE_CHAR

Attribute	Description
Name	MIN_UPPERCASE_CHAR
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

SCREENSAVERREQUIRED

Attribute	**Description**
Name	SCREENSAVERREQUIRED
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

SCREENSAVERTIMEOUTINSECONDS

Attribute	**Description**
Name	SCREENSAVERTIMEOUTINSECONDS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

SCREENSAVERMODIFIABLEBYUSER

Attribute	**Description**
Name	SCREENSAVERMODIFIABLEBYUSER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

PASSWORDEXTERNAL

Attribute	**Description**
Name	PASSWORDEXTERNAL
Datatype	String

Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Smtbs-Branch-Restr

Attribute	Description
Name	Smtbs-Branch-Restr
Datatype	

Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

RESTR_TYPE

Attribute	Description
Name	RESTR_TYPE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255

Smtbs-Restrictive-Passwd

Attribute	Description
Name	Smtbs-Restrictive-Passwd
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.1.2.SM-AuthorizeSMDBANKP-Req-IO-MSG.xsd

AUTHORIZESMDBANKP_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Parameters-IO

SITE_CODE

CHECKER

CHECKERSTAMP

MODNO

AUTHORIZESMDBANKP_IOPK_REQ

Attribute	Description
Name	AUTHORIZESMDBANKP_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Parameters-IO

Attribute	Description
Name	Smtbs-Parameters-IO
Datatype	
Description	

SITE_CODE

Attribute	Description
Name	SITE_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

2.1.3.SM-AuthorizeSMDBANKP-Res-Full-MSG.xsd

AUTHORIZESMDBANKP_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Parameters-Full

HEAD_OFFICE

SITE_CODE

ACTIVATION_KEY

INVALID_LOGINS_CUM

INVALID_LOGINS_SUC

PWD_PREVENT_REUSE

PWD_CHANGE_AFTER

MAXIMUM

MINIMUM

PWD_EXPIRY_MSG_DAYS

ARCHIVAL_PERIOD

CONCHAR_PWD_NUM

FREQ_PWD_CHG

MIN_PWD_NUMERIC_LENGTH

LEGAL_NOTICE

DORMANCY_DAYS

DISPLAY_LEGAL_NOTICE

MIN_SPECIALCHAR_LENGTH

MIN_LOWERCASE_CHAR

MIN_UPPERCASE_CHAR

SCREENSAVERREQUIRED

SCREENSAVERTIMEOUTINSECONDS

SCREENSAVERMODIFIABLEBYUSER

PASSWORDEXTERNAL

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Smtbs-Branch-Restr

RESTR_TYPE

DESCRIPTION

Smtbs-Restrictive-Passwd

PASSWORD

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZESMDBANKP_FSFS_RES

Attribute	Description
Name	AUTHORIZESMDBANKP_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Parameters-Full

Attribute	Description
Name	Smtbs-Parameters-Full
Datatype	
Description	

HEAD_OFFICE

Attribute	Description
Name	HEAD_OFFICE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

SITE_CODE

Attribute	Description
Name	SITE_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

ACTIVATION_KEY

Attribute	Description
Name	ACTIVATION_KEY
Datatype	String
Description	

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	24

INVALID_LOGINS_CUM

Attribute	Description
Name	INVALID_LOGINS_CUM
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	6
maxInclusive	99

INVALID_LOGINS_SUC

Attribute	Description
Name	INVALID_LOGINS_SUC
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	1
minInclusive	3
maxInclusive	5

PWD_PREVENT_REUSE

Attribute	Description
Name	PWD_PREVENT_REUSE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1

PWD_CHANGE_AFTER

Attribute	Description
Name	PWD_CHANGE_AFTER
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: totalDigits = 3; minInclusive = 15; maxInclusive = 180

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: totalDigits = 2; minInclusive = 12; maxInclusive = 30

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: totalDigits = 2; minInclusive = 6; maxInclusive = 11

PWD_EXPIRY_MSG_DAYS

Attribute	Description
Name	PWD_EXPIRY_MSG_DAYS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs = 0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1
maxInclusive	5

ARCHIVAL_PERIOD

Attribute	Description
Name	ARCHIVAL_PERIOD
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	3

CONCHAR_PWD_NUM

Attribute	Description
Name	CONCHAR_PWD_NUM
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2

FREQ_PWD_CHG

Attribute	Description
Name	FREQ_PWD_CHG
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	0

MIN_PWD_NUMERIC_LENGTH

Attribute	Description
Name	MIN_PWD_NUMERIC_LENGTH
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2 minInclusive / 1

LEGAL_NOTICE

Attribute	**Description**
Name	LEGAL_NOTICE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

DORMANCY_DAYS

Attribute	**Description**
Name	DORMANCY_DAYS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2 minInclusive / 1

DISPLAY_LEGAL_NOTICE

Attribute	**Description**
Name	DISPLAY_LEGAL_NOTICE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

MIN_SPECIALCHAR_LENGTH

Attribute	**Description**
Name	MIN_SPECIALCHAR_LENGTH

Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

MIN_LOWERCASE_CHAR

Attribute	**Description**
Name	MIN_LOWERCASE_CHAR
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

MIN_UPPERCASE_CHAR

Attribute	**Description**
Name	MIN_UPPERCASE_CHAR
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

SCREENSAVERREQUIRED

Attribute	**Description**
Name	SCREENSAVERREQUIRED
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

SCREENSAVERTIMEOUTINSECONDS

Attribute	Description
Name	SCREENSAVERTIMEOUTINSECONDS
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

SCREENSAVERMODIFIABLEBYUSER

Attribute	Description
Name	SCREENSAVERMODIFIABLEBYUSER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

PASSWORDEXTERNAL

Attribute	Description
Name	PASSWORDEXTERNAL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Smtbs-Branch-Restr

Attribute	Description
Name	Smtbs-Branch-Restr
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

RESTR_TYPE

Attribute	Description
Name	RESTR_TYPE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

Smtbs-Restrictive-Passwd

Attribute	Description
Name	Smtbs-Restrictive-Passwd
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description

Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150; minLength / 0

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attribute	**Attribute** / **Description**: maxOccurs / unbounded

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	**Description**
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.1.4.SM-AuthorizeSMDBANKP-Res-PK-MSG.xsd

AUTHORIZESMDBANKP_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Parameters-PK

SITE_CODE

Smtbs-Parameters-IO

SITE_CODE

CHECKER

CHECKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZESMDBANKP_IOPK_RES

Attribute	Description
Name	AUTHORIZESMDBANKP_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Parameters-PK

Attribute	Description
Name	Smtbs-Parameters-PK
Datatype	
Description	

SITE_CODE

Attribute	Description
Name	SITE_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

Smtbs-Parameters-IO

Attribute	Description
Name	Smtbs-Parameters-IO
Datatype	
Description	

SITE_CODE

Attribute	Description
Name	SITE_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

CHECKER

Attribute	Description

Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.2.AuthorizeSMDRLMNE

2.2.1.SM-AuthorizeSMDRLMNE-Req-Full-MSG.xsd

AUTHORIZESMDRLMNE_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Role-Limit-Full

ROLEID2

DESCRIPTION

LIMIT_CCY

INPUT_LIMIT

AUTHORIZATION_LIMIT

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

AUTHORIZESMDRLMNE_FSFS_REQ

Attribute	Description
Name	AUTHORIZESMDRLMNE_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.

Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Role-Limit-Full

Attribute	Description
Name	Smtbs-Role-Limit-Full
Datatype	
Description	

ROLEID2

Attribute	Description

Name	ROLEID2
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

DESCRIPTION

Attribute	**Description**
Name	DESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

LIMIT_CCY

Attribute	**Description**
Name	LIMIT_CCY
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

INPUT_LIMIT

Attribute	**Description**
Name	INPUT_LIMIT
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0

AUTHORIZATION_LIMIT

Attribute	**Description**
Name	AUTHORIZATION_LIMIT
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0

MAKER

Attribute	**Description**

Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	**Description**

Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	Indicates Field Name

Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

2.2.2.SM-AuthorizeSMDRLMNE-Req-IO-MSG.xsd

AUTHORIZESMDRLMNE_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Role-Limit-IO

ROLEID2

CHECKER

CHECKERSTAMP

MODNO

AUTHORIZESMDRLMNE_IOPK_REQ

Attribute	Description
Name	AUTHORIZESMDRLMNE_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH

Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String

Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Role-Limit-IO

Attribute	Description
Name	Smtbs-Role-Limit-IO
Datatype	
Description	

ROLEID2

Attribute	Description
Name	ROLEID2
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

2.2.3.SM-AuthorizeSMDRLMNE-Res-Full-MSG.xsd

AUTHORIZESMDRLMNE_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Role-Limit-Full

ROLEID2

DESCRIPTION

LIMIT_CCY

INPUT_LIMIT

AUTHORIZATION_LIMIT

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZESMDRLMNE_FSFS_RES

Attribute	Description
Name	AUTHORIZESMDRLMNE_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.

Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Role-Limit-Full

Attribute	Description
Name	Smtbs-Role-Limit-Full
Datatype	
Description	

ROLEID2

Attribute	Description
Name	ROLEID2
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

LIMIT_CCY

Attribute	Description
Name	LIMIT_CCY
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

INPUT_LIMIT

Attribute	Description
Name	INPUT_LIMIT
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0

AUTHORIZATION_LIMIT

Attribute	Description
Name	AUTHORIZATION_LIMIT
Datatype	Decimal

Description	
Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	150
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description

Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.2.4.SM-AuthorizeSMDRLMNE-Res-PK-MSG.xsd

AUTHORIZESMDRLMNE_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Role-Limit-PK

ROLEID2

Smtbs-Role-Limit-IO

ROLEID2

CHECKER

CHECKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZESMDRLMNE_IOPK_RES

Attribute	Description
Name	AUTHORIZESMDRLMNE_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description**: minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL

Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Role-Limit-PK

Attribute	Description
Name	Smtbs-Role-Limit-PK
Datatype	
Description	

ROLEID2

Attribute	Description
Name	ROLEID2
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

Smtbs-Role-Limit-IO

Attribute	Description

Name	Smtbs-Role-Limit-IO
Datatype	
Description	

ROLEID2

Attribute	Description
Name	ROLEID2
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.3.AuthorizeUserMaint

2.3.1.SM-AuthorizeUserMaint-Req-Full-MSG.xsd

AUTHORIZEUSERMAINT_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

USR-Full

- *STRTDATE*
- *USRNAME*
- *USRPWD*
- *ENDDT*
- *USRLANG*
- *HOMEBRN*
- *CUSTNO*
- *LDAPUSR*
- *TIMELEVEL*
- *AUTOAUTH*
- *USRSTAT*
- *USRID*
- *EXTUSRREF*
- *USRCATEG*
- *TILLALLOW*
- *ACCCLSALLOW*
- *GLALLOW*
- *USRTXNLMT*
- *LMTSCCY*
- *MAXTXNAMT*
- *MAXAUTHAMT*
- *BRNSALLOW*
- *PRDSALLOW*
- *PRDSACCESALLOW*
- *TAX_IDENTIFIER*
- *AMOUNT_FORMAT*
- *DATE_FORMAT*
- *STAFFACCRESTR*
- *DEPT_CODE*
- *DEPT_DESC*
- *USRML*

ELCMUSER

GROUP_CODE

MULTIBRN_ACCESS

OTH_RM_CUST_ACC_ALLOW

SUPERVISOR_ID

SUPERVISOR_NAME

DASHBOARD_REQD

ALERTS_ON_HOME

REFERENCE_NO

NO_CUMULATIVE_LOGINS

NO_SUCCESSIVE_LOGINS

SCREENSAVERTIMEOUTINSECONDS

MFI_USER

F10_REQD

F11_REQD

F12_REQD

ACCESS_CONTROL

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

RESTR_PWD

- *PWD*

MSGSRIGHTS

- *GEN*
- *HLD*
- *CNL*
- *TSTINP*
- *CHGNODE*

CHGADDR

REL

REINS

CHGMEDIA

CHGPRIOR

BRNMOV

PRNT

TSTCHK

HLDAUTH

CNLAUTH

TSTINPAUTH

CHGNODEAUTH

CHGADDRAUTH

RELAUTH

REINSAUTH

CHGMEDIAAUTH

BRNMOVAUTH

CHGPRIORAUTH

FTUPL

LNKCONT

MOVQ

CHGBRNIN

CHGADDRIN

AUTHRGHTS

CHGMSG

CHGMSGAUTH

CHGFORCCOVMATCH

CHANGE_FORCE_RELEASE_FUND

SUPPRESS

DELMSG

QUEUERIGHTS

QUEUE

USERTILLS

TILLID

TILLBRNCD

USERACCCLASS

ACCCLS

USERGLREST

NODEGL

USERGLEXCEPT

EXCEPLEAFGL

USERLIMITSROLE

LMTBRN

LMTSROLE

QLMTCCY

QINPLMT

QAUTHLMT

USERBRANCHES

BRNSBRN

BRNNAME

USERPRODUCTS

PRDPRDCD

PRDDESC

USERACCESSPRODUCTS

PRDACCESSPRDCD

PRDDESC

USERFUNCDISALLOW

FUNCDISALLOWFUNCID

USERROLE

ROLEBRNCD

USRROLEID

MASTERROLEDESC

USERSFUNCTIONS

USERFUNCBRNCD

USERFUNCFUNCID

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

USERFUNCSCTRL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

CONTROL15

CONTROL16

Grp-Restriction

GROUP_CODE

GROUP_DESC

Centralisation

USRROLEID

ROLDESC

Dshmst

USRID

USRNAME

Dshdet

FUNCTIONID

DESCRIPTION

SEQUENCE_NO

DBWHERECLAUSE

SHOW_IN_DASHBOARD

Where-Master

COLUMN_NAME

WHERE_CL

CONDITION

UDFDETAILS

FLDNAM

FLDVAL

AUTHORIZEUSERMAINT_FSFS_REQ

Attribute	Description
Name	AUTHORIZEUSERMAINT_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.

Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

USR-Full

Attribute	Description
Name	USR-Full
Datatype	
Description	

STRTDATE

Attribute	Description

Name	STRTDATE
Datatype	String
Description	

USRNAME

Attribute	Description
Name	USRNAME
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 35

USRPWD

Attribute	Description
Name	USRPWD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

ENDDT

Attribute	Description
Name	ENDDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

USRLANG

Attribute	Description
Name	USRLANG
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

HOMEBRN

Attribute	Description
Name	HOMEBRN
Datatype	String
Description	

Restrictions	
	Restrictions / **Description**: maxLength / 3

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

LDAPUSR

Attribute	Description
Name	LDAPUSR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 500

TIMELEVEL

Attribute	Description
Name	TIMELEVEL
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 9

AUTOAUTH

Attribute	Description
Name	AUTOAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: enumeration / Y,N

USRSTAT

Attribute	Description
Name	USRSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,H,D,L

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12

EXTUSRREF

Attribute	Description
Name	EXTUSRREF
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

USRCATEG

Attribute	Description
Name	USRCATEG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,B

TILLALLOW

Attribute	Description
Name	TILLALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

ACCCLSALLOW

Attribute	Description
Name	ACCCLSALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

GLALLOW

Attribute	Description
Name	GLALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

USRTXNLMT

Attribute	Description
Name	USRTXNLMT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,R,N

LMTSCCY

Attribute	Description
Name	LMTSCCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

MAXTXNAMT

Attribute	Description
Name	MAXTXNAMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

MAXAUTHAMT

Attribute	Description
Name	MAXAUTHAMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

BRNSALLOW

Attribute	Description
Name	BRNSALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

PRDSALLOW

Attribute	Description
Name	PRDSALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

PRDSACCESALLOW

Attribute	Description
Name	PRDSACCESALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

TAX_IDENTIFIER

Attribute	Description
Name	TAX_IDENTIFIER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

AMOUNT_FORMAT

Attribute	Description
Name	AMOUNT_FORMAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>.,,,.,,</td></tr></table>

DATE_FORMAT

Attribute	Description
Name	DATE_FORMAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M/d/yyyy</td></tr></table>

STAFFACCRESTR

Attribute	Description
Name	STAFFACCRESTR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

DEPT_CODE

Attribute	Description
Name	DEPT_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

DEPT_DESC

Attribute	Description
Name	DEPT_DESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

USRML

Attribute	Description
Name	USRML
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

ELCMUSER

Attribute	Description
Name	ELCMUSER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

GROUP_CODE

Attribute	Description
Name	GROUP_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

MULTIBRN_ACCESS

Attribute	Description
Name	MULTIBRN_ACCESS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

OTH_RM_CUST_ACC_ALLOW

Attribute	Description
Name	OTH_RM_CUST_ACC_ALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

SUPERVISOR_ID

Attribute	Description
Name	SUPERVISOR_ID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>80</td></tr></table>

SUPERVISOR_NAME

Attribute	Description
Name	SUPERVISOR_NAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

DASHBOARD_REQD

Attribute	Description
Name	DASHBOARD_REQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

ALERTS_ON_HOME

Attribute	Description
Name	ALERTS_ON_HOME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

NO_CUMULATIVE_LOGINS

Attribute	Description
Name	NO_CUMULATIVE_LOGINS
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

NO_SUCCESSIVE_LOGINS

Attribute	Description
Name	NO_SUCCESSIVE_LOGINS
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

SCREENSAVERTIMEOUTINSECONDS

Attribute	Description
Name	SCREENSAVERTIMEOUTINSECONDS
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

MFI_USER

Attribute	Description
Name	MFI_USER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

F10_REQD

Attribute	Description
Name	F10_REQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

F11_REQD

Attribute	Description
Name	F11_REQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

F12_REQD

Attribute	Description
Name	F12_REQD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

ACCESS_CONTROL

Attribute	Description
Name	ACCESS_CONTROL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,G,B

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

RESTR_PWD

Attribute	Description
Name	RESTR_PWD
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PWD

Attribute	Description
Name	PWD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MSGSRIGHTS

Attribute	Description
Name	MSGSRIGHTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
enumeration	Y,N

HLD

Attribute	Description
Name	HLD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CNL

Attribute	Description
Name	CNL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

TSTINP

Attribute	Description
Name	TSTINP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGNODE

Attribute	Description
Name	CHGNODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGADDR

Attribute	Description
Name	CHGADDR
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

REL

Attribute	Description
Name	REL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

REINS

Attribute	Description
Name	REINS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGMEDIA

Attribute	Description
Name	CHGMEDIA
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGPRIOR

Attribute	Description
Name	CHGPRIOR
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

BRNMOV

Attribute	Description
Name	BRNMOV
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

PRNT

Attribute	Description
Name	PRNT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

TSTCHK

Attribute	Description
Name	TSTCHK
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: enumeration / Y,N

HLDAUTH

Attribute	Description
Name	HLDAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CNLAUTH

Attribute	Description
Name	CNLAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TSTINPAUTH

Attribute	Description
Name	TSTINPAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGNODEAUTH

Attribute	Description
Name	CHGNODEAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: enumeration / Y,N

CHGADDRAUTH

Attribute	Description
Name	CHGADDRAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

RELAUTH

Attribute	Description
Name	RELAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

REINSAUTH

Attribute	Description
Name	REINSAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMEDIAAUTH

Attribute	Description
Name	CHGMEDIAAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	Y,N

BRNMOVAUTH

Attribute	Description
Name	BRNMOVAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGPRIORAUTH

Attribute	Description
Name	CHGPRIORAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

FTUPL

Attribute	Description
Name	FTUPL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

LNKCONT

Attribute	Description
Name	LNKCONT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

MOVQ

Attribute	Description
Name	MOVQ
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGBRNIN

Attribute	Description
Name	CHGBRNIN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGADDRIN

Attribute	Description
Name	CHGADDRIN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

AUTHRGHTS

Attribute	Description
Name	AUTHRGHTS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGMSG

Attribute	Description
Name	CHGMSG
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGMSGAUTH

Attribute	Description
Name	CHGMSGAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGFORCCOVMATCH

Attribute	Description
Name	CHGFORCCOVMATCH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHANGE_FORCE_RELEASE_FUND

Attribute	Description
Name	CHANGE_FORCE_RELEASE_FUND
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

SUPPRESS

Attribute	**Description**
Name	SUPPRESS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

DELMSG

Attribute	**Description**
Name	DELMSG
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

QUEUERIGHTS

Attribute	**Description**
Name	QUEUERIGHTS
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

QUEUE

Attribute	**Description**
Name	QUEUE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 10

USERTILLS

Attribute	**Description**

Name	USERTILLS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

TILLID

Attribute	Description
Name	TILLID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12

TILLBRNCD

Attribute	Description
Name	TILLBRNCD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

USERACCCLASS

Attribute	Description
Name	USERACCCLASS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	6

USERGLREST

Attribute	Description
Name	USERGLREST
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NODEGL

Attribute	Description
Name	NODEGL
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	9

USERGLEXCEPT

Attribute	Description
Name	USERGLEXCEPT
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

EXCEPLEAFGL

Attribute	Description
Name	EXCEPLEAFGL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

USERLIMITSROLE

Attribute	Description
Name	USERLIMITSROLE
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

LMTBRN

Attribute	Description
Name	LMTBRN

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

LMTSROLE

Attribute	**Description**
Name	LMTSROLE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

QLMTCCY

Attribute	**Description**
Name	QLMTCCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

QINPLMT

Attribute	**Description**
Name	QINPLMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

QAUTHLMT

Attribute	**Description**
Name	QAUTHLMT
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** totalDigits / 22

USERBRANCHES

Attribute	**Description**
Name	USERBRANCHES
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

BRNSBRN

Attribute	**Description**
Name	BRNSBRN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 3

BRNNAME

Attribute	**Description**
Name	BRNNAME
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

USERPRODUCTS

Attribute	**Description**
Name	USERPRODUCTS
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

PRDPRDCD

Attribute	Description
Name	PRDPRDCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

USERACCESSPRODUCTS

Attribute	Description
Name	USERACCESSPRODUCTS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

PRDACCESSPRDCD

Attribute	Description
Name	PRDACCESSPRDCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	105

USERFUNCDISALLOW

Attribute	Description
Name	USERFUNCDISALLOW
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FUNCDISALLOWFUNCID

Attribute	Description
Name	FUNCDISALLOWFUNCID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	8

USERROLE

Attribute	Description
Name	USERROLE
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ROLEBRNCD

Attribute	Description
Name	ROLEBRNCD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

USRROLEID

Attribute	Description
Name	USRROLEID
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	15

MASTERROLEDESC

Attribute	Description
Name	MASTERROLEDESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	45

USERSFUNCTIONS

Attribute	Description
Name	USERSFUNCTIONS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

USERFUNCBRNCD

Attribute	Description
Name	USERFUNCBRNCD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

USERFUNCFUNCID

Attribute	Description
Name	USERFUNCFUNCID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	8

CONTROL1

Attribute	Description
Name	CONTROL1
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: totalDigits / 22

CONTROL2

Attribute	**Description**
Name	CONTROL2
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL3

Attribute	**Description**
Name	CONTROL3
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL4

Attribute	**Description**
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL5

Attribute	**Description**
Name	CONTROL5
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: totalDigits / 22

CONTROL6

Attribute	**Description**
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL7

Attribute	**Description**
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL8

Attribute	**Description**
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL9

Attribute	**Description**
Name	CONTROL9
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

USERFUNCSCTRL10

Attribute	**Description**
Name	USERFUNCSCTRL10
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL11

Attribute	**Description**
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL12

Attribute	**Description**
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL13

Attribute	**Description**
Name	CONTROL13
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL14

Attribute	**Description**
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL15

Attribute	**Description**
Name	CONTROL15
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL16

Attribute	**Description**
Name	CONTROL16
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

Grp-Restriction

Attribute	**Description**
Name	Grp-Restriction
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

GROUP_CODE

Attribute	Description
Name	GROUP_CODE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	40

GROUP_DESC

Attribute	Description
Name	GROUP_DESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255

Centralisation

Attribute	Description
Name	Centralisation
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

USRROLEID

Attribute	Description
Name	USRROLEID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	15

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

Dshmst

Attribute	Description
Name	Dshmst
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

USRNAME

Attribute	Description
Name	USRNAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

Dshdet

Attribute	Description
Name	Dshdet
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1000

SEQUENCE_NO

Attribute	Description
Name	SEQUENCE_NO
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	22

DBWHERECLAUSE

Attribute	Description
Name	DBWHERECLAUSE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	4000

SHOW_IN_DASHBOARD

Attribute	Description

Name	SHOW_IN_DASHBOARD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

Where-Master

Attribute	**Description**
Name	Where-Master
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

COLUMN_NAME

Attribute	**Description**
Name	COLUMN_NAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

WHERE_CL

Attribute	**Description**
Name	WHERE_CL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 500

CONDITION

Attribute	**Description**
Name	CONDITION
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.3.2.SM-AuthorizeUserMaint-Req-IO-MSG.xsd

AUTHORIZEUSERMAINT_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

USR-IO

USRID

CHECKER

CHECKERSTAMP

MODNO

AUTHORIZEUSERMAINT_IOPK_REQ

Attribute	Description
Name	AUTHORIZEUSERMAINT_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

USR-IO

Attribute	Description
Name	USR-IO
Datatype	
Description	

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

2.3.3.SM-AuthorizeUserMaint-Res-Full-MSG.xsd

AUTHORIZEUSERMAINT_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

USR-Full

STRTDATE

USRNAME

USRPWD

ENDDT

USRLANG

HOMEBRN

CUSTNO

LDAPUSR

TIMELEVEL

AUTOAUTH

USRSTAT

USRID

EXTUSRREF

USRCATEG

TILLALLOW

ACCCLSALLOW

GLALLOW

USRTXNLMT

LMTSCCY

MAXTXNAMT

MAXAUTHAMT

BRNSALLOW

PRDSALLOW

PRDSACCESALLOW

TAX_IDENTIFIER

AMOUNT_FORMAT

DATE_FORMAT

STAFFACCRESTR

DEPT_CODE

DEPT_DESC

USRML

ELCMUSER

GROUP_CODE

MULTIBRN_ACCESS

OTH_RM_CUST_ACC_ALLOW

SUPERVISOR_ID

SUPERVISOR_NAME

DASHBOARD_REQD

ALERTS_ON_HOME

REFERENCE_NO

NO_CUMULATIVE_LOGINS

NO_SUCCESSIVE_LOGINS

SCREENSAVERTIMEOUTINSECONDS

MFI_USER

F10_REQD

F11_REQD

F12_REQD

ACCESS_CONTROL

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

RESTR_PWD

PWD

MSGSRIGHTS

GEN

HLD

CNL

TSTINP

CHGNODE

CHGADDR

REL

REINS

CHGMEDIA

CHGPRIOR

BRNMOV

PRNT

TSTCHK

HLDAUTH

CNLAUTH

TSTINPAUTH

CHGNODEAUTH

CHGADDRAUTH

RELAUTH

REINSAUTH

CHGMEDIAAUTH

BRNMOVAUTH

CHGPRIORAUTH

FTUPL

LNKCONT

MOVQ

CHGBRNIN

CHGADDRIN

AUTHRGHTS

CHGMSG

CHGMSGAUTH

CHGFORCCOVMATCH

CHANGE_FORCE_RELEASE_FUND

SUPPRESS

DELMSG

QUEUERIGHTS

QUEUE

USERTILLS

TILLID

TILLBRNCD

USERACCCLASS

ACCCLS

USERGLREST

NODEGL

USERGLEXCEPT

EXCEPLEAFGL

USERLIMITSROLE

LMTBRN

LMTSROLE

QLMTCCY

QINPLMT

QAUTHLMT

USERBRANCHES

BRNSBRN

BRNNAME

USERPRODUCTS

PRDPRDCD

PRDDESC

USERACCESSPRODUCTS

PRDACCESSPRDCD

PRDDESC

USERFUNCDISALLOW

FUNCDISALLOWFUNCID

USERROLE

ROLEBRNCD

USRROLEID

MASTERROLEDESC

USERSFUNCTIONS

USERFUNCBRNCD

USERFUNCFUNCID

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

USERFUNCSCTRL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

CONTROL15

CONTROL16

Grp-Restriction

GROUP_CODE

GROUP_DESC

Centralisation

USRROLEID

ROLDESC

Dshmst

USRID

USRNAME

Dshdet

FUNCTIONID

DESCRIPTION

SEQUENCE_NO

DBWHERECLAUSE

SHOW_IN_DASHBOARD

Where-Master

COLUMN_NAME

WHERE_CL

CONDITION

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZEUSERMAINT_FSFS_RES

Attribute	Description
Name	AUTHORIZEUSERMAINT_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

USR-Full

Attribute	Description
Name	USR-Full
Datatype	
Description	

STRTDATE

Attribute	Description
Name	STRTDATE
Datatype	String
Description	

USRNAME

Attribute	Description
Name	USRNAME
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 35

USRPWD

Attribute	Description
Name	USRPWD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

ENDDT

Attribute	Description
Name	ENDDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

USRLANG

Attribute	Description
Name	USRLANG
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

HOMEBRN

Attribute	Description
Name	HOMEBRN
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

LDAPUSR

Attribute	Description
Name	LDAPUSR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	
	Restrictions / **Description**: maxLength / 500

TIMELEVEL

Attribute	Description
Name	TIMELEVEL
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 9

AUTOAUTH

Attribute	Description
Name	AUTOAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

USRSTAT

Attribute	Description
Name	USRSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,H,D,L

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12

EXTUSRREF

Attribute	Description
Name	EXTUSRREF
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

USRCATEG

Attribute	Description
Name	USRCATEG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,B</td></tr></table>

TILLALLOW

Attribute	Description
Name	TILLALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

ACCCLSALLOW

Attribute	Description
Name	ACCCLSALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

GLALLOW

Attribute	Description
Name	GLALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

USRTXNLMT

Attribute	Description
Name	USRTXNLMT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>U,R,N</td></tr></table>

LMTSCCY

Attribute	Description
Name	LMTSCCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

MAXTXNAMT

Attribute	Description
Name	MAXTXNAMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

MAXAUTHAMT

Attribute	Description
Name	MAXAUTHAMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

BRNSALLOW

Attribute	Description
Name	BRNSALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

PRDSALLOW

Attribute	Description
Name	PRDSALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

PRDSACCESALLOW

Attribute	Description
Name	PRDSACCESALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

TAX_IDENTIFIER

Attribute	Description
Name	TAX_IDENTIFIER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

AMOUNT_FORMAT

Attribute	Description
Name	AMOUNT_FORMAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>.,,,.,,</td></tr></table>

DATE_FORMAT

Attribute	Description
Name	DATE_FORMAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M/d/yyyy</td></tr></table>

STAFFACCRESTR

Attribute	Description
Name	STAFFACCRESTR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

DEPT_CODE

Attribute	Description
Name	DEPT_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

DEPT_DESC

Attribute	Description
Name	DEPT_DESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

USRML

Attribute	Description
Name	USRML
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

ELCMUSER

Attribute	Description
Name	ELCMUSER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

GROUP_CODE

Attribute	Description
Name	GROUP_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

MULTIBRN_ACCESS

Attribute	Description
Name	MULTIBRN_ACCESS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

OTH_RM_CUST_ACC_ALLOW

Attribute	Description
Name	OTH_RM_CUST_ACC_ALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

SUPERVISOR_ID

Attribute	Description
Name	SUPERVISOR_ID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>80</td></tr></table>

SUPERVISOR_NAME

Attribute	Description
Name	SUPERVISOR_NAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

DASHBOARD_REQD

Attribute	Description
Name	DASHBOARD_REQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

ALERTS_ON_HOME

Attribute	Description
Name	ALERTS_ON_HOME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

NO_CUMULATIVE_LOGINS

Attribute	Description
Name	NO_CUMULATIVE_LOGINS
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

NO_SUCCESSIVE_LOGINS

Attribute	Description
Name	NO_SUCCESSIVE_LOGINS
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

SCREENSAVERTIMEOUTINSECONDS

Attribute	Description
Name	SCREENSAVERTIMEOUTINSECONDS
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

MFI_USER

Attribute	Description
Name	MFI_USER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

F10_REQD

Attribute	Description
Name	F10_REQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

F11_REQD

Attribute	Description
Name	F11_REQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

F12_REQD

Attribute	Description
Name	F12_REQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

ACCESS_CONTROL

Attribute	Description
Name	ACCESS_CONTROL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>U,G,B</td></tr></table>

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

RESTR_PWD

Attribute	Description
Name	RESTR_PWD
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PWD

Attribute	Description
Name	PWD
Datatype	String

Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MSGSRIGHTS

Attribute	Description
Name	MSGSRIGHTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

HLD

Attribute	Description
Name	HLD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CNL

Attribute	Description
Name	CNL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
enumeration	Y,N

TSTINP

Attribute	Description
Name	TSTINP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGNODE

Attribute	Description
Name	CHGNODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGADDR

Attribute	Description
Name	CHGADDR
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

REL

Attribute	Description
Name	REL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

REINS

Attribute	Description
Name	REINS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGMEDIA

Attribute	Description
Name	CHGMEDIA
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGPRIOR

Attribute	Description
Name	CHGPRIOR
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

BRNMOV

Attribute	Description
Name	BRNMOV
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: enumeration / Y,N

PRNT

Attribute	Description
Name	PRNT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TSTCHK

Attribute	Description
Name	TSTCHK
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

HLDAUTH

Attribute	Description
Name	HLDAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CNLAUTH

Attribute	Description
Name	CNLAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: enumeration / Y,N

TSTINPAUTH

Attribute	Description
Name	TSTINPAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGNODEAUTH

Attribute	Description
Name	CHGNODEAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGADDRAUTH

Attribute	Description
Name	CHGADDRAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

RELAUTH

Attribute	Description
Name	RELAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: enumeration / Y,N

REINSAUTH

Attribute	Description
Name	REINSAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMEDIAAUTH

Attribute	Description
Name	CHGMEDIAAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

BRNMOVAUTH

Attribute	Description
Name	BRNMOVAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGPRIORAUTH

Attribute	Description
Name	CHGPRIORAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	Y,N

FTUPL

Attribute	Description
Name	FTUPL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

LNKCONT

Attribute	Description
Name	LNKCONT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

MOVQ

Attribute	Description
Name	MOVQ
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGBRNIN

Attribute	Description
Name	CHGBRNIN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: enumeration / Y,N

CHGADDRIN

Attribute	Description
Name	CHGADDRIN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

AUTHRGHTS

Attribute	Description
Name	AUTHRGHTS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMSG

Attribute	Description
Name	CHGMSG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMSGAUTH

Attribute	Description
Name	CHGMSGAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGFORCCOVMATCH

Attribute	Description
Name	CHGFORCCOVMATCH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHANGE_FORCE_RELEASE_FUND

Attribute	Description
Name	CHANGE_FORCE_RELEASE_FUND
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

DELMSG

Attribute	Description
Name	DELMSG
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

QUEUERIGHTS

Attribute	Description
Name	QUEUERIGHTS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

QUEUE

Attribute	Description
Name	QUEUE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	10

USERTILLS

Attribute	Description
Name	USERTILLS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

TILLID

Attribute	Description
Name	TILLID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12

TILLBRNCD

Attribute	Description
Name	TILLBRNCD
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	3

USERACCCLASS

Attribute	Description
Name	USERACCCLASS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	6

USERGLREST

Attribute	Description
Name	USERGLREST
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NODEGL

Attribute	Description
Name	NODEGL
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	9

USERGLEXCEPT

Attribute	Description
Name	USERGLEXCEPT
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

EXCEPLEAFGL

Attribute	Description
Name	EXCEPLEAFGL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

USERLIMITSROLE

Attribute	Description
Name	USERLIMITSROLE
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

LMTBRN

Attribute	Description
Name	LMTBRN
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

LMTSROLE

Attribute	Description
Name	LMTSROLE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

QLMTCCY

Attribute	Description
Name	QLMTCCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

QINPLMT

Attribute	Description
Name	QINPLMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

QAUTHLMT

Attribute	Description
Name	QAUTHLMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

USERBRANCHES

Attribute	Description
Name	USERBRANCHES
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRNSBRN

Attribute	Description
Name	BRNSBRN
Datatype	String

Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

USERPRODUCTS

Attribute	Description
Name	USERPRODUCTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PRDPRDCD

Attribute	Description
Name	PRDPRDCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

USERACCESSPRODUCTS

Attribute	Description
Name	USERACCESSPRODUCTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PRDACCESSPRDCD

Attribute	Description
Name	PRDACCESSPRDCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

USERFUNCDISALLOW

Attribute	Description
Name	USERFUNCDISALLOW
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FUNCDISALLOWFUNCID

Attribute	Description
Name	FUNCDISALLOWFUNCID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

USERROLE

Attribute	Description
Name	USERROLE
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ROLEBRNCD

Attribute	Description
Name	ROLEBRNCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

USRROLEID

Attribute	Description
Name	USRROLEID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

MASTERROLEDESC

Attribute	Description
Name	MASTERROLEDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>45</td></tr></table>

USERSFUNCTIONS

Attribute	Description
Name	USERSFUNCTIONS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

USERFUNCBRNCD

Attribute	Description
Name	USERFUNCBRNCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

USERFUNCFUNCID

Attribute	Description
Name	USERFUNCFUNCID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

CONTROL1

Attribute	Description
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL2

Attribute	Description
Name	CONTROL2
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL3

Attribute	Description
Name	CONTROL3
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL4

Attribute	**Description**
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL5

Attribute	**Description**
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL6

Attribute	**Description**
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL7

Attribute	**Description**
Name	CONTROL7
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: totalDigits / 22

CONTROL8

Attribute	**Description**
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL9

Attribute	**Description**
Name	CONTROL9
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

USERFUNCSCTRL10

Attribute	**Description**
Name	USERFUNCSCTRL10
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL11

Attribute	**Description**
Name	CONTROL11
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: totalDigits / 22

CONTROL12

Attribute	**Description**
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL13

Attribute	**Description**
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL14

Attribute	**Description**
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL15

Attribute	**Description**
Name	CONTROL15
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL16

Attribute	**Description**
Name	CONTROL16
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

Grp-Restriction

Attribute	**Description**
Name	Grp-Restriction
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

GROUP_CODE

Attribute	**Description**
Name	GROUP_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 40

GROUP_DESC

Attribute	**Description**
Name	GROUP_DESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	255

Centralisation

Attribute	Description
Name	Centralisation
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

USRROLEID

Attribute	Description
Name	USRROLEID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	15

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

Dshmst

Attribute	Description
Name	Dshmst
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 15

USRNAME

Attribute	**Description**
Name	USRNAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

Dshdet

Attribute	**Description**
Name	Dshdet
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

DESCRIPTION

Attribute	**Description**
Name	DESCRIPTION
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

SEQUENCE_NO

Attribute	**Description**
Name	SEQUENCE_NO
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description** totalDigits / 22

DBWHERECLAUSE

Attribute	**Description**
Name	DBWHERECLAUSE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 4000

SHOW_IN_DASHBOARD

Attribute	**Description**
Name	SHOW_IN_DASHBOARD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

Where-Master

Attribute	**Description**
Name	Where-Master
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

COLUMN_NAME

Attribute	**Description**

Name	COLUMN_NAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

WHERE_CL

Attribute	**Description**
Name	WHERE_CL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 500

CONDITION

Attribute	**Description**
Name	CONDITION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	Indicates Field Name

Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	150
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.3.4.SM-AuthorizeUserMaint-Res-PK-MSG.xsd

AUTHORIZEUSERMAINT_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

USR-PK

USRID

USR-IO

USRID

CHECKER

CHECKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

AUTHORIZEUSERMAINT_IOPK_RES

Attribute	Description
Name	AUTHORIZEUSERMAINT_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description

Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

USR-PK

Attribute	Description
Name	USR-PK
Datatype	
Description	

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

USR-IO

Attribute	Description
Name	USR-IO
Datatype	
Description	

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKER

Attribute	Description

Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.4.CloseSMDBANKP

2.4.1.SM-CloseSMDBANKP-Req-Full-MSG.xsd

CLOSESMDBANKP_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Parameters-Full

HEAD_OFFICE

SITE_CODE

ACTIVATION_KEY

INVALID_LOGINS_CUM

INVALID_LOGINS_SUC

PWD_PREVENT_REUSE

PWD_CHANGE_AFTER

MAXIMUM

MINIMUM

PWD_EXPIRY_MSG_DAYS

ARCHIVAL_PERIOD

CONCHAR_PWD_NUM

FREQ_PWD_CHG

MIN_PWD_NUMERIC_LENGTH

LEGAL_NOTICE

DORMANCY_DAYS

DISPLAY_LEGAL_NOTICE

MIN_SPECIALCHAR_LENGTH

MIN_LOWERCASE_CHAR

MIN_UPPERCASE_CHAR

SCREENSAVERREQUIRED

SCREENSAVERTIMEOUTINSECONDS

SCREENSAVERMODIFIABLEBYUSER

PASSWORDEXTERNAL

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Smtbs-Branch-Restr

- *RESTR_TYPE*
- *DESCRIPTION*

Smtbs-Restrictive-Passwd

- *PASSWORD*

UDFDETAILS

- *FLDNAM*
- *FLDVAL*

Attribute	Description
Name	CLOSESMDBANKP_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Parameters-Full

Attribute	Description
Name	Smtbs-Parameters-Full
Datatype	
Description	

HEAD_OFFICE

Attribute	Description
Name	HEAD_OFFICE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

SITE_CODE

Attribute	Description
Name	SITE_CODE
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	4

ACTIVATION_KEY

Attribute	Description
Name	ACTIVATION_KEY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	24

INVALID_LOGINS_CUM

Attribute	Description
Name	INVALID_LOGINS_CUM
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	6
maxInclusive	99

INVALID_LOGINS_SUC

Attribute	Description
Name	INVALID_LOGINS_SUC
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	1
minInclusive	3
maxInclusive	5

PWD_PREVENT_REUSE

Attribute	Description
Name	PWD_PREVENT_REUSE
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** totalDigits / 2 minInclusive / 1

PWD_CHANGE_AFTER

Attribute	**Description**
Name	PWD_CHANGE_AFTER
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 3 minInclusive / 15 maxInclusive / 180

MAXIMUM

Attribute	**Description**
Name	MAXIMUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2 minInclusive / 12 maxInclusive / 30

MINIMUM

Attribute	**Description**
Name	MINIMUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2 minInclusive / 6 maxInclusive / 11

PWD_EXPIRY_MSG_DAYS

Attribute	Description
Name	PWD_EXPIRY_MSG_DAYS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1; maxInclusive / 5

ARCHIVAL_PERIOD

Attribute	Description
Name	ARCHIVAL_PERIOD
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

CONCHAR_PWD_NUM

Attribute	Description
Name	CONCHAR_PWD_NUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2

FREQ_PWD_CHG

Attribute	Description
Name	FREQ_PWD_CHG
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	0

MIN_PWD_NUMERIC_LENGTH

Attribute	Description
Name	MIN_PWD_NUMERIC_LENGTH
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1

LEGAL_NOTICE

Attribute	Description
Name	LEGAL_NOTICE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4000

DORMANCY_DAYS

Attribute	Description
Name	DORMANCY_DAYS
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1

DISPLAY_LEGAL_NOTICE

Attribute	Description
Name	DISPLAY_LEGAL_NOTICE
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

MIN_SPECIALCHAR_LENGTH

Attribute	**Description**
Name	MIN_SPECIALCHAR_LENGTH
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2 minInclusive / 1

MIN_LOWERCASE_CHAR

Attribute	**Description**
Name	MIN_LOWERCASE_CHAR
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2 minInclusive / 1

MIN_UPPERCASE_CHAR

Attribute	**Description**
Name	MIN_UPPERCASE_CHAR
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2 minInclusive / 1

SCREENSAVERREQUIRED

Attribute	**Description**

Name	SCREENSAVERREQUIRED
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

SCREENSAVERTIMEOUTINSECONDS

Attribute	**Description**
Name	SCREENSAVERTIMEOUTINSECONDS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

SCREENSAVERMODIFIABLEBYUSER

Attribute	**Description**
Name	SCREENSAVERMODIFIABLEBYUSER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

PASSWORDEXTERNAL

Attribute	**Description**
Name	PASSWORDEXTERNAL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

MAKER

Attribute	**Description**

Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	**Description**

Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

Smtbs-Branch-Restr

Attribute	**Description**
Name	Smtbs-Branch-Restr
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

RESTR_TYPE

Attribute	**Description**
Name	RESTR_TYPE
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** maxLength / 12

DESCRIPTION

Attribute	**Description**
Name	DESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

Smtbs-Restrictive-Passwd

Attribute	**Description**
Name	Smtbs-Restrictive-Passwd
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.4.2.SM-CloseSMDBANKP-Req-IO-MSG.xsd

CLOSESMDBANKP_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Parameters-IO

SITE_CODE

MAKER

MAKERSTAMP

MODNO

CLOSESMDBANKP_IOPK_REQ

Attribute	Description
Name	CLOSESMDBANKP_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Parameters-IO

Attribute	Description

Name	Smtbs-Parameters-IO
Datatype	
Description	

SITE_CODE

Attribute	Description
Name	SITE_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

CLOSESMDBANKP_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Parameters-Full

HEAD_OFFICE

SITE_CODE

ACTIVATION_KEY

INVALID_LOGINS_CUM

INVALID_LOGINS_SUC

PWD_PREVENT_REUSE

PWD_CHANGE_AFTER

MAXIMUM

MINIMUM

PWD_EXPIRY_MSG_DAYS

ARCHIVAL_PERIOD

CONCHAR_PWD_NUM

FREQ_PWD_CHG

MIN_PWD_NUMERIC_LENGTH

LEGAL_NOTICE

DORMANCY_DAYS

DISPLAY_LEGAL_NOTICE

MIN_SPECIALCHAR_LENGTH

MIN_LOWERCASE_CHAR

MIN_UPPERCASE_CHAR

SCREENSAVERREQUIRED

SCREENSAVERTIMEOUTINSECONDS

SCREENSAVERMODIFIABLEBYUSER

PASSWORDEXTERNAL

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Smtbs-Branch-Restr

- *RESTR_TYPE*
- *DESCRIPTION*

Smtbs-Restrictive-Passwd

- *PASSWORD*

UDFDETAILS

- *FLDNAM*
- *FLDVAL*

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CLOSESMDBANKP_FSFS_RES

Attribute	Description
Name	CLOSESMDBANKP_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID

Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Parameters-Full

Attribute	Description
Name	Smtbs-Parameters-Full
Datatype	
Description	

HEAD_OFFICE

Attribute	Description

Name	HEAD_OFFICE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

SITE_CODE

Attribute	**Description**
Name	SITE_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

ACTIVATION_KEY

Attribute	**Description**
Name	ACTIVATION_KEY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 24

INVALID_LOGINS_CUM

Attribute	**Description**
Name	INVALID_LOGINS_CUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 6; maxInclusive / 99

INVALID_LOGINS_SUC

Attribute	**Description**
Name	INVALID_LOGINS_SUC
Datatype	Decimal

Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 1; minInclusive / 3; maxInclusive / 5

PWD_PREVENT_REUSE

Attribute	**Description**
Name	PWD_PREVENT_REUSE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

PWD_CHANGE_AFTER

Attribute	**Description**
Name	PWD_CHANGE_AFTER
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3; minInclusive / 15; maxInclusive / 180

MAXIMUM

Attribute	**Description**
Name	MAXIMUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 12; maxInclusive / 30

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 6; maxInclusive / 11

PWD_EXPIRY_MSG_DAYS

Attribute	Description
Name	PWD_EXPIRY_MSG_DAYS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1; maxInclusive / 5

ARCHIVAL_PERIOD

Attribute	Description
Name	ARCHIVAL_PERIOD
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

CONCHAR_PWD_NUM

Attribute	Description
Name	CONCHAR_PWD_NUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	2

FREQ_PWD_CHG

Attribute	Description
Name	FREQ_PWD_CHG
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	0

MIN_PWD_NUMERIC_LENGTH

Attribute	Description
Name	MIN_PWD_NUMERIC_LENGTH
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1

LEGAL_NOTICE

Attribute	Description
Name	LEGAL_NOTICE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4000

DORMANCY_DAYS

Attribute	Description
Name	DORMANCY_DAYS
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2 minInclusive / 1

DISPLAY_LEGAL_NOTICE

Attribute	**Description**
Name	DISPLAY_LEGAL_NOTICE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

MIN_SPECIALCHAR_LENGTH

Attribute	**Description**
Name	MIN_SPECIALCHAR_LENGTH
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2 minInclusive / 1

MIN_LOWERCASE_CHAR

Attribute	**Description**
Name	MIN_LOWERCASE_CHAR
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2 minInclusive / 1

MIN_UPPERCASE_CHAR

Attribute	**Description**

Name	MIN_UPPERCASE_CHAR
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

SCREENSAVERREQUIRED

Attribute	**Description**
Name	SCREENSAVERREQUIRED
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

SCREENSAVERTIMEOUTINSECONDS

Attribute	**Description**
Name	SCREENSAVERTIMEOUTINSECONDS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

SCREENSAVERMODIFIABLEBYUSER

Attribute	**Description**
Name	SCREENSAVERMODIFIABLEBYUSER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

PASSWORDEXTERNAL

Attribute	**Description**

Name	PASSWORDEXTERNAL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	**Description**

Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

Smtbs-Branch-Restr

Attribute	**Description**

Name	Smtbs-Branch-Restr
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

RESTR_TYPE

Attribute	Description
Name	RESTR_TYPE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	12

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	255

Smtbs-Restrictive-Passwd

Attribute	Description
Name	Smtbs-Restrictive-Passwd
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	12

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	150
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description

Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

CLOSESMDBANKP_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Parameters-PK

SITE_CODE

Smtbs-Parameters-IO

SITE_CODE

MAKER

MAKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CLOSESMDBANKP_IOPK_RES

Attribute	Description
Name	CLOSESMDBANKP_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String

Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.

Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Parameters-PK

Attribute	Description
Name	Smtbs-Parameters-PK
Datatype	
Description	

SITE_CODE

Attribute	Description

Name	SITE_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

Smtbs-Parameters-IO

Attribute	Description
Name	Smtbs-Parameters-IO
Datatype	
Description	

SITE_CODE

Attribute	Description
Name	SITE_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	Description
Name	MODNO

Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.5.CloseSMDRLMNE

2.5.1.SM-CloseSMDRLMNE-Req-Full-MSG.xsd

CLOSESMDRLMNE_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Role-Limit-Full

ROLEID2

DESCRIPTION

LIMIT_CCY

INPUT_LIMIT

AUTHORIZATION_LIMIT

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

CLOSESMDRLMNE_FSFS_REQ

Attribute	Description
Name	CLOSESMDRLMNE_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Role-Limit-Full

Attribute	Description
Name	Smtbs-Role-Limit-Full
Datatype	
Description	

ROLEID2

Attribute	Description
Name	ROLEID2
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

LIMIT_CCY

Attribute	Description
Name	LIMIT_CCY
Datatype	String
Description	

Restrictions	
	Restrictions / **Description**: maxLength / 3

INPUT_LIMIT

Attribute	Description
Name	INPUT_LIMIT
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0

AUTHORIZATION_LIMIT

Attribute	Description
Name	AUTHORIZATION_LIMIT
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.5.2.SM-CloseSMDRLMNE-Req-IO-MSG.xsd

CLOSESMDRLMNE_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Role-Limit-IO

ROLEID2

MAKER

MAKERSTAMP

MODNO

CLOSESMDRLMNE_IOPK_REQ

Attribute	Description
Name	CLOSESMDRLMNE_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Role-Limit-IO

Attribute	Description
Name	Smtbs-Role-Limit-IO
Datatype	
Description	

ROLEID2

Attribute	Description
Name	ROLEID2
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

2.5.3.SM-CloseSMDRLMNE-Res-Full-MSG.xsd

CLOSESMDRLMNE_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Role-Limit-Full

ROLEID2

DESCRIPTION

LIMIT_CCY

INPUT_LIMIT

AUTHORIZATION_LIMIT

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CLOSESMDRLMNE_FSFS_RES

Attribute	Description
Name	CLOSESMDRLMNE_FSFS_RES

Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String

Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Role-Limit-Full

Attribute	Description
Name	Smtbs-Role-Limit-Full
Datatype	
Description	

ROLEID2

Attribute	Description
Name	ROLEID2
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	105

LIMIT_CCY

Attribute	Description
Name	LIMIT_CCY
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

INPUT_LIMIT

Attribute	Description
Name	INPUT_LIMIT
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0

AUTHORIZATION_LIMIT

Attribute	Description
Name	AUTHORIZATION_LIMIT
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String

Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	150
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.5.4.SM-CloseSMDRLMNE-Res-PK-MSG.xsd

CLOSESMDRLMNE_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Role-Limit-PK

ROLEID2

Smtbs-Role-Limit-IO

ROLEID2

MAKER

MAKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CLOSESMDRLMNE_IOPK_RES

Attribute	Description
Name	CLOSESMDRLMNE_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Role-Limit-PK

Attribute	Description
Name	Smtbs-Role-Limit-PK
Datatype	
Description	

ROLEID2

Attribute	Description
Name	ROLEID2
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

Smtbs-Role-Limit-IO

Attribute	Description
Name	Smtbs-Role-Limit-IO
Datatype	
Description	

ROLEID2

Attribute	Description
Name	ROLEID2
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

MAKER

Attribute	Description

Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.6.CloseUserMaint

2.6.1.SM-CloseUserMaint-Req-Full-MSG.xsd

CLOSEUSERMAINT_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

USR-Full

STRTDATE

USRNAME

USRPWD

ENDDT

USRLANG

HOMEBRN

CUSTNO

LDAPUSR

TIMELEVEL

AUTOAUTH

USRSTAT

USRID

EXTUSRREF

USRCATEG

TILLALLOW

ACCCLSALLOW

GLALLOW

USRTXNLMT

LMTSCCY

MAXTXNAMT

MAXAUTHAMT

BRNSALLOW

PRDSALLOW

PRDSACCESALLOW

TAX_IDENTIFIER

AMOUNT_FORMAT

DATE_FORMAT

STAFFACCRESTR

DEPT_CODE

DEPT_DESC

USRML

ELCMUSER

GROUP_CODE

MULTIBRN_ACCESS

OTH_RM_CUST_ACC_ALLOW

SUPERVISOR_ID

SUPERVISOR_NAME

DASHBOARD_REQD

ALERTS_ON_HOME

REFERENCE_NO

NO_CUMULATIVE_LOGINS

NO_SUCCESSIVE_LOGINS

SCREENSAVERTIMEOUTINSECONDS

MFI_USER

F10_REQD

F11_REQD

F12_REQD

ACCESS_CONTROL

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

RESTR_PWD

- *PWD*

MSGSRIGHTS

- *GEN*
- *HLD*
- *CNL*
- *TSTINP*
- *CHGNODE*
- *CHGADDR*
- *REL*
- *REINS*
- *CHGMEDIA*
- *CHGPRIOR*
- *BRNMOV*
- *PRNT*
- *TSTCHK*
- *HLDAUTH*

CNLAUTH

TSTINPAUTH

CHGNODEAUTH

CHGADDRAUTH

RELAUTH

REINSAUTH

CHGMEDIAAUTH

BRNMOVAUTH

CHGPRIORAUTH

FTUPL

LNKCONT

MOVQ

CHGBRNIN

CHGADDRIN

AUTHRGHTS

CHGMSG

CHGMSGAUTH

CHGFORCCOVMATCH

CHANGE_FORCE_RELEASE_FUND

SUPPRESS

DELMSG

QUEUERIGHTS

QUEUE

USERTILLS

TILLID

TILLBRNCD

USERACCCLASS

ACCCLS

USERGLREST

NODEGL

USERGLEXCEPT

EXCEPLEAFGL

USERLIMITSROLE

LMTBRN

LMTSROLE

QLMTCCY

QINPLMT

QAUTHLMT

USERBRANCHES

BRNSBRN

BRNNAME

USERPRODUCTS

PRDPRDCD

PRDDESC

USERACCESSPRODUCTS

PRDACCESSPRDCD

PRDDESC

USERFUNCDISALLOW

FUNCDISALLOWFUNCID

USERROLE

ROLEBRNCD

USRROLEID

MASTERROLEDESC

USERSFUNCTIONS

USERFUNCBRNCD

USERFUNCFUNCID

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

USERFUNCSCTRL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

CONTROL15

CONTROL16

Grp-Restriction

GROUP_CODE

GROUP_DESC

Centralisation

USRROLEID

ROLDESC

Dshmst

USRID

USRNAME

Dshdet

FUNCTIONID

DESCRIPTION

SEQUENCE_NO

DBWHERECLAUSE

SHOW_IN_DASHBOARD

Where-Master

COLUMN_NAME

WHERE_CL

CONDITION

UDFDETAILS

FLDNAM

FLDVAL

CLOSEUSERMAINT_FSFS_REQ

Attribute	Description

Name	CLOSEUSERMAINT_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

USR-Full

Attribute	Description
Name	USR-Full
Datatype	
Description	

STRTDATE

Attribute	Description
Name	STRTDATE
Datatype	String
Description	

USRNAME

Attribute	Description
Name	USRNAME
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

USRPWD

Attribute	Description

Name	USRPWD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

ENDDT

Attribute	**Description**
Name	ENDDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

USRLANG

Attribute	**Description**
Name	USRLANG
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

HOMEBRN

Attribute	**Description**
Name	HOMEBRN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

LDAPUSR

Attribute	Description
Name	LDAPUSR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>500</td></tr></table>

TIMELEVEL

Attribute	Description
Name	TIMELEVEL
Datatype	Decimal
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>9</td></tr></table>

AUTOAUTH

Attribute	Description
Name	AUTOAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

USRSTAT

Attribute	Description
Name	USRSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>E,H,D,L</td></tr></table>

USRID

Attribute	Description

Name	USRID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12

EXTUSRREF

Attribute	**Description**
Name	EXTUSRREF
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

USRCATEG

Attribute	**Description**
Name	USRCATEG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,B

TILLALLOW

Attribute	**Description**
Name	TILLALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

ACCCLSALLOW

Attribute	**Description**
Name	ACCCLSALLOW
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

GLALLOW

Attribute	**Description**
Name	GLALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

USRTXNLMT

Attribute	**Description**
Name	USRTXNLMT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,R,N

LMTSCCY

Attribute	**Description**
Name	LMTSCCY
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

MAXTXNAMT

Attribute	**Description**
Name	MAXTXNAMT
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

MAXAUTHAMT

Attribute	**Description**
Name	MAXAUTHAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

BRNSALLOW

Attribute	**Description**
Name	BRNSALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

PRDSALLOW

Attribute	**Description**
Name	PRDSALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

PRDSACCESALLOW

Attribute	**Description**
Name	PRDSACCESALLOW
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TAX_IDENTIFIER

Attribute	**Description**
Name	TAX_IDENTIFIER
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

AMOUNT_FORMAT

Attribute	**Description**
Name	AMOUNT_FORMAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / .,,,.,,

DATE_FORMAT

Attribute	**Description**
Name	DATE_FORMAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M/d/yyyy

STAFFACCRESTR

Attribute	**Description**
Name	STAFFACCRESTR
Datatype	String
Description	

Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

DEPT_CODE

Attribute	**Description**
Name	DEPT_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

DEPT_DESC

Attribute	**Description**
Name	DEPT_DESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

USRML

Attribute	**Description**
Name	USRML
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

ELCMUSER

Attribute	**Description**
Name	ELCMUSER
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

GROUP_CODE

Attribute	**Description**
Name	GROUP_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

MULTIBRN_ACCESS

Attribute	**Description**
Name	MULTIBRN_ACCESS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

OTH_RM_CUST_ACC_ALLOW

Attribute	**Description**
Name	OTH_RM_CUST_ACC_ALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

SUPERVISOR_ID

Attribute	**Description**
Name	SUPERVISOR_ID
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 80

SUPERVISOR_NAME

Attribute	**Description**
Name	SUPERVISOR_NAME
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

DASHBOARD_REQD

Attribute	**Description**
Name	DASHBOARD_REQD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

ALERTS_ON_HOME

Attribute	**Description**
Name	ALERTS_ON_HOME
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

REFERENCE_NO

Attribute	**Description**
Name	REFERENCE_NO
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

NO_CUMULATIVE_LOGINS

Attribute	**Description**
Name	NO_CUMULATIVE_LOGINS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

NO_SUCCESSIVE_LOGINS

Attribute	**Description**
Name	NO_SUCCESSIVE_LOGINS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

SCREENSAVERTIMEOUTINSECONDS

Attribute	**Description**
Name	SCREENSAVERTIMEOUTINSECONDS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

MFI_USER

Attribute	**Description**
Name	MFI_USER
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

F10_REQD

Attribute	Description
Name	F10_REQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

F11_REQD

Attribute	Description
Name	F11_REQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

F12_REQD

Attribute	Description
Name	F12_REQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

ACCESS_CONTROL

Attribute	Description
Name	ACCESS_CONTROL
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,G,B

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

RESTR_PWD

Attribute	Description
Name	RESTR_PWD
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PWD

Attribute	Description
Name	PWD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12

MSGSRIGHTS

Attribute	Description
Name	MSGSRIGHTS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

HLD

Attribute	Description
Name	HLD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CNL

Attribute	Description

Name	CNL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TSTINP

Attribute	**Description**
Name	TSTINP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGNODE

Attribute	**Description**
Name	CHGNODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGADDR

Attribute	**Description**
Name	CHGADDR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

REL

Attribute	**Description**

Name	REL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

REINS

Attribute	**Description**
Name	REINS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMEDIA

Attribute	**Description**
Name	CHGMEDIA
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGPRIOR

Attribute	**Description**
Name	CHGPRIOR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

BRNMOV

Attribute	**Description**

Name	BRNMOV
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

PRNT

Attribute	**Description**
Name	PRNT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TSTCHK

Attribute	**Description**
Name	TSTCHK
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

HLDAUTH

Attribute	**Description**
Name	HLDAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CNLAUTH

Attribute	**Description**

Name	CNLAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TSTINPAUTH

Attribute	**Description**
Name	TSTINPAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGNODEAUTH

Attribute	**Description**
Name	CHGNODEAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGADDRAUTH

Attribute	**Description**
Name	CHGADDRAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

RELAUTH

Attribute	**Description**

Name	RELAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

REINSAUTH

Attribute	**Description**
Name	REINSAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMEDIAAUTH

Attribute	**Description**
Name	CHGMEDIAAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

BRNMOVAUTH

Attribute	**Description**
Name	BRNMOVAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGPRIORAUTH

Attribute	**Description**

Name	CHGPRIORAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

FTUPL

Attribute	**Description**
Name	FTUPL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

LNKCONT

Attribute	**Description**
Name	LNKCONT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

MOVQ

Attribute	**Description**
Name	MOVQ
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGBRNIN

Attribute	**Description**

Name	CHGBRNIN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGADDRIN

Attribute	**Description**
Name	CHGADDRIN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

AUTHRGHTS

Attribute	**Description**
Name	AUTHRGHTS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMSG

Attribute	**Description**
Name	CHGMSG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMSGAUTH

Attribute	**Description**

Name	CHGMSGAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGFORCCOVMATCH

Attribute	**Description**
Name	CHGFORCCOVMATCH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHANGE_FORCE_RELEASE_FUND

Attribute	**Description**
Name	CHANGE_FORCE_RELEASE_FUND
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

SUPPRESS

Attribute	**Description**
Name	SUPPRESS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

DELMSG

Attribute	**Description**

Name	DELMSG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

QUEUERIGHTS

Attribute	**Description**
Name	QUEUERIGHTS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

QUEUE

Attribute	**Description**
Name	QUEUE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 10

USERTILLS

Attribute	**Description**
Name	USERTILLS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

TILLID

Attribute	**Description**
Name	TILLID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12

TILLBRNCD

Attribute	**Description**

Name	TILLBRNCD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

USERACCCLASS

Attribute	Description
Name	USERACCCLASS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	6

USERGLREST

Attribute	Description
Name	USERGLREST
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NODEGL

Attribute	Description
Name	NODEGL
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	9

USERGLEXCEPT

Attribute	Description
Name	USERGLEXCEPT
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

EXCEPLEAFGL

Attribute	Description
Name	EXCEPLEAFGL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

USERLIMITSROLE

Attribute	Description
Name	USERLIMITSROLE
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

LMTBRN

Attribute	Description
Name	LMTBRN
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

LMTSROLE

Attribute	Description
Name	LMTSROLE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

QLMTCCY

Attribute	Description
Name	QLMTCCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

QINPLMT

Attribute	Description
Name	QINPLMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

QAUTHLMT

Attribute	Description
Name	QAUTHLMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

USERBRANCHES

Attribute	Description
Name	USERBRANCHES
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRNSBRN

Attribute	Description
Name	BRNSBRN
Datatype	String

Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

USERPRODUCTS

Attribute	Description
Name	USERPRODUCTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PRDPRDCD

Attribute	Description
Name	PRDPRDCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

USERACCESSPRODUCTS

Attribute	Description
Name	USERACCESSPRODUCTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PRDACCESSPRDCD

Attribute	Description
Name	PRDACCESSPRDCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

USERFUNCDISALLOW

Attribute	Description
Name	USERFUNCDISALLOW
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FUNCDISALLOWFUNCID

Attribute	Description
Name	FUNCDISALLOWFUNCID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

USERROLE

Attribute	Description
Name	USERROLE
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ROLEBRNCD

Attribute	Description
Name	ROLEBRNCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

USRROLEID

Attribute	Description
Name	USRROLEID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

MASTERROLEDESC

Attribute	Description
Name	MASTERROLEDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>45</td></tr></table>

USERSFUNCTIONS

Attribute	Description
Name	USERSFUNCTIONS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

USERFUNCBRNCD

Attribute	Description
Name	USERFUNCBRNCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

USERFUNCFUNCID

Attribute	Description
Name	USERFUNCFUNCID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 8

CONTROL1

Attribute	Description
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL2

Attribute	Description
Name	CONTROL2
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL3

Attribute	Description
Name	CONTROL3
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL4

Attribute	**Description**
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL5

Attribute	**Description**
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL6

Attribute	**Description**
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL7

Attribute	**Description**
Name	CONTROL7
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL8

Attribute	**Description**
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL9

Attribute	**Description**
Name	CONTROL9
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

USERFUNCSCTRL10

Attribute	**Description**
Name	USERFUNCSCTRL10
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL11

Attribute	**Description**
Name	CONTROL11
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL12

Attribute	**Description**
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL13

Attribute	**Description**
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL14

Attribute	**Description**
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL15

Attribute	**Description**
Name	CONTROL15
Datatype	Decimal
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

Grp-Restriction

Attribute	Description
Name	Grp-Restriction
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

GROUP_CODE

Attribute	Description
Name	GROUP_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>40</td></tr></table>

GROUP_DESC

Attribute	Description
Name	GROUP_DESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	255

Centralisation

Attribute	Description
Name	Centralisation
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

USRROLEID

Attribute	Description
Name	USRROLEID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	15

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

Dshmst

Attribute	Description
Name	Dshmst
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 15

USRNAME

Attribute	**Description**
Name	USRNAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

Dshdet

Attribute	**Description**
Name	Dshdet
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

DESCRIPTION

Attribute	**Description**
Name	DESCRIPTION
Datatype	String
Description	

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1000

SEQUENCE_NO

Attribute	Description
Name	SEQUENCE_NO
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	22

DBWHERECLAUSE

Attribute	Description
Name	DBWHERECLAUSE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	4000

SHOW_IN_DASHBOARD

Attribute	Description
Name	SHOW_IN_DASHBOARD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

Where-Master

Attribute	Description
Name	Where-Master
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

COLUMN_NAME

Attribute	Description

Name	COLUMN_NAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

WHERE_CL

Attribute	**Description**
Name	WHERE_CL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 500

CONDITION

Attribute	**Description**
Name	CONDITION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	Indicates Field Name

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.6.2.SM-CloseUserMaint-Req-IO-MSG.xsd

CLOSEUSERMAINT_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

USR-IO

USRID

MAKER

MAKERSTAMP

MODNO

CLOSEUSERMAINT_IOPK_REQ

Attribute	Description
Name	CLOSEUSERMAINT_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH

Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String

Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

USR-IO

Attribute	Description
Name	USR-IO
Datatype	
Description	

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

2.6.3.SM-CloseUserMaint-Res-Full-MSG.xsd

CLOSEUSERMAINT_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

USR-Full

STRTDATE

USRNAME

USRPWD

ENDDT

USRLANG

HOMEBRN

CUSTNO

LDAPUSR

TIMELEVEL

AUTOAUTH

USRSTAT

USRID

EXTUSRREF

USRCATEG

TILLALLOW

ACCCLSALLOW

GLALLOW

USRTXNLMT

LMTSCCY

MAXTXNAMT

MAXAUTHAMT

BRNSALLOW

PRDSALLOW

PRDSACCESALLOW

TAX_IDENTIFIER

AMOUNT_FORMAT

DATE_FORMAT

STAFFACCRESTR

DEPT_CODE

DEPT_DESC

USRML

ELCMUSER

GROUP_CODE

MULTIBRN_ACCESS

OTH_RM_CUST_ACC_ALLOW

SUPERVISOR_ID

SUPERVISOR_NAME

DASHBOARD_REQD

ALERTS_ON_HOME

REFERENCE_NO

NO_CUMULATIVE_LOGINS

NO_SUCCESSIVE_LOGINS

SCREENSAVERTIMEOUTINSECONDS

MFI_USER

F10_REQD

F11_REQD

F12_REQD

ACCESS_CONTROL

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

RESTR_PWD

- *PWD*

MSGSRIGHTS

- *GEN*
- *HLD*
- *CNL*
- *TSTINP*
- *CHGNODE*
- *CHGADDR*
- *REL*
- *REINS*
- *CHGMEDIA*
- *CHGPRIOR*
- *BRNMOV*
- *PRNT*
- *TSTCHK*
- *HLDAUTH*
- *CNLAUTH*

TSTINPAUTH

CHGNODEAUTH

CHGADDRAUTH

RELAUTH

REINSAUTH

CHGMEDIAAUTH

BRNMOVAUTH

CHGPRIORAUTH

FTUPL

LNKCONT

MOVQ

CHGBRNIN

CHGADDRIN

AUTHRGHTS

CHGMSG

CHGMSGAUTH

CHGFORCCOVMATCH

CHANGE_FORCE_RELEASE_FUND

SUPPRESS

DELMSG

QUEUERIGHTS

QUEUE

USERTILLS

TILLID

TILLBRNCD

USERACCCLASS

ACCCLS

USERGLREST

NODEGL

USERGLEXCEPT

EXCEPLEAFGL

USERLIMITSROLE

LMTBRN

LMTSROLE

QLMTCCY

QINPLMT

QAUTHLMT

USERBRANCHES

BRNSBRN

BRNNAME

USERPRODUCTS

PRDPRDCD

PRDDESC

USERACCESSPRODUCTS

PRDACCESSPRDCD

PRDDESC

USERFUNCDISALLOW

FUNCDISALLOWFUNCID

USERROLE

ROLEBRNCD

USRROLEID

MASTERROLEDESC

USERSFUNCTIONS

USERFUNCBRNCD

USERFUNCFUNCID

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

USERFUNCSCTRL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

CONTROL15

CONTROL16

Grp-Restriction

GROUP_CODE

GROUP_DESC

Centralisation

USRROLEID

ROLDESC

Dshmst

USRID

USRNAME

Dshdet

FUNCTIONID

DESCRIPTION

SEQUENCE_NO

DBWHERECLAUSE

SHOW_IN_DASHBOARD

Where-Master

COLUMN_NAME

WHERE_CL

CONDITION

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CLOSEUSERMAINT_FSFS_RES

Attribute	Description
Name	CLOSEUSERMAINT_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

USR-Full

Attribute	Description
Name	USR-Full
Datatype	
Description	

STRTDATE

Attribute	Description
Name	STRTDATE
Datatype	String
Description	

USRNAME

Attribute	Description

Name	USRNAME
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 35

USRPWD

Attribute	**Description**
Name	USRPWD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

ENDDT

Attribute	**Description**
Name	ENDDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

USRLANG

Attribute	**Description**
Name	USRLANG
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

HOMEBRN

Attribute	**Description**
Name	HOMEBRN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

CUSTNO

Attribute	**Description**
Name	CUSTNO

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

LDAPUSR

Attribute	**Description**
Name	LDAPUSR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 500

TIMELEVEL

Attribute	**Description**
Name	TIMELEVEL
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 9

AUTOAUTH

Attribute	**Description**
Name	AUTOAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

USRSTAT

Attribute	**Description**
Name	USRSTAT
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,H,D,L

USRID

Attribute	**Description**
Name	USRID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12

EXTUSRREF

Attribute	**Description**
Name	EXTUSRREF
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

USRCATEG

Attribute	**Description**
Name	USRCATEG
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,B

TILLALLOW

Attribute	**Description**
Name	TILLALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	A,D

ACCCLSALLOW

Attribute	Description
Name	ACCCLSALLOW
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	A,D

GLALLOW

Attribute	Description
Name	GLALLOW
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	A,D

USRTXNLMT

Attribute	Description
Name	USRTXNLMT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	U,R,N

LMTSCCY

Attribute	Description
Name	LMTSCCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: maxLength / 3

MAXTXNAMT

Attribute	Description
Name	MAXTXNAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

MAXAUTHAMT

Attribute	Description
Name	MAXAUTHAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

BRNSALLOW

Attribute	Description
Name	BRNSALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

PRDSALLOW

Attribute	Description
Name	PRDSALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,D

PRDSACCESALLOW

Attribute	**Description**
Name	PRDSACCESALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TAX_IDENTIFIER

Attribute	**Description**
Name	TAX_IDENTIFIER
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

AMOUNT_FORMAT

Attribute	**Description**
Name	AMOUNT_FORMAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / .,,,.,,

DATE_FORMAT

Attribute	**Description**
Name	DATE_FORMAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	M/d/yyyy

STAFFACCRESTR

Attribute	Description
Name	STAFFACCRESTR
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

DEPT_CODE

Attribute	Description
Name	DEPT_CODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

DEPT_DESC

Attribute	Description
Name	DEPT_DESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	50

USRML

Attribute	Description
Name	USRML
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 50

ELCMUSER

Attribute	**Description**
Name	ELCMUSER
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

GROUP_CODE

Attribute	**Description**
Name	GROUP_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

MULTIBRN_ACCESS

Attribute	**Description**
Name	MULTIBRN_ACCESS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

OTH_RM_CUST_ACC_ALLOW

Attribute	**Description**
Name	OTH_RM_CUST_ACC_ALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	Y,N

SUPERVISOR_ID

Attribute	Description
Name	SUPERVISOR_ID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	80

SUPERVISOR_NAME

Attribute	Description
Name	SUPERVISOR_NAME
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

DASHBOARD_REQD

Attribute	Description
Name	DASHBOARD_REQD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

ALERTS_ON_HOME

Attribute	Description
Name	ALERTS_ON_HOME
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: enumeration / Y,N

REFERENCE_NO

Attribute	**Description**
Name	REFERENCE_NO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

NO_CUMULATIVE_LOGINS

Attribute	**Description**
Name	NO_CUMULATIVE_LOGINS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

NO_SUCCESSIVE_LOGINS

Attribute	**Description**
Name	NO_SUCCESSIVE_LOGINS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

SCREENSAVERTIMEOUTINSECONDS

Attribute	**Description**
Name	SCREENSAVERTIMEOUTINSECONDS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description** totalDigits / 22

MFI_USER

Attribute	Description
Name	MFI_USER
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

F10_REQD

Attribute	Description
Name	F10_REQD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

F11_REQD

Attribute	Description
Name	F11_REQD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

F12_REQD

Attribute	Description
Name	F12_REQD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	
	Restrictions / **Description**: enumeration / Y,N

ACCESS_CONTROL

Attribute	**Description**
Name	ACCESS_CONTROL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,G,B

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	4

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

RESTR_PWD

Attribute	Description
Name	RESTR_PWD
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PWD

Attribute	Description
Name	PWD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12

MSGSRIGHTS

Attribute	Description
Name	MSGSRIGHTS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

HLD

Attribute	Description
Name	HLD
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CNL

Attribute	**Description**
Name	CNL
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TSTINP

Attribute	**Description**
Name	TSTINP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGNODE

Attribute	**Description**
Name	CHGNODE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGADDR

Attribute	**Description**
Name	CHGADDR
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / Y,N

REL

Attribute	**Description**
Name	REL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

REINS

Attribute	**Description**
Name	REINS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMEDIA

Attribute	**Description**
Name	CHGMEDIA
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGPRIOR

Attribute	**Description**
Name	CHGPRIOR
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

BRNMOV

Attribute	Description
Name	BRNMOV
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

PRNT

Attribute	Description
Name	PRNT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TSTCHK

Attribute	Description
Name	TSTCHK
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

HLDAUTH

Attribute	Description
Name	HLDAUTH
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

CNLAUTH

Attribute	**Description**
Name	CNLAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TSTINPAUTH

Attribute	**Description**
Name	TSTINPAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGNODEAUTH

Attribute	**Description**
Name	CHGNODEAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGADDRAUTH

Attribute	**Description**
Name	CHGADDRAUTH
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / Y,N

RELAUTH

Attribute	**Description**
Name	RELAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

REINSAUTH

Attribute	**Description**
Name	REINSAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMEDIAAUTH

Attribute	**Description**
Name	CHGMEDIAAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

BRNMOVAUTH

Attribute	**Description**
Name	BRNMOVAUTH
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

CHGPRIORAUTH

Attribute	**Description**
Name	CHGPRIORAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

FTUPL

Attribute	**Description**
Name	FTUPL
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

LNKCONT

Attribute	**Description**
Name	LNKCONT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

MOVQ

Attribute	**Description**
Name	MOVQ
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

CHGBRNIN

Attribute	**Description**
Name	CHGBRNIN
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGADDRIN

Attribute	**Description**
Name	CHGADDRIN
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

AUTHRGHTS

Attribute	**Description**
Name	AUTHRGHTS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGMSG

Attribute	**Description**
Name	CHGMSG
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMSGAUTH

Attribute	**Description**
Name	CHGMSGAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGFORCCOVMATCH

Attribute	**Description**
Name	CHGFORCCOVMATCH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHANGE_FORCE_RELEASE_FUND

Attribute	**Description**
Name	CHANGE_FORCE_RELEASE_FUND
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

SUPPRESS

Attribute	**Description**
Name	SUPPRESS
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

DELMSG

Attribute	**Description**
Name	DELMSG
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

QUEUERIGHTS

Attribute	**Description**
Name	QUEUERIGHTS
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

QUEUE

Attribute	**Description**
Name	QUEUE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 10

USERTILLS

Attribute	**Description**
Name	USERTILLS
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

TILLID

Attribute	Description
Name	TILLID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TILLBRNCD

Attribute	Description
Name	TILLBRNCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

USERACCCLASS

Attribute	Description
Name	USERACCCLASS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

USERGLREST

Attribute	Description
Name	USERGLREST
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NODEGL

Attribute	Description
Name	NODEGL
Datatype	String

Description	
Restrictions	

Restrictions	Description
maxLength	9

USERGLEXCEPT

Attribute	Description
Name	USERGLEXCEPT
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

EXCEPLEAFGL

Attribute	Description
Name	EXCEPLEAFGL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

USERLIMITSROLE

Attribute	Description
Name	USERLIMITSROLE
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

LMTBRN

Attribute	Description
Name	LMTBRN
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

LMTSROLE

Attribute	Description
Name	LMTSROLE

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

QLMTCCY

Attribute	Description
Name	QLMTCCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

QINPLMT

Attribute	Description
Name	QINPLMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

QAUTHLMT

Attribute	Description
Name	QAUTHLMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

USERBRANCHES

Attribute	Description
Name	USERBRANCHES

Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRNSBRN

Attribute	Description
Name	BRNSBRN
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

USERPRODUCTS

Attribute	Description
Name	USERPRODUCTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PRDPRDCD

Attribute	Description
Name	PRDPRDCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

PRDDESC

Attribute	Description

Name	PRDDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

USERACCESSPRODUCTS

Attribute	**Description**
Name	USERACCESSPRODUCTS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

PRDACCESSPRDCD

Attribute	**Description**
Name	PRDACCESSPRDCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

PRDDESC

Attribute	**Description**
Name	PRDDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

USERFUNCDISALLOW

Attribute	**Description**
Name	USERFUNCDISALLOW
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FUNCDISALLOWFUNCID

Attribute	Description
Name	FUNCDISALLOWFUNCID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 8

USERROLE

Attribute	Description
Name	USERROLE
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ROLEBRNCD

Attribute	Description
Name	ROLEBRNCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

USRROLEID

Attribute	Description
Name	USRROLEID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

MASTERROLEDESC

Attribute	Description
Name	MASTERROLEDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 45

USERSFUNCTIONS

Attribute	Description
Name	USERSFUNCTIONS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

USERFUNCBRNCD

Attribute	Description
Name	USERFUNCBRNCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

USERFUNCFUNCID

Attribute	Description
Name	USERFUNCFUNCID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

CONTROL1

Attribute	Description
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL2

Attribute	Description
Name	CONTROL2
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL3

Attribute	Description
Name	CONTROL3
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL4

Attribute	Description
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL5

Attribute	Description
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL6

Attribute	Description
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL8

Attribute	Description
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL9

Attribute	Description
Name	CONTROL9
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

USERFUNCSCTRL10

Attribute	Description
Name	USERFUNCSCTRL10
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL11

Attribute	Description
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL12

Attribute	Description
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL13

Attribute	Description
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL14

Attribute	Description
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL15

Attribute	Description
Name	CONTROL15
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

Grp-Restriction

Attribute	Description
Name	Grp-Restriction
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

GROUP_CODE

Attribute	Description
Name	GROUP_CODE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	40

GROUP_DESC

Attribute	Description

Name	GROUP_DESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

Centralisation

Attribute	**Description**
Name	Centralisation
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

USRROLEID

Attribute	**Description**
Name	USRROLEID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

ROLDESC

Attribute	**Description**
Name	ROLDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

Dshmst

Attribute	**Description**
Name	Dshmst
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

USRNAME

Attribute	Description
Name	USRNAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

Dshdet

Attribute	Description
Name	Dshdet
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

DESCRIPTION

Attribute	Description

Name	DESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

SEQUENCE_NO

Attribute	**Description**
Name	SEQUENCE_NO
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description**: totalDigits / 22

DBWHERECLAUSE

Attribute	**Description**
Name	DBWHERECLAUSE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4000

SHOW_IN_DASHBOARD

Attribute	**Description**
Name	SHOW_IN_DASHBOARD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

Where-Master

Attribute	**Description**
Name	Where-Master
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

COLUMN_NAME

Attribute	Description
Name	COLUMN_NAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

WHERE_CL

Attribute	Description
Name	WHERE_CL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>500</td></tr></table>

CONDITION

Attribute	Description
Name	CONDITION
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM

Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.6.4.SM-CloseUserMaint-Res-PK-MSG.xsd

CLOSEUSERMAINT_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

USR-PK

USRID

USR-IO

USRID

MAKER

MAKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CLOSEUSERMAINT_IOPK_RES

Attribute	Description
Name	CLOSEUSERMAINT_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

USR-PK

Attribute	Description
Name	USR-PK
Datatype	
Description	

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12

USR-IO

Attribute	Description
Name	USR-IO
Datatype	
Description	

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKER

Attribute	Description

Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.7.CreateSMDBANKP

2.7.1.SM-CreateSMDBANKP-Req-Full-MSG.xsd

CREATESMDBANKP_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Parameters-Full

HEAD_OFFICE

SITE_CODE

ACTIVATION_KEY

INVALID_LOGINS_CUM

INVALID_LOGINS_SUC

PWD_PREVENT_REUSE

PWD_CHANGE_AFTER

MAXIMUM

MINIMUM

PWD_EXPIRY_MSG_DAYS

ARCHIVAL_PERIOD

CONCHAR_PWD_NUM

FREQ_PWD_CHG

MIN_PWD_NUMERIC_LENGTH

LEGAL_NOTICE

DORMANCY_DAYS

DISPLAY_LEGAL_NOTICE

MIN_SPECIALCHAR_LENGTH

MIN_LOWERCASE_CHAR

MIN_UPPERCASE_CHAR

SCREENSAVERREQUIRED

SCREENSAVERTIMEOUTINSECONDS

SCREENSAVERMODIFIABLEBYUSER

PASSWORDEXTERNAL

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Smtbs-Branch-Restr

- *RESTR_TYPE*
- *DESCRIPTION*

Smtbs-Restrictive-Passwd

- *PASSWORD*

UDFDETAILS

- *FLDNAM*
- *FLDVAL*

Attribute	Description
Name	CREATESMDBANKP_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Parameters-Full

Attribute	Description
Name	Smtbs-Parameters-Full
Datatype	
Description	

HEAD_OFFICE

Attribute	Description
Name	HEAD_OFFICE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

SITE_CODE

Attribute	Description
Name	SITE_CODE
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	4

ACTIVATION_KEY

Attribute	Description
Name	ACTIVATION_KEY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	24

INVALID_LOGINS_CUM

Attribute	Description
Name	INVALID_LOGINS_CUM
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	6
maxInclusive	99

INVALID_LOGINS_SUC

Attribute	Description
Name	INVALID_LOGINS_SUC
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	1
minInclusive	3
maxInclusive	5

PWD_PREVENT_REUSE

Attribute	Description
Name	PWD_PREVENT_REUSE
Datatype	Decimal
Description	

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1

PWD_CHANGE_AFTER

Attribute	Description
Name	PWD_CHANGE_AFTER
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	3
minInclusive	15
maxInclusive	180

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	12
maxInclusive	30

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	6
maxInclusive	11

PWD_EXPIRY_MSG_DAYS

Attribute	Description
Name	PWD_EXPIRY_MSG_DAYS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1; maxInclusive / 5

ARCHIVAL_PERIOD

Attribute	Description
Name	ARCHIVAL_PERIOD
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

CONCHAR_PWD_NUM

Attribute	Description
Name	CONCHAR_PWD_NUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2

FREQ_PWD_CHG

Attribute	Description
Name	FREQ_PWD_CHG
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	0

MIN_PWD_NUMERIC_LENGTH

Attribute	Description
Name	MIN_PWD_NUMERIC_LENGTH
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1

LEGAL_NOTICE

Attribute	Description
Name	LEGAL_NOTICE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4000

DORMANCY_DAYS

Attribute	Description
Name	DORMANCY_DAYS
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1

DISPLAY_LEGAL_NOTICE

Attribute	Description
Name	DISPLAY_LEGAL_NOTICE
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

MIN_SPECIALCHAR_LENGTH

Attribute	Description
Name	MIN_SPECIALCHAR_LENGTH
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>1</td></tr></table>

MIN_LOWERCASE_CHAR

Attribute	Description
Name	MIN_LOWERCASE_CHAR
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>1</td></tr></table>

MIN_UPPERCASE_CHAR

Attribute	Description
Name	MIN_UPPERCASE_CHAR
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>1</td></tr></table>

SCREENSAVERREQUIRED

Attribute	Description

Name	SCREENSAVERREQUIRED
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

SCREENSAVERTIMEOUTINSECONDS

Attribute	**Description**
Name	SCREENSAVERTIMEOUTINSECONDS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

SCREENSAVERMODIFIABLEBYUSER

Attribute	**Description**
Name	SCREENSAVERMODIFIABLEBYUSER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

PASSWORDEXTERNAL

Attribute	**Description**
Name	PASSWORDEXTERNAL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

MAKER

Attribute	**Description**

Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	**Description**

Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

Smtbs-Branch-Restr

Attribute	**Description**
Name	Smtbs-Branch-Restr
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

RESTR_TYPE

Attribute	**Description**
Name	RESTR_TYPE
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 12

DESCRIPTION

Attribute	**Description**
Name	DESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

Smtbs-Restrictive-Passwd

Attribute	**Description**
Name	Smtbs-Restrictive-Passwd
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.7.2.SM-CreateSMDBANKP-Req-IO-MSG.xsd

CREATESMDBANKP_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Parameters-IO

HEAD_OFFICE

SITE_CODE

ACTIVATION_KEY

INVALID_LOGINS_CUM

INVALID_LOGINS_SUC

PWD_PREVENT_REUSE

PWD_CHANGE_AFTER

MAXIMUM

MINIMUM

PWD_EXPIRY_MSG_DAYS

ARCHIVAL_PERIOD

CONCHAR_PWD_NUM

FREQ_PWD_CHG

MIN_PWD_NUMERIC_LENGTH

LEGAL_NOTICE

DORMANCY_DAYS

DISPLAY_LEGAL_NOTICE

MIN_SPECIALCHAR_LENGTH

MIN_LOWERCASE_CHAR

MIN_UPPERCASE_CHAR

SCREENSAVERREQUIRED

SCREENSAVERTIMEOUTINSECONDS

SCREENSAVERMODIFIABLEBYUSER

Smtbs-Branch-Restr

RESTR_TYPE

DESCRIPTION

Smtbs-Restrictive-Passwd

PASSWORD

UDFDETAILS

FLDNAM

FLDVAL

CREATESMDBANKP_IOPK_REQ

Attribute	Description
Name	CREATESMDBANKP_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String

Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.

Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID

Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Parameters-IO

Attribute	Description
Name	Smtbs-Parameters-IO
Datatype	
Description	

HEAD_OFFICE

Attribute	Description

Name	HEAD_OFFICE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

SITE_CODE

Attribute	**Description**
Name	SITE_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

ACTIVATION_KEY

Attribute	**Description**
Name	ACTIVATION_KEY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 24

INVALID_LOGINS_CUM

Attribute	**Description**
Name	INVALID_LOGINS_CUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 6; maxInclusive / 99

INVALID_LOGINS_SUC

Attribute	**Description**
Name	INVALID_LOGINS_SUC
Datatype	Decimal

Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 1; minInclusive / 3; maxInclusive / 5

PWD_PREVENT_REUSE

Attribute	**Description**
Name	PWD_PREVENT_REUSE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

PWD_CHANGE_AFTER

Attribute	**Description**
Name	PWD_CHANGE_AFTER
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3; minInclusive / 15; maxInclusive / 180

MAXIMUM

Attribute	**Description**
Name	MAXIMUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 12; maxInclusive / 30

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 6; maxInclusive / 11

PWD_EXPIRY_MSG_DAYS

Attribute	Description
Name	PWD_EXPIRY_MSG_DAYS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1; maxInclusive / 5

ARCHIVAL_PERIOD

Attribute	Description
Name	ARCHIVAL_PERIOD
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

CONCHAR_PWD_NUM

Attribute	Description
Name	CONCHAR_PWD_NUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	2

FREQ_PWD_CHG

Attribute	Description
Name	FREQ_PWD_CHG
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	0

MIN_PWD_NUMERIC_LENGTH

Attribute	Description
Name	MIN_PWD_NUMERIC_LENGTH
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1

LEGAL_NOTICE

Attribute	Description
Name	LEGAL_NOTICE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4000

DORMANCY_DAYS

Attribute	Description
Name	DORMANCY_DAYS
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2 minInclusive / 1

DISPLAY_LEGAL_NOTICE

Attribute	**Description**
Name	DISPLAY_LEGAL_NOTICE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

MIN_SPECIALCHAR_LENGTH

Attribute	**Description**
Name	MIN_SPECIALCHAR_LENGTH
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2 minInclusive / 1

MIN_LOWERCASE_CHAR

Attribute	**Description**
Name	MIN_LOWERCASE_CHAR
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2 minInclusive / 1

MIN_UPPERCASE_CHAR

Attribute	**Description**

Name	MIN_UPPERCASE_CHAR
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

SCREENSAVERREQUIRED

Attribute	**Description**
Name	SCREENSAVERREQUIRED
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

SCREENSAVERTIMEOUTINSECONDS

Attribute	**Description**
Name	SCREENSAVERTIMEOUTINSECONDS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

SCREENSAVERMODIFIABLEBYUSER

Attribute	**Description**
Name	SCREENSAVERMODIFIABLEBYUSER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

Smtbs-Branch-Restr

Attribute	**Description**

Name	Smtbs-Branch-Restr
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

RESTR_TYPE

Attribute	Description
Name	RESTR_TYPE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255

Smtbs-Restrictive-Passwd

Attribute	Description
Name	Smtbs-Restrictive-Passwd
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	12

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	150
minLength	0

2.7.3.SM-CreateSMDBANKP-Res-Full-MSG.xsd

CREATESMDBANKP_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Parameters-Full

HEAD_OFFICE

SITE_CODE

ACTIVATION_KEY

INVALID_LOGINS_CUM

INVALID_LOGINS_SUC

PWD_PREVENT_REUSE

PWD_CHANGE_AFTER

MAXIMUM

MINIMUM

PWD_EXPIRY_MSG_DAYS

ARCHIVAL_PERIOD

CONCHAR_PWD_NUM

FREQ_PWD_CHG

MIN_PWD_NUMERIC_LENGTH

LEGAL_NOTICE

DORMANCY_DAYS

DISPLAY_LEGAL_NOTICE

MIN_SPECIALCHAR_LENGTH

MIN_LOWERCASE_CHAR

MIN_UPPERCASE_CHAR

SCREENSAVERREQUIRED

SCREENSAVERTIMEOUTINSECONDS

SCREENSAVERMODIFIABLEBYUSER

PASSWORDEXTERNAL

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Smtbs-Branch-Restr

RESTR_TYPE

DESCRIPTION

Smtbs-Restrictive-Passwd

PASSWORD

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATESMDBANKP_FSFS_RES

Attribute	Description
Name	CREATESMDBANKP_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description**: minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL

Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Parameters-Full

Attribute	Description
Name	Smtbs-Parameters-Full
Datatype	
Description	

HEAD_OFFICE

Attribute	Description
Name	HEAD_OFFICE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	3

SITE_CODE

Attribute	Description
Name	SITE_CODE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	4

ACTIVATION_KEY

Attribute	Description
Name	ACTIVATION_KEY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	24

INVALID_LOGINS_CUM

Attribute	Description
Name	INVALID_LOGINS_CUM
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	6
maxInclusive	99

INVALID_LOGINS_SUC

Attribute	Description
Name	INVALID_LOGINS_SUC
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	1
minInclusive	3
maxInclusive	5

PWD_PREVENT_REUSE

Attribute	Description
Name	PWD_PREVENT_REUSE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1

PWD_CHANGE_AFTER

Attribute	Description
Name	PWD_CHANGE_AFTER
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	3
minInclusive	15
maxInclusive	180

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	12
maxInclusive	30

MINIMUM

Attribute	Description

Name	MINIMUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 6; maxInclusive / 11

PWD_EXPIRY_MSG_DAYS

Attribute	**Description**
Name	PWD_EXPIRY_MSG_DAYS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1; maxInclusive / 5

ARCHIVAL_PERIOD

Attribute	**Description**
Name	ARCHIVAL_PERIOD
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

CONCHAR_PWD_NUM

Attribute	**Description**
Name	CONCHAR_PWD_NUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2

FREQ_PWD_CHG

Attribute	Description
Name	FREQ_PWD_CHG
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 0

MIN_PWD_NUMERIC_LENGTH

Attribute	Description
Name	MIN_PWD_NUMERIC_LENGTH
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

LEGAL_NOTICE

Attribute	Description
Name	LEGAL_NOTICE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

DORMANCY_DAYS

Attribute	Description
Name	DORMANCY_DAYS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1

DISPLAY_LEGAL_NOTICE

Attribute	Description
Name	DISPLAY_LEGAL_NOTICE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

MIN_SPECIALCHAR_LENGTH

Attribute	Description
Name	MIN_SPECIALCHAR_LENGTH
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1

MIN_LOWERCASE_CHAR

Attribute	Description
Name	MIN_LOWERCASE_CHAR
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1

MIN_UPPERCASE_CHAR

Attribute	Description
Name	MIN_UPPERCASE_CHAR
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2 minInclusive / 1

SCREENSAVERREQUIRED

Attribute	**Description**
Name	SCREENSAVERREQUIRED
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

SCREENSAVERTIMEOUTINSECONDS

Attribute	**Description**
Name	SCREENSAVERTIMEOUTINSECONDS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

SCREENSAVERMODIFIABLEBYUSER

Attribute	**Description**
Name	SCREENSAVERMODIFIABLEBYUSER
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

PASSWORDEXTERNAL

Attribute	**Description**
Name	PASSWORDEXTERNAL
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Smtbs-Branch-Restr

Attribute	Description
Name	Smtbs-Branch-Restr
Datatype	

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

RESTR_TYPE

Attribute	Description
Name	RESTR_TYPE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

Smtbs-Restrictive-Passwd

Attribute	Description
Name	Smtbs-Restrictive-Passwd
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.7.4.SM-CreateSMDBANKP-Res-PK-MSG.xsd

CREATESMDBANKP_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Parameters-PK

SITE_CODE

Smtbs-Parameters-IO

HEAD_OFFICE

SITE_CODE

ACTIVATION_KEY

INVALID_LOGINS_CUM

INVALID_LOGINS_SUC

PWD_PREVENT_REUSE

PWD_CHANGE_AFTER

MAXIMUM

MINIMUM

PWD_EXPIRY_MSG_DAYS

ARCHIVAL_PERIOD

CONCHAR_PWD_NUM

FREQ_PWD_CHG

MIN_PWD_NUMERIC_LENGTH

LEGAL_NOTICE

DORMANCY_DAYS

DISPLAY_LEGAL_NOTICE

MIN_SPECIALCHAR_LENGTH

MIN_LOWERCASE_CHAR

MIN_UPPERCASE_CHAR

SCREENSAVERREQUIRED

SCREENSAVERTIMEOUTINSECONDS

SCREENSAVERMODIFIABLEBYUSER

Smtbs-Branch-Restr

RESTR_TYPE

DESCRIPTION

Smtbs-Restrictive-Passwd

PASSWORD

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATESMDBANKP_IOPK_RES

Attribute	Description
Name	CREATESMDBANKP_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description**: minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL

Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Parameters-PK

Attribute	Description
Name	Smtbs-Parameters-PK
Datatype	
Description	

SITE_CODE

Attribute	Description
Name	SITE_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

Smtbs-Parameters-IO

Attribute	Description

Name	Smtbs-Parameters-IO
Datatype	
Description	

HEAD_OFFICE

Attribute	Description
Name	HEAD_OFFICE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

SITE_CODE

Attribute	Description
Name	SITE_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

ACTIVATION_KEY

Attribute	Description
Name	ACTIVATION_KEY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 24

INVALID_LOGINS_CUM

Attribute	Description
Name	INVALID_LOGINS_CUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 6; maxInclusive / 99

INVALID_LOGINS_SUC

Attribute	Description
Name	INVALID_LOGINS_SUC
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 1; minInclusive / 3; maxInclusive / 5

PWD_PREVENT_REUSE

Attribute	Description
Name	PWD_PREVENT_REUSE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

PWD_CHANGE_AFTER

Attribute	Description
Name	PWD_CHANGE_AFTER
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3; minInclusive / 15; maxInclusive / 180

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	12
maxInclusive	30

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	6
maxInclusive	11

PWD_EXPIRY_MSG_DAYS

Attribute	Description
Name	PWD_EXPIRY_MSG_DAYS
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1
maxInclusive	5

ARCHIVAL_PERIOD

Attribute	Description
Name	ARCHIVAL_PERIOD
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	3

CONCHAR_PWD_NUM

Attribute	Description
Name	CONCHAR_PWD_NUM

Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2

FREQ_PWD_CHG

Attribute	**Description**
Name	FREQ_PWD_CHG
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 0

MIN_PWD_NUMERIC_LENGTH

Attribute	**Description**
Name	MIN_PWD_NUMERIC_LENGTH
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

LEGAL_NOTICE

Attribute	**Description**
Name	LEGAL_NOTICE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

DORMANCY_DAYS

Attribute	**Description**

Name	DORMANCY_DAYS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

DISPLAY_LEGAL_NOTICE

Attribute	**Description**
Name	DISPLAY_LEGAL_NOTICE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

MIN_SPECIALCHAR_LENGTH

Attribute	**Description**
Name	MIN_SPECIALCHAR_LENGTH
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

MIN_LOWERCASE_CHAR

Attribute	**Description**
Name	MIN_LOWERCASE_CHAR
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

MIN_UPPERCASE_CHAR

Attribute	Description
Name	MIN_UPPERCASE_CHAR
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>1</td></tr></table>

SCREENSAVERREQUIRED

Attribute	Description
Name	SCREENSAVERREQUIRED
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

SCREENSAVERTIMEOUTINSECONDS

Attribute	Description
Name	SCREENSAVERTIMEOUTINSECONDS
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

SCREENSAVERMODIFIABLEBYUSER

Attribute	Description
Name	SCREENSAVERMODIFIABLEBYUSER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

Smtbs-Branch-Restr

Attribute	Description
Name	Smtbs-Branch-Restr
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

RESTR_TYPE

Attribute	Description
Name	RESTR_TYPE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

Smtbs-Restrictive-Passwd

Attribute	Description
Name	Smtbs-Restrictive-Passwd
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	12

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	150
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description

Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.8.CreateSMDRLMNE

2.8.1.SM-CreateSMDRLMNE-Req-Full-MSG.xsd

- *CREATESMDRLMNE_FSFS_REQ*
  - *FCUBS_HEADER*
    - *SOURCE*
    - *UBSCOMP*
    - *MSGID*
    - *CORRELID*
    - *USERID*
    - *BRANCH*
    - *MODULEID*
    - *SERVICE*
    - *OPERATION*
    - *SOURCE_OPERATION*
    - *SOURCE_USERID*
    - *DESTINATION*
    - *MULTITRIPID*
    - *FUNCTIONID*
    - *ACTION*
    - *MSGSTAT*
    - *PASSWORD*
    - *ADDL*
      - *PARAM*
        - *NAME*
        - *VALUE*
  - *FCUBS_BODY*
    - *Smtbs-Role-Limit-Full*
      - *ROLEID2*
      - *DESCRIPTION*
      - *LIMIT_CCY*
      - *INPUT_LIMIT*
      - *AUTHORIZATION_LIMIT*
      - *MAKER*
      - *MAKERSTAMP*

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

CREATESMDRLMNE_FSFS_REQ

Attribute	Description
Name	CREATESMDRLMNE_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Role-Limit-Full

Attribute	Description
Name	Smtbs-Role-Limit-Full
Datatype	
Description	

ROLEID2

Attribute	Description

Name	ROLEID2
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

DESCRIPTION

Attribute	**Description**
Name	DESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

LIMIT_CCY

Attribute	**Description**
Name	LIMIT_CCY
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

INPUT_LIMIT

Attribute	**Description**
Name	INPUT_LIMIT
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0

AUTHORIZATION_LIMIT

Attribute	**Description**
Name	AUTHORIZATION_LIMIT
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0

MAKER

Attribute	**Description**

Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	**Description**

Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	Indicates Field Name

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.8.2.SM-CreateSMDRLMNE-Req-IO-MSG.xsd

CREATESMDRLMNE_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Role-Limit-IO

ROLEID2

DESCRIPTION

LIMIT_CCY

INPUT_LIMIT

AUTHORIZATION_LIMIT

UDFDETAILS

FLDNAM

FLDVAL

CREATESMDRLMNE_IOPK_REQ

Attribute	Description
Name	CREATESMDRLMNE_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE

Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Role-Limit-IO

Attribute	**Description**

Name	Smtbs-Role-Limit-IO
Datatype	
Description	

ROLEID2

Attribute	Description
Name	ROLEID2
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

LIMIT_CCY

Attribute	Description
Name	LIMIT_CCY
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

INPUT_LIMIT

Attribute	Description
Name	INPUT_LIMIT
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0

AUTHORIZATION_LIMIT

Attribute	Description
Name	AUTHORIZATION_LIMIT
Datatype	Decimal
Description	

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	150
minLength	0

2.8.3.SM-CreateSMDRLMNE-Res-Full-MSG.xsd

CREATESMDRLMNE_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Role-Limit-Full

ROLEID2

DESCRIPTION

LIMIT_CCY

INPUT_LIMIT

AUTHORIZATION_LIMIT

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATESMDRLMNE_FSFS_RES

Attribute	Description
Name	CREATESMDRLMNE_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH

Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String

Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Role-Limit-Full

Attribute	**Description**
Name	Smtbs-Role-Limit-Full
Datatype	
Description	

ROLEID2

Attribute	Description
Name	ROLEID2
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

LIMIT_CCY

Attribute	Description
Name	LIMIT_CCY
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

INPUT_LIMIT

Attribute	Description
Name	INPUT_LIMIT
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0

AUTHORIZATION_LIMIT

Attribute	Description
Name	AUTHORIZATION_LIMIT
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM

Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attribute	**Attribute** / **Description** maxOccurs / unbounded

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.8.4.SM-CreateSMDRLMNE-Res-PK-MSG.xsd

CREATESMDRLMNE_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Role-Limit-PK

ROLEID2

Smtbs-Role-Limit-IO

ROLEID2

DESCRIPTION

LIMIT_CCY

INPUT_LIMIT

AUTHORIZATION_LIMIT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

Attribute	Description
Name	CREATESMDRLMNE_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Role-Limit-PK

Attribute	Description
Name	Smtbs-Role-Limit-PK
Datatype	
Description	

ROLEID2

Attribute	Description
Name	ROLEID2
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

Smtbs-Role-Limit-IO

Attribute	Description
Name	Smtbs-Role-Limit-IO
Datatype	
Description	

ROLEID2

Attribute	Description

Name	ROLEID2
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

DESCRIPTION

Attribute	**Description**
Name	DESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

LIMIT_CCY

Attribute	**Description**
Name	LIMIT_CCY
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

INPUT_LIMIT

Attribute	**Description**
Name	INPUT_LIMIT
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0

AUTHORIZATION_LIMIT

Attribute	**Description**
Name	AUTHORIZATION_LIMIT
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0

UDFDETAILS

Attribute	**Description**

Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions

Restrictions	Description
maxLength	150
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.9.CreateSMRole

2.9.1.SM-CreateSMRole-Req-Full-MSG.xsd

CREATESMROLE_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

ROLEMASTER-Full

ROLEIDENTIFICATION

MASTERROLEDESC

AUTHORISERROLE

BRANCH_RES

ACCCLASSALLOWED

CENTRALISATIONROLE

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

ROLEDETAIL

- *ROLEFUN*
- *CONTROL1*
- *CONTROL2*
- *CONTROL3*
- *CONTROL4*
- *CONTROL5*
- *CONTROL6*
- *CONTROL7*
- *CONTROL8*
- *CONTROL9*
- *CONTROL10*
- *CONTROL11*
- *CONTROL12*
- *CONTROL13*
- *CONTROL14*
- *CONTROL15*
- *CONTROL16*

ROLEDETAILB

- *ROLEFUN*
- *CONT1*
- *CONT2*
- *CONT3*
- *CONT4*
- *CONT5*
- *CONT6*
- *CONTROL7*
- *CONT8*
- *CONT9*
- *CONT10*

CONT11

CONT12

CONT13

CONT14

CONT15

CONTROL16

ROLEDETAILC

ROLEFUN

CNTRL1

CNTRL2

CNTRL3

CNTRL4

CNTRL5

CNTRL6

CNTRL7

CNTRL8

CNTRL9

CNTRL10

CNTRL11

CNTRL12

CNTRL13

CNTRL14

CNTRL15

CNTRL16

ROLEDETAILD

ROLEFUN

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

CONTROL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

CNTRL15

CNTRL16

ROLEBRANCHES

BRANCH

BRNNAME

ROLEACCCLASS

ACCCLS

DESCRIPTION

MSGCRIGHTS

CNL

CHGNODE

REL

CHGMEDIA

BRNMOV

HLD

TSTINP

CHGADDR

REINS

CHGPRIOR

CNLAUTH

CHGNODEAUTH

RELAUTH

CHGMEDIAAUTH

BRNMOVAUTH

HLDAUTH

TSTINPAUTH

CHGADDRAUTH

REINSAUTH

CHGPRIORAUTH

GEN

TSTCHK

LNKCONT

CHGBRNIN

CHGMSG

CHGFORCRELFUND

SUPPRESS

DELMSG

PRNT

FTUPL

MOVQ

CHGADDRIN

CHGMSGAUTH

AUTHRGHTS

CHGFORCCOVMATCH

QUEUERIGHTS

QUEUE

RESTRICTIVEPASSWD

PWD

PWDID

ROLEBRANCHLIMITS

LMTCCY

BRHUSERLMT

Roledetaile

ROLEFUN

BRANCHCODE

EDITABLE

CNTRLSTR

Roledetailf

ROLEID

ROLEFUN

CNTRLSTR

CNTRL1

CNTRL10

CNTRL11

CNTRL12

CNTRL13

CNTRL14

CNTRL15

CNTRL16

CNTRL2

CNTRL3

CNTRL4

CNTRL5

CNTRL6

CNTRL7

CNTRL8

CNTRL9

ATHSTAT

BRNCHCODE

UDFDETAILS

FLDNAM

FLDVAL

CREATESMROLE_FSFS_REQ

Attribute	Description
Name	CREATESMROLE_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description

Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

ROLEMASTER-Full

Attribute	Description
Name	ROLEMASTER-Full
Datatype	
Description	

ROLEIDENTIFICATION

Attribute	Description
Name	ROLEIDENTIFICATION
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

MASTERROLEDESC

Attribute	Description
Name	MASTERROLEDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

AUTHORISERROLE

Attribute	Description
Name	AUTHORISERROLE
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

BRANCH_RES

Attribute	**Description**
Name	BRANCH_RES
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

ACCCLASSALLOWED

Attribute	**Description**
Name	ACCCLASSALLOWED
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

CENTRALISATIONROLE

Attribute	**Description**
Name	CENTRALISATIONROLE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

ROLEDETAIL

Attribute	Description
Name	ROLEDETAIL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	8

CONTROL1

Attribute	Description
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL2

Attribute	Description
Name	CONTROL2
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL3

Attribute	Description
Name	CONTROL3
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL4

Attribute	Description
Name	CONTROL4

Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL5

Attribute	**Description**
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL6

Attribute	**Description**
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL7

Attribute	**Description**
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL8

Attribute	Description
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL9

Attribute	Description
Name	CONTROL9
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL10

Attribute	Description
Name	CONTROL10
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL11

Attribute	Description
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL12

Attribute	Description
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL13

Attribute	Description
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL14

Attribute	Description
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL15

Attribute	Description
Name	CONTROL15
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

ROLEDETAILB

Attribute	Description
Name	ROLEDETAILB
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	8

CONT1

Attribute	Description
Name	CONT1
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT2

Attribute	Description
Name	CONT2
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT3

Attribute	Description
Name	CONT3
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT4

Attribute	Description
Name	CONT4

Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONT5

Attribute	**Description**
Name	CONT5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONT6

Attribute	**Description**
Name	CONT6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL7

Attribute	**Description**
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT8

Attribute	Description
Name	CONT8
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT9

Attribute	Description
Name	CONT9
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT10

Attribute	Description
Name	CONT10
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT11

Attribute	Description
Name	CONT11
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONT12

Attribute	Description
Name	CONT12
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONT13

Attribute	Description
Name	CONT13
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONT14

Attribute	Description
Name	CONT14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT15

Attribute	Description
Name	CONT15
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

ROLEDETAILC

Attribute	Description
Name	ROLEDETAILC
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	8

CNTRL1

Attribute	Description
Name	CNTRL1
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL2

Attribute	Description
Name	CNTRL2
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL3

Attribute	Description
Name	CNTRL3
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL4

Attribute	Description
Name	CNTRL4

Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL5

Attribute	Description
Name	CNTRL5
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL6

Attribute	Description
Name	CNTRL6
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL7

Attribute	Description
Name	CNTRL7
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL8

Attribute	Description
Name	CNTRL8
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL9

Attribute	Description
Name	CNTRL9
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL10

Attribute	Description
Name	CNTRL10
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL11

Attribute	Description
Name	CNTRL11
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL12

Attribute	Description
Name	CNTRL12
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL13

Attribute	Description
Name	CNTRL13
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL14

Attribute	Description
Name	CNTRL14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL15

Attribute	Description
Name	CNTRL15
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL16

Attribute	Description
Name	CNTRL16
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

ROLEDETAILD

Attribute	Description
Name	ROLEDETAILD
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	8

CONTROL1

Attribute	Description
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL2

Attribute	Description
Name	CONTROL2
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL3

Attribute	Description
Name	CONTROL3
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL4

Attribute	Description
Name	CONTROL4

Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL5

Attribute	Description
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL6

Attribute	Description
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL8

Attribute	Description
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL9

Attribute	Description
Name	CONTROL9
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL10

Attribute	Description
Name	CONTROL10
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL11

Attribute	Description
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL12

Attribute	Description
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL13

Attribute	Description
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL14

Attribute	Description
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL15

Attribute	Description
Name	CNTRL15
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL16

Attribute	Description
Name	CNTRL16
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

ROLEBRANCHES

Attribute	Description
Name	ROLEBRANCHES
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	3

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

ROLEACCCLASS

Attribute	Description
Name	ROLEACCCLASS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	6

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

MSGCRIGHTS

Attribute	Description

Name	MSGCRIGHTS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

CNL

Attribute	**Description**
Name	CNL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGNODE

Attribute	**Description**
Name	CHGNODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

REL

Attribute	**Description**
Name	REL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMEDIA

Attribute	**Description**
Name	CHGMEDIA
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

BRNMOV

Attribute	Description
Name	BRNMOV
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

HLD

Attribute	Description
Name	HLD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TSTINP

Attribute	Description
Name	TSTINP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGADDR

Attribute	Description
Name	CHGADDR
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / Y,N

REINS

Attribute	**Description**
Name	REINS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGPRIOR

Attribute	**Description**
Name	CHGPRIOR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CNLAUTH

Attribute	**Description**
Name	CNLAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGNODEAUTH

Attribute	**Description**
Name	CHGNODEAUTH
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

RELAUTH

Attribute	Description
Name	RELAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGMEDIAAUTH

Attribute	Description
Name	CHGMEDIAAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

BRNMOVAUTH

Attribute	Description
Name	BRNMOVAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

HLDAUTH

Attribute	Description
Name	HLDAUTH
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

TSTINPAUTH

Attribute	**Description**
Name	TSTINPAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGADDRAUTH

Attribute	**Description**
Name	CHGADDRAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

REINSAUTH

Attribute	**Description**
Name	REINSAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGPRIORAUTH

Attribute	**Description**
Name	CHGPRIORAUTH
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / Y,N

GEN

Attribute	**Description**
Name	GEN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TSTCHK

Attribute	**Description**
Name	TSTCHK
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

LNKCONT

Attribute	**Description**
Name	LNKCONT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGBRNIN

Attribute	**Description**
Name	CHGBRNIN
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGMSG

Attribute	Description
Name	CHGMSG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGFORCRELFUND

Attribute	Description
Name	CHGFORCRELFUND
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

DELMSG

Attribute	Description
Name	DELMSG
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

PRNT

Attribute	**Description**
Name	PRNT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

FTUPL

Attribute	**Description**
Name	FTUPL
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

MOVQ

Attribute	**Description**
Name	MOVQ
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGADDRIN

Attribute	**Description**
Name	CHGADDRIN
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMSGAUTH

Attribute	**Description**
Name	CHGMSGAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

AUTHRGHTS

Attribute	**Description**
Name	AUTHRGHTS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGFORCCOVMATCH

Attribute	**Description**
Name	CHGFORCCOVMATCH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

QUEUERIGHTS

Attribute	**Description**
Name	QUEUERIGHTS
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

QUEUE

Attribute	Description
Name	QUEUE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	10

RESTRICTIVEPASSWD

Attribute	Description
Name	RESTRICTIVEPASSWD
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PWD

Attribute	Description
Name	PWD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12

PWDID

Attribute	Description
Name	PWDID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

ROLEBRANCHLIMITS

Attribute	Description
Name	ROLEBRANCHLIMITS
Datatype	

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

LMTCCY

Attribute	Description
Name	LMTCCY
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

BRHUSERLMT

Attribute	Description
Name	BRHUSERLMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

Roledetaile

Attribute	Description
Name	Roledetaile
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

EDITABLE

Attribute	Description
Name	EDITABLE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CNTRLSTR

Attribute	Description
Name	CNTRLSTR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

Roledetailf

Attribute	Description
Name	Roledetailf
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ROLEID

Attribute	Description
Name	ROLEID

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

CNTRLSTR

Attribute	Description
Name	CNTRLSTR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

CNTRL1

Attribute	Description
Name	CNTRL1
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL10

Attribute	Description

Name	CNTRL10
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL11

Attribute	**Description**
Name	CNTRL11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL12

Attribute	**Description**
Name	CNTRL12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL13

Attribute	**Description**
Name	CNTRL13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL14

Attribute	Description
Name	CNTRL14
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL15

Attribute	Description
Name	CNTRL15
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL16

Attribute	Description
Name	CNTRL16
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL2

Attribute	Description
Name	CNTRL2
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL3

Attribute	Description
Name	CNTRL3
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL4

Attribute	Description
Name	CNTRL4
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL5

Attribute	Description
Name	CNTRL5
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL6

Attribute	Description
Name	CNTRL6
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL7

Attribute	Description
Name	CNTRL7
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL8

Attribute	Description
Name	CNTRL8
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL9

Attribute	Description
Name	CNTRL9
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

ATHSTAT

Attribute	Description
Name	ATHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

BRNCHCODE

Attribute	Description
Name	BRNCHCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description

Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.9.2.SM-CreateSMRole-Req-IO-MSG.xsd

CREATESMROLE_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

ROLEMASTER-IO

ROLEIDENTIFICATION

MASTERROLEDESC

AUTHORISERROLE

BRANCH_RES

ACCCLASSALLOWED

CENTRALISATIONROLE

ROLEDETAIL

ROLEFUN

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

CONTROL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

CONTROL15

CONTROL16

ROLEDETAILB

ROLEFUN

CONT1

CONT2

CONT3

CONT4

CONT5

CONT6

CONTROL7

CONT8

CONT9

CONT10

CONT11

CONT12

CONT13

CONT14

CONT15

CONTROL16

ROLEDETAILC

ROLEFUN

CNTRL1

CNTRL2

CNTRL3

CNTRL4

CNTRL5

CNTRL6

CNTRL7

CNTRL8

CNTRL9

CNTRL10

CNTRL11

CNTRL12

CNTRL13

CNTRL14

CNTRL15

CNTRL16

ROLEDETAILD

ROLEFUN

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

CONTROL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

ROLEBRANCHES

BRANCH

ROLEACCCLASS

ACCCLS

MSGCRIGHTS

CNL

CHGNODE

REL

CHGMEDIA

BRNMOV

HLD

TSTINP

CHGADDR

REINS

CHGPRIOR

CNLAUTH

CHGNODEAUTH

RELAUTH

CHGMEDIAAUTH

BRNMOVAUTH

HLDAUTH

TSTINPAUTH

CHGADDRAUTH

REINSAUTH

CHGPRIORAUTH

GEN

TSTCHK

LNKCONT

CHGBRNIN

CHGMSG

CHGFORCRELFUND

SUPPRESS

DELMSG

PRNT

FTUPL

MOVQ

CHGADDRIN

CHGMSGAUTH

AUTHRGHTS

CHGFORCCOVMATCH

QUEUERIGHTS

QUEUE

RESTRICTIVEPASSWD

PWD

PWDID

ROLEBRANCHLIMITS

LMTCCY

BRHUSERLMT

Roledetaile

ROLEFUN

BRANCHCODE

EDITABLE

CNTRLSTR

Roledetailf

ROLEID

ROLEFUN

CNTRLSTR

CNTRL1

CNTRL10

CNTRL11

CNTRL12

CNTRL13

CNTRL14

CNTRL15

CNTRL16

CNTRL2

CNTRL3

CNTRL4

CNTRL5

CNTRL6

CNTRL7

CNTRL8

CNTRL9

ATHSTAT

BRNCHCODE

UDFDETAILS

FLDNAM

FLDVAL

CREATESMROLE_IOPK_REQ

Attribute	Description
Name	CREATESMROLE_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description**: minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL

Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

ROLEMASTER-IO

Attribute	Description
Name	ROLEMASTER-IO
Datatype	
Description	

ROLEIDENTIFICATION

Attribute	Description
Name	ROLEIDENTIFICATION
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

MASTERROLEDESC

Attribute	Description

Name	MASTERROLEDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

AUTHORISERROLE

Attribute	**Description**
Name	AUTHORISERROLE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

BRANCH_RES

Attribute	**Description**
Name	BRANCH_RES
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

ACCCLASSALLOWED

Attribute	**Description**
Name	ACCCLASSALLOWED
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

CENTRALISATIONROLE

Attribute	**Description**

Name	CENTRALISATIONROLE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

ROLEDETAIL

Attribute	**Description**
Name	ROLEDETAIL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ROLEFUN

Attribute	**Description**
Name	ROLEFUN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 8

CONTROL1

Attribute	**Description**
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL2

Attribute	**Description**
Name	CONTROL2
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL3

Attribute	**Description**
Name	CONTROL3
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL4

Attribute	**Description**
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL5

Attribute	**Description**
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL6

Attribute	Description
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL8

Attribute	Description
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL9

Attribute	Description
Name	CONTROL9
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL10

Attribute	**Description**
Name	CONTROL10
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL11

Attribute	**Description**
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL12

Attribute	**Description**
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL13

Attribute	Description
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL14

Attribute	Description
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL15

Attribute	Description
Name	CONTROL15
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

ROLEDETAILB

Attribute	Description
Name	ROLEDETAILB
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 8

CONT1

Attribute	Description
Name	CONT1
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT2

Attribute	Description
Name	CONT2
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT3

Attribute	**Description**
Name	CONT3
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT4

Attribute	**Description**
Name	CONT4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT5

Attribute	**Description**
Name	CONT5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT6

Attribute	Description
Name	CONT6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT8

Attribute	Description
Name	CONT8
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT9

Attribute	Description
Name	CONT9
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT10

Attribute	**Description**
Name	CONT10
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT11

Attribute	**Description**
Name	CONT11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT12

Attribute	**Description**
Name	CONT12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT13

Attribute	Description
Name	CONT13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT14

Attribute	Description
Name	CONT14
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT15

Attribute	Description
Name	CONT15
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	Decimal
Description	

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

ROLEDETAILC

Attribute	Description
Name	ROLEDETAILC
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	8

CNTRL1

Attribute	Description
Name	CNTRL1
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL2

Attribute	Description
Name	CNTRL2
Datatype	Decimal
Description	

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL3

Attribute	Description
Name	CNTRL3
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL4

Attribute	Description
Name	CNTRL4
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL5

Attribute	Description
Name	CNTRL5
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL6

Attribute	Description
Name	CNTRL6
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL7

Attribute	Description
Name	CNTRL7
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL8

Attribute	Description
Name	CNTRL8
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL9

Attribute	Description
Name	CNTRL9
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL10

Attribute	**Description**
Name	CNTRL10
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL11

Attribute	**Description**
Name	CNTRL11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL12

Attribute	**Description**
Name	CNTRL12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL13

Attribute	Description
Name	CNTRL13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL14

Attribute	Description
Name	CNTRL14
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL15

Attribute	Description
Name	CNTRL15
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL16

Attribute	Description
Name	CNTRL16
Datatype	Decimal
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

ROLEDETAILD

Attribute	Description
Name	ROLEDETAILD
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

CONTROL1

Attribute	Description
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL2

Attribute	Description
Name	CONTROL2
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL3

Attribute	**Description**
Name	CONTROL3
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL4

Attribute	**Description**
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL5

Attribute	**Description**
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL6

Attribute	Description
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL8

Attribute	Description
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL9

Attribute	Description
Name	CONTROL9
Datatype	Decimal
Description	

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL10

Attribute	Description
Name	CONTROL10
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL11

Attribute	Description
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL12

Attribute	Description
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL13

Attribute	Description
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL14

Attribute	Description
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

ROLEBRANCHES

Attribute	Description
Name	ROLEBRANCHES
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

ROLEACCCLASS

Attribute	Description

Name	ROLEACCCLASS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	6

MSGCRIGHTS

Attribute	Description
Name	MSGCRIGHTS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

CNL

Attribute	Description
Name	CNL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGNODE

Attribute	Description
Name	CHGNODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

REL

Attribute	Description
Name	REL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMEDIA

Attribute	Description
Name	CHGMEDIA
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

BRNMOV

Attribute	Description
Name	BRNMOV
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

HLD

Attribute	Description
Name	HLD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TSTINP

Attribute	Description
Name	TSTINP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGADDR

Attribute	Description
Name	CHGADDR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

REINS

Attribute	Description
Name	REINS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGPRIOR

Attribute	Description
Name	CHGPRIOR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CNLAUTH

Attribute	Description
Name	CNLAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGNODEAUTH

Attribute	Description
Name	CHGNODEAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

RELAUTH

Attribute	Description
Name	RELAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGMEDIAAUTH

Attribute	Description
Name	CHGMEDIAAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

BRNMOVAUTH

Attribute	Description
Name	BRNMOVAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

HLDAUTH

Attribute	Description
Name	HLDAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TSTINPAUTH

Attribute	Description
Name	TSTINPAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGADDRAUTH

Attribute	Description
Name	CHGADDRAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

REINSAUTH

Attribute	Description
Name	REINSAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGPRIORAUTH

Attribute	Description
Name	CHGPRIORAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TSTCHK

Attribute	Description
Name	TSTCHK
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

LNKCONT

Attribute	Description
Name	LNKCONT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGBRNIN

Attribute	Description
Name	CHGBRNIN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGMSG

Attribute	Description
Name	CHGMSG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGFORCRELFUND

Attribute	Description
Name	CHGFORCRELFUND
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

DELMSG

Attribute	Description
Name	DELMSG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

PRNT

Attribute	Description
Name	PRNT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

FTUPL

Attribute	Description
Name	FTUPL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

MOVQ

Attribute	Description
Name	MOVQ
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGADDRIN

Attribute	Description
Name	CHGADDRIN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGMSGAUTH

Attribute	Description
Name	CHGMSGAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

AUTHRGHTS

Attribute	Description
Name	AUTHRGHTS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGFORCCOVMATCH

Attribute	Description
Name	CHGFORCCOVMATCH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

QUEUERIGHTS

Attribute	Description
Name	QUEUERIGHTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

QUEUE

Attribute	Description
Name	QUEUE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

RESTRICTIVEPASSWD

Attribute	Description
Name	RESTRICTIVEPASSWD
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PWD

Attribute	Description
Name	PWD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

PWDID

Attribute	Description
Name	PWDID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

ROLEBRANCHLIMITS

Attribute	Description
Name	ROLEBRANCHLIMITS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

LMTCCY

Attribute	Description
Name	LMTCCY
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

BRHUSERLMT

Attribute	Description
Name	BRHUSERLMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

Roledetaile

Attribute	Description
Name	Roledetaile
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

EDITABLE

Attribute	Description
Name	EDITABLE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CNTRLSTR

Attribute	Description
Name	CNTRLSTR
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** maxLength / 16

Roledetailf

Attribute	**Description**
Name	Roledetailf
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

ROLEID

Attribute	**Description**
Name	ROLEID
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

ROLEFUN

Attribute	**Description**
Name	ROLEFUN
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

CNTRLSTR

Attribute	**Description**
Name	CNTRLSTR
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

CNTRL1

Attribute	**Description**
Name	CNTRL1
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL10

Attribute	**Description**
Name	CNTRL10
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL11

Attribute	**Description**
Name	CNTRL11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL12

Attribute	Description
Name	CNTRL12
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL13

Attribute	Description
Name	CNTRL13
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL14

Attribute	Description
Name	CNTRL14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL15

Attribute	Description
Name	CNTRL15
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL16

Attribute	Description
Name	CNTRL16
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL2

Attribute	Description
Name	CNTRL2
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL3

Attribute	Description
Name	CNTRL3
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL4

Attribute	Description
Name	CNTRL4
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL5

Attribute	Description
Name	CNTRL5
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL6

Attribute	Description
Name	CNTRL6
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL7

Attribute	Description
Name	CNTRL7
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL8

Attribute	Description
Name	CNTRL8
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL9

Attribute	Description
Name	CNTRL9
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

ATHSTAT

Attribute	Description
Name	ATHSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

BRNCHCODE

Attribute	Description
Name	BRNCHCODE

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.9.3.SM-CreateSMRole-Res-Full-MSG.xsd

CREATESMROLE_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

ROLEMASTER-Full

ROLEIDENTIFICATION

MASTERROLEDESC

AUTHORISERROLE

BRANCH_RES

ACCCLASSALLOWED

CENTRALISATIONROLE

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

ROLEDETAIL

ROLEFUN

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

CONTROL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

CONTROL15

CONTROL16

ROLEDETAILB

ROLEFUN

CONT1

CONT2

CONT3

CONT4

CONT5

CONT6

CONTROL7

CONT8

CONT9

CONT10

CONT11

CONT12

CONT13

CONT14

CONT15

CONTROL16

ROLEDETAILC

ROLEFUN

CNTRL1

CNTRL2

CNTRL3

CNTRL4

CNTRL5

CNTRL6

CNTRL7

CNTRL8

CNTRL9

CNTRL10

CNTRL11

CNTRL12

CNTRL13

CNTRL14

CNTRL15

CNTRL16

ROLEDETAILD

ROLEFUN

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

- *CONTROL8*
- *CONTROL9*
- *CONTROL10*
- *CONTROL11*
- *CONTROL12*
- *CONTROL13*
- *CONTROL14*
- *CNTRL15*
- *CNTRL16*

ROLEBRANCHES

- *BRANCH*
- *BRNNAME*

ROLEACCCLASS

- *ACCCLS*
- *DESCRIPTION*

MSGCRIGHTS

- *CNL*
- *CHGNODE*
- *REL*
- *CHGMEDIA*
- *BRNMOV*
- *HLD*
- *TSTINP*
- *CHGADDR*
- *REINS*
- *CHGPRIOR*
- *CNLAUTH*
- *CHGNODEAUTH*
- *RELAUTH*
- *CHGMEDIAAUTH*
- *BRNMOVAUTH*
- *HLDAUTH*

TSTINPAUTH

CHGADDRAUTH

REINSAUTH

CHGPRIORAUTH

GEN

TSTCHK

LNKCONT

CHGBRNIN

CHGMSG

CHGFORCRELFUND

SUPPRESS

DELMSG

PRNT

FTUPL

MOVQ

CHGADDRIN

CHGMSGAUTH

AUTHRGHTS

CHGFORCCOVMATCH

QUEUERIGHTS

QUEUE

RESTRICTIVEPASSWD

PWD

PWDID

ROLEBRANCHLIMITS

LMTCCY

BRHUSERLMT

Roledetaile

ROLEFUN

BRANCHCODE

EDITABLE

CNTRLSTR

Roledetailf

ROLEID

ROLEFUN

CNTRLSTR

CNTRL1

CNTRL10

CNTRL11

CNTRL12

CNTRL13

CNTRL14

CNTRL15

CNTRL16

CNTRL2

CNTRL3

CNTRL4

CNTRL5

CNTRL6

CNTRL7

CNTRL8

CNTRL9

ATHSTAT

BRNCHCODE

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATESMROLE_FSFS_RES

Attribute	Description
Name	CREATESMROLE_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description**: minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL

Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

ROLEMASTER-Full

Attribute	Description
Name	ROLEMASTER-Full
Datatype	
Description	

ROLEIDENTIFICATION

Attribute	Description
Name	ROLEIDENTIFICATION
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

MASTERROLEDESC

Attribute	Description

Name	MASTERROLEDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

AUTHORISERROLE

Attribute	**Description**
Name	AUTHORISERROLE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

BRANCH_RES

Attribute	**Description**
Name	BRANCH_RES
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

ACCCLASSALLOWED

Attribute	**Description**
Name	ACCCLASSALLOWED
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

CENTRALISATIONROLE

Attribute	**Description**

Name	CENTRALISATIONROLE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	**Description**

Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

ROLEDETAIL

Attribute	**Description**

Name	ROLEDETAIL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	8

CONTROL1

Attribute	Description
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL2

Attribute	Description
Name	CONTROL2
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL3

Attribute	Description
Name	CONTROL3
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL4

Attribute	**Description**
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL5

Attribute	**Description**
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL6

Attribute	**Description**
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL8

Attribute	Description
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL9

Attribute	Description
Name	CONTROL9
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL10

Attribute	Description
Name	CONTROL10
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL11

Attribute	**Description**
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL12

Attribute	**Description**
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL13

Attribute	**Description**
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL14

Attribute	Description
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL15

Attribute	Description
Name	CONTROL15
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

ROLEDETAILB

Attribute	Description
Name	ROLEDETAILB
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	8

CONT1

Attribute	Description
Name	CONT1
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT2

Attribute	Description
Name	CONT2
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT3

Attribute	Description
Name	CONT3
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT4

Attribute	**Description**
Name	CONT4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT5

Attribute	**Description**
Name	CONT5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT6

Attribute	**Description**
Name	CONT6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONT8

Attribute	Description
Name	CONT8
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONT9

Attribute	Description
Name	CONT9
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONT10

Attribute	Description
Name	CONT10
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT11

Attribute	**Description**
Name	CONT11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT12

Attribute	**Description**
Name	CONT12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT13

Attribute	**Description**
Name	CONT13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT14

Attribute	Description
Name	CONT14
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONT15

Attribute	Description
Name	CONT15
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

ROLEDETAILC

Attribute	Description
Name	ROLEDETAILC
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	8

CNTRL1

Attribute	Description
Name	CNTRL1
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL2

Attribute	Description
Name	CNTRL2
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL3

Attribute	Description
Name	CNTRL3
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL4

Attribute	**Description**
Name	CNTRL4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL5

Attribute	**Description**
Name	CNTRL5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL6

Attribute	**Description**
Name	CNTRL6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL7

Attribute	Description
Name	CNTRL7
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL8

Attribute	Description
Name	CNTRL8
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL9

Attribute	Description
Name	CNTRL9
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL10

Attribute	Description
Name	CNTRL10
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL11

Attribute	**Description**
Name	CNTRL11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL12

Attribute	**Description**
Name	CNTRL12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL13

Attribute	**Description**
Name	CNTRL13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL14

Attribute	Description
Name	CNTRL14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL15

Attribute	Description
Name	CNTRL15
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL16

Attribute	Description
Name	CNTRL16
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

ROLEDETAILD

Attribute	Description
Name	ROLEDETAILD
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	8

CONTROL1

Attribute	Description
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL2

Attribute	Description
Name	CONTROL2
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL3

Attribute	Description
Name	CONTROL3
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL4

Attribute	**Description**
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL5

Attribute	**Description**
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL6

Attribute	**Description**
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL8

Attribute	Description
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL9

Attribute	Description
Name	CONTROL9
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL10

Attribute	Description
Name	CONTROL10
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL11

Attribute	**Description**
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL12

Attribute	**Description**
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL13

Attribute	**Description**
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL14

Attribute	Description
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL15

Attribute	Description
Name	CNTRL15
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL16

Attribute	Description
Name	CNTRL16
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

ROLEBRANCHES

Attribute	Description
Name	ROLEBRANCHES
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

ROLEACCCLASS

Attribute	Description
Name	ROLEACCCLASS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	6

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

MSGCRIGHTS

Attribute	Description
Name	MSGCRIGHTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

CNL

Attribute	Description
Name	CNL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGNODE

Attribute	Description
Name	CHGNODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

REL

Attribute	Description
Name	REL
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

CHGMEDIA

Attribute	**Description**
Name	CHGMEDIA
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

BRNMOV

Attribute	**Description**
Name	BRNMOV
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

HLD

Attribute	**Description**
Name	HLD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TSTINP

Attribute	**Description**
Name	TSTINP
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGADDR

Attribute	**Description**
Name	CHGADDR
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

REINS

Attribute	**Description**
Name	REINS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGPRIOR

Attribute	**Description**
Name	CHGPRIOR
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CNLAUTH

Attribute	**Description**
Name	CNLAUTH
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / Y,N

CHGNODEAUTH

Attribute	**Description**
Name	CHGNODEAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

RELAUTH

Attribute	**Description**
Name	RELAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMEDIAAUTH

Attribute	**Description**
Name	CHGMEDIAAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

BRNMOVAUTH

Attribute	**Description**
Name	BRNMOVAUTH
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / Y,N

HLDAUTH

Attribute	**Description**
Name	HLDAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TSTINPAUTH

Attribute	**Description**
Name	TSTINPAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGADDRAUTH

Attribute	**Description**
Name	CHGADDRAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

REINSAUTH

Attribute	**Description**
Name	REINSAUTH
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGPRIORAUTH

Attribute	Description
Name	CHGPRIORAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TSTCHK

Attribute	Description
Name	TSTCHK
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

LNKCONT

Attribute	Description
Name	LNKCONT
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / Y,N

CHGBRNIN

Attribute	**Description**
Name	CHGBRNIN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMSG

Attribute	**Description**
Name	CHGMSG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGFORCRELFUND

Attribute	**Description**
Name	CHGFORCRELFUND
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

SUPPRESS

Attribute	**Description**
Name	SUPPRESS
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / Y,N

DELMSG

Attribute	**Description**
Name	DELMSG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

PRNT

Attribute	**Description**
Name	PRNT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

FTUPL

Attribute	**Description**
Name	FTUPL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

MOVQ

Attribute	**Description**
Name	MOVQ
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGADDRIN

Attribute	**Description**
Name	CHGADDRIN
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGMSGAUTH

Attribute	**Description**
Name	CHGMSGAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

AUTHRGHTS

Attribute	**Description**
Name	AUTHRGHTS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGFORCCOVMATCH

Attribute	**Description**
Name	CHGFORCCOVMATCH
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

QUEUERIGHTS

Attribute	**Description**
Name	QUEUERIGHTS
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

QUEUE

Attribute	**Description**
Name	QUEUE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 10

RESTRICTIVEPASSWD

Attribute	**Description**
Name	RESTRICTIVEPASSWD
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

PWD

Attribute	**Description**
Name	PWD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12

PWDID

Attribute	**Description**
Name	PWDID
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

ROLEBRANCHLIMITS

Attribute	Description
Name	ROLEBRANCHLIMITS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

LMTCCY

Attribute	Description
Name	LMTCCY
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

BRHUSERLMT

Attribute	Description
Name	BRHUSERLMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

Roledetaile

Attribute	Description
Name	Roledetaile
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

EDITABLE

Attribute	Description
Name	EDITABLE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CNTRLSTR

Attribute	Description
Name	CNTRLSTR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

Roledetailf

Attribute	Description
Name	Roledetailf
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ROLEID

Attribute	Description
Name	ROLEID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

CNTRLSTR

Attribute	Description
Name	CNTRLSTR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

CNTRL1

Attribute	Description
Name	CNTRL1
Datatype	Decimal

Description	
Attribute	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: totalDigits = 22; minInclusive = 0; maxInclusive = 1

CNTRL10

Attribute	Description
Name	CNTRL10
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: totalDigits = 22; minInclusive = 0; maxInclusive = 1

CNTRL11

Attribute	Description
Name	CNTRL11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: totalDigits = 22; minInclusive = 0; maxInclusive = 1

CNTRL12

Attribute	Description
Name	CNTRL12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: totalDigits = 22; minInclusive = 0; maxInclusive = 1

CNTRL13

Attribute	Description
Name	CNTRL13
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL14

Attribute	Description
Name	CNTRL14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL15

Attribute	Description
Name	CNTRL15
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL16

Attribute	Description
Name	CNTRL16
Datatype	Decimal
Description	

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL2

Attribute	Description
Name	CNTRL2
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL3

Attribute	Description
Name	CNTRL3
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL4

Attribute	Description
Name	CNTRL4
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL5

Attribute	Description
Name	CNTRL5
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL6

Attribute	Description
Name	CNTRL6
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL7

Attribute	Description
Name	CNTRL7
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL8

Attribute	Description
Name	CNTRL8
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL9

Attribute	**Description**
Name	CNTRL9
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

ATHSTAT

Attribute	**Description**
Name	ATHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

BRNCHCODE

Attribute	**Description**
Name	BRNCHCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

UDFDETAILS

Attribute	**Description**

Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions

Restrictions	Description
maxLength	150
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.9.4.SM-CreateSMRole-Res-PK-MSG.xsd

CREATESMROLE_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

ROLEMASTER-PK

ROLEIDENTIFICATION

ROLEMASTER-IO

ROLEIDENTIFICATION

MASTERROLEDESC

AUTHORISERROLE

BRANCH_RES

ACCCLASSALLOWED

CENTRALISATIONROLE

ROLEDETAIL

ROLEFUN

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

CONTROL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

CONTROL15

CONTROL16

ROLEDETAILB

ROLEFUN

CONT1

CONT2

CONT3

CONT4

CONT5

CONT6

CONTROL7

CONT8

CONT9

CONT10

CONT11

CONT12

CONT13

CONT14

CONT15

CONTROL16

ROLEDETAILC

ROLEFUN

CNTRL1

CNTRL2

CNTRL3

CNTRL4

CNTRL5

CNTRL6

CNTRL7

CNTRL8

CNTRL9

CNTRL10

CNTRL11

CNTRL12

CNTRL13

CNTRL14

CNTRL15

CNTRL16

ROLEDETAILD

ROLEFUN

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

CONTROL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

ROLEBRANCHES

BRANCH

ROLEACCCLASS

ACCCLS

MSGCRIGHTS

CNL

CHGNODE

REL

CHGMEDIA

BRNMOV

HLD

TSTINP

CHGADDR

REINS

CHGPRIOR

CNLAUTH

CHGNODEAUTH

RELAUTH

CHGMEDIAAUTH

BRNMOVAUTH

HLDAUTH

TSTINPAUTH

CHGADDRAUTH

REINSAUTH

CHGPRIORAUTH

GEN

TSTCHK

LNKCONT

CHGBRNIN

CHGMSG

CHGFORCRELFUND

SUPPRESS

DELMSG

PRNT

FTUPL

MOVQ

CHGADDRIN

CHGMSGAUTH

AUTHRGHTS

CHGFORCCOVMATCH

QUEUERIGHTS

QUEUE

RESTRICTIVEPASSWD

PWD

PWDID

ROLEBRANCHLIMITS

LMTCCY

BRHUSERLMT

Roledetaile

ROLEFUN

BRANCHCODE

EDITABLE

CNTRLSTR

Roledetailf

ROLEID

ROLEFUN

CNTRLSTR

CNTRL1

CNTRL10

CNTRL11

CNTRL12

CNTRL13

CNTRL14

CNTRL15

CNTRL16

CNTRL2

CNTRL3

CNTRL4

CNTRL5

CNTRL6

CNTRL7

CNTRL8

CNTRL9

ATHSTAT

BRNCHCODE

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATESMROLE_IOPK_RES

Attribute	Description
Name	CREATESMROLE_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

ROLEMASTER-PK

Attribute	Description
Name	ROLEMASTER-PK
Datatype	
Description	

ROLEIDENTIFICATION

Attribute	Description
Name	ROLEIDENTIFICATION
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

ROLEMASTER-IO

Attribute	Description
Name	ROLEMASTER-IO
Datatype	
Description	

ROLEIDENTIFICATION

Attribute	Description
Name	ROLEIDENTIFICATION
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

MASTERROLEDESC

Attribute	Description

Name	MASTERROLEDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

AUTHORISERROLE

Attribute	**Description**
Name	AUTHORISERROLE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

BRANCH_RES

Attribute	**Description**
Name	BRANCH_RES
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

ACCCLASSALLOWED

Attribute	**Description**
Name	ACCCLASSALLOWED
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

CENTRALISATIONROLE

Attribute	**Description**

Name	CENTRALISATIONROLE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

ROLEDETAIL

Attribute	**Description**
Name	ROLEDETAIL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ROLEFUN

Attribute	**Description**
Name	ROLEFUN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 8

CONTROL1

Attribute	**Description**
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL2

Attribute	**Description**
Name	CONTROL2
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL3

Attribute	**Description**
Name	CONTROL3
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL4

Attribute	**Description**
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL5

Attribute	**Description**
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL6

Attribute	Description
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL8

Attribute	Description
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL9

Attribute	Description
Name	CONTROL9
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL10

Attribute	**Description**
Name	CONTROL10
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL11

Attribute	**Description**
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL12

Attribute	**Description**
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL13

Attribute	Description
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL14

Attribute	Description
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL15

Attribute	Description
Name	CONTROL15
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	Decimal
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

ROLEDETAILB

Attribute	Description
Name	ROLEDETAILB
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

CONT1

Attribute	Description
Name	CONT1
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONT2

Attribute	Description
Name	CONT2
Datatype	Decimal
Description	

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT3

Attribute	Description
Name	CONT3
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT4

Attribute	Description
Name	CONT4
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT5

Attribute	Description
Name	CONT5
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT6

Attribute	Description
Name	CONT6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT8

Attribute	Description
Name	CONT8
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT9

Attribute	Description
Name	CONT9
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT10

Attribute	**Description**
Name	CONT10
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT11

Attribute	**Description**
Name	CONT11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT12

Attribute	**Description**
Name	CONT12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT13

Attribute	Description
Name	CONT13
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONT14

Attribute	Description
Name	CONT14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONT15

Attribute	Description
Name	CONT15
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

ROLEDETAILC

Attribute	**Description**
Name	ROLEDETAILC
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ROLEFUN

Attribute	**Description**
Name	ROLEFUN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 8

CNTRL1

Attribute	**Description**
Name	CNTRL1
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL2

Attribute	**Description**
Name	CNTRL2
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL3

Attribute	**Description**
Name	CNTRL3
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL4

Attribute	**Description**
Name	CNTRL4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL5

Attribute	**Description**
Name	CNTRL5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL6

Attribute	Description
Name	CNTRL6
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL7

Attribute	Description
Name	CNTRL7
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL8

Attribute	Description
Name	CNTRL8
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL9

Attribute	Description
Name	CNTRL9
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL10

Attribute	**Description**
Name	CNTRL10
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL11

Attribute	**Description**
Name	CNTRL11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL12

Attribute	**Description**
Name	CNTRL12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL13

Attribute	Description
Name	CNTRL13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL14

Attribute	Description
Name	CNTRL14
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL15

Attribute	Description
Name	CNTRL15
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL16

Attribute	Description
Name	CNTRL16
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

ROLEDETAILD

Attribute	**Description**
Name	ROLEDETAILD
Datatype	
Description	
Attribute	
	Attribute / **Description** minOccurs / 0 maxOccurs / unbounded

ROLEFUN

Attribute	**Description**
Name	ROLEFUN
Datatype	String
Description	
Restrictions	
	Restrictions / **Description** maxLength / 8

CONTROL1

Attribute	**Description**
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL2

Attribute	**Description**
Name	CONTROL2
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL3

Attribute	**Description**
Name	CONTROL3
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL4

Attribute	**Description**
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL5

Attribute	**Description**
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL6

Attribute	Description
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: totalDigits = 22; minInclusive = 0; maxInclusive = 1

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: totalDigits = 22; minInclusive = 0; maxInclusive = 1

CONTROL8

Attribute	Description
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: totalDigits = 22; minInclusive = 0; maxInclusive = 1

CONTROL9

Attribute	Description
Name	CONTROL9
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL10

Attribute	**Description**
Name	CONTROL10
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL11

Attribute	**Description**
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL12

Attribute	**Description**
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL13

Attribute	Description
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL14

Attribute	Description
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

ROLEBRANCHES

Attribute	Description
Name	ROLEBRANCHES
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

ROLEACCCLASS

Attribute	Description

Name	ROLEACCCLASS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	6

MSGCRIGHTS

Attribute	Description
Name	MSGCRIGHTS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

CNL

Attribute	Description
Name	CNL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions

Restrictions	Description
enumeration	Y,N

CHGNODE

Attribute	Description
Name	CHGNODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions

Restrictions	Description
enumeration	Y,N

REL

Attribute	Description
Name	REL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMEDIA

Attribute	Description
Name	CHGMEDIA
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

BRNMOV

Attribute	Description
Name	BRNMOV
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

HLD

Attribute	Description
Name	HLD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TSTINP

Attribute	Description
Name	TSTINP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGADDR

Attribute	Description
Name	CHGADDR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

REINS

Attribute	Description
Name	REINS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGPRIOR

Attribute	Description
Name	CHGPRIOR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CNLAUTH

Attribute	Description
Name	CNLAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGNODEAUTH

Attribute	Description
Name	CHGNODEAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

RELAUTH

Attribute	Description
Name	RELAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMEDIAAUTH

Attribute	Description
Name	CHGMEDIAAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

BRNMOVAUTH

Attribute	Description
Name	BRNMOVAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

HLDAUTH

Attribute	Description
Name	HLDAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TSTINPAUTH

Attribute	Description
Name	TSTINPAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGADDRAUTH

Attribute	Description
Name	CHGADDRAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

REINSAUTH

Attribute	Description
Name	REINSAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGPRIORAUTH

Attribute	Description
Name	CHGPRIORAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TSTCHK

Attribute	Description
Name	TSTCHK
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

LNKCONT

Attribute	Description
Name	LNKCONT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGBRNIN

Attribute	Description
Name	CHGBRNIN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGMSG

Attribute	Description
Name	CHGMSG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGFORCRELFUND

Attribute	Description
Name	CHGFORCRELFUND
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

DELMSG

Attribute	Description
Name	DELMSG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

PRNT

Attribute	Description
Name	PRNT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

FTUPL

Attribute	Description
Name	FTUPL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

MOVQ

Attribute	Description
Name	MOVQ
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGADDRIN

Attribute	Description
Name	CHGADDRIN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGMSGAUTH

Attribute	Description
Name	CHGMSGAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

AUTHRGHTS

Attribute	Description
Name	AUTHRGHTS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGFORCCOVMATCH

Attribute	Description
Name	CHGFORCCOVMATCH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

QUEUERIGHTS

Attribute	Description
Name	QUEUERIGHTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

QUEUE

Attribute	Description
Name	QUEUE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

RESTRICTIVEPASSWD

Attribute	Description
Name	RESTRICTIVEPASSWD
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PWD

Attribute	Description
Name	PWD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

PWDID

Attribute	Description
Name	PWDID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

ROLEBRANCHLIMITS

Attribute	Description
Name	ROLEBRANCHLIMITS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

LMTCCY

Attribute	Description
Name	LMTCCY
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

BRHUSERLMT

Attribute	Description
Name	BRHUSERLMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

Roledetaile

Attribute	Description
Name	Roledetaile
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

EDITABLE

Attribute	Description
Name	EDITABLE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CNTRLSTR

Attribute	Description
Name	CNTRLSTR
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** maxLength / 16

Roledetailf

Attribute	**Description**
Name	Roledetailf
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

ROLEID

Attribute	**Description**
Name	ROLEID
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

ROLEFUN

Attribute	**Description**
Name	ROLEFUN
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

CNTRLSTR

Attribute	**Description**
Name	CNTRLSTR
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

CNTRL1

Attribute	**Description**
Name	CNTRL1
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL10

Attribute	**Description**
Name	CNTRL10
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL11

Attribute	**Description**
Name	CNTRL11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL12

Attribute	Description
Name	CNTRL12
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL13

Attribute	Description
Name	CNTRL13
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL14

Attribute	Description
Name	CNTRL14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL15

Attribute	Description
Name	CNTRL15
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL16

Attribute	Description
Name	CNTRL16
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL2

Attribute	Description
Name	CNTRL2
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL3

Attribute	Description
Name	CNTRL3
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL4

Attribute	Description
Name	CNTRL4
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL5

Attribute	Description
Name	CNTRL5
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL6

Attribute	Description
Name	CNTRL6
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL7

Attribute	Description
Name	CNTRL7
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL8

Attribute	Description
Name	CNTRL8
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL9

Attribute	Description
Name	CNTRL9
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

ATHSTAT

Attribute	Description
Name	ATHSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

BRNCHCODE

Attribute	Description
Name	BRNCHCODE

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.10.CreateUserMaint

2.10.1.SM-CreateUserMaint-Req-Full-MSG.xsd

CREATEUSERMAINT_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

USR-Full

STRTDATE

USRNAME

USRPWD

ENDDT

USRLANG

HOMEBRN

CUSTNO

LDAPUSR

TIMELEVEL

AUTOAUTH

USRSTAT

USRID

EXTUSRREF

USRCATEG

TILLALLOW

ACCCLSALLOW

GLALLOW

USRTXNLMT

LMTSCCY

MAXTXNAMT

MAXAUTHAMT

BRNSALLOW

PRDSALLOW

PRDSACCESALLOW

TAX_IDENTIFIER

AMOUNT_FORMAT

DATE_FORMAT

STAFFACCRESTR

DEPT_CODE

DEPT_DESC

USRML

ELCMUSER

GROUP_CODE

MULTIBRN_ACCESS

OTH_RM_CUST_ACC_ALLOW

SUPERVISOR_ID

SUPERVISOR_NAME

DASHBOARD_REQD

ALERTS_ON_HOME

REFERENCE_NO

NO_CUMULATIVE_LOGINS

NO_SUCCESSIVE_LOGINS

SCREENSAVERTIMEOUTINSECONDS

MFI_USER

F10_REQD

F11_REQD

F12_REQD

ACCESS_CONTROL

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

RESTR_PWD

- *PWD*

MSGSRIGHTS

- *GEN*
- *HLD*
- *CNL*
- *TSTINP*
- *CHGNODE*
- *CHGADDR*
- *REL*
- *REINS*

CHGMEDIA

CHGPRIOR

BRNMOV

PRNT

TSTCHK

HLDAUTH

CNLAUTH

TSTINPAUTH

CHGNODEAUTH

CHGADDRAUTH

RELAUTH

REINSAUTH

CHGMEDIAAUTH

BRNMOVAUTH

CHGPRIORAUTH

FTUPL

LNKCONT

MOVQ

CHGBRNIN

CHGADDRIN

AUTHRGHTS

CHGMSG

CHGMSGAUTH

CHGFORCCOVMATCH

CHANGE_FORCE_RELEASE_FUND

SUPPRESS

DELMSG

QUEUERIGHTS

QUEUE

USERTILLS

TILLID

TILLBRNCD

USERACCCLASS

ACCCLS

USERGLREST

NODEGL

USERGLEXCEPT

EXCEPLEAFGL

USERLIMITSROLE

LMTBRN

LMTSROLE

QLMTCCY

QINPLMT

QAUTHLMT

USERBRANCHES

BRNSBRN

BRNNAME

USERPRODUCTS

PRDPRDCD

PRDDESC

USERACCESSPRODUCTS

PRDACCESSPRDCD

PRDDESC

USERFUNCDISALLOW

FUNCDISALLOWFUNCID

USERROLE

ROLEBRNCD

USRROLEID

MASTERROLEDESC

USERSFUNCTIONS

USERFUNCBRNCD

USERFUNCFUNCID

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

USERFUNCSCTRL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

CONTROL15

CONTROL16

Grp-Restriction

GROUP_CODE

GROUP_DESC

Centralisation

USRROLEID

ROLDESC

Dshmst

USRID

USRNAME

Dshdet

FUNCTIONID

DESCRIPTION

SEQUENCE_NO

DBWHERECLAUSE

SHOW_IN_DASHBOARD

Where-Master

COLUMN_NAME

WHERE_CL

CONDITION

UDFDETAILS

FLDNAM

FLDVAL

CREATEUSERMAINT_FSFS_REQ

Attribute	Description
Name	CREATEUSERMAINT_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

USR-Full

Attribute	Description
Name	USR-Full
Datatype	
Description	

STRTDATE

Attribute	Description
Name	STRTDATE
Datatype	String
Description	

USRNAME

Attribute	Description

Name	USRNAME
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 35

USRPWD

Attribute	**Description**
Name	USRPWD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

ENDDT

Attribute	**Description**
Name	ENDDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

USRLANG

Attribute	**Description**
Name	USRLANG
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

HOMEBRN

Attribute	**Description**
Name	HOMEBRN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

CUSTNO

Attribute	**Description**
Name	CUSTNO

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

LDAPUSR

Attribute	Description
Name	LDAPUSR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>500</td></tr></table>

TIMELEVEL

Attribute	Description
Name	TIMELEVEL
Datatype	Decimal
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>9</td></tr></table>

AUTOAUTH

Attribute	Description
Name	AUTOAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

USRSTAT

Attribute	Description
Name	USRSTAT
Datatype	String
Description	

Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,H,D,L

USRID

Attribute	**Description**
Name	USRID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12

EXTUSRREF

Attribute	**Description**
Name	EXTUSRREF
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

USRCATEG

Attribute	**Description**
Name	USRCATEG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,B

TILLALLOW

Attribute	**Description**
Name	TILLALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	A,D

ACCCLSALLOW

Attribute	Description
Name	ACCCLSALLOW
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	A,D

GLALLOW

Attribute	Description
Name	GLALLOW
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	A,D

USRTXNLMT

Attribute	Description
Name	USRTXNLMT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	U,R,N

LMTSCCY

Attribute	Description
Name	LMTSCCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: maxLength / 3

MAXTXNAMT

Attribute	**Description**
Name	MAXTXNAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

MAXAUTHAMT

Attribute	**Description**
Name	MAXAUTHAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

BRNSALLOW

Attribute	**Description**
Name	BRNSALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

PRDSALLOW

Attribute	**Description**
Name	PRDSALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	A,D

PRDSACCESALLOW

Attribute	Description
Name	PRDSACCESALLOW
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	A,D

TAX_IDENTIFIER

Attribute	Description
Name	TAX_IDENTIFIER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	11

AMOUNT_FORMAT

Attribute	Description
Name	AMOUNT_FORMAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	.,,,.,,

DATE_FORMAT

Attribute	Description
Name	DATE_FORMAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: enumeration / M/d/yyyy

STAFFACCRESTR

Attribute	Description
Name	STAFFACCRESTR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

DEPT_CODE

Attribute	Description
Name	DEPT_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

DEPT_DESC

Attribute	Description
Name	DEPT_DESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

USRML

Attribute	Description
Name	USRML
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	50

ELCMUSER

Attribute	Description
Name	ELCMUSER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

GROUP_CODE

Attribute	Description
Name	GROUP_CODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	A,D

MULTIBRN_ACCESS

Attribute	Description
Name	MULTIBRN_ACCESS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

OTH_RM_CUST_ACC_ALLOW

Attribute	Description
Name	OTH_RM_CUST_ACC_ALLOW
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

SUPERVISOR_ID

Attribute	Description
Name	SUPERVISOR_ID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	80

SUPERVISOR_NAME

Attribute	Description
Name	SUPERVISOR_NAME
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

DASHBOARD_REQD

Attribute	Description
Name	DASHBOARD_REQD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

ALERTS_ON_HOME

Attribute	Description
Name	ALERTS_ON_HOME
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: enumeration / Y,N

REFERENCE_NO

Attribute	**Description**
Name	REFERENCE_NO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

NO_CUMULATIVE_LOGINS

Attribute	**Description**
Name	NO_CUMULATIVE_LOGINS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

NO_SUCCESSIVE_LOGINS

Attribute	**Description**
Name	NO_SUCCESSIVE_LOGINS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

SCREENSAVERTIMEOUTINSECONDS

Attribute	**Description**
Name	SCREENSAVERTIMEOUTINSECONDS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description** totalDigits / 22

MFI_USER

Attribute	Description
Name	MFI_USER
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

F10_REQD

Attribute	Description
Name	F10_REQD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

F11_REQD

Attribute	Description
Name	F11_REQD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

F12_REQD

Attribute	Description
Name	F12_REQD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	
	Restrictions / **Description**: enumeration / Y,N

ACCESS_CONTROL

Attribute	**Description**
Name	ACCESS_CONTROL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,G,B

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	1

RESTR_PWD

Attribute	Description
Name	RESTR_PWD
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PWD

Attribute	Description
Name	PWD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12

MSGSRIGHTS

Attribute	Description
Name	MSGSRIGHTS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

HLD

Attribute	Description
Name	HLD
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / Y,N

CNL

Attribute	**Description**
Name	CNL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TSTINP

Attribute	**Description**
Name	TSTINP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGNODE

Attribute	**Description**
Name	CHGNODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGADDR

Attribute	**Description**
Name	CHGADDR
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / Y,N

REL

Attribute	**Description**
Name	REL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

REINS

Attribute	**Description**
Name	REINS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMEDIA

Attribute	**Description**
Name	CHGMEDIA
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGPRIOR

Attribute	**Description**
Name	CHGPRIOR
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

BRNMOV

Attribute	**Description**
Name	BRNMOV
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

PRNT

Attribute	**Description**
Name	PRNT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TSTCHK

Attribute	**Description**
Name	TSTCHK
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

HLDAUTH

Attribute	**Description**
Name	HLDAUTH
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CNLAUTH

Attribute	**Description**
Name	CNLAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TSTINPAUTH

Attribute	**Description**
Name	TSTINPAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGNODEAUTH

Attribute	**Description**
Name	CHGNODEAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGADDRAUTH

Attribute	**Description**
Name	CHGADDRAUTH
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / Y,N

RELAUTH

Attribute	**Description**
Name	RELAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

REINSAUTH

Attribute	**Description**
Name	REINSAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMEDIAAUTH

Attribute	**Description**
Name	CHGMEDIAAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

BRNMOVAUTH

Attribute	**Description**
Name	BRNMOVAUTH
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGPRIORAUTH

Attribute	**Description**
Name	CHGPRIORAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

FTUPL

Attribute	**Description**
Name	FTUPL
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

LNKCONT

Attribute	**Description**
Name	LNKCONT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

MOVQ

Attribute	**Description**
Name	MOVQ
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGBRNIN

Attribute	**Description**
Name	CHGBRNIN
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGADDRIN

Attribute	**Description**
Name	CHGADDRIN
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

AUTHRGHTS

Attribute	**Description**
Name	AUTHRGHTS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGMSG

Attribute	**Description**
Name	CHGMSG
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMSGAUTH

Attribute	**Description**
Name	CHGMSGAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGFORCCOVMATCH

Attribute	**Description**
Name	CHGFORCCOVMATCH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHANGE_FORCE_RELEASE_FUND

Attribute	**Description**
Name	CHANGE_FORCE_RELEASE_FUND
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

SUPPRESS

Attribute	**Description**
Name	SUPPRESS
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

DELMSG

Attribute	**Description**
Name	DELMSG
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

QUEUERIGHTS

Attribute	**Description**
Name	QUEUERIGHTS
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

QUEUE

Attribute	**Description**
Name	QUEUE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 10

USERTILLS

Attribute	**Description**
Name	USERTILLS
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

TILLID

Attribute	Description
Name	TILLID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TILLBRNCD

Attribute	Description
Name	TILLBRNCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

USERACCCLASS

Attribute	Description
Name	USERACCCLASS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

USERGLREST

Attribute	Description
Name	USERGLREST
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NODEGL

Attribute	Description
Name	NODEGL
Datatype	String

Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

USERGLEXCEPT

Attribute	Description
Name	USERGLEXCEPT
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

EXCEPLEAFGL

Attribute	Description
Name	EXCEPLEAFGL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

USERLIMITSROLE

Attribute	Description
Name	USERLIMITSROLE
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

LMTBRN

Attribute	Description
Name	LMTBRN
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

LMTSROLE

Attribute	Description
Name	LMTSROLE

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

QLMTCCY

Attribute	Description
Name	QLMTCCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

QINPLMT

Attribute	Description
Name	QINPLMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

QAUTHLMT

Attribute	Description
Name	QAUTHLMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

USERBRANCHES

Attribute	Description
Name	USERBRANCHES

Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRNSBRN

Attribute	Description
Name	BRNSBRN
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

USERPRODUCTS

Attribute	Description
Name	USERPRODUCTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PRDPRDCD

Attribute	Description
Name	PRDPRDCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

PRDDESC

Attribute	Description

Name	PRDDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

USERACCESSPRODUCTS

Attribute	**Description**
Name	USERACCESSPRODUCTS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

PRDACCESSPRDCD

Attribute	**Description**
Name	PRDACCESSPRDCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

PRDDESC

Attribute	**Description**
Name	PRDDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

USERFUNCDISALLOW

Attribute	**Description**
Name	USERFUNCDISALLOW
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FUNCDISALLOWFUNCID

Attribute	Description
Name	FUNCDISALLOWFUNCID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 8

USERROLE

Attribute	Description
Name	USERROLE
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ROLEBRNCD

Attribute	Description
Name	ROLEBRNCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

USRROLEID

Attribute	Description
Name	USRROLEID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

MASTERROLEDESC

Attribute	Description
Name	MASTERROLEDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 45

USERSFUNCTIONS

Attribute	Description
Name	USERSFUNCTIONS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

USERFUNCBRNCD

Attribute	Description
Name	USERFUNCBRNCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

USERFUNCFUNCID

Attribute	Description
Name	USERFUNCFUNCID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

CONTROL1

Attribute	Description
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL2

Attribute	Description
Name	CONTROL2
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL3

Attribute	Description
Name	CONTROL3
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL4

Attribute	Description
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL5

Attribute	Description
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL6

Attribute	Description
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL8

Attribute	Description
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL9

Attribute	Description
Name	CONTROL9
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

USERFUNCSCTRL10

Attribute	Description
Name	USERFUNCSCTRL10
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL11

Attribute	Description
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL12

Attribute	Description
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL13

Attribute	Description
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL14

Attribute	Description
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL15

Attribute	Description
Name	CONTROL15
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

Grp-Restriction

Attribute	Description
Name	Grp-Restriction
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

GROUP_CODE

Attribute	Description
Name	GROUP_CODE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	40

GROUP_DESC

Attribute	Description

Name	GROUP_DESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

Centralisation

Attribute	**Description**
Name	Centralisation
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

USRROLEID

Attribute	**Description**
Name	USRROLEID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

ROLDESC

Attribute	**Description**
Name	ROLDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

Dshmst

Attribute	**Description**
Name	Dshmst
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

USRNAME

Attribute	Description
Name	USRNAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

Dshdet

Attribute	Description
Name	Dshdet
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

DESCRIPTION

Attribute	Description

Name	DESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

SEQUENCE_NO

Attribute	**Description**
Name	SEQUENCE_NO
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description**: totalDigits / 22

DBWHERECLAUSE

Attribute	**Description**
Name	DBWHERECLAUSE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4000

SHOW_IN_DASHBOARD

Attribute	**Description**
Name	SHOW_IN_DASHBOARD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

Where-Master

Attribute	**Description**
Name	Where-Master
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

COLUMN_NAME

Attribute	Description
Name	COLUMN_NAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

WHERE_CL

Attribute	Description
Name	WHERE_CL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>500</td></tr></table>

CONDITION

Attribute	Description
Name	CONDITION
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM

Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.10.2.SM-CreateUserMaint-Req-IO-MSG.xsd

CREATEUSERMAINT_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

USR-IO

STRTDATE

USRNAME

USRPWD

ENDDT

USRLANG

HOMEBRN

CUSTNO

LDAPUSR

TIMELEVEL

AUTOAUTH

USRSTAT

USRID

EXTUSRREF

USRCATEG

TILLALLOW

ACCCLSALLOW

GLALLOW

USRTXNLMT

LMTSCCY

MAXTXNAMT

MAXAUTHAMT

BRNSALLOW

PRDSALLOW

PRDSACCESALLOW

TAX_IDENTIFIER

AMOUNT_FORMAT

DATE_FORMAT

STAFFACCRESTR

DEPT_CODE

USRML

ELCMUSER

GROUP_CODE

MULTIBRN_ACCESS

OTH_RM_CUST_ACC_ALLOW

SUPERVISOR_ID

DASHBOARD_REQD

ALERTS_ON_HOME

NO_CUMULATIVE_LOGINS

NO_SUCCESSIVE_LOGINS

SCREENSAVERTIMEOUTINSECONDS

MFI_USER

F10_REQD

F11_REQD

F12_REQD

ACCESS_CONTROL

RESTR_PWD

- *PWD*

MSGSRIGHTS

- *GEN*
- *HLD*
- *CNL*
- *TSTINP*
- *CHGNODE*
- *CHGADDR*
- *REL*
- *REINS*
- *CHGMEDIA*
- *CHGPRIOR*

BRNMOV

PRNT

TSTCHK

HLDAUTH

CNLAUTH

TSTINPAUTH

CHGNODEAUTH

CHGADDRAUTH

RELAUTH

REINSAUTH

CHGMEDIAAUTH

BRNMOVAUTH

CHGPRIORAUTH

FTUPL

LNKCONT

MOVQ

CHGBRNIN

CHGADDRIN

AUTHRGHTS

CHGMSG

CHGMSGAUTH

CHGFORCCOVMATCH

CHANGE_FORCE_RELEASE_FUND

SUPPRESS

DELMSG

QUEUERIGHTS

QUEUE

USERTILLS

TILLID

TILLBRNCD

USERACCCLASS

ACCCLS

USERGLREST

NODEGL

USERGLEXCEPT

EXCEPLEAFGL

USERLIMITSROLE

LMTBRN

LMTSROLE

USERBRANCHES

BRNSBRN

USERPRODUCTS

PRDPRDCD

USERACCESSPRODUCTS

PRDACCESSPRDCD

USERFUNCDISALLOW

FUNCDISALLOWFUNCID

USERROLE

ROLEBRNCD

USRROLEID

USERSFUNCTIONS

USERFUNCBRNCD

USERFUNCFUNCID

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

USERFUNCSCTRL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

CONTROL15

CONTROL16

Grp-Restriction

GROUP_CODE

Centralisation

USRROLEID

Dshdet

SEQUENCE_NO

DBWHERECLAUSE

SHOW_IN_DASHBOARD

Where-Master

COLUMN_NAME

WHERE_CL

CONDITION

UDFDETAILS

FLDNAM

FLDVAL

CREATEUSERMAINT_IOPK_REQ

Attribute	Description
Name	CREATEUSERMAINT_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

USR-IO

Attribute	Description
Name	USR-IO
Datatype	
Description	

STRTDATE

Attribute	Description
Name	STRTDATE
Datatype	String
Description	

USRNAME

Attribute	Description
Name	USRNAME
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 35

USRPWD

Attribute	Description
Name	USRPWD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

ENDDT

Attribute	Description
Name	ENDDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

USRLANG

Attribute	Description
Name	USRLANG
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

HOMEBRN

Attribute	Description
Name	HOMEBRN
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

LDAPUSR

Attribute	Description
Name	LDAPUSR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	500

TIMELEVEL

Attribute	Description
Name	TIMELEVEL
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	9

AUTOAUTH

Attribute	Description
Name	AUTOAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

USRSTAT

Attribute	Description
Name	USRSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	E,H,D,L

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12

EXTUSRREF

Attribute	Description
Name	EXTUSRREF
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

USRCATEG

Attribute	Description
Name	USRCATEG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,B</td></tr></table>

TILLALLOW

Attribute	Description
Name	TILLALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

ACCCLSALLOW

Attribute	Description
Name	ACCCLSALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

GLALLOW

Attribute	Description
Name	GLALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

USRTXNLMT

Attribute	Description
Name	USRTXNLMT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>U,R,N</td></tr></table>

LMTSCCY

Attribute	Description
Name	LMTSCCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

MAXTXNAMT

Attribute	Description
Name	MAXTXNAMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

MAXAUTHAMT

Attribute	Description
Name	MAXAUTHAMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

BRNSALLOW

Attribute	Description
Name	BRNSALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

PRDSALLOW

Attribute	Description
Name	PRDSALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

PRDSACCESALLOW

Attribute	Description
Name	PRDSACCESALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

TAX_IDENTIFIER

Attribute	Description
Name	TAX_IDENTIFIER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

AMOUNT_FORMAT

Attribute	Description
Name	AMOUNT_FORMAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>.,,,.,,</td></tr></table>

DATE_FORMAT

Attribute	Description
Name	DATE_FORMAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M/d/yyyy</td></tr></table>

STAFFACCRESTR

Attribute	Description
Name	STAFFACCRESTR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

DEPT_CODE

Attribute	Description
Name	DEPT_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

USRML

Attribute	Description
Name	USRML
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

ELCMUSER

Attribute	Description
Name	ELCMUSER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

GROUP_CODE

Attribute	Description
Name	GROUP_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

MULTIBRN_ACCESS

Attribute	Description
Name	MULTIBRN_ACCESS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

OTH_RM_CUST_ACC_ALLOW

Attribute	Description
Name	OTH_RM_CUST_ACC_ALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

SUPERVISOR_ID

Attribute	Description
Name	SUPERVISOR_ID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>80</td></tr></table>

DASHBOARD_REQD

Attribute	Description
Name	DASHBOARD_REQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

ALERTS_ON_HOME

Attribute	Description
Name	ALERTS_ON_HOME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

NO_CUMULATIVE_LOGINS

Attribute	Description
Name	NO_CUMULATIVE_LOGINS
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

NO_SUCCESSIVE_LOGINS

Attribute	Description
Name	NO_SUCCESSIVE_LOGINS
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

SCREENSAVERTIMEOUTINSECONDS

Attribute	Description
Name	SCREENSAVERTIMEOUTINSECONDS
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

MFI_USER

Attribute	Description
Name	MFI_USER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

F10_REQD

Attribute	Description
Name	F10_REQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

F11_REQD

Attribute	Description
Name	F11_REQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

F12_REQD

Attribute	Description
Name	F12_REQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

ACCESS_CONTROL

Attribute	Description
Name	ACCESS_CONTROL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>U,G,B</td></tr></table>

RESTR_PWD

Attribute	Description
Name	RESTR_PWD
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PWD

Attribute	Description
Name	PWD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MSGSRIGHTS

Attribute	Description
Name	MSGSRIGHTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	
	Restrictions / **Description**: enumeration / Y,N

HLD

Attribute	Description
Name	HLD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CNL

Attribute	Description
Name	CNL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TSTINP

Attribute	Description
Name	TSTINP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGNODE

Attribute	Description
Name	CHGNODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: enumeration / Y,N

CHGADDR

Attribute	Description
Name	CHGADDR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

REL

Attribute	Description
Name	REL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

REINS

Attribute	Description
Name	REINS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMEDIA

Attribute	Description
Name	CHGMEDIA
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGPRIOR

Attribute	Description
Name	CHGPRIOR
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

BRNMOV

Attribute	Description
Name	BRNMOV
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

PRNT

Attribute	Description
Name	PRNT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

TSTCHK

Attribute	Description
Name	TSTCHK
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: enumeration / Y,N

HLDAUTH

Attribute	Description
Name	HLDAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CNLAUTH

Attribute	Description
Name	CNLAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TSTINPAUTH

Attribute	Description
Name	TSTINPAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGNODEAUTH

Attribute	Description
Name	CHGNODEAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGADDRAUTH

Attribute	Description
Name	CHGADDRAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

RELAUTH

Attribute	Description
Name	RELAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

REINSAUTH

Attribute	Description
Name	REINSAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGMEDIAAUTH

Attribute	Description
Name	CHGMEDIAAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: enumeration / Y,N

BRNMOVAUTH

Attribute	Description
Name	BRNMOVAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGPRIORAUTH

Attribute	Description
Name	CHGPRIORAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

FTUPL

Attribute	Description
Name	FTUPL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

LNKCONT

Attribute	Description
Name	LNKCONT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	Y,N

MOVQ

Attribute	Description
Name	MOVQ
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGBRNIN

Attribute	Description
Name	CHGBRNIN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGADDRIN

Attribute	Description
Name	CHGADDRIN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

AUTHRGHTS

Attribute	Description
Name	AUTHRGHTS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: enumeration / Y,N

CHGMSG

Attribute	Description
Name	CHGMSG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMSGAUTH

Attribute	Description
Name	CHGMSGAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGFORCCOVMATCH

Attribute	Description
Name	CHGFORCCOVMATCH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHANGE_FORCE_RELEASE_FUND

Attribute	Description
Name	CHANGE_FORCE_RELEASE_FUND
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: enumeration / Y,N

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

DELMSG

Attribute	Description
Name	DELMSG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

QUEUERIGHTS

Attribute	Description
Name	QUEUERIGHTS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

QUEUE

Attribute	Description
Name	QUEUE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 10

USERTILLS

Attribute	Description

Name	USERTILLS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

TILLID

Attribute	Description
Name	TILLID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12

TILLBRNCD

Attribute	Description
Name	TILLBRNCD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

USERACCCLASS

Attribute	Description
Name	USERACCCLASS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	6

USERGLREST

Attribute	Description
Name	USERGLREST
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NODEGL

Attribute	Description
Name	NODEGL
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	9

USERGLEXCEPT

Attribute	Description
Name	USERGLEXCEPT
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

EXCEPLEAFGL

Attribute	Description
Name	EXCEPLEAFGL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

USERLIMITSROLE

Attribute	Description
Name	USERLIMITSROLE
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

LMTBRN

Attribute	Description
Name	LMTBRN

Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

LMTSROLE

Attribute	Description
Name	LMTSROLE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

USERBRANCHES

Attribute	Description
Name	USERBRANCHES
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRNSBRN

Attribute	Description
Name	BRNSBRN
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

USERPRODUCTS

Attribute	Description
Name	USERPRODUCTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PRDPRDCD

Attribute	Description

Name	PRDPRDCD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	4

USERACCESSPRODUCTS

Attribute	Description
Name	USERACCESSPRODUCTS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PRDACCESSPRDCD

Attribute	Description
Name	PRDACCESSPRDCD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	4

USERFUNCDISALLOW

Attribute	Description
Name	USERFUNCDISALLOW
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FUNCDISALLOWFUNCID

Attribute	Description
Name	FUNCDISALLOWFUNCID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	8

USERROLE

Attribute	Description
Name	USERROLE
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ROLEBRNCD

Attribute	Description
Name	ROLEBRNCD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

USRROLEID

Attribute	Description
Name	USRROLEID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	15

USERSFUNCTIONS

Attribute	Description
Name	USERSFUNCTIONS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

USERFUNCBRNCD

Attribute	Description
Name	USERFUNCBRNCD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

USERFUNCFUNCID

Attribute	Description
Name	USERFUNCFUNCID
Datatype	String
Description	

Restrictions	
	Restrictions / **Description**: maxLength / 8

CONTROL1

Attribute	Description
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL2

Attribute	Description
Name	CONTROL2
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL3

Attribute	Description
Name	CONTROL3
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL4

Attribute	Description
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL5

Attribute	Description
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL6

Attribute	Description
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL8

Attribute	Description
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL9

Attribute	Description
Name	CONTROL9
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

USERFUNCSCTRL10

Attribute	Description
Name	USERFUNCSCTRL10
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL11

Attribute	Description
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL12

Attribute	Description
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL13

Attribute	Description
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL14

Attribute	Description
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL15

Attribute	Description
Name	CONTROL15
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

Grp-Restriction

Attribute	Description
Name	Grp-Restriction
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

GROUP_CODE

Attribute	Description
Name	GROUP_CODE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	40

Centralisation

Attribute	Description
Name	Centralisation
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

USRROLEID

Attribute	Description
Name	USRROLEID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	15

Dshdet

Attribute	Description
Name	Dshdet
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

SEQUENCE_NO

Attribute	Description
Name	SEQUENCE_NO
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	22

DBWHERECLAUSE

Attribute	Description
Name	DBWHERECLAUSE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	4000

SHOW_IN_DASHBOARD

Attribute	Description
Name	SHOW_IN_DASHBOARD
Datatype	String
Description	
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
enumeration	Y,N

Where-Master

Attribute	Description
Name	Where-Master
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

COLUMN_NAME

Attribute	Description
Name	COLUMN_NAME
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

WHERE_CL

Attribute	**Description**
Name	WHERE_CL
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 500

CONDITION

Attribute	**Description**
Name	CONDITION
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	Indicates Field Name

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.10.3.SM-CreateUserMaint-Res-Full-MSG.xsd

CREATEUSERMAINT_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

USR-Full

STRTDATE

USRNAME

USRPWD

ENDDT

USRLANG

HOMEBRN

CUSTNO

LDAPUSR

TIMELEVEL

AUTOAUTH

USRSTAT

USRID

EXTUSRREF

USRCATEG

TILLALLOW

ACCCLSALLOW

GLALLOW

USRTXNLMT

LMTSCCY

MAXTXNAMT

MAXAUTHAMT

BRNSALLOW

PRDSALLOW

PRDSACCESALLOW

TAX_IDENTIFIER

AMOUNT_FORMAT

DATE_FORMAT

STAFFACCRESTR

DEPT_CODE

DEPT_DESC

USRML

ELCMUSER

GROUP_CODE

MULTIBRN_ACCESS

OTH_RM_CUST_ACC_ALLOW

SUPERVISOR_ID

SUPERVISOR_NAME

DASHBOARD_REQD

ALERTS_ON_HOME

REFERENCE_NO

NO_CUMULATIVE_LOGINS

NO_SUCCESSIVE_LOGINS

SCREENSAVERTIMEOUTINSECONDS

MFI_USER

F10_REQD

F11_REQD

F12_REQD

ACCESS_CONTROL

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

RESTR_PWD

PWD

MSGSRIGHTS

GEN

HLD

CNL

TSTINP

CHGNODE

CHGADDR

REL

REINS

CHGMEDIA

CHGPRIOR

BRNMOV

PRNT

TSTCHK

HLDAUTH

CNLAUTH

TSTINPAUTH

CHGNODEAUTH

CHGADDRAUTH

RELAUTH

REINSAUTH

CHGMEDIAAUTH

BRNMOVAUTH

CHGPRIORAUTH

FTUPL

LNKCONT

MOVQ

CHGBRNIN

CHGADDRIN

AUTHRGHTS

CHGMSG

CHGMSGAUTH

CHGFORCCOVMATCH

CHANGE_FORCE_RELEASE_FUND

SUPPRESS

DELMSG

QUEUERIGHTS

QUEUE

USERTILLS

TILLID

TILLBRNCD

USERACCCLASS

ACCCLS

USERGLREST

NODEGL

USERGLEXCEPT

EXCEPLEAFGL

USERLIMITSROLE

LMTBRN

LMTSROLE

QLMTCCY

QINPLMT

QAUTHLMT

USERBRANCHES

BRNSBRN

BRNNAME

USERPRODUCTS

PRDPRDCD

PRDDESC

USERACCESSPRODUCTS

PRDACCESSPRDCD

PRDDESC

USERFUNCDISALLOW

FUNCDISALLOWFUNCID

USERROLE

ROLEBRNCD

USRROLEID

MASTERROLEDESC

USERSFUNCTIONS

USERFUNCBRNCD

USERFUNCFUNCID

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

USERFUNCSCTRL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

CONTROL15

CONTROL16

Grp-Restriction

GROUP_CODE

GROUP_DESC

Centralisation

USRROLEID

ROLDESC

Dshmst

USRID

USRNAME

Dshdet

FUNCTIONID

DESCRIPTION

SEQUENCE_NO

DBWHERECLAUSE

SHOW_IN_DASHBOARD

Where-Master

COLUMN_NAME

WHERE_CL

CONDITION

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATEUSERMAINT_FSFS_RES

Attribute	Description
Name	CREATEUSERMAINT_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

USR-Full

Attribute	Description
Name	USR-Full
Datatype	
Description	

STRTDATE

Attribute	Description
Name	STRTDATE
Datatype	String
Description	

USRNAME

Attribute	Description
Name	USRNAME
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 35

USRPWD

Attribute	Description
Name	USRPWD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

ENDDT

Attribute	Description
Name	ENDDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

USRLANG

Attribute	Description
Name	USRLANG
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

HOMEBRN

Attribute	Description
Name	HOMEBRN
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

LDAPUSR

Attribute	Description
Name	LDAPUSR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	500

TIMELEVEL

Attribute	Description
Name	TIMELEVEL
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	9

AUTOAUTH

Attribute	Description
Name	AUTOAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

USRSTAT

Attribute	Description
Name	USRSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	E,H,D,L

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12

EXTUSRREF

Attribute	Description
Name	EXTUSRREF
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

USRCATEG

Attribute	Description
Name	USRCATEG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,B</td></tr></table>

TILLALLOW

Attribute	Description
Name	TILLALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

ACCCLSALLOW

Attribute	Description
Name	ACCCLSALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

GLALLOW

Attribute	Description
Name	GLALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

USRTXNLMT

Attribute	Description
Name	USRTXNLMT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>U,R,N</td></tr></table>

LMTSCCY

Attribute	Description
Name	LMTSCCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

MAXTXNAMT

Attribute	Description
Name	MAXTXNAMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

MAXAUTHAMT

Attribute	Description
Name	MAXAUTHAMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

BRNSALLOW

Attribute	Description
Name	BRNSALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

PRDSALLOW

Attribute	Description
Name	PRDSALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

PRDSACCESALLOW

Attribute	Description
Name	PRDSACCESALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

TAX_IDENTIFIER

Attribute	Description
Name	TAX_IDENTIFIER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

AMOUNT_FORMAT

Attribute	Description
Name	AMOUNT_FORMAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>.,,,.,,</td></tr></table>

DATE_FORMAT

Attribute	Description
Name	DATE_FORMAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M/d/yyyy</td></tr></table>

STAFFACCRESTR

Attribute	Description
Name	STAFFACCRESTR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

DEPT_CODE

Attribute	Description
Name	DEPT_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

DEPT_DESC

Attribute	Description
Name	DEPT_DESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

USRML

Attribute	Description
Name	USRML
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

ELCMUSER

Attribute	Description
Name	ELCMUSER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

GROUP_CODE

Attribute	Description
Name	GROUP_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

MULTIBRN_ACCESS

Attribute	Description
Name	MULTIBRN_ACCESS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

OTH_RM_CUST_ACC_ALLOW

Attribute	Description
Name	OTH_RM_CUST_ACC_ALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

SUPERVISOR_ID

Attribute	Description
Name	SUPERVISOR_ID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>80</td></tr></table>

SUPERVISOR_NAME

Attribute	Description
Name	SUPERVISOR_NAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

DASHBOARD_REQD

Attribute	Description
Name	DASHBOARD_REQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

ALERTS_ON_HOME

Attribute	Description
Name	ALERTS_ON_HOME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

NO_CUMULATIVE_LOGINS

Attribute	Description
Name	NO_CUMULATIVE_LOGINS
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

NO_SUCCESSIVE_LOGINS

Attribute	Description
Name	NO_SUCCESSIVE_LOGINS
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

SCREENSAVERTIMEOUTINSECONDS

Attribute	Description
Name	SCREENSAVERTIMEOUTINSECONDS
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

MFI_USER

Attribute	Description
Name	MFI_USER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

F10_REQD

Attribute	Description
Name	F10_REQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

F11_REQD

Attribute	Description
Name	F11_REQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

F12_REQD

Attribute	Description
Name	F12_REQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

ACCESS_CONTROL

Attribute	Description
Name	ACCESS_CONTROL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>U,G,B</td></tr></table>

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

RESTR_PWD

Attribute	Description
Name	RESTR_PWD
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PWD

Attribute	Description
Name	PWD
Datatype	String

Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MSGSRIGHTS

Attribute	Description
Name	MSGSRIGHTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

HLD

Attribute	Description
Name	HLD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CNL

Attribute	Description
Name	CNL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
enumeration	Y,N

TSTINP

Attribute	Description
Name	TSTINP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGNODE

Attribute	Description
Name	CHGNODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGADDR

Attribute	Description
Name	CHGADDR
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

REL

Attribute	Description
Name	REL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

REINS

Attribute	Description
Name	REINS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGMEDIA

Attribute	Description
Name	CHGMEDIA
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGPRIOR

Attribute	Description
Name	CHGPRIOR
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

BRNMOV

Attribute	Description
Name	BRNMOV
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: enumeration / Y,N

PRNT

Attribute	Description
Name	PRNT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TSTCHK

Attribute	Description
Name	TSTCHK
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

HLDAUTH

Attribute	Description
Name	HLDAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CNLAUTH

Attribute	Description
Name	CNLAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	Y,N

TSTINPAUTH

Attribute	Description
Name	TSTINPAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGNODEAUTH

Attribute	Description
Name	CHGNODEAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGADDRAUTH

Attribute	Description
Name	CHGADDRAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

RELAUTH

Attribute	Description
Name	RELAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

REINSAUTH

Attribute	Description
Name	REINSAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGMEDIAAUTH

Attribute	Description
Name	CHGMEDIAAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

BRNMOVAUTH

Attribute	Description
Name	BRNMOVAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGPRIORAUTH

Attribute	Description
Name	CHGPRIORAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

FTUPL

Attribute	Description
Name	FTUPL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

LNKCONT

Attribute	Description
Name	LNKCONT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

MOVQ

Attribute	Description
Name	MOVQ
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGBRNIN

Attribute	Description
Name	CHGBRNIN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGADDRIN

Attribute	Description
Name	CHGADDRIN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

AUTHRGHTS

Attribute	Description
Name	AUTHRGHTS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGMSG

Attribute	Description
Name	CHGMSG
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGMSGAUTH

Attribute	Description
Name	CHGMSGAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGFORCCOVMATCH

Attribute	Description
Name	CHGFORCCOVMATCH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHANGE_FORCE_RELEASE_FUND

Attribute	Description
Name	CHANGE_FORCE_RELEASE_FUND
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

DELMSG

Attribute	Description
Name	DELMSG
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

QUEUERIGHTS

Attribute	Description
Name	QUEUERIGHTS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

QUEUE

Attribute	Description
Name	QUEUE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	10

USERTILLS

Attribute	Description
Name	USERTILLS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

TILLID

Attribute	Description
Name	TILLID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12

TILLBRNCD

Attribute	Description
Name	TILLBRNCD
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	3

USERACCCLASS

Attribute	Description
Name	USERACCCLASS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	6

USERGLREST

Attribute	Description
Name	USERGLREST
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NODEGL

Attribute	Description
Name	NODEGL
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	9

USERGLEXCEPT

Attribute	Description
Name	USERGLEXCEPT
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

EXCEPLEAFGL

Attribute	Description
Name	EXCEPLEAFGL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

USERLIMITSROLE

Attribute	Description
Name	USERLIMITSROLE
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

LMTBRN

Attribute	Description
Name	LMTBRN
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

LMTSROLE

Attribute	Description
Name	LMTSROLE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

QLMTCCY

Attribute	Description
Name	QLMTCCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

QINPLMT

Attribute	Description
Name	QINPLMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

QAUTHLMT

Attribute	Description
Name	QAUTHLMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

USERBRANCHES

Attribute	Description
Name	USERBRANCHES
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRNSBRN

Attribute	Description
Name	BRNSBRN
Datatype	String

Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

USERPRODUCTS

Attribute	Description
Name	USERPRODUCTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PRDPRDCD

Attribute	Description
Name	PRDPRDCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

USERACCESSPRODUCTS

Attribute	Description
Name	USERACCESSPRODUCTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PRDACCESSPRDCD

Attribute	Description
Name	PRDACCESSPRDCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

USERFUNCDISALLOW

Attribute	Description
Name	USERFUNCDISALLOW
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FUNCDISALLOWFUNCID

Attribute	Description
Name	FUNCDISALLOWFUNCID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

USERROLE

Attribute	Description
Name	USERROLE
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ROLEBRNCD

Attribute	Description
Name	ROLEBRNCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

USRROLEID

Attribute	Description
Name	USRROLEID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

MASTERROLEDESC

Attribute	Description
Name	MASTERROLEDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>45</td></tr></table>

USERSFUNCTIONS

Attribute	Description
Name	USERSFUNCTIONS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

USERFUNCBRNCD

Attribute	Description
Name	USERFUNCBRNCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

USERFUNCFUNCID

Attribute	Description
Name	USERFUNCFUNCID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 8

CONTROL1

Attribute	Description
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL2

Attribute	Description
Name	CONTROL2
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL3

Attribute	Description
Name	CONTROL3
Datatype	Decimal
Description	

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL4

Attribute	Description
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL5

Attribute	Description
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL6

Attribute	Description
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: totalDigits / 22

CONTROL8

Attribute	**Description**
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL9

Attribute	**Description**
Name	CONTROL9
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

USERFUNCSCTRL10

Attribute	**Description**
Name	USERFUNCSCTRL10
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL11

Attribute	**Description**
Name	CONTROL11
Datatype	Decimal
Description	

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL12

Attribute	Description
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL13

Attribute	Description
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL14

Attribute	Description
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL15

Attribute	Description
Name	CONTROL15
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL16

Attribute	**Description**
Name	CONTROL16
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

Grp-Restriction

Attribute	**Description**
Name	Grp-Restriction
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

GROUP_CODE

Attribute	**Description**
Name	GROUP_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 40

GROUP_DESC

Attribute	**Description**
Name	GROUP_DESC
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	255

Centralisation

Attribute	Description
Name	Centralisation
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

USRROLEID

Attribute	Description
Name	USRROLEID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	15

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

Dshmst

Attribute	Description
Name	Dshmst
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

USRNAME

Attribute	Description
Name	USRNAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

Dshdet

Attribute	Description
Name	Dshdet
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	

Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

SEQUENCE_NO

Attribute	**Description**
Name	SEQUENCE_NO
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description**: totalDigits / 22

DBWHERECLAUSE

Attribute	**Description**
Name	DBWHERECLAUSE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4000

SHOW_IN_DASHBOARD

Attribute	**Description**
Name	SHOW_IN_DASHBOARD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

Where-Master

Attribute	**Description**
Name	Where-Master
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

COLUMN_NAME

Attribute	**Description**

Name	COLUMN_NAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

WHERE_CL

Attribute	**Description**
Name	WHERE_CL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 500

CONDITION

Attribute	**Description**
Name	CONDITION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	Indicates Field Name

Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	150
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.10.4.SM-CreateUserMaint-Res-PK-MSG.xsd

CREATEUSERMAINT_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

USR-PK

USRID

USR-IO

STRTDATE

USRNAME

USRPWD

ENDDT

USRLANG

HOMEBRN

CUSTNO

LDAPUSR

TIMELEVEL

AUTOAUTH

USRSTAT

USRID

EXTUSRREF

USRCATEG

TILLALLOW

ACCCLSALLOW

GLALLOW

USRTXNLMT

LMTSCCY

MAXTXNAMT

MAXAUTHAMT

BRNSALLOW

PRDSALLOW

PRDSACCESALLOW

TAX_IDENTIFIER

AMOUNT_FORMAT

DATE_FORMAT

STAFFACCRESTR

DEPT_CODE

USRML

ELCMUSER

GROUP_CODE

MULTIBRN_ACCESS

OTH_RM_CUST_ACC_ALLOW

SUPERVISOR_ID

DASHBOARD_REQD

ALERTS_ON_HOME

NO_CUMULATIVE_LOGINS

NO_SUCCESSIVE_LOGINS

SCREENSAVERTIMEOUTINSECONDS

MFI_USER

F10_REQD

F11_REQD

F12_REQD

ACCESS_CONTROL

RESTR_PWD

PWD

MSGSRIGHTS

GEN

HLD

CNL

TSTINP

CHGNODE

CHGADDR

REL

REINS

CHGMEDIA

CHGPRIOR

BRNMOV

PRNT

TSTCHK

HLDAUTH

CNLAUTH

TSTINPAUTH

CHGNODEAUTH

CHGADDRAUTH

RELAUTH

REINSAUTH

CHGMEDIAAUTH

BRNMOVAUTH

CHGPRIORAUTH

FTUPL

LNKCONT

MOVQ

CHGBRNIN

CHGADDRIN

AUTHRGHTS

CHGMSG

CHGMSGAUTH

CHGFORCCOVMATCH

CHANGE_FORCE_RELEASE_FUND

SUPPRESS

DELMSG

QUEUERIGHTS

QUEUE

USERTILLS

TILLID

TILLBRNCD

USERACCCLASS

ACCCLS

USERGLREST

NODEGL

USERGLEXCEPT

EXCEPLEAFGL

USERLIMITSROLE

LMTBRN

LMTSROLE

USERBRANCHES

BRNSBRN

USERPRODUCTS

PRDPRDCD

USERACCESSPRODUCTS

PRDACCESSPRDCD

USERFUNCDISALLOW

FUNCDISALLOWFUNCID

USERROLE

ROLEBRNCD

USRROLEID

USERSFUNCTIONS

USERFUNCBRNCD

USERFUNCFUNCID

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

USERFUNCSCTRL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

CONTROL15

CONTROL16

Grp-Restriction

GROUP_CODE

Centralisation

USRROLEID

Dshdet

SEQUENCE_NO

DBWHERECLAUSE

SHOW_IN_DASHBOARD

Where-Master

COLUMN_NAME

WHERE_CL

CONDITION

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATEUSERMAINT_IOPK_RES

Attribute	Description
Name	CREATEUSERMAINT_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

USR-PK

Attribute	Description
Name	USR-PK
Datatype	
Description	

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

USR-IO

Attribute	Description
Name	USR-IO
Datatype	
Description	

STRTDATE

Attribute	Description
Name	STRTDATE
Datatype	String
Description	

USRNAME

Attribute	Description
Name	USRNAME
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

USRPWD

Attribute	Description
Name	USRPWD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>32</td></tr></table>

ENDDT

Attribute	Description
Name	ENDDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

USRLANG

Attribute	Description
Name	USRLANG
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	3

HOMEBRN

Attribute	Description
Name	HOMEBRN
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

LDAPUSR

Attribute	Description
Name	LDAPUSR
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	500

TIMELEVEL

Attribute	Description
Name	TIMELEVEL
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	9

AUTOAUTH

Attribute	Description
Name	AUTOAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

USRSTAT

Attribute	Description
Name	USRSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>E,H,D,L</td></tr></table>

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

EXTUSRREF

Attribute	Description
Name	EXTUSRREF
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

USRCATEG

Attribute	Description
Name	USRCATEG
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,B</td></tr></table>

TILLALLOW

Attribute	Description
Name	TILLALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

ACCCLSALLOW

Attribute	Description
Name	ACCCLSALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

GLALLOW

Attribute	Description
Name	GLALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

USRTXNLMT

Attribute	Description
Name	USRTXNLMT
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,R,N

LMTSCCY

Attribute	**Description**
Name	LMTSCCY
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

MAXTXNAMT

Attribute	**Description**
Name	MAXTXNAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

MAXAUTHAMT

Attribute	**Description**
Name	MAXAUTHAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

BRNSALLOW

Attribute	**Description**
Name	BRNSALLOW
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / A,D

PRDSALLOW

Attribute	**Description**
Name	PRDSALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

PRDSACCESALLOW

Attribute	**Description**
Name	PRDSACCESALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TAX_IDENTIFIER

Attribute	**Description**
Name	TAX_IDENTIFIER
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

AMOUNT_FORMAT

Attribute	**Description**
Name	AMOUNT_FORMAT
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / .,,,.,,

DATE_FORMAT

Attribute	**Description**
Name	DATE_FORMAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M/d/yyyy

STAFFACCRESTR

Attribute	**Description**
Name	STAFFACCRESTR
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

DEPT_CODE

Attribute	**Description**
Name	DEPT_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

USRML

Attribute	**Description**
Name	USRML
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** maxLength / 50

ELCMUSER

Attribute	**Description**
Name	ELCMUSER
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

GROUP_CODE

Attribute	**Description**
Name	GROUP_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

MULTIBRN_ACCESS

Attribute	**Description**
Name	MULTIBRN_ACCESS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

OTH_RM_CUST_ACC_ALLOW

Attribute	**Description**
Name	OTH_RM_CUST_ACC_ALLOW
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

SUPERVISOR_ID

Attribute	**Description**
Name	SUPERVISOR_ID
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 80

DASHBOARD_REQD

Attribute	**Description**
Name	DASHBOARD_REQD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

ALERTS_ON_HOME

Attribute	**Description**
Name	ALERTS_ON_HOME
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

NO_CUMULATIVE_LOGINS

Attribute	**Description**
Name	NO_CUMULATIVE_LOGINS
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

NO_SUCCESSIVE_LOGINS

Attribute	**Description**
Name	NO_SUCCESSIVE_LOGINS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

SCREENSAVERTIMEOUTINSECONDS

Attribute	**Description**
Name	SCREENSAVERTIMEOUTINSECONDS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

MFI_USER

Attribute	**Description**
Name	MFI_USER
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

F10_REQD

Attribute	**Description**
Name	F10_REQD
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / Y,N

F11_REQD

Attribute	**Description**
Name	F11_REQD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

F12_REQD

Attribute	**Description**
Name	F12_REQD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

ACCESS_CONTROL

Attribute	**Description**
Name	ACCESS_CONTROL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,G,B

RESTR_PWD

Attribute	**Description**
Name	RESTR_PWD
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PWD

Attribute	Description
Name	PWD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12

MSGSRIGHTS

Attribute	Description
Name	MSGSRIGHTS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

HLD

Attribute	Description
Name	HLD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CNL

Attribute	Description

Name	CNL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TSTINP

Attribute	**Description**
Name	TSTINP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGNODE

Attribute	**Description**
Name	CHGNODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGADDR

Attribute	**Description**
Name	CHGADDR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

REL

Attribute	**Description**

Name	REL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

REINS

Attribute	**Description**
Name	REINS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMEDIA

Attribute	**Description**
Name	CHGMEDIA
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGPRIOR

Attribute	**Description**
Name	CHGPRIOR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

BRNMOV

Attribute	**Description**

Name	BRNMOV
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

PRNT

Attribute	**Description**
Name	PRNT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TSTCHK

Attribute	**Description**
Name	TSTCHK
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

HLDAUTH

Attribute	**Description**
Name	HLDAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CNLAUTH

Attribute	**Description**

Name	CNLAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TSTINPAUTH

Attribute	**Description**
Name	TSTINPAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGNODEAUTH

Attribute	**Description**
Name	CHGNODEAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGADDRAUTH

Attribute	**Description**
Name	CHGADDRAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

RELAUTH

Attribute	**Description**

Name	RELAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

REINSAUTH

Attribute	**Description**
Name	REINSAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMEDIAAUTH

Attribute	**Description**
Name	CHGMEDIAAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

BRNMOVAUTH

Attribute	**Description**
Name	BRNMOVAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGPRIORAUTH

Attribute	**Description**

Name	CHGPRIORAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

FTUPL

Attribute	**Description**
Name	FTUPL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

LNKCONT

Attribute	**Description**
Name	LNKCONT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

MOVQ

Attribute	**Description**
Name	MOVQ
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGBRNIN

Attribute	**Description**

Name	CHGBRNIN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGADDRIN

Attribute	**Description**
Name	CHGADDRIN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

AUTHRGHTS

Attribute	**Description**
Name	AUTHRGHTS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMSG

Attribute	**Description**
Name	CHGMSG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMSGAUTH

Attribute	**Description**

Name	CHGMSGAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGFORCCOVMATCH

Attribute	**Description**
Name	CHGFORCCOVMATCH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHANGE_FORCE_RELEASE_FUND

Attribute	**Description**
Name	CHANGE_FORCE_RELEASE_FUND
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

SUPPRESS

Attribute	**Description**
Name	SUPPRESS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

DELMSG

Attribute	**Description**

Name	DELMSG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

QUEUERIGHTS

Attribute	**Description**
Name	QUEUERIGHTS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

QUEUE

Attribute	**Description**
Name	QUEUE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 10

USERTILLS

Attribute	**Description**
Name	USERTILLS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

TILLID

Attribute	**Description**
Name	TILLID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12

TILLBRNCD

Attribute	**Description**

Name	TILLBRNCD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

USERACCCLASS

Attribute	Description
Name	USERACCCLASS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	6

USERGLREST

Attribute	Description
Name	USERGLREST
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NODEGL

Attribute	Description
Name	NODEGL
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	9

USERGLEXCEPT

Attribute	Description
Name	USERGLEXCEPT
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

EXCEPLEAFGL

Attribute	Description
Name	EXCEPLEAFGL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

USERLIMITSROLE

Attribute	Description
Name	USERLIMITSROLE
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

LMTBRN

Attribute	Description
Name	LMTBRN
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

LMTSROLE

Attribute	Description
Name	LMTSROLE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

USERBRANCHES

Attribute	Description
Name	USERBRANCHES
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRNSBRN

Attribute	Description
Name	BRNSBRN
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

USERPRODUCTS

Attribute	Description
Name	USERPRODUCTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PRDPRDCD

Attribute	Description
Name	PRDPRDCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

USERACCESSPRODUCTS

Attribute	Description
Name	USERACCESSPRODUCTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PRDACCESSPRDCD

Attribute	Description
Name	PRDACCESSPRDCD

Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

USERFUNCDISALLOW

Attribute	Description
Name	USERFUNCDISALLOW
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FUNCDISALLOWFUNCID

Attribute	Description
Name	FUNCDISALLOWFUNCID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

USERROLE

Attribute	Description
Name	USERROLE
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ROLEBRNCD

Attribute	Description
Name	ROLEBRNCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

USRROLEID

Attribute	Description
Name	USRROLEID
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	15

USERSFUNCTIONS

Attribute	Description
Name	USERSFUNCTIONS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

USERFUNCBRNCD

Attribute	Description
Name	USERFUNCBRNCD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

USERFUNCFUNCID

Attribute	Description
Name	USERFUNCFUNCID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	8

CONTROL1

Attribute	Description
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL2

Attribute	Description
Name	CONTROL2
Datatype	Decimal
Description	

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL3

Attribute	Description
Name	CONTROL3
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL4

Attribute	Description
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL5

Attribute	Description
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL6

Attribute	Description
Name	CONTROL6
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL7

Attribute	**Description**
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL8

Attribute	**Description**
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL9

Attribute	**Description**
Name	CONTROL9
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

USERFUNCSCTRL10

Attribute	**Description**
Name	USERFUNCSCTRL10
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: totalDigits / 22

CONTROL11

Attribute	**Description**
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL12

Attribute	**Description**
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL13

Attribute	**Description**
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL14

Attribute	**Description**
Name	CONTROL14
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL15

Attribute	Description
Name	CONTROL15
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

Grp-Restriction

Attribute	Description
Name	Grp-Restriction
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

GROUP_CODE

Attribute	Description
Name	GROUP_CODE
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	40

Centralisation

Attribute	Description
Name	Centralisation
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

USRROLEID

Attribute	Description
Name	USRROLEID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	15

Dshdet

Attribute	Description
Name	Dshdet
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

SEQUENCE_NO

Attribute	Description
Name	SEQUENCE_NO
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	22

DBWHERECLAUSE

Attribute	Description
Name	DBWHERECLAUSE
Datatype	String
Description	

Restrictions	
	Restrictions / **Description**: maxLength / 4000

SHOW_IN_DASHBOARD

Attribute	Description
Name	SHOW_IN_DASHBOARD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

Where-Master

Attribute	Description
Name	Where-Master
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

COLUMN_NAME

Attribute	Description
Name	COLUMN_NAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

WHERE_CL

Attribute	Description
Name	WHERE_CL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 500

CONDITION

Attribute	Description
Name	CONDITION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150; minLength / 0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String

Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.11.DeleteSMDBANKP

2.11.1.SM-DeleteSMDBANKP-Req-Full-MSG.xsd

DELETESMDBANKP_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Parameters-Full

HEAD_OFFICE

SITE_CODE

ACTIVATION_KEY

INVALID_LOGINS_CUM

INVALID_LOGINS_SUC

PWD_PREVENT_REUSE

PWD_CHANGE_AFTER

MAXIMUM

MINIMUM

PWD_EXPIRY_MSG_DAYS

ARCHIVAL_PERIOD

CONCHAR_PWD_NUM

FREQ_PWD_CHG

MIN_PWD_NUMERIC_LENGTH

LEGAL_NOTICE

DORMANCY_DAYS

DISPLAY_LEGAL_NOTICE

MIN_SPECIALCHAR_LENGTH

MIN_LOWERCASE_CHAR

MIN_UPPERCASE_CHAR

SCREENSAVERREQUIRED

SCREENSAVERTIMEOUTINSECONDS

SCREENSAVERMODIFIABLEBYUSER

PASSWORDEXTERNAL

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Smtbs-Branch-Restr

- *RESTR_TYPE*

DESCRIPTION

Smtbs-Restrictive-Passwd

PASSWORD

UDFDETAILS

FLDNAM

FLDVAL

DELETESMDBANKP_FSFS_REQ

Attribute	Description
Name	DELETESMDBANKP_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String

Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.

Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Parameters-Full

Attribute	Description
Name	Smtbs-Parameters-Full
Datatype	
Description	

HEAD_OFFICE

Attribute	Description

Name	HEAD_OFFICE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

SITE_CODE

Attribute	**Description**
Name	SITE_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

ACTIVATION_KEY

Attribute	**Description**
Name	ACTIVATION_KEY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 24

INVALID_LOGINS_CUM

Attribute	**Description**
Name	INVALID_LOGINS_CUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 6; maxInclusive / 99

INVALID_LOGINS_SUC

Attribute	**Description**
Name	INVALID_LOGINS_SUC
Datatype	Decimal

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>1</td></tr><tr><td>minInclusive</td><td>3</td></tr><tr><td>maxInclusive</td><td>5</td></tr></table>

PWD_PREVENT_REUSE

Attribute	Description
Name	PWD_PREVENT_REUSE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>1</td></tr></table>

PWD_CHANGE_AFTER

Attribute	Description
Name	PWD_CHANGE_AFTER
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>3</td></tr><tr><td>minInclusive</td><td>15</td></tr><tr><td>maxInclusive</td><td>180</td></tr></table>

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>12</td></tr><tr><td>maxInclusive</td><td>30</td></tr></table>

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 6; maxInclusive / 11

PWD_EXPIRY_MSG_DAYS

Attribute	Description
Name	PWD_EXPIRY_MSG_DAYS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1; maxInclusive / 5

ARCHIVAL_PERIOD

Attribute	Description
Name	ARCHIVAL_PERIOD
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

CONCHAR_PWD_NUM

Attribute	Description
Name	CONCHAR_PWD_NUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	2

FREQ_PWD_CHG

Attribute	Description
Name	FREQ_PWD_CHG
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	0

MIN_PWD_NUMERIC_LENGTH

Attribute	Description
Name	MIN_PWD_NUMERIC_LENGTH
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1

LEGAL_NOTICE

Attribute	Description
Name	LEGAL_NOTICE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4000

DORMANCY_DAYS

Attribute	Description
Name	DORMANCY_DAYS
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

DISPLAY_LEGAL_NOTICE

Attribute	**Description**
Name	DISPLAY_LEGAL_NOTICE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

MIN_SPECIALCHAR_LENGTH

Attribute	**Description**
Name	MIN_SPECIALCHAR_LENGTH
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

MIN_LOWERCASE_CHAR

Attribute	**Description**
Name	MIN_LOWERCASE_CHAR
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

MIN_UPPERCASE_CHAR

Attribute	**Description**

Name	MIN_UPPERCASE_CHAR
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

SCREENSAVERREQUIRED

Attribute	**Description**
Name	SCREENSAVERREQUIRED
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

SCREENSAVERTIMEOUTINSECONDS

Attribute	**Description**
Name	SCREENSAVERTIMEOUTINSECONDS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

SCREENSAVERMODIFIABLEBYUSER

Attribute	**Description**
Name	SCREENSAVERMODIFIABLEBYUSER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

PASSWORDEXTERNAL

Attribute	**Description**

Name	PASSWORDEXTERNAL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	**Description**

Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

Smtbs-Branch-Restr

Attribute	**Description**

Name	Smtbs-Branch-Restr
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

RESTR_TYPE

Attribute	Description
Name	RESTR_TYPE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	12

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	255

Smtbs-Restrictive-Passwd

Attribute	Description
Name	Smtbs-Restrictive-Passwd
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.11.2.SM-DeleteSMDBANKP-Req-IO-MSG.xsd

DELETESMDBANKP_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Parameters-IO

SITE_CODE

DELETESMDBANKP_IOPK_REQ

Attribute	Description
Name	DELETESMDBANKP_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Parameters-IO

Attribute	Description
Name	Smtbs-Parameters-IO
Datatype	
Description	

SITE_CODE

Attribute	Description
Name	SITE_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

2.11.3.SM-DeleteSMDBANKP-Res-Full-MSG.xsd

DELETESMDBANKP_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Parameters-Full

HEAD_OFFICE

SITE_CODE

ACTIVATION_KEY

INVALID_LOGINS_CUM

INVALID_LOGINS_SUC

PWD_PREVENT_REUSE

PWD_CHANGE_AFTER

MAXIMUM

MINIMUM

PWD_EXPIRY_MSG_DAYS

ARCHIVAL_PERIOD

CONCHAR_PWD_NUM

FREQ_PWD_CHG

MIN_PWD_NUMERIC_LENGTH

LEGAL_NOTICE

DORMANCY_DAYS

DISPLAY_LEGAL_NOTICE

MIN_SPECIALCHAR_LENGTH

MIN_LOWERCASE_CHAR

MIN_UPPERCASE_CHAR

SCREENSAVERREQUIRED

SCREENSAVERTIMEOUTINSECONDS

SCREENSAVERMODIFIABLEBYUSER

PASSWORDEXTERNAL

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Smtbs-Branch-Restr

RESTR_TYPE

DESCRIPTION

Smtbs-Restrictive-Passwd

PASSWORD

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETESMDBANKP_FSFS_RES

Attribute	Description
Name	DELETESMDBANKP_FSFS_RES

Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Parameters-Full

Attribute	Description
Name	Smtbs-Parameters-Full
Datatype	
Description	

HEAD_OFFICE

Attribute	Description
Name	HEAD_OFFICE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

SITE_CODE

Attribute	Description
Name	SITE_CODE
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	4

ACTIVATION_KEY

Attribute	Description
Name	ACTIVATION_KEY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	24

INVALID_LOGINS_CUM

Attribute	Description
Name	INVALID_LOGINS_CUM
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	6
maxInclusive	99

INVALID_LOGINS_SUC

Attribute	Description
Name	INVALID_LOGINS_SUC
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	1
minInclusive	3
maxInclusive	5

PWD_PREVENT_REUSE

Attribute	Description
Name	PWD_PREVENT_REUSE
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

PWD_CHANGE_AFTER

Attribute	**Description**
Name	PWD_CHANGE_AFTER
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3; minInclusive / 15; maxInclusive / 180

MAXIMUM

Attribute	**Description**
Name	MAXIMUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 12; maxInclusive / 30

MINIMUM

Attribute	**Description**
Name	MINIMUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 6; maxInclusive / 11

PWD_EXPIRY_MSG_DAYS

Attribute	Description
Name	PWD_EXPIRY_MSG_DAYS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1; maxInclusive / 5

ARCHIVAL_PERIOD

Attribute	Description
Name	ARCHIVAL_PERIOD
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

CONCHAR_PWD_NUM

Attribute	Description
Name	CONCHAR_PWD_NUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2

FREQ_PWD_CHG

Attribute	Description
Name	FREQ_PWD_CHG
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	0

MIN_PWD_NUMERIC_LENGTH

Attribute	Description
Name	MIN_PWD_NUMERIC_LENGTH
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1

LEGAL_NOTICE

Attribute	Description
Name	LEGAL_NOTICE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	4000

DORMANCY_DAYS

Attribute	Description
Name	DORMANCY_DAYS
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1

DISPLAY_LEGAL_NOTICE

Attribute	Description
Name	DISPLAY_LEGAL_NOTICE
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

MIN_SPECIALCHAR_LENGTH

Attribute	**Description**
Name	MIN_SPECIALCHAR_LENGTH
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2 minInclusive / 1

MIN_LOWERCASE_CHAR

Attribute	**Description**
Name	MIN_LOWERCASE_CHAR
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2 minInclusive / 1

MIN_UPPERCASE_CHAR

Attribute	**Description**
Name	MIN_UPPERCASE_CHAR
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2 minInclusive / 1

SCREENSAVERREQUIRED

Attribute	**Description**

Name	SCREENSAVERREQUIRED
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

SCREENSAVERTIMEOUTINSECONDS

Attribute	**Description**
Name	SCREENSAVERTIMEOUTINSECONDS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

SCREENSAVERMODIFIABLEBYUSER

Attribute	**Description**
Name	SCREENSAVERMODIFIABLEBYUSER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

PASSWORDEXTERNAL

Attribute	**Description**
Name	PASSWORDEXTERNAL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

MAKER

Attribute	**Description**

Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	**Description**

Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

Smtbs-Branch-Restr

Attribute	**Description**
Name	Smtbs-Branch-Restr
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

RESTR_TYPE

Attribute	**Description**
Name	RESTR_TYPE
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

DESCRIPTION

Attribute	**Description**
Name	DESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

Smtbs-Restrictive-Passwd

Attribute	**Description**
Name	Smtbs-Restrictive-Passwd
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC

Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.11.4.SM-DeleteSMDBANKP-Res-PK-MSG.xsd

DELETESMDBANKP_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Parameters-PK

SITE_CODE

Smtbs-Parameters-IO

SITE_CODE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETESMDBANKP_IOPK_RES

Attribute	Description
Name	DELETESMDBANKP_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Parameters-PK

Attribute	Description
Name	Smtbs-Parameters-PK
Datatype	
Description	

SITE_CODE

Attribute	Description
Name	SITE_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

Smtbs-Parameters-IO

Attribute	Description
Name	Smtbs-Parameters-IO
Datatype	
Description	

SITE_CODE

Attribute	Description
Name	SITE_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

WCODE

Attribute	Description

Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.12.DeleteSMDRLMNE

2.12.1.SM-DeleteSMDRLMNE-Req-Full-MSG.xsd

DELETESMDRLMNE_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Role-Limit-Full

ROLEID2

DESCRIPTION

LIMIT_CCY

INPUT_LIMIT

AUTHORIZATION_LIMIT

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

DELETESMDRLMNE_FSFS_REQ

Attribute	Description
Name	DELETESMDRLMNE_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description

Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.

Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Smtbs-Role-Limit-Full
Datatype	
Description	

ROLEID2

Attribute	Description
Name	ROLEID2
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

LIMIT_CCY

Attribute	Description
Name	LIMIT_CCY
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

INPUT_LIMIT

Attribute	Description
Name	INPUT_LIMIT
Datatype	Decimal
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr></table>

AUTHORIZATION_LIMIT

Attribute	Description
Name	AUTHORIZATION_LIMIT
Datatype	Decimal

Description	
Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	150
minLength	0

2.12.2.SM-DeleteSMDRLMNE-Req-IO-MSG.xsd

DELETESMDRLMNE_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Role-Limit-IO

ROLEID2

DELETESMDRLMNE_IOPK_REQ

Attribute	Description
Name	DELETESMDRLMNE_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Role-Limit-IO

Attribute	**Description**

Name	Smtbs-Role-Limit-IO
Datatype	
Description	

ROLEID2

Attribute	Description
Name	ROLEID2
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

2.12.3.SM-DeleteSMDRLMNE-Res-Full-MSG.xsd

DELETESMDRLMNE_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Role-Limit-Full

ROLEID2

DESCRIPTION

LIMIT_CCY

INPUT_LIMIT

AUTHORIZATION_LIMIT

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETESMDRLMNE_FSFS_RES

Attribute	Description
Name	DELETESMDRLMNE_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Role-Limit-Full

Attribute	Description
Name	Smtbs-Role-Limit-Full
Datatype	
Description	

ROLEID2

Attribute	Description
Name	ROLEID2
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

LIMIT_CCY

Attribute	Description
Name	LIMIT_CCY
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	3

INPUT_LIMIT

Attribute	Description
Name	INPUT_LIMIT
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0

AUTHORIZATION_LIMIT

Attribute	Description
Name	AUTHORIZATION_LIMIT
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.12.4.SM-DeleteSMDRLMNE-Res-PK-MSG.xsd

DELETESMDRLMNE_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Role-Limit-PK

ROLEID2

Smtbs-Role-Limit-IO

ROLEID2

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETESMDRLMNE_IOPK_RES

Attribute	Description
Name	DELETESMDRLMNE_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description**: minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID

Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Role-Limit-PK

Attribute	Description
Name	Smtbs-Role-Limit-PK
Datatype	
Description	

ROLEID2

Attribute	Description

Name	ROLEID2
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	15

Smtbs-Role-Limit-IO

Attribute	Description
Name	Smtbs-Role-Limit-IO
Datatype	
Description	

ROLEID2

Attribute	Description
Name	ROLEID2
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	15

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC

Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.13.DeleteSMRole

2.13.1.SM-DeleteSMRole-Req-Full-MSG.xsd

DELETESMROLE_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

ROLEMASTER-Full

ROLEIDENTIFICATION

MASTERROLEDESC

AUTHORISERROLE

BRANCH_RES

ACCCLASSALLOWED

CENTRALISATIONROLE

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

ROLEDETAIL

ROLEFUN

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

CONTROL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

CONTROL15

CONTROL16

ROLEDETAILB

ROLEFUN

CONT1

CONT2

CONT3

CONT4

CONT5

CONT6

CONTROL7

CONT8

CONT9

CONT10

CONT11

CONT12

CONT13

CONT14

CONT15

CONTROL16

ROLEDETAILC

ROLEFUN

CNTRL1

CNTRL2

CNTRL3

CNTRL4

CNTRL5

CNTRL6

CNTRL7

CNTRL8

CNTRL9

CNTRL10

CNTRL11

CNTRL12

CNTRL13

CNTRL14

CNTRL15

CNTRL16

ROLEDETAILD

ROLEFUN

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

CONTROL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

CNTRL15

CNTRL16

ROLEBRANCHES

BRANCH

BRNNAME

ROLEACCCLASS

ACCCLS

DESCRIPTION

MSGCRIGHTS

CNL

CHGNODE

REL

CHGMEDIA

BRNMOV

HLD

TSTINP

CHGADDR

REINS

CHGPRIOR

CNLAUTH

CHGNODEAUTH

RELAUTH

CHGMEDIAAUTH

BRNMOVAUTH

HLDAUTH

TSTINPAUTH

CHGADDRAUTH

REINSAUTH

CHGPRIORAUTH

GEN

TSTCHK

LNKCONT

CHGBRNIN

CHGMSG

CHGFORCRELFUND

SUPPRESS

DELMSG

PRNT

FTUPL

MOVQ

CHGADDRIN

CHGMSGAUTH

AUTHRGHTS

CHGFORCCOVMATCH

QUEUERIGHTS

QUEUE

RESTRICTIVEPASSWD

PWD

PWDID

ROLEBRANCHLIMITS

LMTCCY

BRHUSERLMT

Roledetaile

ROLEFUN

BRANCHCODE

EDITABLE

CNTRLSTR

Roledetailf

ROLEID

ROLEFUN

CNTRLSTR

CNTRL1

CNTRL10

CNTRL11

CNTRL12

CNTRL13

CNTRL14

CNTRL15

CNTRL16

CNTRL2

CNTRL3

CNTRL4

CNTRL5

CNTRL6

CNTRL7

CNTRL8

CNTRL9

ATHSTAT

BRNCHCODE

UDFDETAILS

FLDNAM

FLDVAL

DELETESMROLE_FSFS_REQ

Attribute	Description
Name	DELETESMROLE_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

ROLEMASTER-Full

Attribute	Description
Name	ROLEMASTER-Full
Datatype	
Description	

ROLEIDENTIFICATION

Attribute	Description
Name	ROLEIDENTIFICATION
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

MASTERROLEDESC

Attribute	Description
Name	MASTERROLEDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

AUTHORISERROLE

Attribute	Description
Name	AUTHORISERROLE
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / Y,N

BRANCH_RES

Attribute	**Description**
Name	BRANCH_RES
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

ACCCLASSALLOWED

Attribute	**Description**
Name	ACCCLASSALLOWED
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

CENTRALISATIONROLE

Attribute	**Description**
Name	CENTRALISATIONROLE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

ROLEDETAIL

Attribute	**Description**
Name	ROLEDETAIL
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

ROLEFUN

Attribute	**Description**
Name	ROLEFUN
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	8

CONTROL1

Attribute	Description
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL2

Attribute	Description
Name	CONTROL2
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL3

Attribute	Description
Name	CONTROL3
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL4

Attribute	Description
Name	CONTROL4

Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL5

Attribute	Description
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL6

Attribute	Description
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL8

Attribute	Description
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL9

Attribute	Description
Name	CONTROL9
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL10

Attribute	Description
Name	CONTROL10
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL11

Attribute	Description
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL12

Attribute	Description
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL13

Attribute	Description
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL14

Attribute	Description
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL15

Attribute	Description
Name	CONTROL15
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

ROLEDETAILB

Attribute	Description
Name	ROLEDETAILB
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	8

CONT1

Attribute	Description
Name	CONT1
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT2

Attribute	Description
Name	CONT2
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT3

Attribute	Description
Name	CONT3
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT4

Attribute	Description
Name	CONT4

Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONT5

Attribute	**Description**
Name	CONT5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONT6

Attribute	**Description**
Name	CONT6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL7

Attribute	**Description**
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT8

Attribute	Description
Name	CONT8
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT9

Attribute	Description
Name	CONT9
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT10

Attribute	Description
Name	CONT10
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT11

Attribute	Description
Name	CONT11
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONT12

Attribute	Description
Name	CONT12
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONT13

Attribute	Description
Name	CONT13
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONT14

Attribute	Description
Name	CONT14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT15

Attribute	Description
Name	CONT15
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

ROLEDETAILC

Attribute	Description
Name	ROLEDETAILC
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	8

CNTRL1

Attribute	Description
Name	CNTRL1
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL2

Attribute	Description
Name	CNTRL2
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL3

Attribute	Description
Name	CNTRL3
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL4

Attribute	Description
Name	CNTRL4

Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL5

Attribute	**Description**
Name	CNTRL5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL6

Attribute	**Description**
Name	CNTRL6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL7

Attribute	**Description**
Name	CNTRL7
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL8

Attribute	Description
Name	CNTRL8
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL9

Attribute	Description
Name	CNTRL9
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL10

Attribute	Description
Name	CNTRL10
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL11

Attribute	Description
Name	CNTRL11
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL12

Attribute	Description
Name	CNTRL12
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL13

Attribute	Description
Name	CNTRL13
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL14

Attribute	Description
Name	CNTRL14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL15

Attribute	Description
Name	CNTRL15
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL16

Attribute	Description
Name	CNTRL16
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

ROLEDETAILD

Attribute	Description
Name	ROLEDETAILD
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	8

CONTROL1

Attribute	Description
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL2

Attribute	Description
Name	CONTROL2
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL3

Attribute	Description
Name	CONTROL3
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL4

Attribute	Description
Name	CONTROL4

Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: totalDigits = 22; minInclusive = 0; maxInclusive = 1

CONTROL5

Attribute	**Description**
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: totalDigits = 22; minInclusive = 0; maxInclusive = 1

CONTROL6

Attribute	**Description**
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: totalDigits = 22; minInclusive = 0; maxInclusive = 1

CONTROL7

Attribute	**Description**
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs = 0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL8

Attribute	Description
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL9

Attribute	Description
Name	CONTROL9
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL10

Attribute	Description
Name	CONTROL10
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL11

Attribute	Description
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL12

Attribute	Description
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL13

Attribute	Description
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL14

Attribute	Description
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL15

Attribute	Description
Name	CNTRL15
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL16

Attribute	Description
Name	CNTRL16
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

ROLEBRANCHES

Attribute	Description
Name	ROLEBRANCHES
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	
	Restrictions / **Description**: maxLength / 3

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

ROLEACCCLASS

Attribute	Description
Name	ROLEACCCLASS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 6

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

MSGCRIGHTS

Attribute	Description

Name	MSGCRIGHTS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

CNL

Attribute	**Description**
Name	CNL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGNODE

Attribute	**Description**
Name	CHGNODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

REL

Attribute	**Description**
Name	REL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMEDIA

Attribute	**Description**
Name	CHGMEDIA
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

BRNMOV

Attribute	**Description**
Name	BRNMOV
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

HLD

Attribute	**Description**
Name	HLD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TSTINP

Attribute	**Description**
Name	TSTINP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGADDR

Attribute	**Description**
Name	CHGADDR
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

REINS

Attribute	Description
Name	REINS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGPRIOR

Attribute	Description
Name	CHGPRIOR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CNLAUTH

Attribute	Description
Name	CNLAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGNODEAUTH

Attribute	Description
Name	CHGNODEAUTH
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

RELAUTH

Attribute	**Description**
Name	RELAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGMEDIAAUTH

Attribute	**Description**
Name	CHGMEDIAAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

BRNMOVAUTH

Attribute	**Description**
Name	BRNMOVAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

HLDAUTH

Attribute	**Description**
Name	HLDAUTH
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TSTINPAUTH

Attribute	Description
Name	TSTINPAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGADDRAUTH

Attribute	Description
Name	CHGADDRAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

REINSAUTH

Attribute	Description
Name	REINSAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGPRIORAUTH

Attribute	Description
Name	CHGPRIORAUTH
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / Y,N

GEN

Attribute	**Description**
Name	GEN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TSTCHK

Attribute	**Description**
Name	TSTCHK
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

LNKCONT

Attribute	**Description**
Name	LNKCONT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGBRNIN

Attribute	**Description**
Name	CHGBRNIN
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

CHGMSG

Attribute	**Description**
Name	CHGMSG
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGFORCRELFUND

Attribute	**Description**
Name	CHGFORCRELFUND
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

SUPPRESS

Attribute	**Description**
Name	SUPPRESS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

DELMSG

Attribute	**Description**
Name	DELMSG
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

PRNT

Attribute	**Description**
Name	PRNT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

FTUPL

Attribute	**Description**
Name	FTUPL
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

MOVQ

Attribute	**Description**
Name	MOVQ
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGADDRIN

Attribute	**Description**
Name	CHGADDRIN
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGMSGAUTH

Attribute	**Description**
Name	CHGMSGAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

AUTHRGHTS

Attribute	**Description**
Name	AUTHRGHTS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGFORCCOVMATCH

Attribute	**Description**
Name	CHGFORCCOVMATCH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

QUEUERIGHTS

Attribute	**Description**
Name	QUEUERIGHTS
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

QUEUE

Attribute	Description
Name	QUEUE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	10

RESTRICTIVEPASSWD

Attribute	Description
Name	RESTRICTIVEPASSWD
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PWD

Attribute	Description
Name	PWD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12

PWDID

Attribute	Description
Name	PWDID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

ROLEBRANCHLIMITS

Attribute	Description
Name	ROLEBRANCHLIMITS
Datatype	

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

LMTCCY

Attribute	Description
Name	LMTCCY
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

BRHUSERLMT

Attribute	Description
Name	BRHUSERLMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

Roledetaile

Attribute	Description
Name	Roledetaile
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

EDITABLE

Attribute	Description
Name	EDITABLE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CNTRLSTR

Attribute	Description
Name	CNTRLSTR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

Roledetailf

Attribute	Description
Name	Roledetailf
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ROLEID

Attribute	Description
Name	ROLEID

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

ROLEFUN

Attribute	**Description**
Name	ROLEFUN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

CNTRLSTR

Attribute	**Description**
Name	CNTRLSTR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

CNTRL1

Attribute	**Description**
Name	CNTRL1
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL10

Attribute	**Description**

Name	CNTRL10
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL11

Attribute	**Description**
Name	CNTRL11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL12

Attribute	**Description**
Name	CNTRL12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL13

Attribute	**Description**
Name	CNTRL13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL14

Attribute	Description
Name	CNTRL14
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL15

Attribute	Description
Name	CNTRL15
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL16

Attribute	Description
Name	CNTRL16
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL2

Attribute	Description
Name	CNTRL2
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL3

Attribute	Description
Name	CNTRL3
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL4

Attribute	Description
Name	CNTRL4
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL5

Attribute	Description
Name	CNTRL5
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL6

Attribute	Description
Name	CNTRL6
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL7

Attribute	Description
Name	CNTRL7
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL8

Attribute	Description
Name	CNTRL8
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL9

Attribute	Description
Name	CNTRL9
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

ATHSTAT

Attribute	Description
Name	ATHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

BRNCHCODE

Attribute	Description
Name	BRNCHCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description

Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.13.2.SM-DeleteSMRole-Req-IO-MSG.xsd

DELETESMROLE_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

ROLEMASTER-IO

ROLEIDENTIFICATION

DELETESMROLE_IOPK_REQ

Attribute	Description
Name	DELETESMROLE_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description**: minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID

Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

ROLEMASTER-IO

Attribute	Description
Name	ROLEMASTER-IO
Datatype	
Description	

ROLEIDENTIFICATION

Attribute	Description

Name	ROLEIDENTIFICATION
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

2.13.3.SM-DeleteSMRole-Res-Full-MSG.xsd

DELETESMROLE_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

ROLEMASTER-Full

ROLEIDENTIFICATION

MASTERROLEDESC

AUTHORISERROLE

BRANCH_RES

ACCCLASSALLOWED

CENTRALISATIONROLE

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

ROLEDETAIL

- *ROLEFUN*
- *CONTROL1*
- *CONTROL2*
- *CONTROL3*
- *CONTROL4*
- *CONTROL5*
- *CONTROL6*
- *CONTROL7*
- *CONTROL8*
- *CONTROL9*
- *CONTROL10*
- *CONTROL11*
- *CONTROL12*
- *CONTROL13*
- *CONTROL14*
- *CONTROL15*
- *CONTROL16*

ROLEDETAILB

- *ROLEFUN*
- *CONT1*

CONT2

CONT3

CONT4

CONT5

CONT6

CONTROL7

CONT8

CONT9

CONT10

CONT11

CONT12

CONT13

CONT14

CONT15

CONTROL16

ROLEDETAILC

ROLEFUN

CNTRL1

CNTRL2

CNTRL3

CNTRL4

CNTRL5

CNTRL6

CNTRL7

CNTRL8

CNTRL9

CNTRL10

CNTRL11

CNTRL12

CNTRL13

CNTRL14

CNTRL15

CNTRL16

ROLEDETAILD

ROLEFUN

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

CONTROL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

CNTRL15

CNTRL16

ROLEBRANCHES

BRANCH

BRNNAME

ROLEACCCLASS

ACCCLS

DESCRIPTION

MSGCRIGHTS

CNL

CHGNODE

REL

CHGMEDIA

BRNMOV

HLD

TSTINP

CHGADDR

REINS

CHGPRIOR

CNLAUTH

CHGNODEAUTH

RELAUTH

CHGMEDIAAUTH

BRNMOVAUTH

HLDAUTH

TSTINPAUTH

CHGADDRAUTH

REINSAUTH

CHGPRIORAUTH

GEN

TSTCHK

LNKCONT

CHGBRNIN

CHGMSG

CHGFORCRELFUND

SUPPRESS

DELMSG

PRNT

FTUPL

MOVQ

CHGADDRIN

CHGMSGAUTH

AUTHRGHTS

CHGFORCCOVMATCH

QUEUERIGHTS

QUEUE

RESTRICTIVEPASSWD

PWD

PWDID

ROLEBRANCHLIMITS

LMTCCY

BRHUSERLMT

Roledetaile

ROLEFUN

BRANCHCODE

EDITABLE

CNTRLSTR

Roledetailf

ROLEID

ROLEFUN

CNTRLSTR

CNTRL1

CNTRL10

CNTRL11

CNTRL12

CNTRL13

CNTRL14

CNTRL15

CNTRL16

CNTRL2

CNTRL3

CNTRL4

CNTRL5

CNTRL6

CNTRL7

CNTRL8

CNTRL9

ATHSTAT

BRNCHCODE

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETESMROLE_FSFS_RES

Attribute	Description
Name	DELETESMROLE_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: maxLength = 128; pattern = [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs = 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs = 0; maxOccurs = unbounded

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	

ROLEMASTER-Full

Attribute	**Description**

Name	ROLEMASTER-Full
Datatype	
Description	

ROLEIDENTIFICATION

Attribute	Description
Name	ROLEIDENTIFICATION
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

MASTERROLEDESC

Attribute	Description
Name	MASTERROLEDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

AUTHORISERROLE

Attribute	Description
Name	AUTHORISERROLE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

BRANCH_RES

Attribute	Description
Name	BRANCH_RES
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

ACCCLASSALLOWED

Attribute	Description
Name	ACCCLASSALLOWED
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

CENTRALISATIONROLE

Attribute	Description
Name	CENTRALISATIONROLE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

ROLEDETAIL

Attribute	Description
Name	ROLEDETAIL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

CONTROL1

Attribute	Description
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL2

Attribute	Description
Name	CONTROL2
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL3

Attribute	**Description**
Name	CONTROL3
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL4

Attribute	**Description**
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL5

Attribute	**Description**
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL6

Attribute	Description
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL8

Attribute	Description
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL9

Attribute	Description
Name	CONTROL9
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL10

Attribute	**Description**
Name	CONTROL10
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL11

Attribute	**Description**
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL12

Attribute	**Description**
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL13

Attribute	Description
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL14

Attribute	Description
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL15

Attribute	Description
Name	CONTROL15
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

ROLEDETAILB

Attribute	**Description**
Name	ROLEDETAILB
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ROLEFUN

Attribute	**Description**
Name	ROLEFUN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 8

CONT1

Attribute	**Description**
Name	CONT1
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONT2

Attribute	**Description**
Name	CONT2
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT3

Attribute	**Description**
Name	CONT3
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT4

Attribute	**Description**
Name	CONT4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT5

Attribute	**Description**
Name	CONT5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT6

Attribute	Description
Name	CONT6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT8

Attribute	Description
Name	CONT8
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT9

Attribute	Description
Name	CONT9
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT10

Attribute	**Description**
Name	CONT10
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT11

Attribute	**Description**
Name	CONT11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT12

Attribute	**Description**
Name	CONT12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT13

Attribute	Description
Name	CONT13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT14

Attribute	Description
Name	CONT14
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT15

Attribute	Description
Name	CONT15
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

ROLEDETAILC

Attribute	**Description**
Name	ROLEDETAILC
Datatype	
Description	
Attribute	
	Attribute / **Description** minOccurs / 0 maxOccurs / unbounded

ROLEFUN

Attribute	**Description**
Name	ROLEFUN
Datatype	String
Description	
Restrictions	
	Restrictions / **Description** maxLength / 8

CNTRL1

Attribute	**Description**
Name	CNTRL1
Datatype	Decimal
Description	
Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL2

Attribute	**Description**
Name	CNTRL2
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL3

Attribute	**Description**
Name	CNTRL3
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL4

Attribute	**Description**
Name	CNTRL4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL5

Attribute	**Description**
Name	CNTRL5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL6

Attribute	Description
Name	CNTRL6
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL7

Attribute	Description
Name	CNTRL7
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL8

Attribute	Description
Name	CNTRL8
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL9

Attribute	Description
Name	CNTRL9
Datatype	Decimal
Description	

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL10

Attribute	Description
Name	CNTRL10
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL11

Attribute	Description
Name	CNTRL11
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL12

Attribute	Description
Name	CNTRL12
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL13

Attribute	Description
Name	CNTRL13
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL14

Attribute	Description
Name	CNTRL14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL15

Attribute	Description
Name	CNTRL15
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL16

Attribute	Description
Name	CNTRL16
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

ROLEDETAILD

Attribute	Description
Name	ROLEDETAILD
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 8

CONTROL1

Attribute	Description
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL2

Attribute	Description
Name	CONTROL2
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL3

Attribute	**Description**
Name	CONTROL3
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL4

Attribute	**Description**
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL5

Attribute	**Description**
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL6

Attribute	Description
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: totalDigits = 22; minInclusive = 0; maxInclusive = 1

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: totalDigits = 22; minInclusive = 0; maxInclusive = 1

CONTROL8

Attribute	Description
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: totalDigits = 22; minInclusive = 0; maxInclusive = 1

CONTROL9

Attribute	Description
Name	CONTROL9
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL10

Attribute	**Description**
Name	CONTROL10
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL11

Attribute	**Description**
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL12

Attribute	**Description**
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL13

Attribute	Description
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL14

Attribute	Description
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL15

Attribute	Description
Name	CNTRL15
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL16

Attribute	Description
Name	CNTRL16
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

ROLEBRANCHES

Attribute	Description
Name	ROLEBRANCHES
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

ROLEACCCLASS

Attribute	Description
Name	ROLEACCCLASS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 6

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

MSGCRIGHTS

Attribute	Description
Name	MSGCRIGHTS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

CNL

Attribute	Description
Name	CNL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGNODE

Attribute	Description
Name	CHGNODE
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / Y,N

REL

Attribute	**Description**
Name	REL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMEDIA

Attribute	**Description**
Name	CHGMEDIA
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

BRNMOV

Attribute	**Description**
Name	BRNMOV
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

HLD

Attribute	**Description**
Name	HLD
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

TSTINP

Attribute	**Description**
Name	TSTINP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGADDR

Attribute	**Description**
Name	CHGADDR
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

REINS

Attribute	**Description**
Name	REINS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGPRIOR

Attribute	**Description**
Name	CHGPRIOR
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

CNLAUTH

Attribute	**Description**
Name	CNLAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGNODEAUTH

Attribute	**Description**
Name	CHGNODEAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

RELAUTH

Attribute	**Description**
Name	RELAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGMEDIAAUTH

Attribute	**Description**
Name	CHGMEDIAAUTH
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / Y,N

BRNMOVAUTH

Attribute	**Description**
Name	BRNMOVAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

HLDAUTH

Attribute	**Description**
Name	HLDAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TSTINPAUTH

Attribute	**Description**
Name	TSTINPAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGADDRAUTH

Attribute	**Description**
Name	CHGADDRAUTH
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / Y,N

REINSAUTH

Attribute	**Description**
Name	REINSAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGPRIORAUTH

Attribute	**Description**
Name	CHGPRIORAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

GEN

Attribute	**Description**
Name	GEN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TSTCHK

Attribute	**Description**
Name	TSTCHK
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / Y,N

LNKCONT

Attribute	**Description**
Name	LNKCONT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGBRNIN

Attribute	**Description**
Name	CHGBRNIN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMSG

Attribute	**Description**
Name	CHGMSG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGFORCRELFUND

Attribute	**Description**
Name	CHGFORCRELFUND
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

SUPPRESS

Attribute	**Description**
Name	SUPPRESS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

DELMSG

Attribute	**Description**
Name	DELMSG
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

PRNT

Attribute	**Description**
Name	PRNT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

FTUPL

Attribute	**Description**
Name	FTUPL
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / Y,N

MOVQ

Attribute	**Description**
Name	MOVQ
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGADDRIN

Attribute	**Description**
Name	CHGADDRIN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMSGAUTH

Attribute	**Description**
Name	CHGMSGAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

AUTHRGHTS

Attribute	**Description**
Name	AUTHRGHTS
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGFORCCOVMATCH

Attribute	**Description**
Name	CHGFORCCOVMATCH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

QUEUERIGHTS

Attribute	**Description**
Name	QUEUERIGHTS
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

QUEUE

Attribute	**Description**
Name	QUEUE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 10

RESTRICTIVEPASSWD

Attribute	**Description**
Name	RESTRICTIVEPASSWD
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

PWD

Attribute	Description
Name	PWD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

PWDID

Attribute	Description
Name	PWDID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

ROLEBRANCHLIMITS

Attribute	Description
Name	ROLEBRANCHLIMITS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

LMTCCY

Attribute	Description
Name	LMTCCY
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

BRHUSERLMT

Attribute	Description
Name	BRHUSERLMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	
	Restrictions / **Description**
	totalDigits / 22

Roledetaile

Attribute	Description
Name	Roledetaile
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

EDITABLE

Attribute	Description
Name	EDITABLE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: totalDigits / 22

CNTRLSTR

Attribute	Description
Name	CNTRLSTR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

Roledetailf

Attribute	Description
Name	Roledetailf
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ROLEID

Attribute	Description
Name	ROLEID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	8

CNTRLSTR

Attribute	Description
Name	CNTRLSTR
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

CNTRL1

Attribute	Description
Name	CNTRL1
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL10

Attribute	Description
Name	CNTRL10
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL11

Attribute	Description
Name	CNTRL11
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL12

Attribute	**Description**
Name	CNTRL12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL13

Attribute	**Description**
Name	CNTRL13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL14

Attribute	**Description**
Name	CNTRL14
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL15

Attribute	Description
Name	CNTRL15
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL16

Attribute	Description
Name	CNTRL16
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL2

Attribute	Description
Name	CNTRL2
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL3

Attribute	Description
Name	CNTRL3
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL4

Attribute	**Description**
Name	CNTRL4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL5

Attribute	**Description**
Name	CNTRL5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL6

Attribute	**Description**
Name	CNTRL6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL7

Attribute	Description
Name	CNTRL7
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL8

Attribute	Description
Name	CNTRL8
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL9

Attribute	Description
Name	CNTRL9
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

ATHSTAT

Attribute	Description
Name	ATHSTAT
Datatype	String
Description	

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

BRNCHCODE

Attribute	Description
Name	BRNCHCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	150
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.13.4.SM-DeleteSMRole-Res-PK-MSG.xsd

DELETESMROLE_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

ROLEMASTER-PK

ROLEIDENTIFICATION

ROLEMASTER-IO

ROLEIDENTIFICATION

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETESMROLE_IOPK_RES

Attribute	Description
Name	DELETESMROLE_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description

Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.

Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

ROLEMASTER-PK

Attribute	Description
Name	ROLEMASTER-PK
Datatype	
Description	

ROLEIDENTIFICATION

Attribute	Description
Name	ROLEIDENTIFICATION
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

ROLEMASTER-IO

Attribute	Description
Name	ROLEMASTER-IO
Datatype	
Description	

ROLEIDENTIFICATION

Attribute	Description
Name	ROLEIDENTIFICATION
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description

Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.14.DeleteUserMaint

2.14.1.SM-DeleteUserMaint-Req-Full-MSG.xsd

DELETEUSERMAINT_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

USR-Full

STRTDATE

USRNAME

USRPWD

ENDDT

USRLANG

HOMEBRN

CUSTNO

LDAPUSR

TIMELEVEL

AUTOAUTH

USRSTAT

USRID

EXTUSRREF

USRCATEG

TILLALLOW

ACCCLSALLOW

GLALLOW

USRTXNLMT

LMTSCCY

MAXTXNAMT

MAXAUTHAMT

BRNSALLOW

PRDSALLOW

PRDSACCESALLOW

TAX_IDENTIFIER

AMOUNT_FORMAT

DATE_FORMAT

STAFFACCRESTR

DEPT_CODE

DEPT_DESC

USRML

ELCMUSER

GROUP_CODE

MULTIBRN_ACCESS

OTH_RM_CUST_ACC_ALLOW

SUPERVISOR_ID

SUPERVISOR_NAME

DASHBOARD_REQD

ALERTS_ON_HOME

REFERENCE_NO

NO_CUMULATIVE_LOGINS

NO_SUCCESSIVE_LOGINS

SCREENSAVERTIMEOUTINSECONDS

MFI_USER

F10_REQD

F11_REQD

F12_REQD

ACCESS_CONTROL

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

RESTR_PWD

- *PWD*

MSGSRIGHTS

- *GEN*
- *HLD*
- *CNL*
- *TSTINP*
- *CHGNODE*
- *CHGADDR*
- *REL*
- *REINS*
- *CHGMEDIA*
- *CHGPRIOR*
- *BRNMOV*
- *PRNT*
- *TSTCHK*
- *HLDAUTH*
- *CNLAUTH*
- *TSTINPAUTH*
- *CHGNODEAUTH*
- *CHGADDRAUTH*

RELAUTH

REINSAUTH

CHGMEDIAAUTH

BRNMOVAUTH

CHGPRIORAUTH

FTUPL

LNKCONT

MOVQ

CHGBRNIN

CHGADDRIN

AUTHRGHTS

CHGMSG

CHGMSGAUTH

CHGFORCCOVMATCH

CHANGE_FORCE_RELEASE_FUND

SUPPRESS

DELMSG

QUEUERIGHTS

QUEUE

USERTILLS

TILLID

TILLBRNCD

USERACCCLASS

ACCCLS

USERGLREST

NODEGL

USERGLEXCEPT

EXCEPLEAFGL

USERLIMITSROLE

LMTBRN

LMTSROLE

QLMTCCY

QINPLMT

QAUTHLMT

USERBRANCHES

BRNSBRN

BRNNAME

USERPRODUCTS

PRDPRDCD

PRDDESC

USERACCESSPRODUCTS

PRDACCESSPRDCD

PRDDESC

USERFUNCDISALLOW

FUNCDISALLOWFUNCID

USERROLE

ROLEBRNCD

USRROLEID

MASTERROLEDESC

USERSFUNCTIONS

USERFUNCBRNCD

USERFUNCFUNCID

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

USERFUNCSCTRL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

CONTROL15

CONTROL16

Grp-Restriction

GROUP_CODE

GROUP_DESC

Centralisation

USRROLEID

ROLDESC

Dshmst

USRID

USRNAME

Dshdet

FUNCTIONID

DESCRIPTION

SEQUENCE_NO

DBWHERECLAUSE

SHOW_IN_DASHBOARD

Where-Master

COLUMN_NAME

WHERE_CL

CONDITION

UDFDETAILS

FLDNAM

FLDVAL

DELETEUSERMAINT_FSFS_REQ

Attribute	Description
Name	DELETEUSERMAINT_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description

Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

USR-Full

Attribute	Description
Name	USR-Full
Datatype	
Description	

STRTDATE

Attribute	Description
Name	STRTDATE
Datatype	String
Description	

USRNAME

Attribute	Description
Name	USRNAME
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 35

USRPWD

Attribute	Description
Name	USRPWD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

ENDDT

Attribute	Description
Name	ENDDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

USRLANG

Attribute	Description
Name	USRLANG
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

HOMEBRN

Attribute	Description
Name	HOMEBRN
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

LDAPUSR

Attribute	Description
Name	LDAPUSR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	500

TIMELEVEL

Attribute	Description
Name	TIMELEVEL
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	9

AUTOAUTH

Attribute	Description
Name	AUTOAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

USRSTAT

Attribute	Description
Name	USRSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	E,H,D,L

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12

EXTUSRREF

Attribute	Description
Name	EXTUSRREF
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

USRCATEG

Attribute	Description
Name	USRCATEG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,B</td></tr></table>

TILLALLOW

Attribute	Description
Name	TILLALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

ACCCLSALLOW

Attribute	Description
Name	ACCCLSALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

GLALLOW

Attribute	Description
Name	GLALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

USRTXNLMT

Attribute	Description
Name	USRTXNLMT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>U,R,N</td></tr></table>

LMTSCCY

Attribute	Description
Name	LMTSCCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

MAXTXNAMT

Attribute	Description
Name	MAXTXNAMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

MAXAUTHAMT

Attribute	Description
Name	MAXAUTHAMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

BRNSALLOW

Attribute	Description
Name	BRNSALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

PRDSALLOW

Attribute	Description
Name	PRDSALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

PRDSACCESALLOW

Attribute	Description
Name	PRDSACCESALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

TAX_IDENTIFIER

Attribute	Description
Name	TAX_IDENTIFIER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

AMOUNT_FORMAT

Attribute	Description
Name	AMOUNT_FORMAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>.,,,.,,</td></tr></table>

DATE_FORMAT

Attribute	Description
Name	DATE_FORMAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M/d/yyyy</td></tr></table>

STAFFACCRESTR

Attribute	Description
Name	STAFFACCRESTR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

DEPT_CODE

Attribute	Description
Name	DEPT_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

DEPT_DESC

Attribute	Description
Name	DEPT_DESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

USRML

Attribute	Description
Name	USRML
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

ELCMUSER

Attribute	Description
Name	ELCMUSER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

GROUP_CODE

Attribute	Description
Name	GROUP_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

MULTIBRN_ACCESS

Attribute	Description
Name	MULTIBRN_ACCESS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

OTH_RM_CUST_ACC_ALLOW

Attribute	Description
Name	OTH_RM_CUST_ACC_ALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

SUPERVISOR_ID

Attribute	Description
Name	SUPERVISOR_ID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>80</td></tr></table>

SUPERVISOR_NAME

Attribute	Description
Name	SUPERVISOR_NAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

DASHBOARD_REQD

Attribute	Description
Name	DASHBOARD_REQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

ALERTS_ON_HOME

Attribute	Description
Name	ALERTS_ON_HOME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

NO_CUMULATIVE_LOGINS

Attribute	Description
Name	NO_CUMULATIVE_LOGINS
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

NO_SUCCESSIVE_LOGINS

Attribute	Description
Name	NO_SUCCESSIVE_LOGINS
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

SCREENSAVERTIMEOUTINSECONDS

Attribute	Description
Name	SCREENSAVERTIMEOUTINSECONDS
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

MFI_USER

Attribute	Description
Name	MFI_USER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

F10_REQD

Attribute	Description
Name	F10_REQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

F11_REQD

Attribute	Description
Name	F11_REQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

F12_REQD

Attribute	Description
Name	F12_REQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

ACCESS_CONTROL

Attribute	Description
Name	ACCESS_CONTROL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>U,G,B</td></tr></table>

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

RESTR_PWD

Attribute	Description
Name	RESTR_PWD
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PWD

Attribute	Description
Name	PWD
Datatype	String

Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MSGSRIGHTS

Attribute	Description
Name	MSGSRIGHTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

HLD

Attribute	Description
Name	HLD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CNL

Attribute	Description
Name	CNL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
enumeration	Y,N

TSTINP

Attribute	Description
Name	TSTINP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGNODE

Attribute	Description
Name	CHGNODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGADDR

Attribute	Description
Name	CHGADDR
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

REL

Attribute	Description
Name	REL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

REINS

Attribute	Description
Name	REINS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGMEDIA

Attribute	Description
Name	CHGMEDIA
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGPRIOR

Attribute	Description
Name	CHGPRIOR
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

BRNMOV

Attribute	Description
Name	BRNMOV
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

PRNT

Attribute	Description
Name	PRNT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

TSTCHK

Attribute	Description
Name	TSTCHK
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

HLDAUTH

Attribute	Description
Name	HLDAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CNLAUTH

Attribute	Description
Name	CNLAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

TSTINPAUTH

Attribute	Description
Name	TSTINPAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGNODEAUTH

Attribute	Description
Name	CHGNODEAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGADDRAUTH

Attribute	Description
Name	CHGADDRAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

RELAUTH

Attribute	Description
Name	RELAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: enumeration / Y,N

REINSAUTH

Attribute	Description
Name	REINSAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMEDIAAUTH

Attribute	Description
Name	CHGMEDIAAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

BRNMOVAUTH

Attribute	Description
Name	BRNMOVAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGPRIORAUTH

Attribute	Description
Name	CHGPRIORAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	Y,N

FTUPL

Attribute	Description
Name	FTUPL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

LNKCONT

Attribute	Description
Name	LNKCONT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

MOVQ

Attribute	Description
Name	MOVQ
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGBRNIN

Attribute	Description
Name	CHGBRNIN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGADDRIN

Attribute	Description
Name	CHGADDRIN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

AUTHRGHTS

Attribute	Description
Name	AUTHRGHTS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGMSG

Attribute	Description
Name	CHGMSG
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGMSGAUTH

Attribute	Description
Name	CHGMSGAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGFORCCOVMATCH

Attribute	Description
Name	CHGFORCCOVMATCH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHANGE_FORCE_RELEASE_FUND

Attribute	Description
Name	CHANGE_FORCE_RELEASE_FUND
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

DELMSG

Attribute	Description
Name	DELMSG
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

QUEUERIGHTS

Attribute	Description
Name	QUEUERIGHTS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

QUEUE

Attribute	Description
Name	QUEUE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	10

USERTILLS

Attribute	Description
Name	USERTILLS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

TILLID

Attribute	Description
Name	TILLID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12

TILLBRNCD

Attribute	Description
Name	TILLBRNCD
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	3

USERACCCLASS

Attribute	Description
Name	USERACCCLASS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	6

USERGLREST

Attribute	Description
Name	USERGLREST
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NODEGL

Attribute	Description
Name	NODEGL
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	9

USERGLEXCEPT

Attribute	Description
Name	USERGLEXCEPT
Datatype	
Description	

Attribute	
	Attribute / **Description** minOccurs / 0 maxOccurs / unbounded

EXCEPLEAFGL

Attribute	**Description**
Name	EXCEPLEAFGL
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

USERLIMITSROLE

Attribute	**Description**
Name	USERLIMITSROLE
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

LMTBRN

Attribute	**Description**
Name	LMTBRN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 3

LMTSROLE

Attribute	**Description**
Name	LMTSROLE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

QLMTCCY

Attribute	Description
Name	QLMTCCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

QINPLMT

Attribute	Description
Name	QINPLMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

QAUTHLMT

Attribute	Description
Name	QAUTHLMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

USERBRANCHES

Attribute	Description
Name	USERBRANCHES
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRNSBRN

Attribute	Description
Name	BRNSBRN
Datatype	String

Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

USERPRODUCTS

Attribute	Description
Name	USERPRODUCTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PRDPRDCD

Attribute	Description
Name	PRDPRDCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

USERACCESSPRODUCTS

Attribute	Description
Name	USERACCESSPRODUCTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PRDACCESSPRDCD

Attribute	Description
Name	PRDACCESSPRDCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

USERFUNCDISALLOW

Attribute	Description
Name	USERFUNCDISALLOW
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FUNCDISALLOWFUNCID

Attribute	Description
Name	FUNCDISALLOWFUNCID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

USERROLE

Attribute	Description
Name	USERROLE
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ROLEBRNCD

Attribute	Description
Name	ROLEBRNCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

USRROLEID

Attribute	Description
Name	USRROLEID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

MASTERROLEDESC

Attribute	Description
Name	MASTERROLEDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>45</td></tr></table>

USERSFUNCTIONS

Attribute	Description
Name	USERSFUNCTIONS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

USERFUNCBRNCD

Attribute	Description
Name	USERFUNCBRNCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

USERFUNCFUNCID

Attribute	Description
Name	USERFUNCFUNCID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 8

CONTROL1

Attribute	Description
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL2

Attribute	Description
Name	CONTROL2
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL3

Attribute	Description
Name	CONTROL3
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** totalDigits / 22

CONTROL4

Attribute	**Description**
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL5

Attribute	**Description**
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL6

Attribute	**Description**
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL7

Attribute	**Description**
Name	CONTROL7
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: totalDigits / 22

CONTROL8

Attribute	**Description**
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL9

Attribute	**Description**
Name	CONTROL9
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

USERFUNCSCTRL10

Attribute	**Description**
Name	USERFUNCSCTRL10
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL11

Attribute	**Description**
Name	CONTROL11
Datatype	Decimal
Description	

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL12

Attribute	Description
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL13

Attribute	Description
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL14

Attribute	Description
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL15

Attribute	Description
Name	CONTROL15
Datatype	Decimal
Description	

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

Grp-Restriction

Attribute	Description
Name	Grp-Restriction
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

GROUP_CODE

Attribute	Description
Name	GROUP_CODE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	40

GROUP_DESC

Attribute	Description
Name	GROUP_DESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255

Centralisation

Attribute	Description
Name	Centralisation
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

USRROLEID

Attribute	Description
Name	USRROLEID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	15

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

Dshmst

Attribute	Description
Name	Dshmst
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

USRNAME

Attribute	**Description**
Name	USRNAME
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

Dshdet

Attribute	**Description**
Name	Dshdet
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

DESCRIPTION

Attribute	**Description**
Name	DESCRIPTION
Datatype	String
Description	

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1000

SEQUENCE_NO

Attribute	Description
Name	SEQUENCE_NO
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	22

DBWHERECLAUSE

Attribute	Description
Name	DBWHERECLAUSE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	4000

SHOW_IN_DASHBOARD

Attribute	Description
Name	SHOW_IN_DASHBOARD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

Where-Master

Attribute	Description
Name	Where-Master
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

COLUMN_NAME

Attribute	Description

Name	COLUMN_NAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

WHERE_CL

Attribute	**Description**
Name	WHERE_CL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 500

CONDITION

Attribute	**Description**
Name	CONDITION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	Indicates Field Name

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.14.2.SM-DeleteUserMaint-Req-IO-MSG.xsd

DELETEUSERMAINT_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

USR-IO

USRID

DELETEUSERMAINT_IOPK_REQ

Attribute	Description
Name	DELETEUSERMAINT_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String

Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.

Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

USR-IO

Attribute	Description
Name	USR-IO
Datatype	
Description	

USRID

Attribute	Description

Name	USRID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

2.14.3.SM-DeleteUserMaint-Res-Full-MSG.xsd

DELETEUSERMAINT_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

USR-Full

STRTDATE

USRNAME

USRPWD

ENDDT

USRLANG

HOMEBRN

CUSTNO

LDAPUSR

TIMELEVEL

AUTOAUTH

USRSTAT

USRID

EXTUSRREF

USRCATEG

TILLALLOW

ACCCLSALLOW

GLALLOW

USRTXNLMT

LMTSCCY

MAXTXNAMT

MAXAUTHAMT

BRNSALLOW

PRDSALLOW

PRDSACCESALLOW

TAX_IDENTIFIER

AMOUNT_FORMAT

DATE_FORMAT

STAFFACCRESTR

DEPT_CODE

DEPT_DESC

USRML

ELCMUSER

GROUP_CODE

MULTIBRN_ACCESS

OTH_RM_CUST_ACC_ALLOW

SUPERVISOR_ID

SUPERVISOR_NAME

DASHBOARD_REQD

ALERTS_ON_HOME

REFERENCE_NO

NO_CUMULATIVE_LOGINS

NO_SUCCESSIVE_LOGINS

SCREENSAVERTIMEOUTINSECONDS

MFI_USER

F10_REQD

F11_REQD

F12_REQD

ACCESS_CONTROL

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

RESTR_PWD

- *PWD*

MSGSRIGHTS

- *GEN*
- *HLD*
- *CNL*
- *TSTINP*
- *CHGNODE*
- *CHGADDR*
- *REL*
- *REINS*

CHGMEDIA

CHGPRIOR

BRNMOV

PRNT

TSTCHK

HLDAUTH

CNLAUTH

TSTINPAUTH

CHGNODEAUTH

CHGADDRAUTH

RELAUTH

REINSAUTH

CHGMEDIAAUTH

BRNMOVAUTH

CHGPRIORAUTH

FTUPL

LNKCONT

MOVQ

CHGBRNIN

CHGADDRIN

AUTHRGHTS

CHGMSG

CHGMSGAUTH

CHGFORCCOVMATCH

CHANGE_FORCE_RELEASE_FUND

SUPPRESS

DELMSG

QUEUERIGHTS

QUEUE

USERTILLS

TILLID

TILLBRNCD

USERACCCLASS

ACCCLS

USERGLREST

NODEGL

USERGLEXCEPT

EXCEPLEAFGL

USERLIMITSROLE

LMTBRN

LMTSROLE

QLMTCCY

QINPLMT

QAUTHLMT

USERBRANCHES

BRNSBRN

BRNNAME

USERPRODUCTS

PRDPRDCD

PRDDESC

USERACCESSPRODUCTS

PRDACCESSPRDCD

PRDDESC

USERFUNCDISALLOW

FUNCDISALLOWFUNCID

USERROLE

ROLEBRNCD

USRROLEID

MASTERROLEDESC

USERSFUNCTIONS

USERFUNCBRNCD

USERFUNCFUNCID

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

USERFUNCSCTRL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

CONTROL15

CONTROL16

Grp-Restriction

GROUP_CODE

GROUP_DESC

Centralisation

USRROLEID

ROLDESC

Dshmst

USRID

USRNAME

Dshdet

FUNCTIONID

DESCRIPTION

SEQUENCE_NO

DBWHERECLAUSE

SHOW_IN_DASHBOARD

Where-Master

COLUMN_NAME

WHERE_CL

CONDITION

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETEUSERMAINT_FSFS_RES

Attribute	Description
Name	DELETEUSERMAINT_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	

USR-Full

Attribute	**Description**

Name	USR-Full
Datatype	
Description	

STRTDATE

Attribute	Description
Name	STRTDATE
Datatype	String
Description	

USRNAME

Attribute	Description
Name	USRNAME
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 35

USRPWD

Attribute	Description
Name	USRPWD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

ENDDT

Attribute	Description
Name	ENDDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

USRLANG

Attribute	Description
Name	USRLANG
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

HOMEBRN

Attribute	Description
Name	HOMEBRN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

LDAPUSR

Attribute	Description
Name	LDAPUSR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 500

TIMELEVEL

Attribute	Description
Name	TIMELEVEL
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 9

AUTOAUTH

Attribute	Description
Name	AUTOAUTH
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

USRSTAT

Attribute	**Description**
Name	USRSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,H,D,L

USRID

Attribute	**Description**
Name	USRID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12

EXTUSRREF

Attribute	**Description**
Name	EXTUSRREF
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

USRCATEG

Attribute	**Description**
Name	USRCATEG
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	
	Restrictions / **Description**: enumeration / S,B

TILLALLOW

Attribute	Description
Name	TILLALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

ACCCLSALLOW

Attribute	Description
Name	ACCCLSALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

GLALLOW

Attribute	Description
Name	GLALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

USRTXNLMT

Attribute	Description
Name	USRTXNLMT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	U,R,N

LMTSCCY

Attribute	Description
Name	LMTSCCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

MAXTXNAMT

Attribute	Description
Name	MAXTXNAMT
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

MAXAUTHAMT

Attribute	Description
Name	MAXAUTHAMT
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

BRNSALLOW

Attribute	Description
Name	BRNSALLOW
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: enumeration / A,D

PRDSALLOW

Attribute	Description
Name	PRDSALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

PRDSACCESALLOW

Attribute	Description
Name	PRDSACCESALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TAX_IDENTIFIER

Attribute	Description
Name	TAX_IDENTIFIER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

AMOUNT_FORMAT

Attribute	Description
Name	AMOUNT_FORMAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	.,,,.,,

DATE_FORMAT

Attribute	Description
Name	DATE_FORMAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	M/d/yyyy

STAFFACCRESTR

Attribute	Description
Name	STAFFACCRESTR
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

DEPT_CODE

Attribute	Description
Name	DEPT_CODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

DEPT_DESC

Attribute	Description
Name	DEPT_DESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	50

USRML

Attribute	Description
Name	USRML
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	50

ELCMUSER

Attribute	Description
Name	ELCMUSER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

GROUP_CODE

Attribute	Description
Name	GROUP_CODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	A,D

MULTIBRN_ACCESS

Attribute	Description
Name	MULTIBRN_ACCESS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: enumeration / Y,N

OTH_RM_CUST_ACC_ALLOW

Attribute	Description
Name	OTH_RM_CUST_ACC_ALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

SUPERVISOR_ID

Attribute	Description
Name	SUPERVISOR_ID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 80

SUPERVISOR_NAME

Attribute	Description
Name	SUPERVISOR_NAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

DASHBOARD_REQD

Attribute	Description
Name	DASHBOARD_REQD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	Y,N

ALERTS_ON_HOME

Attribute	Description
Name	ALERTS_ON_HOME
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

NO_CUMULATIVE_LOGINS

Attribute	Description
Name	NO_CUMULATIVE_LOGINS
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

NO_SUCCESSIVE_LOGINS

Attribute	Description
Name	NO_SUCCESSIVE_LOGINS
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

SCREENSAVERTIMEOUTINSECONDS

Attribute	Description
Name	SCREENSAVERTIMEOUTINSECONDS
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

MFI_USER

Attribute	Description
Name	MFI_USER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

F10_REQD

Attribute	Description
Name	F10_REQD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

F11_REQD

Attribute	Description
Name	F11_REQD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

F12_REQD

Attribute	Description
Name	F12_REQD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

ACCESS_CONTROL

Attribute	Description
Name	ACCESS_CONTROL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	U,G,B

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: maxLength / 35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	1

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

RESTR_PWD

Attribute	Description
Name	RESTR_PWD
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PWD

Attribute	Description
Name	PWD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12

MSGSRIGHTS

Attribute	Description
Name	MSGSRIGHTS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

HLD

Attribute	Description
Name	HLD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CNL

Attribute	Description
Name	CNL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TSTINP

Attribute	Description
Name	TSTINP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGNODE

Attribute	Description
Name	CHGNODE
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / Y,N

CHGADDR

Attribute	**Description**
Name	CHGADDR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

REL

Attribute	**Description**
Name	REL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

REINS

Attribute	**Description**
Name	REINS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMEDIA

Attribute	**Description**
Name	CHGMEDIA
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGPRIOR

Attribute	Description
Name	CHGPRIOR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

BRNMOV

Attribute	Description
Name	BRNMOV
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

PRNT

Attribute	Description
Name	PRNT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TSTCHK

Attribute	Description
Name	TSTCHK
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / Y,N

HLDAUTH

Attribute	**Description**
Name	HLDAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CNLAUTH

Attribute	**Description**
Name	CNLAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TSTINPAUTH

Attribute	**Description**
Name	TSTINPAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGNODEAUTH

Attribute	**Description**
Name	CHGNODEAUTH
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGADDRAUTH

Attribute	Description
Name	CHGADDRAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

RELAUTH

Attribute	Description
Name	RELAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

REINSAUTH

Attribute	Description
Name	REINSAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGMEDIAAUTH

Attribute	Description
Name	CHGMEDIAAUTH
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

BRNMOVAUTH

Attribute	**Description**
Name	BRNMOVAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGPRIORAUTH

Attribute	**Description**
Name	CHGPRIORAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

FTUPL

Attribute	**Description**
Name	FTUPL
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

LNKCONT

Attribute	**Description**
Name	LNKCONT
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / Y,N

MOVQ

Attribute	**Description**
Name	MOVQ
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGBRNIN

Attribute	**Description**
Name	CHGBRNIN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGADDRIN

Attribute	**Description**
Name	CHGADDRIN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

AUTHRGHTS

Attribute	**Description**
Name	AUTHRGHTS
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

CHGMSG

Attribute	**Description**
Name	CHGMSG
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGMSGAUTH

Attribute	**Description**
Name	CHGMSGAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGFORCCOVMATCH

Attribute	**Description**
Name	CHGFORCCOVMATCH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHANGE_FORCE_RELEASE_FUND

Attribute	**Description**
Name	CHANGE_FORCE_RELEASE_FUND
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

SUPPRESS

Attribute	**Description**
Name	SUPPRESS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

DELMSG

Attribute	**Description**
Name	DELMSG
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

QUEUERIGHTS

Attribute	**Description**
Name	QUEUERIGHTS
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

QUEUE

Attribute	**Description**
Name	QUEUE
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	10

USERTILLS

Attribute	Description
Name	USERTILLS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

TILLID

Attribute	Description
Name	TILLID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12

TILLBRNCD

Attribute	Description
Name	TILLBRNCD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

USERACCCLASS

Attribute	Description
Name	USERACCCLASS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	6

USERGLREST

Attribute	Description
Name	USERGLREST
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NODEGL

Attribute	Description
Name	NODEGL
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	9

USERGLEXCEPT

Attribute	Description
Name	USERGLEXCEPT
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

EXCEPLEAFGL

Attribute	Description
Name	EXCEPLEAFGL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

USERLIMITSROLE

Attribute	Description
Name	USERLIMITSROLE
Datatype	

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

LMTBRN

Attribute	Description
Name	LMTBRN
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

LMTSROLE

Attribute	Description
Name	LMTSROLE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

QLMTCCY

Attribute	Description
Name	QLMTCCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

QINPLMT

Attribute	Description
Name	QINPLMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22

QAUTHLMT

Attribute	Description
Name	QAUTHLMT
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

USERBRANCHES

Attribute	Description
Name	USERBRANCHES
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

BRNSBRN

Attribute	Description
Name	BRNSBRN
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

USERPRODUCTS

Attribute	Description

Name	USERPRODUCTS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PRDPRDCD

Attribute	Description
Name	PRDPRDCD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	4

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

USERACCESSPRODUCTS

Attribute	Description
Name	USERACCESSPRODUCTS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PRDACCESSPRDCD

Attribute	Description
Name	PRDACCESSPRDCD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	4

PRDDESC

Attribute	Description

Name	PRDDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

USERFUNCDISALLOW

Attribute	**Description**
Name	USERFUNCDISALLOW
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FUNCDISALLOWFUNCID

Attribute	**Description**
Name	FUNCDISALLOWFUNCID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 8

USERROLE

Attribute	**Description**
Name	USERROLE
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ROLEBRNCD

Attribute	**Description**
Name	ROLEBRNCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

USRROLEID

Attribute	**Description**

Name	USRROLEID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

MASTERROLEDESC

Attribute	**Description**
Name	MASTERROLEDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 45

USERSFUNCTIONS

Attribute	**Description**
Name	USERSFUNCTIONS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

USERFUNCBRNCD

Attribute	**Description**
Name	USERFUNCBRNCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

USERFUNCFUNCID

Attribute	**Description**
Name	USERFUNCFUNCID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 8

CONTROL1

Attribute	**Description**

Name	CONTROL1
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL2

Attribute	**Description**
Name	CONTROL2
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL3

Attribute	**Description**
Name	CONTROL3
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL4

Attribute	**Description**
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL5

Attribute	**Description**

Name	CONTROL5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL6

Attribute	**Description**
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL7

Attribute	**Description**
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL8

Attribute	**Description**
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL9

Attribute	**Description**

Name	CONTROL9
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

USERFUNCSCTRL10

Attribute	**Description**
Name	USERFUNCSCTRL10
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL11

Attribute	**Description**
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL12

Attribute	**Description**
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL13

Attribute	**Description**

Name	CONTROL13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL14

Attribute	**Description**
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL15

Attribute	**Description**
Name	CONTROL15
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL16

Attribute	**Description**
Name	CONTROL16
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

Grp-Restriction

Attribute	**Description**

Name	Grp-Restriction
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

GROUP_CODE

Attribute	Description
Name	GROUP_CODE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	40

GROUP_DESC

Attribute	Description
Name	GROUP_DESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255

Centralisation

Attribute	Description
Name	Centralisation
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

USRROLEID

Attribute	Description
Name	USRROLEID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	15

ROLDESC

Attribute	Description

Name	ROLDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

Dshmst

Attribute	**Description**
Name	Dshmst
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

USRID

Attribute	**Description**
Name	USRID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

USRNAME

Attribute	**Description**
Name	USRNAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

Dshdet

Attribute	**Description**
Name	Dshdet
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1000

SEQUENCE_NO

Attribute	Description
Name	SEQUENCE_NO
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	22

DBWHERECLAUSE

Attribute	Description
Name	DBWHERECLAUSE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	4000

SHOW_IN_DASHBOARD

Attribute	Description

Name	SHOW_IN_DASHBOARD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

Where-Master

Attribute	**Description**
Name	Where-Master
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

COLUMN_NAME

Attribute	**Description**
Name	COLUMN_NAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

WHERE_CL

Attribute	**Description**
Name	WHERE_CL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 500

CONDITION

Attribute	**Description**
Name	CONDITION
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150; minLength / 0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String

Description	

2.14.4.SM-DeleteUserMaint-Res-PK-MSG.xsd

DELETEUSERMAINT_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

USR-PK

USRID

USR-IO

USRID

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETEUSERMAINT_IOPK_RES

Attribute	Description
Name	DELETEUSERMAINT_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

USR-PK

Attribute	Description
Name	USR-PK
Datatype	
Description	

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

USR-IO

Attribute	Description
Name	USR-IO
Datatype	
Description	

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.15.ModifySMDBANKP

2.15.1.SM-ModifySMDBANKP-Req-Full-MSG.xsd

MODIFYSMDBANKP_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Parameters-Full

HEAD_OFFICE

SITE_CODE

ACTIVATION_KEY

INVALID_LOGINS_CUM

INVALID_LOGINS_SUC

PWD_PREVENT_REUSE

PWD_CHANGE_AFTER

MAXIMUM

MINIMUM

PWD_EXPIRY_MSG_DAYS

ARCHIVAL_PERIOD

CONCHAR_PWD_NUM

FREQ_PWD_CHG

MIN_PWD_NUMERIC_LENGTH

LEGAL_NOTICE

DORMANCY_DAYS

DISPLAY_LEGAL_NOTICE

MIN_SPECIALCHAR_LENGTH

MIN_LOWERCASE_CHAR

MIN_UPPERCASE_CHAR

SCREENSAVERREQUIRED

SCREENSAVERTIMEOUTINSECONDS

SCREENSAVERMODIFIABLEBYUSER

PASSWORDEXTERNAL

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Smtbs-Branch-Restr

RESTR_TYPE

DESCRIPTION

Smtbs-Restrictive-Passwd

PASSWORD

UDFDETAILS

FLDNAM

FLDVAL

MODIFYSMDBANKP_FSFS_REQ

Attribute	Description
Name	MODIFYSMDBANKP_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Parameters-Full

Attribute	Description
Name	Smtbs-Parameters-Full
Datatype	
Description	

HEAD_OFFICE

Attribute	Description
Name	HEAD_OFFICE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

SITE_CODE

Attribute	Description
Name	SITE_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

ACTIVATION_KEY

Attribute	Description
Name	ACTIVATION_KEY
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 24

INVALID_LOGINS_CUM

Attribute	**Description**
Name	INVALID_LOGINS_CUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 6; maxInclusive / 99

INVALID_LOGINS_SUC

Attribute	**Description**
Name	INVALID_LOGINS_SUC
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 1; minInclusive / 3; maxInclusive / 5

PWD_PREVENT_REUSE

Attribute	**Description**
Name	PWD_PREVENT_REUSE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

PWD_CHANGE_AFTER

Attribute	Description
Name	PWD_CHANGE_AFTER
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>3</td></tr><tr><td>minInclusive</td><td>15</td></tr><tr><td>maxInclusive</td><td>180</td></tr></table>

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>12</td></tr><tr><td>maxInclusive</td><td>30</td></tr></table>

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>6</td></tr><tr><td>maxInclusive</td><td>11</td></tr></table>

PWD_EXPIRY_MSG_DAYS

Attribute	Description
Name	PWD_EXPIRY_MSG_DAYS
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1
maxInclusive	5

ARCHIVAL_PERIOD

Attribute	Description
Name	ARCHIVAL_PERIOD
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	3

CONCHAR_PWD_NUM

Attribute	Description
Name	CONCHAR_PWD_NUM
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2

FREQ_PWD_CHG

Attribute	Description
Name	FREQ_PWD_CHG
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	0

MIN_PWD_NUMERIC_LENGTH

Attribute	Description
Name	MIN_PWD_NUMERIC_LENGTH
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

LEGAL_NOTICE

Attribute	**Description**
Name	LEGAL_NOTICE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

DORMANCY_DAYS

Attribute	**Description**
Name	DORMANCY_DAYS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

DISPLAY_LEGAL_NOTICE

Attribute	**Description**
Name	DISPLAY_LEGAL_NOTICE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

MIN_SPECIALCHAR_LENGTH

Attribute	**Description**
Name	MIN_SPECIALCHAR_LENGTH

Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

MIN_LOWERCASE_CHAR

Attribute	**Description**
Name	MIN_LOWERCASE_CHAR
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

MIN_UPPERCASE_CHAR

Attribute	**Description**
Name	MIN_UPPERCASE_CHAR
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

SCREENSAVERREQUIRED

Attribute	**Description**
Name	SCREENSAVERREQUIRED
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

SCREENSAVERTIMEOUTINSECONDS

Attribute	Description
Name	SCREENSAVERTIMEOUTINSECONDS
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

SCREENSAVERMODIFIABLEBYUSER

Attribute	Description
Name	SCREENSAVERMODIFIABLEBYUSER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

PASSWORDEXTERNAL

Attribute	Description
Name	PASSWORDEXTERNAL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Smtbs-Branch-Restr

Attribute	Description
Name	Smtbs-Branch-Restr
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

RESTR_TYPE

Attribute	Description
Name	RESTR_TYPE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

Smtbs-Restrictive-Passwd

Attribute	Description
Name	Smtbs-Restrictive-Passwd
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description

Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150; minLength / 0

2.15.2.SM-ModifySMDBANKP-Req-IO-MSG.xsd

MODIFYSMDBANKP_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Parameters-IO

SITE_CODE

INVALID_LOGINS_CUM

INVALID_LOGINS_SUC

PWD_PREVENT_REUSE

PWD_CHANGE_AFTER

MAXIMUM

MINIMUM

PWD_EXPIRY_MSG_DAYS

ARCHIVAL_PERIOD

CONCHAR_PWD_NUM

FREQ_PWD_CHG

MIN_PWD_NUMERIC_LENGTH

LEGAL_NOTICE

DORMANCY_DAYS

DISPLAY_LEGAL_NOTICE

MIN_SPECIALCHAR_LENGTH

MIN_LOWERCASE_CHAR

MIN_UPPERCASE_CHAR

SCREENSAVERREQUIRED

SCREENSAVERTIMEOUTINSECONDS

SCREENSAVERMODIFIABLEBYUSER

PASSWORDEXTERNAL

MAKER

MAKERSTAMP

Smtbs-Branch-Restr

- *RESTR_TYPE*
- *DESCRIPTION*

Smtbs-Restrictive-Passwd

- *PASSWORD*

UDFDETAILS

- *FLDNAM*
- *FLDVAL*

MODIFYSMDBANKP_IOPK_REQ

Attribute	Description
Name	MODIFYSMDBANKP_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description**: minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL

Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Parameters-IO

Attribute	Description
Name	Smtbs-Parameters-IO
Datatype	
Description	

SITE_CODE

Attribute	Description
Name	SITE_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

INVALID_LOGINS_CUM

Attribute	Description

Name	INVALID_LOGINS_CUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 6; maxInclusive / 99

INVALID_LOGINS_SUC

Attribute	**Description**
Name	INVALID_LOGINS_SUC
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 1; minInclusive / 3; maxInclusive / 5

PWD_PREVENT_REUSE

Attribute	**Description**
Name	PWD_PREVENT_REUSE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

PWD_CHANGE_AFTER

Attribute	**Description**
Name	PWD_CHANGE_AFTER
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	3
minInclusive	15
maxInclusive	180

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	12
maxInclusive	30

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	6
maxInclusive	11

PWD_EXPIRY_MSG_DAYS

Attribute	Description
Name	PWD_EXPIRY_MSG_DAYS
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1
maxInclusive	5

ARCHIVAL_PERIOD

Attribute	Description
Name	ARCHIVAL_PERIOD
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>3</td></tr></table>

CONCHAR_PWD_NUM

Attribute	Description
Name	CONCHAR_PWD_NUM
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>2</td></tr></table>

FREQ_PWD_CHG

Attribute	Description
Name	FREQ_PWD_CHG
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>0</td></tr></table>

MIN_PWD_NUMERIC_LENGTH

Attribute	Description
Name	MIN_PWD_NUMERIC_LENGTH
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>1</td></tr></table>

LEGAL_NOTICE

Attribute	Description
Name	LEGAL_NOTICE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

DORMANCY_DAYS

Attribute	Description
Name	DORMANCY_DAYS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

DISPLAY_LEGAL_NOTICE

Attribute	Description
Name	DISPLAY_LEGAL_NOTICE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

MIN_SPECIALCHAR_LENGTH

Attribute	Description
Name	MIN_SPECIALCHAR_LENGTH
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

MIN_LOWERCASE_CHAR

Attribute	Description
Name	MIN_LOWERCASE_CHAR
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

MIN_UPPERCASE_CHAR

Attribute	Description
Name	MIN_UPPERCASE_CHAR
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

SCREENSAVERREQUIRED

Attribute	Description
Name	SCREENSAVERREQUIRED
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

SCREENSAVERTIMEOUTINSECONDS

Attribute	Description
Name	SCREENSAVERTIMEOUTINSECONDS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	4

SCREENSAVERMODIFIABLEBYUSER

Attribute	Description
Name	SCREENSAVERMODIFIABLEBYUSER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

PASSWORDEXTERNAL

Attribute	Description
Name	PASSWORDEXTERNAL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

Smtbs-Branch-Restr

Attribute	Description
Name	Smtbs-Branch-Restr
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

RESTR_TYPE

Attribute	Description
Name	RESTR_TYPE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255

Smtbs-Restrictive-Passwd

Attribute	Description
Name	Smtbs-Restrictive-Passwd
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.15.3.SM-ModifySMDBANKP-Res-Full-MSG.xsd

MODIFYSMDBANKP_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Parameters-Full

HEAD_OFFICE

SITE_CODE

ACTIVATION_KEY

INVALID_LOGINS_CUM

INVALID_LOGINS_SUC

PWD_PREVENT_REUSE

PWD_CHANGE_AFTER

MAXIMUM

MINIMUM

PWD_EXPIRY_MSG_DAYS

ARCHIVAL_PERIOD

CONCHAR_PWD_NUM

FREQ_PWD_CHG

MIN_PWD_NUMERIC_LENGTH

LEGAL_NOTICE

DORMANCY_DAYS

DISPLAY_LEGAL_NOTICE

MIN_SPECIALCHAR_LENGTH

MIN_LOWERCASE_CHAR

MIN_UPPERCASE_CHAR

SCREENSAVERREQUIRED

SCREENSAVERTIMEOUTINSECONDS

SCREENSAVERMODIFIABLEBYUSER

PASSWORDEXTERNAL

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Smtbs-Branch-Restr

RESTR_TYPE

DESCRIPTION

Smtbs-Restrictive-Passwd

PASSWORD

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYSMDBANKP_FSFS_RES

Attribute	Description
Name	MODIFYSMDBANKP_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Parameters-Full

Attribute	Description
Name	Smtbs-Parameters-Full
Datatype	
Description	

HEAD_OFFICE

Attribute	Description
Name	HEAD_OFFICE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	3

SITE_CODE

Attribute	Description
Name	SITE_CODE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	4

ACTIVATION_KEY

Attribute	Description
Name	ACTIVATION_KEY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	24

INVALID_LOGINS_CUM

Attribute	Description
Name	INVALID_LOGINS_CUM
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	6
maxInclusive	99

INVALID_LOGINS_SUC

Attribute	Description
Name	INVALID_LOGINS_SUC
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	1
minInclusive	3
maxInclusive	5

PWD_PREVENT_REUSE

Attribute	Description
Name	PWD_PREVENT_REUSE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1

PWD_CHANGE_AFTER

Attribute	Description
Name	PWD_CHANGE_AFTER
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	3
minInclusive	15
maxInclusive	180

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	12
maxInclusive	30

MINIMUM

Attribute	Description

Name	MINIMUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 6; maxInclusive / 11

PWD_EXPIRY_MSG_DAYS

Attribute	**Description**
Name	PWD_EXPIRY_MSG_DAYS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1; maxInclusive / 5

ARCHIVAL_PERIOD

Attribute	**Description**
Name	ARCHIVAL_PERIOD
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

CONCHAR_PWD_NUM

Attribute	**Description**
Name	CONCHAR_PWD_NUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2

FREQ_PWD_CHG

Attribute	Description
Name	FREQ_PWD_CHG
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 0

MIN_PWD_NUMERIC_LENGTH

Attribute	Description
Name	MIN_PWD_NUMERIC_LENGTH
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

LEGAL_NOTICE

Attribute	Description
Name	LEGAL_NOTICE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

DORMANCY_DAYS

Attribute	Description
Name	DORMANCY_DAYS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1

DISPLAY_LEGAL_NOTICE

Attribute	Description
Name	DISPLAY_LEGAL_NOTICE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

MIN_SPECIALCHAR_LENGTH

Attribute	Description
Name	MIN_SPECIALCHAR_LENGTH
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1

MIN_LOWERCASE_CHAR

Attribute	Description
Name	MIN_LOWERCASE_CHAR
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1

MIN_UPPERCASE_CHAR

Attribute	Description
Name	MIN_UPPERCASE_CHAR
Datatype	Decimal
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>1</td></tr></table>

SCREENSAVERREQUIRED

Attribute	Description
Name	SCREENSAVERREQUIRED
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

SCREENSAVERTIMEOUTINSECONDS

Attribute	Description
Name	SCREENSAVERTIMEOUTINSECONDS
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

SCREENSAVERMODIFIABLEBYUSER

Attribute	Description
Name	SCREENSAVERMODIFIABLEBYUSER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

PASSWORDEXTERNAL

Attribute	Description
Name	PASSWORDEXTERNAL
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Smtbs-Branch-Restr

Attribute	Description
Name	Smtbs-Branch-Restr
Datatype	

Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

RESTR_TYPE

Attribute	Description
Name	RESTR_TYPE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255

Smtbs-Restrictive-Passwd

Attribute	Description
Name	Smtbs-Restrictive-Passwd
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.15.4.SM-ModifySMDBANKP-Res-PK-MSG.xsd

MODIFYSMDBANKP_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Parameters-PK

SITE_CODE

Smtbs-Parameters-IO

SITE_CODE

INVALID_LOGINS_CUM

INVALID_LOGINS_SUC

PWD_PREVENT_REUSE

PWD_CHANGE_AFTER

MAXIMUM

MINIMUM

PWD_EXPIRY_MSG_DAYS

ARCHIVAL_PERIOD

CONCHAR_PWD_NUM

FREQ_PWD_CHG

MIN_PWD_NUMERIC_LENGTH

LEGAL_NOTICE

DORMANCY_DAYS

DISPLAY_LEGAL_NOTICE

MIN_SPECIALCHAR_LENGTH

MIN_LOWERCASE_CHAR

MIN_UPPERCASE_CHAR

SCREENSAVERREQUIRED

SCREENSAVERTIMEOUTINSECONDS

SCREENSAVERMODIFIABLEBYUSER

PASSWORDEXTERNAL

MAKER

MAKERSTAMP

Smtbs-Branch-Restr

RESTR_TYPE

DESCRIPTION

Smtbs-Restrictive-Passwd

PASSWORD

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYSMDBANKP_IOPK_RES

Attribute	Description
Name	MODIFYSMDBANKP_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description**: minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL

Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Parameters-PK

Attribute	Description
Name	Smtbs-Parameters-PK
Datatype	
Description	

SITE_CODE

Attribute	Description
Name	SITE_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

Smtbs-Parameters-IO

Attribute	Description

Name	Smtbs-Parameters-IO
Datatype	
Description	

SITE_CODE

Attribute	Description
Name	SITE_CODE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	4

INVALID_LOGINS_CUM

Attribute	Description
Name	INVALID_LOGINS_CUM
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions

Restrictions	Description
totalDigits	2
minInclusive	6
maxInclusive	99

INVALID_LOGINS_SUC

Attribute	Description
Name	INVALID_LOGINS_SUC
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions

Restrictions	Description
totalDigits	1
minInclusive	3
maxInclusive	5

PWD_PREVENT_REUSE

Attribute	Description
Name	PWD_PREVENT_REUSE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1

PWD_CHANGE_AFTER

Attribute	Description
Name	PWD_CHANGE_AFTER
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	3
minInclusive	15
maxInclusive	180

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	12
maxInclusive	30

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	6
maxInclusive	11

PWD_EXPIRY_MSG_DAYS

Attribute	Description

Name	PWD_EXPIRY_MSG_DAYS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1; maxInclusive / 5

ARCHIVAL_PERIOD

Attribute	**Description**
Name	ARCHIVAL_PERIOD
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

CONCHAR_PWD_NUM

Attribute	**Description**
Name	CONCHAR_PWD_NUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2

FREQ_PWD_CHG

Attribute	**Description**
Name	FREQ_PWD_CHG
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 0

MIN_PWD_NUMERIC_LENGTH

Attribute	Description
Name	MIN_PWD_NUMERIC_LENGTH
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>1</td></tr></table>

LEGAL_NOTICE

Attribute	Description
Name	LEGAL_NOTICE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4000</td></tr></table>

DORMANCY_DAYS

Attribute	Description
Name	DORMANCY_DAYS
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>1</td></tr></table>

DISPLAY_LEGAL_NOTICE

Attribute	Description
Name	DISPLAY_LEGAL_NOTICE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

MIN_SPECIALCHAR_LENGTH

Attribute	Description
Name	MIN_SPECIALCHAR_LENGTH
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

MIN_LOWERCASE_CHAR

Attribute	Description
Name	MIN_LOWERCASE_CHAR
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

MIN_UPPERCASE_CHAR

Attribute	Description
Name	MIN_UPPERCASE_CHAR
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

SCREENSAVERREQUIRED

Attribute	Description
Name	SCREENSAVERREQUIRED
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	Y,N

SCREENSAVERTIMEOUTINSECONDS

Attribute	Description
Name	SCREENSAVERTIMEOUTINSECONDS
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	4

SCREENSAVERMODIFIABLEBYUSER

Attribute	Description
Name	SCREENSAVERMODIFIABLEBYUSER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

PASSWORDEXTERNAL

Attribute	Description
Name	PASSWORDEXTERNAL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

Smtbs-Branch-Restr

Attribute	Description
Name	Smtbs-Branch-Restr
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

RESTR_TYPE

Attribute	Description
Name	RESTR_TYPE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	255

Smtbs-Restrictive-Passwd

Attribute	Description
Name	Smtbs-Restrictive-Passwd
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	150
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.16.ModifySMDRLMNE

2.16.1.SM-ModifySMDRLMNE-Req-Full-MSG.xsd

MODIFYSMDRLMNE_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Role-Limit-Full

ROLEID2

DESCRIPTION

LIMIT_CCY

INPUT_LIMIT

AUTHORIZATION_LIMIT

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

MODIFYSMDRLMNE_FSFS_REQ

Attribute	Description
Name	MODIFYSMDRLMNE_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Role-Limit-Full

Attribute	Description
Name	Smtbs-Role-Limit-Full
Datatype	
Description	

ROLEID2

Attribute	Description
Name	ROLEID2
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

LIMIT_CCY

Attribute	Description
Name	LIMIT_CCY
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	3

INPUT_LIMIT

Attribute	Description
Name	INPUT_LIMIT
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0

AUTHORIZATION_LIMIT

Attribute	Description
Name	AUTHORIZATION_LIMIT
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.16.2.SM-ModifySMDRLMNE-Req-IO-MSG.xsd

MODIFYSMDRLMNE_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Role-Limit-IO

ROLEID2

DESCRIPTION

LIMIT_CCY

INPUT_LIMIT

AUTHORIZATION_LIMIT

MAKER

MAKERSTAMP

UDFDETAILS

FLDNAM

FLDVAL

Attribute	Description
Name	MODIFYSMDRLMNE_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String

Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Role-Limit-IO

Attribute	Description
Name	Smtbs-Role-Limit-IO
Datatype	
Description	

ROLEID2

Attribute	Description
Name	ROLEID2
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	
	Restrictions / **Description**: maxLength / 105

LIMIT_CCY

Attribute	Description
Name	LIMIT_CCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

INPUT_LIMIT

Attribute	Description
Name	INPUT_LIMIT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0

AUTHORIZATION_LIMIT

Attribute	Description
Name	AUTHORIZATION_LIMIT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.16.3.SM-ModifySMDRLMNE-Res-Full-MSG.xsd

MODIFYSMDRLMNE_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Role-Limit-Full

ROLEID2

DESCRIPTION

LIMIT_CCY

INPUT_LIMIT

AUTHORIZATION_LIMIT

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYSMDRLMNE_FSFS_RES

Attribute	Description
Name	MODIFYSMDRLMNE_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Role-Limit-Full

Attribute	Description
Name	Smtbs-Role-Limit-Full
Datatype	
Description	

ROLEID2

Attribute	Description
Name	ROLEID2
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

LIMIT_CCY

Attribute	Description
Name	LIMIT_CCY
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	3

INPUT_LIMIT

Attribute	Description
Name	INPUT_LIMIT
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0

AUTHORIZATION_LIMIT

Attribute	Description
Name	AUTHORIZATION_LIMIT
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.16.4.SM-ModifySMDRLMNE-Res-PK-MSG.xsd

MODIFYSMDRLMNE_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Role-Limit-PK

ROLEID2

Smtbs-Role-Limit-IO

ROLEID2

DESCRIPTION

LIMIT_CCY

INPUT_LIMIT

AUTHORIZATION_LIMIT

MAKER

MAKERSTAMP

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYSMDRLMNE_IOPK_RES

Attribute	Description
Name	MODIFYSMDRLMNE_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description

Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String

Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Role-Limit-PK

Attribute	Description
Name	Smtbs-Role-Limit-PK
Datatype	
Description	

ROLEID2

Attribute	Description
Name	ROLEID2
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

Smtbs-Role-Limit-IO

Attribute	Description
Name	Smtbs-Role-Limit-IO
Datatype	
Description	

ROLEID2

Attribute	Description
Name	ROLEID2
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

LIMIT_CCY

Attribute	Description
Name	LIMIT_CCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

INPUT_LIMIT

Attribute	Description
Name	INPUT_LIMIT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr></table>

AUTHORIZATION_LIMIT

Attribute	Description
Name	AUTHORIZATION_LIMIT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr></table>

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150; minLength / 0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String

Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.17.ModifySMRole

2.17.1.SM-ModifySMRole-Req-Full-MSG.xsd

MODIFYSMROLE_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

ROLEMASTER-Full

ROLEIDENTIFICATION

MASTERROLEDESC

AUTHORISERROLE

BRANCH_RES

ACCCLASSALLOWED

CENTRALISATIONROLE

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

ROLEDETAIL

- *ROLEFUN*
- *CONTROL1*
- *CONTROL2*
- *CONTROL3*
- *CONTROL4*
- *CONTROL5*
- *CONTROL6*
- *CONTROL7*
- *CONTROL8*
- *CONTROL9*
- *CONTROL10*
- *CONTROL11*
- *CONTROL12*
- *CONTROL13*
- *CONTROL14*
- *CONTROL15*
- *CONTROL16*

ROLEDETAILB

- *ROLEFUN*

CONT1

CONT2

CONT3

CONT4

CONT5

CONT6

CONTROL7

CONT8

CONT9

CONT10

CONT11

CONT12

CONT13

CONT14

CONT15

CONTROL16

ROLEDETAILC

ROLEFUN

CNTRL1

CNTRL2

CNTRL3

CNTRL4

CNTRL5

CNTRL6

CNTRL7

CNTRL8

CNTRL9

CNTRL10

CNTRL11

CNTRL12

CNTRL13

CNTRL14

CNTRL15

CNTRL16

ROLEDETAILD

ROLEFUN

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

CONTROL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

CNTRL15

CNTRL16

ROLEBRANCHES

BRANCH

BRNNAME

ROLEACCCLASS

ACCCLS

DESCRIPTION

MSGCRIGHTS

CNL

CHGNODE

REL

CHGMEDIA

BRNMOV

HLD

TSTINP

CHGADDR

REINS

CHGPRIOR

CNLAUTH

CHGNODEAUTH

RELAUTH

CHGMEDIAAUTH

BRNMOVAUTH

HLDAUTH

TSTINPAUTH

CHGADDRAUTH

REINSAUTH

CHGPRIORAUTH

GEN

TSTCHK

LNKCONT

CHGBRNIN

CHGMSG

CHGFORCRELFUND

SUPPRESS

DELMSG

PRNT

FTUPL

MOVQ

CHGADDRIN

CHGMSGAUTH

AUTHRGHTS

CHGFORCCOVMATCH

QUEUERIGHTS

QUEUE

RESTRICTIVEPASSWD

PWD

PWDID

ROLEBRANCHLIMITS

LMTCCY

BRHUSERLMT

Roledetaile

ROLEFUN

BRANCHCODE

EDITABLE

CNTRLSTR

Roledetailf

ROLEID

ROLEFUN

CNTRLSTR

CNTRL1

CNTRL10

CNTRL11

CNTRL12

CNTRL13

CNTRL14

CNTRL15

CNTRL16

CNTRL2

CNTRL3

CNTRL4

CNTRL5

CNTRL6

CNTRL7

CNTRL8

CNTRL9

ATHSTAT

BRNCHCODE

UDFDETAILS

FLDNAM

FLDVAL

MODIFYSMROLE_FSFS_REQ

Attribute	Description
Name	MODIFYSMROLE_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

ROLEMASTER-Full

Attribute	Description
Name	ROLEMASTER-Full
Datatype	
Description	

ROLEIDENTIFICATION

Attribute	Description
Name	ROLEIDENTIFICATION
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

MASTERROLEDESC

Attribute	Description
Name	MASTERROLEDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

AUTHORISERROLE

Attribute	Description
Name	AUTHORISERROLE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

BRANCH_RES

Attribute	Description
Name	BRANCH_RES
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

ACCCLASSALLOWED

Attribute	Description
Name	ACCCLASSALLOWED
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

CENTRALISATIONROLE

Attribute	Description
Name	CENTRALISATIONROLE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

ROLEDETAIL

Attribute	Description
Name	ROLEDETAIL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

CONTROL1

Attribute	Description
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL2

Attribute	Description
Name	CONTROL2
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL3

Attribute	Description
Name	CONTROL3
Datatype	Decimal

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL4

Attribute	Description
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL5

Attribute	Description
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL6

Attribute	Description
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL8

Attribute	Description
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL9

Attribute	Description
Name	CONTROL9
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL10

Attribute	Description
Name	CONTROL10
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL11

Attribute	**Description**
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL12

Attribute	**Description**
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL13

Attribute	**Description**
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL14

Attribute	Description
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL15

Attribute	Description
Name	CONTROL15
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

ROLEDETAILB

Attribute	Description
Name	ROLEDETAILB
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	8

CONT1

Attribute	Description
Name	CONT1
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT2

Attribute	Description
Name	CONT2
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT3

Attribute	Description
Name	CONT3
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT4

Attribute	**Description**
Name	CONT4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT5

Attribute	**Description**
Name	CONT5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT6

Attribute	**Description**
Name	CONT6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONT8

Attribute	Description
Name	CONT8
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONT9

Attribute	Description
Name	CONT9
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONT10

Attribute	Description
Name	CONT10
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT11

Attribute	**Description**
Name	CONT11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT12

Attribute	**Description**
Name	CONT12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT13

Attribute	**Description**
Name	CONT13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT14

Attribute	Description
Name	CONT14
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT15

Attribute	Description
Name	CONT15
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

ROLEDETAILC

Attribute	Description
Name	ROLEDETAILC
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	8

CNTRL1

Attribute	Description
Name	CNTRL1
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL2

Attribute	Description
Name	CNTRL2
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL3

Attribute	Description
Name	CNTRL3
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL4

Attribute	**Description**
Name	CNTRL4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL5

Attribute	**Description**
Name	CNTRL5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL6

Attribute	**Description**
Name	CNTRL6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL7

Attribute	Description
Name	CNTRL7
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL8

Attribute	Description
Name	CNTRL8
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL9

Attribute	Description
Name	CNTRL9
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL10

Attribute	Description
Name	CNTRL10
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL11

Attribute	**Description**
Name	CNTRL11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL12

Attribute	**Description**
Name	CNTRL12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL13

Attribute	**Description**
Name	CNTRL13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL14

Attribute	Description
Name	CNTRL14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL15

Attribute	Description
Name	CNTRL15
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL16

Attribute	Description
Name	CNTRL16
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

ROLEDETAILD

Attribute	Description
Name	ROLEDETAILD
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	8

CONTROL1

Attribute	Description
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL2

Attribute	Description
Name	CONTROL2
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL3

Attribute	Description
Name	CONTROL3
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL4

Attribute	**Description**
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL5

Attribute	**Description**
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL6

Attribute	**Description**
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL8

Attribute	Description
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL9

Attribute	Description
Name	CONTROL9
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL10

Attribute	Description
Name	CONTROL10
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL11

Attribute	**Description**
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL12

Attribute	**Description**
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL13

Attribute	**Description**
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL14

Attribute	Description
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL15

Attribute	Description
Name	CNTRL15
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL16

Attribute	Description
Name	CNTRL16
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

ROLEBRANCHES

Attribute	Description
Name	ROLEBRANCHES
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

ROLEACCCLASS

Attribute	Description
Name	ROLEACCCLASS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	6

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

MSGCRIGHTS

Attribute	Description
Name	MSGCRIGHTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

CNL

Attribute	Description
Name	CNL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGNODE

Attribute	Description
Name	CHGNODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

REL

Attribute	Description
Name	REL
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGMEDIA

Attribute	**Description**
Name	CHGMEDIA
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

BRNMOV

Attribute	**Description**
Name	BRNMOV
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

HLD

Attribute	**Description**
Name	HLD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TSTINP

Attribute	**Description**
Name	TSTINP
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

CHGADDR

Attribute	**Description**
Name	CHGADDR
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

REINS

Attribute	**Description**
Name	REINS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGPRIOR

Attribute	**Description**
Name	CHGPRIOR
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CNLAUTH

Attribute	**Description**
Name	CNLAUTH
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGNODEAUTH

Attribute	**Description**
Name	CHGNODEAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

RELAUTH

Attribute	**Description**
Name	RELAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGMEDIAAUTH

Attribute	**Description**
Name	CHGMEDIAAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

BRNMOVAUTH

Attribute	**Description**
Name	BRNMOVAUTH
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

HLDAUTH

Attribute	**Description**
Name	HLDAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TSTINPAUTH

Attribute	**Description**
Name	TSTINPAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGADDRAUTH

Attribute	**Description**
Name	CHGADDRAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

REINSAUTH

Attribute	**Description**
Name	REINSAUTH
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGPRIORAUTH

Attribute	Description
Name	CHGPRIORAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TSTCHK

Attribute	Description
Name	TSTCHK
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

LNKCONT

Attribute	Description
Name	LNKCONT
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGBRNIN

Attribute	**Description**
Name	CHGBRNIN
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGMSG

Attribute	**Description**
Name	CHGMSG
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGFORCRELFUND

Attribute	**Description**
Name	CHGFORCRELFUND
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

SUPPRESS

Attribute	**Description**
Name	SUPPRESS
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

DELMSG

Attribute	Description
Name	DELMSG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

PRNT

Attribute	Description
Name	PRNT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

FTUPL

Attribute	Description
Name	FTUPL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

MOVQ

Attribute	Description
Name	MOVQ
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGADDRIN

Attribute	**Description**
Name	CHGADDRIN
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGMSGAUTH

Attribute	**Description**
Name	CHGMSGAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

AUTHRGHTS

Attribute	**Description**
Name	AUTHRGHTS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGFORCCOVMATCH

Attribute	**Description**
Name	CHGFORCCOVMATCH
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

QUEUERIGHTS

Attribute	**Description**
Name	QUEUERIGHTS
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

QUEUE

Attribute	**Description**
Name	QUEUE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 10

RESTRICTIVEPASSWD

Attribute	**Description**
Name	RESTRICTIVEPASSWD
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

PWD

Attribute	**Description**
Name	PWD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12

PWDID

Attribute	**Description**
Name	PWDID
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

ROLEBRANCHLIMITS

Attribute	Description
Name	ROLEBRANCHLIMITS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

LMTCCY

Attribute	Description
Name	LMTCCY
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

BRHUSERLMT

Attribute	Description
Name	BRHUSERLMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

Roledetaile

Attribute	Description
Name	Roledetaile
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

EDITABLE

Attribute	Description
Name	EDITABLE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CNTRLSTR

Attribute	Description
Name	CNTRLSTR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

Roledetailf

Attribute	Description
Name	Roledetailf
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ROLEID

Attribute	Description
Name	ROLEID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

CNTRLSTR

Attribute	Description
Name	CNTRLSTR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

CNTRL1

Attribute	Description
Name	CNTRL1
Datatype	Decimal

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL10

Attribute	Description
Name	CNTRL10
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL11

Attribute	Description
Name	CNTRL11
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL12

Attribute	Description
Name	CNTRL12
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL13

Attribute	Description
Name	CNTRL13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL14

Attribute	Description
Name	CNTRL14
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL15

Attribute	Description
Name	CNTRL15
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL16

Attribute	Description
Name	CNTRL16
Datatype	Decimal
Description	

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL2

Attribute	Description
Name	CNTRL2
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL3

Attribute	Description
Name	CNTRL3
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL4

Attribute	Description
Name	CNTRL4
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL5

Attribute	Description
Name	CNTRL5
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL6

Attribute	Description
Name	CNTRL6
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL7

Attribute	Description
Name	CNTRL7
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL8

Attribute	Description
Name	CNTRL8
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL9

Attribute	**Description**
Name	CNTRL9
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

ATHSTAT

Attribute	**Description**
Name	ATHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

BRNCHCODE

Attribute	**Description**
Name	BRNCHCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

UDFDETAILS

Attribute	**Description**

Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.17.2.SM-ModifySMRole-Req-IO-MSG.xsd

MODIFYSMROLE_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

ROLEMASTER-IO

ROLEIDENTIFICATION

MASTERROLEDESC

BRANCHROLE

BRANCHROLELEVEL

BRANCHPWDRESETFREQ

AUTHORISERROLE

BRANCHVLTROLE

BRANCH_RES

ACCCLASSALLOWED

CENTRALISATIONROLE

MAKER

MAKERSTAMP

ROLEDETAIL

CONTROLSTRING

ROLEFUN

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

CONTROL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

CONTROL15

CONTROL16

ATHSTAT

BRNCHCODE

ROLEDETAILB

CNTRLSTR

ROLEFUN

CONT1

CONT2

CONT3

CONT4

CONT5

CONT6

CONTROL7

CONT8

CONT9

CONT10

CONT11

CONT12

CONT13

CONT14

CONT15

CONTROL16

ATHATAT

BRHCODE

ROLEDETAILC

CNTRLSTR

ROLEFUN

CNTRL1

CNTRL2

CNTRL3

CNTRL4

CNTRL5

CNTRL6

CNTRL7

CNTRL8

CNTRL9

CNTRL10

CNTRL11

CNTRL12

CNTRL13

CNTRL14

CNTRL15

CNTRL16

ATHSTAT

ROLEDETAILD

CNTRLSTRING

ROLEFUN

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

CONTROL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

CNTRL15

CNTRL16

ROLEBRANCHES

BRANCH

ROLEACCCLASS

ACCCLS

MSGCRIGHTS

CNL

CHGNODE

REL

CHGMEDIA

BRNMOV

HLD

TSTINP

CHGADDR

REINS

CHGPRIOR

CNLAUTH

CHGNODEAUTH

RELAUTH

CHGMEDIAAUTH

BRNMOVAUTH

HLDAUTH

TSTINPAUTH

CHGADDRAUTH

REINSAUTH

CHGPRIORAUTH

GEN

TSTCHK

LNKCONT

CHGBRNIN

CHGMSG

CHGFORCRELFUND

SUPPRESS

DELMSG

PRNT

FTUPL

MOVQ

CHGADDRIN

CHGMSGAUTH

AUTHRGHTS

CHGFORCCOVMATCH

QUEUERIGHTS

QUEUE

RESTRICTIVEPASSWD

PWD

ROLEBRANCHLIMITS

LMTCCY

EXRATE

BRHLOWERLMT

BRHUPPRLMT

BRHUSERLMT

Roledetaile

ROLEFUN

EDITABLE

CNTRLSTR

CONTROL_1

CONTROL_10

CONTROL_11

CONTROL_12

CONTROL_13

CONTROL_14

CONTROL_15

CONTROL_16

CONTROL_2

CONTROL_3

CONTROL_4

CONTROL_6

CONTROL_7

CONTROL_8

CONTROL_9

Roledetailf

ROLEFUN

CNTRLSTR

CNTRL1

CNTRL10

CNTRL11

CNTRL12

CNTRL13

CNTRL14

CNTRL15

CNTRL16

CNTRL2

CNTRL3

CNTRL4

CNTRL5

CNTRL6

CNTRL7

CNTRL8

CNTRL9

UDFDETAILS

FLDNAM

FLDVAL

MODIFYSMROLE_IOPK_REQ

Attribute	Description
Name	MODIFYSMROLE_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

ROLEMASTER-IO

Attribute	Description
Name	ROLEMASTER-IO
Datatype	
Description	

ROLEIDENTIFICATION

Attribute	Description
Name	ROLEIDENTIFICATION
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

MASTERROLEDESC

Attribute	Description
Name	MASTERROLEDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

BRANCHROLE

Attribute	Description
Name	BRANCHROLE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

BRANCHROLELEVEL

Attribute	Description
Name	BRANCHROLELEVEL
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

BRANCHPWDRESETFREQ

Attribute	Description
Name	BRANCHPWDRESETFREQ
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

AUTHORISERROLE

Attribute	Description
Name	AUTHORISERROLE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

BRANCHVLTROLE

Attribute	Description
Name	BRANCHVLTROLE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

BRANCH_RES

Attribute	Description
Name	BRANCH_RES
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

ACCCLASSALLOWED

Attribute	Description
Name	ACCCLASSALLOWED
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

CENTRALISATIONROLE

Attribute	Description
Name	CENTRALISATIONROLE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

ROLEDETAIL

Attribute	Description
Name	ROLEDETAIL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

CONTROLSTRING

Attribute	Description
Name	CONTROLSTRING
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 16

ROLEFUN

Attribute	**Description**
Name	ROLEFUN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 8

CONTROL1

Attribute	**Description**
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL2

Attribute	**Description**
Name	CONTROL2
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL3

Attribute	**Description**
Name	CONTROL3
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL4

Attribute	**Description**
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL5

Attribute	**Description**
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL6

Attribute	**Description**
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL8

Attribute	Description
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL9

Attribute	Description
Name	CONTROL9
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL10

Attribute	Description
Name	CONTROL10
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL11

Attribute	**Description**
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL12

Attribute	**Description**
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL13

Attribute	**Description**
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL14

Attribute	Description
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL15

Attribute	Description
Name	CONTROL15
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

ATHSTAT

Attribute	Description
Name	ATHSTAT
Datatype	String
Description	

Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

BRNCHCODE

Attribute	**Description**
Name	BRNCHCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

ROLEDETAILB

Attribute	**Description**
Name	ROLEDETAILB
Datatype	
Description	
Attribute	**Attribute** / **Description**: maxOccurs / unbounded

CNTRLSTR

Attribute	**Description**
Name	CNTRLSTR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

ROLEFUN

Attribute	**Description**
Name	ROLEFUN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 8

CONT1

Attribute	Description
Name	CONT1
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONT2

Attribute	Description
Name	CONT2
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONT3

Attribute	Description
Name	CONT3
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONT4

Attribute	Description
Name	CONT4
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONT5

Attribute	**Description**
Name	CONT5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONT6

Attribute	**Description**
Name	CONT6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL7

Attribute	**Description**
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONT8

Attribute	Description
Name	CONT8
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT9

Attribute	Description
Name	CONT9
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT10

Attribute	Description
Name	CONT10
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT11

Attribute	Description
Name	CONT11
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT12

Attribute	**Description**
Name	CONT12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT13

Attribute	**Description**
Name	CONT13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT14

Attribute	**Description**
Name	CONT14
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT15

Attribute	Description
Name	CONT15
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

ATHATAT

Attribute	Description
Name	ATHATAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

BRHCODE

Attribute	Description
Name	BRHCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	3

ROLEDETAILC

Attribute	Description
Name	ROLEDETAILC
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

CNTRLSTR

Attribute	Description
Name	CNTRLSTR
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	8

CNTRL1

Attribute	Description
Name	CNTRL1
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL2

Attribute	Description
Name	CNTRL2
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL3

Attribute	Description
Name	CNTRL3
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL4

Attribute	Description
Name	CNTRL4
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL5

Attribute	Description
Name	CNTRL5
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL6

Attribute	Description
Name	CNTRL6
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL7

Attribute	Description
Name	CNTRL7
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL8

Attribute	Description
Name	CNTRL8
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL9

Attribute	Description
Name	CNTRL9
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL10

Attribute	Description
Name	CNTRL10
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL11

Attribute	Description
Name	CNTRL11
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL12

Attribute	Description
Name	CNTRL12
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL13

Attribute	Description
Name	CNTRL13
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL14

Attribute	Description
Name	CNTRL14
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL15

Attribute	Description
Name	CNTRL15
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL16

Attribute	Description
Name	CNTRL16
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

ATHSTAT

Attribute	Description
Name	ATHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

ROLEDETAILD

Attribute	Description
Name	ROLEDETAILD
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

CNTRLSTRING

Attribute	Description
Name	CNTRLSTRING
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

ROLEFUN

Attribute	Description
Name	ROLEFUN

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 8

CONTROL1

Attribute	**Description**
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL2

Attribute	**Description**
Name	CONTROL2
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL3

Attribute	**Description**
Name	CONTROL3
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL4

Attribute	Description
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL5

Attribute	Description
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL6

Attribute	Description
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL8

Attribute	Description
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL9

Attribute	Description
Name	CONTROL9
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL10

Attribute	Description
Name	CONTROL10
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL11

Attribute	Description
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL12

Attribute	Description
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL13

Attribute	Description
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL14

Attribute	Description
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL15

Attribute	Description
Name	CNTRL15
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL16

Attribute	Description
Name	CNTRL16
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

ROLEBRANCHES

Attribute	Description
Name	ROLEBRANCHES
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	3

ROLEACCCLASS

Attribute	Description
Name	ROLEACCCLASS
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	6

MSGCRIGHTS

Attribute	Description
Name	MSGCRIGHTS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

CNL

Attribute	Description
Name	CNL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGNODE

Attribute	Description
Name	CHGNODE
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

REL

Attribute	**Description**
Name	REL
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGMEDIA

Attribute	**Description**
Name	CHGMEDIA
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

BRNMOV

Attribute	**Description**
Name	BRNMOV
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

HLD

Attribute	**Description**
Name	HLD
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / Y,N

TSTINP

Attribute	**Description**
Name	TSTINP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGADDR

Attribute	**Description**
Name	CHGADDR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

REINS

Attribute	**Description**
Name	REINS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGPRIOR

Attribute	**Description**
Name	CHGPRIOR
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

CNLAUTH

Attribute	**Description**
Name	CNLAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGNODEAUTH

Attribute	**Description**
Name	CHGNODEAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

RELAUTH

Attribute	**Description**
Name	RELAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGMEDIAAUTH

Attribute	**Description**
Name	CHGMEDIAAUTH
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / Y,N

BRNMOVAUTH

Attribute	**Description**
Name	BRNMOVAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

HLDAUTH

Attribute	**Description**
Name	HLDAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TSTINPAUTH

Attribute	**Description**
Name	TSTINPAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGADDRAUTH

Attribute	**Description**
Name	CHGADDRAUTH
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

REINSAUTH

Attribute	**Description**
Name	REINSAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGPRIORAUTH

Attribute	**Description**
Name	CHGPRIORAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

GEN

Attribute	**Description**
Name	GEN
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TSTCHK

Attribute	**Description**
Name	TSTCHK
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

LNKCONT

Attribute	**Description**
Name	LNKCONT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGBRNIN

Attribute	**Description**
Name	CHGBRNIN
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGMSG

Attribute	**Description**
Name	CHGMSG
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGFORCRELFUND

Attribute	**Description**
Name	CHGFORCRELFUND
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

SUPPRESS

Attribute	**Description**
Name	SUPPRESS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

DELMSG

Attribute	**Description**
Name	DELMSG
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

PRNT

Attribute	**Description**
Name	PRNT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

FTUPL

Attribute	**Description**
Name	FTUPL
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / Y,N

MOVQ

Attribute	**Description**
Name	MOVQ
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGADDRIN

Attribute	**Description**
Name	CHGADDRIN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMSGAUTH

Attribute	**Description**
Name	CHGMSGAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

AUTHRGHTS

Attribute	**Description**
Name	AUTHRGHTS
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGFORCCOVMATCH

Attribute	**Description**
Name	CHGFORCCOVMATCH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

QUEUERIGHTS

Attribute	**Description**
Name	QUEUERIGHTS
Datatype	
Description	
Attribute	**Attribute** / **Description** maxOccurs / unbounded

QUEUE

Attribute	**Description**
Name	QUEUE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 10

RESTRICTIVEPASSWD

Attribute	**Description**
Name	RESTRICTIVEPASSWD
Datatype	
Description	
Attribute	**Attribute** / **Description** maxOccurs / unbounded

PWD

Attribute	**Description**

Name	PWD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12

ROLEBRANCHLIMITS

Attribute	Description
Name	ROLEBRANCHLIMITS
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

LMTCCY

Attribute	Description
Name	LMTCCY
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

BRHLOWERLMT

Attribute	Description
Name	BRHLOWERLMT
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

BRHUPPRLMT

Attribute	Description
Name	BRHUPPRLMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

BRHUSERLMT

Attribute	Description
Name	BRHUSERLMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

Roledetaile

Attribute	Description
Name	Roledetaile
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

EDITABLE

Attribute	Description
Name	EDITABLE
Datatype	Decimal

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CNTRLSTR

Attribute	Description
Name	CNTRLSTR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

CONTROL_1

Attribute	Description
Name	CONTROL_1
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL_10

Attribute	Description
Name	CONTROL_10
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL_11

Attribute	Description
Name	CONTROL_11
Datatype	Decimal

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL_12

Attribute	Description
Name	CONTROL_12
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL_13

Attribute	Description
Name	CONTROL_13
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL_14

Attribute	Description
Name	CONTROL_14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL_15

Attribute	Description
Name	CONTROL_15
Datatype	Decimal

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL_16

Attribute	Description
Name	CONTROL_16
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL_2

Attribute	Description
Name	CONTROL_2
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL_3

Attribute	Description
Name	CONTROL_3
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL_4

Attribute	Description
Name	CONTROL_4
Datatype	Decimal

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL_6

Attribute	Description
Name	CONTROL_6
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL_7

Attribute	Description
Name	CONTROL_7
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL_8

Attribute	Description
Name	CONTROL_8
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL_9

Attribute	Description
Name	CONTROL_9
Datatype	Decimal

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

Roledetailf

Attribute	Description
Name	Roledetailf
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

CNTRLSTR

Attribute	Description
Name	CNTRLSTR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

CNTRL1

Attribute	Description
Name	CNTRL1
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL10

Attribute	**Description**
Name	CNTRL10
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL11

Attribute	**Description**
Name	CNTRL11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL12

Attribute	**Description**
Name	CNTRL12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL13

Attribute	Description
Name	CNTRL13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL14

Attribute	Description
Name	CNTRL14
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL15

Attribute	Description
Name	CNTRL15
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL16

Attribute	Description
Name	CNTRL16
Datatype	Decimal
Description	

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL2

Attribute	Description
Name	CNTRL2
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL3

Attribute	Description
Name	CNTRL3
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL4

Attribute	Description
Name	CNTRL4
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL5

Attribute	Description
Name	CNTRL5
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL6

Attribute	Description
Name	CNTRL6
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL7

Attribute	Description
Name	CNTRL7
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL8

Attribute	Description
Name	CNTRL8
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL9

Attribute	**Description**
Name	CNTRL9
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	Indicates Field Value

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	150
minLength	0

2.17.3.SM-ModifySMRole-Res-Full-MSG.xsd

MODIFYSMROLE_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

ROLEMASTER-Full

ROLEIDENTIFICATION

MASTERROLEDESC

AUTHORISERROLE

BRANCH_RES

ACCCLASSALLOWED

CENTRALISATIONROLE

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

ROLEDETAIL

- *ROLEFUN*
- *CONTROL1*
- *CONTROL2*
- *CONTROL3*
- *CONTROL4*
- *CONTROL5*
- *CONTROL6*
- *CONTROL7*
- *CONTROL8*
- *CONTROL9*
- *CONTROL10*
- *CONTROL11*
- *CONTROL12*
- *CONTROL13*
- *CONTROL14*
- *CONTROL15*
- *CONTROL16*

ROLEDETAILB

- *ROLEFUN*

CONT1

CONT2

CONT3

CONT4

CONT5

CONT6

CONTROL7

CONT8

CONT9

CONT10

CONT11

CONT12

CONT13

CONT14

CONT15

CONTROL16

ROLEDETAILC

ROLEFUN

CNTRL1

CNTRL2

CNTRL3

CNTRL4

CNTRL5

CNTRL6

CNTRL7

CNTRL8

CNTRL9

CNTRL10

CNTRL11

CNTRL12

CNTRL13

CNTRL14

CNTRL15

CNTRL16

ROLEDETAILD

ROLEFUN

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

CONTROL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

CNTRL15

CNTRL16

ROLEBRANCHES

BRANCH

BRNNAME

ROLEACCCLASS

ACCCLS

DESCRIPTION

MSGCRIGHTS

CNL

CHGNODE

REL

CHGMEDIA

BRNMOV

HLD

TSTINP

CHGADDR

REINS

CHGPRIOR

CNLAUTH

CHGNODEAUTH

RELAUTH

CHGMEDIAAUTH

BRNMOVAUTH

HLDAUTH

TSTINPAUTH

CHGADDRAUTH

REINSAUTH

CHGPRIORAUTH

GEN

TSTCHK

LNKCONT

CHGBRNIN

CHGMSG

CHGFORCRELFUND

SUPPRESS

DELMSG

PRNT

FTUPL

MOVQ

CHGADDRIN

CHGMSGAUTH

AUTHRGHTS

CHGFORCCOVMATCH

QUEUERIGHTS

QUEUE

RESTRICTIVEPASSWD

PWD

PWDID

ROLEBRANCHLIMITS

LMTCCY

BRHUSERLMT

Roledetaile

ROLEFUN

BRANCHCODE

EDITABLE

CNTRLSTR

Roledetailf

ROLEID

ROLEFUN

CNTRLSTR

CNTRL1

CNTRL10

CNTRL11

CNTRL12

CNTRL13

CNTRL14

CNTRL15

CNTRL16

CNTRL2

CNTRL3

CNTRL4

CNTRL5

CNTRL6

CNTRL7

CNTRL8

CNTRL9

ATHSTAT

BRNCHCODE

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYSMROLE_FSFS_RES

Attribute	Description
Name	MODIFYSMROLE_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

ROLEMASTER-Full

Attribute	Description

Name	ROLEMASTER-Full
Datatype	
Description	

ROLEIDENTIFICATION

Attribute	Description
Name	ROLEIDENTIFICATION
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

MASTERROLEDESC

Attribute	Description
Name	MASTERROLEDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

AUTHORISERROLE

Attribute	Description
Name	AUTHORISERROLE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

BRANCH_RES

Attribute	Description
Name	BRANCH_RES
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

ACCCLASSALLOWED

Attribute	Description
Name	ACCCLASSALLOWED
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

CENTRALISATIONROLE

Attribute	Description
Name	CENTRALISATIONROLE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

ROLEDETAIL

Attribute	Description
Name	ROLEDETAIL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

CONTROL1

Attribute	Description
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL2

Attribute	Description
Name	CONTROL2
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL3

Attribute	**Description**
Name	CONTROL3
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL4

Attribute	**Description**
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL5

Attribute	**Description**
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL6

Attribute	Description
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL8

Attribute	Description
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL9

Attribute	Description
Name	CONTROL9
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL10

Attribute	**Description**
Name	CONTROL10
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL11

Attribute	**Description**
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL12

Attribute	**Description**
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL13

Attribute	Description
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: totalDigits = 22; minInclusive = 0; maxInclusive = 1

CONTROL14

Attribute	Description
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: totalDigits = 22; minInclusive = 0; maxInclusive = 1

CONTROL15

Attribute	Description
Name	CONTROL15
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: totalDigits = 22; minInclusive = 0; maxInclusive = 1

CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

ROLEDETAILB

Attribute	**Description**
Name	ROLEDETAILB
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ROLEFUN

Attribute	**Description**
Name	ROLEFUN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 8

CONT1

Attribute	**Description**
Name	CONT1
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONT2

Attribute	**Description**
Name	CONT2
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT3

Attribute	**Description**
Name	CONT3
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT4

Attribute	**Description**
Name	CONT4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT5

Attribute	**Description**
Name	CONT5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT6

Attribute	Description
Name	CONT6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT8

Attribute	Description
Name	CONT8
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT9

Attribute	Description
Name	CONT9
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT10

Attribute	**Description**
Name	CONT10
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT11

Attribute	**Description**
Name	CONT11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT12

Attribute	**Description**
Name	CONT12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT13

Attribute	Description
Name	CONT13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT14

Attribute	Description
Name	CONT14
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONT15

Attribute	Description
Name	CONT15
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

ROLEDETAILC

Attribute	Description
Name	ROLEDETAILC
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 8

CNTRL1

Attribute	Description
Name	CNTRL1
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL2

Attribute	Description
Name	CNTRL2
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL3

Attribute	**Description**
Name	CNTRL3
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL4

Attribute	**Description**
Name	CNTRL4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL5

Attribute	**Description**
Name	CNTRL5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL6

Attribute	Description
Name	CNTRL6
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL7

Attribute	Description
Name	CNTRL7
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL8

Attribute	Description
Name	CNTRL8
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL9

Attribute	Description
Name	CNTRL9
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL10

Attribute	**Description**
Name	CNTRL10
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL11

Attribute	**Description**
Name	CNTRL11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL12

Attribute	**Description**
Name	CNTRL12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL13

Attribute	Description
Name	CNTRL13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL14

Attribute	Description
Name	CNTRL14
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL15

Attribute	Description
Name	CNTRL15
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL16

Attribute	Description
Name	CNTRL16
Datatype	Decimal
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

ROLEDETAILD

Attribute	Description
Name	ROLEDETAILD
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

CONTROL1

Attribute	Description
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL2

Attribute	Description
Name	CONTROL2
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL3

Attribute	**Description**
Name	CONTROL3
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL4

Attribute	**Description**
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL5

Attribute	**Description**
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL6

Attribute	Description
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL8

Attribute	Description
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CONTROL9

Attribute	Description
Name	CONTROL9
Datatype	Decimal
Description	

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL10

Attribute	Description
Name	CONTROL10
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL11

Attribute	Description
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL12

Attribute	Description
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL13

Attribute	Description
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: totalDigits = 22; minInclusive = 0; maxInclusive = 1

CONTROL14

Attribute	Description
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: totalDigits = 22; minInclusive = 0; maxInclusive = 1

CNTRL15

Attribute	Description
Name	CNTRL15
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: totalDigits = 22; minInclusive = 0; maxInclusive = 1

CNTRL16

Attribute	Description
Name	CNTRL16
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

ROLEBRANCHES

Attribute	Description
Name	ROLEBRANCHES
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 3

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

ROLEACCCLASS

Attribute	Description
Name	ROLEACCCLASS
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 6

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

MSGCRIGHTS

Attribute	Description
Name	MSGCRIGHTS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

CNL

Attribute	Description
Name	CNL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGNODE

Attribute	Description
Name	CHGNODE
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / Y,N

REL

Attribute	**Description**
Name	REL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMEDIA

Attribute	**Description**
Name	CHGMEDIA
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

BRNMOV

Attribute	**Description**
Name	BRNMOV
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

HLD

Attribute	**Description**
Name	HLD
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

TSTINP

Attribute	**Description**
Name	TSTINP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGADDR

Attribute	**Description**
Name	CHGADDR
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

REINS

Attribute	**Description**
Name	REINS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGPRIOR

Attribute	**Description**
Name	CHGPRIOR
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CNLAUTH

Attribute	Description
Name	CNLAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGNODEAUTH

Attribute	Description
Name	CHGNODEAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

RELAUTH

Attribute	Description
Name	RELAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGMEDIAAUTH

Attribute	Description
Name	CHGMEDIAAUTH
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

BRNMOVAUTH

Attribute	**Description**
Name	BRNMOVAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

HLDAUTH

Attribute	**Description**
Name	HLDAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TSTINPAUTH

Attribute	**Description**
Name	TSTINPAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGADDRAUTH

Attribute	**Description**
Name	CHGADDRAUTH
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

REINSAUTH

Attribute	Description
Name	REINSAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGPRIORAUTH

Attribute	Description
Name	CHGPRIORAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TSTCHK

Attribute	Description
Name	TSTCHK
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / Y,N

LNKCONT

Attribute	**Description**
Name	LNKCONT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGBRNIN

Attribute	**Description**
Name	CHGBRNIN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMSG

Attribute	**Description**
Name	CHGMSG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGFORCRELFUND

Attribute	**Description**
Name	CHGFORCRELFUND
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

SUPPRESS

Attribute	**Description**
Name	SUPPRESS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

DELMSG

Attribute	**Description**
Name	DELMSG
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

PRNT

Attribute	**Description**
Name	PRNT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

FTUPL

Attribute	**Description**
Name	FTUPL
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

MOVQ

Attribute	**Description**
Name	MOVQ
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGADDRIN

Attribute	**Description**
Name	CHGADDRIN
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGMSGAUTH

Attribute	**Description**
Name	CHGMSGAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

AUTHRGHTS

Attribute	**Description**
Name	AUTHRGHTS
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGFORCCOVMATCH

Attribute	**Description**
Name	CHGFORCCOVMATCH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

QUEUERIGHTS

Attribute	**Description**
Name	QUEUERIGHTS
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

QUEUE

Attribute	**Description**
Name	QUEUE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 10

RESTRICTIVEPASSWD

Attribute	**Description**
Name	RESTRICTIVEPASSWD
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

PWD

Attribute	Description
Name	PWD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12

PWDID

Attribute	Description
Name	PWDID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

ROLEBRANCHLIMITS

Attribute	Description
Name	ROLEBRANCHLIMITS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

LMTCCY

Attribute	Description
Name	LMTCCY
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

BRHUSERLMT

Attribute	Description
Name	BRHUSERLMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**
	totalDigits / 22

Roledetaile

Attribute	Description
Name	Roledetaile
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

EDITABLE

Attribute	Description
Name	EDITABLE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: totalDigits / 22

CNTRLSTR

Attribute	Description
Name	CNTRLSTR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

Roledetailf

Attribute	Description
Name	Roledetailf
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ROLEID

Attribute	Description
Name	ROLEID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	8

CNTRLSTR

Attribute	Description
Name	CNTRLSTR
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

CNTRL1

Attribute	Description
Name	CNTRL1
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL10

Attribute	Description
Name	CNTRL10
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL11

Attribute	Description
Name	CNTRL11
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL12

Attribute	**Description**
Name	CNTRL12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL13

Attribute	**Description**
Name	CNTRL13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL14

Attribute	**Description**
Name	CNTRL14
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL15

Attribute	Description
Name	CNTRL15
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL16

Attribute	Description
Name	CNTRL16
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL2

Attribute	Description
Name	CNTRL2
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL3

Attribute	Description
Name	CNTRL3
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL4

Attribute	**Description**
Name	CNTRL4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL5

Attribute	**Description**
Name	CNTRL5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL6

Attribute	**Description**
Name	CNTRL6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL7

Attribute	Description
Name	CNTRL7
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL8

Attribute	Description
Name	CNTRL8
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL9

Attribute	Description
Name	CNTRL9
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

ATHSTAT

Attribute	Description
Name	ATHSTAT
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** maxLength / 1

BRNCHCODE

Attribute	**Description**
Name	BRNCHCODE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	150
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.17.4.SM-ModifySMRole-Res-PK-MSG.xsd

MODIFYSMROLE_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

ROLEMASTER-PK

ROLEIDENTIFICATION

ROLEMASTER-IO

ROLEIDENTIFICATION

MASTERROLEDESC

BRANCHROLE

BRANCHROLELEVEL

BRANCHPWDRESETFREQ

AUTHORISERROLE

BRANCHVLTROLE

BRANCH_RES

ACCCLASSALLOWED

CENTRALISATIONROLE

MAKER

MAKERSTAMP

ROLEDETAIL

CONTROLSTRING

ROLEFUN

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

CONTROL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

CONTROL15

CONTROL16

ATHSTAT

BRNCHCODE

ROLEDETAILB

CNTRLSTR

ROLEFUN

CONT1

CONT2

CONT3

CONT4

CONT5

CONT6

CONTROL7

CONT8

CONT9

CONT10

CONT11

CONT12

CONT13

CONT14

CONT15

CONTROL16

ATHATAT

BRHCODE

ROLEDETAILC

CNTRLSTR

ROLEFUN

CNTRL1

CNTRL2

CNTRL3

CNTRL4

CNTRL5

CNTRL6

CNTRL7

CNTRL8

CNTRL9

CNTRL10

CNTRL11

CNTRL12

CNTRL13

CNTRL14

CNTRL15

CNTRL16

ATHSTAT

ROLEDETAILD

CNTRLSTRING

ROLEFUN

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

CONTROL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

CNTRL15

CNTRL16

ROLEBRANCHES

BRANCH

ROLEACCCLASS

ACCCLS

MSGCRIGHTS

CNL

CHGNODE

REL

CHGMEDIA

BRNMOV

HLD

TSTINP

CHGADDR

REINS

CHGPRIOR

CNLAUTH

CHGNODEAUTH

RELAUTH

CHGMEDIAAUTH

BRNMOVAUTH

HLDAUTH

TSTINPAUTH

CHGADDRAUTH

REINSAUTH

CHGPRIORAUTH

GEN

TSTCHK

LNKCONT

CHGBRNIN

CHGMSG

CHGFORCRELFUND

SUPPRESS

DELMSG

PRNT

FTUPL

MOVQ

CHGADDRIN

CHGMSGAUTH

AUTHRGHTS

CHGFORCCOVMATCH

QUEUERIGHTS

QUEUE

RESTRICTIVEPASSWD

PWD

ROLEBRANCHLIMITS

LMTCCY

EXRATE

BRHLOWERLMT

BRHUPPRLMT

BRHUSERLMT

Roledetaile

ROLEFUN

EDITABLE

CNTRLSTR

CONTROL_1

CONTROL_10

CONTROL_11

CONTROL_12

CONTROL_13

CONTROL_14

CONTROL_15

CONTROL_16

CONTROL_2

CONTROL_3

CONTROL_4

CONTROL_6

CONTROL_7

CONTROL_8

CONTROL_9

Roledetailf

ROLEFUN

CNTRLSTR

CNTRL1

CNTRL10

CNTRL11

CNTRL12

CNTRL13

CNTRL14

CNTRL15

CNTRL16

CNTRL2

CNTRL3

CNTRL4

CNTRL5

CNTRL6

CNTRL7

CNTRL8

CNTRL9

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYSMROLE_IOPK_RES

Attribute	Description
Name	MODIFYSMROLE_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String

Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.

Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

ROLEMASTER-PK

Attribute	Description
Name	ROLEMASTER-PK
Datatype	
Description	

ROLEIDENTIFICATION

Attribute	Description

Name	ROLEIDENTIFICATION
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	15

ROLEMASTER-IO

Attribute	Description
Name	ROLEMASTER-IO
Datatype	
Description	

ROLEIDENTIFICATION

Attribute	Description
Name	ROLEIDENTIFICATION
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	15

MASTERROLEDESC

Attribute	Description
Name	MASTERROLEDESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

BRANCHROLE

Attribute	Description
Name	BRANCHROLE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

BRANCHROLELEVEL

Attribute	Description
Name	BRANCHROLELEVEL

Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

BRANCHPWDRESETFREQ

Attribute	**Description**
Name	BRANCHPWDRESETFREQ
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

AUTHORISERROLE

Attribute	**Description**
Name	AUTHORISERROLE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

BRANCHVLTROLE

Attribute	**Description**
Name	BRANCHVLTROLE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

BRANCH_RES

Attribute	**Description**
Name	BRANCH_RES

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

ACCCLASSALLOWED

Attribute	Description
Name	ACCCLASSALLOWED
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

CENTRALISATIONROLE

Attribute	Description
Name	CENTRALISATIONROLE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

ROLEDETAIL

Attribute	**Description**
Name	ROLEDETAIL
Datatype	
Description	
Attribute	**Attribute** / **Description**: maxOccurs / unbounded

CONTROLSTRING

Attribute	**Description**
Name	CONTROLSTRING
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

ROLEFUN

Attribute	**Description**
Name	ROLEFUN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 8

CONTROL1

Attribute	**Description**
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL2

Attribute	Description
Name	CONTROL2
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL3

Attribute	Description
Name	CONTROL3
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL4

Attribute	Description
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL5

Attribute	Description
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL6

Attribute	Description
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL8

Attribute	Description
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL9

Attribute	Description
Name	CONTROL9
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL10

Attribute	Description
Name	CONTROL10
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL11

Attribute	Description
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL12

Attribute	Description
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL13

Attribute	Description
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL14

Attribute	Description
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL15

Attribute	Description
Name	CONTROL15
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

ATHSTAT

Attribute	Description
Name	ATHSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

BRNCHCODE

Attribute	Description
Name	BRNCHCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

ROLEDETAILB

Attribute	Description
Name	ROLEDETAILB
Datatype	
Description	

Attribute	

Attribute	Description
maxOccurs	unbounded

CNTRLSTR

Attribute	Description
Name	CNTRLSTR
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	8

CONT1

Attribute	Description
Name	CONT1
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT2

Attribute	Description
Name	CONT2
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT3

Attribute	Description
Name	CONT3
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT4

Attribute	Description
Name	CONT4
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT5

Attribute	Description
Name	CONT5
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT6

Attribute	Description
Name	CONT6
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONT8

Attribute	Description
Name	CONT8
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONT9

Attribute	Description
Name	CONT9
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT10

Attribute	Description
Name	CONT10
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT11

Attribute	Description
Name	CONT11
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT12

Attribute	Description
Name	CONT12
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT13

Attribute	Description
Name	CONT13
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONT14

Attribute	Description
Name	CONT14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONT15

Attribute	Description
Name	CONT15
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

ATHATAT

Attribute	Description
Name	ATHATAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

BRHCODE

Attribute	Description
Name	BRHCODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

ROLEDETAILC

Attribute	Description
Name	ROLEDETAILC
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

CNTRLSTR

Attribute	Description
Name	CNTRLSTR
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: maxLength / 16

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 8

CNTRL1

Attribute	Description
Name	CNTRL1
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL2

Attribute	Description
Name	CNTRL2
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL3

Attribute	Description
Name	CNTRL3
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL4

Attribute	Description
Name	CNTRL4
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL5

Attribute	Description
Name	CNTRL5
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL6

Attribute	Description
Name	CNTRL6
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL7

Attribute	Description
Name	CNTRL7
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL8

Attribute	Description
Name	CNTRL8
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL9

Attribute	Description
Name	CNTRL9
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL10

Attribute	Description
Name	CNTRL10
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL11

Attribute	Description
Name	CNTRL11
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL12

Attribute	Description
Name	CNTRL12
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL13

Attribute	Description
Name	CNTRL13
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL14

Attribute	Description
Name	CNTRL14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL15

Attribute	Description
Name	CNTRL15
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL16

Attribute	Description
Name	CNTRL16
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

ATHSTAT

Attribute	Description
Name	ATHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	1

ROLEDETAILD

Attribute	Description
Name	ROLEDETAILD
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

CNTRLSTRING

Attribute	Description
Name	CNTRLSTRING
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	16

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	8

CONTROL1

Attribute	Description
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL2

Attribute	Description
Name	CONTROL2
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL3

Attribute	Description
Name	CONTROL3
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL4

Attribute	Description
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL5

Attribute	Description
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL6

Attribute	Description
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL8

Attribute	Description
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL9

Attribute	Description
Name	CONTROL9
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL10

Attribute	Description
Name	CONTROL10
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL11

Attribute	Description
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL12

Attribute	Description
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL13

Attribute	Description
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL14

Attribute	Description
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL15

Attribute	Description
Name	CNTRL15
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL16

Attribute	Description
Name	CNTRL16
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

ROLEBRANCHES

Attribute	Description
Name	ROLEBRANCHES
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

ROLEACCCLASS

Attribute	Description
Name	ROLEACCCLASS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

MSGCRIGHTS

Attribute	Description
Name	MSGCRIGHTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

CNL

Attribute	Description
Name	CNL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGNODE

Attribute	Description
Name	CHGNODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

REL

Attribute	Description
Name	REL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGMEDIA

Attribute	Description
Name	CHGMEDIA
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

BRNMOV

Attribute	Description
Name	BRNMOV
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

HLD

Attribute	Description
Name	HLD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TSTINP

Attribute	Description
Name	TSTINP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGADDR

Attribute	Description
Name	CHGADDR
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

REINS

Attribute	Description
Name	REINS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGPRIOR

Attribute	Description
Name	CHGPRIOR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CNLAUTH

Attribute	Description
Name	CNLAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGNODEAUTH

Attribute	Description
Name	CHGNODEAUTH
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

RELAUTH

Attribute	Description
Name	RELAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGMEDIAAUTH

Attribute	Description
Name	CHGMEDIAAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

BRNMOVAUTH

Attribute	Description
Name	BRNMOVAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

HLDAUTH

Attribute	Description
Name	HLDAUTH
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TSTINPAUTH

Attribute	Description
Name	TSTINPAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGADDRAUTH

Attribute	Description
Name	CHGADDRAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

REINSAUTH

Attribute	Description
Name	REINSAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGPRIORAUTH

Attribute	Description
Name	CHGPRIORAUTH
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TSTCHK

Attribute	Description
Name	TSTCHK
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

LNKCONT

Attribute	Description
Name	LNKCONT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGBRNIN

Attribute	Description
Name	CHGBRNIN
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGMSG

Attribute	Description
Name	CHGMSG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGFORCRELFUND

Attribute	Description
Name	CHGFORCRELFUND
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

DELMSG

Attribute	Description
Name	DELMSG
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

PRNT

Attribute	Description
Name	PRNT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

FTUPL

Attribute	Description
Name	FTUPL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

MOVQ

Attribute	Description
Name	MOVQ
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGADDRIN

Attribute	Description
Name	CHGADDRIN
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGMSGAUTH

Attribute	Description
Name	CHGMSGAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

AUTHRGHTS

Attribute	Description
Name	AUTHRGHTS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGFORCCOVMATCH

Attribute	Description
Name	CHGFORCCOVMATCH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

QUEUERIGHTS

Attribute	Description
Name	QUEUERIGHTS
Datatype	

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

QUEUE

Attribute	Description
Name	QUEUE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

RESTRICTIVEPASSWD

Attribute	Description
Name	RESTRICTIVEPASSWD
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PWD

Attribute	Description
Name	PWD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

ROLEBRANCHLIMITS

Attribute	Description
Name	ROLEBRANCHLIMITS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

LMTCCY

Attribute	Description
Name	LMTCCY
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

BRHLOWERLMT

Attribute	Description
Name	BRHLOWERLMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

BRHUPPRLMT

Attribute	Description
Name	BRHUPPRLMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

BRHUSERLMT

Attribute	Description
Name	BRHUSERLMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

Roledetaile

Attribute	Description
Name	Roledetaile
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

EDITABLE

Attribute	Description
Name	EDITABLE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CNTRLSTR

Attribute	Description
Name	CNTRLSTR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

CONTROL_1

Attribute	Description
Name	CONTROL_1
Datatype	Decimal

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL_10

Attribute	Description
Name	CONTROL_10
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL_11

Attribute	Description
Name	CONTROL_11
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL_12

Attribute	Description
Name	CONTROL_12
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL_13

Attribute	Description
Name	CONTROL_13
Datatype	Decimal

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL_14

Attribute	Description
Name	CONTROL_14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL_15

Attribute	Description
Name	CONTROL_15
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL_16

Attribute	Description
Name	CONTROL_16
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL_2

Attribute	Description
Name	CONTROL_2
Datatype	Decimal

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL_3

Attribute	Description
Name	CONTROL_3
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL_4

Attribute	Description
Name	CONTROL_4
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL_6

Attribute	Description
Name	CONTROL_6
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL_7

Attribute	Description
Name	CONTROL_7
Datatype	Decimal

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL_8

Attribute	Description
Name	CONTROL_8
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL_9

Attribute	Description
Name	CONTROL_9
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

Roledetailf

Attribute	Description
Name	Roledetailf
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

CNTRLSTR

Attribute	**Description**
Name	CNTRLSTR
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

CNTRL1

Attribute	**Description**
Name	CNTRL1
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL10

Attribute	**Description**
Name	CNTRL10
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22 minInclusive / 0 maxInclusive / 1

CNTRL11

Attribute	**Description**

Name	CNTRL11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL12

Attribute	**Description**
Name	CNTRL12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL13

Attribute	**Description**
Name	CNTRL13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL14

Attribute	**Description**
Name	CNTRL14
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL15

Attribute	Description
Name	CNTRL15
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL16

Attribute	Description
Name	CNTRL16
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL2

Attribute	Description
Name	CNTRL2
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL3

Attribute	Description
Name	CNTRL3
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL4

Attribute	Description
Name	CNTRL4
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL5

Attribute	Description
Name	CNTRL5
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL6

Attribute	Description
Name	CNTRL6
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL7

Attribute	Description
Name	CNTRL7
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL8

Attribute	Description
Name	CNTRL8
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL9

Attribute	Description
Name	CNTRL9
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.18.ModifyUserMaint

2.18.1.SM-ModifyUserMaint-Req-Full-MSG.xsd

MODIFYUSERMAINT_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

USR-Full

STRTDATE

USRNAME

USRPWD

ENDDT

USRLANG

HOMEBRN

CUSTNO

LDAPUSR

TIMELEVEL

AUTOAUTH

USRSTAT

USRID

EXTUSRREF

USRCATEG

TILLALLOW

ACCCLSALLOW

GLALLOW

USRTXNLMT

LMTSCCY

MAXTXNAMT

MAXAUTHAMT

BRNSALLOW

PRDSALLOW

PRDSACCESALLOW

TAX_IDENTIFIER

AMOUNT_FORMAT

DATE_FORMAT

STAFFACCRESTR

DEPT_CODE

DEPT_DESC

USRML

ELCMUSER

GROUP_CODE

MULTIBRN_ACCESS

OTH_RM_CUST_ACC_ALLOW

SUPERVISOR_ID

SUPERVISOR_NAME

DASHBOARD_REQD

ALERTS_ON_HOME

REFERENCE_NO

NO_CUMULATIVE_LOGINS

NO_SUCCESSIVE_LOGINS

SCREENSAVERTIMEOUTINSECONDS

MFI_USER

F10_REQD

F11_REQD

F12_REQD

ACCESS_CONTROL

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

RESTR_PWD

- *PWD*

MSGSRIGHTS

- *GEN*
- *HLD*
- *CNL*
- *TSTINP*
- *CHGNODE*
- *CHGADDR*
- *REL*
- *REINS*
- *CHGMEDIA*
- *CHGPRIOR*
- *BRNMOV*
- *PRNT*
- *TSTCHK*
- *HLDAUTH*
- *CNLAUTH*
- *TSTINPAUTH*
- *CHGNODEAUTH*

CHGADDRAUTH

RELAUTH

REINSAUTH

CHGMEDIAAUTH

BRNMOVAUTH

CHGPRIORAUTH

FTUPL

LNKCONT

MOVQ

CHGBRNIN

CHGADDRIN

AUTHRGHTS

CHGMSG

CHGMSGAUTH

CHGFORCCOVMATCH

CHANGE_FORCE_RELEASE_FUND

SUPPRESS

DELMSG

QUEUERIGHTS

QUEUE

USERTILLS

TILLID

TILLBRNCD

USERACCCLASS

ACCCLS

USERGLREST

NODEGL

USERGLEXCEPT

EXCEPLEAFGL

USERLIMITSROLE

LMTBRN

LMTSROLE

QLMTCCY

QINPLMT

QAUTHLMT

USERBRANCHES

BRNSBRN

BRNNAME

USERPRODUCTS

PRDPRDCD

PRDDESC

USERACCESSPRODUCTS

PRDACCESSPRDCD

PRDDESC

USERFUNCDISALLOW

FUNCDISALLOWFUNCID

USERROLE

ROLEBRNCD

USRROLEID

MASTERROLEDESC

USERSFUNCTIONS

USERFUNCBRNCD

USERFUNCFUNCID

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

USERFUNCSCTRL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

CONTROL15

CONTROL16

Grp-Restriction

GROUP_CODE

GROUP_DESC

Centralisation

USRROLEID

ROLDESC

Dshmst

USRID

USRNAME

Dshdet

FUNCTIONID

DESCRIPTION

SEQUENCE_NO

DBWHERECLAUSE

SHOW_IN_DASHBOARD

Where-Master

COLUMN_NAME

WHERE_CL

CONDITION

UDFDETAILS

FLDNAM

FLDVAL

MODIFYUSERMAINT_FSFS_REQ

Attribute	Description
Name	MODIFYUSERMAINT_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

USR-Full

Attribute	Description
Name	USR-Full
Datatype	
Description	

STRTDATE

Attribute	Description
Name	STRTDATE
Datatype	String
Description	

USRNAME

Attribute	Description
Name	USRNAME
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 35

USRPWD

Attribute	Description
Name	USRPWD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

ENDDT

Attribute	Description
Name	ENDDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

USRLANG

Attribute	Description
Name	USRLANG
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

HOMEBRN

Attribute	Description
Name	HOMEBRN
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

LDAPUSR

Attribute	Description
Name	LDAPUSR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	500

TIMELEVEL

Attribute	Description
Name	TIMELEVEL
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	9

AUTOAUTH

Attribute	Description
Name	AUTOAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

USRSTAT

Attribute	Description
Name	USRSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	E,H,D,L

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12

EXTUSRREF

Attribute	Description
Name	EXTUSRREF
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

USRCATEG

Attribute	Description
Name	USRCATEG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>S,B</td></tr></table>

TILLALLOW

Attribute	Description
Name	TILLALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

ACCCLSALLOW

Attribute	Description
Name	ACCCLSALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

GLALLOW

Attribute	Description
Name	GLALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

USRTXNLMT

Attribute	Description
Name	USRTXNLMT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>U,R,N</td></tr></table>

LMTSCCY

Attribute	Description
Name	LMTSCCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

MAXTXNAMT

Attribute	Description
Name	MAXTXNAMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

MAXAUTHAMT

Attribute	Description
Name	MAXAUTHAMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

BRNSALLOW

Attribute	Description
Name	BRNSALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

PRDSALLOW

Attribute	Description
Name	PRDSALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

PRDSACCESALLOW

Attribute	Description
Name	PRDSACCESALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

TAX_IDENTIFIER

Attribute	Description
Name	TAX_IDENTIFIER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

AMOUNT_FORMAT

Attribute	Description
Name	AMOUNT_FORMAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>.,,,.,,</td></tr></table>

DATE_FORMAT

Attribute	Description
Name	DATE_FORMAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>M/d/yyyy</td></tr></table>

STAFFACCRESTR

Attribute	Description
Name	STAFFACCRESTR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

DEPT_CODE

Attribute	Description
Name	DEPT_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

DEPT_DESC

Attribute	Description
Name	DEPT_DESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

USRML

Attribute	Description
Name	USRML
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

ELCMUSER

Attribute	Description
Name	ELCMUSER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

GROUP_CODE

Attribute	Description
Name	GROUP_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

MULTIBRN_ACCESS

Attribute	Description
Name	MULTIBRN_ACCESS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

OTH_RM_CUST_ACC_ALLOW

Attribute	Description
Name	OTH_RM_CUST_ACC_ALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

SUPERVISOR_ID

Attribute	Description
Name	SUPERVISOR_ID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>80</td></tr></table>

SUPERVISOR_NAME

Attribute	Description
Name	SUPERVISOR_NAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

DASHBOARD_REQD

Attribute	Description
Name	DASHBOARD_REQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

ALERTS_ON_HOME

Attribute	Description
Name	ALERTS_ON_HOME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

NO_CUMULATIVE_LOGINS

Attribute	Description
Name	NO_CUMULATIVE_LOGINS
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

NO_SUCCESSIVE_LOGINS

Attribute	Description
Name	NO_SUCCESSIVE_LOGINS
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

SCREENSAVERTIMEOUTINSECONDS

Attribute	Description
Name	SCREENSAVERTIMEOUTINSECONDS
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

MFI_USER

Attribute	Description
Name	MFI_USER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

F10_REQD

Attribute	Description
Name	F10_REQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

F11_REQD

Attribute	Description
Name	F11_REQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

F12_REQD

Attribute	Description
Name	F12_REQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

ACCESS_CONTROL

Attribute	Description
Name	ACCESS_CONTROL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>U,G,B</td></tr></table>

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

RESTR_PWD

Attribute	Description
Name	RESTR_PWD
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PWD

Attribute	Description
Name	PWD
Datatype	String

Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MSGSRIGHTS

Attribute	Description
Name	MSGSRIGHTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

HLD

Attribute	Description
Name	HLD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CNL

Attribute	Description
Name	CNL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
enumeration	Y,N

TSTINP

Attribute	Description
Name	TSTINP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGNODE

Attribute	Description
Name	CHGNODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGADDR

Attribute	Description
Name	CHGADDR
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

REL

Attribute	Description
Name	REL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

REINS

Attribute	Description
Name	REINS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGMEDIA

Attribute	Description
Name	CHGMEDIA
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGPRIOR

Attribute	Description
Name	CHGPRIOR
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

BRNMOV

Attribute	Description
Name	BRNMOV
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

PRNT

Attribute	Description
Name	PRNT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

TSTCHK

Attribute	Description
Name	TSTCHK
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

HLDAUTH

Attribute	Description
Name	HLDAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CNLAUTH

Attribute	Description
Name	CNLAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

TSTINPAUTH

Attribute	Description
Name	TSTINPAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGNODEAUTH

Attribute	Description
Name	CHGNODEAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGADDRAUTH

Attribute	Description
Name	CHGADDRAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

RELAUTH

Attribute	Description
Name	RELAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: enumeration / Y,N

REINSAUTH

Attribute	Description
Name	REINSAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMEDIAAUTH

Attribute	Description
Name	CHGMEDIAAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

BRNMOVAUTH

Attribute	Description
Name	BRNMOVAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGPRIORAUTH

Attribute	Description
Name	CHGPRIORAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	Y,N

FTUPL

Attribute	Description
Name	FTUPL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

LNKCONT

Attribute	Description
Name	LNKCONT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

MOVQ

Attribute	Description
Name	MOVQ
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGBRNIN

Attribute	Description
Name	CHGBRNIN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGADDRIN

Attribute	Description
Name	CHGADDRIN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

AUTHRGHTS

Attribute	Description
Name	AUTHRGHTS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGMSG

Attribute	Description
Name	CHGMSG
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGMSGAUTH

Attribute	Description
Name	CHGMSGAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGFORCCOVMATCH

Attribute	Description
Name	CHGFORCCOVMATCH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHANGE_FORCE_RELEASE_FUND

Attribute	Description
Name	CHANGE_FORCE_RELEASE_FUND
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

DELMSG

Attribute	Description
Name	DELMSG
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

QUEUERIGHTS

Attribute	Description
Name	QUEUERIGHTS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

QUEUE

Attribute	Description
Name	QUEUE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	10

USERTILLS

Attribute	Description
Name	USERTILLS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

TILLID

Attribute	Description
Name	TILLID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12

TILLBRNCD

Attribute	Description
Name	TILLBRNCD
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	3

USERACCCLASS

Attribute	Description
Name	USERACCCLASS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	6

USERGLREST

Attribute	Description
Name	USERGLREST
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NODEGL

Attribute	Description
Name	NODEGL
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	9

USERGLEXCEPT

Attribute	Description
Name	USERGLEXCEPT
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

EXCEPLEAFGL

Attribute	Description
Name	EXCEPLEAFGL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

USERLIMITSROLE

Attribute	Description
Name	USERLIMITSROLE
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

LMTBRN

Attribute	Description
Name	LMTBRN
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

LMTSROLE

Attribute	Description
Name	LMTSROLE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

QLMTCCY

Attribute	Description
Name	QLMTCCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

QINPLMT

Attribute	Description
Name	QINPLMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

QAUTHLMT

Attribute	Description
Name	QAUTHLMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

USERBRANCHES

Attribute	Description
Name	USERBRANCHES
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRNSBRN

Attribute	Description
Name	BRNSBRN
Datatype	String

Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

USERPRODUCTS

Attribute	Description
Name	USERPRODUCTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PRDPRDCD

Attribute	Description
Name	PRDPRDCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

USERACCESSPRODUCTS

Attribute	Description
Name	USERACCESSPRODUCTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PRDACCESSPRDCD

Attribute	Description
Name	PRDACCESSPRDCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

USERFUNCDISALLOW

Attribute	Description
Name	USERFUNCDISALLOW
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FUNCDISALLOWFUNCID

Attribute	Description
Name	FUNCDISALLOWFUNCID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

USERROLE

Attribute	Description
Name	USERROLE
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ROLEBRNCD

Attribute	Description
Name	ROLEBRNCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

USRROLEID

Attribute	Description
Name	USRROLEID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

MASTERROLEDESC

Attribute	Description
Name	MASTERROLEDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>45</td></tr></table>

USERSFUNCTIONS

Attribute	Description
Name	USERSFUNCTIONS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

USERFUNCBRNCD

Attribute	Description
Name	USERFUNCBRNCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

USERFUNCFUNCID

Attribute	Description
Name	USERFUNCFUNCID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 8

CONTROL1

Attribute	Description
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL2

Attribute	Description
Name	CONTROL2
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL3

Attribute	Description
Name	CONTROL3
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL4

Attribute	**Description**
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL5

Attribute	**Description**
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL6

Attribute	**Description**
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL7

Attribute	**Description**
Name	CONTROL7
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: totalDigits / 22

CONTROL8

Attribute	**Description**
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL9

Attribute	**Description**
Name	CONTROL9
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

USERFUNCSCTRL10

Attribute	**Description**
Name	USERFUNCSCTRL10
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL11

Attribute	**Description**
Name	CONTROL11
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: totalDigits / 22

CONTROL12

Attribute	**Description**
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL13

Attribute	**Description**
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL14

Attribute	**Description**
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL15

Attribute	**Description**
Name	CONTROL15
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** totalDigits / 22

CONTROL16

Attribute	**Description**
Name	CONTROL16
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

Grp-Restriction

Attribute	**Description**
Name	Grp-Restriction
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

GROUP_CODE

Attribute	**Description**
Name	GROUP_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 40

GROUP_DESC

Attribute	**Description**
Name	GROUP_DESC
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	255

Centralisation

Attribute	Description
Name	Centralisation
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

USRROLEID

Attribute	Description
Name	USRROLEID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	15

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

Dshmst

Attribute	Description
Name	Dshmst
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

USRNAME

Attribute	**Description**
Name	USRNAME
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

Dshdet

Attribute	**Description**
Name	Dshdet
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

DESCRIPTION

Attribute	**Description**
Name	DESCRIPTION
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

SEQUENCE_NO

Attribute	**Description**
Name	SEQUENCE_NO
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description** totalDigits / 22

DBWHERECLAUSE

Attribute	**Description**
Name	DBWHERECLAUSE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 4000

SHOW_IN_DASHBOARD

Attribute	**Description**
Name	SHOW_IN_DASHBOARD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

Where-Master

Attribute	**Description**
Name	Where-Master
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

COLUMN_NAME

Attribute	**Description**

Name	COLUMN_NAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

WHERE_CL

Attribute	**Description**
Name	WHERE_CL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 500

CONDITION

Attribute	**Description**
Name	CONDITION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	Indicates Field Name

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.18.2.SM-ModifyUserMaint-Req-IO-MSG.xsd

MODIFYUSERMAINT_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

USR-IO

STRTDATE

USRNAME

USRPWD

ENDDT

USRLANG

HOMEBRN

CUSTNO

LDAPUSR

TIMELEVEL

AUTOAUTH

USRSTAT

USRID

FORCPWDCHG

USRCATEG

TILLALLOW

ACCCLSALLOW

GLALLOW

USRTXNLMT

LMTSCCY

MAXTXNAMT

MAXAUTHAMT

BRNSALLOW

PRDSALLOW

PRDSACCESALLOW

TAX_IDENTIFIER

STAFFACCRESTR

DEPT_CODE

USRML

ELCMUSER

GROUP_CODE

MULTIBRN_ACCESS

OTH_RM_CUST_ACC_ALLOW

SUPERVISOR_ID

SUPERVISOR_NAME

DASHBOARD_REQD

ALERTS_ON_HOME

MFI_USER

F10_REQD

F11_REQD

F12_REQD

ACCESS_CONTROL

MAKER

MAKERSTAMP

RESTR_PWD

- *PWD*

MSGSRIGHTS

- *GEN*
- *HLD*
- *CNL*
- *TSTINP*
- *CHGNODE*
- *CHGADDR*
- *REL*
- *REINS*
- *CHGMEDIA*
- *CHGPRIOR*
- *BRNMOV*
- *PRNT*
- *TSTCHK*

HLDAUTH

CNLAUTH

TSTINPAUTH

CHGNODEAUTH

CHGADDRAUTH

RELAUTH

REINSAUTH

CHGMEDIAAUTH

BRNMOVAUTH

CHGPRIORAUTH

FTUPL

LNKCONT

MOVQ

CHGBRNIN

CHGADDRIN

AUTHRGHTS

CHGMSG

CHGMSGAUTH

CHGFORCCOVMATCH

CHANGE_FORCE_RELEASE_FUND

SUPPRESS

DELMSG

QUEUERIGHTS

QUEUE

USERTILLS

TILLID

USERACCCLASS

ACCCLS

USERGLREST

NODEGL

USERGLEXCEPT

EXPNODEGL

EXCEPLEAFGL

USERLIMITSROLE

LMTBRN

LMTSROLE

USERBRANCHES

BRNSBRN

USERPRODUCTS

PRDPRDCD

USERACCESSPRODUCTS

PRDACCESSPRDCD

USERFUNCDISALLOW

FUNCDISALLOWFUNCID

USERROLE

ROLEBRNCD

USRROLEID

USERSFUNCTIONS

USERFUNCBRNCD

USERFUNCFUNCID

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

USERFUNCSCTRL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

CONTROL15

CONTROL16

USERFUNCSCTRSTR

Grp-Restriction

GROUP_CODE

Centralisation

USRROLEID

Dshdet

UDFDETAILS

FLDNAM

FLDVAL

MODIFYUSERMAINT_IOPK_REQ

Attribute	Description
Name	MODIFYUSERMAINT_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

USR-IO

Attribute	Description

Name	USR-IO
Datatype	
Description	

STRTDATE

Attribute	Description
Name	STRTDATE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

USRNAME

Attribute	Description
Name	USRNAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

USRPWD

Attribute	Description
Name	USRPWD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>32</td></tr></table>

ENDDT

Attribute	Description
Name	ENDDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

USRLANG

Attribute	Description
Name	USRLANG

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

HOMEBRN

Attribute	Description
Name	HOMEBRN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

LDAPUSR

Attribute	Description
Name	LDAPUSR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>500</td></tr></table>

TIMELEVEL

Attribute	Description
Name	TIMELEVEL

Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 9

AUTOAUTH

Attribute	**Description**
Name	AUTOAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

USRSTAT

Attribute	**Description**
Name	USRSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / E,H,D,L

USRID

Attribute	**Description**
Name	USRID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12

FORCPWDCHG

Attribute	**Description**
Name	FORCPWDCHG
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

USRCATEG

Attribute	**Description**
Name	USRCATEG
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,B

TILLALLOW

Attribute	**Description**
Name	TILLALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

ACCCLSALLOW

Attribute	**Description**
Name	ACCCLSALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

GLALLOW

Attribute	**Description**
Name	GLALLOW
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

USRTXNLMT

Attribute	**Description**
Name	USRTXNLMT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,R,N

LMTSCCY

Attribute	**Description**
Name	LMTSCCY
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

MAXTXNAMT

Attribute	**Description**
Name	MAXTXNAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

MAXAUTHAMT

Attribute	**Description**
Name	MAXAUTHAMT
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: totalDigits / 22

BRNSALLOW

Attribute	**Description**
Name	BRNSALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

PRDSALLOW

Attribute	**Description**
Name	PRDSALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

PRDSACCESALLOW

Attribute	**Description**
Name	PRDSACCESALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TAX_IDENTIFIER

Attribute	**Description**
Name	TAX_IDENTIFIER
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

STAFFACCRESTR

Attribute	Description
Name	STAFFACCRESTR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

DEPT_CODE

Attribute	Description
Name	DEPT_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

USRML

Attribute	Description
Name	USRML
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

ELCMUSER

Attribute	Description
Name	ELCMUSER
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

GROUP_CODE

Attribute	**Description**
Name	GROUP_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

MULTIBRN_ACCESS

Attribute	**Description**
Name	MULTIBRN_ACCESS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

OTH_RM_CUST_ACC_ALLOW

Attribute	**Description**
Name	OTH_RM_CUST_ACC_ALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

SUPERVISOR_ID

Attribute	**Description**
Name	SUPERVISOR_ID
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 80

SUPERVISOR_NAME

Attribute	**Description**
Name	SUPERVISOR_NAME
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

DASHBOARD_REQD

Attribute	**Description**
Name	DASHBOARD_REQD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

ALERTS_ON_HOME

Attribute	**Description**
Name	ALERTS_ON_HOME
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

MFI_USER

Attribute	**Description**
Name	MFI_USER
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

F10_REQD

Attribute	**Description**
Name	F10_REQD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

F11_REQD

Attribute	**Description**
Name	F11_REQD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

F12_REQD

Attribute	**Description**
Name	F12_REQD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

ACCESS_CONTROL

Attribute	**Description**
Name	ACCESS_CONTROL
Datatype	String
Description	

Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,G,B

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

RESTR_PWD

Attribute	**Description**
Name	RESTR_PWD
Datatype	
Description	
Attribute	**Attribute** / **Description**: maxOccurs / unbounded

PWD

Attribute	**Description**
Name	PWD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12

MSGSRIGHTS

Attribute	Description
Name	MSGSRIGHTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

HLD

Attribute	Description
Name	HLD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CNL

Attribute	Description
Name	CNL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TSTINP

Attribute	Description
Name	TSTINP

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGNODE

Attribute	**Description**
Name	CHGNODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGADDR

Attribute	**Description**
Name	CHGADDR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

REL

Attribute	**Description**
Name	REL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

REINS

Attribute	**Description**
Name	REINS

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGMEDIA

Attribute	Description
Name	CHGMEDIA
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGPRIOR

Attribute	Description
Name	CHGPRIOR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

BRNMOV

Attribute	Description
Name	BRNMOV
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

PRNT

Attribute	Description
Name	PRNT

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TSTCHK

Attribute	Description
Name	TSTCHK
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

HLDAUTH

Attribute	Description
Name	HLDAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CNLAUTH

Attribute	Description
Name	CNLAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TSTINPAUTH

Attribute	Description
Name	TSTINPAUTH

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGNODEAUTH

Attribute	Description
Name	CHGNODEAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGADDRAUTH

Attribute	Description
Name	CHGADDRAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

RELAUTH

Attribute	Description
Name	RELAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

REINSAUTH

Attribute	Description
Name	REINSAUTH

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGMEDIAAUTH

Attribute	Description
Name	CHGMEDIAAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

BRNMOVAUTH

Attribute	Description
Name	BRNMOVAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGPRIORAUTH

Attribute	Description
Name	CHGPRIORAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

FTUPL

Attribute	Description
Name	FTUPL

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

LNKCONT

Attribute	Description
Name	LNKCONT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

MOVQ

Attribute	Description
Name	MOVQ
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGBRNIN

Attribute	Description
Name	CHGBRNIN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGADDRIN

Attribute	Description
Name	CHGADDRIN

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

AUTHRGHTS

Attribute	Description
Name	AUTHRGHTS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGMSG

Attribute	Description
Name	CHGMSG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGMSGAUTH

Attribute	Description
Name	CHGMSGAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGFORCCOVMATCH

Attribute	Description
Name	CHGFORCCOVMATCH

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHANGE_FORCE_RELEASE_FUND

Attribute	**Description**
Name	CHANGE_FORCE_RELEASE_FUND
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

SUPPRESS

Attribute	**Description**
Name	SUPPRESS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

DELMSG

Attribute	**Description**
Name	DELMSG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

QUEUERIGHTS

Attribute	**Description**
Name	QUEUERIGHTS

Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

QUEUE

Attribute	Description
Name	QUEUE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

USERTILLS

Attribute	Description
Name	USERTILLS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TILLID

Attribute	Description
Name	TILLID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

USERACCCLASS

Attribute	Description
Name	USERACCCLASS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	6

USERGLREST

Attribute	Description
Name	USERGLREST
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

NODEGL

Attribute	Description
Name	NODEGL
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	9

USERGLEXCEPT

Attribute	Description
Name	USERGLEXCEPT
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

EXPNODEGL

Attribute	Description
Name	EXPNODEGL
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	9

EXCEPLEAFGL

Attribute	Description
Name	EXCEPLEAFGL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

USERLIMITSROLE

Attribute	Description
Name	USERLIMITSROLE
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

LMTBRN

Attribute	Description
Name	LMTBRN
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

LMTSROLE

Attribute	Description
Name	LMTSROLE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

USERBRANCHES

Attribute	Description
Name	USERBRANCHES
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

BRNSBRN

Attribute	Description
Name	BRNSBRN
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	3

USERPRODUCTS

Attribute	Description
Name	USERPRODUCTS
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

PRDPRDCD

Attribute	Description
Name	PRDPRDCD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	4

USERACCESSPRODUCTS

Attribute	Description
Name	USERACCESSPRODUCTS
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

PRDACCESSPRDCD

Attribute	Description
Name	PRDACCESSPRDCD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	4

USERFUNCDISALLOW

Attribute	Description
Name	USERFUNCDISALLOW
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

FUNCDISALLOWFUNCID

Attribute	Description
Name	FUNCDISALLOWFUNCID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

USERROLE

Attribute	Description
Name	USERROLE
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ROLEBRNCD

Attribute	Description
Name	ROLEBRNCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

USRROLEID

Attribute	Description
Name	USRROLEID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

USERSFUNCTIONS

Attribute	Description
Name	USERSFUNCTIONS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

USERFUNCBRNCD

Attribute	Description
Name	USERFUNCBRNCD
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	3

USERFUNCFUNCID

Attribute	Description
Name	USERFUNCFUNCID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	8

CONTROL1

Attribute	Description
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL2

Attribute	Description
Name	CONTROL2
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL3

Attribute	Description
Name	CONTROL3
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL4

Attribute	Description
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL5

Attribute	Description
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL6

Attribute	Description
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL8

Attribute	Description
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL9

Attribute	Description
Name	CONTROL9
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

USERFUNCSCTRL10

Attribute	Description
Name	USERFUNCSCTRL10
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL11

Attribute	Description
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL12

Attribute	Description
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL13

Attribute	Description
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL14

Attribute	Description
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL15

Attribute	Description
Name	CONTROL15
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

USERFUNCSCTRSTR

Attribute	Description
Name	USERFUNCSCTRSTR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

Grp-Restriction

Attribute	Description
Name	Grp-Restriction
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

GROUP_CODE

Attribute	Description
Name	GROUP_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>40</td></tr></table>

Centralisation

Attribute	Description
Name	Centralisation
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

USRROLEID

Attribute	Description
Name	USRROLEID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	15

Dshdet

Attribute	Description
Name	Dshdet
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	150
minLength	0

2.18.3.SM-ModifyUserMaint-Res-Full-MSG.xsd

MODIFYUSERMAINT_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

USR-Full

STRTDATE

USRNAME

USRPWD

ENDDT

USRLANG

HOMEBRN

CUSTNO

LDAPUSR

TIMELEVEL

AUTOAUTH

USRSTAT

USRID

EXTUSRREF

USRCATEG

TILLALLOW

ACCCLSALLOW

GLALLOW

USRTXNLMT

LMTSCCY

MAXTXNAMT

MAXAUTHAMT

BRNSALLOW

PRDSALLOW

PRDSACCESALLOW

TAX_IDENTIFIER

AMOUNT_FORMAT

DATE_FORMAT

STAFFACCRESTR

DEPT_CODE

DEPT_DESC

USRML

ELCMUSER

GROUP_CODE

MULTIBRN_ACCESS

OTH_RM_CUST_ACC_ALLOW

SUPERVISOR_ID

SUPERVISOR_NAME

DASHBOARD_REQD

ALERTS_ON_HOME

REFERENCE_NO

NO_CUMULATIVE_LOGINS

NO_SUCCESSIVE_LOGINS

SCREENSAVERTIMEOUTINSECONDS

MFI_USER

F10_REQD

F11_REQD

F12_REQD

ACCESS_CONTROL

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

RESTR_PWD

- *PWD*

MSGSRIGHTS

- *GEN*
- *HLD*
- *CNL*
- *TSTINP*
- *CHGNODE*
- *CHGADDR*
- *REL*

REINS

CHGMEDIA

CHGPRIOR

BRNMOV

PRNT

TSTCHK

HLDAUTH

CNLAUTH

TSTINPAUTH

CHGNODEAUTH

CHGADDRAUTH

RELAUTH

REINSAUTH

CHGMEDIAAUTH

BRNMOVAUTH

CHGPRIORAUTH

FTUPL

LNKCONT

MOVQ

CHGBRNIN

CHGADDRIN

AUTHRGHTS

CHGMSG

CHGMSGAUTH

CHGFORCCOVMATCH

CHANGE_FORCE_RELEASE_FUND

SUPPRESS

DELMSG

QUEUERIGHTS

QUEUE

USERTILLS

TILLID

TILLBRNCD

USERACCCLASS

ACCCLS

USERGLREST

NODEGL

USERGLEXCEPT

EXCEPLEAFGL

USERLIMITSROLE

LMTBRN

LMTSROLE

QLMTCCY

QINPLMT

QAUTHLMT

USERBRANCHES

BRNSBRN

BRNNAME

USERPRODUCTS

PRDPRDCD

PRDDESC

USERACCESSPRODUCTS

PRDACCESSPRDCD

PRDDESC

USERFUNCDISALLOW

FUNCDISALLOWFUNCID

USERROLE

ROLEBRNCD

USRROLEID

MASTERROLEDESC

USERSFUNCTIONS

USERFUNCBRNCD

USERFUNCFUNCID

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

USERFUNCSCTRL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

CONTROL15

CONTROL16

Grp-Restriction

GROUP_CODE

GROUP_DESC

Centralisation

USRROLEID

ROLDESC

Dshmst

USRID

USRNAME

Dshdet

FUNCTIONID

DESCRIPTION

SEQUENCE_NO

DBWHERECLAUSE

SHOW_IN_DASHBOARD

Where-Master

COLUMN_NAME

WHERE_CL

CONDITION

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYUSERMAINT_FSFS_RES

Attribute	Description
Name	MODIFYUSERMAINT_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE

Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

USR-Full

Attribute	Description

Name	USR-Full
Datatype	
Description	

STRTDATE

Attribute	Description
Name	STRTDATE
Datatype	String
Description	

USRNAME

Attribute	Description
Name	USRNAME
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 35

USRPWD

Attribute	Description
Name	USRPWD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

ENDDT

Attribute	Description
Name	ENDDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

USRLANG

Attribute	Description
Name	USRLANG
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

HOMEBRN

Attribute	Description
Name	HOMEBRN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

LDAPUSR

Attribute	Description
Name	LDAPUSR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 500

TIMELEVEL

Attribute	Description
Name	TIMELEVEL
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 9

AUTOAUTH

Attribute	Description
Name	AUTOAUTH
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

USRSTAT

Attribute	**Description**
Name	USRSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,H,D,L

USRID

Attribute	**Description**
Name	USRID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12

EXTUSRREF

Attribute	**Description**
Name	EXTUSRREF
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

USRCATEG

Attribute	**Description**
Name	USRCATEG
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	
	Restrictions / **Description**: enumeration / S,B

TILLALLOW

Attribute	Description
Name	TILLALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

ACCCLSALLOW

Attribute	Description
Name	ACCCLSALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

GLALLOW

Attribute	Description
Name	GLALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

USRTXNLMT

Attribute	Description
Name	USRTXNLMT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	U,R,N

LMTSCCY

Attribute	Description
Name	LMTSCCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

MAXTXNAMT

Attribute	Description
Name	MAXTXNAMT
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

MAXAUTHAMT

Attribute	Description
Name	MAXAUTHAMT
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

BRNSALLOW

Attribute	Description
Name	BRNSALLOW
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: enumeration / A,D

PRDSALLOW

Attribute	Description
Name	PRDSALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

PRDSACCESALLOW

Attribute	Description
Name	PRDSACCESALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TAX_IDENTIFIER

Attribute	Description
Name	TAX_IDENTIFIER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

AMOUNT_FORMAT

Attribute	Description
Name	AMOUNT_FORMAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	.,,,.,,

DATE_FORMAT

Attribute	Description
Name	DATE_FORMAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	M/d/yyyy

STAFFACCRESTR

Attribute	Description
Name	STAFFACCRESTR
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

DEPT_CODE

Attribute	Description
Name	DEPT_CODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

DEPT_DESC

Attribute	Description
Name	DEPT_DESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	50

USRML

Attribute	Description
Name	USRML
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	50

ELCMUSER

Attribute	Description
Name	ELCMUSER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

GROUP_CODE

Attribute	Description
Name	GROUP_CODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	A,D

MULTIBRN_ACCESS

Attribute	Description
Name	MULTIBRN_ACCESS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: enumeration / Y,N

OTH_RM_CUST_ACC_ALLOW

Attribute	Description
Name	OTH_RM_CUST_ACC_ALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

SUPERVISOR_ID

Attribute	Description
Name	SUPERVISOR_ID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 80

SUPERVISOR_NAME

Attribute	Description
Name	SUPERVISOR_NAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

DASHBOARD_REQD

Attribute	Description
Name	DASHBOARD_REQD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: enumeration / Y,N

ALERTS_ON_HOME

Attribute	Description
Name	ALERTS_ON_HOME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

NO_CUMULATIVE_LOGINS

Attribute	Description
Name	NO_CUMULATIVE_LOGINS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

NO_SUCCESSIVE_LOGINS

Attribute	Description
Name	NO_SUCCESSIVE_LOGINS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22

SCREENSAVERTIMEOUTINSECONDS

Attribute	Description
Name	SCREENSAVERTIMEOUTINSECONDS
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

MFI_USER

Attribute	Description
Name	MFI_USER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

F10_REQD

Attribute	Description
Name	F10_REQD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

F11_REQD

Attribute	Description
Name	F11_REQD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: enumeration / Y,N

F12_REQD

Attribute	Description
Name	F12_REQD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

ACCESS_CONTROL

Attribute	Description
Name	ACCESS_CONTROL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,G,B

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: maxLength / 35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	1

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

RESTR_PWD

Attribute	Description
Name	RESTR_PWD
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PWD

Attribute	Description
Name	PWD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12

MSGSRIGHTS

Attribute	Description
Name	MSGSRIGHTS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

HLD

Attribute	**Description**
Name	HLD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CNL

Attribute	**Description**
Name	CNL
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TSTINP

Attribute	**Description**
Name	TSTINP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGNODE

Attribute	**Description**
Name	CHGNODE
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

CHGADDR

Attribute	**Description**
Name	CHGADDR
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

REL

Attribute	**Description**
Name	REL
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

REINS

Attribute	**Description**
Name	REINS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGMEDIA

Attribute	**Description**
Name	CHGMEDIA
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

CHGPRIOR

Attribute	**Description**
Name	CHGPRIOR
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

BRNMOV

Attribute	**Description**
Name	BRNMOV
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

PRNT

Attribute	**Description**
Name	PRNT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TSTCHK

Attribute	**Description**
Name	TSTCHK
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

HLDAUTH

Attribute	**Description**
Name	HLDAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CNLAUTH

Attribute	**Description**
Name	CNLAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TSTINPAUTH

Attribute	**Description**
Name	TSTINPAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGNODEAUTH

Attribute	**Description**
Name	CHGNODEAUTH
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

CHGADDRAUTH

Attribute	**Description**
Name	CHGADDRAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

RELAUTH

Attribute	**Description**
Name	RELAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

REINSAUTH

Attribute	**Description**
Name	REINSAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGMEDIAAUTH

Attribute	**Description**
Name	CHGMEDIAAUTH
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

BRNMOVAUTH

Attribute	**Description**
Name	BRNMOVAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGPRIORAUTH

Attribute	**Description**
Name	CHGPRIORAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

FTUPL

Attribute	**Description**
Name	FTUPL
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

LNKCONT

Attribute	**Description**
Name	LNKCONT
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

MOVQ

Attribute	**Description**
Name	MOVQ
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGBRNIN

Attribute	**Description**
Name	CHGBRNIN
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGADDRIN

Attribute	**Description**
Name	CHGADDRIN
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

AUTHRGHTS

Attribute	**Description**
Name	AUTHRGHTS
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGMSG

Attribute	**Description**
Name	CHGMSG
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGMSGAUTH

Attribute	**Description**
Name	CHGMSGAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGFORCCOVMATCH

Attribute	**Description**
Name	CHGFORCCOVMATCH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHANGE_FORCE_RELEASE_FUND

Attribute	**Description**
Name	CHANGE_FORCE_RELEASE_FUND
Datatype	String
Description	

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

DELMSG

Attribute	Description
Name	DELMSG
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

QUEUERIGHTS

Attribute	Description
Name	QUEUERIGHTS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

QUEUE

Attribute	Description
Name	QUEUE
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	10

USERTILLS

Attribute	Description
Name	USERTILLS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

TILLID

Attribute	Description
Name	TILLID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12

TILLBRNCD

Attribute	Description
Name	TILLBRNCD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

USERACCCLASS

Attribute	Description
Name	USERACCCLASS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	6

USERGLREST

Attribute	Description
Name	USERGLREST
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NODEGL

Attribute	Description
Name	NODEGL
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	9

USERGLEXCEPT

Attribute	Description
Name	USERGLEXCEPT
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

EXCEPLEAFGL

Attribute	Description
Name	EXCEPLEAFGL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

USERLIMITSROLE

Attribute	Description
Name	USERLIMITSROLE
Datatype	

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

LMTBRN

Attribute	Description
Name	LMTBRN
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

LMTSROLE

Attribute	Description
Name	LMTSROLE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

QLMTCCY

Attribute	Description
Name	QLMTCCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

QINPLMT

Attribute	Description
Name	QINPLMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22

QAUTHLMT

Attribute	Description
Name	QAUTHLMT
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

USERBRANCHES

Attribute	Description
Name	USERBRANCHES
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

BRNSBRN

Attribute	Description
Name	BRNSBRN
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

USERPRODUCTS

Attribute	Description

Name	USERPRODUCTS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PRDPRDCD

Attribute	Description
Name	PRDPRDCD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	4

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

USERACCESSPRODUCTS

Attribute	Description
Name	USERACCESSPRODUCTS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PRDACCESSPRDCD

Attribute	Description
Name	PRDACCESSPRDCD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	4

PRDDESC

Attribute	Description

Name	PRDDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

USERFUNCDISALLOW

Attribute	**Description**
Name	USERFUNCDISALLOW
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FUNCDISALLOWFUNCID

Attribute	**Description**
Name	FUNCDISALLOWFUNCID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 8

USERROLE

Attribute	**Description**
Name	USERROLE
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ROLEBRNCD

Attribute	**Description**
Name	ROLEBRNCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

USRROLEID

Attribute	**Description**

Name	USRROLEID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

MASTERROLEDESC

Attribute	**Description**
Name	MASTERROLEDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 45

USERSFUNCTIONS

Attribute	**Description**
Name	USERSFUNCTIONS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

USERFUNCBRNCD

Attribute	**Description**
Name	USERFUNCBRNCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

USERFUNCFUNCID

Attribute	**Description**
Name	USERFUNCFUNCID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 8

CONTROL1

Attribute	**Description**

Name	CONTROL1
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL2

Attribute	**Description**
Name	CONTROL2
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL3

Attribute	**Description**
Name	CONTROL3
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL4

Attribute	**Description**
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL5

Attribute	**Description**

Name	CONTROL5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL6

Attribute	**Description**
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL7

Attribute	**Description**
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL8

Attribute	**Description**
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL9

Attribute	**Description**

Name	CONTROL9
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

USERFUNCSCTRL10

Attribute	**Description**
Name	USERFUNCSCTRL10
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL11

Attribute	**Description**
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL12

Attribute	**Description**
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL13

Attribute	**Description**

Name	CONTROL13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL14

Attribute	**Description**
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL15

Attribute	**Description**
Name	CONTROL15
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL16

Attribute	**Description**
Name	CONTROL16
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

Grp-Restriction

Attribute	**Description**

Name	Grp-Restriction
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

GROUP_CODE

Attribute	Description
Name	GROUP_CODE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	40

GROUP_DESC

Attribute	Description
Name	GROUP_DESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255

Centralisation

Attribute	Description
Name	Centralisation
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

USRROLEID

Attribute	Description
Name	USRROLEID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	15

ROLDESC

Attribute	Description

Name	ROLDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

Dshmst

Attribute	**Description**
Name	Dshmst
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

USRID

Attribute	**Description**
Name	USRID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

USRNAME

Attribute	**Description**
Name	USRNAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

Dshdet

Attribute	**Description**
Name	Dshdet
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1000

SEQUENCE_NO

Attribute	Description
Name	SEQUENCE_NO
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	22

DBWHERECLAUSE

Attribute	Description
Name	DBWHERECLAUSE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	4000

SHOW_IN_DASHBOARD

Attribute	Description

Name	SHOW_IN_DASHBOARD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

Where-Master

Attribute	**Description**
Name	Where-Master
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

COLUMN_NAME

Attribute	**Description**
Name	COLUMN_NAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

WHERE_CL

Attribute	**Description**
Name	WHERE_CL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 500

CONDITION

Attribute	**Description**
Name	CONDITION
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150; minLength / 0

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String

Description	

2.18.4.SM-ModifyUserMaint-Res-PK-MSG.xsd

- *MODIFYUSERMAINT_IOPK_RES*
  - *FCUBS_HEADER*
    - *SOURCE*
    - *UBSCOMP*
    - *MSGID*
    - *CORRELID*
    - *USERID*
    - *BRANCH*
    - *MODULEID*
    - *SERVICE*
    - *OPERATION*
    - *SOURCE_OPERATION*
    - *SOURCE_USERID*
    - *DESTINATION*
    - *MULTITRIPID*
    - *FUNCTIONID*
    - *ACTION*
    - *MSGSTAT*
    - *PASSWORD*
    - *ADDL*
      - *PARAM*
        - *NAME*
        - *VALUE*
  - *FCUBS_BODY*
    - *USR-PK*
      - *USRID*
    - *USR-IO*
      - *STRTDATE*
      - *USRNAME*
      - *USRPWD*
      - *ENDDT*

USRLANG

HOMEBRN

CUSTNO

LDAPUSR

TIMELEVEL

AUTOAUTH

USRSTAT

USRID

FORCPWDCHG

USRCATEG

TILLALLOW

ACCCLSALLOW

GLALLOW

USRTXNLMT

LMTSCCY

MAXTXNAMT

MAXAUTHAMT

BRNSALLOW

PRDSALLOW

PRDSACCESALLOW

TAX_IDENTIFIER

STAFFACCRESTR

DEPT_CODE

USRML

ELCMUSER

GROUP_CODE

MULTIBRN_ACCESS

OTH_RM_CUST_ACC_ALLOW

SUPERVISOR_ID

SUPERVISOR_NAME

DASHBOARD_REQD

ALERTS_ON_HOME

MFI_USER

F10_REQD

F11_REQD

F12_REQD

ACCESS_CONTROL

MAKER

MAKERSTAMP

RESTR_PWD

- *PWD*

MSGSRIGHTS

- *GEN*
- *HLD*
- *CNL*
- *TSTINP*
- *CHGNODE*
- *CHGADDR*
- *REL*
- *REINS*
- *CHGMEDIA*
- *CHGPRIOR*
- *BRNMOV*
- *PRNT*
- *TSTCHK*
- *HLDAUTH*
- *CNLAUTH*
- *TSTINPAUTH*
- *CHGNODEAUTH*
- *CHGADDRAUTH*
- *RELAUTH*
- *REINSAUTH*
- *CHGMEDIAAUTH*
- *BRNMOVAUTH*

CHGPRIORAUTH

FTUPL

LNKCONT

MOVQ

CHGBRNIN

CHGADDRIN

AUTHRGHTS

CHGMSG

CHGMSGAUTH

CHGFORCCOVMATCH

CHANGE_FORCE_RELEASE_FUND

SUPPRESS

DELMSG

QUEUERIGHTS

QUEUE

USERTILLS

TILLID

USERACCCLASS

ACCCLS

USERGLREST

NODEGL

USERGLEXCEPT

EXPNODEGL

EXCEPLEAFGL

USERLIMITSROLE

LMTBRN

LMTSROLE

USERBRANCHES

BRNSBRN

USERPRODUCTS

PRDPRDCD

USERACCESSPRODUCTS

PRDACCESSPRDCD

USERFUNCDISALLOW

FUNCDISALLOWFUNCID

USERROLE

ROLEBRNCD

USRROLEID

USERSFUNCTIONS

USERFUNCBRNCD

USERFUNCFUNCID

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

USERFUNCSCTRL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

CONTROL15

CONTROL16

USERFUNCSCTRSTR

Grp-Restriction

GROUP_CODE

Centralisation

USRROLEID

Dshdet

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYUSERMAINT_IOPK_RES

Attribute	Description
Name	MODIFYUSERMAINT_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

USR-PK

Attribute	Description

Name	USR-PK
Datatype	
Description	

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12

USR-IO

Attribute	Description
Name	USR-IO
Datatype	
Description	

STRTDATE

Attribute	Description
Name	STRTDATE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

USRNAME

Attribute	Description
Name	USRNAME
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

USRPWD

Attribute	Description
Name	USRPWD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: maxLength / 32

ENDDT

Attribute	Description
Name	ENDDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

USRLANG

Attribute	Description
Name	USRLANG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

HOMEBRN

Attribute	Description
Name	HOMEBRN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

LDAPUSR

Attribute	Description
Name	LDAPUSR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 500

TIMELEVEL

Attribute	Description
Name	TIMELEVEL
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 9

AUTOAUTH

Attribute	Description
Name	AUTOAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

USRSTAT

Attribute	Description
Name	USRSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	E,H,D,L

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12

FORCPWDCHG

Attribute	Description
Name	FORCPWDCHG
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

USRCATEG

Attribute	Description
Name	USRCATEG
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	S,B

TILLALLOW

Attribute	Description
Name	TILLALLOW
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	A,D

ACCCLSALLOW

Attribute	Description
Name	ACCCLSALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

GLALLOW

Attribute	Description
Name	GLALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

USRTXNLMT

Attribute	Description
Name	USRTXNLMT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,R,N

LMTSCCY

Attribute	Description
Name	LMTSCCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

MAXTXNAMT

Attribute	Description
Name	MAXTXNAMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

MAXAUTHAMT

Attribute	Description
Name	MAXAUTHAMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

BRNSALLOW

Attribute	Description
Name	BRNSALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

PRDSALLOW

Attribute	Description
Name	PRDSALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

PRDSACCESALLOW

Attribute	Description
Name	PRDSACCESALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

TAX_IDENTIFIER

Attribute	Description
Name	TAX_IDENTIFIER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>11</td></tr></table>

STAFFACCRESTR

Attribute	Description
Name	STAFFACCRESTR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

DEPT_CODE

Attribute	Description
Name	DEPT_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

USRML

Attribute	Description
Name	USRML
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>50</td></tr></table>

ELCMUSER

Attribute	Description
Name	ELCMUSER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

GROUP_CODE

Attribute	Description
Name	GROUP_CODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>A,D</td></tr></table>

MULTIBRN_ACCESS

Attribute	Description
Name	MULTIBRN_ACCESS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

OTH_RM_CUST_ACC_ALLOW

Attribute	Description
Name	OTH_RM_CUST_ACC_ALLOW
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

SUPERVISOR_ID

Attribute	Description
Name	SUPERVISOR_ID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>80</td></tr></table>

SUPERVISOR_NAME

Attribute	Description
Name	SUPERVISOR_NAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

DASHBOARD_REQD

Attribute	Description
Name	DASHBOARD_REQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

ALERTS_ON_HOME

Attribute	Description
Name	ALERTS_ON_HOME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

MFI_USER

Attribute	Description
Name	MFI_USER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

F10_REQD

Attribute	Description
Name	F10_REQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

F11_REQD

Attribute	Description
Name	F11_REQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

F12_REQD

Attribute	Description
Name	F12_REQD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

ACCESS_CONTROL

Attribute	Description
Name	ACCESS_CONTROL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,G,B

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

RESTR_PWD

Attribute	Description
Name	RESTR_PWD
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PWD

Attribute	Description
Name	PWD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MSGSRIGHTS

Attribute	Description
Name	MSGSRIGHTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

HLD

Attribute	Description
Name	HLD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CNL

Attribute	Description
Name	CNL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TSTINP

Attribute	Description
Name	TSTINP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGNODE

Attribute	Description
Name	CHGNODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGADDR

Attribute	Description
Name	CHGADDR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

REL

Attribute	Description
Name	REL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

REINS

Attribute	Description
Name	REINS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGMEDIA

Attribute	Description
Name	CHGMEDIA
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGPRIOR

Attribute	Description
Name	CHGPRIOR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

BRNMOV

Attribute	Description
Name	BRNMOV
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

PRNT

Attribute	Description
Name	PRNT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TSTCHK

Attribute	Description
Name	TSTCHK
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

HLDAUTH

Attribute	Description
Name	HLDAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CNLAUTH

Attribute	Description
Name	CNLAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TSTINPAUTH

Attribute	Description
Name	TSTINPAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGNODEAUTH

Attribute	Description
Name	CHGNODEAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGADDRAUTH

Attribute	Description
Name	CHGADDRAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

RELAUTH

Attribute	Description
Name	RELAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

REINSAUTH

Attribute	Description
Name	REINSAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGMEDIAAUTH

Attribute	Description
Name	CHGMEDIAAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

BRNMOVAUTH

Attribute	Description
Name	BRNMOVAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGPRIORAUTH

Attribute	Description
Name	CHGPRIORAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

FTUPL

Attribute	Description
Name	FTUPL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

LNKCONT

Attribute	Description
Name	LNKCONT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

MOVQ

Attribute	Description
Name	MOVQ
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGBRNIN

Attribute	Description
Name	CHGBRNIN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGADDRIN

Attribute	Description
Name	CHGADDRIN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

AUTHRGHTS

Attribute	Description
Name	AUTHRGHTS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGMSG

Attribute	Description
Name	CHGMSG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGMSGAUTH

Attribute	Description
Name	CHGMSGAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGFORCCOVMATCH

Attribute	Description
Name	CHGFORCCOVMATCH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHANGE_FORCE_RELEASE_FUND

Attribute	Description
Name	CHANGE_FORCE_RELEASE_FUND
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

DELMSG

Attribute	Description
Name	DELMSG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

QUEUERIGHTS

Attribute	Description
Name	QUEUERIGHTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

QUEUE

Attribute	Description
Name	QUEUE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

USERTILLS

Attribute	Description
Name	USERTILLS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TILLID

Attribute	Description
Name	TILLID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

USERACCCLASS

Attribute	Description

Name	USERACCCLASS
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	6

USERGLREST

Attribute	Description
Name	USERGLREST
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

NODEGL

Attribute	Description
Name	NODEGL
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	9

USERGLEXCEPT

Attribute	Description
Name	USERGLEXCEPT
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

EXPNODEGL

Attribute	Description
Name	EXPNODEGL
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	9

EXCEPLEAFGL

Attribute	Description
Name	EXCEPLEAFGL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

USERLIMITSROLE

Attribute	Description
Name	USERLIMITSROLE
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

LMTBRN

Attribute	Description
Name	LMTBRN
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

LMTSROLE

Attribute	Description
Name	LMTSROLE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

USERBRANCHES

Attribute	Description

Name	USERBRANCHES
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

BRNSBRN

Attribute	Description
Name	BRNSBRN
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

USERPRODUCTS

Attribute	Description
Name	USERPRODUCTS
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

PRDPRDCD

Attribute	Description
Name	PRDPRDCD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	4

USERACCESSPRODUCTS

Attribute	Description
Name	USERACCESSPRODUCTS
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

PRDACCESSPRDCD

Attribute	Description
Name	PRDACCESSPRDCD
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	4

USERFUNCDISALLOW

Attribute	Description
Name	USERFUNCDISALLOW
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

FUNCDISALLOWFUNCID

Attribute	Description
Name	FUNCDISALLOWFUNCID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	8

USERROLE

Attribute	Description
Name	USERROLE
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ROLEBRNCD

Attribute	Description
Name	ROLEBRNCD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

USRROLEID

Attribute	Description
Name	USRROLEID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	15

USERSFUNCTIONS

Attribute	Description
Name	USERSFUNCTIONS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

USERFUNCBRNCD

Attribute	Description
Name	USERFUNCBRNCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

USERFUNCFUNCID

Attribute	Description
Name	USERFUNCFUNCID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

CONTROL1

Attribute	Description
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL2

Attribute	Description
Name	CONTROL2
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL3

Attribute	Description
Name	CONTROL3
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL4

Attribute	Description
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL5

Attribute	Description
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL6

Attribute	Description
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL8

Attribute	Description
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL9

Attribute	Description
Name	CONTROL9
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

USERFUNCSCTRL10

Attribute	Description
Name	USERFUNCSCTRL10
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL11

Attribute	Description
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL12

Attribute	Description
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL13

Attribute	Description
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL14

Attribute	Description
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: totalDigits / 22

CONTROL15

Attribute	Description
Name	CONTROL15
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

USERFUNCSCTRSTR

Attribute	Description
Name	USERFUNCSCTRSTR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

Grp-Restriction

Attribute	Description
Name	Grp-Restriction
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

GROUP_CODE

Attribute	Description
Name	GROUP_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 40

Centralisation

Attribute	Description
Name	Centralisation
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

USRROLEID

Attribute	Description
Name	USRROLEID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

Dshdet

Attribute	Description
Name	Dshdet
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength 105; minLength 1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 150; minLength 0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs 0; maxOccurs unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	**Attribute** / **Description**: maxOccurs unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC

Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.19.QuerySMDBANKP

2.19.1.SM-QuerySMDBANKP-Req-IO-MSG.xsd

QUERYSMDBANKP_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Parameters-IO

SITE_CODE

QUERYSMDBANKP_IOFS_REQ

Attribute	Description
Name	QUERYSMDBANKP_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID

Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String

Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Parameters-IO

Attribute	Description
Name	Smtbs-Parameters-IO
Datatype	
Description	

SITE_CODE

Attribute	Description
Name	SITE_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

2.19.2.SM-QuerySMDBANKP-Res-Full-MSG.xsd

QUERYSMDBANKP_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Parameters-IO

SITE_CODE

Smtbs-Parameters-Full

HEAD_OFFICE

SITE_CODE

ACTIVATION_KEY

INVALID_LOGINS_CUM

INVALID_LOGINS_SUC

PWD_PREVENT_REUSE

PWD_CHANGE_AFTER

MAXIMUM

MINIMUM

PWD_EXPIRY_MSG_DAYS

ARCHIVAL_PERIOD

CONCHAR_PWD_NUM

FREQ_PWD_CHG

MIN_PWD_NUMERIC_LENGTH

LEGAL_NOTICE

DORMANCY_DAYS

DISPLAY_LEGAL_NOTICE

MIN_SPECIALCHAR_LENGTH

MIN_LOWERCASE_CHAR

MIN_UPPERCASE_CHAR

SCREENSAVERREQUIRED

SCREENSAVERTIMEOUTINSECONDS

SCREENSAVERMODIFIABLEBYUSER

PASSWORDEXTERNAL

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Smtbs-Branch-Restr

RESTR_TYPE

DESCRIPTION

Smtbs-Restrictive-Passwd

PASSWORD

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYSMDBANKP_IOFS_RES

Attribute	Description
Name	QUERYSMDBANKP_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Parameters-IO

Attribute	Description
Name	Smtbs-Parameters-IO
Datatype	
Description	

SITE_CODE

Attribute	Description
Name	SITE_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

Smtbs-Parameters-Full

Attribute	Description
Name	Smtbs-Parameters-Full
Datatype	
Description	

HEAD_OFFICE

Attribute	Description
Name	HEAD_OFFICE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

SITE_CODE

Attribute	Description
Name	SITE_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

ACTIVATION_KEY

Attribute	Description
Name	ACTIVATION_KEY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 24

INVALID_LOGINS_CUM

Attribute	Description
Name	INVALID_LOGINS_CUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 6; maxInclusive / 99

INVALID_LOGINS_SUC

Attribute	Description
Name	INVALID_LOGINS_SUC
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 1; minInclusive / 3; maxInclusive / 5

PWD_PREVENT_REUSE

Attribute	Description
Name	PWD_PREVENT_REUSE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

PWD_CHANGE_AFTER

Attribute	Description
Name	PWD_CHANGE_AFTER
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3; minInclusive / 15; maxInclusive / 180

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 12; maxInclusive / 30

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	6
maxInclusive	11

PWD_EXPIRY_MSG_DAYS

Attribute	Description
Name	PWD_EXPIRY_MSG_DAYS
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1
maxInclusive	5

ARCHIVAL_PERIOD

Attribute	Description
Name	ARCHIVAL_PERIOD
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	3

CONCHAR_PWD_NUM

Attribute	Description
Name	CONCHAR_PWD_NUM
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2

FREQ_PWD_CHG

Attribute	Description
Name	FREQ_PWD_CHG
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2 minInclusive / 0

MIN_PWD_NUMERIC_LENGTH

Attribute	**Description**
Name	MIN_PWD_NUMERIC_LENGTH
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2 minInclusive / 1

LEGAL_NOTICE

Attribute	**Description**
Name	LEGAL_NOTICE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

DORMANCY_DAYS

Attribute	**Description**
Name	DORMANCY_DAYS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 2 minInclusive / 1

DISPLAY_LEGAL_NOTICE

Attribute	**Description**

Name	DISPLAY_LEGAL_NOTICE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

MIN_SPECIALCHAR_LENGTH

Attribute	**Description**
Name	MIN_SPECIALCHAR_LENGTH
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

MIN_LOWERCASE_CHAR

Attribute	**Description**
Name	MIN_LOWERCASE_CHAR
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

MIN_UPPERCASE_CHAR

Attribute	**Description**
Name	MIN_UPPERCASE_CHAR
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

SCREENSAVERREQUIRED

Attribute	Description
Name	SCREENSAVERREQUIRED
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

SCREENSAVERTIMEOUTINSECONDS

Attribute	Description
Name	SCREENSAVERTIMEOUTINSECONDS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

SCREENSAVERMODIFIABLEBYUSER

Attribute	Description
Name	SCREENSAVERMODIFIABLEBYUSER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

PASSWORDEXTERNAL

Attribute	Description
Name	PASSWORDEXTERNAL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Smtbs-Branch-Restr

Attribute	Description
Name	Smtbs-Branch-Restr
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

RESTR_TYPE

Attribute	Description
Name	RESTR_TYPE
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

Smtbs-Restrictive-Passwd

Attribute	Description
Name	Smtbs-Restrictive-Passwd
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description

Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.20.QuerySMDRLMNE

2.20.1.SM-QuerySMDRLMNE-Req-IO-MSG.xsd

QUERYSMDRLMNE_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Role-Limit-IO

ROLEID2

QUERYSMDRLMNE_IOFS_REQ

Attribute	Description
Name	QUERYSMDRLMNE_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description

Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String

Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Role-Limit-IO

Attribute	Description
Name	Smtbs-Role-Limit-IO
Datatype	
Description	

ROLEID2

Attribute	Description
Name	ROLEID2
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

2.20.2.SM-QuerySMDRLMNE-Res-Full-MSG.xsd

QUERYSMDRLMNE_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Role-Limit-IO

ROLEID2

Smtbs-Role-Limit-Full

ROLEID2

DESCRIPTION

LIMIT_CCY

INPUT_LIMIT

AUTHORIZATION_LIMIT

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYSMDRLMNE_IOFS_RES

Attribute	Description
Name	QUERYSMDRLMNE_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description**: minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL

Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Role-Limit-IO

Attribute	Description
Name	Smtbs-Role-Limit-IO
Datatype	
Description	

ROLEID2

Attribute	Description
Name	ROLEID2
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

Smtbs-Role-Limit-Full

Attribute	Description

Name	Smtbs-Role-Limit-Full
Datatype	
Description	

ROLEID2

Attribute	Description
Name	ROLEID2
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	15

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

LIMIT_CCY

Attribute	Description
Name	LIMIT_CCY
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

INPUT_LIMIT

Attribute	Description
Name	INPUT_LIMIT
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0

AUTHORIZATION_LIMIT

Attribute	Description
Name	AUTHORIZATION_LIMIT
Datatype	Decimal
Description	

Restrictions	
	Restrictions / **Description** totalDigits / 22 minInclusive / 0

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	

Restrictions	Description
maxLength	105
minLength	1

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	150
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description

Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.21.QuerySMRole

2.21.1.SM-QuerySMRole-Req-IO-MSG.xsd

QUERYSMROLE_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

ROLEMASTER-IO

ROLEIDENTIFICATION

QUERYSMROLE_IOFS_REQ

Attribute	Description
Name	QUERYSMROLE_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

ROLEMASTER-IO

Attribute	Description
Name	ROLEMASTER-IO
Datatype	
Description	

ROLEIDENTIFICATION

Attribute	Description
Name	ROLEIDENTIFICATION
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

2.21.2.SM-QuerySMRole-Res-Full-MSG.xsd

QUERYSMROLE_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

ROLEMASTER-IO

ROLEIDENTIFICATION

ROLEMASTER-Full

ROLEIDENTIFICATION

MASTERROLEDESC

AUTHORISERROLE

BRANCH_RES

ACCCLASSALLOWED

CENTRALISATIONROLE

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

ROLEDETAIL

ROLEFUN

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

CONTROL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

CONTROL15

CONTROL16

ROLEDETAILB

ROLEFUN

CONT1

CONT2

CONT3

CONT4

CONT5

CONT6

CONTROL7

CONT8

CONT9

CONT10

CONT11

CONT12

CONT13

CONT14

CONT15

CONTROL16

ROLEDETAILC

ROLEFUN

CNTRL1

CNTRL2

CNTRL3

CNTRL4

CNTRL5

CNTRL6

CNTRL7

CNTRL8

CNTRL9

CNTRL10

CNTRL11

CNTRL12

CNTRL13

CNTRL14

CNTRL15

CNTRL16

ROLEDETAILD

ROLEFUN

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

CONTROL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

CNTRL15

CNTRL16

ROLEBRANCHES

BRANCH

BRNNAME

ROLEACCCLASS

ACCCLS

DESCRIPTION

MSGCRIGHTS

CNL

CHGNODE

REL

CHGMEDIA

BRNMOV

HLD

TSTINP

CHGADDR

REINS

CHGPRIOR

CNLAUTH

CHGNODEAUTH

RELAUTH

CHGMEDIAAUTH

BRNMOVAUTH

HLDAUTH

TSTINPAUTH

CHGADDRAUTH

REINSAUTH

CHGPRIORAUTH

GEN

TSTCHK

LNKCONT

CHGBRNIN

CHGMSG

CHGFORCRELFUND

SUPPRESS

DELMSG

PRNT

FTUPL

MOVQ

CHGADDRIN

CHGMSGAUTH

AUTHRGHTS

CHGFORCCOVMATCH

QUEUERIGHTS

QUEUE

RESTRICTIVEPASSWD

PWD

PWDID

ROLEBRANCHLIMITS

LMTCCY

BRHUSERLMT

Roledetaile

ROLEFUN

BRANCHCODE

EDITABLE

CNTRLSTR

Roledetailf

ROLEID

ROLEFUN

CNTRLSTR

CNTRL1

CNTRL10

CNTRL11

CNTRL12

CNTRL13

CNTRL14

CNTRL15

CNTRL16

CNTRL2

CNTRL3

CNTRL4

CNTRL5

CNTRL6

CNTRL7

CNTRL8

CNTRL9

ATHSTAT

BRNCHCODE

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYSMROLE_IOFS_RES

Attribute	Description
Name	QUERYSMROLE_IOFS_RES

Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

ROLEMASTER-IO

Attribute	Description
Name	ROLEMASTER-IO
Datatype	
Description	

ROLEIDENTIFICATION

Attribute	Description
Name	ROLEIDENTIFICATION
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

ROLEMASTER-Full

Attribute	Description
Name	ROLEMASTER-Full
Datatype	
Description	

ROLEIDENTIFICATION

Attribute	Description

Name	ROLEIDENTIFICATION
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

MASTERROLEDESC

Attribute	**Description**
Name	MASTERROLEDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

AUTHORISERROLE

Attribute	**Description**
Name	AUTHORISERROLE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

BRANCH_RES

Attribute	**Description**
Name	BRANCH_RES
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

ACCCLASSALLOWED

Attribute	**Description**
Name	ACCCLASSALLOWED
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

CENTRALISATIONROLE

Attribute	**Description**
Name	CENTRALISATIONROLE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

ROLEDETAIL

Attribute	**Description**
Name	ROLEDETAIL
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ROLEFUN

Attribute	**Description**
Name	ROLEFUN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 8

CONTROL1

Attribute	**Description**
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CONTROL2

Attribute	**Description**
Name	CONTROL2
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL3

Attribute	Description
Name	CONTROL3
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL4

Attribute	Description
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL5

Attribute	Description
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL6

Attribute	Description
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL8

Attribute	Description
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL9

Attribute	Description
Name	CONTROL9
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL10

Attribute	Description
Name	CONTROL10
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL11

Attribute	Description
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL12

Attribute	Description
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL13

Attribute	Description
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL14

Attribute	Description
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL15

Attribute	Description
Name	CONTROL15
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

ROLEDETAILB

Attribute	Description
Name	ROLEDETAILB
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	8

CONT1

Attribute	Description
Name	CONT1
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT2

Attribute	Description
Name	CONT2
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT3

Attribute	Description
Name	CONT3
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT4

Attribute	Description
Name	CONT4
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT5

Attribute	Description
Name	CONT5
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT6

Attribute	Description
Name	CONT6
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONT8

Attribute	Description
Name	CONT8
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONT9

Attribute	Description
Name	CONT9
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT10

Attribute	Description
Name	CONT10
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT11

Attribute	Description
Name	CONT11
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT12

Attribute	Description
Name	CONT12
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONT13

Attribute	Description
Name	CONT13
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONT14

Attribute	Description
Name	CONT14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONT15

Attribute	Description
Name	CONT15
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

ROLEDETAILC

Attribute	Description
Name	ROLEDETAILC
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	8

CNTRL1

Attribute	Description
Name	CNTRL1
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL2

Attribute	Description
Name	CNTRL2
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL3

Attribute	Description
Name	CNTRL3
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL4

Attribute	Description
Name	CNTRL4
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL5

Attribute	Description
Name	CNTRL5
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL6

Attribute	Description
Name	CNTRL6
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL7

Attribute	Description
Name	CNTRL7
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL8

Attribute	Description
Name	CNTRL8
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL9

Attribute	Description
Name	CNTRL9
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL10

Attribute	Description
Name	CNTRL10
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL11

Attribute	Description
Name	CNTRL11
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL12

Attribute	Description
Name	CNTRL12
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL13

Attribute	Description
Name	CNTRL13
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL14

Attribute	Description
Name	CNTRL14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL15

Attribute	Description
Name	CNTRL15
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL16

Attribute	Description
Name	CNTRL16
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

ROLEDETAILD

Attribute	Description
Name	ROLEDETAILD
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	8

CONTROL1

Attribute	Description
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL2

Attribute	Description
Name	CONTROL2
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL3

Attribute	Description
Name	CONTROL3
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL4

Attribute	Description
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL5

Attribute	Description
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL6

Attribute	Description
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL8

Attribute	Description
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL9

Attribute	Description
Name	CONTROL9
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL10

Attribute	Description
Name	CONTROL10
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL11

Attribute	Description
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL12

Attribute	Description
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CONTROL13

Attribute	Description
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CONTROL14

Attribute	Description
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL15

Attribute	Description
Name	CNTRL15
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL16

Attribute	Description
Name	CNTRL16
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

ROLEBRANCHES

Attribute	Description
Name	ROLEBRANCHES
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	105

ROLEACCCLASS

Attribute	Description
Name	ROLEACCCLASS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ACCCLS

Attribute	Description

Name	ACCCLS
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 6

DESCRIPTION

Attribute	**Description**
Name	DESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

MSGCRIGHTS

Attribute	**Description**
Name	MSGCRIGHTS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

CNL

Attribute	**Description**
Name	CNL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGNODE

Attribute	**Description**
Name	CHGNODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	Y,N

REL

Attribute	Description
Name	REL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGMEDIA

Attribute	Description
Name	CHGMEDIA
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

BRNMOV

Attribute	Description
Name	BRNMOV
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

HLD

Attribute	Description
Name	HLD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

TSTINP

Attribute	Description
Name	TSTINP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGADDR

Attribute	Description
Name	CHGADDR
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

REINS

Attribute	Description
Name	REINS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGPRIOR

Attribute	Description
Name	CHGPRIOR
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CNLAUTH

Attribute	Description
Name	CNLAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGNODEAUTH

Attribute	Description
Name	CHGNODEAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

RELAUTH

Attribute	Description
Name	RELAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGMEDIAAUTH

Attribute	Description
Name	CHGMEDIAAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

BRNMOVAUTH

Attribute	Description
Name	BRNMOVAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

HLDAUTH

Attribute	Description
Name	HLDAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

TSTINPAUTH

Attribute	Description
Name	TSTINPAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGADDRAUTH

Attribute	Description
Name	CHGADDRAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: enumeration / Y,N

REINSAUTH

Attribute	Description
Name	REINSAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGPRIORAUTH

Attribute	Description
Name	CHGPRIORAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TSTCHK

Attribute	Description
Name	TSTCHK
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	Y,N

LNKCONT

Attribute	Description
Name	LNKCONT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGBRNIN

Attribute	Description
Name	CHGBRNIN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGMSG

Attribute	Description
Name	CHGMSG
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGFORCRELFUND

Attribute	Description
Name	CHGFORCRELFUND
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: enumeration / Y,N

SUPPRESS

Attribute	Description
Name	SUPPRESS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

DELMSG

Attribute	Description
Name	DELMSG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

PRNT

Attribute	Description
Name	PRNT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

FTUPL

Attribute	Description
Name	FTUPL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	Y,N

MOVQ

Attribute	Description
Name	MOVQ
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGADDRIN

Attribute	Description
Name	CHGADDRIN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGMSGAUTH

Attribute	Description
Name	CHGMSGAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

AUTHRGHTS

Attribute	Description
Name	AUTHRGHTS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGFORCCOVMATCH

Attribute	Description
Name	CHGFORCCOVMATCH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

QUEUERIGHTS

Attribute	Description
Name	QUEUERIGHTS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

QUEUE

Attribute	Description
Name	QUEUE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	10

RESTRICTIVEPASSWD

Attribute	Description
Name	RESTRICTIVEPASSWD
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PWD

Attribute	Description
Name	PWD
Datatype	String

Description	
Restrictions	

Restrictions	Description
maxLength	12

PWDID

Attribute	Description
Name	PWDID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

ROLEBRANCHLIMITS

Attribute	Description
Name	ROLEBRANCHLIMITS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

LMTCCY

Attribute	Description
Name	LMTCCY
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

BRHUSERLMT

Attribute	Description
Name	BRHUSERLMT
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

Roledetaile

Attribute	Description
Name	Roledetaile
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

BRANCHCODE

Attribute	Description
Name	BRANCHCODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

EDITABLE

Attribute	Description
Name	EDITABLE
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CNTRLSTR

Attribute	Description
Name	CNTRLSTR
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>16</td></tr></table>

Roledetailf

Attribute	Description
Name	Roledetailf
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ROLEID

Attribute	Description
Name	ROLEID
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

ROLEFUN

Attribute	Description
Name	ROLEFUN
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

CNTRLSTR

Attribute	Description
Name	CNTRLSTR
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 16

CNTRL1

Attribute	**Description**
Name	CNTRL1
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL10

Attribute	**Description**
Name	CNTRL10
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL11

Attribute	**Description**
Name	CNTRL11
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 1

CNTRL12

Attribute	Description
Name	CNTRL12
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL13

Attribute	Description
Name	CNTRL13
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL14

Attribute	Description
Name	CNTRL14
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL15

Attribute	Description
Name	CNTRL15
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL16

Attribute	Description
Name	CNTRL16
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL2

Attribute	Description
Name	CNTRL2
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL3

Attribute	Description
Name	CNTRL3
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL4

Attribute	Description
Name	CNTRL4
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL5

Attribute	Description
Name	CNTRL5
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL6

Attribute	Description
Name	CNTRL6
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>1</td></tr></table>

CNTRL7

Attribute	Description
Name	CNTRL7
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL8

Attribute	Description
Name	CNTRL8
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

CNTRL9

Attribute	Description
Name	CNTRL9
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0
maxInclusive	1

ATHSTAT

Attribute	Description
Name	ATHSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

BRNCHCODE

Attribute	Description
Name	BRNCHCODE

Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.22.QueryUserMaint

2.22.1.SM-QueryUserMaint-Req-IO-MSG.xsd

QUERYUSERMAINT_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

USR-IO

USRID

DASHBOARD_REQD

ALERTS_ON_HOME

Grp-Restriction

QUERYUSERMAINT_IOFS_REQ

Attribute	Description
Name	QUERYUSERMAINT_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

USR-IO

Attribute	Description
Name	USR-IO
Datatype	
Description	

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

DASHBOARD_REQD

Attribute	Description
Name	DASHBOARD_REQD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

ALERTS_ON_HOME

Attribute	Description
Name	ALERTS_ON_HOME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

Grp-Restriction

Attribute	Description
Name	Grp-Restriction
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

2.22.2.SM-QueryUserMaint-Res-Full-MSG.xsd

QUERYUSERMAINT_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

USR-IO

USRID

DASHBOARD_REQD

ALERTS_ON_HOME

Grp-Restriction

USR-Full

STRTDATE

USRNAME

USRPWD

ENDDT

USRLANG

HOMEBRN

CUSTNO

LDAPUSR

TIMELEVEL

AUTOAUTH

USRSTAT

USRID

EXTUSRREF

USRCATEG

TILLALLOW

ACCCLSALLOW

GLALLOW

USRTXNLMT

LMTSCCY

MAXTXNAMT

MAXAUTHAMT

BRNSALLOW

PRDSALLOW

PRDSACCESALLOW

TAX_IDENTIFIER

AMOUNT_FORMAT

DATE_FORMAT

STAFFACCRESTR

DEPT_CODE

DEPT_DESC

USRML

ELCMUSER

GROUP_CODE

MULTIBRN_ACCESS

OTH_RM_CUST_ACC_ALLOW

SUPERVISOR_ID

SUPERVISOR_NAME

DASHBOARD_REQD

ALERTS_ON_HOME

REFERENCE_NO

NO_CUMULATIVE_LOGINS

NO_SUCCESSIVE_LOGINS

SCREENSAVERTIMEOUTINSECONDS

MFI_USER

F10_REQD

F11_REQD

F12_REQD

ACCESS_CONTROL

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

RESTR_PWD

- *PWD*

MSGSRIGHTS

- *GEN*
- *HLD*
- *CNL*
- *TSTINP*
- *CHGNODE*
- *CHGADDR*
- *REL*
- *REINS*
- *CHGMEDIA*
- *CHGPRIOR*
- *BRNMOV*
- *PRNT*
- *TSTCHK*
- *HLDAUTH*
- *CNLAUTH*
- *TSTINPAUTH*
- *CHGNODEAUTH*
- *CHGADDRAUTH*

RELAUTH

REINSAUTH

CHGMEDIAAUTH

BRNMOVAUTH

CHGPRIORAUTH

FTUPL

LNKCONT

MOVQ

CHGBRNIN

CHGADDRIN

AUTHRGHTS

CHGMSG

CHGMSGAUTH

CHGFORCCOVMATCH

CHANGE_FORCE_RELEASE_FUND

SUPPRESS

DELMSG

QUEUERIGHTS

QUEUE

USERTILLS

TILLID

TILLBRNCD

USERACCCLASS

ACCCLS

USERGLREST

NODEGL

USERGLEXCEPT

EXCEPLEAFGL

USERLIMITSROLE

LMTBRN

LMTSROLE

QLMTCCY

- *QINPLMT*
- *QAUTHLMT*

USERBRANCHES

- *BRNSBRN*
- *BRNNAME*

USERPRODUCTS

- *PRDPRDCD*
- *PRDDESC*

USERACCESSPRODUCTS

- *PRDACCESSPRDCD*
- *PRDDESC*

USERFUNCDISALLOW

- *FUNCDISALLOWFUNCID*

USERROLE

- *ROLEBRNCD*
- *USRROLEID*
- *MASTERROLEDESC*

USERSFUNCTIONS

- *USERFUNCBRNCD*
- *USERFUNCFUNCID*
- *CONTROL1*
- *CONTROL2*
- *CONTROL3*
- *CONTROL4*
- *CONTROL5*
- *CONTROL6*
- *CONTROL7*
- *CONTROL8*
- *CONTROL9*
- *USERFUNCSCTRL10*
- *CONTROL11*
- *CONTROL12*

CONTROL13

CONTROL14

CONTROL15

CONTROL16

Grp-Restriction

GROUP_CODE

GROUP_DESC

Centralisation

USRROLEID

ROLDESC

Dshmst

USRID

USRNAME

Dshdet

FUNCTIONID

DESCRIPTION

SEQUENCE_NO

DBWHERECLAUSE

SHOW_IN_DASHBOARD

Where-Master

COLUMN_NAME

WHERE_CL

CONDITION

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYUSERMAINT_IOFS_RES

Attribute	Description
Name	QUERYUSERMAINT_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

USR-IO

Attribute	Description
Name	USR-IO
Datatype	
Description	

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

DASHBOARD_REQD

Attribute	Description
Name	DASHBOARD_REQD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

ALERTS_ON_HOME

Attribute	Description
Name	ALERTS_ON_HOME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

Grp-Restriction

Attribute	Description
Name	Grp-Restriction
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

USR-Full

Attribute	Description
Name	USR-Full
Datatype	
Description	

STRTDATE

Attribute	Description
Name	STRTDATE
Datatype	String
Description	

USRNAME

Attribute	Description
Name	USRNAME

Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

USRPWD

Attribute	Description
Name	USRPWD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>32</td></tr></table>

ENDDT

Attribute	Description
Name	ENDDT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

USRLANG

Attribute	Description
Name	USRLANG
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

HOMEBRN

Attribute	Description
Name	HOMEBRN
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

LDAPUSR

Attribute	Description
Name	LDAPUSR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>500</td></tr></table>

TIMELEVEL

Attribute	Description
Name	TIMELEVEL
Datatype	Decimal
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>9</td></tr></table>

AUTOAUTH

Attribute	Description
Name	AUTOAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

USRSTAT

Attribute	Description
Name	USRSTAT
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,H,D,L

USRID

Attribute	**Description**
Name	USRID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12

EXTUSRREF

Attribute	**Description**
Name	EXTUSRREF
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

USRCATEG

Attribute	**Description**
Name	USRCATEG
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,B

TILLALLOW

Attribute	**Description**
Name	TILLALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	A,D

ACCCLSALLOW

Attribute	Description
Name	ACCCLSALLOW
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	A,D

GLALLOW

Attribute	Description
Name	GLALLOW
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	A,D

USRTXNLMT

Attribute	Description
Name	USRTXNLMT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	U,R,N

LMTSCCY

Attribute	Description
Name	LMTSCCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: maxLength / 3

MAXTXNAMT

Attribute	Description
Name	MAXTXNAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

MAXAUTHAMT

Attribute	Description
Name	MAXAUTHAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

BRNSALLOW

Attribute	Description
Name	BRNSALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

PRDSALLOW

Attribute	Description
Name	PRDSALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	A,D

PRDSACCESALLOW

Attribute	Description
Name	PRDSACCESALLOW
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	A,D

TAX_IDENTIFIER

Attribute	Description
Name	TAX_IDENTIFIER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	11

AMOUNT_FORMAT

Attribute	Description
Name	AMOUNT_FORMAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	.,,,.,,

DATE_FORMAT

Attribute	Description
Name	DATE_FORMAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	M/d/yyyy

STAFFACCRESTR

Attribute	Description
Name	STAFFACCRESTR
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

DEPT_CODE

Attribute	Description
Name	DEPT_CODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

DEPT_DESC

Attribute	Description
Name	DEPT_DESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	50

USRML

Attribute	Description
Name	USRML
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: maxLength / 50

ELCMUSER

Attribute	Description
Name	ELCMUSER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

GROUP_CODE

Attribute	Description
Name	GROUP_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

MULTIBRN_ACCESS

Attribute	Description
Name	MULTIBRN_ACCESS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

OTH_RM_CUST_ACC_ALLOW

Attribute	Description
Name	OTH_RM_CUST_ACC_ALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	Y,N

SUPERVISOR_ID

Attribute	Description
Name	SUPERVISOR_ID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	80

SUPERVISOR_NAME

Attribute	Description
Name	SUPERVISOR_NAME
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

DASHBOARD_REQD

Attribute	Description
Name	DASHBOARD_REQD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

ALERTS_ON_HOME

Attribute	Description
Name	ALERTS_ON_HOME
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: enumeration / Y,N

REFERENCE_NO

Attribute	**Description**
Name	REFERENCE_NO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

NO_CUMULATIVE_LOGINS

Attribute	**Description**
Name	NO_CUMULATIVE_LOGINS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

NO_SUCCESSIVE_LOGINS

Attribute	**Description**
Name	NO_SUCCESSIVE_LOGINS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

SCREENSAVERTIMEOUTINSECONDS

Attribute	**Description**
Name	SCREENSAVERTIMEOUTINSECONDS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: totalDigits / 22

MFI_USER

Attribute	Description
Name	MFI_USER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

F10_REQD

Attribute	Description
Name	F10_REQD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

F11_REQD

Attribute	Description
Name	F11_REQD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

F12_REQD

Attribute	Description
Name	F12_REQD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	Y,N

ACCESS_CONTROL

Attribute	Description
Name	ACCESS_CONTROL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	U,G,B

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	4

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

RESTR_PWD

Attribute	Description
Name	RESTR_PWD
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PWD

Attribute	Description
Name	PWD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12

MSGSRIGHTS

Attribute	Description
Name	MSGSRIGHTS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

HLD

Attribute	Description
Name	HLD
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CNL

Attribute	Description
Name	CNL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

TSTINP

Attribute	Description
Name	TSTINP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGNODE

Attribute	Description
Name	CHGNODE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

CHGADDR

Attribute	Description
Name	CHGADDR
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

REL

Attribute	**Description**
Name	REL
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

REINS

Attribute	**Description**
Name	REINS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGMEDIA

Attribute	**Description**
Name	CHGMEDIA
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGPRIOR

Attribute	**Description**
Name	CHGPRIOR
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / Y,N

BRNMOV

Attribute	**Description**
Name	BRNMOV
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

PRNT

Attribute	**Description**
Name	PRNT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TSTCHK

Attribute	**Description**
Name	TSTCHK
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

HLDAUTH

Attribute	**Description**
Name	HLDAUTH
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

CNLAUTH

Attribute	**Description**
Name	CNLAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TSTINPAUTH

Attribute	**Description**
Name	TSTINPAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGNODEAUTH

Attribute	**Description**
Name	CHGNODEAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGADDRAUTH

Attribute	**Description**
Name	CHGADDRAUTH
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

RELAUTH

Attribute	**Description**
Name	RELAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

REINSAUTH

Attribute	**Description**
Name	REINSAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGMEDIAAUTH

Attribute	**Description**
Name	CHGMEDIAAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

BRNMOVAUTH

Attribute	**Description**
Name	BRNMOVAUTH
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

CHGPRIORAUTH

Attribute	**Description**
Name	CHGPRIORAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

FTUPL

Attribute	**Description**
Name	FTUPL
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

LNKCONT

Attribute	**Description**
Name	LNKCONT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

MOVQ

Attribute	**Description**
Name	MOVQ
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGBRNIN

Attribute	**Description**
Name	CHGBRNIN
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGADDRIN

Attribute	**Description**
Name	CHGADDRIN
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

AUTHRGHTS

Attribute	**Description**
Name	AUTHRGHTS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGMSG

Attribute	**Description**
Name	CHGMSG
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGMSGAUTH

Attribute	**Description**
Name	CHGMSGAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGFORCCOVMATCH

Attribute	**Description**
Name	CHGFORCCOVMATCH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHANGE_FORCE_RELEASE_FUND

Attribute	**Description**
Name	CHANGE_FORCE_RELEASE_FUND
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

SUPPRESS

Attribute	**Description**
Name	SUPPRESS
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

DELMSG

Attribute	**Description**
Name	DELMSG
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

QUEUERIGHTS

Attribute	**Description**
Name	QUEUERIGHTS
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

QUEUE

Attribute	**Description**
Name	QUEUE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 10

USERTILLS

Attribute	**Description**
Name	USERTILLS
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

TILLID

Attribute	Description
Name	TILLID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TILLBRNCD

Attribute	Description
Name	TILLBRNCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

USERACCCLASS

Attribute	Description
Name	USERACCCLASS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

USERGLREST

Attribute	Description
Name	USERGLREST
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NODEGL

Attribute	Description
Name	NODEGL
Datatype	String

Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

USERGLEXCEPT

Attribute	Description
Name	USERGLEXCEPT
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

EXCEPLEAFGL

Attribute	Description
Name	EXCEPLEAFGL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

USERLIMITSROLE

Attribute	Description
Name	USERLIMITSROLE
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

LMTBRN

Attribute	Description
Name	LMTBRN
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

LMTSROLE

Attribute	Description
Name	LMTSROLE

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

QLMTCCY

Attribute	**Description**
Name	QLMTCCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

QINPLMT

Attribute	**Description**
Name	QINPLMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

QAUTHLMT

Attribute	**Description**
Name	QAUTHLMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

USERBRANCHES

Attribute	**Description**
Name	USERBRANCHES

Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRNSBRN

Attribute	Description
Name	BRNSBRN
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

USERPRODUCTS

Attribute	Description
Name	USERPRODUCTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PRDPRDCD

Attribute	Description
Name	PRDPRDCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

PRDDESC

Attribute	Description

Name	PRDDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

USERACCESSPRODUCTS

Attribute	**Description**
Name	USERACCESSPRODUCTS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

PRDACCESSPRDCD

Attribute	**Description**
Name	PRDACCESSPRDCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

PRDDESC

Attribute	**Description**
Name	PRDDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

USERFUNCDISALLOW

Attribute	**Description**
Name	USERFUNCDISALLOW
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FUNCDISALLOWFUNCID

Attribute	Description
Name	FUNCDISALLOWFUNCID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 8

USERROLE

Attribute	Description
Name	USERROLE
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ROLEBRNCD

Attribute	Description
Name	ROLEBRNCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

USRROLEID

Attribute	Description
Name	USRROLEID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

MASTERROLEDESC

Attribute	Description
Name	MASTERROLEDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 45

USERSFUNCTIONS

Attribute	Description
Name	USERSFUNCTIONS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

USERFUNCBRNCD

Attribute	Description
Name	USERFUNCBRNCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

USERFUNCFUNCID

Attribute	Description
Name	USERFUNCFUNCID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

CONTROL1

Attribute	Description
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL2

Attribute	Description
Name	CONTROL2
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	
	Restrictions / **Description** totalDigits / 22

CONTROL3

Attribute	Description
Name	CONTROL3
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL4

Attribute	Description
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL5

Attribute	Description
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL6

Attribute	Description
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL8

Attribute	Description
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL9

Attribute	Description
Name	CONTROL9
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

USERFUNCSCTRL10

Attribute	Description
Name	USERFUNCSCTRL10
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL11

Attribute	Description
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL12

Attribute	Description
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL13

Attribute	Description
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL14

Attribute	Description
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL15

Attribute	Description
Name	CONTROL15
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

Grp-Restriction

Attribute	Description
Name	Grp-Restriction
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

GROUP_CODE

Attribute	Description
Name	GROUP_CODE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	40

GROUP_DESC

Attribute	Description

Name	GROUP_DESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

Centralisation

Attribute	**Description**
Name	Centralisation
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

USRROLEID

Attribute	**Description**
Name	USRROLEID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

ROLDESC

Attribute	**Description**
Name	ROLDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

Dshmst

Attribute	**Description**
Name	Dshmst
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

USRNAME

Attribute	Description
Name	USRNAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

Dshdet

Attribute	Description
Name	Dshdet
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

DESCRIPTION

Attribute	Description

Name	DESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

SEQUENCE_NO

Attribute	**Description**
Name	SEQUENCE_NO
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description**: totalDigits / 22

DBWHERECLAUSE

Attribute	**Description**
Name	DBWHERECLAUSE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4000

SHOW_IN_DASHBOARD

Attribute	**Description**
Name	SHOW_IN_DASHBOARD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

Where-Master

Attribute	**Description**
Name	Where-Master
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

COLUMN_NAME

Attribute	Description
Name	COLUMN_NAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

WHERE_CL

Attribute	Description
Name	WHERE_CL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>500</td></tr></table>

CONDITION

Attribute	Description
Name	CONDITION
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM

Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150 minLength / 0

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attribute	**Attribute** / **Description** maxOccurs / unbounded

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.23.ReopenSMDBANKP

2.23.1.SM-ReopenSMDBANKP-Req-Full-MSG.xsd

REOPENSMDBANKP_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Parameters-Full

HEAD_OFFICE

SITE_CODE

ACTIVATION_KEY

INVALID_LOGINS_CUM

INVALID_LOGINS_SUC

PWD_PREVENT_REUSE

PWD_CHANGE_AFTER

MAXIMUM

MINIMUM

PWD_EXPIRY_MSG_DAYS

ARCHIVAL_PERIOD

CONCHAR_PWD_NUM

FREQ_PWD_CHG

MIN_PWD_NUMERIC_LENGTH

LEGAL_NOTICE

DORMANCY_DAYS

DISPLAY_LEGAL_NOTICE

MIN_SPECIALCHAR_LENGTH

MIN_LOWERCASE_CHAR

MIN_UPPERCASE_CHAR

SCREENSAVERREQUIRED

SCREENSAVERTIMEOUTINSECONDS

SCREENSAVERMODIFIABLEBYUSER

PASSWORDEXTERNAL

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Smtbs-Branch-Restr

RESTR_TYPE

DESCRIPTION

Smtbs-Restrictive-Passwd

PASSWORD

UDFDETAILS

FLDNAM

FLDVAL

REOPENSMDBANKP_FSFS_REQ

Attribute	Description
Name	REOPENSMDBANKP_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Parameters-Full

Attribute	Description
Name	Smtbs-Parameters-Full
Datatype	
Description	

HEAD_OFFICE

Attribute	Description
Name	HEAD_OFFICE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

SITE_CODE

Attribute	Description
Name	SITE_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

ACTIVATION_KEY

Attribute	Description
Name	ACTIVATION_KEY
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 24

INVALID_LOGINS_CUM

Attribute	**Description**
Name	INVALID_LOGINS_CUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 6; maxInclusive / 99

INVALID_LOGINS_SUC

Attribute	**Description**
Name	INVALID_LOGINS_SUC
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 1; minInclusive / 3; maxInclusive / 5

PWD_PREVENT_REUSE

Attribute	**Description**
Name	PWD_PREVENT_REUSE
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

PWD_CHANGE_AFTER

Attribute	Description
Name	PWD_CHANGE_AFTER
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>3</td></tr><tr><td>minInclusive</td><td>15</td></tr><tr><td>maxInclusive</td><td>180</td></tr></table>

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>12</td></tr><tr><td>maxInclusive</td><td>30</td></tr></table>

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>2</td></tr><tr><td>minInclusive</td><td>6</td></tr><tr><td>maxInclusive</td><td>11</td></tr></table>

PWD_EXPIRY_MSG_DAYS

Attribute	Description
Name	PWD_EXPIRY_MSG_DAYS
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1
maxInclusive	5

ARCHIVAL_PERIOD

Attribute	Description
Name	ARCHIVAL_PERIOD
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	3

CONCHAR_PWD_NUM

Attribute	Description
Name	CONCHAR_PWD_NUM
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2

FREQ_PWD_CHG

Attribute	Description
Name	FREQ_PWD_CHG
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	0

MIN_PWD_NUMERIC_LENGTH

Attribute	Description
Name	MIN_PWD_NUMERIC_LENGTH
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: totalDigits / 2; minInclusive / 1

LEGAL_NOTICE

Attribute	**Description**
Name	LEGAL_NOTICE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

DORMANCY_DAYS

Attribute	**Description**
Name	DORMANCY_DAYS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

DISPLAY_LEGAL_NOTICE

Attribute	**Description**
Name	DISPLAY_LEGAL_NOTICE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

MIN_SPECIALCHAR_LENGTH

Attribute	**Description**
Name	MIN_SPECIALCHAR_LENGTH

Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

MIN_LOWERCASE_CHAR

Attribute	**Description**
Name	MIN_LOWERCASE_CHAR
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

MIN_UPPERCASE_CHAR

Attribute	**Description**
Name	MIN_UPPERCASE_CHAR
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

SCREENSAVERREQUIRED

Attribute	**Description**
Name	SCREENSAVERREQUIRED
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

SCREENSAVERTIMEOUTINSECONDS

Attribute	Description
Name	SCREENSAVERTIMEOUTINSECONDS
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

SCREENSAVERMODIFIABLEBYUSER

Attribute	Description
Name	SCREENSAVERMODIFIABLEBYUSER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

PASSWORDEXTERNAL

Attribute	Description
Name	PASSWORDEXTERNAL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Smtbs-Branch-Restr

Attribute	Description
Name	Smtbs-Branch-Restr
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

RESTR_TYPE

Attribute	Description
Name	RESTR_TYPE
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

Smtbs-Restrictive-Passwd

Attribute	Description
Name	Smtbs-Restrictive-Passwd
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description

Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150; minLength / 0

2.23.2.SM-ReopenSMDBANKP-Req-IO-MSG.xsd

REOPENSMDBANKP_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Parameters-IO

SITE_CODE

MAKER

MAKERSTAMP

MODNO

REOPENSMDBANKP_IOPK_REQ

Attribute	Description
Name	REOPENSMDBANKP_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Parameters-IO

Attribute	Description
Name	Smtbs-Parameters-IO
Datatype	
Description	

SITE_CODE

Attribute	Description
Name	SITE_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

2.23.3.SM-ReopenSMDBANKP-Res-Full-MSG.xsd

REOPENSMDBANKP_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Parameters-Full

HEAD_OFFICE

SITE_CODE

ACTIVATION_KEY

INVALID_LOGINS_CUM

INVALID_LOGINS_SUC

PWD_PREVENT_REUSE

PWD_CHANGE_AFTER

MAXIMUM

MINIMUM

PWD_EXPIRY_MSG_DAYS

ARCHIVAL_PERIOD

CONCHAR_PWD_NUM

FREQ_PWD_CHG

MIN_PWD_NUMERIC_LENGTH

LEGAL_NOTICE

DORMANCY_DAYS

DISPLAY_LEGAL_NOTICE

MIN_SPECIALCHAR_LENGTH

MIN_LOWERCASE_CHAR

MIN_UPPERCASE_CHAR

SCREENSAVERREQUIRED

SCREENSAVERTIMEOUTINSECONDS

SCREENSAVERMODIFIABLEBYUSER

PASSWORDEXTERNAL

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Smtbs-Branch-Restr

RESTR_TYPE

DESCRIPTION

Smtbs-Restrictive-Passwd

PASSWORD

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

REOPENSMDBANKP_FSFS_RES

Attribute	Description
Name	REOPENSMDBANKP_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description**: minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL

Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Parameters-Full

Attribute	Description
Name	Smtbs-Parameters-Full
Datatype	
Description	

HEAD_OFFICE

Attribute	Description
Name	HEAD_OFFICE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: maxLength / 3

SITE_CODE

Attribute	Description
Name	SITE_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

ACTIVATION_KEY

Attribute	Description
Name	ACTIVATION_KEY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 24

INVALID_LOGINS_CUM

Attribute	Description
Name	INVALID_LOGINS_CUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 6; maxInclusive / 99

INVALID_LOGINS_SUC

Attribute	Description
Name	INVALID_LOGINS_SUC
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	1
minInclusive	3
maxInclusive	5

PWD_PREVENT_REUSE

Attribute	Description
Name	PWD_PREVENT_REUSE
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1

PWD_CHANGE_AFTER

Attribute	Description
Name	PWD_CHANGE_AFTER
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	3
minInclusive	15
maxInclusive	180

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	12
maxInclusive	30

MINIMUM

Attribute	Description

Name	MINIMUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 6; maxInclusive / 11

PWD_EXPIRY_MSG_DAYS

Attribute	**Description**
Name	PWD_EXPIRY_MSG_DAYS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1; maxInclusive / 5

ARCHIVAL_PERIOD

Attribute	**Description**
Name	ARCHIVAL_PERIOD
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 3

CONCHAR_PWD_NUM

Attribute	**Description**
Name	CONCHAR_PWD_NUM
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2

FREQ_PWD_CHG

Attribute	Description
Name	FREQ_PWD_CHG
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 0

MIN_PWD_NUMERIC_LENGTH

Attribute	Description
Name	MIN_PWD_NUMERIC_LENGTH
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

LEGAL_NOTICE

Attribute	Description
Name	LEGAL_NOTICE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

DORMANCY_DAYS

Attribute	Description
Name	DORMANCY_DAYS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1

DISPLAY_LEGAL_NOTICE

Attribute	Description
Name	DISPLAY_LEGAL_NOTICE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

MIN_SPECIALCHAR_LENGTH

Attribute	Description
Name	MIN_SPECIALCHAR_LENGTH
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1

MIN_LOWERCASE_CHAR

Attribute	Description
Name	MIN_LOWERCASE_CHAR
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	2
minInclusive	1

MIN_UPPERCASE_CHAR

Attribute	Description
Name	MIN_UPPERCASE_CHAR
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 2; minInclusive / 1

SCREENSAVERREQUIRED

Attribute	**Description**
Name	SCREENSAVERREQUIRED
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

SCREENSAVERTIMEOUTINSECONDS

Attribute	**Description**
Name	SCREENSAVERTIMEOUTINSECONDS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

SCREENSAVERMODIFIABLEBYUSER

Attribute	**Description**
Name	SCREENSAVERMODIFIABLEBYUSER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

PASSWORDEXTERNAL

Attribute	**Description**
Name	PASSWORDEXTERNAL
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

Smtbs-Branch-Restr

Attribute	Description
Name	Smtbs-Branch-Restr
Datatype	

Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

RESTR_TYPE

Attribute	Description
Name	RESTR_TYPE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	255

Smtbs-Restrictive-Passwd

Attribute	Description
Name	Smtbs-Restrictive-Passwd
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.23.4.SM-ReopenSMDBANKP-Res-PK-MSG.xsd

REOPENSMDBANKP_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Parameters-PK

SITE_CODE

Smtbs-Parameters-IO

SITE_CODE

MAKER

MAKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

REOPENSMDBANKP_IOPK_RES

Attribute	Description
Name	REOPENSMDBANKP_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Parameters-PK

Attribute	Description
Name	Smtbs-Parameters-PK
Datatype	
Description	

SITE_CODE

Attribute	Description
Name	SITE_CODE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

Smtbs-Parameters-IO

Attribute	Description
Name	Smtbs-Parameters-IO
Datatype	
Description	

SITE_CODE

Attribute	Description
Name	SITE_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
totalDigits	4

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	

Attribute	

Attribute	Description
maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.24.ReopenSMDRLMNE

2.24.1.SM-ReopenSMDRLMNE-Req-Full-MSG.xsd

REOPENSMDRLMNE_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Role-Limit-Full

ROLEID2

DESCRIPTION

LIMIT_CCY

INPUT_LIMIT

AUTHORIZATION_LIMIT

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

REOPENSMDRLMNE_FSFS_REQ

Attribute	Description
Name	REOPENSMDRLMNE_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	
	Restrictions / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Role-Limit-Full

Attribute	Description
Name	Smtbs-Role-Limit-Full
Datatype	
Description	

ROLEID2

Attribute	Description
Name	ROLEID2
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

LIMIT_CCY

Attribute	Description
Name	LIMIT_CCY
Datatype	String
Description	

Restrictions	

Restrictions	Description
maxLength	3

INPUT_LIMIT

Attribute	Description
Name	INPUT_LIMIT
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0

AUTHORIZATION_LIMIT

Attribute	Description
Name	AUTHORIZATION_LIMIT
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.24.2.SM-ReopenSMDRLMNE-Req-IO-MSG.xsd

REOPENSMDRLMNE_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Role-Limit-IO

ROLEID2

MAKER

MAKERSTAMP

MODNO

REOPENSMDRLMNE_IOPK_REQ

Attribute	Description
Name	REOPENSMDRLMNE_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Role-Limit-IO

Attribute	Description
Name	Smtbs-Role-Limit-IO
Datatype	
Description	

ROLEID2

Attribute	Description
Name	ROLEID2
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

2.24.3.SM-ReopenSMDRLMNE-Res-Full-MSG.xsd

REOPENSMDRLMNE_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Role-Limit-Full

ROLEID2

DESCRIPTION

LIMIT_CCY

INPUT_LIMIT

AUTHORIZATION_LIMIT

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

REOPENSMDRLMNE_FSFS_RES

Attribute	Description
Name	REOPENSMDRLMNE_FSFS_RES

Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Role-Limit-Full

Attribute	Description
Name	Smtbs-Role-Limit-Full
Datatype	
Description	

ROLEID2

Attribute	Description
Name	ROLEID2
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	105

LIMIT_CCY

Attribute	Description
Name	LIMIT_CCY
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

INPUT_LIMIT

Attribute	Description
Name	INPUT_LIMIT
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0

AUTHORIZATION_LIMIT

Attribute	Description
Name	AUTHORIZATION_LIMIT
Datatype	Decimal
Description	
Restrictions	

Restrictions	Description
totalDigits	22
minInclusive	0

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>4</td></tr></table>

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>1</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
maxLength	150
minLength	0

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	

Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.24.4.SM-ReopenSMDRLMNE-Res-PK-MSG.xsd

REOPENSMDRLMNE_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Smtbs-Role-Limit-PK

ROLEID2

Smtbs-Role-Limit-IO

ROLEID2

MAKER

MAKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

REOPENSMDRLMNE_IOPK_RES

Attribute	Description
Name	REOPENSMDRLMNE_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	

Restrictions	Description
enumeration	FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
pattern	[a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	

Restrictions	Description
maxLength	12
pattern	[A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	

Restrictions	Description
length	3
pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	8
pattern	[A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Smtbs-Role-Limit-PK

Attribute	Description
Name	Smtbs-Role-Limit-PK
Datatype	
Description	

ROLEID2

Attribute	Description
Name	ROLEID2
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

Smtbs-Role-Limit-IO

Attribute	Description
Name	Smtbs-Role-Limit-IO
Datatype	
Description	

ROLEID2

Attribute	Description
Name	ROLEID2
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

MAKER

Attribute	Description

Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.25.ReopenUserMaint

2.25.1.SM-ReopenUserMaint-Req-Full-MSG.xsd

REOPENUSERMAINT_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

USR-Full

STRTDATE

USRNAME

USRPWD

ENDDT

USRLANG

HOMEBRN

CUSTNO

LDAPUSR

TIMELEVEL

AUTOAUTH

USRSTAT

USRID

EXTUSRREF

USRCATEG

TILLALLOW

ACCCLSALLOW

GLALLOW

USRTXNLMT

LMTSCCY

MAXTXNAMT

MAXAUTHAMT

BRNSALLOW

PRDSALLOW

PRDSACCESALLOW

TAX_IDENTIFIER

AMOUNT_FORMAT

DATE_FORMAT

STAFFACCRESTR

DEPT_CODE

DEPT_DESC

USRML

ELCMUSER

GROUP_CODE

MULTIBRN_ACCESS

OTH_RM_CUST_ACC_ALLOW

SUPERVISOR_ID

SUPERVISOR_NAME

DASHBOARD_REQD

ALERTS_ON_HOME

REFERENCE_NO

NO_CUMULATIVE_LOGINS

NO_SUCCESSIVE_LOGINS

SCREENSAVERTIMEOUTINSECONDS

MFI_USER

F10_REQD

F11_REQD

F12_REQD

ACCESS_CONTROL

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

RESTR_PWD

- *PWD*

MSGSRIGHTS

- *GEN*
- *HLD*
- *CNL*
- *TSTINP*
- *CHGNODE*
- *CHGADDR*
- *REL*
- *REINS*
- *CHGMEDIA*
- *CHGPRIOR*
- *BRNMOV*
- *PRNT*
- *TSTCHK*
- *HLDAUTH*

CNLAUTH

TSTINPAUTH

CHGNODEAUTH

CHGADDRAUTH

RELAUTH

REINSAUTH

CHGMEDIAAUTH

BRNMOVAUTH

CHGPRIORAUTH

FTUPL

LNKCONT

MOVQ

CHGBRNIN

CHGADDRIN

AUTHRGHTS

CHGMSG

CHGMSGAUTH

CHGFORCCOVMATCH

CHANGE_FORCE_RELEASE_FUND

SUPPRESS

DELMSG

QUEUERIGHTS

QUEUE

USERTILLS

TILLID

TILLBRNCD

USERACCCLASS

ACCCLS

USERGLREST

NODEGL

USERGLEXCEPT

EXCEPLEAFGL

USERLIMITSROLE

LMTBRN

LMTSROLE

QLMTCCY

QINPLMT

QAUTHLMT

USERBRANCHES

BRNSBRN

BRNNAME

USERPRODUCTS

PRDPRDCD

PRDDESC

USERACCESSPRODUCTS

PRDACCESSPRDCD

PRDDESC

USERFUNCDISALLOW

FUNCDISALLOWFUNCID

USERROLE

ROLEBRNCD

USRROLEID

MASTERROLEDESC

USERSFUNCTIONS

USERFUNCBRNCD

USERFUNCFUNCID

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

USERFUNCSCTRL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

CONTROL15

CONTROL16

Grp-Restriction

GROUP_CODE

GROUP_DESC

Centralisation

USRROLEID

ROLDESC

Dshmst

USRID

USRNAME

Dshdet

FUNCTIONID

DESCRIPTION

SEQUENCE_NO

DBWHERECLAUSE

SHOW_IN_DASHBOARD

Where-Master

COLUMN_NAME

WHERE_CL

CONDITION

UDFDETAILS

FLDNAM

FLDVAL

REOPENUSERMAINT_FSFS_REQ

Attribute	Description

Name	REOPENUSERMAINT_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute	

Attribute	Description
minOccurs	0

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	

Attribute	Description
nillable	true

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	This is the user id in the Source system who is performing the action.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

USR-Full

Attribute	Description
Name	USR-Full
Datatype	
Description	

STRTDATE

Attribute	Description
Name	STRTDATE
Datatype	String
Description	

USRNAME

Attribute	Description
Name	USRNAME
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>35</td></tr></table>

USRPWD

Attribute	Description

Name	USRPWD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

ENDDT

Attribute	**Description**
Name	ENDDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

USRLANG

Attribute	**Description**
Name	USRLANG
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

HOMEBRN

Attribute	**Description**
Name	HOMEBRN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

LDAPUSR

Attribute	Description
Name	LDAPUSR
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>500</td></tr></table>

TIMELEVEL

Attribute	Description
Name	TIMELEVEL
Datatype	Decimal
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr><tr><td>minInclusive</td><td>0</td></tr><tr><td>maxInclusive</td><td>9</td></tr></table>

AUTOAUTH

Attribute	Description
Name	AUTOAUTH
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

USRSTAT

Attribute	Description
Name	USRSTAT
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>E,H,D,L</td></tr></table>

USRID

Attribute	Description

Name	USRID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12

EXTUSRREF

Attribute	**Description**
Name	EXTUSRREF
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

USRCATEG

Attribute	**Description**
Name	USRCATEG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,B

TILLALLOW

Attribute	**Description**
Name	TILLALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

ACCCLSALLOW

Attribute	**Description**
Name	ACCCLSALLOW
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / A,D

GLALLOW

Attribute	**Description**
Name	GLALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

USRTXNLMT

Attribute	**Description**
Name	USRTXNLMT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,R,N

LMTSCCY

Attribute	**Description**
Name	LMTSCCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

MAXTXNAMT

Attribute	**Description**
Name	MAXTXNAMT
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

MAXAUTHAMT

Attribute	**Description**
Name	MAXAUTHAMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

BRNSALLOW

Attribute	**Description**
Name	BRNSALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

PRDSALLOW

Attribute	**Description**
Name	PRDSALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

PRDSACCESALLOW

Attribute	**Description**
Name	PRDSACCESALLOW
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TAX_IDENTIFIER

Attribute	**Description**
Name	TAX_IDENTIFIER
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

AMOUNT_FORMAT

Attribute	**Description**
Name	AMOUNT_FORMAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / .,,,.,,

DATE_FORMAT

Attribute	**Description**
Name	DATE_FORMAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M/d/yyyy

STAFFACCRESTR

Attribute	**Description**
Name	STAFFACCRESTR
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

DEPT_CODE

Attribute	**Description**
Name	DEPT_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

DEPT_DESC

Attribute	**Description**
Name	DEPT_DESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

USRML

Attribute	**Description**
Name	USRML
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

ELCMUSER

Attribute	**Description**
Name	ELCMUSER
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

GROUP_CODE

Attribute	**Description**
Name	GROUP_CODE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

MULTIBRN_ACCESS

Attribute	**Description**
Name	MULTIBRN_ACCESS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

OTH_RM_CUST_ACC_ALLOW

Attribute	**Description**
Name	OTH_RM_CUST_ACC_ALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

SUPERVISOR_ID

Attribute	**Description**
Name	SUPERVISOR_ID
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 80

SUPERVISOR_NAME

Attribute	**Description**
Name	SUPERVISOR_NAME
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

DASHBOARD_REQD

Attribute	**Description**
Name	DASHBOARD_REQD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

ALERTS_ON_HOME

Attribute	**Description**
Name	ALERTS_ON_HOME
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

REFERENCE_NO

Attribute	**Description**
Name	REFERENCE_NO
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

NO_CUMULATIVE_LOGINS

Attribute	**Description**
Name	NO_CUMULATIVE_LOGINS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

NO_SUCCESSIVE_LOGINS

Attribute	**Description**
Name	NO_SUCCESSIVE_LOGINS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

SCREENSAVERTIMEOUTINSECONDS

Attribute	**Description**
Name	SCREENSAVERTIMEOUTINSECONDS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

MFI_USER

Attribute	**Description**
Name	MFI_USER
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

F10_REQD

Attribute	**Description**
Name	F10_REQD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

F11_REQD

Attribute	**Description**
Name	F11_REQD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

F12_REQD

Attribute	**Description**
Name	F12_REQD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

ACCESS_CONTROL

Attribute	**Description**
Name	ACCESS_CONTROL
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / U,G,B

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 4

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

RESTR_PWD

Attribute	**Description**
Name	RESTR_PWD
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PWD

Attribute	Description
Name	PWD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12

MSGSRIGHTS

Attribute	Description
Name	MSGSRIGHTS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

HLD

Attribute	Description
Name	HLD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CNL

Attribute	Description

Name	CNL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TSTINP

Attribute	**Description**
Name	TSTINP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGNODE

Attribute	**Description**
Name	CHGNODE
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGADDR

Attribute	**Description**
Name	CHGADDR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

REL

Attribute	**Description**

Name	REL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

REINS

Attribute	**Description**
Name	REINS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMEDIA

Attribute	**Description**
Name	CHGMEDIA
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGPRIOR

Attribute	**Description**
Name	CHGPRIOR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

BRNMOV

Attribute	**Description**

Name	BRNMOV
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

PRNT

Attribute	**Description**
Name	PRNT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TSTCHK

Attribute	**Description**
Name	TSTCHK
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

HLDAUTH

Attribute	**Description**
Name	HLDAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CNLAUTH

Attribute	**Description**

Name	CNLAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TSTINPAUTH

Attribute	**Description**
Name	TSTINPAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGNODEAUTH

Attribute	**Description**
Name	CHGNODEAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGADDRAUTH

Attribute	**Description**
Name	CHGADDRAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

RELAUTH

Attribute	**Description**

Name	RELAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

REINSAUTH

Attribute	**Description**
Name	REINSAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMEDIAAUTH

Attribute	**Description**
Name	CHGMEDIAAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

BRNMOVAUTH

Attribute	**Description**
Name	BRNMOVAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGPRIORAUTH

Attribute	**Description**

Name	CHGPRIORAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

FTUPL

Attribute	**Description**
Name	FTUPL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

LNKCONT

Attribute	**Description**
Name	LNKCONT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

MOVQ

Attribute	**Description**
Name	MOVQ
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGBRNIN

Attribute	**Description**

Name	CHGBRNIN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGADDRIN

Attribute	**Description**
Name	CHGADDRIN
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

AUTHRGHTS

Attribute	**Description**
Name	AUTHRGHTS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMSG

Attribute	**Description**
Name	CHGMSG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGMSGAUTH

Attribute	**Description**

Name	CHGMSGAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHGFORCCOVMATCH

Attribute	**Description**
Name	CHGFORCCOVMATCH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

CHANGE_FORCE_RELEASE_FUND

Attribute	**Description**
Name	CHANGE_FORCE_RELEASE_FUND
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

SUPPRESS

Attribute	**Description**
Name	SUPPRESS
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

DELMSG

Attribute	**Description**

Name	DELMSG
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

QUEUERIGHTS

Attribute	**Description**
Name	QUEUERIGHTS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

QUEUE

Attribute	**Description**
Name	QUEUE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 10

USERTILLS

Attribute	**Description**
Name	USERTILLS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

TILLID

Attribute	**Description**
Name	TILLID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12

TILLBRNCD

Attribute	**Description**

Name	TILLBRNCD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

USERACCCLASS

Attribute	Description
Name	USERACCCLASS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	6

USERGLREST

Attribute	Description
Name	USERGLREST
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NODEGL

Attribute	Description
Name	NODEGL
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	9

USERGLEXCEPT

Attribute	Description
Name	USERGLEXCEPT
Datatype	
Description	

Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

EXCEPLEAFGL

Attribute	Description
Name	EXCEPLEAFGL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	9

USERLIMITSROLE

Attribute	Description
Name	USERLIMITSROLE
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

LMTBRN

Attribute	Description
Name	LMTBRN
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	3

LMTSROLE

Attribute	Description
Name	LMTSROLE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	15

QLMTCCY

Attribute	Description
Name	QLMTCCY
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

QINPLMT

Attribute	Description
Name	QINPLMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

QAUTHLMT

Attribute	Description
Name	QAUTHLMT
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

USERBRANCHES

Attribute	Description
Name	USERBRANCHES
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRNSBRN

Attribute	Description
Name	BRNSBRN
Datatype	String

Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

USERPRODUCTS

Attribute	Description
Name	USERPRODUCTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PRDPRDCD

Attribute	Description
Name	PRDPRDCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

USERACCESSPRODUCTS

Attribute	Description
Name	USERACCESSPRODUCTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PRDACCESSPRDCD

Attribute	Description
Name	PRDACCESSPRDCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

USERFUNCDISALLOW

Attribute	Description
Name	USERFUNCDISALLOW
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FUNCDISALLOWFUNCID

Attribute	Description
Name	FUNCDISALLOWFUNCID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

USERROLE

Attribute	Description
Name	USERROLE
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ROLEBRNCD

Attribute	Description
Name	ROLEBRNCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

USRROLEID

Attribute	Description
Name	USRROLEID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>15</td></tr></table>

MASTERROLEDESC

Attribute	Description
Name	MASTERROLEDESC
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>45</td></tr></table>

USERSFUNCTIONS

Attribute	Description
Name	USERSFUNCTIONS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

USERFUNCBRNCD

Attribute	Description
Name	USERFUNCBRNCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

USERFUNCFUNCID

Attribute	Description
Name	USERFUNCFUNCID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 8

CONTROL1

Attribute	Description
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL2

Attribute	Description
Name	CONTROL2
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL3

Attribute	Description
Name	CONTROL3
Datatype	Decimal
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL4

Attribute	**Description**
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL5

Attribute	**Description**
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL6

Attribute	**Description**
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL7

Attribute	**Description**
Name	CONTROL7
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** totalDigits / 22

CONTROL8

Attribute	**Description**
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL9

Attribute	**Description**
Name	CONTROL9
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

USERFUNCSCTRL10

Attribute	**Description**
Name	USERFUNCSCTRL10
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

CONTROL11

Attribute	**Description**
Name	CONTROL11
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: totalDigits / 22

CONTROL12

Attribute	**Description**
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL13

Attribute	**Description**
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL14

Attribute	**Description**
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

CONTROL15

Attribute	**Description**
Name	CONTROL15
Datatype	Decimal
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** totalDigits / 22

CONTROL16

Attribute	**Description**
Name	CONTROL16
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

Grp-Restriction

Attribute	**Description**
Name	Grp-Restriction
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

GROUP_CODE

Attribute	**Description**
Name	GROUP_CODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 40

GROUP_DESC

Attribute	**Description**
Name	GROUP_DESC
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
maxLength	255

Centralisation

Attribute	Description
Name	Centralisation
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

USRROLEID

Attribute	Description
Name	USRROLEID
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	15

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	20

Dshmst

Attribute	Description
Name	Dshmst
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

USRNAME

Attribute	**Description**
Name	USRNAME
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

Dshdet

Attribute	**Description**
Name	Dshdet
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0 maxOccurs / unbounded

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

DESCRIPTION

Attribute	**Description**
Name	DESCRIPTION
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

SEQUENCE_NO

Attribute	**Description**
Name	SEQUENCE_NO
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description** totalDigits / 22

DBWHERECLAUSE

Attribute	**Description**
Name	DBWHERECLAUSE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 4000

SHOW_IN_DASHBOARD

Attribute	**Description**
Name	SHOW_IN_DASHBOARD
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

Where-Master

Attribute	**Description**
Name	Where-Master
Datatype	
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

COLUMN_NAME

Attribute	**Description**

Name	COLUMN_NAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

WHERE_CL

Attribute	**Description**
Name	WHERE_CL
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 500

CONDITION

Attribute	**Description**
Name	CONDITION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	Indicates Field Name

Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

2.25.2.SM-ReopenUserMaint-Req-IO-MSG.xsd

REOPENUSERMAINT_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

USR-IO

USRID

MAKER

MAKERSTAMP

MODNO

REOPENUSERMAINT_IOPK_REQ

Attribute	Description
Name	REOPENUSERMAINT_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH

Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	**Attribute** / **Description** minOccurs / 0

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String

Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></table>

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/]*</td></tr></table>

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

USR-IO

Attribute	Description
Name	USR-IO
Datatype	
Description	

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

2.25.3.SM-ReopenUserMaint-Res-Full-MSG.xsd

REOPENUSERMAINT_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

USR-Full

STRTDATE

USRNAME

USRPWD

ENDDT

USRLANG

HOMEBRN

CUSTNO

LDAPUSR

TIMELEVEL

AUTOAUTH

USRSTAT

USRID

EXTUSRREF

USRCATEG

TILLALLOW

ACCCLSALLOW

GLALLOW

USRTXNLMT

LMTSCCY

MAXTXNAMT

MAXAUTHAMT

BRNSALLOW

PRDSALLOW

PRDSACCESALLOW

TAX_IDENTIFIER

AMOUNT_FORMAT

DATE_FORMAT

STAFFACCRESTR

DEPT_CODE

DEPT_DESC

USRML

ELCMUSER

GROUP_CODE

MULTIBRN_ACCESS

OTH_RM_CUST_ACC_ALLOW

SUPERVISOR_ID

SUPERVISOR_NAME

DASHBOARD_REQD

ALERTS_ON_HOME

REFERENCE_NO

NO_CUMULATIVE_LOGINS

NO_SUCCESSIVE_LOGINS

SCREENSAVERTIMEOUTINSECONDS

MFI_USER

F10_REQD

F11_REQD

F12_REQD

ACCESS_CONTROL

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

RESTR_PWD

- *PWD*

MSGSRIGHTS

- *GEN*
- *HLD*
- *CNL*
- *TSTINP*
- *CHGNODE*
- *CHGADDR*
- *REL*
- *REINS*
- *CHGMEDIA*
- *CHGPRIOR*
- *BRNMOV*
- *PRNT*
- *TSTCHK*
- *HLDAUTH*
- *CNLAUTH*

TSTINPAUTH

CHGNODEAUTH

CHGADDRAUTH

RELAUTH

REINSAUTH

CHGMEDIAAUTH

BRNMOVAUTH

CHGPRIORAUTH

FTUPL

LNKCONT

MOVQ

CHGBRNIN

CHGADDRIN

AUTHRGHTS

CHGMSG

CHGMSGAUTH

CHGFORCCOVMATCH

CHANGE_FORCE_RELEASE_FUND

SUPPRESS

DELMSG

QUEUERIGHTS

QUEUE

USERTILLS

TILLID

TILLBRNCD

USERACCCLASS

ACCCLS

USERGLREST

NODEGL

USERGLEXCEPT

EXCEPLEAFGL

USERLIMITSROLE

LMTBRN

LMTSROLE

QLMTCCY

QINPLMT

QAUTHLMT

USERBRANCHES

BRNSBRN

BRNNAME

USERPRODUCTS

PRDPRDCD

PRDDESC

USERACCESSPRODUCTS

PRDACCESSPRDCD

PRDDESC

USERFUNCDISALLOW

FUNCDISALLOWFUNCID

USERROLE

ROLEBRNCD

USRROLEID

MASTERROLEDESC

USERSFUNCTIONS

USERFUNCBRNCD

USERFUNCFUNCID

CONTROL1

CONTROL2

CONTROL3

CONTROL4

CONTROL5

CONTROL6

CONTROL7

CONTROL8

CONTROL9

USERFUNCSCTRL10

CONTROL11

CONTROL12

CONTROL13

CONTROL14

CONTROL15

CONTROL16

Grp-Restriction

GROUP_CODE

GROUP_DESC

Centralisation

USRROLEID

ROLDESC

Dshmst

USRID

USRNAME

Dshdet

FUNCTIONID

DESCRIPTION

SEQUENCE_NO

DBWHERECLAUSE

SHOW_IN_DASHBOARD

Where-Master

COLUMN_NAME

WHERE_CL

CONDITION

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

REOPENUSERMAINT_FSFS_RES

Attribute	Description
Name	REOPENUSERMAINT_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>nillable</td><td>true</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	

Attribute	Description
minOccurs	0

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

USR-Full

Attribute	Description
Name	USR-Full
Datatype	
Description	

STRTDATE

Attribute	Description
Name	STRTDATE
Datatype	String
Description	

USRNAME

Attribute	Description

Name	USRNAME
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 35

USRPWD

Attribute	**Description**
Name	USRPWD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

ENDDT

Attribute	**Description**
Name	ENDDT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

USRLANG

Attribute	**Description**
Name	USRLANG
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

HOMEBRN

Attribute	**Description**
Name	HOMEBRN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

CUSTNO

Attribute	**Description**
Name	CUSTNO

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

LDAPUSR

Attribute	**Description**
Name	LDAPUSR
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 500

TIMELEVEL

Attribute	**Description**
Name	TIMELEVEL
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description**: totalDigits / 22; minInclusive / 0; maxInclusive / 9

AUTOAUTH

Attribute	**Description**
Name	AUTOAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

USRSTAT

Attribute	**Description**
Name	USRSTAT
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / E,H,D,L

USRID

Attribute	**Description**
Name	USRID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12

EXTUSRREF

Attribute	**Description**
Name	EXTUSRREF
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

USRCATEG

Attribute	**Description**
Name	USRCATEG
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,B

TILLALLOW

Attribute	**Description**
Name	TILLALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	A,D

ACCCLSALLOW

Attribute	Description
Name	ACCCLSALLOW
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	A,D

GLALLOW

Attribute	Description
Name	GLALLOW
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	A,D

USRTXNLMT

Attribute	Description
Name	USRTXNLMT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	U,R,N

LMTSCCY

Attribute	Description
Name	LMTSCCY
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

MAXTXNAMT

Attribute	Description
Name	MAXTXNAMT
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

MAXAUTHAMT

Attribute	Description
Name	MAXAUTHAMT
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

BRNSALLOW

Attribute	Description
Name	BRNSALLOW
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	A,D

PRDSALLOW

Attribute	Description
Name	PRDSALLOW
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / A,D

PRDSACCESALLOW

Attribute	**Description**
Name	PRDSACCESALLOW
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TAX_IDENTIFIER

Attribute	**Description**
Name	TAX_IDENTIFIER
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

AMOUNT_FORMAT

Attribute	**Description**
Name	AMOUNT_FORMAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / .,,,.,,

DATE_FORMAT

Attribute	**Description**
Name	DATE_FORMAT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	M/d/yyyy

STAFFACCRESTR

Attribute	Description
Name	STAFFACCRESTR
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

DEPT_CODE

Attribute	Description
Name	DEPT_CODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	3

DEPT_DESC

Attribute	Description
Name	DEPT_DESC
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	50

USRML

Attribute	Description
Name	USRML
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	50

ELCMUSER

Attribute	Description
Name	ELCMUSER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

GROUP_CODE

Attribute	Description
Name	GROUP_CODE
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	A,D

MULTIBRN_ACCESS

Attribute	Description
Name	MULTIBRN_ACCESS
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

OTH_RM_CUST_ACC_ALLOW

Attribute	Description
Name	OTH_RM_CUST_ACC_ALLOW
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

SUPERVISOR_ID

Attribute	Description
Name	SUPERVISOR_ID
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	80

SUPERVISOR_NAME

Attribute	Description
Name	SUPERVISOR_NAME
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

DASHBOARD_REQD

Attribute	Description
Name	DASHBOARD_REQD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

ALERTS_ON_HOME

Attribute	Description
Name	ALERTS_ON_HOME
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	
	Restrictions / **Description**: enumeration / Y,N

REFERENCE_NO

Attribute	**Description**
Name	REFERENCE_NO
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

NO_CUMULATIVE_LOGINS

Attribute	**Description**
Name	NO_CUMULATIVE_LOGINS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

NO_SUCCESSIVE_LOGINS

Attribute	**Description**
Name	NO_SUCCESSIVE_LOGINS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

SCREENSAVERTIMEOUTINSECONDS

Attribute	**Description**
Name	SCREENSAVERTIMEOUTINSECONDS
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	
	Restrictions / **Description**: totalDigits / 22

MFI_USER

Attribute	Description
Name	MFI_USER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

F10_REQD

Attribute	Description
Name	F10_REQD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

F11_REQD

Attribute	Description
Name	F11_REQD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

F12_REQD

Attribute	Description
Name	F12_REQD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

Restrictions	

Restrictions	Description
enumeration	Y,N

ACCESS_CONTROL

Attribute	Description
Name	ACCESS_CONTROL
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	U,G,B

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	12

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	35

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	4

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	1

RESTR_PWD

Attribute	Description
Name	RESTR_PWD
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

PWD

Attribute	Description
Name	PWD
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	12

MSGSRIGHTS

Attribute	Description
Name	MSGSRIGHTS
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

GEN

Attribute	Description
Name	GEN
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

HLD

Attribute	Description
Name	HLD
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

CNL

Attribute	**Description**
Name	CNL
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TSTINP

Attribute	**Description**
Name	TSTINP
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGNODE

Attribute	**Description**
Name	CHGNODE
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGADDR

Attribute	**Description**
Name	CHGADDR
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

REL

Attribute	**Description**
Name	REL
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

REINS

Attribute	**Description**
Name	REINS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGMEDIA

Attribute	**Description**
Name	CHGMEDIA
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGPRIOR

Attribute	**Description**
Name	CHGPRIOR
Datatype	String
Description	

Attribute	
	Attribute / **Description**: minOccurs / 0
Restrictions	
	Restrictions / **Description**: enumeration / Y,N

BRNMOV

Attribute	**Description**
Name	BRNMOV
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

PRNT

Attribute	**Description**
Name	PRNT
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TSTCHK

Attribute	**Description**
Name	TSTCHK
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

HLDAUTH

Attribute	**Description**
Name	HLDAUTH
Datatype	String
Description	

Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CNLAUTH

Attribute	Description
Name	CNLAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

TSTINPAUTH

Attribute	Description
Name	TSTINPAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGNODEAUTH

Attribute	Description
Name	CHGNODEAUTH
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	Y,N

CHGADDRAUTH

Attribute	Description
Name	CHGADDRAUTH
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

RELAUTH

Attribute	**Description**
Name	RELAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

REINSAUTH

Attribute	**Description**
Name	REINSAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGMEDIAAUTH

Attribute	**Description**
Name	CHGMEDIAAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

BRNMOVAUTH

Attribute	**Description**
Name	BRNMOVAUTH
Datatype	String
Description	

Attribute	
	Attribute / **Description** minOccurs / 0
Restrictions	
	Restrictions / **Description** enumeration / Y,N

CHGPRIORAUTH

Attribute	**Description**
Name	CHGPRIORAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

FTUPL

Attribute	**Description**
Name	FTUPL
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

LNKCONT

Attribute	**Description**
Name	LNKCONT
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

MOVQ

Attribute	**Description**
Name	MOVQ
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGBRNIN

Attribute	**Description**
Name	CHGBRNIN
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGADDRIN

Attribute	**Description**
Name	CHGADDRIN
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

AUTHRGHTS

Attribute	**Description**
Name	AUTHRGHTS
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGMSG

Attribute	**Description**
Name	CHGMSG
Datatype	String
Description	

Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGMSGAUTH

Attribute	**Description**
Name	CHGMSGAUTH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHGFORCCOVMATCH

Attribute	**Description**
Name	CHGFORCCOVMATCH
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

CHANGE_FORCE_RELEASE_FUND

Attribute	**Description**
Name	CHANGE_FORCE_RELEASE_FUND
Datatype	String
Description	
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

SUPPRESS

Attribute	**Description**
Name	SUPPRESS
Datatype	String
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

DELMSG

Attribute	Description
Name	DELMSG
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>Y,N</td></tr></table>

QUEUERIGHTS

Attribute	Description
Name	QUEUERIGHTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

QUEUE

Attribute	Description
Name	QUEUE
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>10</td></tr></table>

USERTILLS

Attribute	Description
Name	USERTILLS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TILLID

Attribute	Description
Name	TILLID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

TILLBRNCD

Attribute	Description
Name	TILLBRNCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

USERACCCLASS

Attribute	Description
Name	USERACCCLASS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ACCCLS

Attribute	Description
Name	ACCCLS
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>6</td></tr></table>

USERGLREST

Attribute	Description
Name	USERGLREST
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

NODEGL

Attribute	Description
Name	NODEGL
Datatype	String

Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

USERGLEXCEPT

Attribute	Description
Name	USERGLEXCEPT
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

EXCEPLEAFGL

Attribute	Description
Name	EXCEPLEAFGL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>9</td></tr></table>

USERLIMITSROLE

Attribute	Description
Name	USERLIMITSROLE
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

LMTBRN

Attribute	Description
Name	LMTBRN
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

LMTSROLE

Attribute	Description
Name	LMTSROLE

Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

QLMTCCY

Attribute	**Description**
Name	QLMTCCY
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

QINPLMT

Attribute	**Description**
Name	QINPLMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

QAUTHLMT

Attribute	**Description**
Name	QAUTHLMT
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

USERBRANCHES

Attribute	**Description**
Name	USERBRANCHES

Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

BRNSBRN

Attribute	Description
Name	BRNSBRN
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr></table>

USERPRODUCTS

Attribute	Description
Name	USERPRODUCTS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

PRDPRDCD

Attribute	Description
Name	PRDPRDCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>4</td></tr></table>

PRDDESC

Attribute	Description

Name	PRDDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

USERACCESSPRODUCTS

Attribute	**Description**
Name	USERACCESSPRODUCTS
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

PRDACCESSPRDCD

Attribute	**Description**
Name	PRDACCESSPRDCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4

PRDDESC

Attribute	**Description**
Name	PRDDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

USERFUNCDISALLOW

Attribute	**Description**
Name	USERFUNCDISALLOW
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FUNCDISALLOWFUNCID

Attribute	Description
Name	FUNCDISALLOWFUNCID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 8

USERROLE

Attribute	Description
Name	USERROLE
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ROLEBRNCD

Attribute	Description
Name	ROLEBRNCD
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 3

USRROLEID

Attribute	Description
Name	USRROLEID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

MASTERROLEDESC

Attribute	Description
Name	MASTERROLEDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 45

USERSFUNCTIONS

Attribute	Description
Name	USERSFUNCTIONS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

USERFUNCBRNCD

Attribute	Description
Name	USERFUNCBRNCD
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>3</td></tr></table>

USERFUNCFUNCID

Attribute	Description
Name	USERFUNCFUNCID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr></table>

CONTROL1

Attribute	Description
Name	CONTROL1
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>totalDigits</td><td>22</td></tr></table>

CONTROL2

Attribute	Description
Name	CONTROL2
Datatype	Decimal
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL3

Attribute	Description
Name	CONTROL3
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL4

Attribute	Description
Name	CONTROL4
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL5

Attribute	Description
Name	CONTROL5
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL6

Attribute	Description
Name	CONTROL6
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL7

Attribute	Description
Name	CONTROL7
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL8

Attribute	Description
Name	CONTROL8
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL9

Attribute	Description
Name	CONTROL9
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

USERFUNCSCTRL10

Attribute	Description
Name	USERFUNCSCTRL10
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL11

Attribute	Description
Name	CONTROL11
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL12

Attribute	Description
Name	CONTROL12
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL13

Attribute	Description
Name	CONTROL13
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL14

Attribute	Description
Name	CONTROL14
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL15

Attribute	Description
Name	CONTROL15
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

CONTROL16

Attribute	Description
Name	CONTROL16
Datatype	Decimal
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
totalDigits	22

Grp-Restriction

Attribute	Description
Name	Grp-Restriction
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

GROUP_CODE

Attribute	Description
Name	GROUP_CODE
Datatype	String
Description	
Restrictions	

Restrictions	Description
maxLength	40

GROUP_DESC

Attribute	Description

Name	GROUP_DESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

Centralisation

Attribute	**Description**
Name	Centralisation
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

USRROLEID

Attribute	**Description**
Name	USRROLEID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 15

ROLDESC

Attribute	**Description**
Name	ROLDESC
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

Dshmst

Attribute	**Description**
Name	Dshmst
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

USRNAME

Attribute	Description
Name	USRNAME
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

Dshdet

Attribute	Description
Name	Dshdet
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

DESCRIPTION

Attribute	Description

Name	DESCRIPTION
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

SEQUENCE_NO

Attribute	**Description**
Name	SEQUENCE_NO
Datatype	Decimal
Description	
Restrictions	**Restrictions** / **Description**: totalDigits / 22

DBWHERECLAUSE

Attribute	**Description**
Name	DBWHERECLAUSE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 4000

SHOW_IN_DASHBOARD

Attribute	**Description**
Name	SHOW_IN_DASHBOARD
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

Where-Master

Attribute	**Description**
Name	Where-Master
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0

COLUMN_NAME

Attribute	Description
Name	COLUMN_NAME
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>2000</td></tr></table>

WHERE_CL

Attribute	Description
Name	WHERE_CL
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>500</td></tr></table>

CONDITION

Attribute	Description
Name	CONDITION
Datatype	String
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>30</td></tr></table>

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

FLDNAM

Attribute	Description
Name	FLDNAM

Datatype	String
Description	Indicates Field Name
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></table>

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.25.4.SM-ReopenUserMaint-Res-PK-MSG.xsd

REOPENUSERMAINT_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

USR-PK

USRID

USR-IO

USRID

MAKER

MAKERSTAMP

MODNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

REOPENUSERMAINT_IOPK_RES

Attribute	Description
Name	REOPENUSERMAINT_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></table>

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></table>

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.
Attribute	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.
Attribute	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	This is the user id in the Source system who is performing the action.
Attribute	**Attribute** / **Description** minOccurs / 0

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></table>

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></table>

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	

Restrictions	Description
pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attribute	

Attribute	Description
minOccurs	0

Restrictions	

Restrictions	Description
maxLength	128
pattern	[a-zA-Z_0-9=+/]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	

Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

USR-PK

Attribute	Description
Name	USR-PK
Datatype	
Description	

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

USR-IO

Attribute	Description
Name	USR-IO
Datatype	
Description	

USRID

Attribute	Description
Name	USRID
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>12</td></tr></table>

MAKER

Attribute	Description

Name	MAKER
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Decimal
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 4

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attribute	**Attribute** / **Description**: minOccurs / 0; maxOccurs / unbounded

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	

Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

Gateway Documentation - FCUBSSMService
[Febraury] [2016]

Oracle Financial services Software Limited
Oracle Park
Off western Express Highway
Goregaon(East)
Mumbai,Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax:+91 22 6718 3001
www.oracle.com/financialservices/

Copyright © [2013], [2016], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.