

Gateway Documentation - FCUBSUPService
Oracle FLEXCUBE Universal Banking
Release 12.87.02.0.0
[February][2016]



Table Of Contents

1. Background	1
2. FCUBSUPService	2
2.1.AuthorizeBillInstr	2
2.1.1.UP-AuthorizeBillInstr-Req-Full-MSG.xsd	2
2.1.2.UP-AuthorizeBillInstr-Req-IO-MSG.xsd	21
2.1.3.UP-AuthorizeBillInstr-Res-Full-MSG.xsd	28
2.1.4.UP-AuthorizeBillInstr-Res-PK-MSG.xsd	49
2.2.CreateBillInstr	59
2.2.1.UP-CreateBillInstr-Req-Full-MSG.xsd	59
2.2.2.UP-CreateBillInstr-Req-IO-MSG.xsd	78
2.2.3.UP-CreateBillInstr-Res-Full-MSG.xsd	91
2.2.4.UP-CreateBillInstr-Res-PK-MSG.xsd	111
2.3.DeleteBillInstr	126
2.3.1.UP-DeleteBillInstr-Req-Full-MSG.xsd	126
2.3.2.UP-DeleteBillInstr-Req-IO-MSG.xsd	145
2.3.3.UP-DeleteBillInstr-Res-Full-MSG.xsd	152
2.3.4.UP-DeleteBillInstr-Res-PK-MSG.xsd	173
2.4.ModifyBillInstr	181
2.4.1.UP-ModifyBillInstr-Req-Full-MSG.xsd	181
2.4.2.UP-ModifyBillInstr-Req-IO-MSG.xsd	201
2.4.3.UP-ModifyBillInstr-Res-Full-MSG.xsd	213
2.4.4.UP-ModifyBillInstr-Res-PK-MSG.xsd	233
2.5.QueryBillInstr	247
2.5.1.UP-QueryBillInstr-Req-IO-MSG.xsd	247
2.5.2.UP-QueryBillInstr-Res-Full-MSG.xsd	254
2.6.CreateUPTransaction	275
2.6.1.Utility-Payment-Create-Req-Full-MSG.xsd	275
2.6.2.Utility-Payment-Create-Req-MSG.xsd	337
2.6.3.Utility-Payment-Create-Res-Full-MSG.xsd	394
2.6.4.Utility-Payment-Create-Res-PK-MSG.xsd	457
2.7.ReverseUPTransaction	517
2.7.1.Utility-Payment-Reverse-Req-Full-MSG.xsd	517
2.7.2.Utility-Payment-Reverse-Req-MSG.xsd	524
2.7.3.Utility-Payment-Reverse-Res-Full-MSG.xsd	531
2.7.4.Utility-Payment-Reverse-Res-PK-MSG.xsd	594

1. Background

Integration of different applications and solutions is a key area in today's systems. A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data. The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs. The integration needs supported by the Gateway can be broadly categorized from the perspective of Gateway as follows

1. Inbound application integration :

This is used when any external system needs to add, modify or query information within FLEXCUBE UBS

2. Outbound application integration :

This is used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS

The following sections provide detailed XSD documentation of all operations available in FCUBSUPService of Branch Module

2. FCUBSUPService

2.1.AuthorizeBillInstr

2.1.1.UP-AuthorizeBillInstr-Req-Full-MSG.xsd

AUTHORIZEBILLINSTR_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Bill-Instruct-Full

INSTRCTNO

CUSTID

UPTYPE

PROVDDID

PRM1VAL
PRM2VAL
PRM3VAL
PRM4VAL
PRM5VAL
PAYMOD
PAYAMNT
PAYCCY
DBTBRN
DBTACC
FRSTEXEDT
EXEFRQ
EXERETRYCNT
RETRYMOD
LSTEXEDT
NXTEXEDT
BRANCD
UPTYPDSC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Exec-Log
EXECDT
PAYMOD
PAYAMNT
PAYCCY
DBTBRN
DBTACC

MAXRCNT

ACBILAMT

STAT

Exec-Logdtl

COUNT

PDBILAMT

STAT

ERRCD

MESSAGE

Display

UDFDETAILS

FLDNAM

FLDVAL

AUTHORIZEBILLINSTR_FSFS_REQ

Attribute	Description
Name	AUTHORIZEBILLINSTR_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

ORACLE®

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description	This is the user id in the Source system who is performing the action.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description	This is the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>8</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	8						
pattern	[A-Z_0-9]*						

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>SUCCESS,WARNING,FAILURE</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	SUCCESS,WARNING,FAILURE
Restrictions	Description				
enumeration	SUCCESS,WARNING,FAILURE				

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD							
Datatype	String							
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>128</td></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9=+/*]</td></tr> </tbody> </table>		Restrictions	Description	maxLength	128	pattern	[a-zA-Z_0-9=+/*]
Restrictions	Description							
maxLength	128							
pattern	[a-zA-Z_0-9=+/*]							

ADDL

Attribute	Description					
Name	ADDL					
Datatype						
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

PARAM

Attribute	Description							
Name	PARAM							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Bill-Instruct-Full

Attribute	Description	

Name	Bill-Instruct-Full
Datatype	
Description	

INSTRCTNO

Attribute	Description					
Name	INSTRCTNO					
Datatype	String					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>16</td></tr> </tbody> </table>		Restrictions	Description	maxLength	16
Restrictions	Description					
maxLength	16					

CUSTID

Attribute	Description					
Name	CUSTID					
Datatype	String					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> </tbody> </table>		Restrictions	Description	maxLength	9
Restrictions	Description					
maxLength	9					

UPTYPE

Attribute	Description					
Name	UPTYPE					
Datatype	String					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>35</td></tr> </tbody> </table>		Restrictions	Description	maxLength	35
Restrictions	Description					
maxLength	35					

PROVIDID

Attribute	Description					
Name	PROVIDID					
Datatype	String					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>35</td></tr> </tbody> </table>		Restrictions	Description	maxLength	35
Restrictions	Description					
maxLength	35					

PRM1VAL

Attribute	Description	
Name	PRM1VAL	
Datatype	String	
Description		

Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	50

PRM2VAL

Attribute	Description	
	Name	PRM2VAL
Datatype	String	
	Description	
Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	50

PRM3VAL

Attribute	Description	
	Name	PRM3VAL
Datatype	String	
	Description	
Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	50

PRM4VAL

Attribute	Description	
	Name	PRM4VAL
Datatype	String	
	Description	
Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	50

PRM5VAL

Attribute	Description	
	Name	PRM5VAL
Datatype	String	
	Description	

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	50	

PAYMOD

Attribute	Description	
Name	PAYMOD	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	F,P

PAYAMNT

Attribute	Description	
Name	PAYAMNT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

PAYCCY

Attribute	Description	
Name	PAYCCY	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

DBTBRN

Attribute	Description	
Name	DBTBRN	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	3

DBTACC

Attribute	Description				
Name	DBTACC				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

FRSTEXEDT

Attribute	Description
Name	FRSTEXEDT
Datatype	String
Description	

EXEFRQ

Attribute	Description				
Name	EXEFRQ				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>M,Q,H,Y</td></tr></tbody></table>	Restrictions	Description	enumeration	M,Q,H,Y
Restrictions	Description				
enumeration	M,Q,H,Y				

EXERETRYCNT

Attribute	Description						
Name	EXERETRYCNT						
Datatype	Decimal						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>maxInclusive</td><td>99</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	maxInclusive	99
Restrictions	Description						
totalDigits	22						
maxInclusive	99						

RETRYMOD

Attribute	Description				
Name	RETRYMOD				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>P,F</td></tr></tbody></table>	Restrictions	Description	enumeration	P,F
Restrictions	Description				
enumeration	P,F				

LSTEXEDT

Attribute	Description
Name	LSTEXEDT
Datatype	String
Description	

NXTEXEDT

ORACLE®

Attribute	Description				
Name	NXTEXEDT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

BRANCD

Attribute	Description				
Name	BRANCD				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

UPTYPDSC

Attribute	Description				
Name	UPTYPDSC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> </tbody> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>12</td></tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	

Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
	Name	CHECKER
Datatype	String	
	Description	
Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
	Name	CHECKERSTAMP
Datatype	String	
	Description	
Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
	Name	MODNO
Datatype	Decimal	
	Description	
Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
	Name	TXNSTAT
Datatype	String	
	Description	

Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
	Name	AUTHSTAT
Datatype		
	String	
Description		
	Attribute	Description
Attribute	minOccurs	0
	Restrictions	Description
Restrictions	maxLength	1

Exec-Log

Attribute	Description	
	Name	Exec-Log
Datatype		
	String	
Description		
	Attribute	Description
Attribute	minOccurs	0
	maxOccurs	unbounded

EXECDT

Attribute	Description	
	Name	EXECDT
Datatype		
	String	
Description		
	Attribute	Description
Attribute	minOccurs	0

PAYMOD

Attribute	Description	
	Name	PAYMOD
Datatype		
	String	
Description		
	Attribute	Description
Attribute	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

PAYAMNT

Attribute	Description				
Name	PAYAMNT				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

PAYCCY

Attribute	Description				
Name	PAYCCY				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

DBTBRN

Attribute	Description				
Name	DBTBRN				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

DBTACC

Attribute	Description				
Name	DBTACC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

MAXRYCNT

Attribute	Description				
Name	MAXRYCNT				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

ACBILAMT

Attribute	Description				
Name	ACBILAMT				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

STAT

Attribute	Description				
Name	STAT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>P,S,F,U</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	P,S,F,U
Restrictions	Description				
enumeration	P,S,F,U				

Exec-Logdtl

Attribute	Description						
Name	Exec-Logdtl						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

COUNT

Attribute	Description				
Name	COUNT				
Datatype	Decimal				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

PDBILAMT

Attribute	Description				
Name	PDBILAMT				
Datatype	Decimal				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

STAT

Attribute	Description				
Name	STAT				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

ERRCD

Attribute	Description				
Name	ERRCD				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1000</td></tr></tbody></table>	Restrictions	Description	maxLength	1000
Restrictions	Description				
maxLength	1000				

MESSAGE

Attribute	Description				
Name	MESSAGE				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1000</td></tr> </tbody> </table>	Restrictions	Description	maxLength	1000
Restrictions	Description				
maxLength	1000				

Display

Attribute	Description				
Name	Display				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

UDFDETAILS

Attribute	Description						
Name	UDFDETAILS						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

FLDNAM

Attribute	Description						
Name	FLDNAM						
Datatype	String						
Description	Indicates Field Name						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	105	minLength	1
Restrictions	Description						
maxLength	105						
minLength	1						

FLDVAL

Attribute	Description				
Name	FLDVAL				
Datatype	String				
Description	Indicates Field Value				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.1.2.UP-AuthorizeBillInstr-Req-IO-MSG.xsd

AUTHORIZEBILLINSTR_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Bill-Instruct-IO

INSTRCTNO

CHECKER

CHECKERSTAMP

ORACLE®

MODNO

AUTHORIZEBILLINSTR_IOPK_REQ

Attribute	Description
Name	AUTHORIZEBILLINSTR_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_USERID

ORACLE®

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description	This is the user id in the Source system who is performing the action.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

FUNCTIONID

Attribute	Description				
Name	FUNCTIONID				
Datatype	String				
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>8</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	8						
pattern	[A-Z_0-9]*						

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>SUCCESS,WARNING,FAILURE</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	SUCCESS,WARNING,FAILURE
Restrictions	Description				
enumeration	SUCCESS,WARNING,FAILURE				

PASSWORD

Attribute	Description						
Name	PASSWORD						
Datatype	String						
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>128</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9=+/*]</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	128	pattern	[a-zA-Z_0-9=+/*]
Restrictions	Description						
maxLength	128						
pattern	[a-zA-Z_0-9=+/*]						

ADDL

Attribute	Description
Name	ADDL

ORACLE®

Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Bill-Instruct-IO

Attribute	Description	
Name	Bill-Instruct-IO	
Datatype		
Description		

INSTRCTNO

Attribute	Description	
Name	INSTRCTNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>16</td></tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

CHECKER

Attribute	Description				
Name	CHECKER				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

CHECKERSTAMP

Attribute	Description				
Name	CHECKERSTAMP				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

MODNO

Attribute	Description				
Name	MODNO				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>4</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	4
Restrictions	Description				
totalDigits	4				

2.1.3.UP-AuthorizeBillInstr-Res-Full-MSG.xsd

AUTHORIZEBILLINSTR_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

ORACLE®

CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY

Bill-Instruct-Full

INSTRCTNO
CUSTID
UPTYPE
PROVDID
PRM1VAL
PRM2VAL
PRM3VAL
PRM4VAL
PRM5VAL
PAYMOD
PAYAMNT
PAYCCY

DBTBRN
DBTACC
FRSTEXEDT
EXEFRQ
EXERETRYCNT
RETRYMOD
LSTEXEDT
NXTEXEDT
BRANCD
UPTYPDSC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Exec-Log
EXECDT
PAYMOD
PAYAMNT
PAYCCY
DBTBRN
DBTACC
MAXRYCNT
ACBILAMT
STAT
Exec-Logdtl
COUNT
PDBILAMT
STAT
ERRCD

MESSAGE

Display

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

E CODE

EDESC

FCUBS_WARNING_RESP

WARNING

W CODE

WDESC

AUTHORIZEBILLINSTR_FSFS_RES

Attribute	Description
Name	AUTHORIZEBILLINSTR_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services.

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description					
Name	MSGID					
Datatype	String					
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	String					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

USERID

Attribute	Description							
Name	USERID							
Datatype	String							
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description							
maxLength	12							
pattern	[A-Z_0-9]*							

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

ORACLE®

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description	This is the user id in the Source system who is performing the action.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description	This is the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>8</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	8						
pattern	[A-Z_0-9]*						

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>SUCCESS,WARNING,FAILURE</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	SUCCESS,WARNING,FAILURE
Restrictions	Description				
enumeration	SUCCESS,WARNING,FAILURE				

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD							
Datatype	String							
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>128</td></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9=+/*]</td></tr> </tbody> </table>		Restrictions	Description	maxLength	128	pattern	[a-zA-Z_0-9=+/*]
Restrictions	Description							
maxLength	128							
pattern	[a-zA-Z_0-9=+/*]							

ADDL

Attribute	Description					
Name	ADDL					
Datatype						
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

PARAM

Attribute	Description							
Name	PARAM							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Bill-Instruct-Full

Attribute	Description	

ORACLE®

Name	Bill-Instruct-Full
Datatype	
Description	

INSTRCTNO

Attribute	Description					
Name	INSTRCTNO					
Datatype	String					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>16</td></tr> </tbody> </table>		Restrictions	Description	maxLength	16
Restrictions	Description					
maxLength	16					

CUSTID

Attribute	Description					
Name	CUSTID					
Datatype	String					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> </tbody> </table>		Restrictions	Description	maxLength	9
Restrictions	Description					
maxLength	9					

UPTYPE

Attribute	Description					
Name	UPTYPE					
Datatype	String					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>35</td></tr> </tbody> </table>		Restrictions	Description	maxLength	35
Restrictions	Description					
maxLength	35					

PROVIDID

Attribute	Description					
Name	PROVIDID					
Datatype	String					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>35</td></tr> </tbody> </table>		Restrictions	Description	maxLength	35
Restrictions	Description					
maxLength	35					

PRM1VAL

Attribute	Description	
Name	PRM1VAL	
Datatype	String	
Description		

Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	50

PRM2VAL

Attribute	Description	
	Name	PRM2VAL
Datatype	String	
	Description	
Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	50

PRM3VAL

Attribute	Description	
	Name	PRM3VAL
Datatype	String	
	Description	
Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	50

PRM4VAL

Attribute	Description	
	Name	PRM4VAL
Datatype	String	
	Description	
Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	50

PRM5VAL

Attribute	Description	
	Name	PRM5VAL
Datatype	String	
	Description	

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	50	

PAYMOD

Attribute	Description	
Name	PAYMOD	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	F,P

PAYAMNT

Attribute	Description	
Name	PAYAMNT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
		minOccurs
	Restrictions	Description
		totalDigits

PAYCCY

Attribute	Description	
Name	PAYCCY	
Datatype	String	
Description		
Attribute	Attribute	Description
		minOccurs
Restrictions	Restrictions	Description
		maxLength

DBTBRN

Attribute	Description	
Name	DBTBRN	
Datatype	String	
Description		
Restrictions	Restrictions	Description
		maxLength

DBTACC

Attribute	Description				
Name	DBTACC				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

FRSTEXEDT

Attribute	Description
Name	FRSTEXEDT
Datatype	String
Description	

EXEFRQ

Attribute	Description				
Name	EXEFRQ				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>M,Q,H,Y</td></tr></tbody></table>	Restrictions	Description	enumeration	M,Q,H,Y
Restrictions	Description				
enumeration	M,Q,H,Y				

EXERETRYCNT

Attribute	Description						
Name	EXERETRYCNT						
Datatype	Decimal						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>maxInclusive</td><td>99</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	maxInclusive	99
Restrictions	Description						
totalDigits	22						
maxInclusive	99						

RETRYMOD

Attribute	Description				
Name	RETRYMOD				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>P,F</td></tr></tbody></table>	Restrictions	Description	enumeration	P,F
Restrictions	Description				
enumeration	P,F				

LSTEXEDT

Attribute	Description
Name	LSTEXEDT
Datatype	String
Description	

NXTEXEDT

ORACLE®

Attribute	Description				
Name	NXTEXEDT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

BRANCD

Attribute	Description				
Name	BRANCD				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

UPTYPDSC

Attribute	Description				
Name	UPTYPDSC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> </tbody> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>12</td></tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	

Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
	Name	CHECKER
Datatype	String	
	Description	
Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
	Name	CHECKERSTAMP
Datatype	String	
	Description	
Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
	Name	MODNO
Datatype	Decimal	
	Description	
Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
	Name	TXNSTAT
Datatype	String	
	Description	

Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
	Name	AUTHSTAT
Datatype		
	String	
Description		
	Attribute	Description
Attribute	minOccurs	0
	Restrictions	Description
Restrictions	maxLength	1

Exec-Log

Attribute	Description	
	Name	Exec-Log
Datatype		
	String	
Description		
	Attribute	Description
Attribute	minOccurs	0
	maxOccurs	unbounded

EXECDT

Attribute	Description	
	Name	EXECDT
Datatype		
	String	
Description		
	Attribute	Description
Attribute	minOccurs	0

PAYMOD

Attribute	Description	
	Name	PAYMOD
Datatype		
	String	
Description		
	Attribute	Description
Attribute	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

PAYAMNT

Attribute	Description				
Name	PAYAMNT				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

PAYCCY

Attribute	Description				
Name	PAYCCY				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

DBTBRN

Attribute	Description				
Name	DBTBRN				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

DBTACC

Attribute	Description				
Name	DBTACC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

MAXRYCNT

Attribute	Description				
Name	MAXRYCNT				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

ACBILAMT

Attribute	Description				
Name	ACBILAMT				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

STAT

Attribute	Description				
Name	STAT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>P,S,F,U</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	P,S,F,U
Restrictions	Description				
enumeration	P,S,F,U				

Exec-Logdtl

Attribute	Description						
Name	Exec-Logdtl						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

COUNT

Attribute	Description				
Name	COUNT				
Datatype	Decimal				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

PDBILAMT

Attribute	Description				
Name	PDBILAMT				
Datatype	Decimal				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

STAT

Attribute	Description				
Name	STAT				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

ERRCD

Attribute	Description				
Name	ERRCD				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1000</td></tr></tbody></table>	Restrictions	Description	maxLength	1000
Restrictions	Description				
maxLength	1000				

MESSAGE

Attribute	Description				
Name	MESSAGE				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1000</td></tr> </tbody> </table>	Restrictions	Description	maxLength	1000
Restrictions	Description				
maxLength	1000				

Display

Attribute	Description				
Name	Display				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

UDFDETAILS

Attribute	Description						
Name	UDFDETAILS						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

FLDNAM

Attribute	Description						
Name	FLDNAM						
Datatype	String						
Description	Indicates Field Name						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	105	minLength	1
Restrictions	Description						
maxLength	105						
minLength	1						

FLDVAL

Attribute	Description				
Name	FLDVAL				
Datatype	String				
Description	Indicates Field Value				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>150</td></tr> <tr> <td>minLength</td><td>0</td></tr> </tbody> </table>	Restrictions	Description	maxLength	150	minLength	0
Restrictions	Description						
maxLength	150						
minLength	0						

FCUBS_ERROR_RESP

Attribute	Description							
Name	FCUBS_ERROR_RESP							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

ERROR

Attribute	Description					
Name	ERROR					
Datatype						
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>		Attribute	Description	maxOccurs	unbounded
Attribute	Description					
maxOccurs	unbounded					

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description							
Name	FCUBS_WARNING_RESP							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

WARNING

Attribute	Description	
Name	WARNING	
Datatype		

ORACLE®

Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.1.4. UP-AuthorizeBillInstr-Res-PK-MSG.xsd

AUTHORIZEBILLINSTR_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

<i>NAME</i>	
<i>VALUE</i>	
<i>FCUBS_BODY</i>	
<i>Bill-Instruct-PK</i>	
<i>INSTRCTNO</i>	
<i>Bill-Instruct-IO</i>	
<i>INSTRCTNO</i>	
<i>CHECKER</i>	
<i>CHECKERSTAMP</i>	
<i>MODNO</i>	
<i>FCUBS_ERROR_RESP</i>	
<i>ERROR</i>	
<i>E CODE</i>	
<i>E DESC</i>	
<i>FCUBS_WARNING_RESP</i>	
<i>WARNING</i>	
<i>W CODE</i>	
<i>W DESC</i>	

AUTHORIZEBILLINSTR_IOPK_RES

Attribute	Description
Name	AUTHORIZEBILLINSTR_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td></tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description							
Name	USERID							
Datatype	String							
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description							
maxLength	12							
pattern	[A-Z_0-9]*							

BRANCH

Attribute	Description							
Name	BRANCH							
Datatype	String							
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>		Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description							
length	3							
pattern	[a-zA-Z_0-9]{3}							

MODULEID

Attribute	Description					
Name	MODULEID					
Datatype	String					
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

SERVICE

Attribute	Description					
Name	SERVICE					
Datatype	String					
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		Attribute	Description	nillable	true
Attribute	Description					
nillable	true					

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description					
Name	OPERATION					
Datatype	String					
Description	This is the operation of the service which is being invoked. This field is case-sensitive.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		Attribute	Description	nillable	true
Attribute	Description					
nillable	true					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

SOURCE_OPERATION

Attribute	Description					
Name	SOURCE_OPERATION					
Datatype	String					
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

SOURCE_USERID

Attribute	Description					
Name	SOURCE_USERID					
Datatype	String					
Description	This is the user id in the Source system who is performing the action.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This is the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	pattern	[a-zA-Z_0-9]*	

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MSGSTAT

Attribute	Description					
Name	MSGSTAT					
Datatype	String					
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>SUCCESS,WARNING,FAILURE</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	SUCCESS,WARNING,FAILURE
Restrictions	Description					
enumeration	SUCCESS,WARNING,FAILURE					

PASSWORD

Attribute	Description							
Name	PASSWORD							
Datatype	String							
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>128</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9+=/]*</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	128	pattern	[a-zA-Z_0-9+=/]*
Restrictions	Description							
maxLength	128							
pattern	[a-zA-Z_0-9+=/]*							

ADDL

Attribute	Description					
Name	ADDL					
Datatype						
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

PARAM

Attribute	Description							
Name	PARAM							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Bill-Instruct-PK

Attribute	Description
Name	Bill-Instruct-PK
Datatype	
Description	

INSTRCTNO

Attribute	Description		
Name	INSTRCTNO		
Datatype	String		
Description			
Attribute			
	Attribute	Description	
	minOccurs	0	
Restrictions		Restrictions	Description
		maxLength	16

Bill-Instruct-IO

Attribute	Description
Name	Bill-Instruct-IO
Datatype	
Description	

INSTRCTNO

Attribute	Description	
Name	INSTRCTNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>16</td></tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

CHECKER

Attribute	Description				
Name	CHECKER				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

CHECKERSTAMP

Attribute	Description				
Name	CHECKERSTAMP				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

MODNO

Attribute	Description				
Name	MODNO				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>4</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	4
Restrictions	Description				
totalDigits	4				

FCUBS_ERROR_RESP

Attribute	Description						
Name	FCUBS_ERROR_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String

Description	
-------------	--

2.2.CreateBillInstr

2.2.1.UP->CreateBillInstr-Req-Full-MSG.xsd

CREATEBILLINSTR_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Bill-Instruct-Full

INSTRCTNO

CUSTID

UPTYPE

PROVDDID

ORACLE®

PRM1VAL

PRM2VAL

PRM3VAL

PRM4VAL

PRM5VAL

PAYMOD

PAYAMNT

PAYCCY

DBTBRN

DBTACC

FRSTEXEDT

EXEFRQ

EXERETRYCNT

RETRYMOD

LSTEXEDT

NXTEXEDT

BRANCD

UPTYPDSC

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Exec-Log

EXECDT

PAYMOD

PAYAMNT

PAYCCY

DBTBRN

DBTACC

MAXRYCNT

ORACLE®

ACBILAMT

STAT

Exec-Logdtl

COUNT

PDBILAMT

STAT

ERRCD

MESSAGE

Display

UDFDETAILS

FLDNAM

FLDVAL

CREATEBILLINSTR_FSFS_REQ

Attribute	Description
Name	CREATEBILLINSTR_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description					
Name	MSGID					
Datatype	String					
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	String					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

USERID

Attribute	Description							
Name	USERID							
Datatype	String							
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description							
maxLength	12							
pattern	[A-Z_0-9]*							

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

ORACLE®

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description	This is the user id in the Source system who is performing the action.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description	This is the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>8</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	8						
pattern	[A-Z_0-9]*						

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>SUCCESS,WARNING,FAILURE</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	SUCCESS,WARNING,FAILURE
Restrictions	Description				
enumeration	SUCCESS,WARNING,FAILURE				

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD							
Datatype	String							
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>128</td></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9=+/*]</td></tr> </tbody> </table>		Restrictions	Description	maxLength	128	pattern	[a-zA-Z_0-9=+/*]
Restrictions	Description							
maxLength	128							
pattern	[a-zA-Z_0-9=+/*]							

ADDL

Attribute	Description					
Name	ADDL					
Datatype						
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

PARAM

Attribute	Description							
Name	PARAM							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Bill-Instruct-Full

Attribute	Description	

ORACLE®

Name	Bill-Instruct-Full
Datatype	
Description	

INSTRCTNO

Attribute	Description					
Name	INSTRCTNO					
Datatype	String					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>16</td></tr> </tbody> </table>		Restrictions	Description	maxLength	16
Restrictions	Description					
maxLength	16					

CUSTID

Attribute	Description					
Name	CUSTID					
Datatype	String					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> </tbody> </table>		Restrictions	Description	maxLength	9
Restrictions	Description					
maxLength	9					

UPTYPE

Attribute	Description					
Name	UPTYPE					
Datatype	String					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>35</td></tr> </tbody> </table>		Restrictions	Description	maxLength	35
Restrictions	Description					
maxLength	35					

PROVIDID

Attribute	Description					
Name	PROVIDID					
Datatype	String					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>35</td></tr> </tbody> </table>		Restrictions	Description	maxLength	35
Restrictions	Description					
maxLength	35					

PRM1VAL

Attribute	Description	
Name	PRM1VAL	
Datatype	String	
Description		

Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	50

PRM2VAL

Attribute	Description	
	Name	PRM2VAL
Datatype	String	
	Description	
Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	50

PRM3VAL

Attribute	Description	
	Name	PRM3VAL
Datatype	String	
	Description	
Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	50

PRM4VAL

Attribute	Description	
	Name	PRM4VAL
Datatype	String	
	Description	
Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	50

PRM5VAL

Attribute	Description	
	Name	PRM5VAL
Datatype	String	
	Description	

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	50	

PAYMOD

Attribute	Description	
Name	PAYMOD	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	F,P

PAYAMNT

Attribute	Description	
Name	PAYAMNT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
		minOccurs
	Restrictions	Description
		totalDigits

PAYCCY

Attribute	Description	
Name	PAYCCY	
Datatype	String	
Description		
Attribute	Attribute	Description
		minOccurs
Restrictions	Restrictions	Description
		maxLength

DBTBRN

Attribute	Description	
Name	DBTBRN	
Datatype	String	
Description		
Restrictions	Restrictions	Description
		maxLength

DBTACC

Attribute	Description				
Name	DBTACC				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

FRSTEXEDT

Attribute	Description
Name	FRSTEXEDT
Datatype	String
Description	

EXEFRQ

Attribute	Description				
Name	EXEFRQ				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>M,Q,H,Y</td></tr></tbody></table>	Restrictions	Description	enumeration	M,Q,H,Y
Restrictions	Description				
enumeration	M,Q,H,Y				

EXERETRYCNT

Attribute	Description						
Name	EXERETRYCNT						
Datatype	Decimal						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr><tr><td>maxInclusive</td><td>99</td></tr></tbody></table>	Restrictions	Description	totalDigits	22	maxInclusive	99
Restrictions	Description						
totalDigits	22						
maxInclusive	99						

RETRYMOD

Attribute	Description				
Name	RETRYMOD				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>P,F</td></tr></tbody></table>	Restrictions	Description	enumeration	P,F
Restrictions	Description				
enumeration	P,F				

LSTEXEDT

Attribute	Description
Name	LSTEXEDT
Datatype	String
Description	

NXTEXEDT

ORACLE®

Attribute	Description				
Name	NXTEXEDT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

BRANCD

Attribute	Description				
Name	BRANCD				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

UPTYPDSC

Attribute	Description				
Name	UPTYPDSC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> </tbody> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>12</td></tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	

Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
	Name	CHECKER
Datatype	String	
	Description	
Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
	Name	CHECKERSTAMP
Datatype	String	
	Description	
Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
	Name	MODNO
Datatype	Decimal	
	Description	
Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
	Name	TXNSTAT
Datatype	String	
	Description	

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	1	

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	1

Exec-Log

Attribute	Description	
Name	Exec-Log	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

EXECDT

Attribute	Description	
Name	EXECDT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

PAYMOD

Attribute	Description	
Name	PAYMOD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

PAYAMNT

Attribute	Description				
Name	PAYAMNT				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

PAYCCY

Attribute	Description				
Name	PAYCCY				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

DBTBRN

Attribute	Description				
Name	DBTBRN				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

DBTACC

Attribute	Description				
Name	DBTACC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

MAXRYCNT

Attribute	Description				
Name	MAXRYCNT				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

ACBILAMT

Attribute	Description				
Name	ACBILAMT				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

STAT

Attribute	Description				
Name	STAT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>P,S,F,U</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	P,S,F,U
Restrictions	Description				
enumeration	P,S,F,U				

Exec-Logdtl

Attribute	Description						
Name	Exec-Logdtl						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

COUNT

Attribute	Description				
Name	COUNT				
Datatype	Decimal				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

PDBILAMT

Attribute	Description				
Name	PDBILAMT				
Datatype	Decimal				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

STAT

Attribute	Description				
Name	STAT				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

ERRCD

Attribute	Description				
Name	ERRCD				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1000</td></tr></tbody></table>	Restrictions	Description	maxLength	1000
Restrictions	Description				
maxLength	1000				

MESSAGE

Attribute	Description				
Name	MESSAGE				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1000</td></tr> </tbody> </table>	Restrictions	Description	maxLength	1000
Restrictions	Description				
maxLength	1000				

Display

Attribute	Description				
Name	Display				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

UDFDETAILS

Attribute	Description						
Name	UDFDETAILS						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

FLDNAM

Attribute	Description						
Name	FLDNAM						
Datatype	String						
Description	Indicates Field Name						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	105	minLength	1
Restrictions	Description						
maxLength	105						
minLength	1						

FLDVAL

Attribute	Description				
Name	FLDVAL				
Datatype	String				
Description	Indicates Field Value				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.2.2.UP-CreateBillInstr-Req-IO-MSG.xsd

CREATEBILLINSTR_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Bill-Instruct-IO

INSTRCTNO

CUSTID

UPTYPE

ORACLE®

PROVIDID
PRM1VAL
PRM2VAL
PRM3VAL
PRM4VAL
PRM5VAL
PAYMOD
PAYAMNT
PAYCCY
DBTBRN
DBTACC
FRSTEXEDT
EXEFRQ
EXERETRYCNT
RETRYMOD
LSTEXEDT
BRANCD
Exec-Log
STAT
Exec-Logdtl
UDFDETAILS
FLDNAM
FLDVAL

CREATEBILLINSTR_IOPK_REQ

Attribute	Description
Name	CREATEBILLINSTR_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description

Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description					
Name	UBSCOMP					
Datatype	String					
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>		Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description					
enumeration	FCUBS,FCIS					

MSGID

Attribute	Description					
Name	MSGID					
Datatype	String					
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	pattern	[a-zA-Z_0-9]*	

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Attribute	Attribute		Description
	nillable	true	
Restrictions	Restrictions		Description
	pattern	[a-zA-Z_0-9]*	

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	pattern	[a-zA-Z_0-9]*	

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>SUCCESS,WARNING,FAILURE</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	SUCCESS,WARNING,FAILURE
Restrictions	Description				
enumeration	SUCCESS,WARNING,FAILURE				

PASSWORD

Attribute	Description						
Name	PASSWORD						
Datatype	String						
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>128</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9+=/]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	128	pattern	[a-zA-Z_0-9+=/]*
Restrictions	Description						
maxLength	128						
pattern	[a-zA-Z_0-9+=/]*						

ADDL

Attribute	Description				
Name	ADDL				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Bill-Instruct-IO

Attribute	Description
Name	Bill-Instruct-IO
Datatype	
Description	

INSTRCTNO

Attribute	Description		
Name	INSTRCTNO		
Datatype	String		
Description			
Attribute			
	Attribute	Description	
	minOccurs	0	
Restrictions		Restrictions	Description
		maxLength	16

CUSTID

Attribute	Description	
Name	CUSTID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

UPTYPE

Attribute	Description
Name	UPTYPE
Datatype	String
Description	

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>35</td></tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

PROVIDID

Attribute	Description				
Name	PROVIDID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

PRM1VAL

Attribute	Description				
Name	PRM1VAL				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

PRM2VAL

Attribute	Description				
Name	PRM2VAL				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

PRM3VAL

Attribute	Description				
Name	PRM3VAL				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

PRM4VAL

Attribute	Description				
Name	PRM4VAL				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

PRM5VAL

Attribute	Description				
Name	PRM5VAL				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

PAYMOD

Attribute	Description				
Name	PAYMOD				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>F,P</td></tr></tbody></table>	Restrictions	Description	enumeration	F,P
Restrictions	Description				
enumeration	F,P				

PAYAMNT

Attribute	Description				
Name	PAYAMNT				
Datatype	Decimal				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

PAYCCY

Attribute	Description
Name	PAYCCY

Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	3

DBTBRN

Attribute	Description	
Name	DBTBRN	
Datatype	String	
Description		
Restrictions	Restrictions	
	maxLength	3

DBTACC

Attribute	Description	
Name	DBTACC	
Datatype	String	
Description		
Restrictions	Restrictions	
	maxLength	20

FRSTEXEDT

Attribute	Description	
Name	FRSTEXEDT	
Datatype	String	
Description		

EXEFRQ

Attribute	Description	
Name	EXEFRQ	
Datatype	String	
Description		
Restrictions	Restrictions	
	enumeration	M,Q,H,Y

EXERETRYCNT

Attribute	Description	
Name	EXERETRYCNT	
Datatype	Decimal	
Description		

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> <tr> <td>maxInclusive</td><td>99</td></tr> </tbody> </table>	Restrictions	Description	totalDigits	22	maxInclusive	99
Restrictions	Description						
totalDigits	22						
maxInclusive	99						

RETRYMOD

Attribute	Description					
Name	RETRYMOD					
Datatype	String					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>P,F</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	P,F
Restrictions	Description					
enumeration	P,F					

LSTEXEDT

Attribute	Description	
Name	LSTEXEDT	
Datatype	String	
Description		

BRANCD

Attribute	Description					
Name	BRANCD					
Datatype	String					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	3
Restrictions	Description					
maxLength	3					

Exec-Log

Attribute	Description							
Name	Exec-Log							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

STAT

Attribute	Description	
Name	STAT	
Datatype	String	
Description		

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	enumeration	P,S,F,U	

Exec-Logdtl

Attribute	Description							
Name	Exec-Logdtl							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

UDFDETAILS

Attribute	Description							
Name	UDFDETAILS							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

FLDNAM

Attribute	Description							
Name	FLDNAM							
Datatype	String							
Description	Indicates Field Name							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>		Restrictions	Description	maxLength	105	minLength	1
Restrictions	Description							
maxLength	105							
minLength	1							

FLDVAL

Attribute	Description							
Name	FLDVAL							
Datatype	String							
Description	Indicates Field Value							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>150</td></tr> <tr> <td>minLength</td><td>0</td></tr> </tbody> </table>		Restrictions	Description	maxLength	150	minLength	0
Restrictions	Description							
maxLength	150							
minLength	0							

2.2.3.UP-CreateBillInstr-Res-Full-MSG.xsd

CREATEBILLINSTR_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Bill-Instruct-Full

INSTRCTNO

CUSTID

UPTYPE

PROVDID

PRM1VAL

PRM2VAL

PRM3VAL

ORACLE®

PRM4VAL
PRM5VAL
PAYMOD
PAYAMNT
PAYCCY
DBTBRN
DBTACC
FRSTEXEDT
EXEFRQ
EXERETRYCNT
RETRYMOD
LSTEXEDT
NXTTEXEDT
BRANCD
UPTYPDSC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Exec-Log

EXECDT
PAYMOD
PAYAMNT
PAYCCY
DBTBRN
DBTACC
MAXRYCNT
ACBILAMT
STAT

Exec-Logdtl
COUNT
PDBILAMT
STAT
ERRCD
MESSAGE
Display
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
E CODE
EDESC
FCUBS_WARNING_RESP
WARNING
W CODE
WDESC

CREATEBILLINSTR_FSFS_RES

Attribute	Description
Name	CREATEBILLINSTR_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td></tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description							
Name	USERID							
Datatype	String							
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description							
maxLength	12							
pattern	[A-Z_0-9]*							

BRANCH

Attribute	Description							
Name	BRANCH							
Datatype	String							
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>		Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description							
length	3							
pattern	[a-zA-Z_0-9]{3}							

MODULEID

Attribute	Description					
Name	MODULEID					
Datatype	String					
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

SERVICE

Attribute	Description					
Name	SERVICE					
Datatype	String					
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		Attribute	Description	nillable	true
Attribute	Description					
nillable	true					

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description					
Name	OPERATION					
Datatype	String					
Description	This is the operation of the service which is being invoked. This field is case-sensitive.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		Attribute	Description	nillable	true
Attribute	Description					
nillable	true					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

SOURCE_OPERATION

Attribute	Description					
Name	SOURCE_OPERATION					
Datatype	String					
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

SOURCE_USERID

Attribute	Description					
Name	SOURCE_USERID					
Datatype	String					
Description	This is the user id in the Source system who is performing the action.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This is the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	pattern	[a-zA-Z_0-9]*	

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MSGSTAT

Attribute	Description					
Name	MSGSTAT					
Datatype	String					
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>SUCCESS,WARNING,FAILURE</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	SUCCESS,WARNING,FAILURE
Restrictions	Description					
enumeration	SUCCESS,WARNING,FAILURE					

PASSWORD

Attribute	Description							
Name	PASSWORD							
Datatype	String							
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>128</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9+=/]*</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	128	pattern	[a-zA-Z_0-9+=/]*
Restrictions	Description							
maxLength	128							
pattern	[a-zA-Z_0-9+=/]*							

ADDL

Attribute	Description					
Name	ADDL					
Datatype						
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

PARAM

Attribute	Description							
Name	PARAM							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Bill-Instruct-Full

Attribute	Description
Name	Bill-Instruct-Full
Datatype	
Description	

INSTRCTNO

Attribute	Description		
Name	INSTRCTNO		
Datatype	String		
Description			
Attribute			
	Attribute	Description	
	minOccurs	0	
Restrictions		Restrictions	Description
		maxLength	16

CUSTID

Attribute	Description	
Name	CUSTID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

UPTYPE

Attribute	Description
Name	UPTYPE
Datatype	String
Description	

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>35</td></tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

PROVIDID

Attribute	Description				
Name	PROVIDID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

PRM1VAL

Attribute	Description				
Name	PRM1VAL				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

PRM2VAL

Attribute	Description				
Name	PRM2VAL				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

PRM3VAL

Attribute	Description				
Name	PRM3VAL				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

PRM4VAL

Attribute	Description				
Name	PRM4VAL				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

PRM5VAL

Attribute	Description				
Name	PRM5VAL				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

PAYMOD

Attribute	Description				
Name	PAYMOD				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>F,P</td></tr></tbody></table>	Restrictions	Description	enumeration	F,P
Restrictions	Description				
enumeration	F,P				

PAYAMNT

Attribute	Description				
Name	PAYAMNT				
Datatype	Decimal				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

PAYCCY

Attribute	Description
Name	PAYCCY

Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	3

DBTBRN

Attribute	Description	
Name	DBTBRN	
Datatype	String	
Description		
Restrictions	Restrictions	
	maxLength	3

DBTACC

Attribute	Description	
Name	DBTACC	
Datatype	String	
Description		
Restrictions	Restrictions	
	maxLength	20

FRSTEXEDT

Attribute	Description	
Name	FRSTEXEDT	
Datatype	String	
Description		

EXEFRQ

Attribute	Description	
Name	EXEFRQ	
Datatype	String	
Description		
Restrictions	Restrictions	
	enumeration	M,Q,H,Y

EXERETRYCNT

Attribute	Description	
Name	EXERETRYCNT	
Datatype	Decimal	
Description		

Restrictions	
	Restrictions
	totalDigits
	99

RETRYMOD

Attribute	Description
Name	RETRYMOD
Datatype	String
Description	
Restrictions	
	Restrictions
	enumeration
	P,F

LSTEXEDT

Attribute	Description
Name	LSTEXEDT
Datatype	String
Description	

NXTEXEDT

Attribute	Description
Name	NXTEXEDT
Datatype	String
Description	
Attribute	
	Attribute
	minOccurs
	0

BRANCD

Attribute	Description
Name	BRANCD
Datatype	String
Description	
Attribute	
	Attribute
	minOccurs
	0
Restrictions	
	Restrictions
	maxLength
	3

UPTYPDSC

Attribute	Description
Name	UPTYPDSC
Datatype	String
Description	
Attribute	
	Attribute
	minOccurs
	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> </tbody> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MAKERSTAMP

Attribute	Description				
Name	MAKERSTAMP				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

CHECKER

Attribute	Description				
Name	CHECKER				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

CHECKERSTAMP

Attribute	Description				
Name	CHECKERSTAMP				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>35</td></tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

MODNO

Attribute	Description				
Name	MODNO				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>4</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	4
Restrictions	Description				
totalDigits	4				

TXNSTAT

Attribute	Description				
Name	TXNSTAT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

AUTHSTAT

Attribute	Description				
Name	AUTHSTAT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

Exec-Log

Attribute	Description						
Name	Exec-Log						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

EXECDT

Attribute	Description				
Name	EXECDT				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PAYMOD

Attribute	Description				
Name	PAYMOD				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

PAYAMNT

Attribute	Description				
Name	PAYAMNT				
Datatype	Decimal				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

PAYCCY

Attribute	Description				
Name	PAYCCY				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

DBTBRN

Attribute	Description
Name	DBTBRN

Datatype	String					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3	
Restrictions	Description					
maxLength	3					

DBTACC

Attribute	Description					
Name	DBTACC					
Datatype	String					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>	Restrictions	Description	maxLength	20	
Restrictions	Description					
maxLength	20					

MAXRYCNT

Attribute	Description					
Name	MAXRYCNT					
Datatype	Decimal					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	totalDigits	22	
Restrictions	Description					
totalDigits	22					

ACBILAMT

Attribute	Description					
Name	ACBILAMT					
Datatype	Decimal					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	totalDigits	22	
Restrictions	Description					
totalDigits	22					

STAT

Attribute	Description	
Name	STAT	

Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	enumeration	P,S,F,U

Exec-Logdtl

Attribute	Description	
Name	Exec-Logdtl	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

COUNT

Attribute	Description	
Name	COUNT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

PDBILAMT

Attribute	Description	
Name	PDBILAMT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

STAT

Attribute	Description	
Name	STAT	
Datatype	String	
Description		

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	1	

ERRCD

Attribute	Description	
Name	ERRCD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	1000

MESSAGE

Attribute	Description	
Name	MESSAGE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	1000

Display

Attribute	Description	
Name	Display	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description						
Name	FLDNAM						
Datatype	String						
Description	Indicates Field Name						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	105	minLength	1
Restrictions	Description						
maxLength	105						
minLength	1						

FLDVAL

Attribute	Description						
Name	FLDVAL						
Datatype	String						
Description	Indicates Field Value						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></tbody></table>	Restrictions	Description	maxLength	150	minLength	0
Restrictions	Description						
maxLength	150						
minLength	0						

FCUBS_ERROR_RESP

Attribute	Description						
Name	FCUBS_ERROR_RESP						
Datatype							
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

ECODE

Attribute	Description
Name	EDESC
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.2.4.UP-CreateBillInstr-Res-PK-MSG.xsd

CREATEBILLINSTR_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

ORACLE®

SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY

Bill-Instruct-PK
INSTRCTNO
Bill-Instruct-IO
INSTRCTNO
CUSTID
UPTYPE
PROVDID
PRM1VAL
PRM2VAL
PRM3VAL
PRM4VAL
PRM5VAL
PAYMOD
PAYAMNT
PAYCCY
DBTBRN
DBTACC

FRSTEXEDT

EXEFRQ

EXERETRYCNT

RETRYMOD

LSTEXEDT

BRANCD

Exec-Log

STAT

Exec-Logdtl

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

E CODE

EDESC

FCUBS_WARNING_RESP

WARNING

W CODE

WDESC

CREATEBILLINSTR_IOPK_RES

Attribute	Description
Name	CREATEBILLINSTR_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td></tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description							
Name	USERID							
Datatype	String							
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description							
maxLength	12							
pattern	[A-Z_0-9]*							

BRANCH

Attribute	Description							
Name	BRANCH							
Datatype	String							
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>		Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description							
length	3							
pattern	[a-zA-Z_0-9]{3}							

MODULEID

Attribute	Description					
Name	MODULEID					
Datatype	String					
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

SERVICE

Attribute	Description					
Name	SERVICE					
Datatype	String					
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		Attribute	Description	nillable	true
Attribute	Description					
nillable	true					

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description					
Name	OPERATION					
Datatype	String					
Description	This is the operation of the service which is being invoked. This field is case-sensitive.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		Attribute	Description	nillable	true
Attribute	Description					
nillable	true					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

SOURCE_OPERATION

Attribute	Description					
Name	SOURCE_OPERATION					
Datatype	String					
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

SOURCE_USERID

Attribute	Description					
Name	SOURCE_USERID					
Datatype	String					
Description	This is the user id in the Source system who is performing the action.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This is the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	pattern	[a-zA-Z_0-9]*	

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MSGSTAT

Attribute	Description					
Name	MSGSTAT					
Datatype	String					
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>SUCCESS,WARNING,FAILURE</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	SUCCESS,WARNING,FAILURE
Restrictions	Description					
enumeration	SUCCESS,WARNING,FAILURE					

PASSWORD

Attribute	Description							
Name	PASSWORD							
Datatype	String							
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>128</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9+=/]*</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	128	pattern	[a-zA-Z_0-9+=/]*
Restrictions	Description							
maxLength	128							
pattern	[a-zA-Z_0-9+=/]*							

ADDL

Attribute	Description					
Name	ADDL					
Datatype						
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

PARAM

Attribute	Description							
Name	PARAM							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Bill-Instruct-PK

Attribute	Description
Name	Bill-Instruct-PK
Datatype	
Description	

INSTRCTNO

Attribute	Description		
Name	INSTRCTNO		
Datatype	String		
Description			
Attribute			
	Attribute	Description	
	minOccurs	0	
Restrictions		Restrictions	Description
		maxLength	16

Bill-Instruct-IO

Attribute	Description
Name	Bill-Instruct-IO
Datatype	
Description	

INSTRCTNO

Attribute	Description	
Name	INSTRCTNO	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>16</td></tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

CUSTID

Attribute	Description					
Name	CUSTID					
Datatype	String					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	9
Restrictions	Description					
maxLength	9					

UPTYPE

Attribute	Description					
Name	UPTYPE					
Datatype	String					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	35
Restrictions	Description					
maxLength	35					

PROVDid

Attribute	Description					
Name	PROVDid					
Datatype	String					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	35
Restrictions	Description					
maxLength	35					

PRM1VAL

Attribute	Description					
Name	PRM1VAL					
Datatype	String					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	50
Restrictions	Description					
maxLength	50					

PRM2VAL

Attribute	Description	
Name	PRM2VAL	
Datatype	String	
Description		

Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	50

PRM3VAL

Attribute	Description	
	Name	PRM3VAL
Datatype	String	
	Description	
Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	50

PRM4VAL

Attribute	Description	
	Name	PRM4VAL
Datatype	String	
	Description	
Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	50

PRM5VAL

Attribute	Description	
	Name	PRM5VAL
Datatype	String	
	Description	
Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	50

PAYMOD

Attribute	Description	
	Name	PAYMOD
Datatype	String	
	Description	

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>F,P</td></tr> </tbody> </table>	Restrictions	Description	enumeration	F,P
Restrictions	Description				
enumeration	F,P				

PAYAMNT

Attribute	Description				
Name	PAYAMNT				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

PAYCCY

Attribute	Description				
Name	PAYCCY				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

DBTBRN

Attribute	Description				
Name	DBTBRN				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

DBTACC

Attribute	Description				
Name	DBTACC				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

FRSTEXEDT

Attribute	Description
-----------	--------------------

Name	FRSTTEXEDT
Datatype	String
Description	

EXEFRQ

Attribute	Description					
Name	EXEFRQ					
Datatype	String					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>M,Q,H,Y</td></tr> </tbody> </table>		Restrictions	Description	enumeration	M,Q,H,Y
Restrictions	Description					
enumeration	M,Q,H,Y					

EXERETRYCNT

Attribute	Description							
Name	EXERETRYCNT							
Datatype	Decimal							
Description								
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> <tr> <td>maxInclusive</td><td>99</td></tr> </tbody> </table>		Restrictions	Description	totalDigits	22	maxInclusive	99
Restrictions	Description							
totalDigits	22							
maxInclusive	99							

RETRYMOD

Attribute	Description					
Name	RETRYMOD					
Datatype	String					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>P,F</td></tr> </tbody> </table>		Restrictions	Description	enumeration	P,F
Restrictions	Description					
enumeration	P,F					

LSTEXEDT

Attribute	Description	
Name	LSTEXEDT	
Datatype	String	
Description		

BRANCD

Attribute	Description					
Name	BRANCD					
Datatype	String					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>		Restrictions	Description	maxLength	3
Restrictions	Description					
maxLength	3					

Attribute	Description						
Name	Exec-Log						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

STAT

Attribute	Description				
Name	STAT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>P,S,F,U</td></tr> </tbody> </table>	Restrictions	Description	enumeration	P,S,F,U
Restrictions	Description				
enumeration	P,S,F,U				

Exec-Logdtl

Attribute	Description						
Name	Exec-Logdtl						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

UDFDETAILS

Attribute	Description						
Name	UDFDETAILS						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

FLDNAM

Attribute	Description						
Name	FLDNAM						
Datatype	String						
Description	Indicates Field Name						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	105	minLength	1
Restrictions	Description						
maxLength	105						
minLength	1						

FLDVAL

Attribute	Description						
Name	FLDVAL						
Datatype	String						
Description	Indicates Field Value						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></tbody></table>	Restrictions	Description	maxLength	150	minLength	0
Restrictions	Description						
maxLength	150						
minLength	0						

FCUBS_ERROR_RESP

Attribute	Description						
Name	FCUBS_ERROR_RESP						
Datatype							
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attribute	
Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.3.DeleteBillInstr

2.3.1.UP-DeleteBillInstr-Req-Full-MSG.xsd

DELETEBILLINSTR_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

ORACLE®

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Bill-Instruct-Full

INSTRCTNO

CUSTID

UPTYPE

PROVDDID

PRM1VAL

PRM2VAL

PRM3VAL

PRM4VAL

PRM5VAL

PAYMOD

PAYAMNT

PAYCCY

DBTBRN

DBTACC

FRSTEXEDT

EXEFRQ

EXERETRYCNT

RETRYMOD

LSTEXEDT

NXTEXEDT

BRANCD

UPTYPDSC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Exec-Log
 EXECDT
 PAYMOD
 PAYAMNT
 PAYCCY
 DBTBRN
 DBTACC
 MAXRYCNT
 ACBILAMT
 STAT
Exec-Logdtl
 COUNT
 PDBILAMT
 STAT
 ERRCD
 MESSAGE
Display
UDFDETAILS
 FLDNAM
 FLDVAL

DELETEBILLINSTR_FSFS_REQ

Attribute	Description
Name	DELETEBILLINSTR_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>12</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

ORACLE®

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description	This is the user id in the Source system who is performing the action.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

DESTINATION

ORACLE®

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description	This is the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>8</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	8						
pattern	[A-Z_0-9]*						

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	pattern	[a-zA-Z_0-9]*	

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		

Attribute	
Attribute	Description
minOccurs	0
maxOccurs	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Bill-Instruct-Full

Attribute	Description
Name	Bill-Instruct-Full
Datatype	
Description	

INSTRCTNO

Attribute	Description
Name	INSTRCTNO
Datatype	String
Description	
Attribute	
Attribute	Description
minOccurs	0
Restrictions	
Restrictions	Description
maxLength	16

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	
Restrictions	
Restrictions	Description
maxLength	9

UPTYPE

ORACLE®

Attribute	Description				
Name	UPTYPE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>35</td></tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

PROVIDID

Attribute	Description				
Name	PROVIDID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>35</td></tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

PRM1VAL

Attribute	Description				
Name	PRM1VAL				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>50</td></tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

PRM2VAL

Attribute	Description				
Name	PRM2VAL				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>50</td></tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

PRM3VAL

Attribute	Description
Name	PRM3VAL
Datatype	String
Description	

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	50	

PRM4VAL

Attribute	Description	
Name	PRM4VAL	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	50

PRM5VAL

Attribute	Description	
Name	PRM5VAL	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	50

PAYMOD

Attribute	Description	
Name	PAYMOD	
Datatype	String	
Description		
Restrictions	Restrictions	
	enumeration	F,P

PAYAMNT

Attribute	Description	
Name	PAYAMNT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

PAYCCY

Attribute	Description				
Name	PAYCCY				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

DBTBRN

Attribute	Description				
Name	DBTBRN				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

DBTACC

Attribute	Description				
Name	DBTACC				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

FRSTEXEDT

Attribute	Description
Name	FRSTEXEDT
Datatype	String
Description	

EXEFRQ

Attribute	Description				
Name	EXEFRQ				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>M,Q,H,Y</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	M,Q,H,Y
Restrictions	Description				
enumeration	M,Q,H,Y				

EXERETRYCNT

ORACLE®

Attribute	Description						
Name	EXERETRYCNT						
Datatype	Decimal						
Description							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> <tr> <td>maxInclusive</td><td>99</td></tr> </tbody> </table>	Restrictions	Description	totalDigits	22	maxInclusive	99
Restrictions	Description						
totalDigits	22						
maxInclusive	99						

RETRYMOD

Attribute	Description				
Name	RETRYMOD				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>P,F</td></tr> </tbody> </table>	Restrictions	Description	enumeration	P,F
Restrictions	Description				
enumeration	P,F				

LSTEXEDT

Attribute	Description
Name	LSTEXEDT
Datatype	String
Description	

NXTEXEDT

Attribute	Description				
Name	NXTEXEDT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

BRANCD

Attribute	Description				
Name	BRANCD				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

UPTYPDSC

Attribute	Description
Name	UPTYPDSC
Datatype	String

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	105

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	

Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

Exec-Log

Attribute	Description	
Name	Exec-Log	
Datatype		

Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

EXECDT

Attribute	Description	
Name	EXECDT	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0

PAYMOD

Attribute	Description	
Name	PAYMOD	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	maxLength	1

PAYAMNT

Attribute	Description	
Name	PAYAMNT	
Datatype	Decimal	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	totalDigits	22

PAYCCY

Attribute	Description	
Name	PAYCCY	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

DBTBRN

Attribute	Description				
Name	DBTBRN				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

DBTACC

Attribute	Description				
Name	DBTACC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

MAXRYCNT

Attribute	Description				
Name	MAXRYCNT				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

ACBILAMT

Attribute	Description				
Name	ACBILAMT				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

STAT

Attribute	Description				
Name	STAT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>P,S,F,U</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	P,S,F,U
Restrictions	Description				
enumeration	P,S,F,U				

Exec-Logdtl

Attribute	Description						
Name	Exec-Logdtl						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

COUNT

Attribute	Description				
Name	COUNT				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

PDBILAMT

Attribute	Description				
Name	PDBILAMT				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

STAT

Attribute	Description				
Name	STAT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

ERRCD

Attribute	Description				
Name	ERRCD				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>1000</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	1000
Restrictions	Description				
maxLength	1000				

MESSAGE

Attribute	Description				
Name	MESSAGE				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>1000</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	1000
Restrictions	Description				
maxLength	1000				

Display

Attribute	Description				
Name	Display				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

UDFDETAILS

Attribute	Description							
Name	UDFDETAILS							
Datatype								
Description								
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

FLDNAM

Attribute	Description							
Name	FLDNAM							
Datatype	String							
Description	Indicates Field Name							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>		Restrictions	Description	maxLength	105	minLength	1
Restrictions	Description							
maxLength	105							
minLength	1							

FLDVAL

Attribute	Description							
Name	FLDVAL							
Datatype	String							
Description	Indicates Field Value							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></tbody></table>		Restrictions	Description	maxLength	150	minLength	0
Restrictions	Description							
maxLength	150							
minLength	0							

2.3.2. UP-DeleteBillInstr-Req-IO-MSG.xsd

DELETEBILLINSTR_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

ORACLE®

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Bill-Instruct-IO

INSTRCTNO

DELETEBILLINSTR_IOPK_REQ

Attribute	Description
Name	DELETEBILLINSTR_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

ORACLE®

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>12</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute	Attribute		Description
	nillable	true	
Restrictions	Restrictions		Description
	pattern	[a-zA-Z_0-9]*	

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	

Datatype	String					
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

FUNCTIONID

Attribute	Description							
Name	FUNCTIONID							
Datatype	String							
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>8</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
Restrictions	Description							
maxLength	8							
pattern	[A-Z_0-9]*							

ACTION

Attribute	Description					
Name	ACTION					
Datatype	String					
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	enumeration	SUCCESS,WARNING,FAILURE	

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Bill-Instruct-IO

Attribute	Description
Name	Bill-Instruct-IO
Datatype	
Description	

INSTRCTNO

Attribute	Description				
Name	INSTRCTNO				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>16</td></tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

2.3.3. UP-DeleteBillInstr-Res-Full-MSG.xsd

DELETEBILLINSTR_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Bill-Instruct-Full

INSTRCTNO

CUSTID

UPTYPE

PROVDID

PRM1VAL

PRM2VAL

PRM3VAL

PRM4VAL

PRM5VAL

PAYMOD

PAYAMNT

PAYCCY

DBTBRN

DBTACC

FRSTEXEDT

EXEFRQ

EXERETRYCNT

RETRYMOD

LSTEXEDT

NXTEXEDT

BRANCD

UPTYPDSC

ORACLE®

MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Exec-Log
EXECDT
PAYMOD
PAYAMNT
PAYCCY
DBTBRN
DBTACC
MAXRYCNT
ACBILAMT
STAT
Exec-Logdtl
COUNT
PDBILAMT
STAT
ERRCD
MESSAGE
Display
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP

WARNING**WCODE****WDESC****DELETEBILLINSTR_FSFS_RES**

Attribute	Description
Name	DELETEBILLINSTR_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	pattern	[a-zA-Z_0-9]*	

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description	This is the user id in the Source system who is performing the action.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	8	
		pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	128
		pattern
		[a-zA-Z_0-9=+/*]

Attribute	Description				
Name	ADDL				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Bill-Instruct-Full

Attribute	Description
Name	Bill-Instruct-Full
Datatype	
Description	

INSTRCTNO

Attribute	Description				
Name	INSTRCTNO				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>16</td></tr> </tbody> </table>		Restrictions	Description	maxLength	16
Restrictions	Description					
maxLength	16					

CUSTID

Attribute	Description					
Name	CUSTID					
Datatype	String					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	9
Restrictions	Description					
maxLength	9					

UPTYPE

Attribute	Description					
Name	UPTYPE					
Datatype	String					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	35
Restrictions	Description					
maxLength	35					

PROVIDID

Attribute	Description					
Name	PROVIDID					
Datatype	String					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	35
Restrictions	Description					
maxLength	35					

PRM1VAL

Attribute	Description					
Name	PRM1VAL					
Datatype	String					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	50
Restrictions	Description					
maxLength	50					

PRM2VAL

Attribute	Description	
Name	PRM2VAL	
Datatype	String	
Description		

Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	50

PRM3VAL

Attribute	Description	
	Name	PRM3VAL
Datatype	String	
	Description	
Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	50

PRM4VAL

Attribute	Description	
	Name	PRM4VAL
Datatype	String	
	Description	
Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	50

PRM5VAL

Attribute	Description	
	Name	PRM5VAL
Datatype	String	
	Description	
Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	50

PAYMOD

Attribute	Description	
	Name	PAYMOD
Datatype	String	
	Description	

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>F,P</td></tr> </tbody> </table>	Restrictions	Description	enumeration	F,P
Restrictions	Description				
enumeration	F,P				

PAYAMNT

Attribute	Description				
Name	PAYAMNT				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

PAYCCY

Attribute	Description				
Name	PAYCCY				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

DBTBRN

Attribute	Description				
Name	DBTBRN				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

DBTACC

Attribute	Description				
Name	DBTACC				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

FRSTEXEDT

Attribute	Description
-----------	--------------------

Name	FRSTTEXEDT
Datatype	String
Description	

EXEFRQ

Attribute	Description					
Name	EXEFRQ					
Datatype	String					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>M,Q,H,Y</td></tr> </tbody> </table>		Restrictions	Description	enumeration	M,Q,H,Y
Restrictions	Description					
enumeration	M,Q,H,Y					

EXERETRYCNT

Attribute	Description							
Name	EXERETRYCNT							
Datatype	Decimal							
Description								
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> <tr> <td>maxInclusive</td><td>99</td></tr> </tbody> </table>		Restrictions	Description	totalDigits	22	maxInclusive	99
Restrictions	Description							
totalDigits	22							
maxInclusive	99							

RETRYMOD

Attribute	Description					
Name	RETRYMOD					
Datatype	String					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>P,F</td></tr> </tbody> </table>		Restrictions	Description	enumeration	P,F
Restrictions	Description					
enumeration	P,F					

LSTEXEDT

Attribute	Description	
Name	LSTEXEDT	
Datatype	String	
Description		

NXTEXEDT

Attribute	Description					
Name	NXTEXEDT					
Datatype	String					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

BRANCD

Attribute	Description	
Name	BRANCD	

ORACLE®

Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	3

UPTYPDSC

Attribute	Description	
Name	UPTYPDSC	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	105

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	35

CHECKER

Attribute	Description	
Name	CHECKER	

Datatype	String					
Description						
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>12</td></tr> </table>	Restrictions	Description	maxLength	12	
Restrictions	Description					
maxLength	12					

CHECKERSTAMP

Attribute	Description					
Name	CHECKERSTAMP					
Datatype	String					
Description						
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>35</td></tr> </table>	Restrictions	Description	maxLength	35	
Restrictions	Description					
maxLength	35					

MODNO

Attribute	Description					
Name	MODNO					
Datatype	Decimal					
Description						
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>totalDigits</td><td>4</td></tr> </table>	Restrictions	Description	totalDigits	4	
Restrictions	Description					
totalDigits	4					

TXNSTAT

Attribute	Description					
Name	TXNSTAT					
Datatype	String					
Description						
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>1</td></tr> </table>	Restrictions	Description	maxLength	1	
Restrictions	Description					
maxLength	1					

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	

Datatype	String	
Description		
Attribute	Attribute	Description
		minOccurs 0
Restrictions	Restrictions	Description
		maxLength 1

Exec-Log

Attribute	Description	
Name	Exec-Log	
Datatype		
Description		
Attribute	Attribute	Description
		minOccurs 0
		maxOccurs unbounded

EXECDT

Attribute	Description	
Name	EXECDT	
Datatype	String	
Description		
Attribute	Attribute	Description
		minOccurs 0

PAYMOD

Attribute	Description	
Name	PAYMOD	
Datatype	String	
Description		
Attribute	Attribute	Description
		minOccurs 0
Restrictions	Restrictions	Description
		maxLength 1

PAYAMNT

Attribute	Description	
Name	PAYAMNT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
		minOccurs 0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

PAYCCY

Attribute	Description				
Name	PAYCCY				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

DBTBRN

Attribute	Description				
Name	DBTBRN				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

DBTACC

Attribute	Description				
Name	DBTACC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

MAXRYCNT

Attribute	Description				
Name	MAXRYCNT				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

ACBILAMT

Attribute	Description				
Name	ACBILAMT				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

STAT

Attribute	Description				
Name	STAT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>P,S,F,U</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	P,S,F,U
Restrictions	Description				
enumeration	P,S,F,U				

Exec-Logdtl

Attribute	Description						
Name	Exec-Logdtl						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

COUNT

Attribute	Description				
Name	COUNT				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

PDBILAMT

Attribute	Description				
Name	PDBILAMT				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

STAT

Attribute	Description				
Name	STAT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

ERRCD

Attribute	Description				
Name	ERRCD				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>1000</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	1000
Restrictions	Description				
maxLength	1000				

MESSAGE

Attribute	Description				
Name	MESSAGE				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1000</td></tr> </tbody> </table>	Restrictions	Description	maxLength	1000
Restrictions	Description				
maxLength	1000				

Display

Attribute	Description				
Name	Display				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

UDFDETAILS

Attribute	Description						
Name	UDFDETAILS						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

FLDNAM

Attribute	Description						
Name	FLDNAM						
Datatype	String						
Description	Indicates Field Name						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>105</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	105	minLength	1
Restrictions	Description						
maxLength	105						
minLength	1						

FLDVAL

Attribute	Description						
Name	FLDVAL						
Datatype	String						
Description	Indicates Field Value						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>150</td> </tr> <tr> <td>minLength</td> <td>0</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	150	minLength	0
Restrictions	Description						
maxLength	150						
minLength	0						

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP

Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded	
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE

ORACLE®

Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.3.4. UP-DeleteBillInstr-Res-PK-MSG.xsd

DELETEBILLINSTR_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Bill-Instruct-PK

INSTRCTNO

ORACLE®

Bill-Instruct-IO

INSTRCTNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

DELETEBILLINSTR_IOPK_RES

Attribute	Description
Name	DELETEBILLINSTR_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

ORACLE®

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description	This is the user id in the Source system who is performing the action.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description	This is the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>8</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	8						
pattern	[A-Z_0-9]*						

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>SUCCESS,WARNING,FAILURE</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	SUCCESS,WARNING,FAILURE
Restrictions	Description				
enumeration	SUCCESS,WARNING,FAILURE				

PASSWORD

Attribute	Description
------------------	--------------------

Name	PASSWORD							
Datatype	String							
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>128</td></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9=+/*]</td></tr> </tbody> </table>		Restrictions	Description	maxLength	128	pattern	[a-zA-Z_0-9=+/*]
Restrictions	Description							
maxLength	128							
pattern	[a-zA-Z_0-9=+/*]							

ADDL

Attribute	Description					
Name	ADDL					
Datatype						
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

PARAM

Attribute	Description							
Name	PARAM							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Bill-Instruct-PK

Attribute	Description	

ORACLE®

Name	Bill-Instruct-PK
Datatype	
Description	

INSTRCTNO

Attribute	Description					
Name	INSTRCTNO					
Datatype	String					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>16</td></tr> </tbody> </table>		Restrictions	Description	maxLength	16
Restrictions	Description					
maxLength	16					

Bill-Instruct-IO

Attribute	Description	
Name	Bill-Instruct-IO	
Datatype		
Description		

INSTRCTNO

Attribute	Description					
Name	INSTRCTNO					
Datatype	String					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>16</td></tr> </tbody> </table>		Restrictions	Description	maxLength	16
Restrictions	Description					
maxLength	16					

FCUBS_ERROR_RESP

Attribute	Description							
Name	FCUBS_ERROR_RESP							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		

Attribute	
Attribute	Description
maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"> <tr> <td>Attribute</td> <td>Description</td> </tr> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"> <tr> <td>Attribute</td> <td>Description</td> </tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.4.ModifyBillInstr

2.4.1.UP-ModifyBillInstr-Req-Full-MSG.xsd

MODIFYBILLINSTR_FSFS_REQ

ORACLE®

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Bill-Instruct-Full

INSTRCTNO

CUSTID

UPTYPE

PROVDID

PRM1VAL

PRM2VAL

PRM3VAL

PRM4VAL

ORACLE®

PRM5VAL
PAYMOD
PAYAMNT
PAYCCY
DBTBRN
DBTACC
FRSTEXEDT
EXEFRQ
EXERETRYCNT
RETRYMOD
LSTEXEDT
NXTEXEDT
BRANCD
UPTYPDSC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Exec-Log
EXECDT
PAYMOD
PAYAMNT
PAYCCY
DBTBRN
DBTACC
MAXRYCNT
ACBILAMT
STAT
Exec-Logdtl

COUNT

PDBILAMT

STAT

ERRCD

MESSAGE

Display

UDFDETAILS

FLDNAM

FLDVAL

MODIFYBILLINSTR_FSFS_REQ

Attribute	Description
Name	MODIFYBILLINSTR_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>12</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description
Name	BRANCH

Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description	This is the user id in the Source system who is performing the action.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description	This is the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>8</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	8						
pattern	[A-Z_0-9]*						

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr> </tbody> </table>	Restrictions	Description	enumeration	SUCCESS,WARNING,FAILURE
Restrictions	Description				
enumeration	SUCCESS,WARNING,FAILURE				

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	128	
	pattern	[a-zA-Z_0-9=+/-]*	

ADDL

Attribute	Description					
Name	ADDL					
Datatype						
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

PARAM

Attribute	Description							
Name	PARAM							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Bill-Instruct-Full

Attribute	Description	
Name	Bill-Instruct-Full	
Datatype		
Description		

INSTRCTNO

Attribute	Description				
Name	INSTRCTNO				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>16</td></tr></tbody></table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

CUSTID

Attribute	Description				
Name	CUSTID				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

UPTYPE

Attribute	Description				
Name	UPTYPE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

PROVIDID

Attribute	Description				
Name	PROVIDID				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

PRM1VAL

Attribute	Description				
Name	PRM1VAL				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>50</td></tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

PRM2VAL

Attribute	Description				
Name	PRM2VAL				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

PRM3VAL

Attribute	Description				
Name	PRM3VAL				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

PRM4VAL

Attribute	Description				
Name	PRM4VAL				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

PRM5VAL

Attribute	Description				
Name	PRM5VAL				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>50</td></tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

PAYMOD

Attribute	Description					
Name	PAYMOD					
Datatype	String					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>F,P</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	F,P
Restrictions	Description					
enumeration	F,P					

PAYAMNT

Attribute	Description					
Name	PAYAMNT					
Datatype	Decimal					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>		Restrictions	Description	totalDigits	22
Restrictions	Description					
totalDigits	22					

PAYCCY

Attribute	Description					
Name	PAYCCY					
Datatype	String					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	3
Restrictions	Description					
maxLength	3					

DBTBRN

Attribute	Description					
Name	DBTBRN					
Datatype	String					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	3
Restrictions	Description					
maxLength	3					

DBTACC

Attribute	Description	
-----------	-------------	--

Name	DBTACC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

FRSTEXEDT

Attribute	Description	
Name	FRSTEXEDT	
Datatype	String	
Description		

EXEFRQ

Attribute	Description	
Name	EXEFRQ	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	M,Q,H,Y

EXERETRYCNT

Attribute	Description	
Name	EXERETRYCNT	
Datatype	Decimal	
Description		
Restrictions		
	Restrictions	Description
	totalDigits	22
	maxInclusive	99

RETRYMOD

Attribute	Description	
Name	RETRYMOD	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	P,F

LSTEXEDT

Attribute	Description	
Name	LSTEXEDT	
Datatype	String	
Description		

NXTEXEDT

Attribute	Description	
Name	NXTEXEDT	

Datatype	String					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					

BRANCD

Attribute	Description					
Name	BRANCD					
Datatype	String					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3	
Restrictions	Description					
maxLength	3					

UPTYPDSC

Attribute	Description					
Name	UPTYPDSC					
Datatype	String					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>105</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	105	
Restrictions	Description					
maxLength	105					

MAKER

Attribute	Description					
Name	MAKER					
Datatype	String					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12	
Restrictions	Description					
maxLength	12					

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		

Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
	Name	CHECKER
Datatype	String	
	Description	
Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
	Name	CHECKERSTAMP
Datatype	String	
	Description	
Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
	Name	MODNO
Datatype	Decimal	
	Description	
Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
	Name	TXNSTAT
Datatype	String	
	Description	

Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	1

AUTHSTAT

Attribute	Description	
	Name	AUTHSTAT
Datatype		
	String	
Description		
	Attribute	Description
Attribute	minOccurs	0
	Restrictions	Description
Restrictions	maxLength	1

Exec-Log

Attribute	Description	
	Name	Exec-Log
Datatype		
	String	
Description		
	Attribute	Description
Attribute	minOccurs	0
	maxOccurs	unbounded

EXECDT

Attribute	Description	
	Name	EXECDT
Datatype		
	String	
Description		
	Attribute	Description
Attribute	minOccurs	0

PAYMOD

Attribute	Description	
	Name	PAYMOD
Datatype		
	String	
Description		
	Attribute	Description
Attribute	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

PAYAMNT

Attribute	Description				
Name	PAYAMNT				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

PAYCCY

Attribute	Description				
Name	PAYCCY				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

DBTBRN

Attribute	Description				
Name	DBTBRN				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

DBTACC

Attribute	Description				
Name	DBTACC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

MAXRYCNT

Attribute	Description				
Name	MAXRYCNT				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

ACBILAMT

Attribute	Description				
Name	ACBILAMT				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

STAT

Attribute	Description				
Name	STAT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>P,S,F,U</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	P,S,F,U
Restrictions	Description				
enumeration	P,S,F,U				

Exec-Logdtl

Attribute	Description						
Name	Exec-Logdtl						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

COUNT

Attribute	Description				
Name	COUNT				
Datatype	Decimal				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

PDBILAMT

Attribute	Description				
Name	PDBILAMT				
Datatype	Decimal				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

STAT

Attribute	Description				
Name	STAT				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

ERRCD

Attribute	Description				
Name	ERRCD				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1000</td></tr></tbody></table>	Restrictions	Description	maxLength	1000
Restrictions	Description				
maxLength	1000				

MESSAGE

Attribute	Description				
Name	MESSAGE				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1000</td></tr> </tbody> </table>	Restrictions	Description	maxLength	1000
Restrictions	Description				
maxLength	1000				

Display

Attribute	Description				
Name	Display				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

UDFDETAILS

Attribute	Description						
Name	UDFDETAILS						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

FLDNAM

Attribute	Description						
Name	FLDNAM						
Datatype	String						
Description	Indicates Field Name						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	105	minLength	1
Restrictions	Description						
maxLength	105						
minLength	1						

FLDVAL

Attribute	Description				
Name	FLDVAL				
Datatype	String				
Description	Indicates Field Value				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	Restrictions	Description
	maxLength	150
	minLength	0

2.4.2.UP-ModifyBillInstr-Req-IO-MSG.xsd

MODIFYBILLINSTR_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Bill-Instruct-IO

INSTRCTNO

PRM1VAL

PRM2VAL

ORACLE®

PRM3VAL
PRM4VAL
PRM5VAL
PAYMOD
PAYAMNT
PAYCCY
DBTBRN
DBTACC
EXERETRYCNT
LSTEXEDT
MAKER
MAKERSTAMP
Exec-Log
STAT
UDFDETAILS
FLDNAM
FLDVAL

MODIFYBILLINSTR_IOPK_REQ

Attribute	Description
Name	MODIFYBILLINSTR_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description
Name	USERID

Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute	Attribute		Description
	nillable	true	
Restrictions	Restrictions		Description
	pattern	[a-zA-Z_0-9]*	

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	

Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>8</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	8						
pattern	[A-Z_0-9]*						

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	enumeration	SUCCESS,WARNING,FAILURE	

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	

Description	
-------------	--

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Bill-Instruct-IO

Attribute	Description
Name	Bill-Instruct-IO
Datatype	
Description	

INSTRCTNO

Attribute	Description
Name	INSTRCTNO
Datatype	String
Description	
Attribute	
Attribute	Description
minOccurs	0
Restrictions	
Restrictions	Description
maxLength	16

PRM1VAL

Attribute	Description
Name	PRM1VAL
Datatype	String
Description	
Attribute	
Attribute	Description
minOccurs	0
Restrictions	
Restrictions	Description
maxLength	50

PRM2VAL

Attribute	Description
Name	PRM2VAL
Datatype	String
Description	
Attribute	
Attribute	Description
minOccurs	0
Restrictions	
Restrictions	Description
maxLength	50

PRM3VAL

Attribute	Description				
Name	PRM3VAL				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

PRM4VAL

Attribute	Description				
Name	PRM4VAL				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

PRM5VAL

Attribute	Description				
Name	PRM5VAL				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

PAYMOD

Attribute	Description				
Name	PAYMOD				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>F,P</td></tr></tbody></table>	Restrictions	Description	enumeration	F,P
Restrictions	Description				
enumeration	F,P				

PAYAMNT

Attribute	Description				
Name	PAYAMNT				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

PAYCCY

Attribute	Description				
Name	PAYCCY				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

DBTBRN

Attribute	Description				
Name	DBTBRN				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

DBTACC

Attribute	Description				
Name	DBTACC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

EXERETRYCNT

ORACLE®

Attribute	Description						
Name	EXERETRYCNT						
Datatype	Decimal						
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> <tr> <td>maxInclusive</td><td>99</td></tr> </tbody> </table>	Restrictions	Description	totalDigits	22	maxInclusive	99
Restrictions	Description						
totalDigits	22						
maxInclusive	99						

LSTEXEDT

Attribute	Description				
Name	LSTEXEDT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>12</td></tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MAKERSTAMP

Attribute	Description				
Name	MAKERSTAMP				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>35</td></tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

Exec-Log

Attribute	Description
Name	Exec-Log
Datatype	

Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

STAT

Attribute	Description	
Name	STAT	
Datatype	String	
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	enumeration	P,S,F,U

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description	Indicates Field Name	
Restrictions	Restrictions	
	Description	
	maxLength	105
	minLength	1

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attribute	Attribute	
	Description	
	minOccurs	0
Restrictions	Restrictions	
	Description	
	maxLength	150
	minLength	0

2.4.3.UP-ModifyBillInstr-Res-Full-MSG.xsd

MODIFYBILLINSTR_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Bill-Instruct-Full

INSTRCTNO

CUSTID

UPTYPE

PROVDID

PRM1VAL

PRM2VAL

PRM3VAL

ORACLE®

PRM4VAL
PRM5VAL
PAYMOD
PAYAMNT
PAYCCY
DBTBRN
DBTACC
FRSTEXEDT
EXEFRQ
EXERETRYCNT
RETRYMOD
LSTEXEDT
NXTTEXEDT
BRANCD
UPTYPDSC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Exec-Log

EXECDT
PAYMOD
PAYAMNT
PAYCCY
DBTBRN
DBTACC
MAXRYCNT
ACBILAMT
STAT

Exec-Logdtl
COUNT
PDBILAMT
STAT
ERRCD
MESSAGE
Display
UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
E CODE
EDESC
FCUBS_WARNING_RESP
WARNING
W CODE
WDESC

MODIFYBILLINSTR_FSFS_RES

Attribute	Description
Name	MODIFYBILLINSTR_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td></tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description							
Name	USERID							
Datatype	String							
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description							
maxLength	12							
pattern	[A-Z_0-9]*							

BRANCH

Attribute	Description							
Name	BRANCH							
Datatype	String							
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>		Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description							
length	3							
pattern	[a-zA-Z_0-9]{3}							

MODULEID

Attribute	Description					
Name	MODULEID					
Datatype	String					
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

SERVICE

Attribute	Description					
Name	SERVICE					
Datatype	String					
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		Attribute	Description	nillable	true
Attribute	Description					
nillable	true					

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description					
Name	OPERATION					
Datatype	String					
Description	This is the operation of the service which is being invoked. This field is case-sensitive.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		Attribute	Description	nillable	true
Attribute	Description					
nillable	true					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

SOURCE_OPERATION

Attribute	Description					
Name	SOURCE_OPERATION					
Datatype	String					
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

SOURCE_USERID

Attribute	Description					
Name	SOURCE_USERID					
Datatype	String					
Description	This is the user id in the Source system who is performing the action.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This is the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	pattern	[a-zA-Z_0-9]*	

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MSGSTAT

Attribute	Description					
Name	MSGSTAT					
Datatype	String					
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>SUCCESS,WARNING,FAILURE</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	SUCCESS,WARNING,FAILURE
Restrictions	Description					
enumeration	SUCCESS,WARNING,FAILURE					

PASSWORD

Attribute	Description							
Name	PASSWORD							
Datatype	String							
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>128</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9+=/]*</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	128	pattern	[a-zA-Z_0-9+=/]*
Restrictions	Description							
maxLength	128							
pattern	[a-zA-Z_0-9+=/]*							

ADDL

Attribute	Description					
Name	ADDL					
Datatype						
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

PARAM

Attribute	Description							
Name	PARAM							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Bill-Instruct-Full

Attribute	Description
Name	Bill-Instruct-Full
Datatype	
Description	

INSTRCTNO

Attribute	Description		
Name	INSTRCTNO		
Datatype	String		
Description			
Attribute			
	Attribute	Description	
	minOccurs	0	
Restrictions		Restrictions	Description
		maxLength	16

CUSTID

Attribute	Description	
Name	CUSTID	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	9

UPTYPE

Attribute	Description
Name	UPTYPE
Datatype	String
Description	

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>35</td></tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

PROVIDID

Attribute	Description				
Name	PROVIDID				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

PRM1VAL

Attribute	Description				
Name	PRM1VAL				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

PRM2VAL

Attribute	Description				
Name	PRM2VAL				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

PRM3VAL

Attribute	Description				
Name	PRM3VAL				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

PRM4VAL

Attribute	Description				
Name	PRM4VAL				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

PRM5VAL

Attribute	Description				
Name	PRM5VAL				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

PAYMOD

Attribute	Description				
Name	PAYMOD				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>F,P</td></tr></tbody></table>	Restrictions	Description	enumeration	F,P
Restrictions	Description				
enumeration	F,P				

PAYAMNT

Attribute	Description				
Name	PAYAMNT				
Datatype	Decimal				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

PAYCCY

Attribute	Description
Name	PAYCCY

Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	3

DBTBRN

Attribute	Description	
Name	DBTBRN	
Datatype	String	
Description		
Restrictions	Restrictions	
	maxLength	3

DBTACC

Attribute	Description	
Name	DBTACC	
Datatype	String	
Description		
Restrictions	Restrictions	
	maxLength	20

FRSTEXEDT

Attribute	Description	
Name	FRSTEXEDT	
Datatype	String	
Description		

EXEFRQ

Attribute	Description	
Name	EXEFRQ	
Datatype	String	
Description		
Restrictions	Restrictions	
	enumeration	M,Q,H,Y

EXERETRYCNT

Attribute	Description	
Name	EXERETRYCNT	
Datatype	Decimal	
Description		

Restrictions	
	Restrictions
	totalDigits
	99

RETRYMOD

Attribute	Description
Name	RETRYMOD
Datatype	String
Description	
Restrictions	
	Restrictions
	enumeration
	P,F

LSTEXEDT

Attribute	Description
Name	LSTEXEDT
Datatype	String
Description	

NXTEXEDT

Attribute	Description
Name	NXTEXEDT
Datatype	String
Description	
Attribute	
	Attribute
	minOccurs
	0

BRANCD

Attribute	Description
Name	BRANCD
Datatype	String
Description	
Attribute	
	Attribute
	minOccurs
	0
Restrictions	
	Restrictions
	maxLength
	3

UPTYPDSC

Attribute	Description
Name	UPTYPDSC
Datatype	String
Description	
Attribute	
	Attribute
	minOccurs
	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> </tbody> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MAKERSTAMP

Attribute	Description				
Name	MAKERSTAMP				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

CHECKER

Attribute	Description				
Name	CHECKER				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

CHECKERSTAMP

Attribute	Description				
Name	CHECKERSTAMP				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>35</td></tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

MODNO

Attribute	Description				
Name	MODNO				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>4</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	4
Restrictions	Description				
totalDigits	4				

TXNSTAT

Attribute	Description				
Name	TXNSTAT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

AUTHSTAT

Attribute	Description				
Name	AUTHSTAT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

Exec-Log

Attribute	Description						
Name	Exec-Log						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

EXECDT

Attribute	Description				
Name	EXECDT				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PAYMOD

Attribute	Description				
Name	PAYMOD				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

PAYAMNT

Attribute	Description				
Name	PAYAMNT				
Datatype	Decimal				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

PAYCCY

Attribute	Description				
Name	PAYCCY				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

DBTBRN

Attribute	Description
Name	DBTBRN

Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	3

DBTACC

Attribute	Description	
Name	DBTACC	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	20

MAXRYCNT

Attribute	Description	
Name	MAXRYCNT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	totalDigits	22

ACBILAMT

Attribute	Description	
Name	ACBILAMT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	totalDigits	22

STAT

Attribute	Description	
Name	STAT	

Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	enumeration	P,S,F,U

Exec-Logdtl

Attribute	Description	
Name	Exec-Logdtl	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

COUNT

Attribute	Description	
Name	COUNT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

PDBILAMT

Attribute	Description	
Name	PDBILAMT	
Datatype	Decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

STAT

Attribute	Description	
Name	STAT	
Datatype	String	
Description		

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	1	

ERRCD

Attribute	Description	
Name	ERRCD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	1000

MESSAGE

Attribute	Description	
Name	MESSAGE	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	1000

Display

Attribute	Description	
Name	Display	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

FLDNAM

Attribute	Description						
Name	FLDNAM						
Datatype	String						
Description	Indicates Field Name						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	105	minLength	1
Restrictions	Description						
maxLength	105						
minLength	1						

FLDVAL

Attribute	Description						
Name	FLDVAL						
Datatype	String						
Description	Indicates Field Value						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>150</td></tr><tr><td>minLength</td><td>0</td></tr></tbody></table>	Restrictions	Description	maxLength	150	minLength	0
Restrictions	Description						
maxLength	150						
minLength	0						

FCUBS_ERROR_RESP

Attribute	Description						
Name	FCUBS_ERROR_RESP						
Datatype							
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

ECODE

Attribute	Description
Name	EDESC
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.4.4.UP-ModifyBillInstr-Res-PK-MSG.xsd

MODIFYBILLINSTR_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

ORACLE®

SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Bill-Instruct-PK
INSTRCTNO
Bill-Instruct-IO
INSTRCTNO
PRM1VAL
PRM2VAL
PRM3VAL
PRM4VAL
PRM5VAL
PAYMOD
PAYAMNT
PAYCCY
DBTBRN
DBTACC
EXERETRYCNT
LSTEXEDT
MAKER

MAKERSTAMP

Exec-Log

STAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

MODIFYBILLINSTR_IOPK_RES

Attribute	Description
Name	MODIFYBILLINSTR_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description					
enumeration	FCUBS,FCIS					

MSGID

Attribute	Description					
Name	MSGID					
Datatype	String					
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	String					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>12</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description							
Name	BRANCH							
Datatype	String							
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>		Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description							
length	3							
pattern	[a-zA-Z_0-9]{3}							

MODULEID

Attribute	Description					
Name	MODULEID					
Datatype	String					
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

SERVICE

Attribute	Description					
Name	SERVICE					
Datatype	String					
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		Attribute	Description	nillable	true
Attribute	Description					
nillable	true					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

OPERATION

Attribute	Description					
Name	OPERATION					
Datatype	String					
Description	This is the operation of the service which is being invoked. This field is case-sensitive.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		Attribute	Description	nillable	true
Attribute	Description					
nillable	true					

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description					
Name	SOURCE_OPERATION					
Datatype	String					
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

SOURCE_USERID

Attribute	Description					
Name	SOURCE_USERID					
Datatype	String					
Description	This is the user id in the Source system who is performing the action.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

DESTINATION

Attribute	Description					
Name	DESTINATION					
Datatype	String					
Description	This is the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	pattern	[a-zA-Z_0-9]*	

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description						
Name	PASSWORD						
Datatype	String						
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/*]</td></tr></tbody></table>	Restrictions	Description	maxLength	128	pattern	[a-zA-Z_0-9=+/*]
Restrictions	Description						
maxLength	128						
pattern	[a-zA-Z_0-9=+/*]						

ADDL

Attribute	Description				
Name	ADDL				
Datatype					
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Bill-Instruct-PK
Datatype	
Description	

INSTRCTNO

Attribute	Description				
Name	INSTRCTNO				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>16</td></tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

Bill-Instruct-IO

Attribute	Description
Name	Bill-Instruct-IO
Datatype	
Description	

INSTRCTNO

Attribute	Description				
Name	INSTRCTNO				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>16</td></tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

PRM1VAL

Attribute	Description				
Name	PRM1VAL				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>50</td></tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

PRM2VAL

Attribute	Description
------------------	--------------------

Name	PRM2VAL					
Datatype	String					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>50</td></tr> </tbody> </table>		Restrictions	Description	maxLength	50
Restrictions	Description					
maxLength	50					

PRM3VAL

Attribute	Description					
Name	PRM3VAL					
Datatype	String					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>50</td></tr> </tbody> </table>		Restrictions	Description	maxLength	50
Restrictions	Description					
maxLength	50					

PRM4VAL

Attribute	Description					
Name	PRM4VAL					
Datatype	String					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>50</td></tr> </tbody> </table>		Restrictions	Description	maxLength	50
Restrictions	Description					
maxLength	50					

PRM5VAL

Attribute	Description					
Name	PRM5VAL					
Datatype	String					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>50</td></tr> </tbody> </table>		Restrictions	Description	maxLength	50
Restrictions	Description					
maxLength	50					

PAYMOD

Attribute	Description	

Name	PAYMOD					
Datatype	String					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>F,P</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	F,P
Restrictions	Description					
enumeration	F,P					

PAYAMNT

Attribute	Description					
Name	PAYAMNT					
Datatype	Decimal					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>		Restrictions	Description	totalDigits	22
Restrictions	Description					
totalDigits	22					

PAYCCY

Attribute	Description					
Name	PAYCCY					
Datatype	String					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	3
Restrictions	Description					
maxLength	3					

DBTBRN

Attribute	Description					
Name	DBTBRN					
Datatype	String					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	3
Restrictions	Description					
maxLength	3					

DBTACC

Attribute	Description	

Name	DBTACC					
Datatype	String					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>	Restrictions	Description	maxLength	20	
Restrictions	Description					
maxLength	20					

EXERETRYCNT

Attribute	Description							
Name	EXERETRYCNT							
Datatype	Decimal							
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0			
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> <tr> <td>maxInclusive</td><td>99</td></tr> </tbody> </table>	Restrictions	Description	totalDigits	22	maxInclusive	99	
Restrictions	Description							
totalDigits	22							
maxInclusive	99							

LSTEXEDT

Attribute	Description					
Name	LSTEXEDT					
Datatype	String					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					

MAKER

Attribute	Description					
Name	MAKER					
Datatype	String					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>12</td></tr> </tbody> </table>	Restrictions	Description	maxLength	12	
Restrictions	Description					
maxLength	12					

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	35	

Exec-Log

Attribute	Description							
Name	Exec-Log							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

STAT

Attribute	Description					
Name	STAT					
Datatype	String					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>P,S,F,U</td></tr> </tbody> </table>		Restrictions	Description	enumeration	P,S,F,U
Restrictions	Description					
enumeration	P,S,F,U					

UDFDETAILS

Attribute	Description							
Name	UDFDETAILS							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

FLDNAM

Attribute	Description							
Name	FLDNAM							
Datatype	String							
Description	Indicates Field Name							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>		Restrictions	Description	maxLength	105	minLength	1
Restrictions	Description							
maxLength	105							
minLength	1							

FLDVAL

Attribute	Description						
Name	FLDVAL						
Datatype	String						
Description	Indicates Field Value						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>150</td></tr> <tr> <td>minLength</td><td>0</td></tr> </tbody> </table>	Restrictions	Description	maxLength	150	minLength	0
Restrictions	Description						
maxLength	150						
minLength	0						

FCUBS_ERROR_RESP

Attribute	Description						
Name	FCUBS_ERROR_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attribute	
Attribute	Description
minOccurs	0
maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.5.QueryBillInstr

2.5.1.UP-QueryBillInstr-Req-IO-MSG.xsd

QUERYBILLINSTR_IOFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

ORACLE®

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Bill-Instruct-IO

INSTRCTNO

QUERYBILLINSTR_IOFS_REQ

Attribute	Description
Name	QUERYBILLINSTR_IOFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

ORACLE®

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description	This is the user id in the Source system who is performing the action.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description	This is the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>8</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	8						
pattern	[A-Z_0-9]*						

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>SUCCESS,WARNING,FAILURE</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	SUCCESS,WARNING,FAILURE
Restrictions	Description				
enumeration	SUCCESS,WARNING,FAILURE				

PASSWORD

Attribute	Description
------------------	--------------------

ORACLE®

Name	PASSWORD							
Datatype	String							
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>128</td></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9=+/-]*</td></tr> </tbody> </table>		Restrictions	Description	maxLength	128	pattern	[a-zA-Z_0-9=+/-]*
Restrictions	Description							
maxLength	128							
pattern	[a-zA-Z_0-9=+/-]*							

ADDL

Attribute	Description					
Name	ADDL					
Datatype						
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

PARAM

Attribute	Description							
Name	PARAM							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Bill-Instruct-IO

Attribute	Description	

ORACLE®

Name	Bill-Instruct-IO
Datatype	
Description	

INSTRCTNO

Attribute	Description					
Name	INSTRCTNO					
Datatype	String					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>16</td></tr> </tbody> </table>	Restrictions	Description	maxLength	16	
Restrictions	Description					
maxLength	16					

2.5.2.*UP-QueryBillInstr-Res-Full-MSG.xsd*

QUERYBILLINSTR_IOFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE
FCUBS_BODY
Bill-Instruct-IO
INSTRCTNO
Bill-Instruct-Full
INSTRCTNO
CUSTID
UPTYPE
PROVDIR
PRM1VAL
PRM2VAL
PRM3VAL
PRM4VAL
PRM5VAL
PAYMOD
PAYAMNT
PAYCCY
DBTBRN
DBTACC
FRSTEXEDT
EXEFRQ
EXERETRYCNT
RETRYMOD
LSTEXEDT
NXTEXEDT
BRANCD
UPTYPDSC
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO

TXNSTAT

AUTHSTAT

Exec-Log

EXECDT

PAYMOD

PAYAMNT

PAYCCY

DBTBRN

DBTACC

MAXRYCNT

ACBILAMT

STAT

Exec-Logdtl

COUNT

PDBILAMT

STAT

ERRCD

MESSAGE

Display

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

QUERYBILLINSTR_IOFS_RES

Attribute	Description
-----------	-------------

Name	QUERYBILLINSTR_IOFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

ORACLE®

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>12</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	

Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This is the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr> </tbody> </table>	Restrictions	Description	enumeration	SUCCESS,WARNING,FAILURE
Restrictions	Description				
enumeration	SUCCESS,WARNING,FAILURE				

PASSWORD

Attribute	Description						
Name	PASSWORD						
Datatype	String						
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>128</td></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9=+/*]</td></tr> </tbody> </table>	Restrictions	Description	maxLength	128	pattern	[a-zA-Z_0-9=+/*]
Restrictions	Description						
maxLength	128						
pattern	[a-zA-Z_0-9=+/*]						

ADDL

Attribute	Description				
Name	ADDL				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

ORACLE®

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Bill-Instruct-IO

Attribute	Description
Name	Bill-Instruct-IO
Datatype	
Description	

INSTRCTNO

Attribute	Description				
Name	INSTRCTNO				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>16</td></tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

Bill-Instruct-Full

Attribute	Description
Name	Bill-Instruct-Full
Datatype	
Description	

INSTRCTNO

Attribute	Description				
Name	INSTRCTNO				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>16</td></tr></tbody></table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

CUSTID

Attribute	Description				
Name	CUSTID				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr></tbody></table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

UPTYPE

Attribute	Description				
Name	UPTYPE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

PROVIDID

Attribute	Description				
Name	PROVIDID				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

PRM1VAL

Attribute	Description				
Name	PRM1VAL				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>50</td></tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

PRM2VAL

Attribute	Description				
Name	PRM2VAL				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

PRM3VAL

Attribute	Description				
Name	PRM3VAL				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

PRM4VAL

Attribute	Description				
Name	PRM4VAL				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

PRM5VAL

Attribute	Description				
Name	PRM5VAL				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>50</td></tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

PAYMOD

Attribute	Description					
Name	PAYMOD					
Datatype	String					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>F,P</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	F,P
Restrictions	Description					
enumeration	F,P					

PAYAMNT

Attribute	Description					
Name	PAYAMNT					
Datatype	Decimal					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>		Restrictions	Description	totalDigits	22
Restrictions	Description					
totalDigits	22					

PAYCCY

Attribute	Description					
Name	PAYCCY					
Datatype	String					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	3
Restrictions	Description					
maxLength	3					

DBTBRN

Attribute	Description					
Name	DBTBRN					
Datatype	String					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	3
Restrictions	Description					
maxLength	3					

DBTACC

Attribute	Description	
-----------	-------------	--

Name	DBTACC	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	maxLength	20

FRSTEXEDT

Attribute	Description	
Name	FRSTEXEDT	
Datatype	String	
Description		

EXEFRQ

Attribute	Description	
Name	EXEFRQ	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	M,Q,H,Y

EXERETRYCNT

Attribute	Description	
Name	EXERETRYCNT	
Datatype	Decimal	
Description		
Restrictions		
	Restrictions	Description
	totalDigits	22
	maxInclusive	99

RETRYMOD

Attribute	Description	
Name	RETRYMOD	
Datatype	String	
Description		
Restrictions		
	Restrictions	Description
	enumeration	P,F

LSTEXEDT

Attribute	Description	
Name	LSTEXEDT	
Datatype	String	
Description		

NXTEXEDT

Attribute	Description	
Name	NXTEXEDT	

ORACLE®

Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

BRANCD

Attribute	Description	
Name	BRANCD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

UPTYPDSC

Attribute	Description	
Name	UPTYPDSC	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		

Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	35

CHECKER

Attribute	Description	
	Name	CHECKER
Datatype	String	
	Description	
Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
	Name	CHECKERSTAMP
Datatype	String	
	Description	
Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	maxLength	35

MODNO

Attribute	Description	
	Name	MODNO
Datatype	Decimal	
	Description	
Attribute		
	Attribute	Description
Restrictions	minOccurs	0
	Restrictions	Description
	totalDigits	4

TXNSTAT

Attribute	Description	
	Name	TXNSTAT
Datatype	String	
	Description	

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	1	

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	1

Exec-Log

Attribute	Description	
Name	Exec-Log	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

EXECDT

Attribute	Description	
Name	EXECDT	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

PAYMOD

Attribute	Description	
Name	PAYMOD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

PAYAMNT

Attribute	Description				
Name	PAYAMNT				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

PAYCCY

Attribute	Description				
Name	PAYCCY				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

DBTBRN

Attribute	Description				
Name	DBTBRN				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

DBTACC

Attribute	Description				
Name	DBTACC				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

MAXRYCNT

Attribute	Description				
Name	MAXRYCNT				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

ACBILAMT

Attribute	Description				
Name	ACBILAMT				
Datatype	Decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

STAT

Attribute	Description				
Name	STAT				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>P,S,F,U</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	P,S,F,U
Restrictions	Description				
enumeration	P,S,F,U				

Exec-Logdtl

Attribute	Description						
Name	Exec-Logdtl						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

COUNT

Attribute	Description				
Name	COUNT				
Datatype	Decimal				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

PDBILAMT

Attribute	Description				
Name	PDBILAMT				
Datatype	Decimal				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

STAT

Attribute	Description				
Name	STAT				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

ERRCD

Attribute	Description				
Name	ERRCD				
Datatype	String				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1000</td></tr></tbody></table>	Restrictions	Description	maxLength	1000
Restrictions	Description				
maxLength	1000				

MESSAGE

Attribute	Description				
Name	MESSAGE				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1000</td></tr> </tbody> </table>	Restrictions	Description	maxLength	1000
Restrictions	Description				
maxLength	1000				

Display

Attribute	Description				
Name	Display				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

UDFDETAILS

Attribute	Description						
Name	UDFDETAILS						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

FLDNAM

Attribute	Description						
Name	FLDNAM						
Datatype	String						
Description	Indicates Field Name						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	105	minLength	1
Restrictions	Description						
maxLength	105						
minLength	1						

FLDVAL

Attribute	Description				
Name	FLDVAL				
Datatype	String				
Description	Indicates Field Value				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>150</td></tr> <tr> <td>minLength</td><td>0</td></tr> </tbody> </table>	Restrictions	Description	maxLength	150	minLength	0
Restrictions	Description						
maxLength	150						
minLength	0						

FCUBS_ERROR_RESP

Attribute	Description							
Name	FCUBS_ERROR_RESP							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

ERROR

Attribute	Description					
Name	ERROR					
Datatype						
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>		Attribute	Description	maxOccurs	unbounded
Attribute	Description					
maxOccurs	unbounded					

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

FCUBS_WARNING_RESP

Attribute	Description							
Name	FCUBS_WARNING_RESP							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

WARNING

Attribute	Description	
Name	WARNING	
Datatype		

Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.6.CreateUPTransaction

2.6.1.Utility-Payment-Create-Req-Full-MSG.xsd

CREATEUPTRANSACTION_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Transaction-Details

XREF

FCCREF

PRD

INSTID

BILLNO

BILLDT

BAMT

BCCY

CUSTACNO

ACCCY

CONSNO

NETAMT

RATECODE

TXNCCY

OFSACNO

OFSACBRN

OFSACCCY

TXNDATE

TXNBRN

RATETYPE

MAKERID

MAKERSTAMP

CHECKERID

CHECKERSTAMP

AUTHSTAT

CONTSTAT

MODNO

RECORDSTAT
ONCEAUTH
CUSTBRN
SERVICEID
NARRATIVE
INSTRNO
LCYTOTCHGAMT
TCYTOTCHGAMT
XRATE
CUST_ID
ACCTITLE
ACTAMT
DENMCCY1
DENMAMT1
DENMCCY2
DENMAMT2
CHGAMT1
CHGCCY1
CHGAMT2
CHGCCY2
CHGAMT3
CHGCCY3
CHGAMT4
CHGCCY4
CHGAMT5
CHGCCY5
SUBSYSTEMSTAT
Charge-Details
CHGCOMP
WAIVER
CHGAMT
CHGCCY

MISHEAD

TXNCODE

NETTINGIND

CHGGL

TYPE

LCYCHG

XRATE

TCYCHG

TCYXRATE

Denomination-Details

CDCCY

CDDENOM

VALUE

UNITS

INOUTIND

DENMVAL

Cheque-Details

SRNO

PAYBRN

CHQNO

STAT

EXPDT

BENFNAME

BENFADDR1

BENFADDR2

BENFADDR3

BENFADDR4

CRNO

ISB

OTHERDETLS1

OTHERDETLS1TYPE1

OTHERDETLS2

OTHERDETLTYPE2

OTHERDETLS3

OTHERDETLTYPE3

OTHERDETLS4

OTHERDETLTYPE4

OTHERDETLS5

OTHERDETLTYPE5

OTHERDETLS6

OTHERDETLTYPE6

Mis-Details

BRANCH

CUSTNO

MISGRP

REL_REF

REL_ACC

MISHD

POOLCD

REFRT

REFRTTYPE

REFXRT

CALCMETH

MISGRPTXN

REFRTCD

REFRTSPRD

FUNDMIS1

FUNDMIS2

FUNDMIS3

FUNDMIS4

FUNDMIS5

FUNDMIS6

FUNDMIS7

FUNDMIS8

FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10

FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10

COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10

TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Udf-Details

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

CREATEUPTRANSACTION_FSFS_REQ

Attribute	Description
Name	CREATEUPTRANSACTION_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	pattern	[a-zA-Z_0-9]*	

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description	This is the user id in the Source system who is performing the action.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	8	
		pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	128
		pattern
		[a-zA-Z_0-9=+/*]

Attribute	Description				
Name	ADDL				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Transaction-Details

Attribute	Description
Name	Transaction-Details
Datatype	
Description	

XREF

Attribute	Description				
Name	XREF				
Datatype	String				
Description	Indicates External Reference Number				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

FCCREF

Attribute	Description				
Name	FCCREF				
Datatype	String				
Description	Indicates the Reference Number of the External System. Note: This field is mandatory only in case where FCCREF is not available.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z0-9]{16}
Restrictions	Description				
pattern	[a-zA-Z0-9]{16}				

PRD

Attribute	Description						
Name	PRD						
Datatype	String						
Description	Indicates Product Code						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>4</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{4}</td></tr></tbody></table>	Restrictions	Description	maxLength	4	pattern	[a-zA-Z0-9]{4}
Restrictions	Description						
maxLength	4						
pattern	[a-zA-Z0-9]{4}						

INSTID

Attribute	Description				
Name	INSTID				
Datatype	String				
Description	Indicates Instrument Number				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

BILLNO

Attribute	Description				
Name	BILLNO				
Datatype	String				
Description	Indicates Bill Number				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

BILLDT

Attribute	Description
Name	BILLDT
Datatype	Date
Description	Indicates Bill Date

BAMT

Attribute	Description
------------------	--------------------

Name	BAMT						
Datatype	Decimal						
Description	Indicates Bill Amount						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

BCCY

Attribute	Description							
Name	BCCY							
Datatype	String							
Description	Indicates Bill Currency							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[A-Z]{3}</td></tr> </tbody> </table>		Restrictions	Description	length	3	pattern	[A-Z]{3}
Restrictions	Description							
length	3							
pattern	[A-Z]{3}							

CUSTACNO

Attribute	Description							
Name	CUSTACNO							
Datatype	String							
Description	Indicates Customer Account Number							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> <tr> <td>pattern</td><td>[a-zA-Z0-9]*</td></tr> </tbody> </table>		Restrictions	Description	maxLength	20	pattern	[a-zA-Z0-9]*
Restrictions	Description							
maxLength	20							
pattern	[a-zA-Z0-9]*							

ACCCY

Attribute	Description							
Name	ACCCY							
Datatype	String							
Description	Indicates Account Currency							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[A-Z]{3}</td></tr> </tbody> </table>		Restrictions	Description	length	3	pattern	[A-Z]{3}
Restrictions	Description							
length	3							
pattern	[A-Z]{3}							

CONSNO

Attribute	Description	
Name	CONSNO	
Datatype	String	
Description	Indicates Consumer Serial Number	

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	35	

NETAMT

Attribute	Description	
Name	NETAMT	
Datatype	Decimal	
Description	Indicates Net Amount	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	fractionDigits	3
	totalDigits	22

RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Indicates Rate Code Type	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	10

TXNCCY

Attribute	Description	
Name	TXNCCY	
Datatype	String	
Description	Indicates Transaction currency	
Restrictions	Restrictions	
	length	3
	pattern	[A-Z]{3}

OF SAC NO

Attribute	Description	
Name	OF SAC NO	
Datatype	String	
Description	Indicates Offset Account Number	

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	20	
		pattern	[a-zA-Z0-9]*

OFACBRN

Attribute	Description	
Name	OFSACBRN	
Datatype	String	
Description	Indicates Offset Account Branch	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	length	3
		pattern
		[a-zA-Z_0-9]{3}

OFACCCY

Attribute	Description	
Name	OFSACCCY	
Datatype	String	
Description	This specifies the Offset Account Currency.	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	length	3
		pattern
		[A-Z]{3}

TXNDATE

Attribute	Description	
Name	TXNDATE	
Datatype	Date	
Description	Indicates Transaction date	

TXNBRN

Attribute	Description	
Name	TXNBRN	
Datatype	String	
Description	Indicates Transaction Branch	
Restrictions	Restrictions	
	length	3
		pattern
		[a-zA-Z_0-9]{3}

RATETYPE

Attribute	Description				
Name	RATETYPE				
Datatype	String				
Description	Indicates Rate Type				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

MAKERID

Attribute	Description				
Name	MAKERID				
Datatype	String				
Description	The User Id who has created\last modified the record.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MAKERSTAMP

Attribute	Description				
Name	MAKERSTAMP				
Datatype	String				
Description	Indicates Date and Stamp when the User has created\last modified the record.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

CHECKERID

Attribute	Description				
Name	CHECKERID				
Datatype	String				
Description	The User Id who has Authorized the creation\modificaion of the record				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

CHECKERSTAMP

Attribute	Description				
Name	CHECKERSTAMP				
Datatype	String				
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

AUTHSTAT

Attribute	Description				
Name	AUTHSTAT				
Datatype	String				
Description	Indicates Authorization Status A - Authorized U - Un Authorized				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>A,U</td></tr> </tbody> </table>	Restrictions	Description	enumeration	A,U
Restrictions	Description				
enumeration	A,U				

CONTSTAT

Attribute	Description				
Name	CONTSTAT				
Datatype	String				
Description	Indicates Contract Status				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

MODNO

Attribute	Description						
Name	MODNO						
Datatype	Decimal						
Description	Indicates Modification number i.e. the number of times the record has been modified.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>0</td></tr> <tr> <td>totalDigits</td><td>10</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	0	totalDigits	10
Restrictions	Description						
fractionDigits	0						
totalDigits	10						

RECORDSTAT

Attribute	Description
------------------	--------------------

Name	RECORDSTAT					
Datatype	String					
Description	Indicates Record Status O - Open C - Close					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>O,C</td></tr> </tbody> </table>	Restrictions	Description	enumeration	O,C	
Restrictions	Description					
enumeration	O,C					

ONCEAUTH

Attribute	Description					
Name	ONCEAUTH					
Datatype	String					
Description	Indicates whether the record is Authorized atleast Once.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>Y,N</td></tr> </tbody> </table>	Restrictions	Description	enumeration	Y,N	
Restrictions	Description					
enumeration	Y,N					

CUSTBRN

Attribute	Description							
Name	CUSTBRN							
Datatype	String							
Description	Indicates Customer Branch							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0			
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}	
Restrictions	Description							
length	3							
pattern	[a-zA-Z_0-9]{3}							

SERVICEID

Attribute	Description					
Name	SERVICEID					
Datatype	String					
Description	Indicates Service Id					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>35</td></tr> </tbody> </table>	Restrictions	Description	maxLength	35	
Restrictions	Description					
maxLength	35					

NARRATIVE

Attribute	Description	
-----------	-------------	--

Name	NARRATIVE					
Datatype	String					
Description	Indicates Narrative					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>255</td></tr> </tbody> </table>	Restrictions	Description	maxLength	255	
Restrictions	Description					
maxLength	255					

INSTRNO

Attribute	Description					
Name	INSTRNO					
Datatype	String					
Description	Indicates Instrument Number					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>6</td></tr> </tbody> </table>	Restrictions	Description	maxLength	6	
Restrictions	Description					
maxLength	6					

LCYTOTCHGAMT

Attribute	Description							
Name	LCYTOTCHGAMT							
Datatype	Decimal							
Description	Indicates Total Charge in Local Currency.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0			
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22	
Restrictions	Description							
fractionDigits	3							
totalDigits	22							

TCYTOTCHGAMT

Attribute	Description							
Name	TCYTOTCHGAMT							
Datatype	Decimal							
Description	Indicates Total Charge in Transaction Currency.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0			
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22	
Restrictions	Description							
fractionDigits	3							
totalDigits	22							

XRATE

ORACLE®

Attribute	Description	
Name	XRATE	
Datatype	Decimal	
Description	Indicates Exchange rate	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

CUST_ID

Attribute	Description	
Name	CUST_ID	
Datatype	String	
Description	Indicates Customer Identification	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

ACCTITLE

Attribute	Description	
Name	ACCTITLE	
Datatype	String	
Description	Indicates Account Description	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

ACTAMT

Attribute	Description	
Name	ACTAMT	
Datatype	Decimal	
Description	Indicates Actual Amount	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

DENMCCY1

Attribute	Description						
Name	DENMCCY1						
Datatype	String						
Description	Indicates Denomination Currency						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[A-Z]{3}
Restrictions	Description						
length	3						
pattern	[A-Z]{3}						

DENMAMT1

Attribute	Description						
Name	DENMAMT1						
Datatype	Decimal						
Description	It indicates Denomination Amount						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

DENMCCY2

Attribute	Description						
Name	DENMCCY2						
Datatype	String						
Description	Indicates Denomination Currency						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[A-Z]{3}
Restrictions	Description						
length	3						
pattern	[A-Z]{3}						

DENMAMT2

Attribute	Description				
Name	DENMAMT2				
Datatype	Decimal				
Description	It indicates Denomination Amount				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

CHGAMT1

Attribute	Description						
Name	CHGAMT1						
Datatype	Decimal						
Description	Indicates Charge Amount						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>fractionDigits</td> <td>3</td> </tr> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

CHGCCY1

Attribute	Description						
Name	CHGCCY1						
Datatype	String						
Description	Indicates Charge Currency						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[A-Z]{3}</td> </tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[A-Z]{3}
Restrictions	Description						
length	3						
pattern	[A-Z]{3}						

CHGAMT2

Attribute	Description						
Name	CHGAMT2						
Datatype	Decimal						
Description	Indicates Charge Amount						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>fractionDigits</td> <td>3</td> </tr> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

CHGCCY2

Attribute	Description
Name	CHGCCY2
Datatype	String
Description	Indicates Charge Currency

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	length	3	
	pattern	[A-Z]{3}	

CHGAMT3

Attribute	Description	
Name	CHGAMT3	
Datatype	Decimal	
Description	Indicates Charge Amount	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	fractionDigits	3
	totalDigits	22

CHGCCY3

Attribute	Description	
Name	CHGCCY3	
Datatype	String	
Description	Indicates Charge Currency	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	length	3
	pattern	[A-Z]{3}

CHGAMT4

Attribute	Description	
Name	CHGAMT4	
Datatype	Decimal	
Description	Indicates Charge Amount	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	fractionDigits	3
	totalDigits	22

CHGCCY4

Attribute	Description	
------------------	--------------------	--

Name	CHGCCY4							
Datatype	String							
Description	Indicates Charge Currency							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0			
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[A-Z]{3}</td></tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[A-Z]{3}	
Restrictions	Description							
length	3							
pattern	[A-Z]{3}							

CHGAMT5

Attribute	Description							
Name	CHGAMT5							
Datatype	Decimal							
Description	Indicates Charge Amount							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0			
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22	
Restrictions	Description							
fractionDigits	3							
totalDigits	22							

CHGCCY5

Attribute	Description							
Name	CHGCCY5							
Datatype	String							
Description	Indicates Charge Currency							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0			
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[A-Z]{3}</td></tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[A-Z]{3}	
Restrictions	Description							
length	3							
pattern	[A-Z]{3}							

SUBSYSTEMSTAT

Attribute	Description					
Name	SUBSYSTEMSTAT					
Datatype	String					
Description	Indicates Subsystem Status					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> </tbody> </table>	Restrictions	Description	maxLength	105	
Restrictions	Description					
maxLength	105					

Attribute	Description						
Name	Charge-Details						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

CHGCOMP

Attribute	Description				
Name	CHGCOMP				
Datatype	String				
Description	Indicates Charge Components				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>255</td></tr> </tbody> </table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

WAIVER

Attribute	Description				
Name	WAIVER				
Datatype	String				
Description	Indicates Charge Waiver.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

CHGAMT

Attribute	Description						
Name	CHGAMT						
Datatype	Decimal						
Description	Indicates Charge Amount						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

CHGCCY

Attribute	Description

Name	CHGCCY					
Datatype	String					
Description	Indicates Charge Currency					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3	
Restrictions	Description					
maxLength	3					

MISHEAD

Attribute	Description					
Name	MISHEAD					
Datatype	String					
Description	Indicates MIS Head					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	
Restrictions	Description					
maxLength	9					

TXNCODE

Attribute	Description					
Name	TXNCODE					
Datatype	String					
Description	Indicates Transaction Code					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3	
Restrictions	Description					
maxLength	3					

NETTINGIND

Attribute	Description					
Name	NETTINGIND					
Datatype	String					
Description	Netting Index					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	1	
Restrictions	Description					
maxLength	1					

CHGGL

Attribute	Description	

Name	CHGGL					
Datatype	String					
Description	Charge General Ledger					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>	Restrictions	Description	maxLength	20	
Restrictions	Description					
maxLength	20					

TYPE

Attribute	Description					
Name	TYPE					
Datatype	String					
Description	Type					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	1	
Restrictions	Description					
maxLength	1					

LCYCHG

Attribute	Description							
Name	LCYCHG							
Datatype	Decimal							
Description	Indicates Charge in Local Currency							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0			
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22	
Restrictions	Description							
fractionDigits	3							
totalDigits	22							

XRATE

Attribute	Description							
Name	XRATE							
Datatype	Decimal							
Description	Indicates Exchange rate							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0			
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22	
Restrictions	Description							
fractionDigits	3							
totalDigits	22							

TCYCHG

ORACLE®

Attribute	Description						
Name	TCYCHG						
Datatype	Decimal						
Description	Charge In Transaction Currency						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

TCYXRATE

Attribute	Description						
Name	TCYXRATE						
Datatype	Decimal						
Description	Transaction Currency Exchange rate						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

Denomination-Details

Attribute	Description						
Name	Denomination-Details						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

CDCCY

Attribute	Description				
Name	CDCCY				
Datatype	String				
Description	Indicates Credit Currency				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

CDDENOM

Attribute	Description

Name	CDDENOM					
Datatype	String					
Description	Credit Denomination					
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>50</td></tr> </table>	Restrictions	Description	maxLength	50	
Restrictions	Description					
maxLength	50					

VALUE

Attribute	Description							
Name	VALUE							
Datatype	Decimal							
Description	Indicates Value							
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0			
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22	
Restrictions	Description							
fractionDigits	3							
totalDigits	22							

UNITS

Attribute	Description							
Name	UNITS							
Datatype	Decimal							
Description	Indicates Units							
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0			
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>fractionDigits</td><td>0</td></tr> <tr> <td>totalDigits</td><td>10</td></tr> </table>	Restrictions	Description	fractionDigits	0	totalDigits	10	
Restrictions	Description							
fractionDigits	0							
totalDigits	10							

INOUTIND

Attribute	Description					
Name	INOUTIND					
Datatype	String					
Description	IN OUT INDEX					
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>1</td></tr> </table>	Restrictions	Description	maxLength	1	
Restrictions	Description					
maxLength	1					

DENMVAL

ORACLE®

Attribute	Description						
Name	DENMVAL						
Datatype	Decimal						
Description	Indicates Denomination Value						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

Cheque-Details

Attribute	Description						
Name	Cheque-Details						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

SRNO

Attribute	Description				
Name	SRNO				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>16</td></tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

PAYBRN

Attribute	Description				
Name	PAYBRN				
Datatype	String				
Description	Indicates Payable Branch				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

CHQNO

Attribute	Description
Name	CHQNO

Datatype	String	
Description	Indicates Cheque Number	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	16

STAT

Attribute	Description	
Name	STAT	
Datatype	String	
Description	Status of Cheque	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	4

EXPDT

Attribute	Description	
Name	EXPDT	
Datatype	Date	
Description	Indicates Expected Date	

BENFNAME

Attribute	Description	
Name	BENFNAME	
Datatype	String	
Description	Indicates Beneficiary Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	105

BENFADDR1

Attribute	Description	
Name	BENFADDR1	
Datatype	String	
Description	Beneficiary address Line 1	
Attribute	Attribute	Description
	minOccurs	0

Restrictions					
	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>105</td></tr> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

BENFADDR2

Attribute	Description				
Name	BENFADDR2				
Datatype	String				
Description	Beneficiary address Line 2				
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>105</td></tr> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

BENFADDR3

Attribute	Description				
Name	BENFADDR3				
Datatype	String				
Description	Beneficiary address Line 3				
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>105</td></tr> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

BENFADDR4

Attribute	Description				
Name	BENFADDR4				
Datatype	String				
Description	Beneficiary address Line 4				
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>105</td></tr> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

CRNO

Attribute	Description				
Name	CRNO				
Datatype	String				
Description	Credit Number				
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>16</td></tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

ISB

Attribute	Description				
Name	ISB				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

OTHERDETLS1

Attribute	Description				
Name	OTHERDETLS1				
Datatype	String				
Description	Indicates Other Details 1				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLSTYPE1

Attribute	Description				
Name	OTHERDETLSTYPE1				
Datatype	String				
Description	Indicates Other Details Type 1				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLS2

Attribute	Description				
Name	OTHERDETLS2				
Datatype	String				
Description	Indicates Other Details 2				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>65</td></tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLSTYPE2

Attribute	Description					
Name	OTHERDETLSTYPE2					
Datatype	String					
Description	Indicates Other Details Type 1					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	65
Restrictions	Description					
maxLength	65					

OTHERDETLS3

Attribute	Description					
Name	OTHERDETLS3					
Datatype	String					
Description	Indicates Other Details 3					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	65
Restrictions	Description					
maxLength	65					

OTHERDETLSTYPE3

Attribute	Description					
Name	OTHERDETLSTYPE3					
Datatype	String					
Description	Indicates Other Details Type 3					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	65
Restrictions	Description					
maxLength	65					

OTHERDETLS4

Attribute	Description					
Name	OTHERDETLS4					
Datatype	String					
Description	Indicates Other Details 4					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>65</td></tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLSTYPE4

Attribute	Description					
Name	OTHERDETLSTYPE4					
Datatype	String					
Description	Indicates Other Details Type 4					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	65
Restrictions	Description					
maxLength	65					

OTHERDETLS5

Attribute	Description					
Name	OTHERDETLS5					
Datatype	String					
Description	Indicates Other Details 5					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	65
Restrictions	Description					
maxLength	65					

OTHERDETLSTYPE5

Attribute	Description					
Name	OTHERDETLSTYPE5					
Datatype	String					
Description	Indicates Other Details Type 5					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	65
Restrictions	Description					
maxLength	65					

OTHERDETLS6

Attribute	Description					
Name	OTHERDETLS6					
Datatype	String					
Description	Indicates Other Details 6					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>65</td></tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLSTYPE6

Attribute	Description				
Name	OTHERDETLSTYPE6				
Datatype	String				
Description	Indicates Other Details Type 6				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

Mis-Details

Attribute	Description						
Name	Mis-Details						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	Indicates Branch Code						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

CUSTNO

Attribute	Description				
Name	CUSTNO				
Datatype	String				
Description	Indicates Customer Number				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions							
	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

MISGRP

Attribute	Description						
Name	MISGRP						
Datatype	String						
Description	Indicates MIS Group						
Attribute							
	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions							
	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>12</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	12	minLength	1
Restrictions	Description						
maxLength	12						
minLength	1						

REL_REF

Attribute	Description						
Name	REL_REF						
Datatype	String						
Description	Indicates Related Reference Number						
Attribute							
	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions							
	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>16</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	16	minLength	1
Restrictions	Description						
maxLength	16						
minLength	1						

REL_ACC

Attribute	Description						
Name	REL_ACC						
Datatype	String						
Description	Indicates Related Account						
Attribute							
	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions							
	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>16</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	16	minLength	1
Restrictions	Description						
maxLength	16						
minLength	1						

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	

Attribute		
	Attribute	Description
	minOccurs	0

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description	Indicates Pool Code	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9
	minLength	1

REFRT

Attribute	Description	
Name	REFRT	
Datatype	Decimal	
Description	Indicates the Refinancing Rate	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	fractionDigits	15
	minInclusive	0
	totalDigits	26

REFRTTYPE

Attribute	Description	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

REFXRT

Attribute	Description	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	9	
		minLength	1

CALCMETH

Attribute	Description	
Name	CALCMETH	
Datatype	Integer	
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 : 6	
Attribute	Attribute	Description
	minOccurs	0

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

REFRTCD

Attribute	Description	
Name	REFRTCD	
Datatype	String	
Description	Indicates the Refinancing Rate Code	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	10

REFRTSPRD

Attribute	Description	
Name	REFRTSPRD	
Datatype	Decimal	
Description	Indicates the spread for the Refinance Rate Code	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>5</td></tr> <tr> <td>minInclusive</td><td>0</td></tr> <tr> <td>totalDigits</td><td>15</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	5	minInclusive	0	totalDigits	15
Restrictions	Description								
fractionDigits	5								
minInclusive	0								
totalDigits	15								

FUNDMIS1

Attribute	Description						
Name	FUNDMIS1						
Datatype	String						
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS2

Attribute	Description						
Name	FUNDMIS2						
Datatype	String						
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS3

Attribute	Description						
Name	FUNDMIS3						
Datatype	String						
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS4

Attribute	Description						
Name	FUNDMIS4						
Datatype	String						
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS5

Attribute	Description						
Name	FUNDMIS5						
Datatype	String						
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS6

Attribute	Description						
Name	FUNDMIS6						
Datatype	String						
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS7

Attribute	Description				
Name	FUNDMIS7				
Datatype	String				
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS8

Attribute	Description						
Name	FUNDMIS8						
Datatype	String						
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS9

Attribute	Description						
Name	FUNDMIS9						
Datatype	String						
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS10

Attribute	Description						
Name	FUNDMIS10						
Datatype	String						
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

MISGRPCOMP

Attribute	Description
-----------	--------------------

Name	MISGRPCOMP	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

COMPMIS2

Attribute	Description	
Name	COMPMIS2	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

COMPMIS3

Attribute	Description	
Name	COMPMIS3	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

COMPMIS4

Attribute	Description						
Name	COMPMIS4						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS5

Attribute	Description						
Name	COMPMIS5						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS6

Attribute	Description						
Name	COMPMIS6						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	9	
	minLength	1	

COMPMIS8

Attribute	Description	
Name	COMPMIS8	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

COMPMIS9

Attribute	Description	
Name	COMPMIS9	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

COMPMIS10

Attribute	Description	
Name	COMPMIS10	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

COSTCOD1

Attribute	Description						
Name	COSTCOD1						
Datatype	String						
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COSTCOD2

Attribute	Description						
Name	COSTCOD2						
Datatype	String						
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COSTCOD3

Attribute	Description						
Name	COSTCOD3						
Datatype	String						
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	9	
		minLength	1

COSTCOD5

Attribute	Description	
Name	COSTCOD5	
Datatype	String	
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
		minLength
		1

LINKGRP

Attribute	Description	
Name	LINKGRP	
Datatype	String	
Description	Indicates the Link To Group	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	12
		minLength
		1

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description	Indicates Currency	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	3

RTFLAG

Attribute	Description	
------------------	--------------------	--

Name	RTFLAG					
Datatype	String					
Description	Indicates the refinancing rate that should be used for the transaction					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1</td></tr> </tbody> </table>		Restrictions	Description	maxLength	1
Restrictions	Description					
maxLength	1					

PROCFLG

Attribute	Description					
Name	PROCFLG					
Datatype	String					
Description	Indicates ProcflgType R-Related Reference Number A-Related Account					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1</td></tr> </tbody> </table>		Restrictions	Description	maxLength	1
Restrictions	Description					
maxLength	1					

TXNMIS1

Attribute	Description							
Name	TXNMIS1							
Datatype	String							
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>		Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description							
maxLength	9							
minLength	1							

TXNMIS2

Attribute	Description							
Name	TXNMIS2							
Datatype	String							
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>		Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description							
maxLength	9							
minLength	1							

TXNMIS3

Attribute	Description						
Name	TXNMIS3						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS4

Attribute	Description						
Name	TXNMIS4						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS5

Attribute	Description						
Name	TXNMIS5						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	9	
	minLength	1	

TXNMIS7

Attribute	Description	
Name	TXNMIS7	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

TXNMIS8

Attribute	Description	
Name	TXNMIS8	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

TXNMIS9

Attribute	Description	
Name	TXNMIS9	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

TXNMIS10

Attribute	Description						
Name	TXNMIS10						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS1LBL1

Attribute	Description						
Name	FUNDMIS1LBL1						
Datatype	String						
Description	Indicates the Fund to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS2LBL2

Attribute	Description						
Name	FUNDMIS2LBL2						
Datatype	String						
Description	Indicates the Fund to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS3LBL3

Attribute	Description				
Name	FUNDMIS3LBL3				
Datatype	String				
Description	Indicates the Fund to which the transaction is linked.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS4LBL4

Attribute	Description						
Name	FUNDMIS4LBL4						
Datatype	String						
Description	Indicates the Fund to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS5LBL5

Attribute	Description						
Name	FUNDMIS5LBL5						
Datatype	String						
Description	Indicates the Fund to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS6LBL6

Attribute	Description						
Name	FUNDMIS6LBL6						
Datatype	String						
Description	Indicates the Fund to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	9	
		minLength	1

FUNDMIS8LBL8

Attribute	Description	
Name	FUNDMIS8LBL8	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
		minLength
		1

FUNDMIS9LBL9

Attribute	Description	
Name	FUNDMIS9LBL9	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
		minLength
		1

FUNDMIS10LBL10

Attribute	Description	
Name	FUNDMIS10LBL10	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
		minLength
		1

COMPMIS1LBL1

Attribute	Description	
------------------	--------------------	--

Name	COMPMIS1LBL1	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9
	minLength	1

COMPMIS2LBL2

Attribute	Description	
Name	COMPMIS2LBL2	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9
	minLength	1

COMPMIS3LBL3

Attribute	Description	
Name	COMPMIS3LBL3	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9
	minLength	1

COMPMIS4LBL4

Attribute	Description	
Name	COMPMIS4LBL4	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS5LBL5

Attribute	Description						
Name	COMPMIS5LBL5						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS6LBL6

Attribute	Description						
Name	COMPMIS6LBL6						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS7LBL7

Attribute	Description						
Name	COMPMIS7LBL7						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS8LBL8

Attribute	Description
-----------	--------------------

Name	COMPMIS8LBL8	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9
	minLength	1

COMPMIS9LBL9

Attribute	Description	
Name	COMPMIS9LBL9	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9
	minLength	1

COMPMIS10LBL10

Attribute	Description	
Name	COMPMIS10LBL10	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9
	minLength	1

TXNMIS1LBL1

Attribute	Description	
Name	TXNMIS1LBL1	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS2LBL2

Attribute	Description						
Name	TXNMIS2LBL2						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS3LBL3

Attribute	Description						
Name	TXNMIS3LBL3						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS4LBL4

Attribute	Description						
Name	TXNMIS4LBL4						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS5LBL5

Attribute	Description
-----------	--------------------

Name	TXNMIS5LBL5	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9
	minLength	1

TXNMIS6LBL6

Attribute	Description	
Name	TXNMIS6LBL6	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9
	minLength	1

TXNMIS7LBL7

Attribute	Description	
Name	TXNMIS7LBL7	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9
	minLength	1

TXNMIS8LBL8

Attribute	Description	
Name	TXNMIS8LBL8	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS9LBL9

Attribute	Description						
Name	TXNMIS9LBL9						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS10LBL10

Attribute	Description						
Name	TXNMIS10LBL10						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

Udf-Details

Attribute	Description						
Name	Udf-Details						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	8	

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value Type	

Attribute	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left; padding: 2px;">Attribute</th><th style="text-align: left; padding: 2px;">Description</th></tr> </thead> <tbody> <tr> <td style="padding: 2px;">minOccurs</td><td style="padding: 2px;">0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left; padding: 2px;">Restrictions</th><th style="text-align: left; padding: 2px;">Description</th></tr> </thead> <tbody> <tr> <td style="padding: 2px;">maxLength</td><td style="padding: 2px;">2</td></tr> <tr> <td style="padding: 2px;">minLength</td><td style="padding: 2px;">0</td></tr> </tbody> </table>	Restrictions	Description	maxLength	2	minLength	0
Restrictions	Description						
maxLength	2						
minLength	0						

2.6.2. Utility-Payment-Create-Req-MSG.xsd

CREATEUPTRANSACTION_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Transaction-Details-IO

XREF

ORACLE®

PRD
INSTID
BILLNO
BILLDT
BAMT
BCCY
CUSTACNO
ACCCY
CONSNO
RATECODE
TXNCCY
OFSACNO
OFSACBRN
OFSACCCY
TXNDATE
TXNBRN
RATETYPE
CUSTBRN
SERVICEID
NARRATIVE
INSTRNO
TCYTOTCHGAMT
CUST_ID
DENMCCY1
DENMAMT1
DENMCCY2
DENMAMT2
CHGAMT1
CHGCCY1
CHGAMT2
CHGCCY2
CHGAMT3

CHGCCY3

CHGAMT4

CHGCCY4

CHGAMT5

CHGCCY5

Charge-Details

CHGCOMP

WAIVER

CHGAMT

CHGCCY

MISHEAD

TXNCODE

NETTINGIND

CHGGL

TYPE

LCYCHG

XRATE

TCYCHG

TCYXRATE

Denomination-Details

CDCCY

CDDENOM

VALUE

UNITS

INOUTIND

DENMVAL

Cheque-Details

SRNO

PAYBRN

CHQNO

STAT

EXPDT

BENFNAME
BENFADDR1
BENFADDR2
BENFADDR3
BENFADDR4
CRNO
ISB
OTHERDETLS1
OTHERDETLSTYPE1
OTHERDETLS2
OTHERDETLSTYPE2
OTHERDETLS3
OTHERDETLSTYPE3
OTHERDETLS4
OTHERDETLSTYPE4
OTHERDETLS5
OTHERDETLSTYPE5
OTHERDETLS6
OTHERDETLSTYPE6

Mis-Details

BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN

REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG

TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2

TXNMIS3LBL3

TXNMIS4LBL4

TXNMIS5LBL5

TXNMIS6LBL6

TXNMIS7LBL7

TXNMIS8LBL8

TXNMIS9LBL9

TXNMIS10LBL10

Udf-Details

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

CREATEUPTRANSACTION_IOPK_REQ

Attribute	Description
Name	CREATEUPTRANSACTION_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description					
enumeration	FCUBS,FCIS					

MSGID

Attribute	Description					
Name	MSGID					
Datatype	String					
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	String					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>12</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description							
Name	BRANCH							
Datatype	String							
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr> </tbody> </table>		Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description							
length	3							
pattern	[a-zA-Z_0-9]{3}							

MODULEID

Attribute	Description					
Name	MODULEID					
Datatype	String					
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

SERVICE

Attribute	Description					
Name	SERVICE					
Datatype	String					
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>		Attribute	Description	nillable	true
Attribute	Description					
nillable	true					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

OPERATION

Attribute	Description					
Name	OPERATION					
Datatype	String					
Description	This is the operation of the service which is being invoked. This field is case-sensitive.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>		Attribute	Description	nillable	true
Attribute	Description					
nillable	true					

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description					
Name	SOURCE_OPERATION					
Datatype	String					
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

SOURCE_USERID

Attribute	Description					
Name	SOURCE_USERID					
Datatype	String					
Description	This is the user id in the Source system who is performing the action.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

DESTINATION

Attribute	Description					
Name	DESTINATION					
Datatype	String					
Description	This is the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	pattern	[a-zA-Z_0-9]*	

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description						
Name	PASSWORD						
Datatype	String						
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/*]</td></tr></tbody></table>	Restrictions	Description	maxLength	128	pattern	[a-zA-Z_0-9=+/*]
Restrictions	Description						
maxLength	128						
pattern	[a-zA-Z_0-9=+/*]						

ADDL

Attribute	Description				
Name	ADDL				
Datatype					
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Transaction-Details-IO
Datatype	
Description	

XREF

Attribute	Description				
Name	XREF				
Datatype	String				
Description	Indicates External Reference Number				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

PRD

Attribute	Description						
Name	PRD						
Datatype	String						
Description	Indicates Product Code						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>4</td></tr> <tr> <td>pattern</td><td>[a-zA-Z0-9]{4}</td></tr> </tbody> </table>	Restrictions	Description	maxLength	4	pattern	[a-zA-Z0-9]{4}
Restrictions	Description						
maxLength	4						
pattern	[a-zA-Z0-9]{4}						

INSTID

Attribute	Description				
Name	INSTID				
Datatype	String				
Description	Indicates Instrument Number				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

BILLNO

Attribute	Description				
Name	BILLNO				
Datatype	String				
Description	Indicates Bill Number				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>35</td></tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

BILLDT

Attribute	Description
Name	BILLDT
Datatype	Date
Description	Indicates Bill Date

BAMT

Attribute	Description
------------------	--------------------

Name	BAMT						
Datatype	Decimal						
Description	Indicates Bill Amount						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

BCCY

Attribute	Description							
Name	BCCY							
Datatype	String							
Description	Indicates Bill Currency							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[A-Z]{3}</td></tr> </tbody> </table>		Restrictions	Description	length	3	pattern	[A-Z]{3}
Restrictions	Description							
length	3							
pattern	[A-Z]{3}							

CUSTACNO

Attribute	Description							
Name	CUSTACNO							
Datatype	String							
Description	Indicates Customer Account Number							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> <tr> <td>pattern</td><td>[a-zA-Z0-9]*</td></tr> </tbody> </table>		Restrictions	Description	maxLength	20	pattern	[a-zA-Z0-9]*
Restrictions	Description							
maxLength	20							
pattern	[a-zA-Z0-9]*							

ACCCY

Attribute	Description							
Name	ACCCY							
Datatype	String							
Description	Indicates Account Currency							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[A-Z]{3}</td></tr> </tbody> </table>		Restrictions	Description	length	3	pattern	[A-Z]{3}
Restrictions	Description							
length	3							
pattern	[A-Z]{3}							

CONSNO

Attribute	Description	
Name	CONSNO	
Datatype	String	
Description	Indicates Consumer Serial Number	

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	35	

RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Indicates Rate Code Type	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	10

TXNCCY

Attribute	Description	
Name	TXNCCY	
Datatype	String	
Description	Indicates Transaction currency	
Restrictions	Restrictions	
	length	3
	pattern	[A-Z]{3}

OF SACNO

Attribute	Description	
Name	OF SACNO	
Datatype	String	
Description	Indicates Offset Account Number	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	20
	pattern	[a-zA-Z0-9]*

OF SACBRN

Attribute	Description	
Name	OF SACBRN	
Datatype	String	
Description	Indicates Offset Account Branch	

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	length	3	
		pattern	[a-zA-Z_0-9]{3}

OFSAACCCY

Attribute	Description	
Name	OFSACCCY	
Datatype	String	
Description	This specifies the Offset Account Currency.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	length	3
		pattern
		[A-Z]{3}

TXNDATE

Attribute	Description	
Name	TXNDATE	
Datatype	Date	
Description	Indicates Transaction date	

TXNBRN

Attribute	Description	
Name	TXNBRN	
Datatype	String	
Description	Indicates Transaction Branch	
Restrictions	Restrictions	
	length	3
		pattern
		[a-zA-Z_0-9]{3}

RATETYPE

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Indicates Rate Type	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	1

CUSTBRN

ORACLE®

Attribute	Description						
Name	CUSTBRN						
Datatype	String						
Description	Indicates Customer Branch						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

SERVICEID

Attribute	Description				
Name	SERVICEID				
Datatype	String				
Description	Indicates Service Id				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>35</td></tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

NARRATIVE

Attribute	Description				
Name	NARRATIVE				
Datatype	String				
Description	Indicates Narrative				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>255</td></tr> </tbody> </table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

INSTRNO

Attribute	Description				
Name	INSTRNO				
Datatype	String				
Description	Indicates Instrument Number				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>6</td></tr> </tbody> </table>	Restrictions	Description	maxLength	6
Restrictions	Description				
maxLength	6				

Attribute	Description						
Name	TCYTOTCHGAMT						
Datatype	Decimal						
Description	Indicates Total Charge in Transaction Currency.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

CUST_ID

Attribute	Description						
Name	CUST_ID						
Datatype	String						
Description	Indicates Customer Identification						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>pattern</td><td>[a-zA-Z0-9]*</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	pattern	[a-zA-Z0-9]*
Restrictions	Description						
maxLength	9						
pattern	[a-zA-Z0-9]*						

DENMCCY1

Attribute	Description						
Name	DENMCCY1						
Datatype	String						
Description	Indicates Denomination Currency						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[A-Z]{3}</td></tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[A-Z]{3}
Restrictions	Description						
length	3						
pattern	[A-Z]{3}						

DENMAMT1

Attribute	Description				
Name	DENMAMT1				
Datatype	Decimal				
Description	It indicates Denomination Amount				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

DENMCCY2

Attribute	Description						
Name	DENMCCY2						
Datatype	String						
Description	Indicates Denomination Currency						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[A-Z]{3}</td> </tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[A-Z]{3}
Restrictions	Description						
length	3						
pattern	[A-Z]{3}						

DENMAMT2

Attribute	Description						
Name	DENMAMT2						
Datatype	Decimal						
Description	It indicates Denomination Amount						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>fractionDigits</td> <td>3</td> </tr> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

CHGAMT1

Attribute	Description						
Name	CHGAMT1						
Datatype	Decimal						
Description	Indicates Charge Amount						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>fractionDigits</td> <td>3</td> </tr> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

CHGCCY1

Attribute	Description
Name	CHGCCY1
Datatype	String
Description	Indicates Charge Currency

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	length	3	
	pattern		[A-Z]{3}

CHGAMT2

Attribute	Description	
Name	CHGAMT2	
Datatype	Decimal	
Description	Indicates Charge Amount	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	fractionDigits	3
	totalDigits	
	22	

CHGCCY2

Attribute	Description	
Name	CHGCCY2	
Datatype	String	
Description	Indicates Charge Currency	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	length	3
	pattern	
	[A-Z]{3}	

CHGAMT3

Attribute	Description	
Name	CHGAMT3	
Datatype	Decimal	
Description	Indicates Charge Amount	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	fractionDigits	3
	totalDigits	
	22	

CHGCCY3

Attribute	Description	
------------------	--------------------	--

Name	CHGCCY3	
Datatype	String	
Description	Indicates Charge Currency	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

CHGAMT4

Attribute	Description	
Name	CHGAMT4	
Datatype	Decimal	
Description	Indicates Charge Amount	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

CHGCCY4

Attribute	Description	
Name	CHGCCY4	
Datatype	String	
Description	Indicates Charge Currency	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

CHGAMT5

Attribute	Description	
Name	CHGAMT5	
Datatype	Decimal	
Description	Indicates Charge Amount	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

CHGCCY5

Attribute	Description						
Name	CHGCCY5						
Datatype	String						
Description	Indicates Charge Currency						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[A-Z]{3}
Restrictions	Description						
length	3						
pattern	[A-Z]{3}						

Charge-Details

Attribute	Description						
Name	Charge-Details						
Datatype							
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

CHGCOMP

Attribute	Description				
Name	CHGCOMP				
Datatype	String				
Description	Indicates Charge Components				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

WAIVER

Attribute	Description				
Name	WAIVER				
Datatype	String				
Description	Indicates Charge Waiver.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

CHGAMT

Attribute	Description						
Name	CHGAMT						
Datatype	Decimal						
Description	Indicates Charge Amount						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

CHGCCY

Attribute	Description				
Name	CHGCCY				
Datatype	String				
Description	Indicates Charge Currency				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

MISHEAD

Attribute	Description				
Name	MISHEAD				
Datatype	String				
Description	Indicates MIS Head				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

TXNCODE

Attribute	Description				
Name	TXNCODE				
Datatype	String				
Description	Indicates Transaction Code				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

NETTINGIND

Attribute	Description				
Name	NETTINGIND				
Datatype	String				
Description	Netting Index				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

CHGGL

Attribute	Description				
Name	CHGGL				
Datatype	String				
Description	Charge General Ledger				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

TYPE

Attribute	Description				
Name	TYPE				
Datatype	String				
Description	Type				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

LCYCHG

Attribute	Description						
Name	LCYCHG						
Datatype	Decimal						
Description	Indicates Charge in Local Currency						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

Attribute	Description						
Name	XRATE						
Datatype	Decimal						
Description	Indicates Exchange rate						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

TCYCHG

Attribute	Description						
Name	TCYCHG						
Datatype	Decimal						
Description	Charge In Transaction Currency						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

TCYXRATE

Attribute	Description						
Name	TCYXRATE						
Datatype	Decimal						
Description	Transaction Currency Exchange rate						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

Denomination-Details

Attribute	Description						
Name	Denomination-Details						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

CDCCY

ORACLE®

Attribute	Description				
Name	CDCCY				
Datatype	String				
Description	Indicates Credit Currency				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

CDDENOM

Attribute	Description				
Name	CDDENOM				
Datatype	String				
Description	Credit Denomination				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>50</td></tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

VALUE

Attribute	Description						
Name	VALUE						
Datatype	Decimal						
Description	Indicates Value						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

UNITS

Attribute	Description						
Name	UNITS						
Datatype	Decimal						
Description	Indicates Units						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>0</td></tr> <tr> <td>totalDigits</td><td>10</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	0	totalDigits	10
Restrictions	Description						
fractionDigits	0						
totalDigits	10						

INOUTIND

Attribute	Description				
Name	INOUTIND				
Datatype	String				
Description	IN OUT INDEX				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

DENMVAL

Attribute	Description						
Name	DENMVAL						
Datatype	Decimal						
Description	Indicates Denomination Value						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

Cheque-Details

Attribute	Description						
Name	Cheque-Details						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

SRNO

Attribute	Description				
Name	SRNO				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>16</td></tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

PAYBRN

Attribute	Description

Name	PAYBRN					
Datatype	String					
Description	Indicates Payable Branch					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3	
Restrictions	Description					
maxLength	3					

CHQNO

Attribute	Description					
Name	CHQNO					
Datatype	String					
Description	Indicates Cheque Number					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>16</td></tr> </tbody> </table>	Restrictions	Description	maxLength	16	
Restrictions	Description					
maxLength	16					

STAT

Attribute	Description					
Name	STAT					
Datatype	String					
Description	Status of Cheque					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>4</td></tr> </tbody> </table>	Restrictions	Description	maxLength	4	
Restrictions	Description					
maxLength	4					

EXPDT

Attribute	Description	
Name	EXPDT	
Datatype	Date	
Description	Indicates Expected Date	

BENFNAME

Attribute	Description					
Name	BENFNAME					
Datatype	String					
Description	Indicates Beneficiary Name					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					

Restrictions					
	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>105</td></tr> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

BENFADDR1

Attribute	Description				
Name	BENFADDR1				
Datatype	String				
Description	Beneficiary address Line 1				
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>105</td></tr> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

BENFADDR2

Attribute	Description				
Name	BENFADDR2				
Datatype	String				
Description	Beneficiary address Line 2				
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>105</td></tr> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

BENFADDR3

Attribute	Description				
Name	BENFADDR3				
Datatype	String				
Description	Beneficiary address Line 3				
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>105</td></tr> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

BENFADDR4

Attribute	Description				
Name	BENFADDR4				
Datatype	String				
Description	Beneficiary address Line 4				
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> </tbody> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

CRNO

Attribute	Description				
Name	CRNO				
Datatype	String				
Description	Credit Number				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

ISB

Attribute	Description				
Name	ISB				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

OTHERDETLS1

Attribute	Description				
Name	OTHERDETLS1				
Datatype	String				
Description	Indicates Other Details 1				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLSTYPE1

Attribute	Description				
Name	OTHERDETLSTYPE1				
Datatype	String				
Description	Indicates Other Details Type 1				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>65</td></tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLS2

Attribute	Description				
Name	OTHERDETLS2				
Datatype	String				
Description	Indicates Other Details 2				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLSTYPE2

Attribute	Description				
Name	OTHERDETLSTYPE2				
Datatype	String				
Description	Indicates Other Details Type 1				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLS3

Attribute	Description				
Name	OTHERDETLS3				
Datatype	String				
Description	Indicates Other Details 3				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLSTYPE3

Attribute	Description				
Name	OTHERDETLSTYPE3				
Datatype	String				
Description	Indicates Other Details Type 3				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>65</td></tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLS4

Attribute	Description				
Name	OTHERDETLS4				
Datatype	String				
Description	Indicates Other Details 4				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETTYPE4

Attribute	Description				
Name	OTHERDETTYPE4				
Datatype	String				
Description	Indicates Other Details Type 4				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLS5

Attribute	Description				
Name	OTHERDETLS5				
Datatype	String				
Description	Indicates Other Details 5				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETTYPE5

Attribute	Description				
Name	OTHERDETTYPE5				
Datatype	String				
Description	Indicates Other Details Type 5				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>65</td></tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLS6

Attribute	Description					
Name	OTHERDETLS6					
Datatype	String					
Description	Indicates Other Details 6					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	65
Restrictions	Description					
maxLength	65					

OTHERDETLSTYPE6

Attribute	Description					
Name	OTHERDETLSTYPE6					
Datatype	String					
Description	Indicates Other Details Type 6					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	65
Restrictions	Description					
maxLength	65					

Mis-Details

Attribute	Description							
Name	Mis-Details							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

BRANCH

Attribute	Description					
Name	BRANCH					
Datatype	String					
Description	Indicates Branch Code					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

CUSTNO

Attribute	Description						
Name	CUSTNO						
Datatype	String						
Description	Indicates Customer Number						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

MISGRP

Attribute	Description						
Name	MISGRP						
Datatype	String						
Description	Indicates MIS Group						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12	minLength	1
Restrictions	Description						
maxLength	12						
minLength	1						

REL_REF

Attribute	Description						
Name	REL_REF						
Datatype	String						
Description	Indicates Related Reference Number						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16	minLength	1
Restrictions	Description						
maxLength	16						
minLength	1						

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Indicates Related Account

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	16	
		minLength	1

MISHD

Attribute	Description	
Name	MISHD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description	Indicates Pool Code	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

REFRT

Attribute	Description	
Name	REFRT	
Datatype	Decimal	
Description	Indicates the Refinancing Rate	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	fractionDigits	15
	minInclusive	0
	totalDigits	26

REFRTTYPE

Attribute	Description	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	1	

REFXRT

Attribute	Description	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

CALCMETH

Attribute	Description	
Name	CALCMETH	
Datatype	Integer	
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6	
Attribute	Attribute	Description
	minOccurs	0

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

REFRTCD

Attribute	Description	
Name	REFRTCD	
Datatype	String	
Description	Indicates the Refinancing Rate Code	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>10</td></tr> </tbody> </table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

REFRTSPRD

Attribute	Description								
Name	REFRTSPRD								
Datatype	Decimal								
Description	Indicates the spread for the Refinance Rate Code								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0				
Attribute	Description								
minOccurs	0								
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>fractionDigits</td> <td>5</td> </tr> <tr> <td>minInclusive</td> <td>0</td> </tr> <tr> <td>totalDigits</td> <td>15</td> </tr> </tbody> </table>	Restrictions	Description	fractionDigits	5	minInclusive	0	totalDigits	15
Restrictions	Description								
fractionDigits	5								
minInclusive	0								
totalDigits	15								

FUNDMIS1

Attribute	Description						
Name	FUNDMIS1						
Datatype	String						
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS2

Attribute	Description						
Name	FUNDMIS2						
Datatype	String						
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS3

Attribute	Description
Name	FUNDMIS3

Datatype	String							
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.							
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0			
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </table>	Restrictions	Description	maxLength	9	minLength	1	
Restrictions	Description							
maxLength	9							
minLength	1							

FUNDMIS4

Attribute	Description							
Name	FUNDMIS4							
Datatype	String							
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.							
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0			
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </table>	Restrictions	Description	maxLength	9	minLength	1	
Restrictions	Description							
maxLength	9							
minLength	1							

FUNDMIS5

Attribute	Description							
Name	FUNDMIS5							
Datatype	String							
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.							
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0			
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </table>	Restrictions	Description	maxLength	9	minLength	1	
Restrictions	Description							
maxLength	9							
minLength	1							

FUNDMIS6

Attribute	Description					
Name	FUNDMIS6					
Datatype	String					
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.					
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS7

Attribute	Description						
Name	FUNDMIS7						
Datatype	String						
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS8

Attribute	Description						
Name	FUNDMIS8						
Datatype	String						
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS9

Attribute	Description						
Name	FUNDMIS9						
Datatype	String						
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS10

Attribute	Description
-----------	--------------------

Name	FUNDMIS10						
Datatype	String						
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

MISGRPCOMP

Attribute	Description				
Name	MISGRPCOMP				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

COMPMIS1

Attribute	Description						
Name	COMPMIS1						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS2

Attribute	Description						
Name	COMPMIS2						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS3

Attribute	Description						
Name	COMPMIS3						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS4

Attribute	Description						
Name	COMPMIS4						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS5

Attribute	Description						
Name	COMPMIS5						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	9	
	minLength	1	

COMPMIS7

Attribute	Description	
Name	COMPMIS7	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

COMPMIS8

Attribute	Description	
Name	COMPMIS8	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

COMPMIS9

Attribute	Description	
Name	COMPMIS9	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

COMPMS10

Attribute	Description						
Name	COMPMS10						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COSTCOD1

Attribute	Description						
Name	COSTCOD1						
Datatype	String						
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COSTCOD2

Attribute	Description						
Name	COSTCOD2						
Datatype	String						
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	9	
		minLength	1

COSTCOD4

Attribute	Description	
Name	COSTCOD4	
Datatype	String	
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
		minLength
		1

COSTCOD5

Attribute	Description	
Name	COSTCOD5	
Datatype	String	
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
		minLength
		1

LINKGRP

Attribute	Description	
Name	LINKGRP	
Datatype	String	
Description	Indicates the Link To Group	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	12
		minLength
		1

Attribute	Description				
Name	CCY				
Datatype	String				
Description	Indicates Currency				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

RTFLAG

Attribute	Description				
Name	RTFLAG				
Datatype	String				
Description	Indicates the refinancing rate that should be used for the transaction				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

PROCFLG

Attribute	Description				
Name	PROCFLG				
Datatype	String				
Description	Indicates ProcflgType R-Related Reference Number A-Related Account				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

TXNMIS1

Attribute	Description						
Name	TXNMIS1						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS2

Attribute	Description						
Name	TXNMIS2						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS3

Attribute	Description						
Name	TXNMIS3						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS4

Attribute	Description						
Name	TXNMIS4						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	9	
	minLength	1	

TXNMIS6

Attribute	Description	
Name	TXNMIS6	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

TXNMIS7

Attribute	Description	
Name	TXNMIS7	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

TXNMIS8

Attribute	Description	
Name	TXNMIS8	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

TXNMIS9

Attribute	Description						
Name	TXNMIS9						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS10

Attribute	Description						
Name	TXNMIS10						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS1LBL1

Attribute	Description						
Name	FUNDMIS1LBL1						
Datatype	String						
Description	Indicates the Fund to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS2LBL2

Attribute	Description				
Name	FUNDMIS2LBL2				
Datatype	String				
Description	Indicates the Fund to which the transaction is linked.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS3LBL3

Attribute	Description						
Name	FUNDMIS3LBL3						
Datatype	String						
Description	Indicates the Fund to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS4LBL4

Attribute	Description						
Name	FUNDMIS4LBL4						
Datatype	String						
Description	Indicates the Fund to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS5LBL5

Attribute	Description						
Name	FUNDMIS5LBL5						
Datatype	String						
Description	Indicates the Fund to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	9	
		minLength	1

FUNDMIS7LBL7

Attribute	Description	
Name	FUNDMIS7LBL7	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
		minLength
		1

FUNDMIS8LBL8

Attribute	Description	
Name	FUNDMIS8LBL8	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
		minLength
		1

FUNDMIS9LBL9

Attribute	Description	
Name	FUNDMIS9LBL9	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
		minLength
		1

FUNDMIS10LBL10

Attribute	Description	
------------------	--------------------	--

Name	FUNDMIS10LBL10							
Datatype	String							
Description	Indicates the Fund to which the transaction is linked.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>		Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description							
maxLength	9							
minLength	1							

COMPMIS1LBL1

Attribute	Description							
Name	COMPMIS1LBL1							
Datatype	String							
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>		Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description							
maxLength	9							
minLength	1							

COMPMIS2LBL2

Attribute	Description							
Name	COMPMIS2LBL2							
Datatype	String							
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>		Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description							
maxLength	9							
minLength	1							

COMPMIS3LBL3

Attribute	Description					
Name	COMPMIS3LBL3					
Datatype	String					
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS4LBL4

Attribute	Description						
Name	COMPMIS4LBL4						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS5LBL5

Attribute	Description						
Name	COMPMIS5LBL5						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS6LBL6

Attribute	Description						
Name	COMPMIS6LBL6						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS7LBL7

Attribute	Description
-----------	--------------------

Name	COMPMIS7LBL7							
Datatype	String							
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description							
maxLength	9							
minLength	1							

COMPMIS8LBL8

Attribute	Description							
Name	COMPMIS8LBL8							
Datatype	String							
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description							
maxLength	9							
minLength	1							

COMPMIS9LBL9

Attribute	Description							
Name	COMPMIS9LBL9							
Datatype	String							
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description							
maxLength	9							
minLength	1							

COMPMIS10LBL10

Attribute	Description					
Name	COMPMIS10LBL10					
Datatype	String					
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS1LBL1

Attribute	Description						
Name	TXNMIS1LBL1						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS2LBL2

Attribute	Description						
Name	TXNMIS2LBL2						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS3LBL3

Attribute	Description						
Name	TXNMIS3LBL3						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS4LBL4

Attribute	Description
-----------	--------------------

Name	TXNMIS4LBL4	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9
	minLength	1

TXNMIS5LBL5

Attribute	Description	
Name	TXNMIS5LBL5	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9
	minLength	1

TXNMIS6LBL6

Attribute	Description	
Name	TXNMIS6LBL6	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9
	minLength	1

TXNMIS7LBL7

Attribute	Description	
Name	TXNMIS7LBL7	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS8LBL8

Attribute	Description						
Name	TXNMIS8LBL8						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS9LBL9

Attribute	Description						
Name	TXNMIS9LBL9						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS10LBL10

Attribute	Description						
Name	TXNMIS10LBL10						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

Udf-Details

Attribute	Description
-----------	--------------------

Name	Udf-Details							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded	
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

FUNCTIONID

Attribute	Description					
Name	FUNCTIONID					
Datatype	String					
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>8</td></tr> </tbody> </table>	Restrictions	Description	maxLength	8	
Restrictions	Description					
maxLength	8					

FIELD_NAME

Attribute	Description							
Name	FIELD_NAME							
Datatype	String							
Description	Indicates the User Defined Field Name							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	105	minLength	1	
Restrictions	Description							
maxLength	105							
minLength	1							

DATATYPE

Attribute	Description					
Name	DATATYPE					
Datatype	String					
Description	Indicates Data Type					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>15</td></tr> </tbody> </table>	Restrictions	Description	maxLength	15	
Restrictions	Description					
maxLength	15					

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value	

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	255	
		minLength	0

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value Type	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
		minLength
		0

2.6.3.Utility-Payment-Create-Res-Full-MSG.xsd

CREATEUPTRANSACTION_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Transaction-Details

XREF

FCCREF

PRD

INSTID

BILLNO

BILLDT

BAMT

BCCY

CUSTACNO

ACCCY

CONSNO

NETAMT

RATECODE

TXNCCY

OFSACNO

OFSACBRN

OFSACCCY

TXNDATE

TXNBRN

RATETYPE

MAKERID

MAKERSTAMP

CHECKERID

CHECKERSTAMP

AUTHSTAT

ORACLE®

CONTSTAT
MODNO
RECORDSTAT
ONCEAUTH
CUSTBRN
SERVICEID
NARRATIVE
INSTRNO
LCYTOTCHGAMT
TCYTOTCHGAMT
XRATE
CUST_ID
ACCTITLE
ACTAMT
DENMCCY1
DENMAMT1
DENMCCY2
DENMAMT2
CHGAMT1
CHGCCY1
CHGAMT2
CHGCCY2
CHGAMT3
CHGCCY3
CHGAMT4
CHGCCY4
CHGAMT5
CHGCCY5
SUBSYSTEMSTAT
Charge-Details
CHGCOMP
WAIVER

CHGAMT
CHGCCY
MISHEAD
TXNCODE
NETTINGIND
CHGGL
TYPE
LCYCHG
XRATE
TCYCHG
TCYXRATE

Denomination-Details

CDCCY
CDDENOM
VALUE
UNITS
INOUTIND
DENMVAL

Cheque-Details

SRNO
PAYBRN
CHQNO
STAT
EXPDT
BENFNAME
BENFADDR1
BENFADDR2
BENFADDR3
BENFADDR4
CRNO
ISB
OTHERDETLS1

OTHERDETLTYPE1

OTHERDETLS2

OTHERDETLTYPE2

OTHERDETLS3

OTHERDETLTYPE3

OTHERDETLS4

OTHERDETLTYPE4

OTHERDETLS5

OTHERDETLTYPE5

OTHERDETLS6

OTHERDETLTYPE6

Mis-Details

BRANCH

CUSTNO

MISGRP

REL_REF

REL_ACC

MISHD

POOLCD

REFRT

REFRTTYPE

REFXRT

CALCMETH

MISGRPTXN

REFRTCD

REFRTSPRD

FUNDMIS1

FUNDMIS2

FUNDMIS3

FUNDMIS4

FUNDMIS5

FUNDMIS6

FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8

TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Udf-Details

FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

CREATEUPTRANSACTION_FSFS_RES

Attribute	Description
Name	CREATEUPTRANSACTION_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description					
enumeration	FCUBS,FCIS					

MSGID

Attribute	Description					
Name	MSGID					
Datatype	String					
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

CORRELID

Attribute	Description					
Name	CORRELID					
Datatype	String					
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>12</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description							
Name	BRANCH							
Datatype	String							
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>		Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description							
length	3							
pattern	[a-zA-Z_0-9]{3}							

MODULEID

Attribute	Description					
Name	MODULEID					
Datatype	String					
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

SERVICE

Attribute	Description					
Name	SERVICE					
Datatype	String					
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		Attribute	Description	nillable	true
Attribute	Description					
nillable	true					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

OPERATION

Attribute	Description					
Name	OPERATION					
Datatype	String					
Description	This is the operation of the service which is being invoked. This field is case-sensitive.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		Attribute	Description	nillable	true
Attribute	Description					
nillable	true					

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description					
Name	SOURCE_OPERATION					
Datatype	String					
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

SOURCE_USERID

Attribute	Description					
Name	SOURCE_USERID					
Datatype	String					
Description	This is the user id in the Source system who is performing the action.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

DESTINATION

Attribute	Description					
Name	DESTINATION					
Datatype	String					
Description	This is the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	pattern	[a-zA-Z_0-9]*	

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description						
Name	PASSWORD						
Datatype	String						
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/*]</td></tr></tbody></table>	Restrictions	Description	maxLength	128	pattern	[a-zA-Z_0-9=+/*]
Restrictions	Description						
maxLength	128						
pattern	[a-zA-Z_0-9=+/*]						

ADDL

Attribute	Description				
Name	ADDL				
Datatype					
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Attribute	Description
Name	Transaction-Details
Datatype	
Description	

XREF

Attribute	Description				
Name	XREF				
Datatype	String				
Description	Indicates External Reference Number				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

FCCREF

Attribute	Description				
Name	FCCREF				
Datatype	String				
Description	Indicates the Reference Number of the External System. Note: This field is mandatory only in case where FCCREF is not available.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z0-9]{16}
Restrictions	Description				
pattern	[a-zA-Z0-9]{16}				

PRD

Attribute	Description						
Name	PRD						
Datatype	String						
Description	Indicates Product Code						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>4</td></tr> <tr> <td>pattern</td><td>[a-zA-Z0-9]{4}</td></tr> </tbody> </table>	Restrictions	Description	maxLength	4	pattern	[a-zA-Z0-9]{4}
Restrictions	Description						
maxLength	4						
pattern	[a-zA-Z0-9]{4}						

INSTID

Attribute	Description				
Name	INSTID				
Datatype	String				
Description	Indicates Instrument Number				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

BILLNO

Attribute	Description
Name	BILLNO

Datatype	String	
Description	Indicates Bill Number	
Restrictions	Restrictions	Description
	maxLength	35

BILLDT

Attribute	Description	
Name	BILLDT	
Datatype	Date	
Description	Indicates Bill Date	

BAMT

Attribute	Description	
Name	BAMT	
Datatype	Decimal	
Description	Indicates Bill Amount	
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

BCCY

Attribute	Description	
Name	BCCY	
Datatype	String	
Description	Indicates Bill Currency	
Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

CUSTACNO

Attribute	Description	
Name	CUSTACNO	
Datatype	String	
Description	Indicates Customer Account Number	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20
	pattern	[a-zA-Z0-9]*

ACCCY

Attribute	Description	
Name	ACCCY	
Datatype	String	
Description	Indicates Account Currency	

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	length	3	
		pattern	[A-Z]{3}

CONSNO

Attribute	Description	
Name	CONSNO	
Datatype	String	
Description	Indicates Consumer Serial Number	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	35

NETAMT

Attribute	Description	
Name	NETAMT	
Datatype	Decimal	
Description	Indicates Net Amount	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	fractionDigits	3
	totalDigits	22

RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Indicates Rate Code Type	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	10

TXNCCY

Attribute	Description	
Name	TXNCCY	

Datatype	String							
Description	Indicates Transaction currency							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[A-Z]{3}</td></tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[A-Z]{3}	
Restrictions	Description							
length	3							
pattern	[A-Z]{3}							

OF SAC NO

Attribute	Description							
Name	OFSACNO							
Datatype	String							
Description	Indicates Offset Account Number							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0			
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> <tr> <td>pattern</td><td>[a-zA-Z0-9]*</td></tr> </tbody> </table>	Restrictions	Description	maxLength	20	pattern	[a-zA-Z0-9]*	
Restrictions	Description							
maxLength	20							
pattern	[a-zA-Z0-9]*							

OF SAC B R N

Attribute	Description							
Name	OFSACBRN							
Datatype	String							
Description	Indicates Offset Account Branch							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0			
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}	
Restrictions	Description							
length	3							
pattern	[a-zA-Z_0-9]{3}							

OF SAC C C Y

Attribute	Description							
Name	OFSACCCY							
Datatype	String							
Description	This specifies the Offset Account Currency.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0			
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[A-Z]{3}</td></tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[A-Z]{3}	
Restrictions	Description							
length	3							
pattern	[A-Z]{3}							

T X N D A T E

Attribute	Description	
Name	TXNDATE	

Datatype	Date
Description	Indicates Transaction date

TXNBRN

Attribute	Description							
Name	TXNBRN							
Datatype	String							
Description	Indicates Transaction Branch							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}	
Restrictions	Description							
length	3							
pattern	[a-zA-Z_0-9]{3}							

RATETYPE

Attribute	Description					
Name	RATETYPE					
Datatype	String					
Description	Indicates Rate Type					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	1	
Restrictions	Description					
maxLength	1					

MAKERID

Attribute	Description					
Name	MAKERID					
Datatype	String					
Description	The User Id who has created\last modified the record.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12	
Restrictions	Description					
maxLength	12					

MAKERSTAMP

Attribute	Description					
Name	MAKERSTAMP					
Datatype	String					
Description	Indicates Date and Stamp when the User has created\last modified the record.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					

CHECKERID

Attribute	Description	

ORACLE®

Name	CHECKERID	
Datatype	String	
Description	The User Id who has Authorized the creation\modificaion of the record	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.	
Attribute		
	Attribute	Description
	minOccurs	0

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status A - Authorized U - Un Authorized	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	A,U

CONTSTAT

Attribute	Description	
Name	CONTSTAT	
Datatype	String	
Description	Indicates Contract Status	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

MODNO

Attribute	Description
Name	MODNO
Datatype	Decimal

Description	Indicates Modification number i.e. the number of times the record has been modified.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	0
	totalDigits	10

RECORDSTAT

Attribute	Description	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates Record Status O - Open C - Close	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	O,C

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates whether the record is Authorized atleast Once.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

CUSTBRN

Attribute	Description	
Name	CUSTBRN	
Datatype	String	
Description	Indicates Customer Branch	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

SERVICEID

Attribute	Description	
------------------	--------------------	--

Name	SERVICEID					
Datatype	String					
Description	Indicates Service Id					
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>35</td></tr> </table>	Restrictions	Description	maxLength	35	
Restrictions	Description					
maxLength	35					

NARRATIVE

Attribute	Description					
Name	NARRATIVE					
Datatype	String					
Description	Indicates Narrative					
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>255</td></tr> </table>	Restrictions	Description	maxLength	255	
Restrictions	Description					
maxLength	255					

INSTRNO

Attribute	Description					
Name	INSTRNO					
Datatype	String					
Description	Indicates Instrument Number					
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>6</td></tr> </table>	Restrictions	Description	maxLength	6	
Restrictions	Description					
maxLength	6					

LCYTOTCHGAMT

Attribute	Description							
Name	LCYTOTCHGAMT							
Datatype	Decimal							
Description	Indicates Total Charge in Local Currency.							
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0			
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22	
Restrictions	Description							
fractionDigits	3							
totalDigits	22							

TCYTOTCHGAMT

Attribute	Description	
-----------	-------------	--

Name	TCYTOTCHGAMT							
Datatype	Decimal							
Description	Indicates Total Charge in Transaction Currency.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>		Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description							
fractionDigits	3							
totalDigits	22							

XRATE

Attribute	Description							
Name	XRATE							
Datatype	Decimal							
Description	Indicates Exchange rate							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>12</td></tr> <tr> <td>totalDigits</td><td>24</td></tr> </tbody> </table>		Restrictions	Description	fractionDigits	12	totalDigits	24
Restrictions	Description							
fractionDigits	12							
totalDigits	24							

CUST_ID

Attribute	Description							
Name	CUST_ID							
Datatype	String							
Description	Indicates Customer Identification							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>pattern</td><td>[a-zA-Z0-9]*</td></tr> </tbody> </table>		Restrictions	Description	maxLength	9	pattern	[a-zA-Z0-9]*
Restrictions	Description							
maxLength	9							
pattern	[a-zA-Z0-9]*							

ACCTITLE

Attribute	Description					
Name	ACCTITLE					
Datatype	String					
Description	Indicates Account Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> </tbody> </table>		Restrictions	Description	maxLength	105
Restrictions	Description					
maxLength	105					

ACTAMT

ORACLE®

Attribute	Description						
Name	ACTAMT						
Datatype	Decimal						
Description	Indicates Actual Amount						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

DENMCCY1

Attribute	Description						
Name	DENMCCY1						
Datatype	String						
Description	Indicates Denomination Currency						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[A-Z]{3}</td></tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[A-Z]{3}
Restrictions	Description						
length	3						
pattern	[A-Z]{3}						

DENMAMT1

Attribute	Description						
Name	DENMAMT1						
Datatype	Decimal						
Description	It indicates Denomination Amount						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

DENMCCY2

Attribute	Description				
Name	DENMCCY2				
Datatype	String				
Description	Indicates Denomination Currency				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[A-Z]{3}</td></tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[A-Z]{3}
Restrictions	Description						
length	3						
pattern	[A-Z]{3}						

DENMAMT2

Attribute	Description						
Name	DENMAMT2						
Datatype	Decimal						
Description	It indicates Denomination Amount						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>fractionDigits</td> <td>3</td> </tr> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

CHGAMT1

Attribute	Description						
Name	CHGAMT1						
Datatype	Decimal						
Description	Indicates Charge Amount						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>fractionDigits</td> <td>3</td> </tr> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

CHGCCY1

Attribute	Description						
Name	CHGCCY1						
Datatype	String						
Description	Indicates Charge Currency						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[A-Z]{3}</td> </tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[A-Z]{3}
Restrictions	Description						
length	3						
pattern	[A-Z]{3}						

CHGAMT2

Attribute	Description
Name	CHGAMT2
Datatype	Decimal
Description	Indicates Charge Amount

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	fractionDigits	3	
	totalDigits	22	

CHGCCY2

Attribute	Description	
Name	CHGCCY2	
Datatype	String	
Description	Indicates Charge Currency	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	length	3
	pattern	[A-Z]{3}

CHGAMT3

Attribute	Description	
Name	CHGAMT3	
Datatype	Decimal	
Description	Indicates Charge Amount	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	fractionDigits	3
	totalDigits	22

CHGCCY3

Attribute	Description	
Name	CHGCCY3	
Datatype	String	
Description	Indicates Charge Currency	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	length	3
	pattern	[A-Z]{3}

CHGAMT4

Attribute	Description	
------------------	--------------------	--

Name	CHGAMT4							
Datatype	Decimal							
Description	Indicates Charge Amount							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>		Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description							
fractionDigits	3							
totalDigits	22							

CHGCCY4

Attribute	Description							
Name	CHGCCY4							
Datatype	String							
Description	Indicates Charge Currency							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[A-Z]{3}</td></tr> </tbody> </table>		Restrictions	Description	length	3	pattern	[A-Z]{3}
Restrictions	Description							
length	3							
pattern	[A-Z]{3}							

CHGAMT5

Attribute	Description							
Name	CHGAMT5							
Datatype	Decimal							
Description	Indicates Charge Amount							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>		Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description							
fractionDigits	3							
totalDigits	22							

CHGCCY5

Attribute	Description							
Name	CHGCCY5							
Datatype	String							
Description	Indicates Charge Currency							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[A-Z]{3}</td></tr> </tbody> </table>		Restrictions	Description	length	3	pattern	[A-Z]{3}
Restrictions	Description							
length	3							
pattern	[A-Z]{3}							

SUBSYSTEMSTAT

Attribute	Description				
Name	SUBSYSTEMSTAT				
Datatype	String				
Description	Indicates Subsystem Status				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

Charge-Details

Attribute	Description						
Name	Charge-Details						
Datatype							
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

CHGCOMP

Attribute	Description				
Name	CHGCOMP				
Datatype	String				
Description	Indicates Charge Components				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

WAIVER

Attribute	Description				
Name	WAIVER				
Datatype	String				
Description	Indicates Charge Waiver.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

CHGAMT

Attribute	Description

Name	CHGAMT							
Datatype	Decimal							
Description	Indicates Charge Amount							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0	nillable	true
Attribute	Description							
minOccurs	0							
nillable	true							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22	
Restrictions	Description							
fractionDigits	3							
totalDigits	22							

CHGCCY

Attribute	Description					
Name	CHGCCY					
Datatype	String					
Description	Indicates Charge Currency					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3	
Restrictions	Description					
maxLength	3					

MISHEAD

Attribute	Description					
Name	MISHEAD					
Datatype	String					
Description	Indicates MIS Head					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	
Restrictions	Description					
maxLength	9					

TXNCODE

Attribute	Description					
Name	TXNCODE					
Datatype	String					
Description	Indicates Transaction Code					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3	
Restrictions	Description					
maxLength	3					

NETTINGIND

ORACLE®

Attribute	Description	
Name	NETTINGIND	
Datatype	String	
Description	Netting Index	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

CHGGL

Attribute	Description	
Name	CHGGL	
Datatype	String	
Description	Charge General Ledger	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	
Description	Type	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

LCYCHG

Attribute	Description	
Name	LCYCHG	
Datatype	Decimal	
Description	Indicates Charge in Local Currency	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

XRATE

ORACLE®

Attribute	Description						
Name	XRATE						
Datatype	Decimal						
Description	Indicates Exchange rate						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

TCYCHG

Attribute	Description						
Name	TCYCHG						
Datatype	Decimal						
Description	Charge In Transaction Currency						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

TCYXRATE

Attribute	Description						
Name	TCYXRATE						
Datatype	Decimal						
Description	Transaction Currency Exchange rate						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

Denomination-Details

Attribute	Description						
Name	Denomination-Details						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

Attribute	Description				
Name	CDCCY				
Datatype	String				
Description	Indicates Credit Currency				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

CDDENOM

Attribute	Description				
Name	CDDENOM				
Datatype	String				
Description	Credit Denomination				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>50</td></tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

VALUE

Attribute	Description						
Name	VALUE						
Datatype	Decimal						
Description	Indicates Value						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

UNITS

Attribute	Description						
Name	UNITS						
Datatype	Decimal						
Description	Indicates Units						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>0</td></tr> <tr> <td>totalDigits</td><td>10</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	0	totalDigits	10
Restrictions	Description						
fractionDigits	0						
totalDigits	10						

INOUTIND

Attribute	Description				
Name	INOUTIND				
Datatype	String				
Description	IN OUT INDEX				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

DENMVAL

Attribute	Description						
Name	DENMVAL						
Datatype	Decimal						
Description	Indicates Denomination Value						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

Cheque-Details

Attribute	Description						
Name	Cheque-Details						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

SRNO

Attribute	Description				
Name	SRNO				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>16</td></tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

PAYBRN

Attribute	Description

Name	PAYBRN					
Datatype	String					
Description	Indicates Payable Branch					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3	
Restrictions	Description					
maxLength	3					

CHQNO

Attribute	Description					
Name	CHQNO					
Datatype	String					
Description	Indicates Cheque Number					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>16</td></tr> </tbody> </table>	Restrictions	Description	maxLength	16	
Restrictions	Description					
maxLength	16					

STAT

Attribute	Description					
Name	STAT					
Datatype	String					
Description	Status of Cheque					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>4</td></tr> </tbody> </table>	Restrictions	Description	maxLength	4	
Restrictions	Description					
maxLength	4					

EXPDT

Attribute	Description	
Name	EXPDT	
Datatype	Date	
Description	Indicates Expected Date	

BENFNAME

Attribute	Description					
Name	BENFNAME					
Datatype	String					
Description	Indicates Beneficiary Name					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					

Restrictions					
	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>105</td></tr> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

BENFADDR1

Attribute	Description				
Name	BENFADDR1				
Datatype	String				
Description	Beneficiary address Line 1				
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>105</td></tr> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

BENFADDR2

Attribute	Description				
Name	BENFADDR2				
Datatype	String				
Description	Beneficiary address Line 2				
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>105</td></tr> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

BENFADDR3

Attribute	Description				
Name	BENFADDR3				
Datatype	String				
Description	Beneficiary address Line 3				
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>105</td></tr> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

BENFADDR4

Attribute	Description				
Name	BENFADDR4				
Datatype	String				
Description	Beneficiary address Line 4				
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions					
	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>105</td></tr> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

CRNO

Attribute	Description				
Name	CRNO				
Datatype	String				
Description	Credit Number				
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>16</td></tr> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

ISB

Attribute	Description				
Name	ISB				
Datatype	String				
Description					
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>9</td></tr> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

OTHERDETLS1

Attribute	Description				
Name	OTHERDETLS1				
Datatype	String				
Description	Indicates Other Details 1				
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>65</td></tr> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLSTYPE1

Attribute	Description				
Name	OTHERDETLSTYPE1				
Datatype	String				
Description	Indicates Other Details Type 1				
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>65</td></tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLS2

Attribute	Description				
Name	OTHERDETLS2				
Datatype	String				
Description	Indicates Other Details 2				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLSTYPE2

Attribute	Description				
Name	OTHERDETLSTYPE2				
Datatype	String				
Description	Indicates Other Details Type 1				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLS3

Attribute	Description				
Name	OTHERDETLS3				
Datatype	String				
Description	Indicates Other Details 3				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLSTYPE3

Attribute	Description				
Name	OTHERDETLSTYPE3				
Datatype	String				
Description	Indicates Other Details Type 3				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>65</td></tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLS4

Attribute	Description				
Name	OTHERDETLS4				
Datatype	String				
Description	Indicates Other Details 4				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETTYPE4

Attribute	Description				
Name	OTHERDETTYPE4				
Datatype	String				
Description	Indicates Other Details Type 4				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLS5

Attribute	Description				
Name	OTHERDETLS5				
Datatype	String				
Description	Indicates Other Details 5				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETTYPE5

Attribute	Description				
Name	OTHERDETTYPE5				
Datatype	String				
Description	Indicates Other Details Type 5				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>65</td></tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLS6

Attribute	Description					
Name	OTHERDETLS6					
Datatype	String					
Description	Indicates Other Details 6					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	65
Restrictions	Description					
maxLength	65					

OTHERDETLSTYPE6

Attribute	Description					
Name	OTHERDETLSTYPE6					
Datatype	String					
Description	Indicates Other Details Type 6					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	65
Restrictions	Description					
maxLength	65					

Mis-Details

Attribute	Description							
Name	Mis-Details							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

BRANCH

Attribute	Description					
Name	BRANCH					
Datatype	String					
Description	Indicates Branch Code					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

CUSTNO

Attribute	Description						
Name	CUSTNO						
Datatype	String						
Description	Indicates Customer Number						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

MISGRP

Attribute	Description						
Name	MISGRP						
Datatype	String						
Description	Indicates MIS Group						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12	minLength	1
Restrictions	Description						
maxLength	12						
minLength	1						

REL_REF

Attribute	Description						
Name	REL_REF						
Datatype	String						
Description	Indicates Related Reference Number						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16	minLength	1
Restrictions	Description						
maxLength	16						
minLength	1						

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Indicates Related Account

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	16	
		minLength	1

MISHD

Attribute	Description	
Name	MISHD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description	Indicates Pool Code	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

REFRT

Attribute	Description	
Name	REFRT	
Datatype	Decimal	
Description	Indicates the Refinancing Rate	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	fractionDigits	15
	minInclusive	0
	totalDigits	26

REFRTTYPE

Attribute	Description	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	1	

REFXRT

Attribute	Description	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

CALCMETH

Attribute	Description	
Name	CALCMETH	
Datatype	Integer	
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6	
Attribute	Attribute	Description
	minOccurs	0

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

REFRTCD

Attribute	Description	
Name	REFRTCD	
Datatype	String	
Description	Indicates the Refinancing Rate Code	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>10</td></tr> </tbody> </table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

REFRTSPRD

Attribute	Description								
Name	REFRTSPRD								
Datatype	Decimal								
Description	Indicates the spread for the Refinance Rate Code								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0				
Attribute	Description								
minOccurs	0								
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>fractionDigits</td> <td>5</td> </tr> <tr> <td>minInclusive</td> <td>0</td> </tr> <tr> <td>totalDigits</td> <td>15</td> </tr> </tbody> </table>	Restrictions	Description	fractionDigits	5	minInclusive	0	totalDigits	15
Restrictions	Description								
fractionDigits	5								
minInclusive	0								
totalDigits	15								

FUNDMIS1

Attribute	Description						
Name	FUNDMIS1						
Datatype	String						
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS2

Attribute	Description						
Name	FUNDMIS2						
Datatype	String						
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS3

Attribute	Description
Name	FUNDMIS3

Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

FUNDMIS4

Attribute	Description	
Name	FUNDMIS4	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

FUNDMIS5

Attribute	Description	
Name	FUNDMIS5	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

FUNDMIS6

Attribute	Description	
Name	FUNDMIS6	
Datatype	String	
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS7

Attribute	Description						
Name	FUNDMIS7						
Datatype	String						
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS8

Attribute	Description						
Name	FUNDMIS8						
Datatype	String						
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS9

Attribute	Description						
Name	FUNDMIS9						
Datatype	String						
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS10

Attribute	Description
-----------	--------------------

Name	FUNDMIS10						
Datatype	String						
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

MISGRPCOMP

Attribute	Description				
Name	MISGRPCOMP				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

COMPMIS1

Attribute	Description						
Name	COMPMIS1						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS2

Attribute	Description						
Name	COMPMIS2						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS3

Attribute	Description						
Name	COMPMIS3						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS4

Attribute	Description						
Name	COMPMIS4						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS5

Attribute	Description						
Name	COMPMIS5						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	9	
	minLength	1	

COMPMIS7

Attribute	Description	
Name	COMPMIS7	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

COMPMIS8

Attribute	Description	
Name	COMPMIS8	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

COMPMIS9

Attribute	Description	
Name	COMPMIS9	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

COMPMS10

Attribute	Description						
Name	COMPMS10						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COSTCOD1

Attribute	Description						
Name	COSTCOD1						
Datatype	String						
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COSTCOD2

Attribute	Description						
Name	COSTCOD2						
Datatype	String						
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	9	
		minLength	1

COSTCOD4

Attribute	Description	
Name	COSTCOD4	
Datatype	String	
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
		minLength
		1

COSTCOD5

Attribute	Description	
Name	COSTCOD5	
Datatype	String	
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
		minLength
		1

LINKGRP

Attribute	Description	
Name	LINKGRP	
Datatype	String	
Description	Indicates the Link To Group	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	12
		minLength
		1

Attribute	Description				
Name	CCY				
Datatype	String				
Description	Indicates Currency				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

RTFLAG

Attribute	Description				
Name	RTFLAG				
Datatype	String				
Description	Indicates the refinancing rate that should be used for the transaction				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

PROCFLG

Attribute	Description				
Name	PROCFLG				
Datatype	String				
Description	Indicates ProcflgType R-Related Reference Number A-Related Account				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

TXNMIS1

Attribute	Description						
Name	TXNMIS1						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS2

Attribute	Description						
Name	TXNMIS2						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS3

Attribute	Description						
Name	TXNMIS3						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS4

Attribute	Description						
Name	TXNMIS4						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	9	
	minLength	1	

TXNMIS6

Attribute	Description	
Name	TXNMIS6	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

TXNMIS7

Attribute	Description	
Name	TXNMIS7	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

TXNMIS8

Attribute	Description	
Name	TXNMIS8	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

TXNMIS9

Attribute	Description						
Name	TXNMIS9						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS10

Attribute	Description						
Name	TXNMIS10						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS1LBL1

Attribute	Description						
Name	FUNDMIS1LBL1						
Datatype	String						
Description	Indicates the Fund to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS2LBL2

Attribute	Description				
Name	FUNDMIS2LBL2				
Datatype	String				
Description	Indicates the Fund to which the transaction is linked.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS3LBL3

Attribute	Description						
Name	FUNDMIS3LBL3						
Datatype	String						
Description	Indicates the Fund to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS4LBL4

Attribute	Description						
Name	FUNDMIS4LBL4						
Datatype	String						
Description	Indicates the Fund to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS5LBL5

Attribute	Description						
Name	FUNDMIS5LBL5						
Datatype	String						
Description	Indicates the Fund to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	9	
		minLength	1

FUNDMIS7LBL7

Attribute	Description	
Name	FUNDMIS7LBL7	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
		minLength
		1

FUNDMIS8LBL8

Attribute	Description	
Name	FUNDMIS8LBL8	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
		minLength
		1

FUNDMIS9LBL9

Attribute	Description	
Name	FUNDMIS9LBL9	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
		minLength
		1

FUNDMIS10LBL10

Attribute	Description	
------------------	--------------------	--

Name	FUNDMIS10LBL10							
Datatype	String							
Description	Indicates the Fund to which the transaction is linked.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>		Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description							
maxLength	9							
minLength	1							

COMPMIS1LBL1

Attribute	Description							
Name	COMPMIS1LBL1							
Datatype	String							
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>		Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description							
maxLength	9							
minLength	1							

COMPMIS2LBL2

Attribute	Description							
Name	COMPMIS2LBL2							
Datatype	String							
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>		Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description							
maxLength	9							
minLength	1							

COMPMIS3LBL3

Attribute	Description					
Name	COMPMIS3LBL3					
Datatype	String					
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS4LBL4

Attribute	Description						
Name	COMPMIS4LBL4						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS5LBL5

Attribute	Description						
Name	COMPMIS5LBL5						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS6LBL6

Attribute	Description						
Name	COMPMIS6LBL6						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS7LBL7

Attribute	Description
-----------	--------------------

Name	COMPMIS7LBL7	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9
	minLength	1

COMPMIS8LBL8

Attribute	Description	
Name	COMPMIS8LBL8	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9
	minLength	1

COMPMIS9LBL9

Attribute	Description	
Name	COMPMIS9LBL9	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9
	minLength	1

COMPMIS10LBL10

Attribute	Description	
Name	COMPMIS10LBL10	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS1LBL1

Attribute	Description						
Name	TXNMIS1LBL1						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS2LBL2

Attribute	Description						
Name	TXNMIS2LBL2						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS3LBL3

Attribute	Description						
Name	TXNMIS3LBL3						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS4LBL4

Attribute	Description
-----------	--------------------

Name	TXNMIS4LBL4	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9
	minLength	1

TXNMIS5LBL5

Attribute	Description	
Name	TXNMIS5LBL5	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9
	minLength	1

TXNMIS6LBL6

Attribute	Description	
Name	TXNMIS6LBL6	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9
	minLength	1

TXNMIS7LBL7

Attribute	Description	
Name	TXNMIS7LBL7	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS8LBL8

Attribute	Description						
Name	TXNMIS8LBL8						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS9LBL9

Attribute	Description						
Name	TXNMIS9LBL9						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS10LBL10

Attribute	Description						
Name	TXNMIS10LBL10						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

Udf-Details

Attribute	Description
-----------	--------------------

Name	Udf-Details							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded	
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

FUNCTIONID

Attribute	Description					
Name	FUNCTIONID					
Datatype	String					
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>8</td></tr> </tbody> </table>	Restrictions	Description	maxLength	8	
Restrictions	Description					
maxLength	8					

FIELD_NAME

Attribute	Description							
Name	FIELD_NAME							
Datatype	String							
Description	Indicates the User Defined Field Name							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	105	minLength	1	
Restrictions	Description							
maxLength	105							
minLength	1							

DATATYPE

Attribute	Description					
Name	DATATYPE					
Datatype	String					
Description	Indicates Data Type					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>15</td></tr> </tbody> </table>	Restrictions	Description	maxLength	15	
Restrictions	Description					
maxLength	15					

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value	

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	255	
		minLength	0

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value Type	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	2
		minLength
		0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
		maxOccurs
		unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	

Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description							
Name	FCUBS_WARNING_RESP							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

WARNING

Attribute	Description					
Name	WARNING					
Datatype						
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>		Attribute	Description	maxOccurs	unbounded
Attribute	Description					
maxOccurs	unbounded					

WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

2.6.4. Utility-Payment-Create-Res-PK-MSG.xsd

CREATEUPTRANSACTION_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Transaction-Details-PK
XREF
FCCREF
Transaction-Details-IO
XREF
PRD
INSTID
BILLNO
BILLDT
BAMT
BCCY
CUSTACNO
ACCCY
CONSNO
RATECODE
TXNCCY
OFSACNO
OFSACBRN
OFSACCCY

TXNDATE
TXNBRN
RATETYPE
CUSTBRN
SERVICEID
NARRATIVE
INSTRNO
TCYTOTCHGAMT
CUST_ID
DENMCCY1
DENMAMT1
DENMCCY2
DENMAMT2
CHGAMT1
CHGCCY1
CHGAMT2
CHGCCY2
CHGAMT3
CHGCCY3
CHGAMT4
CHGCCY4
CHGAMT5
CHGCCY5
Charge-Details
CHGCOMP
WAIVER
CHGAMT
CHGCCY
MISHEAD
TXNCODE
NETTINGIND
CHGGL

TYPE

LCYCHG

XRATE

TCYCHG

TCYXRATE

Denomination-Details

CDCCY

CDDENOM

VALUE

UNITS

INOUTIND

DENMVAL

Cheque-Details

SRNO

PAYBRN

CHQNO

STAT

EXPDT

BENFNAME

BENFADDR1

BENFADDR2

BENFADDR3

BENFADDR4

CRNO

ISB

OTHERDETLS1

OTHERDETLSTYPE1

OTHERDETLS2

OTHERDETLSTYPE2

OTHERDETLS3

OTHERDETLSTYPE3

OTHERDETLS4

OTHERDETLTYPE4

OTHERDETLS5

OTHERDETLTYPE5

OTHERDETLS6

OTHERDETLTYPE6

Mis-Details

BRANCH

CUSTNO

MISGRP

REL_REF

REL_ACC

MISHD

POOLCD

REFRT

REFRTTYPE

REFXRT

CALCMETH

MISGRPTXN

REFRTCD

REFRTSPRD

FUNDMIS1

FUNDMIS2

FUNDMIS3

FUNDMIS4

FUNDMIS5

FUNDMIS6

FUNDMIS7

FUNDMIS8

FUNDMIS9

FUNDMIS10

MISGRPCOMP

COMPMIS1

COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4

FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Udf-Details

FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

CREATEUPTRANSACTION_IOPK_RES

Attribute	Description
Name	CREATEUPTRANSACTION_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

ORACLE®

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>12</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	pattern	[a-zA-Z_0-9]*	

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This is the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	

Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>8</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	8						
pattern	[A-Z_0-9]*						

ACTION

Attribute	Description					
Name	ACTION					
Datatype	String					
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

MSGSTAT

Attribute	Description					
Name	MSGSTAT					
Datatype	String					
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr> </tbody> </table>		Restrictions	Description	enumeration	SUCCESS,WARNING,FAILURE
Restrictions	Description					
enumeration	SUCCESS,WARNING,FAILURE					

PASSWORD

Attribute	Description					
Name	PASSWORD					
Datatype	String					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

Restrictions	
	Restrictions
	maxLength
	[a-zA-Z_0-9=+]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	
Attribute	Description
	minOccurs
	0

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	
Attribute	Description
	minOccurs
	0
	maxOccurs
	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Transaction-Details-PK

Attribute	Description
Name	Transaction-Details-PK
Datatype	
Description	

XREF

Attribute	Description

ORACLE®

Name	XREF					
Datatype	String					
Description	Indicates External Reference Number					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>	Restrictions	Description	maxLength	20	
Restrictions	Description					
maxLength	20					

FCCREF

Attribute	Description					
Name	FCCREF					
Datatype	String					
Description	Indicates the Reference Number of the External System. Note: This field is mandatory only in case where FCCREF is not available.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z0-9]{16}	
Restrictions	Description					
pattern	[a-zA-Z0-9]{16}					

Transaction-Details-IO

Attribute	Description	
Name	Transaction-Details-IO	
Datatype		
Description		

XREF

Attribute	Description					
Name	XREF					
Datatype	String					
Description	Indicates External Reference Number					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>	Restrictions	Description	maxLength	20	
Restrictions	Description					
maxLength	20					

PRD

Attribute	Description							
Name	PRD							
Datatype	String							
Description	Indicates Product Code							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>4</td></tr> <tr> <td>pattern</td><td>[a-zA-Z0-9]{4}</td></tr> </tbody> </table>	Restrictions	Description	maxLength	4	pattern	[a-zA-Z0-9]{4}	
Restrictions	Description							
maxLength	4							
pattern	[a-zA-Z0-9]{4}							

INSTID

Attribute	Description	
Name	INSTID	
Datatype	String	
Description	Indicates Instrument Number	

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

BILLNO

Attribute	Description					
Name	BILLNO					
Datatype	String					
Description	Indicates Bill Number					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35	
Restrictions	Description					
maxLength	35					

BILLDT

Attribute	Description	
Name	BILLDT	
Datatype	Date	
Description	Indicates Bill Date	

BAMT

Attribute	Description							
Name	BAMT							
Datatype	Decimal							
Description	Indicates Bill Amount							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>fractionDigits</td> <td>3</td> </tr> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22	
Restrictions	Description							
fractionDigits	3							
totalDigits	22							

BCCY

Attribute	Description							
Name	BCCY							
Datatype	String							
Description	Indicates Bill Currency							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[A-Z]{3}</td> </tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[A-Z]{3}	
Restrictions	Description							
length	3							
pattern	[A-Z]{3}							

CUSTACNO

Attribute	Description					
Name	CUSTACNO					
Datatype	String					
Description	Indicates Customer Account Number					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> <tr> <td>pattern</td><td>[a-zA-Z0-9]*</td></tr> </tbody> </table>	Restrictions	Description	maxLength	20	pattern	[a-zA-Z0-9]*
Restrictions	Description						
maxLength	20						
pattern	[a-zA-Z0-9]*						

ACCCY

Attribute	Description						
Name	ACCCY						
Datatype	String						
Description	Indicates Account Currency						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[A-Z]{3}</td> </tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[A-Z]{3}
Restrictions	Description						
length	3						
pattern	[A-Z]{3}						

CONSNO

Attribute	Description				
Name	CONSNO				
Datatype	String				
Description	Indicates Consumer Serial Number				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

RATECODE

Attribute	Description				
Name	RATECODE				
Datatype	String				
Description	Indicates Rate Code Type				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>10</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

TXNCCY

Attribute	Description
Name	TXNCCY
Datatype	String
Description	Indicates Transaction currency

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[A-Z]{3}</td></tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[A-Z]{3}
Restrictions	Description						
length	3						
pattern	[A-Z]{3}						

OF SAC NO

Attribute	Description						
Name	OF SAC NO						
Datatype	String						
Description	Indicates Offset Account Number						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20	pattern	[a-zA-Z0-9]*
Restrictions	Description						
maxLength	20						
pattern	[a-zA-Z0-9]*						

OF SAC BRN

Attribute	Description						
Name	OF SAC BRN						
Datatype	String						
Description	Indicates Offset Account Branch						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

OF SAC CCY

Attribute	Description						
Name	OF SAC CCY						
Datatype	String						
Description	This specifies the Offset Account Currency.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[A-Z]{3}</td> </tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[A-Z]{3}
Restrictions	Description						
length	3						
pattern	[A-Z]{3}						

TXN DATE

Attribute	Description
Name	TXN DATE
Datatype	Date
Description	Indicates Transaction date

TXNBRN

Attribute	Description						
Name	TXNBRN						
Datatype	String						
Description	Indicates Transaction Branch						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

RATETYPE

Attribute	Description				
Name	RATETYPE				
Datatype	String				
Description	Indicates Rate Type				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

CUSTBRN

Attribute	Description						
Name	CUSTBRN						
Datatype	String						
Description	Indicates Customer Branch						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

SERVICEID

Attribute	Description				
Name	SERVICEID				
Datatype	String				
Description	Indicates Service Id				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

NARRATIVE

Attribute	Description	
Name	NARRATIVE	
Datatype	String	
Description	Indicates Narrative	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

INSTRNO

Attribute	Description	
Name	INSTRNO	
Datatype	String	
Description	Indicates Instrument Number	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6

TCYTOTCHGAMT

Attribute	Description	
Name	TCYTOTCHGAMT	
Datatype	Decimal	
Description	Indicates Total Charge in Transaction Currency.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

CUST_ID

Attribute	Description	
Name	CUST_ID	
Datatype	String	
Description	Indicates Customer Identification	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

Attribute	Description						
Name	DENMCCY1						
Datatype	String						
Description	Indicates Denomination Currency						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[A-Z]{3}</td></tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[A-Z]{3}
Restrictions	Description						
length	3						
pattern	[A-Z]{3}						

DENMAMT1

Attribute	Description						
Name	DENMAMT1						
Datatype	Decimal						
Description	It indicates Denomination Amount						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

DENMCCY2

Attribute	Description						
Name	DENMCCY2						
Datatype	String						
Description	Indicates Denomination Currency						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[A-Z]{3}</td></tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[A-Z]{3}
Restrictions	Description						
length	3						
pattern	[A-Z]{3}						

DENMAMT2

Attribute	Description				
Name	DENMAMT2				
Datatype	Decimal				
Description	It indicates Denomination Amount				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

CHGAMT1

Attribute	Description						
Name	CHGAMT1						
Datatype	Decimal						
Description	Indicates Charge Amount						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>fractionDigits</td> <td>3</td> </tr> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

CHGCCY1

Attribute	Description						
Name	CHGCCY1						
Datatype	String						
Description	Indicates Charge Currency						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[A-Z]{3}</td> </tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[A-Z]{3}
Restrictions	Description						
length	3						
pattern	[A-Z]{3}						

CHGAMT2

Attribute	Description						
Name	CHGAMT2						
Datatype	Decimal						
Description	Indicates Charge Amount						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>fractionDigits</td> <td>3</td> </tr> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

CHGCCY2

Attribute	Description
Name	CHGCCY2
Datatype	String
Description	Indicates Charge Currency

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	length	3	
	pattern	[A-Z]{3}	

CHGAMT3

Attribute	Description	
Name	CHGAMT3	
Datatype	Decimal	
Description	Indicates Charge Amount	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	fractionDigits	3
	totalDigits	22

CHGCCY3

Attribute	Description	
Name	CHGCCY3	
Datatype	String	
Description	Indicates Charge Currency	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	length	3
	pattern	[A-Z]{3}

CHGAMT4

Attribute	Description	
Name	CHGAMT4	
Datatype	Decimal	
Description	Indicates Charge Amount	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	fractionDigits	3
	totalDigits	22

CHGCCY4

Attribute	Description	
------------------	--------------------	--

Name	CHGCCY4	
Datatype	String	
Description	Indicates Charge Currency	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

CHGAMT5

Attribute	Description	
Name	CHGAMT5	
Datatype	Decimal	
Description	Indicates Charge Amount	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

CHGCCY5

Attribute	Description	
Name	CHGCCY5	
Datatype	String	
Description	Indicates Charge Currency	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

Charge-Details

Attribute	Description	
Name	Charge-Details	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

CHGCOMP

Attribute	Description

Name	CHGCOMP					
Datatype	String					
Description	Indicates Charge Components					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>255</td></tr> </tbody> </table>	Restrictions	Description	maxLength	255	
Restrictions	Description					
maxLength	255					

WAIVER

Attribute	Description					
Name	WAIVER					
Datatype	String					
Description	Indicates Charge Waiver.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	1	
Restrictions	Description					
maxLength	1					

CHGAMT

Attribute	Description							
Name	CHGAMT							
Datatype	Decimal							
Description	Indicates Charge Amount							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true	
Attribute	Description							
minOccurs	0							
nillable	true							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22	
Restrictions	Description							
fractionDigits	3							
totalDigits	22							

CHGCCY

Attribute	Description					
Name	CHGCCY					
Datatype	String					
Description	Indicates Charge Currency					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3	
Restrictions	Description					
maxLength	3					

MISHEAD

ORACLE®

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description	Indicates MIS Head	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TXNCODE

Attribute	Description	
Name	TXNCODE	
Datatype	String	
Description	Indicates Transaction Code	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

NETTINGIND

Attribute	Description	
Name	NETTINGIND	
Datatype	String	
Description	Netting Index	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

CHGGL

Attribute	Description	
Name	CHGGL	
Datatype	String	
Description	Charge General Ledger	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TYPE

ORACLE®

Attribute	Description					
Name	TYPE					
Datatype	String					
Description	Type					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>1</td></tr> </tbody> </table>		Restrictions	Description	maxLength	1
Restrictions	Description					
maxLength	1					

LCYCHG

Attribute	Description							
Name	LCYCHG							
Datatype	Decimal							
Description	Indicates Charge in Local Currency							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>		Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description							
fractionDigits	3							
totalDigits	22							

XRATE

Attribute	Description							
Name	XRATE							
Datatype	Decimal							
Description	Indicates Exchange rate							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>		Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description							
fractionDigits	3							
totalDigits	22							

TCYCHG

Attribute	Description							
Name	TCYCHG							
Datatype	Decimal							
Description	Charge In Transaction Currency							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>		Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description							
fractionDigits	3							
totalDigits	22							

TCYXRATE

Attribute	Description						
Name	TCYXRATE						
Datatype	Decimal						
Description	Transaction Currency Exchange rate						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

Denomination-Details

Attribute	Description						
Name	Denomination-Details						
Datatype							
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

CDCCY

Attribute	Description				
Name	CDCCY				
Datatype	String				
Description	Indicates Credit Currency				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

CDDENOM

Attribute	Description				
Name	CDDENOM				
Datatype	String				
Description	Credit Denomination				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

VALUE

Attribute	Description						
Name	VALUE						
Datatype	Decimal						
Description	Indicates Value						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

UNITS

Attribute	Description						
Name	UNITS						
Datatype	Decimal						
Description	Indicates Units						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>0</td></tr> <tr> <td>totalDigits</td><td>10</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	0	totalDigits	10
Restrictions	Description						
fractionDigits	0						
totalDigits	10						

INOUTIND

Attribute	Description				
Name	INOUTIND				
Datatype	String				
Description	IN OUT INDEX				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

DENMVAL

Attribute	Description						
Name	DENMVAL						
Datatype	Decimal						
Description	Indicates Denomination Value						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

Cheque-Details

Attribute	Description	
Name	Cheque-Details	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

SRNO

Attribute	Description	
Name	SRNO	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

PAYBRN

Attribute	Description	
Name	PAYBRN	
Datatype	String	
Description	Indicates Payable Branch	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

CHQNO

Attribute	Description	
Name	CHQNO	
Datatype	String	
Description	Indicates Cheque Number	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

STAT

Attribute	Description	

Name	STAT	
Datatype	String	
Description	Status of Cheque	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

EXPDT

Attribute	Description	
Name	EXPDT	
Datatype	Date	
Description	Indicates Expected Date	

BENFNAME

Attribute	Description	
Name	BENFNAME	
Datatype	String	
Description	Indicates Beneficiary Name	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

BENFADDR1

Attribute	Description	
Name	BENFADDR1	
Datatype	String	
Description	Beneficiary address Line 1	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

BENFADDR2

Attribute	Description	
Name	BENFADDR2	
Datatype	String	
Description	Beneficiary address Line 2	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	
	Restrictions
	maxLength

BENFADDR3

Attribute	Description
Name	BENFADDR3
Datatype	String
Description	Beneficiary address Line 3
Attribute	
Attribute	Description
	minOccurs
	0
Restrictions	
Restrictions	Description
	maxLength
	105

BENFADDR4

Attribute	Description
Name	BENFADDR4
Datatype	String
Description	Beneficiary address Line 4
Attribute	
Attribute	Description
	minOccurs
	0
Restrictions	
Restrictions	Description
	maxLength
	105

CRNO

Attribute	Description
Name	CRNO
Datatype	String
Description	Credit Number
Attribute	
Attribute	Description
	minOccurs
	0
Restrictions	
Restrictions	Description
	maxLength
	16

ISB

Attribute	Description
Name	ISB
Datatype	String
Description	
Attribute	
Attribute	Description
	minOccurs
	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

OTHERDETLS1

Attribute	Description				
Name	OTHERDETLS1				
Datatype	String				
Description	Indicates Other Details 1				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLS1TYPE1

Attribute	Description				
Name	OTHERDETLS1TYPE1				
Datatype	String				
Description	Indicates Other Details Type 1				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLS2

Attribute	Description				
Name	OTHERDETLS2				
Datatype	String				
Description	Indicates Other Details 2				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLS1TYPE2

Attribute	Description				
Name	OTHERDETLS1TYPE2				
Datatype	String				
Description	Indicates Other Details Type 1				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>65</td></tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLS3

Attribute	Description				
Name	OTHERDETLS3				
Datatype	String				
Description	Indicates Other Details 3				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLSTYPE3

Attribute	Description				
Name	OTHERDETLSTYPE3				
Datatype	String				
Description	Indicates Other Details Type 3				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLS4

Attribute	Description				
Name	OTHERDETLS4				
Datatype	String				
Description	Indicates Other Details 4				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLSTYPE4

Attribute	Description				
Name	OTHERDETLSTYPE4				
Datatype	String				
Description	Indicates Other Details Type 4				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>65</td></tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLS5

Attribute	Description				
Name	OTHERDETLS5				
Datatype	String				
Description	Indicates Other Details 5				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETTYPE5

Attribute	Description				
Name	OTHERDETTYPE5				
Datatype	String				
Description	Indicates Other Details Type 5				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLS6

Attribute	Description				
Name	OTHERDETLS6				
Datatype	String				
Description	Indicates Other Details 6				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETTYPE6

Attribute	Description				
Name	OTHERDETTYPE6				
Datatype	String				
Description	Indicates Other Details Type 6				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>65</td></tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

Mis-Details

Attribute	Description							
Name	Mis-Details							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

BRANCH

Attribute	Description							
Name	BRANCH							
Datatype	String							
Description	Indicates Branch Code							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description							
maxLength	9							
minLength	1							

CUSTNO

Attribute	Description							
Name	CUSTNO							
Datatype	String							
Description	Indicates Customer Number							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description							
maxLength	9							
minLength	1							

MISGRP

Attribute	Description					
Name	MISGRP					
Datatype	String					
Description	Indicates MIS Group					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>12</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	12	minLength	1
Restrictions	Description						
maxLength	12						
minLength	1						

REL_REF

Attribute	Description						
Name	REL_REF						
Datatype	String						
Description	Indicates Related Reference Number						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16	minLength	1
Restrictions	Description						
maxLength	16						
minLength	1						

REL_ACC

Attribute	Description						
Name	REL_ACC						
Datatype	String						
Description	Indicates Related Account						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16	minLength	1
Restrictions	Description						
maxLength	16						
minLength	1						

MISHD

Attribute	Description				
Name	MISHD				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

POOLCD

Attribute	Description				
Name	POOLCD				
Datatype	String				
Description	Indicates Pool Code				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

REFRT

Attribute	Description								
Name	REFRT								
Datatype	Decimal								
Description	Indicates the Refinancing Rate								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0				
Attribute	Description								
minOccurs	0								
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>fractionDigits</td> <td>15</td> </tr> <tr> <td>minInclusive</td> <td>0</td> </tr> <tr> <td>totalDigits</td> <td>26</td> </tr> </tbody> </table>	Restrictions	Description	fractionDigits	15	minInclusive	0	totalDigits	26
Restrictions	Description								
fractionDigits	15								
minInclusive	0								
totalDigits	26								

REFRTTYPE

Attribute	Description				
Name	REFRTTYPE				
Datatype	String				
Description	Indicates the Refinancing Rate Type				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

REFXRT

Attribute	Description						
Name	REFXRT						
Datatype	String						
Description	Indicates Refinancing Exchange Rate						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Integer
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 : 6

Attribute	
Attribute	Description
minOccurs	0

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attribute	
Attribute	Description
minOccurs	0

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attribute	
Attribute	Description
minOccurs	0
Restrictions	
Restrictions	Description
maxLength	10

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Decimal
Description	Indicates the spread for the Refinance Rate Code
Attribute	
Attribute	Description
minOccurs	0
Restrictions	
Restrictions	Description
fractionDigits	5
minInclusive	0
totalDigits	15

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attribute	
Attribute	Description
minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS2

Attribute	Description						
Name	FUNDMIS2						
Datatype	String						
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS3

Attribute	Description						
Name	FUNDMIS3						
Datatype	String						
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS4

Attribute	Description						
Name	FUNDMIS4						
Datatype	String						
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS5

Attribute	Description
-----------	--------------------

Name	FUNDMIS5							
Datatype	String							
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>		Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description							
maxLength	9							
minLength	1							

FUNDMIS6

Attribute	Description							
Name	FUNDMIS6							
Datatype	String							
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>		Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description							
maxLength	9							
minLength	1							

FUNDMIS7

Attribute	Description							
Name	FUNDMIS7							
Datatype	String							
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>		Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description							
maxLength	9							
minLength	1							

FUNDMIS8

Attribute	Description					
Name	FUNDMIS8					
Datatype	String					
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS9

Attribute	Description						
Name	FUNDMIS9						
Datatype	String						
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS10

Attribute	Description						
Name	FUNDMIS10						
Datatype	String						
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

MISGRPCOMP

Attribute	Description				
Name	MISGRPCOMP				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	9	
	minLength	1	

COMPMIS2

Attribute	Description	
Name	COMPMIS2	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

COMPMIS3

Attribute	Description	
Name	COMPMIS3	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

COMPMIS4

Attribute	Description	
Name	COMPMIS4	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

COMPMIS5

Attribute	Description						
Name	COMPMIS5						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS6

Attribute	Description						
Name	COMPMIS6						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS7

Attribute	Description						
Name	COMPMIS7						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	9	
	minLength	1	

COMPMIS9

Attribute	Description	
Name	COMPMIS9	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

COMPMIS10

Attribute	Description	
Name	COMPMIS10	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

COSTCOD1

Attribute	Description	
Name	COSTCOD1	
Datatype	String	
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

COSTCOD2

Attribute	Description						
Name	COSTCOD2						
Datatype	String						
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COSTCOD3

Attribute	Description						
Name	COSTCOD3						
Datatype	String						
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COSTCOD4

Attribute	Description						
Name	COSTCOD4						
Datatype	String						
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	9	
		minLength	1

LINKGRP

Attribute	Description	
Name	LINKGRP	
Datatype	String	
Description	Indicates the Link To Group	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	12
		minLength
		1

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description	Indicates Currency	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	3

RTFLAG

Attribute	Description	
Name	RTFLAG	
Datatype	String	
Description	Indicates the refinancing rate that should be used for the transaction	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	1

PROCFLG

Attribute	Description	
Name	PROCFLG	

Datatype	String					
Description	Indicates ProcflgType R-Related Reference Number A-Related Account					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1</td></tr> </tbody> </table>		Restrictions	Description	maxLength	1
Restrictions	Description					
maxLength	1					

TXNMIS1

Attribute	Description							
Name	TXNMIS1							
Datatype	String							
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>		Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description							
maxLength	9							
minLength	1							

TXNMIS2

Attribute	Description							
Name	TXNMIS2							
Datatype	String							
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>		Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description							
maxLength	9							
minLength	1							

TXNMIS3

Attribute	Description					
Name	TXNMIS3					
Datatype	String					
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS4

Attribute	Description						
Name	TXNMIS4						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS5

Attribute	Description						
Name	TXNMIS5						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS6

Attribute	Description						
Name	TXNMIS6						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS7

Attribute	Description
-----------	--------------------

Name	TXNMIS7							
Datatype	String							
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>		Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description							
maxLength	9							
minLength	1							

TXNMIS8

Attribute	Description							
Name	TXNMIS8							
Datatype	String							
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>		Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description							
maxLength	9							
minLength	1							

TXNMIS9

Attribute	Description							
Name	TXNMIS9							
Datatype	String							
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>		Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description							
maxLength	9							
minLength	1							

TXNMIS10

Attribute	Description					
Name	TXNMIS10					
Datatype	String					
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS1LBL1

Attribute	Description						
Name	FUNDMIS1LBL1						
Datatype	String						
Description	Indicates the Fund to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS2LBL2

Attribute	Description						
Name	FUNDMIS2LBL2						
Datatype	String						
Description	Indicates the Fund to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS3LBL3

Attribute	Description						
Name	FUNDMIS3LBL3						
Datatype	String						
Description	Indicates the Fund to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	9	
		minLength	1

FUNDMIS5LBL5

Attribute	Description	
Name	FUNDMIS5LBL5	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
		minLength
		1

FUNDMIS6LBL6

Attribute	Description	
Name	FUNDMIS6LBL6	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
		minLength
		1

FUNDMIS7LBL7

Attribute	Description	
Name	FUNDMIS7LBL7	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
		minLength
		1

FUNDMIS8LBL8

Attribute	Description	
------------------	--------------------	--

Name	FUNDMIS8LBL8							
Datatype	String							
Description	Indicates the Fund to which the transaction is linked.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0			
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1	
Restrictions	Description							
maxLength	9							
minLength	1							

FUNDMIS9LBL9

Attribute	Description							
Name	FUNDMIS9LBL9							
Datatype	String							
Description	Indicates the Fund to which the transaction is linked.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0			
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1	
Restrictions	Description							
maxLength	9							
minLength	1							

FUNDMIS10LBL10

Attribute	Description							
Name	FUNDMIS10LBL10							
Datatype	String							
Description	Indicates the Fund to which the transaction is linked.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0			
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1	
Restrictions	Description							
maxLength	9							
minLength	1							

COMPMIS1LBL1

Attribute	Description							
Name	COMPMIS1LBL1							
Datatype	String							
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0			
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1	
Restrictions	Description							
maxLength	9							
minLength	1							

COMPMIS2LBL2

Attribute	Description						
Name	COMPMIS2LBL2						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS3LBL3

Attribute	Description						
Name	COMPMIS3LBL3						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS4LBL4

Attribute	Description						
Name	COMPMIS4LBL4						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	9	
	minLength	1	

COMPMIS6LBL6

Attribute	Description	
Name	COMPMIS6LBL6	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

COMPMIS7LBL7

Attribute	Description	
Name	COMPMIS7LBL7	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

COMPMIS8LBL8

Attribute	Description	
Name	COMPMIS8LBL8	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

COMPMIS9LBL9

Attribute	Description						
Name	COMPMIS9LBL9						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS10LBL10

Attribute	Description						
Name	COMPMIS10LBL10						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS1LBL1

Attribute	Description						
Name	TXNMIS1LBL1						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	9	
	minLength	1	

TXNMIS3LBL3

Attribute	Description	
Name	TXNMIS3LBL3	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

TXNMIS4LBL4

Attribute	Description	
Name	TXNMIS4LBL4	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

TXNMIS5LBL5

Attribute	Description	
Name	TXNMIS5LBL5	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

TXNMIS6LBL6

Attribute	Description						
Name	TXNMIS6LBL6						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS7LBL7

Attribute	Description						
Name	TXNMIS7LBL7						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS8LBL8

Attribute	Description						
Name	TXNMIS8LBL8						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS9LBL9

Attribute	Description
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	9	
		minLength	1

TXNMIS10LBL10

Attribute	Description	
Name	TXNMIS10LBL10	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
		minLength
		1

Udf-Details

Attribute	Description	
Name	Udf-Details	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
		maxOccurs
		unbounded

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	8

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	

Datatype	String							
Description	Indicates the User Defined Field Name							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	105	minLength	1	
Restrictions	Description							
maxLength	105							
minLength	1							

DATATYPE

Attribute	Description					
Name	DATATYPE					
Datatype	String					
Description	Indicates Data Type					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>15</td></tr> </tbody> </table>	Restrictions	Description	maxLength	15	
Restrictions	Description					
maxLength	15					

FIELD_VALUE

Attribute	Description							
Name	FIELD_VALUE							
Datatype	String							
Description	Indicates the User Defined Field Value							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0			
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>255</td></tr> <tr> <td>minLength</td><td>0</td></tr> </tbody> </table>	Restrictions	Description	maxLength	255	minLength	0	
Restrictions	Description							
maxLength	255							
minLength	0							

VAL_TYPE

Attribute	Description							
Name	VAL_TYPE							
Datatype	String							
Description	Indicates Value Type							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0			
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>2</td></tr> <tr> <td>minLength</td><td>0</td></tr> </tbody> </table>	Restrictions	Description	maxLength	2	minLength	0	
Restrictions	Description							
maxLength	2							
minLength	0							

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		

Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	
	Description	
	maxOccurs	unbounded

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	
	Description	
	minOccurs	0
	maxOccurs	unbounded

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	
	Description	
	maxOccurs	unbounded

WCODE

Attribute	Description
Name	WCODE
Datatype	String

Description	
-------------	--

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

2.7.ReverseUPTransaction

2.7.1.Utility-Payment-Reverse-Req-Full-MSG.xsd

REVERSEUPTRANSACTION_FSFS_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Transaction-Details

XREF

REVERSEUPTRANSACTION_FSFS_REQ

Attribute	Description
Name	REVERSEUPTRANSACTION_FSFS_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

ORACLE®

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description	This is the user id in the Source system who is performing the action.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

FUNCTIONID

Attribute	Description				
Name	FUNCTIONID				
Datatype	String				
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>8</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	8						
pattern	[A-Z_0-9]*						

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>SUCCESS,WARNING,FAILURE</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	SUCCESS,WARNING,FAILURE
Restrictions	Description				
enumeration	SUCCESS,WARNING,FAILURE				

PASSWORD

Attribute	Description						
Name	PASSWORD						
Datatype	String						
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>128</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9=+/*]</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	128	pattern	[a-zA-Z_0-9=+/*]
Restrictions	Description						
maxLength	128						
pattern	[a-zA-Z_0-9=+/*]						

ADDL

Attribute	Description
Name	ADDL

ORACLE®

Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

FCUBS_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description		

Transaction-Details

Attribute	Description	
Name	Transaction-Details	
Datatype		
Description		

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description	Indicates External Reference Number	
Restrictions	Restrictions	Description
	maxLength	20

FCCREF

Attribute	Description	
-----------	-------------	--

Name	FCCREF				
Datatype	String				
Description	Indicates the Reference Number of the External System. Note: This field is mandatory only in case where FCCREF is not available.				
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr> </table>	Restrictions	Description	pattern	[a-zA-Z0-9]{16}
Restrictions	Description				
pattern	[a-zA-Z0-9]{16}				

2.7.2.Utility-Payment-Reverse-Req-MSG.xsd

REVERSEUPTRANSACTION_IOPK_REQ

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

XREF

FCCREF

REVERSEUPTRANSACTION_IOPK_REQ

Attribute	Description
Name	REVERSEUPTRANSACTION_IOPK_REQ
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	pattern	[a-zA-Z_0-9]*	

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description				
Name	SOURCE_OPERATION				
Datatype	String				
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description	This is the user id in the Source system who is performing the action.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	8	
		pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	enumeration	SUCCESS,WARNING,FAILURE

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	128
		pattern
		[a-zA-Z_0-9=+/*]

Attribute	Description				
Name	ADDL				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Transaction-Details-IO

Attribute	Description
Name	Transaction-Details-IO
Datatype	
Description	

XREF

Attribute	Description				
Name	XREF				
Datatype	String				
Description	Indicates External Reference Number				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

FCCREF

Attribute	Description				
Name	FCCREF				
Datatype	String				
Description	Indicates the Reference Number of the External System. Note: This field is mandatory only in case where FCCREF is not available.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z0-9]{16}
Restrictions	Description				
pattern	[a-zA-Z0-9]{16}				

2.7.3.Utility-Payment-Reverse-Res-Full-MSG.xsd

REVERSEUPTRANSACTION_FSFS_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

ORACLE®

FCUBS_BODY

Transaction-Details

XREF

FCCREF

PRD

INSTID

BILLNO

BILLDT

BAMT

BCCY

CUSTACNO

ACCCY

CONSNO

NETAMT

RATECODE

TXNCCY

OFSACNO

OFSACBRN

OFSACCCY

TXNDATE

TXNBRN

RATETYPE

MAKERID

MAKERSTAMP

CHECKERID

CHECKERSTAMP

AUTHSTAT

CONTSTAT

MODNO

RECORDSTAT

ONCEAUTH

CUSTBRN

ORACLE®

SERVICEID
NARRATIVE
INSTRNO
LCYTOTCHGAMT
TCYTOTCHGAMT
XRATE
CUST_ID
ACCTITLE
ACTAMT
DENMCCY1
DENMAMT1
DENMCCY2
DENMAMT2
CHGAMT1
CHGCCY1
CHGAMT2
CHGCCY2
CHGAMT3
CHGCCY3
CHGAMT4
CHGCCY4
CHGAMT5
CHGCCY5
SUBSYSTEMSTAT
Charge-Details

CHGCOMP
WAIVER
CHGAMT
CHGCCY
MISHEAD
TXNCODE
NETTINGIND

CHGGL

TYPE

LCYCHG

XRATE

TCYCHG

TCYXRATE

Denomination-Details

CDCCY

CDDENOM

VALUE

UNITS

INOUTIND

DENMVAL

Cheque-Details

SRNO

PAYBRN

CHQNO

STAT

EXPDT

BENFNAME

BENFADDR1

BENFADDR2

BENFADDR3

BENFADDR4

CRNO

ISB

OTHERDETLS1

OTHERDETLSTYPE1

OTHERDETLS2

OTHERDETLSTYPE2

OTHERDETLS3

OTHERDETLSTYPE3

OTHERDETLS4
OTHERDETLSTYPE4
OTHERDETLS5
OTHERDETLSTYPE5
OTHERDETLS6
OTHERDETLSTYPE6

Mis-Details

BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP

COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3

FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Udf-Details

FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

E CODE

E DESC

FCUBS_WARNING_RESP

WARNING

W CODE

W DESC

REVERSEUPTRANSACTION_FSFS_RES

Attribute	Description
Name	REVERSEUPTRANSACTION_FSFS_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td></tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description				
Name	CORRELID				
Datatype	String				
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>12</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

BRANCH

Attribute	Description
Name	BRANCH

Datatype	String						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

MODULEID

Attribute	Description				
Name	MODULEID				
Datatype	String				
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

SOURCE_USERID

Attribute	Description				
Name	SOURCE_USERID				
Datatype	String				
Description	This is the user id in the Source system who is performing the action.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description	This is the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>8</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	8						
pattern	[A-Z_0-9]*						

ACTION

Attribute	Description				
Name	ACTION				
Datatype	String				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr> </tbody> </table>	Restrictions	Description	enumeration	SUCCESS,WARNING,FAILURE
Restrictions	Description				
enumeration	SUCCESS,WARNING,FAILURE				

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
pattern		[a-zA-Z_0-9=+/-]*

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attribute	Attribute
	minOccurs

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attribute	Attribute
	minOccurs
	maxOccurs
	unbounded

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Transaction-Details

Attribute	Description
Name	Transaction-Details
Datatype	
Description	

XREF

Attribute	Description				
Name	XREF				
Datatype	String				
Description	Indicates External Reference Number				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

FCCREF

Attribute	Description				
Name	FCCREF				
Datatype	String				
Description	Indicates the Reference Number of the External System. Note: This field is mandatory only in case where FCCREF is not available.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z0-9]{16}
Restrictions	Description				
pattern	[a-zA-Z0-9]{16}				

PRD

Attribute	Description						
Name	PRD						
Datatype	String						
Description	Indicates Product Code						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>4</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]{4}</td></tr></tbody></table>	Restrictions	Description	maxLength	4	pattern	[a-zA-Z0-9]{4}
Restrictions	Description						
maxLength	4						
pattern	[a-zA-Z0-9]{4}						

INSTID

Attribute	Description				
Name	INSTID				
Datatype	String				
Description	Indicates Instrument Number				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

BILLNO

Attribute	Description				
Name	BILLNO				
Datatype	String				
Description	Indicates Bill Number				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

BILLDT

Attribute	Description
Name	BILLDT
Datatype	Date
Description	Indicates Bill Date

BAMT

Attribute	Description						
Name	BAMT						
Datatype	Decimal						
Description	Indicates Bill Amount						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>fractionDigits</td><td>3</td></tr><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

BCCY

Attribute	Description						
Name	BCCY						
Datatype	String						
Description	Indicates Bill Currency						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[A-Z]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[A-Z]{3}
Restrictions	Description						
length	3						
pattern	[A-Z]{3}						

CUSTACNO

Attribute	Description						
Name	CUSTACNO						
Datatype	String						
Description	Indicates Customer Account Number						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr><tr><td>pattern</td><td>[a-zA-Z0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	20	pattern	[a-zA-Z0-9]*
Restrictions	Description						
maxLength	20						
pattern	[a-zA-Z0-9]*						

ACCCY

Attribute	Description				
Name	ACCCY				
Datatype	String				
Description	Indicates Account Currency				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[A-Z]{3}</td></tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[A-Z]{3}
Restrictions	Description						
length	3						
pattern	[A-Z]{3}						

CONSNO

Attribute	Description					
Name	CONSNO					
Datatype	String					
Description	Indicates Consumer Serial Number					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	35
Restrictions	Description					
maxLength	35					

NETAMT

Attribute	Description							
Name	NETAMT							
Datatype	Decimal							
Description	Indicates Net Amount							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>fractionDigits</td> <td>3</td> </tr> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>		Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description							
fractionDigits	3							
totalDigits	22							

RATECODE

Attribute	Description					
Name	RATECODE					
Datatype	String					
Description	Indicates Rate Code Type					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>10</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	10
Restrictions	Description					
maxLength	10					

TXNCCY

Attribute	Description	
Name	TXNCCY	
Datatype	String	
Description	Indicates Transaction currency	

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[A-Z]{3}</td></tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[A-Z]{3}
Restrictions	Description						
length	3						
pattern	[A-Z]{3}						

OF SAC NO

Attribute	Description						
Name	OF SAC NO						
Datatype	String						
Description	Indicates Offset Account Number						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20	pattern	[a-zA-Z0-9]*
Restrictions	Description						
maxLength	20						
pattern	[a-zA-Z0-9]*						

OF SAC BRN

Attribute	Description						
Name	OF SAC BRN						
Datatype	String						
Description	Indicates Offset Account Branch						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

OF SAC CCY

Attribute	Description						
Name	OF SAC CCY						
Datatype	String						
Description	This specifies the Offset Account Currency.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[A-Z]{3}</td> </tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[A-Z]{3}
Restrictions	Description						
length	3						
pattern	[A-Z]{3}						

TXN DATE

Attribute	Description
Name	TXN DATE
Datatype	Date
Description	Indicates Transaction date

TXNBRN

Attribute	Description						
Name	TXNBRN						
Datatype	String						
Description	Indicates Transaction Branch						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

RATETYPE

Attribute	Description				
Name	RATETYPE				
Datatype	String				
Description	Indicates Rate Type				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

MAKERID

Attribute	Description				
Name	MAKERID				
Datatype	String				
Description	The User Id who has created\last modified the record.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

MAKERSTAMP

Attribute	Description				
Name	MAKERSTAMP				
Datatype	String				
Description	Indicates Date and Stamp when the User has created\last modified the record.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	The User Id who has Authorized the creation\modificaion of the record

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	12	

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.	
Attribute	Attribute	Description
	minOccurs	0

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status A - Authorized U - Un Authorized	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	enumeration	A,U

CONTSTAT

Attribute	Description	
Name	CONTSTAT	
Datatype	String	
Description	Indicates Contract Status	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	1

MODNO

Attribute	Description	
Name	MODNO	
Datatype	Decimal	
Description	Indicates Modification number i.e. the number of times the record has been modified.	

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	fractionDigits	0	
		totalDigits	10

RECORDSTAT

Attribute	Description	
Name	RECORDSTAT	
Datatype	String	
Description	Indicates Record Status O - Open C - Close	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	enumeration	O,C

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates whether the record is Authorized atleast Once.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	enumeration	Y,N

CUSTBRN

Attribute	Description	
Name	CUSTBRN	
Datatype	String	
Description	Indicates Customer Branch	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	length	3
		[a-zA-Z_0-9]{3}

SERVICEID

Attribute	Description	
Name	SERVICEID	

Datatype	String	
Description	Indicates Service Id	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	35

NARRATIVE

Attribute	Description	
Name	NARRATIVE	
Datatype	String	
Description	Indicates Narrative	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	255

INSTRNO

Attribute	Description	
Name	INSTRNO	
Datatype	String	
Description	Indicates Instrument Number	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	6

LCYTOTCHGAMT

Attribute	Description	
Name	LCYTOTCHGAMT	
Datatype	Decimal	
Description	Indicates Total Charge in Local Currency.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	fractionDigits	3
	totalDigits	22

TCYTOTCHGAMT

Attribute	Description	
-----------	-------------	--

Name	TCYTOTCHGAMT							
Datatype	Decimal							
Description	Indicates Total Charge in Transaction Currency.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>		Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description							
fractionDigits	3							
totalDigits	22							

XRATE

Attribute	Description							
Name	XRATE							
Datatype	Decimal							
Description	Indicates Exchange rate							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>12</td></tr> <tr> <td>totalDigits</td><td>24</td></tr> </tbody> </table>		Restrictions	Description	fractionDigits	12	totalDigits	24
Restrictions	Description							
fractionDigits	12							
totalDigits	24							

CUST_ID

Attribute	Description							
Name	CUST_ID							
Datatype	String							
Description	Indicates Customer Identification							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>pattern</td><td>[a-zA-Z0-9]*</td></tr> </tbody> </table>		Restrictions	Description	maxLength	9	pattern	[a-zA-Z0-9]*
Restrictions	Description							
maxLength	9							
pattern	[a-zA-Z0-9]*							

ACCTITLE

Attribute	Description					
Name	ACCTITLE					
Datatype	String					
Description	Indicates Account Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> </tbody> </table>		Restrictions	Description	maxLength	105
Restrictions	Description					
maxLength	105					

ACTAMT

ORACLE®

Attribute	Description						
Name	ACTAMT						
Datatype	Decimal						
Description	Indicates Actual Amount						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

DENMCCY1

Attribute	Description						
Name	DENMCCY1						
Datatype	String						
Description	Indicates Denomination Currency						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[A-Z]{3}</td></tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[A-Z]{3}
Restrictions	Description						
length	3						
pattern	[A-Z]{3}						

DENMAMT1

Attribute	Description						
Name	DENMAMT1						
Datatype	Decimal						
Description	It indicates Denomination Amount						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

DENMCCY2

Attribute	Description				
Name	DENMCCY2				
Datatype	String				
Description	Indicates Denomination Currency				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[A-Z]{3}</td></tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[A-Z]{3}
Restrictions	Description						
length	3						
pattern	[A-Z]{3}						

DENMAMT2

Attribute	Description						
Name	DENMAMT2						
Datatype	Decimal						
Description	It indicates Denomination Amount						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>fractionDigits</td> <td>3</td> </tr> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

CHGAMT1

Attribute	Description						
Name	CHGAMT1						
Datatype	Decimal						
Description	Indicates Charge Amount						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>fractionDigits</td> <td>3</td> </tr> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

CHGCCY1

Attribute	Description						
Name	CHGCCY1						
Datatype	String						
Description	Indicates Charge Currency						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[A-Z]{3}</td> </tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[A-Z]{3}
Restrictions	Description						
length	3						
pattern	[A-Z]{3}						

CHGAMT2

Attribute	Description
Name	CHGAMT2
Datatype	Decimal
Description	Indicates Charge Amount

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	fractionDigits	3	
	totalDigits	22	

CHGCCY2

Attribute	Description	
Name	CHGCCY2	
Datatype	String	
Description	Indicates Charge Currency	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	length	3
	pattern	[A-Z]{3}

CHGAMT3

Attribute	Description	
Name	CHGAMT3	
Datatype	Decimal	
Description	Indicates Charge Amount	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	fractionDigits	3
	totalDigits	22

CHGCCY3

Attribute	Description	
Name	CHGCCY3	
Datatype	String	
Description	Indicates Charge Currency	
Attribute	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	length	3
	pattern	[A-Z]{3}

CHGAMT4

Attribute	Description	
------------------	--------------------	--

Name	CHGAMT4							
Datatype	Decimal							
Description	Indicates Charge Amount							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>		Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description							
fractionDigits	3							
totalDigits	22							

CHGCCY4

Attribute	Description							
Name	CHGCCY4							
Datatype	String							
Description	Indicates Charge Currency							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[A-Z]{3}</td></tr> </tbody> </table>		Restrictions	Description	length	3	pattern	[A-Z]{3}
Restrictions	Description							
length	3							
pattern	[A-Z]{3}							

CHGAMT5

Attribute	Description							
Name	CHGAMT5							
Datatype	Decimal							
Description	Indicates Charge Amount							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>		Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description							
fractionDigits	3							
totalDigits	22							

CHGCCY5

Attribute	Description							
Name	CHGCCY5							
Datatype	String							
Description	Indicates Charge Currency							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[A-Z]{3}</td></tr> </tbody> </table>		Restrictions	Description	length	3	pattern	[A-Z]{3}
Restrictions	Description							
length	3							
pattern	[A-Z]{3}							

SUBSYSTEMSTAT

Attribute	Description				
Name	SUBSYSTEMSTAT				
Datatype	String				
Description	Indicates Subsystem Status				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

Charge-Details

Attribute	Description						
Name	Charge-Details						
Datatype							
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

CHGCOMP

Attribute	Description				
Name	CHGCOMP				
Datatype	String				
Description	Indicates Charge Components				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr></tbody></table>	Restrictions	Description	maxLength	255
Restrictions	Description				
maxLength	255				

WAIVER

Attribute	Description				
Name	WAIVER				
Datatype	String				
Description	Indicates Charge Waiver.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

CHGAMT

Attribute	Description

Name	CHGAMT							
Datatype	Decimal							
Description	Indicates Charge Amount							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0	nillable	true
Attribute	Description							
minOccurs	0							
nillable	true							
Restrictions								

CHGCCY

Attribute	Description					
Name	CHGCCY					
Datatype	String					
Description	Indicates Charge Currency					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions						

MISHEAD

Attribute	Description					
Name	MISHEAD					
Datatype	String					
Description	Indicates MIS Head					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions						

TXNCODE

Attribute	Description					
Name	TXNCODE					
Datatype	String					
Description	Indicates Transaction Code					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions						

NETTINGIND

ORACLE®

Attribute	Description	
Name	NETTINGIND	
Datatype	String	
Description	Netting Index	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

CHGGL

Attribute	Description	
Name	CHGGL	
Datatype	String	
Description	Charge General Ledger	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TYPE

Attribute	Description	
Name	TYPE	
Datatype	String	
Description	Type	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

LCYCHG

Attribute	Description	
Name	LCYCHG	
Datatype	Decimal	
Description	Indicates Charge in Local Currency	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

XRATE

ORACLE®

Attribute	Description						
Name	XRATE						
Datatype	Decimal						
Description	Indicates Exchange rate						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

TCYCHG

Attribute	Description						
Name	TCYCHG						
Datatype	Decimal						
Description	Charge In Transaction Currency						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

TCYXRATE

Attribute	Description						
Name	TCYXRATE						
Datatype	Decimal						
Description	Transaction Currency Exchange rate						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

Denomination-Details

Attribute	Description						
Name	Denomination-Details						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

Attribute	Description				
Name	CDCCY				
Datatype	String				
Description	Indicates Credit Currency				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

CDDENOM

Attribute	Description				
Name	CDDENOM				
Datatype	String				
Description	Credit Denomination				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>50</td></tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

VALUE

Attribute	Description						
Name	VALUE						
Datatype	Decimal						
Description	Indicates Value						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

UNITS

Attribute	Description						
Name	UNITS						
Datatype	Decimal						
Description	Indicates Units						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>0</td></tr> <tr> <td>totalDigits</td><td>10</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	0	totalDigits	10
Restrictions	Description						
fractionDigits	0						
totalDigits	10						

INOUTIND

Attribute	Description				
Name	INOUTIND				
Datatype	String				
Description	IN OUT INDEX				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

DENMVAL

Attribute	Description						
Name	DENMVAL						
Datatype	Decimal						
Description	Indicates Denomination Value						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>fractionDigits</td><td>3</td></tr> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	fractionDigits	3	totalDigits	22
Restrictions	Description						
fractionDigits	3						
totalDigits	22						

Cheque-Details

Attribute	Description						
Name	Cheque-Details						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

SRNO

Attribute	Description				
Name	SRNO				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>16</td></tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

PAYBRN

Attribute	Description

Name	PAYBRN					
Datatype	String					
Description	Indicates Payable Branch					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3	
Restrictions	Description					
maxLength	3					

CHQNO

Attribute	Description					
Name	CHQNO					
Datatype	String					
Description	Indicates Cheque Number					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>16</td></tr> </tbody> </table>	Restrictions	Description	maxLength	16	
Restrictions	Description					
maxLength	16					

STAT

Attribute	Description					
Name	STAT					
Datatype	String					
Description	Status of Cheque					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>4</td></tr> </tbody> </table>	Restrictions	Description	maxLength	4	
Restrictions	Description					
maxLength	4					

EXPDT

Attribute	Description	
Name	EXPDT	
Datatype	Date	
Description	Indicates Expected Date	

BENFNAME

Attribute	Description					
Name	BENFNAME					
Datatype	String					
Description	Indicates Beneficiary Name					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					

Restrictions					
	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>105</td></tr> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

BENFADDR1

Attribute	Description				
Name	BENFADDR1				
Datatype	String				
Description	Beneficiary address Line 1				
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>105</td></tr> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

BENFADDR2

Attribute	Description				
Name	BENFADDR2				
Datatype	String				
Description	Beneficiary address Line 2				
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>105</td></tr> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

BENFADDR3

Attribute	Description				
Name	BENFADDR3				
Datatype	String				
Description	Beneficiary address Line 3				
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>105</td></tr> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

BENFADDR4

Attribute	Description				
Name	BENFADDR4				
Datatype	String				
Description	Beneficiary address Line 4				
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> </tbody> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

CRNO

Attribute	Description				
Name	CRNO				
Datatype	String				
Description	Credit Number				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16
Restrictions	Description				
maxLength	16				

ISB

Attribute	Description				
Name	ISB				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9
Restrictions	Description				
maxLength	9				

OTHERDETLS1

Attribute	Description				
Name	OTHERDETLS1				
Datatype	String				
Description	Indicates Other Details 1				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLSTYPE1

Attribute	Description				
Name	OTHERDETLSTYPE1				
Datatype	String				
Description	Indicates Other Details Type 1				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>65</td></tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLS2

Attribute	Description				
Name	OTHERDETLS2				
Datatype	String				
Description	Indicates Other Details 2				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLSTYPE2

Attribute	Description				
Name	OTHERDETLSTYPE2				
Datatype	String				
Description	Indicates Other Details Type 1				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLS3

Attribute	Description				
Name	OTHERDETLS3				
Datatype	String				
Description	Indicates Other Details 3				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLSTYPE3

Attribute	Description				
Name	OTHERDETLSTYPE3				
Datatype	String				
Description	Indicates Other Details Type 3				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>65</td></tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLS4

Attribute	Description				
Name	OTHERDETLS4				
Datatype	String				
Description	Indicates Other Details 4				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETTYPE4

Attribute	Description				
Name	OTHERDETTYPE4				
Datatype	String				
Description	Indicates Other Details Type 4				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLS5

Attribute	Description				
Name	OTHERDETLS5				
Datatype	String				
Description	Indicates Other Details 5				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETTYPE5

Attribute	Description				
Name	OTHERDETTYPE5				
Datatype	String				
Description	Indicates Other Details Type 5				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>65</td></tr> </tbody> </table>	Restrictions	Description	maxLength	65
Restrictions	Description				
maxLength	65				

OTHERDETLS6

Attribute	Description					
Name	OTHERDETLS6					
Datatype	String					
Description	Indicates Other Details 6					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	65
Restrictions	Description					
maxLength	65					

OTHERDETLSTYPE6

Attribute	Description					
Name	OTHERDETLSTYPE6					
Datatype	String					
Description	Indicates Other Details Type 6					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>65</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	65
Restrictions	Description					
maxLength	65					

Mis-Details

Attribute	Description							
Name	Mis-Details							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

BRANCH

Attribute	Description					
Name	BRANCH					
Datatype	String					
Description	Indicates Branch Code					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

CUSTNO

Attribute	Description						
Name	CUSTNO						
Datatype	String						
Description	Indicates Customer Number						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

MISGRP

Attribute	Description						
Name	MISGRP						
Datatype	String						
Description	Indicates MIS Group						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12	minLength	1
Restrictions	Description						
maxLength	12						
minLength	1						

REL_REF

Attribute	Description						
Name	REL_REF						
Datatype	String						
Description	Indicates Related Reference Number						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>16</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	16	minLength	1
Restrictions	Description						
maxLength	16						
minLength	1						

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Indicates Related Account

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	16	
		minLength	1

MISHD

Attribute	Description	
Name	MISHD	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description	Indicates Pool Code	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

REFRT

Attribute	Description	
Name	REFRT	
Datatype	Decimal	
Description	Indicates the Refinancing Rate	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	fractionDigits	15
	minInclusive	0
	totalDigits	26

REFRTTYPE

Attribute	Description	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	1	

REFXRT

Attribute	Description	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

CALCMETH

Attribute	Description	
Name	CALCMETH	
Datatype	Integer	
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6	
Attribute	Attribute	Description
	minOccurs	0

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attribute	Attribute	Description
	minOccurs	0

REFRTCD

Attribute	Description	
Name	REFRTCD	
Datatype	String	
Description	Indicates the Refinancing Rate Code	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>10</td></tr> </tbody> </table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

REFRTSPRD

Attribute	Description								
Name	REFRTSPRD								
Datatype	Decimal								
Description	Indicates the spread for the Refinance Rate Code								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0				
Attribute	Description								
minOccurs	0								
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>fractionDigits</td> <td>5</td> </tr> <tr> <td>minInclusive</td> <td>0</td> </tr> <tr> <td>totalDigits</td> <td>15</td> </tr> </tbody> </table>	Restrictions	Description	fractionDigits	5	minInclusive	0	totalDigits	15
Restrictions	Description								
fractionDigits	5								
minInclusive	0								
totalDigits	15								

FUNDMIS1

Attribute	Description						
Name	FUNDMIS1						
Datatype	String						
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS2

Attribute	Description						
Name	FUNDMIS2						
Datatype	String						
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS3

Attribute	Description
Name	FUNDMIS3

Datatype	String							
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.							
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0			
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </table>	Restrictions	Description	maxLength	9	minLength	1	
Restrictions	Description							
maxLength	9							
minLength	1							

FUNDMIS4

Attribute	Description							
Name	FUNDMIS4							
Datatype	String							
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.							
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0			
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </table>	Restrictions	Description	maxLength	9	minLength	1	
Restrictions	Description							
maxLength	9							
minLength	1							

FUNDMIS5

Attribute	Description							
Name	FUNDMIS5							
Datatype	String							
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.							
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0			
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </table>	Restrictions	Description	maxLength	9	minLength	1	
Restrictions	Description							
maxLength	9							
minLength	1							

FUNDMIS6

Attribute	Description					
Name	FUNDMIS6					
Datatype	String					
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.					
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS7

Attribute	Description						
Name	FUNDMIS7						
Datatype	String						
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS8

Attribute	Description						
Name	FUNDMIS8						
Datatype	String						
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS9

Attribute	Description						
Name	FUNDMIS9						
Datatype	String						
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS10

Attribute	Description
-----------	--------------------

Name	FUNDMIS10						
Datatype	String						
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

MISGRPCOMP

Attribute	Description				
Name	MISGRPCOMP				
Datatype	String				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

COMPMIS1

Attribute	Description						
Name	COMPMIS1						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS2

Attribute	Description						
Name	COMPMIS2						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS3

Attribute	Description						
Name	COMPMIS3						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS4

Attribute	Description						
Name	COMPMIS4						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS5

Attribute	Description						
Name	COMPMIS5						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	9	
	minLength	1	

COMPMIS7

Attribute	Description	
Name	COMPMIS7	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

COMPMIS8

Attribute	Description	
Name	COMPMIS8	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

COMPMIS9

Attribute	Description	
Name	COMPMIS9	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

COMPMS10

Attribute	Description						
Name	COMPMS10						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COSTCOD1

Attribute	Description						
Name	COSTCOD1						
Datatype	String						
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COSTCOD2

Attribute	Description						
Name	COSTCOD2						
Datatype	String						
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	9	
		minLength	1

COSTCOD4

Attribute	Description	
Name	COSTCOD4	
Datatype	String	
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
		minLength
		1

COSTCOD5

Attribute	Description	
Name	COSTCOD5	
Datatype	String	
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
		minLength
		1

LINKGRP

Attribute	Description	
Name	LINKGRP	
Datatype	String	
Description	Indicates the Link To Group	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	12
		minLength
		1

Attribute	Description				
Name	CCY				
Datatype	String				
Description	Indicates Currency				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

RTFLAG

Attribute	Description				
Name	RTFLAG				
Datatype	String				
Description	Indicates the refinancing rate that should be used for the transaction				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

PROCFLG

Attribute	Description				
Name	PROCFLG				
Datatype	String				
Description	Indicates ProcflgType R-Related Reference Number A-Related Account				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	1
Restrictions	Description				
maxLength	1				

TXNMIS1

Attribute	Description						
Name	TXNMIS1						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS2

Attribute	Description						
Name	TXNMIS2						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS3

Attribute	Description						
Name	TXNMIS3						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS4

Attribute	Description						
Name	TXNMIS4						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	9	
	minLength	1	

TXNMIS6

Attribute	Description	
Name	TXNMIS6	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

TXNMIS7

Attribute	Description	
Name	TXNMIS7	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

TXNMIS8

Attribute	Description	
Name	TXNMIS8	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
	minLength	1

TXNMIS9

Attribute	Description						
Name	TXNMIS9						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS10

Attribute	Description						
Name	TXNMIS10						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS1LBL1

Attribute	Description						
Name	FUNDMIS1LBL1						
Datatype	String						
Description	Indicates the Fund to which the transaction is linked.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>9</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS2LBL2

Attribute	Description				
Name	FUNDMIS2LBL2				
Datatype	String				
Description	Indicates the Fund to which the transaction is linked.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS3LBL3

Attribute	Description						
Name	FUNDMIS3LBL3						
Datatype	String						
Description	Indicates the Fund to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS4LBL4

Attribute	Description						
Name	FUNDMIS4LBL4						
Datatype	String						
Description	Indicates the Fund to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS5LBL5

Attribute	Description						
Name	FUNDMIS5LBL5						
Datatype	String						
Description	Indicates the Fund to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	9	
		minLength	1

FUNDMIS7LBL7

Attribute	Description	
Name	FUNDMIS7LBL7	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
		minLength
		1

FUNDMIS8LBL8

Attribute	Description	
Name	FUNDMIS8LBL8	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
		minLength
		1

FUNDMIS9LBL9

Attribute	Description	
Name	FUNDMIS9LBL9	
Datatype	String	
Description	Indicates the Fund to which the transaction is linked.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	9
		minLength
		1

FUNDMIS10LBL10

Attribute	Description	
------------------	--------------------	--

Name	FUNDMIS10LBL10							
Datatype	String							
Description	Indicates the Fund to which the transaction is linked.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description							
maxLength	9							
minLength	1							

COMPMIS1LBL1

Attribute	Description							
Name	COMPMIS1LBL1							
Datatype	String							
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description							
maxLength	9							
minLength	1							

COMPMIS2LBL2

Attribute	Description							
Name	COMPMIS2LBL2							
Datatype	String							
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description							
maxLength	9							
minLength	1							

COMPMIS3LBL3

Attribute	Description					
Name	COMPMIS3LBL3					
Datatype	String					
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS4LBL4

Attribute	Description						
Name	COMPMIS4LBL4						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS5LBL5

Attribute	Description						
Name	COMPMIS5LBL5						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS6LBL6

Attribute	Description						
Name	COMPMIS6LBL6						
Datatype	String						
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

COMPMIS7LBL7

Attribute	Description
-----------	--------------------

Name	COMPMIS7LBL7	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9
	minLength	1

COMPMIS8LBL8

Attribute	Description	
Name	COMPMIS8LBL8	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9
	minLength	1

COMPMIS9LBL9

Attribute	Description	
Name	COMPMIS9LBL9	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9
	minLength	1

COMPMIS10LBL10

Attribute	Description	
Name	COMPMIS10LBL10	
Datatype	String	
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS1LBL1

Attribute	Description						
Name	TXNMIS1LBL1						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS2LBL2

Attribute	Description						
Name	TXNMIS2LBL2						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS3LBL3

Attribute	Description						
Name	TXNMIS3LBL3						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS4LBL4

Attribute	Description
-----------	--------------------

Name	TXNMIS4LBL4	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9
	minLength	1

TXNMIS5LBL5

Attribute	Description	
Name	TXNMIS5LBL5	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9
	minLength	1

TXNMIS6LBL6

Attribute	Description	
Name	TXNMIS6LBL6	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	9
	minLength	1

TXNMIS7LBL7

Attribute	Description	
Name	TXNMIS7LBL7	
Datatype	String	
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>9</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS8LBL8

Attribute	Description						
Name	TXNMIS8LBL8						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS9LBL9

Attribute	Description						
Name	TXNMIS9LBL9						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

TXNMIS10LBL10

Attribute	Description						
Name	TXNMIS10LBL10						
Datatype	String						
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>9</td> </tr> <tr> <td>minLength</td> <td>1</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	9	minLength	1
Restrictions	Description						
maxLength	9						
minLength	1						

Udf-Details

Attribute	Description
-----------	--------------------

Name	Udf-Details							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded	
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

FUNCTIONID

Attribute	Description					
Name	FUNCTIONID					
Datatype	String					
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>8</td></tr> </tbody> </table>	Restrictions	Description	maxLength	8	
Restrictions	Description					
maxLength	8					

FIELD_NAME

Attribute	Description							
Name	FIELD_NAME							
Datatype	String							
Description	Indicates the User Defined Field Name							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	105	minLength	1	
Restrictions	Description							
maxLength	105							
minLength	1							

DATATYPE

Attribute	Description					
Name	DATATYPE					
Datatype	String					
Description	Indicates Data Type					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>15</td></tr> </tbody> </table>	Restrictions	Description	maxLength	15	
Restrictions	Description					
maxLength	15					

FIELD_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value	

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	maxLength	255	
		minLength	0

VAL_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value Type	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	2
		minLength
		0

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
		maxOccurs
		unbounded

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

Attribute	Description	
Name	EDESC	

Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description							
Name	FCUBS_WARNING_RESP							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

WARNING

Attribute	Description					
Name	WARNING					
Datatype						
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>		Attribute	Description	maxOccurs	unbounded
Attribute	Description					
maxOccurs	unbounded					

WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

2.7.4. Utility-Payment-Reverse-Res-PK-MSG.xsd

REVERSEUPTRANSACTION_IOPK_RES

FCUBS_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE_OPERATION

SOURCE_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

FCUBS_BODY

Transaction-Details-PK

XREF

FCCREF

Transaction-Details-IO

XREF

FCCREF

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

REVERSEUPTRANSACTION_IOPK_RES

Attribute	Description
Name	REVERSEUPTRANSACTION_IOPK_RES
Datatype	
Description	

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

MSGID

Attribute	Description				
Name	MSGID				
Datatype	String				
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	pattern	[a-zA-Z_0-9]*	

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	Attribute	Description
	minOccurs	0

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	

Attribute	Attribute		Description
	nillable	true	
Restrictions	Restrictions		Description
	pattern	[a-zA-Z_0-9]*	

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	Attribute	Description
	nillable	true
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description	This is the user id in the Source system who is performing the action.	
Attribute	Attribute	Description
	minOccurs	0

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute	Attribute		Description
	minOccurs	0	
Restrictions	Restrictions		Description
	pattern	[a-zA-Z_0-9]*	

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	
	maxLength	8
	pattern	[A-Z_0-9]*

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>SUCCESS,WARNING,FAILURE</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	SUCCESS,WARNING,FAILURE
Restrictions	Description				
enumeration	SUCCESS,WARNING,FAILURE				

PASSWORD

Attribute	Description						
Name	PASSWORD						
Datatype	String						
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>128</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9+=/]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	128	pattern	[a-zA-Z_0-9+=/]*
Restrictions	Description						
maxLength	128						
pattern	[a-zA-Z_0-9+=/]*						

ADDL

Attribute	Description				
Name	ADDL				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

Transaction-Details-PK

Attribute	Description
Name	Transaction-Details-PK
Datatype	
Description	

XREF

Attribute	Description				
Name	XREF				
Datatype	String				
Description	Indicates External Reference Number				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

FCCREF

Attribute	Description				
Name	FCCREF				
Datatype	String				
Description	Indicates the Reference Number of the External System. Note: This field is mandatory only in case where FCCREF is not available.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z0-9]{16}
Restrictions	Description				
pattern	[a-zA-Z0-9]{16}				

Transaction-Details-IO

Attribute	Description
Name	Transaction-Details-IO
Datatype	

Description	
-------------	--

XREF

Attribute	Description					
Name	XREF					
Datatype	String					
Description	Indicates External Reference Number					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>20</td></tr> </tbody> </table>	Restrictions	Description	maxLength	20	
Restrictions	Description					
maxLength	20					

FCCREF

Attribute	Description					
Name	FCCREF					
Datatype	String					
Description	Indicates the Reference Number of the External System. Note: This field is mandatory only in case where FCCREF is not available.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z0-9]{16}</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z0-9]{16}	
Restrictions	Description					
pattern	[a-zA-Z0-9]{16}					

FCUBS_ERROR_RESP

Attribute	Description							
Name	FCUBS_ERROR_RESP							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded	
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

ERROR

Attribute	Description					
Name	ERROR					
Datatype						
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded	
Attribute	Description					
maxOccurs	unbounded					

ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

EDESC

ORACLE®

Attribute	Description
Name	EDESC
Datatype	String
Description	

FCUBS_WARNING_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

Gateway Documentation - FCUBSUPService
[February] [2016]

Oracle Financial services Software Limited
Oracle Park
Off western Express Highway
Goregaon(East)
Mumbai,Maharashtra 400 063
India

Worldwide Inquiries:

Phone: +91 22 6718 3000
Fax:+91 22 6718 3001
www.oracle.com/financialservices/

Copyright © [2013], [2016], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.