Gateway Documentation - Customer Service

Oracle FLEXCUBE Universal Banking Release 11.3.83.02.0

Release FCUBS_11.3.2.0.0LA

[April] [2014]

ORACLE
FINANCIAL SERVICES

ORACLE

Table Of Contents

1. BACKGROUND 1
2. FCUBSCustomerService 2
2.1. AmountBlocksAuthorize 2
2.1.1. CA-AmountBlocksAuthorize-Req-Full-MSG.xsd 2
2.1.2. CA-AmountBlocksAuthorize-Req-IO-MSG.xsd 14
2.1.3. CA-AmountBlocksAuthorize-Res-Full-MSG.xsd 21
2.1.4. CA-AmountBlocksAuthorize-Res-PK-MSG.xsd 41
2.2. AmountBlocksClose 61
2.2.1. CA-AmountBlocksClose-Req-Full-MSG.xsd 61
2.2.2. CA-AmountBlocksClose-Req-IO-MSG.xsd 73
2.2.3. CA-AmountBlocksClose-Res-Full-MSG.xsd 80
2.2.4. CA-AmountBlocksClose-Res-PK-MSG.xsd 100
2.3. AmountBlocksDelete 120
2.3.1. CA-AmountBlocksDelete-Req-Full-MSG.xsd 120
2.3.2. CA-AmountBlocksDelete-Req-IO-MSG.xsd 132
2.3.3. CA-AmountBlocksDelete-Res-Full-MSG.xsd 138
2.3.4. CA-AmountBlocksDelete-Res-PK-MSG.xsd 151
2.4. AmountBlocksModify 159
2.4.1. CA-AmountBlocksModify-Req-Full-MSG.xsd 159
2.4.2. CA-AmountBlocksModify-Req-IO-MSG.xsd 171
2.4.3. CA-AmountBlocksModify-Res-Full-MSG.xsd 180
2.4.4. CA-AmountBlocksModify-Res-PK-MSG.xsd 200
2.5. AmountBlocksNew 220
2.5.1. CA-AmountBlocksNew-Req-Full-MSG.xsd 220
2.5.2. CA-AmountBlocksNew-Req-IO-MSG.xsd 232
2.5.3. CA-AmountBlocksNew-Res-Full-MSG.xsd 244
2.5.4. CA-AmountBlocksNew-Res-PK-MSG.xsd 264
2.6. AmountBlocksQuery 284
2.6.1. CA-AmountBlocksQuery-Req-IO-MSG.xsd 284
2.6.2. CA-AmountBlocksQuery-Res-Full-MSG.xsd 290
2.7. AmountBlocksReopen 310
2.7.1. CA-AmountBlocksReopen-Req-Full-MSG.xsd 310
2.7.2. CA-AmountBlocksReopen-Req-IO-MSG.xsd 322
2.7.3. CA-AmountBlocksReopen-Res-Full-MSG.xsd 329
2.7.4. CA-AmountBlocksReopen-Res-PK-MSG.xsd 349
2.8. CreateAccountStructure 369
2.8.1. CA-CreateAccountStructure-Req-Full-MSG.xsd 369
2.8.2. CA-CreateAccountStructure-Req-IO-MSG.xsd 380
2.8.3. CA-CreateAccountStructure-Res-Full-MSG.xsd 388
2.8.4. CA-CreateAccountStructure-Res-PK-MSG.xsd 401
2.9. ModifyAccountStructure 411
2.9.1. CA-ModifyAccountStructure-Req-Full-MSG.xsd 411
2.9.2. CA-ModifyAccountStructure-Req-IO-MSG.xsd 422
2.9.3. CA-ModifyAccountStructure-Res-Full-MSG.xsd 430
2.9.4. CA-ModifyAccountStructure-Res-PK-MSG.xsd 443
2.10. QueryAccountStructure 453
2.10.1. CA-QueryAccountStructure-Req-IO-MSG.xsd 453
2.10.2. CA-QueryAccountStructure-Res-Full-MSG.xsd 459
2.11. AuthorizeCustomer 472
2.11.1. ST-AuthorizeCustomer-Req-Full-MSG.xsd 472
2.11.2. ST-AuthorizeCustomer-Req-IO-MSG.xsd 568
2.11.3. ST-AuthorizeCustomer-Res-Full-MSG.xsd 575
2.11.4. ST-AuthorizeCustomer-Res-PK-MSG.xsd 673
2.12. AuthorizeTDAmountBlock 682

ORACLE

2.12.1. ST-AuthorizeTDAmountBlock-Req-Full-MSG.xsd *682*
2.12.2. ST-AuthorizeTDAmountBlock-Req-IO-MSG.xsd *693*
2.12.3. ST-AuthorizeTDAmountBlock-Res-Full-MSG.xsd *699*
2.12.4. ST-AuthorizeTDAmountBlock-Res-PK-MSG.xsd *712*
2.13. CloseCustomer **721**
2.13.1. ST-CloseCustomer-Req-Full-MSG.xsd *721*
2.13.2. ST-CloseCustomer-Req-IO-MSG.xsd *817*
2.13.3. ST-CloseCustomer-Res-Full-MSG.xsd *824*
2.13.4. ST-CloseCustomer-Res-PK-MSG.xsd *922*
2.14. CloseTDAmountBlock **931**
2.14.1. ST-CloseTDAmountBlock-Req-Full-MSG.xsd *931*
2.14.2. ST-CloseTDAmountBlock-Req-IO-MSG.xsd *942*
2.14.3. ST-CloseTDAmountBlock-Res-Full-MSG.xsd *949*
2.14.4. ST-CloseTDAmountBlock-Res-PK-MSG.xsd *962*
2.15. CreateCustomer **971**
2.15.1. ST-CreateCustomer-Req-Full-MSG.xsd *971*
2.15.2. ST-CreateCustomer-Req-IO-MSG.xsd *1067*
2.15.3. ST-CreateCustomer-Res-Full-MSG.xsd *1154*
2.15.4. ST-CreateCustomer-Res-PK-MSG.xsd *1252*
2.16. CreateTDAmountBlock **1341**
2.16.1. ST-CreateTDAmountBlock-Req-Full-MSG.xsd *1341*
2.16.2. ST-CreateTDAmountBlock-Req-IO-MSG.xsd *1352*
2.16.3. ST-CreateTDAmountBlock-Res-Full-MSG.xsd *1361*
2.16.4. ST-CreateTDAmountBlock-Res-PK-MSG.xsd *1374*
2.17. DeleteCustomer **1385**
2.17.1. ST-DeleteCustomer-Req-Full-MSG.xsd *1385*
2.17.2. ST-DeleteCustomer-Req-IO-MSG.xsd *1481*
2.17.3. ST-DeleteCustomer-Res-Full-MSG.xsd *1487*
2.17.4. ST-DeleteCustomer-Res-PK-MSG.xsd *1585*
2.18. DeleteTDAmountBlock **1594**
2.18.1. ST-DeleteTDAmountBlock-Req-Full-MSG.xsd *1594*
2.18.2. ST-DeleteTDAmountBlock-Req-IO-MSG.xsd *1605*
2.18.3. ST-DeleteTDAmountBlock-Res-Full-MSG.xsd *1611*
2.18.4. ST-DeleteTDAmountBlock-Res-PK-MSG.xsd *1624*
2.19. ModifyCustomer **1633**
2.19.1. ST-ModifyCustomer-Req-Full-MSG.xsd *1633*
2.19.2. ST-ModifyCustomer-Req-IO-MSG.xsd *1729*
2.19.3. ST-ModifyCustomer-Res-Full-MSG.xsd *1821*
2.19.4. ST-ModifyCustomer-Res-PK-MSG.xsd *1919*
2.20. ModifyTDAmountBlock **2014**
2.20.1. ST-ModifyTDAmountBlock-Req-Full-MSG.xsd *2014*
2.20.2. ST-ModifyTDAmountBlock-Req-IO-MSG.xsd *2025*
2.20.3. ST-ModifyTDAmountBlock-Res-Full-MSG.xsd *2034*
2.20.4. ST-ModifyTDAmountBlock-Res-PK-MSG.xsd *2047*
2.21. QueryCustomer **2058**
2.21.1. ST-QueryCustomer-Req-IO-MSG.xsd *2058*
2.21.2. ST-QueryCustomer-Res-Full-MSG.xsd *2065*
2.22. QueryCustomerStat **2164**
2.22.1. ST-QueryCustomerStat-Req-IO-MSG.xsd *2164*
2.22.2. ST-QueryCustomerStat-Res-Full-MSG.xsd *2171*
2.23. QueryTDAmountBlock **2192**
2.23.1. ST-QueryTDAmountBlock-Req-IO-MSG.xsd *2192*
2.23.2. ST-QueryTDAmountBlock-Res-Full-MSG.xsd *2198*
2.24. QueryUIDCustomer **2212**
2.24.1. ST-QueryUIDCustomer-Req-IO-MSG.xsd *2212*
2.24.2. ST-QueryUIDCustomer-Res-Full-MSG.xsd *2219*
2.25. ReopenCustomer **2228**

2.25.1. ST-ReopenCustomer-Req-Full-MSG.xsd *2228*
2.25.2. ST-ReopenCustomer-Req-IO-MSG.xsd *2324*
2.25.3. ST-ReopenCustomer-Res-Full-MSG.xsd *2331*
2.25.4. ST-ReopenCustomer-Res-PK-MSG.xsd *2429*
2.26. ReopenTDAmountBlock **2438**
2.26.1. ST-ReopenTDAmountBlock-Req-Full-MSG.xsd *2438*
2.26.2. ST-ReopenTDAmountBlock-Req-IO-MSG.xsd *2449*
2.26.3. ST-ReopenTDAmountBlock-Res-Full-MSG.xsd *2456*
2.26.4. ST-ReopenTDAmountBlock-Res-PK-MSG.xsd *2469*

1.BACKGROUND

Integration of different applications and solutions is a key area in today's systems. A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data.The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs.
The integration needs supported by the Gateway can be broadly categorized from the perspective of the Gateway as follows:

1. Inbound application integration – used when any external system needs to add, modify or query information within FLEXCUBE UBS
2. Outbound application integration– used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS
The following sections provide detailed XSD documentation of all operations available in FCUBSCustomerService of Core-Module

2.FCUBSCustomerService

Customer ServiceCustomer Service

2.1.AmountBlocksAuthorize

Authorization of Customer Account Amount Blocks

2.1.1.CA-AmountBlocksAuthorize-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-Full*
    - *ACC*
    - *AMTBLKNO*
    - *AMT*
    - *EXPDATE*
    - *REM*
    - *ABLKTYPE*
    - *REFERENCENO*
    - *HPCODE*
    - *EFFDATE*
    - *HOLDDESC*
    - *BRANCH*
    - *MAKER*

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String

Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Amount-Blocks-Full

Attribute	Description
Name	Amount-Blocks-Full
Datatype	
Description	Include amount blocks Full details.

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account Number.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date

Attributes	Attribute	Description
	minOccurs	0

TOP

REM

Attribute	Description	
Name	REM	
Datatype	String	
Description	Indicates the Remarks.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ABLKTYPE

Attribute	Description	
Name	ABLKTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,S,P,E,A,C,B,H

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	40

TOP

HPCODE

Attribute	Description	
Name	HPCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HOLDDESC

Attribute	Description
Name	HOLDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Specifies whether the record is authorized atleast once
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	User Defined Fields details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description

Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.1.2.CA-AmountBlocksAuthorize-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-IO*
    - *AMTBLKNO*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration — Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	minOccurs: 0; nillable: true
Restrictions	pattern: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	minOccurs: 0; nillable: true
Restrictions	pattern: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	maxLength: 12; pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	

Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	Include amount blocks PK ACR type details.

TOP

Amount-Blocks-IO

Attribute	Description
Name	Amount-Blocks-IO
Datatype	
Description	This gives the Amount block PK request

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MODNO

Attribute	Description

Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

2.1.3.CA-AmountBlocksAuthorize-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Amount-Blocks-PK*
      - *AMTBLKNO*
    - *Amount-Blocks-IO*
      - *BRANCH*
      - *ACC*
      - *AMTBLKNO*
      - *AMT*
      - *EFFDATE*
      - *EXPDATE*
      - *REM*
      - *HOLD_CODE*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Amount-Blocks-Full

ACC

AMTBLKNO

AMT

EXPDATE

REM

ABLKTYPE

REFERENCENO

HPCODE

EFFDATE

HOLDDESC

BRANCH

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Amount-Blocks-PK

Attribute	Description
Name	Amount-Blocks-PK
Datatype	
Description	Include amount blocks Pk type details.

TOP

AMTBLKNO

Attribute	Description	
Name	AMTBLKNO	
Datatype	String	
Description	Indicates the Amount Block Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Amount-Blocks-IO

Attribute	Description
Name	Amount-Blocks-IO
Datatype	
Description	Include amount blocks IO type details.

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates the Account Number.	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTBLKNO

Attribute	Description

Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

HOLD_CODE

Attribute	Description
Name	HOLD_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting Date time of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description

Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Specifies whether the record is authorized atleast once
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	User Defined Fields details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Amount-Blocks-Full

Attribute	Description
Name	Amount-Blocks-Full
Datatype	
Description	Include amount blocks Full details.

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account Number.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	Attribute: minOccurs — Description: 0

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date
Attributes	Attribute: minOccurs — Description: 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ABLKTYPE

Attribute	Description
Name	ABLKTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: F,S,P,E,A,C,B,H

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 40

TOP

HPCODE

Attribute	**Description**
Name	HPCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

EFFDATE

Attribute	**Description**
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HOLDDESC

Attribute	**Description**
Name	HOLDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Specifies whether the record is authorized atleast once

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	User Defined Fields details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 255
	minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include error type details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include warning type details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.1.4.CA-AmountBlocksAuthorize-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Amount-Blocks-PK*
      - *AMTBLKNO*
    - *Amount-Blocks-IO*
      - *BRANCH*
      - *ACC*
      - *AMTBLKNO*
      - *AMT*
      - *EFFDATE*
      - *EXPDATE*
      - *REM*
      - *HOLD_CODE*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Amount-Blocks-Full

ACC

AMTBLKNO

AMT

EXPDATE

REM

ABLKTYPE

REFERENCENO

HPCODE

EFFDATE

HOLDDESC

BRANCH

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Amount-Blocks-PK

Attribute	Description
Name	Amount-Blocks-PK
Datatype	
Description	Include amount blocks PK type details.

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Amount-Blocks-IO

Attribute	Description
Name	Amount-Blocks-IO
Datatype	
Description	Include amount blocks IO type details.

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account Number.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTBLKNO

Attribute	Description

Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

HOLD_CODE

Attribute	Description
Name	HOLD_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting Date time of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description

Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Specifies whether the record is authorized atleast once
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	User Defined Fields details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Amount-Blocks-Full

Attribute	Description
Name	Amount-Blocks-Full
Datatype	
Description	Include amount blocks Full type details.

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account Number.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	Attribute: minOccurs — Description: 0

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date
Attributes	Attribute: minOccurs — Description: 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ABLKTYPE

Attribute	Description
Name	ABLKTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: F,S,P,E,A,C,B,H

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 40

TOP

HPCODE

Attribute	**Description**
Name	HPCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

EFFDATE

Attribute	**Description**
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HOLDDESC

Attribute	**Description**
Name	HOLDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Specifies whether the record is authorized atleast once

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	User Defined Fields details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 255
	minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include error type details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include warning type details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.2.AmountBlocksClose

Closure of Customer Account Amount Blocks

2.2.1.CA-AmountBlocksClose-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-Full*
    - *ACC*
    - *AMTBLKNO*
    - *AMT*
    - *EXPDATE*
    - *REM*
    - *ABLKTYPE*
    - *REFERENCENO*
    - *HPCODE*
    - *EFFDATE*
    - *HOLDDESC*
    - *BRANCH*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO

TXNSTAT

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Amount-Blocks-Full

Attribute	Description
Name	Amount-Blocks-Full
Datatype	
Description	Include amount blocks Full details.

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account Number.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date

Attributes	Attribute	Description
	minOccurs	0

TOP

REM

Attribute	Description	
Name	REM	
Datatype	String	
Description	Indicates the Remarks.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ABLKTYPE

Attribute	Description	
Name	ABLKTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,S,P,E,A,C,B,H

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	40

TOP

HPCODE

Attribute	Description	
Name	HPCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HOLDDESC

Attribute	Description
Name	HOLDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Specifies whether the record is authorized atleast once
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	User Defined Fields details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description

Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.2.2.CA-AmountBlocksClose-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-IO*
    - *AMTBLKNO*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration — Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0 Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0 Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	Restrictions: maxLength — Description: 12 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	

Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Amount-Blocks-IO

Attribute	Description
Name	Amount-Blocks-IO
Datatype	
Description	Include amount blocks PK ACR type details.

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MODNO

Attribute	Description

Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

2.2.3.CA-AmountBlocksClose-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Amount-Blocks-PK*
      - *AMTBLKNO*
    - *Amount-Blocks-IO*
      - *BRANCH*
      - *ACC*
      - *AMTBLKNO*
      - *AMT*
      - *EFFDATE*
      - *EXPDATE*
      - *REM*
      - *HOLD_CODE*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Amount-Blocks-Full

ACC

AMTBLKNO

AMT

EXPDATE

REM

ABLKTYPE

REFERENCENO

HPCODE

EFFDATE

HOLDDESC

BRANCH

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Amount-Blocks-PK

Attribute	Description
Name	Amount-Blocks-PK
Datatype	
Description	Include amount blocks PK type details.

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Amount-Blocks-IO

Attribute	Description
Name	Amount-Blocks-IO
Datatype	
Description	Include amount blocks IO type details.

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account Number.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTBLKNO

Attribute	Description

Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

HOLD_CODE

Attribute	Description
Name	HOLD_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting Date time of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description

Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Specifies whether the record is authorized atleast once
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	User Defined Fields details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Amount-Blocks-Full

Attribute	Description
Name	Amount-Blocks-Full
Datatype	
Description	Include amount blocks Full details.

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account Number.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	Attribute: minOccurs — Description: 0

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date
Attributes	Attribute: minOccurs — Description: 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ABLKTYPE

Attribute	Description
Name	ABLKTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: F,S,P,E,A,C,B,H

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 40

TOP

HPCODE

Attribute	**Description**
Name	HPCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

EFFDATE

Attribute	**Description**
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

HOLDDESC

Attribute	**Description**
Name	HOLDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Specifies whether the record is authorized atleast once

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	User Defined Fields details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 255
	minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include error type details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include warning type details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.2.4.CA-AmountBlocksClose-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Amount-Blocks-PK*
      - *AMTBLKNO*
    - *Amount-Blocks-IO*
      - *BRANCH*
      - *ACC*
      - *AMTBLKNO*
      - *AMT*
      - *EFFDATE*
      - *EXPDATE*
      - *REM*
      - *HOLD_CODE*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Amount-Blocks-Full

ACC

AMTBLKNO

AMT

EXPDATE

REM

ABLKTYPE

REFERENCENO

HPCODE

EFFDATE

HOLDDESC

BRANCH

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Amount-Blocks-PK

Attribute	Description
Name	Amount-Blocks-PK
Datatype	
Description	Include amount blocks PK type details.

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Amount-Blocks-IO

Attribute	Description
Name	Amount-Blocks-IO
Datatype	
Description	Include amount blocks IO type details.

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account Number.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTBLKNO

Attribute	Description

Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

HOLD_CODE

Attribute	Description
Name	HOLD_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting Date time of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description

Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Specifies whether the record is authorized atleast once
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	User Defined Fields details
Attributes	Attribute: Description maxOccurs: unbounded minOccurs: 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description maxLength: 8 pattern: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	Restrictions: Description maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Amount-Blocks-Full

Attribute	Description
Name	Amount-Blocks-Full
Datatype	
Description	Include amount blocks full details.

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account Number.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates the Amount.	
Attributes	Attribute	Description
	minOccurs	0

TOP

EXPDATE

Attribute	Description	
Name	EXPDATE	
Datatype	Date	
Description	Indicates the Expiry Date	
Attributes	Attribute	Description
	minOccurs	0

TOP

REM

Attribute	Description	
Name	REM	
Datatype	String	
Description	Indicates the Remarks.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TOP

ABLKTYPE

Attribute	Description	
Name	ABLKTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	F,S,P,E,A,C,B,H

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 40

TOP

HPCODE

Attribute	**Description**
Name	HPCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

EFFDATE

Attribute	**Description**
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HOLDDESC

Attribute	**Description**
Name	HOLDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Specifies whether the record is authorized atleast once

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	User Defined Fields details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 255
	minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include error type details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include warning type details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.3.AmountBlocksDelete

Deletion of Customer Account Amount Blocks

2.3.1.CA-AmountBlocksDelete-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-Full*
    - *ACC*
    - *AMTBLKNO*
    - *AMT*
    - *EXPDATE*
    - *REM*
    - *ABLKTYPE*
    - *REFERENCENO*
    - *HPCODE*
    - *EFFDATE*
    - *HOLDDESC*
    - *BRANCH*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO

TXNSTAT

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Amount-Blocks-Full

Attribute	Description
Name	Amount-Blocks-Full
Datatype	
Description	Include amount blocks Full details.

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account Number.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date

Attributes	Attribute	Description
	minOccurs	0

TOP

REM

Attribute	Description	
Name	REM	
Datatype	String	
Description	Indicates the Remarks.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ABLKTYPE

Attribute	Description	
Name	ABLKTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,S,P,E,A,C,B,H

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	40

TOP

HPCODE

Attribute	Description	
Name	HPCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HOLDDESC

Attribute	Description
Name	HOLDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Specifies whether the record is authorized atleast once
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	User Defined Fields details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description

Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.3.2.CA-AmountBlocksDelete-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-IO*
    - *AMTBLKNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration — Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0 Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0 Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	Restrictions: maxLength — Description: 12 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	

Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	Include amount blocks Pk type details.

TOP

Amount-Blocks-IO

Attribute	Description
Name	Amount-Blocks-IO
Datatype	
Description	This gives the Amount Block PK request

TOP

AMTBLKNO

Attribute	Description	
Name	AMTBLKNO	
Datatype	String	
Description	Indicates the Amount Block Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

2.3.3.CA-AmountBlocksDelete-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-Full*
    - *ACC*
    - *AMTBLKNO*
    - *AMT*
    - *EXPDATE*
    - *REM*
    - *ABLKTYPE*
    - *REFERENCENO*
    - *HPCODE*
    - *EFFDATE*
    - *HOLDDESC*
    - *BRANCH*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

RECSTAT

ONCEAUTH

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Amount-Blocks-Full

Attribute	Description
Name	Amount-Blocks-Full
Datatype	
Description	Include amount blocks Full details.

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates the Account Number.	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTBLKNO

Attribute	Description	
Name	AMTBLKNO	
Datatype	String	
Description	Indicates the Amount Block Number.	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates the Amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXPDATE

Attribute	Description

Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REM

Attribute	**Description**
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ABLKTYPE

Attribute	**Description**
Name	ABLKTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,S,P,E,A,C,B,H

TOP

REFERENCENO

Attribute	**Description**
Name	REFERENCENO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 40

TOP

HPCODE

Attribute	**Description**
Name	HPCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	15

TOP

EFFDATE

Attribute	Description	
Name	EFFDATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

HOLDDESC

Attribute	Description	
Name	HOLDDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description

Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Specifies whether the record is authorized atleast once
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include error type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include warning type details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.3.4.CA-AmountBlocksDelete-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-PK*
    - *AMTBLKNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Amount-Blocks-PK

Attribute	Description
Name	Amount-Blocks-PK
Datatype	
Description	Include amount blocks PK type details.

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Include error type details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Include warning type details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.4.AmountBlocksModify

Modification of Customer Account Amount Blocks

2.4.1.CA-AmountBlocksModify-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-Full*
    - *ACC*
    - *AMTBLKNO*
    - *AMT*
    - *EXPDATE*
    - *REM*
    - *ABLKTYPE*
    - *REFERENCENO*
    - *HPCODE*
    - *EFFDATE*
    - *HOLDDESC*
    - *BRANCH*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO

TXNSTAT

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0 nillable: true
Restrictions	**Restrictions** / **Description** pattern: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength: 12 pattern: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length: 3 pattern: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0 nillable: true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

ORACLE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Amount-Blocks-Full

Attribute	Description
Name	Amount-Blocks-Full
Datatype	
Description	Include amount blocks Full type details.

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account Number.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date

Attributes	Attribute	Description
	minOccurs	0

TOP

REM

Attribute	Description	
Name	REM	
Datatype	String	
Description	Indicates the Remarks.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ABLKTYPE

Attribute	Description	
Name	ABLKTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,S,P,E,A,C,B,H

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	40

TOP

HPCODE

Attribute	Description	
Name	HPCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

HOLDDESC

Attribute	Description
Name	HOLDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Specifies whether the record is authorized atleast once
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	User Defined Fields details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description

Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.4.2.CA-AmountBlocksModify-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-IO*
    - *BRANCH*
    - *ACC*
    - *AMTBLKNO*
    - *AMT*
    - *EFFDATE*
    - *EXPDATE*
    - *REM*
    - *HPCODE*
    - *MODNO*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Amount-Blocks-IO

Attribute	Description
Name	Amount-Blocks-IO
Datatype	
Description	Include amount blocks IO type details.

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account Number.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

HPCODE

Attribute	Description
Name	HPCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	

Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

2.4.3.CA-AmountBlocksModify-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Amount-Blocks-PK*
      - *AMTBLKNO*
    - *Amount-Blocks-IO*
      - *BRANCH*
      - *ACC*
      - *AMTBLKNO*
      - *AMT*
      - *EFFDATE*
      - *EXPDATE*
      - *REM*
      - *HOLD_CODE*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Amount-Blocks-Full

ACC

AMTBLKNO

AMT

EXPDATE

REM

ABLKTYPE

REFERENCENO

HPCODE

EFFDATE

HOLDDESC

BRANCH

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Amount-Blocks-PK

Attribute	Description
Name	Amount-Blocks-PK
Datatype	
Description	Include amount blocks PK type details.

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Amount-Blocks-IO

Attribute	Description
Name	Amount-Blocks-IO
Datatype	
Description	Include amount blocks IO type details.

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account Number.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTBLKNO

Attribute	Description

Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

HOLD_CODE

Attribute	Description
Name	HOLD_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting Date time of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description

Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Specifies whether the record is authorized atleast once
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	User Defined Fields details
Attributes	Attribute: Description maxOccurs: unbounded minOccurs: 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description maxLength: 8 pattern: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	Restrictions: Description maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Amount-Blocks-Full

Attribute	Description
Name	Amount-Blocks-Full
Datatype	
Description	Include amount blocks Full type details.

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account Number.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates the Amount.	
Attributes	Attribute	Description
	minOccurs	0

TOP

EXPDATE

Attribute	Description	
Name	EXPDATE	
Datatype	Date	
Description	Indicates the Expiry Date	
Attributes	Attribute	Description
	minOccurs	0

TOP

REM

Attribute	Description	
Name	REM	
Datatype	String	
Description	Indicates the Remarks.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TOP

ABLKTYPE

Attribute	Description	
Name	ABLKTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	F,S,P,E,A,C,B,H

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 40

TOP

HPCODE

Attribute	**Description**
Name	HPCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

EFFDATE

Attribute	**Description**
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HOLDDESC

Attribute	**Description**
Name	HOLDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Specifies whether the record is authorized atleast once

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	User Defined Fields details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 255
	minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include error type details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include warning type details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.4.4.CA-AmountBlocksModify-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Amount-Blocks-PK*
      - *AMTBLKNO*
    - *Amount-Blocks-IO*
      - *BRANCH*
      - *ACC*
      - *AMTBLKNO*
      - *AMT*
      - *EFFDATE*
      - *EXPDATE*
      - *REM*
      - *HOLD_CODE*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Amount-Blocks-Full

ACC

AMTBLKNO

AMT

EXPDATE

REM

ABLKTYPE

REFERENCENO

HPCODE

EFFDATE

HOLDDESC

BRANCH

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Amount-Blocks-PK

Attribute	Description
Name	Amount-Blocks-PK
Datatype	
Description	Include amount blocks PK type details.

TOP

AMTBLKNO

Attribute	Description	
Name	AMTBLKNO	
Datatype	String	
Description	Indicates the Amount Block Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Amount-Blocks-IO

Attribute	Description
Name	Amount-Blocks-IO
Datatype	
Description	Include amount blocks IO type details.

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates the Account Number.	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTBLKNO

Attribute	Description

Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

HOLD_CODE

Attribute	Description
Name	HOLD_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting Date time of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description

Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	**Description**
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	Specifies whether the record is authorized atleast once
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	User Defined Fields details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Amount-Blocks-Full

Attribute	Description
Name	Amount-Blocks-Full
Datatype	
Description	Include amount blocks Full details.

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account Number.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates the Amount.	
Attributes	Attribute	Description
	minOccurs	0

TOP

EXPDATE

Attribute	Description	
Name	EXPDATE	
Datatype	Date	
Description	Indicates the Expiry Date	
Attributes	Attribute	Description
	minOccurs	0

TOP

REM

Attribute	Description	
Name	REM	
Datatype	String	
Description	Indicates the Remarks.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TOP

ABLKTYPE

Attribute	Description	
Name	ABLKTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	F,S,P,E,A,C,B,H

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 40

TOP

HPCODE

Attribute	**Description**
Name	HPCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

EFFDATE

Attribute	**Description**
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HOLDDESC

Attribute	**Description**
Name	HOLDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Specifies whether the record is authorized atleast once

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	User Defined Fields details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 255
	minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include error type details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include warning type details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.5.AmountBlocksNew

Input of Customer Account Amount Blocks

2.5.1.CA-AmountBlocksNew-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-Full*
    - *ACC*
    - *AMTBLKNO*
    - *AMT*
    - *EXPDATE*
    - *REM*
    - *ABLKTYPE*
    - *REFERENCENO*
    - *HPCODE*
    - *EFFDATE*
    - *HOLDDESC*
    - *BRANCH*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO

TXNSTAT

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Amount-Blocks-Full

Attribute	Description
Name	Amount-Blocks-Full
Datatype	
Description	include amount-Blocks full type details.

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account Number.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date

Attributes	Attribute	Description
	minOccurs	0

TOP

REM

Attribute	Description	
Name	REM	
Datatype	String	
Description	Indicates the Remarks.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ABLKTYPE

Attribute	Description	
Name	ABLKTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,S,P,E,A,C,B,H

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	40

TOP

HPCODE

Attribute	Description	
Name	HPCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HOLDDESC

Attribute	Description
Name	HOLDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Specifies whether the record is authorized atleast once
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	User Defined Fields details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description

Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.5.2.CA-AmountBlocksNew-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-IO*
    - *BRANCH*
    - *ACC*
    - *AMTBLKNO*
    - *AMT*
    - *EFFDATE*
    - *EXPDATE*
    - *REM*
    - *HOLD_CODE*
    - *MAKERID*
    - *MAKERDTSTAMP*
    - *CHECKERID*
    - *CHECKERDTSTAMP*
    - *MODNO*
    - *AUTHSTAT*
    - *RECSTAT*
    - *ONCEAUTH*
    - *UDFDETAILS*
      - *FUNCTIONID*

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	

TOP

Amount-Blocks-IO

Attribute	Description
Name	Amount-Blocks-IO
Datatype	
Description	Include amount blocks IO type details.

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates the Account Number.	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTBLKNO

Attribute	Description	
Name	AMTBLKNO	
Datatype	String	
Description	Indicates the Amount Block Number.	
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates the Amount.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	Attribute: minOccurs, Description: 0

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date
Attributes	Attribute: minOccurs, Description: 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 255

TOP

HOLD_CODE

Attribute	Description
Name	HOLD_CODE
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 15

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	Attribute: minOccurs, Description: 0

Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting Date time of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Specifies whether the record is authorized atleast once
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	User Defined Fields details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

TOP

2.5.3.CA-AmountBlocksNew-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Amount-Blocks-PK*
      - *AMTBLKNO*
    - *Amount-Blocks-IO*
      - *BRANCH*
      - *ACC*
      - *AMTBLKNO*
      - *AMT*
      - *EFFDATE*
      - *EXPDATE*
      - *REM*
      - *HOLD_CODE*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Amount-Blocks-Full

ACC

AMTBLKNO

AMT

EXPDATE

REM

ABLKTYPE

REFERENCENO

HPCODE

EFFDATE

HOLDDESC

BRANCH

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Amount-Blocks-PK

Attribute	Description
Name	Amount-Blocks-PK
Datatype	
Description	Include Amount Blocks PK type details

TOP

AMTBLKNO

Attribute	Description	
Name	AMTBLKNO	
Datatype	String	
Description	Indicates the Amount Block Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Amount-Blocks-IO

Attribute	Description
Name	Amount-Blocks-IO
Datatype	
Description	Include Amount Blocks IO type details

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates the Account Number.	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTBLKNO

Attribute	Description

Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

HOLD_CODE

Attribute	Description
Name	HOLD_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting Date time of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description

Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Specifies whether the record is authorized atleast once
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	User Defined Fields details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Amount-Blocks-Full

Attribute	Description
Name	Amount-Blocks-Full
Datatype	
Description	Include Amount Blocks full details

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account Number.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	Attribute: minOccurs — Description: 0

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date
Attributes	Attribute: minOccurs — Description: 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ABLKTYPE

Attribute	Description
Name	ABLKTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: F,S,P,E,A,C,B,H

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 40

TOP

HPCODE

Attribute	**Description**
Name	HPCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

EFFDATE

Attribute	**Description**
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HOLDDESC

Attribute	**Description**
Name	HOLDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Specifies whether the record is authorized atleast once

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	User Defined Fields details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 255
	minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include error type details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include warning type details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.5.4.CA-AmountBlocksNew-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Amount-Blocks-PK*
      - *AMTBLKNO*
    - *Amount-Blocks-IO*
      - *BRANCH*
      - *ACC*
      - *AMTBLKNO*
      - *AMT*
      - *EFFDATE*
      - *EXPDATE*
      - *REM*
      - *HOLD_CODE*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Amount-Blocks-Full

ACC

AMTBLKNO

AMT

EXPDATE

REM

ABLKTYPE

REFERENCENO

HPCODE

EFFDATE

HOLDDESC

BRANCH

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Amount-Blocks-PK

Attribute	Description
Name	Amount-Blocks-PK
Datatype	
Description	Include amount blocks Pk type details.

TOP

AMTBLKNO

Attribute	Description	
Name	AMTBLKNO	
Datatype	String	
Description	Indicates the Amount Block Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Amount-Blocks-IO

Attribute	Description
Name	Amount-Blocks-IO
Datatype	
Description	Include amount blocks IO type details.

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates the Account Number.	
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTBLKNO

Attribute	Description

Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

HOLD_CODE

Attribute	Description
Name	HOLD_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting Date time of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description

Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Specifies whether the record is authorized atleast once
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	User Defined Fields details
Attributes	Attribute: Description maxOccurs: unbounded minOccurs: 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description maxLength: 8 pattern: [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	Restrictions: Description maxLength: 105 minLength: 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description maxLength: 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Amount-Blocks-Full

Attribute	Description
Name	Amount-Blocks-Full
Datatype	
Description	Include amount blocks Full details.

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account Number.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates the Amount.	
Attributes	Attribute	Description
	minOccurs	0

TOP

EXPDATE

Attribute	Description	
Name	EXPDATE	
Datatype	Date	
Description	Indicates the Expiry Date	
Attributes	Attribute	Description
	minOccurs	0

TOP

REM

Attribute	Description	
Name	REM	
Datatype	String	
Description	Indicates the Remarks.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TOP

ABLKTYPE

Attribute	Description	
Name	ABLKTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	F,S,P,E,A,C,B,H

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 40

TOP

HPCODE

Attribute	**Description**
Name	HPCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

EFFDATE

Attribute	**Description**
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

HOLDDESC

Attribute	**Description**
Name	HOLDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Specifies whether the record is authorized atleast once

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	User Defined Fields details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 255
	minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include error type details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include warning type details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.6.AmountBlocksQuery

Query of Customer Account Amount Blocks

2.6.1.CA-AmountBlocksQuery-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-IO*
    - *AMTBLKNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Amount-Blocks-IO

Attribute	Description
Name	Amount-Blocks-IO
Datatype	
Description	Includes amount blocks PK type details

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

2.6.2.CA-AmountBlocksQuery-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Amount-Blocks-PK*
      - *AMTBLKNO*
    - *Amount-Blocks-IO*
      - *BRANCH*
      - *ACC*
      - *AMTBLKNO*
      - *AMT*
      - *EFFDATE*
      - *EXPDATE*
      - *REM*
      - *HOLD_CODE*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Amount-Blocks-Full

ACC

AMTBLKNO

AMT

EXPDATE

REM

ABLKTYPE

REFERENCENO

HPCODE

EFFDATE

HOLDDESC

BRANCH

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Amount-Blocks-PK

Attribute	Description
Name	Amount-Blocks-PK
Datatype	
Description	include amount blocksPK type details

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Amount-Blocks-IO

Attribute	Description
Name	Amount-Blocks-IO
Datatype	
Description	include amount blocks IO type details

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account Number.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

AMTBLKNO

Attribute	Description

Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

HOLD_CODE

Attribute	Description
Name	HOLD_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting Date time of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description

Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Specifies whether the record is authorized atleast once
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	User Defined Fields details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Amount-Blocks-Full

Attribute	Description
Name	Amount-Blocks-Full
Datatype	
Description	include amount blocks Full type details

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account Number.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates the Amount.	
Attributes	Attribute	Description
	minOccurs	0

TOP

EXPDATE

Attribute	Description	
Name	EXPDATE	
Datatype	Date	
Description	Indicates the Expiry Date	
Attributes	Attribute	Description
	minOccurs	0

TOP

REM

Attribute	Description	
Name	REM	
Datatype	String	
Description	Indicates the Remarks.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TOP

ABLKTYPE

Attribute	Description	
Name	ABLKTYPE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	F,S,P,E,A,C,B,H

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 40

TOP

HPCODE

Attribute	**Description**
Name	HPCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

EFFDATE

Attribute	**Description**
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HOLDDESC

Attribute	**Description**
Name	HOLDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Specifies whether the record is authorized atleast once

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	User Defined Fields details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 255
	minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include error type details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include warning type details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.7.AmountBlocksReopen

Reopen of Customer Account Amount Blocks

2.7.1.CA-AmountBlocksReopen-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-Full*
    - *ACC*
    - *AMTBLKNO*
    - *AMT*
    - *EXPDATE*
    - *REM*
    - *ABLKTYPE*
    - *REFERENCENO*
    - *HPCODE*
    - *EFFDATE*
    - *HOLDDESC*
    - *BRANCH*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO

TXNSTAT

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Amount-Blocks-Full

Attribute	Description
Name	Amount-Blocks-Full
Datatype	
Description	Include amount blocks full details.

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account Number.
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date

Attributes	Attribute	Description
	minOccurs	0

TOP

REM

Attribute	Description	
Name	REM	
Datatype	String	
Description	Indicates the Remarks.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ABLKTYPE

Attribute	Description	
Name	ABLKTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,S,P,E,A,C,B,H

TOP

REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	40

TOP

HPCODE

Attribute	Description	
Name	HPCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HOLDDESC

Attribute	Description
Name	HOLDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Specifies whether the record is authorized atleast once
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	User Defined Fields details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description

Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.7.2.CA-AmountBlocksReopen-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-IO*
    - *AMTBLKNO*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration — Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0 Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0 Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	Restrictions: maxLength — Description: 12 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	

Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Amount-Blocks-IO

Attribute	Description
Name	Amount-Blocks-IO
Datatype	
Description	Include amount blocks PK ACR Type details.

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MODNO

Attribute	Description

<table>
<tr><td>Name</td><td>MODNO</td></tr>
<tr><td>Datatype</td><td>Number</td></tr>
<tr><td>Description</td><td>Indicates the Modification number of the record</td></tr>
<tr><td>Attributes</td><td><table>
<tr><th>Attribute</th><th>Description</th></tr>
<tr><td>minOccurs</td><td>0</td></tr>
</table></td></tr>
<tr><td>Restrictions</td><td><table>
<tr><th>Restrictions</th><th>Description</th></tr>
<tr><td>totalDigits</td><td>22</td></tr>
</table></td></tr>
</table>

TOP

2.7.3.CA-AmountBlocksReopen-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Amount-Blocks-PK*
      - *AMTBLKNO*
    - *Amount-Blocks-IO*
      - *BRANCH*
      - *ACC*
      - *AMTBLKNO*
      - *AMT*
      - *EFFDATE*
      - *EXPDATE*
      - *REM*
      - *HOLD_CODE*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Amount-Blocks-Full

ACC

AMTBLKNO

AMT

EXPDATE

REM

ABLKTYPE

REFERENCENO

HPCODE

EFFDATE

HOLDDESC

BRANCH

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Amount-Blocks-PK

Attribute	Description
Name	Amount-Blocks-PK
Datatype	
Description	Include amount block PK type details.

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Amount-Blocks-IO

Attribute	Description
Name	Amount-Blocks-IO
Datatype	
Description	Include amount block IO type details.

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account Number.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTBLKNO

Attribute	Description

Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

HOLD_CODE

Attribute	Description
Name	HOLD_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting Date time of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description

Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Specifies whether the record is authorized atleast once
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	User Defined Fields details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Amount-Blocks-Full

Attribute	Description
Name	Amount-Blocks-Full
Datatype	
Description	Include amount block full type details.

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account Number.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMT

Attribute	**Description**
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXPDATE

Attribute	**Description**
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REM

Attribute	**Description**
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ABLKTYPE

Attribute	**Description**
Name	ABLKTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,S,P,E,A,C,B,H

TOP

REFERENCENO

Attribute	**Description**
Name	REFERENCENO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 40

TOP

HPCODE

Attribute	**Description**
Name	HPCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

EFFDATE

Attribute	**Description**
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HOLDDESC

Attribute	**Description**
Name	HOLDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Specifies whether the record is authorized atleast once

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	User Defined Fields details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 255
	minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include error type details.
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include warning type details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.7.4.CA-AmountBlocksReopen-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Amount-Blocks-PK*
      - *AMTBLKNO*
    - *Amount-Blocks-IO*
      - *BRANCH*
      - *ACC*
      - *AMTBLKNO*
      - *AMT*
      - *EFFDATE*
      - *EXPDATE*
      - *REM*
      - *HOLD_CODE*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*

ONCEAUTH

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

Amount-Blocks-Full

ACC

AMTBLKNO

AMT

EXPDATE

REM

ABLKTYPE

REFERENCENO

HPCODE

EFFDATE

HOLDDESC

BRANCH

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

RECSTAT

ONCEAUTH

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Amount-Blocks-PK

Attribute	Description
Name	Amount-Blocks-PK
Datatype	
Description	Include amount blocks PK type details

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Amount-Blocks-IO

Attribute	Description
Name	Amount-Blocks-IO
Datatype	
Description	Include amount blocks IO type details

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account Number.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTBLKNO

Attribute	Description

Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

HOLD_CODE

Attribute	Description
Name	HOLD_CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	Indicates the User Identification who inputted the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates the inputting Date time of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Indicates the User Identification who authorised the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	Description

Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Authorised time of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Specifies whether the record is authorized atleast once
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	User Defined Fields details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Amount-Blocks-Full

Attribute	Description
Name	Amount-Blocks-Full
Datatype	
Description	Include amount blocks full type details

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates the Account Number.
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	Attribute: minOccurs — Description: 0

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date
Attributes	Attribute: minOccurs — Description: 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ABLKTYPE

Attribute	Description
Name	ABLKTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: F,S,P,E,A,C,B,H

TOP

REFERENCENO

Attribute	Description
Name	REFERENCENO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 40

TOP

HPCODE

Attribute	**Description**
Name	HPCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

EFFDATE

Attribute	**Description**
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HOLDDESC

Attribute	**Description**
Name	HOLDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates the Modification number of the record
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECSTAT

Attribute	Description
Name	RECSTAT
Datatype	String
Description	Indicates the Record Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	Specifies whether the record is authorized atleast once

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	User Defined Fields details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**
	maxLength / 105
	minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0
Restrictions	**Restrictions** / **Description**
	maxLength / 255
	minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Include error type details
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Include warning type details
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.8.CreateAccountStructure

Creation of Account Structure

2.8.1.CA-CreateAccountStructure-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Struct-Full*
    - *STRUCTG*
    - *GRPDESC*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Struct-Detail*
      - *SEQNO*
      - *PACCOUNT*
      - *PBRANCH*
      - *PCCY*
      - *CACCOUNT*

CBRANCH

CCCY

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Struct-Full

Attribute	Description
Name	Struct-Full
Datatype	
Description	

TOP

STRUCTG

Attribute	Description	
Name	STRUCTG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

GRPDESC

Attribute	Description	
Name	GRPDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description	The User Id who has created/last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Struct-Detail

Attribute	**Description**
Name	Struct-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SEQNO

Attribute	**Description**
Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PACCOUNT

Attribute	**Description**
Name	PACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PBRANCH

Attribute	**Description**

Name	PBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PCCY

Attribute	**Description**
Name	PCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CACCOUNT

Attribute	**Description**
Name	CACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CBRANCH

Attribute	**Description**
Name	CBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CCCY

Attribute	**Description**
Name	CCCY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description**: maxOccurs = unbounded; minOccurs = 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength = 105; minLength = 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: maxLength = 255; minLength = 0

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Struct-IO
STRUCTG
GRPDESC
Struct-Detail
PACCOUNT
UDFDETAILS
FLDNAM
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration — Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0 Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0 Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	Restrictions: maxLength — Description: 12 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0; nillable true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 128 Restrictions: pattern; Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Struct-IO

Attribute	Description
Name	Struct-IO
Datatype	
Description	

TOP

STRUCTG

Attribute	Description
Name	STRUCTG
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	Restrictions	Description
	maxLength	20

TOP

GRPDESC

Attribute	Description	
Name	GRPDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

TOP

Struct-Detail

Attribute	Description	
Name	Struct-Detail	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

PACCOUNT

Attribute	Description	
Name	PACCOUNT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	UDF Details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.8.3.CA-CreateAccountStructure-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Struct-Full*
    - *STRUCTG*
    - *GRPDESC*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Struct-Detail*
      - *SEQNO*
      - *PACCOUNT*
      - *PBRANCH*
      - *PCCY*
      - *CACCOUNT*
      - *CBRANCH*
      - *CCCY*
    - *UDFDETAILS*

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String

Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Struct-Full

Attribute	Description
Name	Struct-Full
Datatype	
Description	

TOP

STRUCTG

Attribute	Description	
Name	STRUCTG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

GRPDESC

Attribute	Description	
Name	GRPDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description	The User Id who has created/last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

ORACLE

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Struct-Detail

Attribute	Description
Name	Struct-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PACCOUNT

Attribute	Description
Name	PACCOUNT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PBRANCH

Attribute	Description	
Name	PBRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PCCY

Attribute	Description	
Name	PCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CACCOUNT

Attribute	Description	
Name	CACCOUNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CBRANCH

Attribute	Description	
Name	CBRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCCY

Attribute	**Description**
Name	CCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.8.4.CA-CreateAccountStructure-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Struct-PK*
      - *STRUCTG*
    - *Struct-IO*
      - *STRUCTG*
      - *GRPDESC*
      - *Struct-Detail*
        - *PACCOUNT*
      - *UDFDETAILS*
        - *FLDNAM*
        - *FLDVAL*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Struct-PK

Attribute	Description
Name	Struct-PK
Datatype	
Description	

TOP

STRUCTG

Attribute	Description	
Name	STRUCTG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

Struct-IO

Attribute	Description
Name	Struct-IO
Datatype	
Description	

TOP

STRUCTG

Attribute	Description	
Name	STRUCTG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

GRPDESC

Attribute	Description	
Name	GRPDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	50

TOP

Struct-Detail

Attribute	Description	
Name	Struct-Detail	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PACCOUNT

Attribute	Description	
Name	PACCOUNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	UDF Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	Description

Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attributes		
	Attribute	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	**Description**	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	**Description**
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	**Description**
Name	WDESC
Datatype	String
Description	

TOP

2.9.ModifyAccountStructure

Modification of Account Structure

2.9.1.CA-ModifyAccountStructure-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Struct-Full*
    - *STRUCTG*
    - *GRPDESC*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Struct-Detail*
      - *SEQNO*
      - *PACCOUNT*
      - *PBRANCH*
      - *PCCY*
      - *CACCOUNT*

CBRANCH

CCCY

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Struct-Full

Attribute	Description
Name	Struct-Full
Datatype	
Description	

TOP

STRUCTG

Attribute	Description	
Name	STRUCTG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

GRPDESC

Attribute	Description	
Name	GRPDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description	The User Id who has created/last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Struct-Detail

Attribute	**Description**
Name	Struct-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SEQNO

Attribute	**Description**
Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PACCOUNT

Attribute	**Description**
Name	PACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PBRANCH

Attribute	**Description**

Name	PBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PCCY

Attribute	**Description**
Name	PCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CACCOUNT

Attribute	**Description**
Name	CACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CBRANCH

Attribute	**Description**
Name	CBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CCCY

Attribute	**Description**
Name	CCCY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description**
	maxOccurs: unbounded
	minOccurs: 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**
	maxLength: 105
	minLength: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**
	minOccurs: 0
Restrictions	**Restrictions** / **Description**
	maxLength: 255
	minLength: 0

TOP

2.9.2.CA-ModifyAccountStructure-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Struct-IO*
    - *STRUCTG*
    - *GRPDESC*
    - *MODNO*
    - *Struct-Detail*
      - *PACCOUNT*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Struct-IO

Attribute	Description
Name	Struct-IO
Datatype	
Description	

TOP

STRUCTG

Attribute	Description
Name	STRUCTG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	20

TOP

GRPDESC

Attribute	Description
Name	GRPDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 50

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: totalDigits — Description: 22

TOP

Struct-Detail

Attribute	Description
Name	Struct-Detail
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

PACCOUNT

Attribute	Description
Name	PACCOUNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.9.3.CA-ModifyAccountStructure-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Struct-Full*
    - *STRUCTG*
    - *GRPDESC*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Struct-Detail*
      - *SEQNO*
      - *PACCOUNT*
      - *PBRANCH*
      - *PCCY*
      - *CACCOUNT*
      - *CBRANCH*
      - *CCCY*
    - *UDFDETAILS*

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String

Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Struct-Full

Attribute	Description
Name	Struct-Full
Datatype	
Description	

TOP

STRUCTG

Attribute	Description	
Name	STRUCTG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

GRPDESC

Attribute	Description	
Name	GRPDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description	The User Id who has created/last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Struct-Detail

Attribute	Description
Name	Struct-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PACCOUNT

Attribute	Description
Name	PACCOUNT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

PBRANCH

Attribute	Description	
Name	PBRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PCCY

Attribute	Description	
Name	PCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CACCOUNT

Attribute	Description	
Name	CACCOUNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CBRANCH

Attribute	Description	
Name	CBRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	3

TOP

CCCY

Attribute	Description	
Name	CCCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	UDF Details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.9.4.CA-ModifyAccountStructure-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Struct-PK*
      - *STRUCTG*
    - *Struct-IO*
      - *STRUCTG*
      - *GRPDESC*
      - *MODNO*
      - *Struct-Detail*
        - *PACCOUNT*
      - *UDFDETAILS*
        - *FLDNAM*
        - *FLDVAL*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**

Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

ORACLE

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Struct-PK

Attribute	Description
Name	Struct-PK
Datatype	
Description	

TOP

STRUCTG

Attribute	Description	
Name	STRUCTG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

Struct-IO

Attribute	Description
Name	Struct-IO
Datatype	
Description	

TOP

STRUCTG

Attribute	Description	
Name	STRUCTG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

GRPDESC

Attribute	Description	
Name	GRPDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	50

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TOP

Struct-Detail

Attribute	Description
Name	Struct-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PACCOUNT

Attribute	Description
Name	PACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.10.QueryAccountStructure

Query of Account Structure

2.10.1.CA-QueryAccountStructure-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Struct-IO*
    - *STRUCTG*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Struct-IO

Attribute	Description
Name	Struct-IO
Datatype	
Description	

TOP

STRUCTG

Attribute	Description
Name	STRUCTG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

2.10.2.CA-QueryAccountStructure-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Struct-IO*
      - *STRUCTG*
    - *Struct-Full*
      - *STRUCTG*
      - *GRPDESC*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
      - *TXNSTAT*
      - *AUTHSTAT*
      - *Struct-Detail*
        - *SEQNO*
        - *PACCOUNT*
        - *PBRANCH*
        - *PCCY*
        - *CACCOUNT*

CBRANCH

CCCY

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Struct-IO

Attribute	Description
Name	Struct-IO
Datatype	
Description	

TOP

STRUCTG

Attribute	Description	
Name	STRUCTG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

Struct-Full

Attribute	Description
Name	Struct-Full
Datatype	
Description	

TOP

STRUCTG

Attribute	Description
Name	STRUCTG
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

GRPDESC

Attribute	Description
Name	GRPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

Struct-Detail

Attribute	Description
Name	Struct-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PACCOUNT

Attribute	Description
Name	PACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PBRANCH

Attribute	Description
Name	PBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PCCY

Attribute	Description
Name	PCCY
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CACCOUNT

Attribute	Description
Name	CACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CBRANCH

Attribute	Description
Name	CBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CCCY

Attribute	Description
Name	CCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	Restrictions: Description maxLength: 105 minLength: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description maxLength: 255 minLength: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: Description maxOccurs: unbounded minOccurs: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: Description maxOccurs: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.11.AuthorizeCustomer

Authorization of Customer

2.11.1.ST-AuthorizeCustomer-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Customer-Full*
    - *NAME*
    - *ADDRLN1*
    - *ADDRLN3*
    - *ADDRLN2*
    - *ADDRLN4*
    - *SWIFTCD*
    - *FAX*
    - *COUNTRY*
    - *NLTY*
    - *LANG*
    - *EXPCNTRY*
    - *UIDNAME*
    - *UIDVAL*
    - *LOC*
    - *FROZEN*

DEAD
WHRUNKN
GRPCD
CHGGRP
CUSTCLGGRP
TAXGROUP
CCATEG
EXPCAT
CUSTCLASSFN
FXNETTCUST
XREF
MEDIA
SSN
CIFSTAT
CIFSTATSNC
MAILRSREQD
CLSPARTICIPANT
CRMCUST
ISSUCUST
TRSRYCUST
CUSTNO
SNAME
LBRN
CTYPE
FULLNAME
AMLCUSTGRP
AMLREQD
FLGUTLTYPRVDR
UTLTYPRVDRID
CHKDIGITVALREQD
ALGID
CONSTAXCERTRQD
INDTAXCERTRQD
HOACNO
RISKPRFL
DRCAT
FTACCASOF
UDF1
UDF2
UDF3
UDF4
UDF5
UDFLBL1
UDFLBL2

UDFLBL3
UDFLBL4
UDFLBL5
FXCUSTCLRILIM
OVRLIM
FX_CLEAN_RISK
CRRATE
REVDT
LIMCCY
SECCUSTCLRILIM
SECCLRILIM
SECCUSTPSRILIM
SECPSRILIM
CUSTUNADV
RISKCATEG
CLSCCYALLWD
NETTREQD
LIABUNADV
MT920
RELPRICING
FLGJOINT
KYCSTAT
SSTAFF
UPTYPE
KYC_REFNO
JOINT_VENTURE
PRIVATE_CUSTOMER
LC_COLLAT_PCT
ISELCMCUST
ELCMCUSTNO
ALT_CUST_NO
DETERIORATION_DATE
CHQ_TAX_EXEMPT_1
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Custpersonal
- *TITLE*
- *FSTNAME*
- *MIDNAME*

LSTNAME
DOB
GUARDIAN
MINOR
SEX
NATIONID
PPTNO
PPTISSDT
PPTEXPDT
DADD1
DADD2
DADD3
TEL
FAX
EMAIL
PADD1
PADD2
PADD3
DCNTRY
PCNTRY
RESSTATUS
CUSTPREFIX1
CUSTPREFIX2
MOBNUM
SBMTAGEPROOF
CUST_COMM_MODE
LAST_UPD_DT
Custdomestic
- *EDUSTAT*
- *MARITALSTAT*
- *SPNAME*
- *SPEMPSTATUS*
- *DEPCHILD*
- *DEPOTH*
- *ACCOMODATE*
- *CUSTNO*

Custprof
- *EMPSTAT*
- *EMPTENURE*
- *RETIREAGE*
- *PREVDESIG*
- *PREVEMP*
- *CURRDESIG*
- *CURREMP*

ADD1
ADD2
ADD3
TEL
TELEX
FAX
EMAIL
SALARY
OTHER1
RENT
INSURANCE
LOANPMNT
OTHEXP
HOUSEVAL
CRCARD
CNTY
AMTCCY1
CUSTNO
EMPLOYER_DESC
EMP_DESC

Custcorp

CORPNAME
NATIONID
REGADD1
REGADD2
REGADD3
INCORPDT
CAPITAL
NETWORTH
INCORPCNTRY
REGCNTRY
AMTCCY
CORPDESC
CUSTNO
Custcorpdir

DIRNAME
TEL
NADDR1
NADDR2
NADDR3
NADDR4
ADDR1
ADDRS2
ADDRS3

- *COUNTRY*
- *TAXID*
- *MOBNO*
- *EMAIL*
- *Issuerdet*
  - *OVERLIMIT*
  - *CUSTNO*
  - *OVERLMTCCY*
  - *Issuerlmts*
    - *CLTRLTYP*
    - *LMTAMT*
    - *LMTCCY*
    - *ISSID*
- *Custgrp*
  - *GRPNO*
  - *RELATION*
- *Custshhold*
  - *SHHOLDID*
  - *SHHOLDPCT*
  - *SHRHLDRNAME*
- *Clsccyrest*
  - *CCY*
  - *DESC*
- *Bic*
  - *ACC*
  - *BICCD*
- *Linkedac*
  - *VRFD*
  - *LINKEDACCNO*
  - *LINKEDACCIBAN*
  - *LINKEDACCBIC*
- *JointVenture*
  - *PARTYID*
  - *PARTYRATIO*
  - *PARTYNAME*
- *Custdoc-Chklist*
  - *DOCUMENT_TYPE*
  - *CHECKED*
- *Doctype-Remarks*
  - *REMARK1*
  - *REMARK2*
  - *REMARK3*
  - *REMARK4*
  - *REMARK5*

- *REMARK6*
- *REMARK7*
- *REMARK8*
- *REMARK9*
- *REMARK10*

Custmis

- *MISGRP*
- *CUST*
- *BRNCD*
- *Custchnglog*
  - *MISCLS*
  - *TXNDT*
  - *OLDMISCD*
  - *NWMISCD*
- *Baltrnsfrlog*
  - *BRN*
  - *PRDCD*
  - *FINYR*
  - *TXNDT*
  - *GLCODE*
  - *MISCLS*
  - *OLDMISCD*
  - *NWMISCD*
  - *TRNIND*
  - *CCY*
  - *AMT*
  - *XRATE*
- *Dfltcd*
  - *MISCLS*
  - *MISCD*
- *Dfltcda*
  - *MISCLS*
  - *MISCD*
- *Custloghead*

Jointcustomer

- *CUSTNO*
- *Custjoint*
  - *CUSTPREFIX*
  - *FRSTNAME*
  - *MIDNAME*
  - *LASTNAME*
  - *DOB*
  - *SEX*
  - *PPNO*

PPTISSDT

PPTEXPDT

ADD1

ADD2

ADD3

TEL

EMAIL

SSN

DECEASED

RESISTAT

Cust-Acc-Det

CUSTNO

Diary-Mst

INSTRNO

UNTTYP

UNTVAL

BRN

INSTR

INSTRTYPE

EXEDAYS

EXEMONTHS

EXEYEARS

MNTHENDFLG

HLDRULE

FRSTDUEDT

NXTDUEDT

NXTEXEDT

CONDELEM

OPRTR

CONDVAL

ACCOFCR

SPLINSTRTYP

EXPDT

SPLINSTR

Custaccdet

CUSTNO

BRNCD

Relationship-Linkage

CUSTOMER

RELATIONSHIP

INHERIT

DESCP

Custacdetail

CUSTNO

CUSTTEXT

SEQNO

CUSTNO

TDESC

UDFDETAILS

FLDNAM

FLDVAL

Sttms-Debit

BRANCH_CODE

CUST_NO

ACTNO

Sttms-Detail

BRANCH_CODE

REQUEST_REFERENCE_NO

CARDNO

CUST_NO

CARD_PRODUCT

PRIMARY_CARD

NAME_ON_CARD

OWNER_ID_NO

CARD_ISSUED_DT

CARD_EXPIRY_DT

CARD_STATUS

RECORD_STAT

AUTH_STAT

CARD_BIN

CUST_AC_NO

Extsys-Ws-Master

Extsys-Ws-Details

EXTWSRESP

USERREMARKS

Stvws-Cust-Trntax

CUSTOMER_NO

Sttms-Cust-Trn-Tax

TAX_SCHEME

TXN_TAX_EXEMPTED

TXN_TAX_EXEMPTION_PERCENT

TXN_TAX_EFF_DATE

TXN_TAX_EXEMPTION_REASON

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Customer-Full

Attribute	Description
Name	Customer-Full
Datatype	
Description	

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

ADDRLN1

Attribute	Description	
Name	ADDRLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN3

Attribute	Description	
Name	ADDRLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN2

Attribute	Description	
Name	ADDRLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN4

Attribute	Description
Name	ADDRLN4
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SWIFTCD

Attribute	Description
Name	SWIFTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FAX

Attribute	Description
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRY

Attribute	Description
Name	COUNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NLTY

Attribute	Description
Name	NLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	3

TOP

LANG

Attribute	Description	
Name	LANG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

TOP

EXPCNTRY

Attribute	Description	
Name	EXPCNTRY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

UIDNAME

Attribute	Description	
Name	UIDNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

UIDVAL

Attribute	Description	
Name	UIDVAL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

LOC

Attribute	Description
Name	LOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FROZEN

Attribute	Description
Name	FROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEAD

Attribute	Description
Name	DEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

WHRUNKN

Attribute	Description
Name	WHRUNKN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

CHGGRP

Attribute	Description
Name	CHGGRP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

CUSTCLGGRP

Attribute	Description
Name	CUSTCLGGRP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TAXGROUP

Attribute	Description
Name	TAXGROUP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

CCATEG

Attribute	Description
Name	CCATEG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EXPCAT

Attribute	**Description**
Name	EXPCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUSTCLASSFN

Attribute	**Description**
Name	CUSTCLASSFN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

FXNETTCUST

Attribute	**Description**
Name	FXNETTCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

XREF

Attribute	**Description**
Name	XREF
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SSN

Attribute	Description
Name	SSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

CIFSTAT

Attribute	Description
Name	CIFSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CIFSTATSNC

Attribute	Description
Name	CIFSTATSNC
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAILRSREQD

Attribute	Description
Name	MAILRSREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLSPARTICIPANT

Attribute	Description
Name	CLSPARTICIPANT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CRMCUST

Attribute	Description
Name	CRMCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ISSUCUST

Attribute	Description
Name	ISSUCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRSRYCUST

Attribute	Description
Name	TRSRYCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

SNAME

Attribute	Description
Name	SNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 20

TOP

LBRN

Attribute	Description
Name	LBRN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CTYPE

Attribute	Description
Name	CTYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,C,B

TOP

FULLNAME

Attribute	Description
Name	FULLNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

AMLCUSTGRP

Attribute	Description
Name	AMLCUSTGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

AMLREQD

Attribute	Description
Name	AMLREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FLGUTLTYPRVDR

Attribute	Description
Name	FLGUTLTYPRVDR
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

UTLTYPRVDRID

Attribute	Description	
Name	UTLTYPRVDRID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHKDIGITVALREQD

Attribute	Description	
Name	CHKDIGITVALREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALGID

Attribute	Description	
Name	ALGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CONSTAXCERTRQD

Attribute	Description	
Name	CONSTAXCERTRQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

INDTAXCERTRQD

Attribute	Description	
Name	INDTAXCERTRQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

HOACNO

Attribute	Description	
Name	HOACNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RISKPRFL

Attribute	Description	
Name	RISKPRFL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

DRCAT

Attribute	Description	
Name	DRCAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

FTACCASOF

Attribute	Description
Name	FTACCASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,M,D

TOP

UDF1

Attribute	Description
Name	UDF1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDF2

Attribute	Description
Name	UDF2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDF3

Attribute	Description
Name	UDF3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

UDF4

Attribute	Description
Name	UDF4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

UDF5

Attribute	Description
Name	UDF5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDFLBL1

Attribute	Description
Name	UDFLBL1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDFLBL2

Attribute	Description
Name	UDFLBL2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDFLBL3

Attribute	Description
Name	UDFLBL3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL4

Attribute	Description
Name	UDFLBL4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL5

Attribute	Description
Name	UDFLBL5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

FXCUSTCLRILIM

Attribute	Description
Name	FXCUSTCLRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OVRLIM

Attribute	Description
Name	OVRLIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FX_CLEAN_RISK

Attribute	Description
Name	FX_CLEAN_RISK
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CRRATE

Attribute	Description
Name	CRRATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

REVDT

Attribute	Description
Name	REVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIMCCY

Attribute	Description
Name	LIMCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SECCUSTCLRILIM

Attribute	Description
Name	SECCUSTCLRILIM
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SECCLRILIM

Attribute	Description
Name	SECCLRILIM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SECCUSTPSRILIM

Attribute	Description
Name	SECCUSTPSRILIM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SECPSRILIM

Attribute	Description
Name	SECPSRILIM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CUSTUNADV

Attribute	Description
Name	CUSTUNADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

RISKCATEG

Attribute	Description
Name	RISKCATEG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CLSCCYALLWD

Attribute	**Description**	
Name	CLSCCYALLWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D

TOP

NETTREQD

Attribute	**Description**	
Name	NETTREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIABUNADV

Attribute	**Description**	
Name	LIABUNADV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MT920

Attribute	**Description**	
Name	MT920	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RELPRICING

Attribute	**Description**
Name	RELPRICING
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FLGJOINT

Attribute	**Description**
Name	FLGJOINT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

KYCSTAT

Attribute	**Description**
Name	KYCSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,N,F

TOP

SSTAFF

Attribute	**Description**
Name	SSTAFF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UPTYPE

Attribute	Description
Name	UPTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

KYC_REFNO

Attribute	Description
Name	KYC_REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

JOINT_VENTURE

Attribute	Description
Name	JOINT_VENTURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIVATE_CUSTOMER

Attribute	Description
Name	PRIVATE_CUSTOMER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LC_COLLAT_PCT

Attribute	Description
Name	LC_COLLAT_PCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISELCMCUST

Attribute	Description
Name	ISELCMCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ELCMCUSTNO

Attribute	Description
Name	ELCMCUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ALT_CUST_NO

Attribute	Description
Name	ALT_CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DETERIORATION_DATE

Attribute	Description
Name	DETERIORATION_DATE
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CHQ_TAX_EXEMPT_1

Attribute	Description	
Name	CHQ_TAX_EXEMPT_1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Custpersonal

Attribute	Description
Name	Custpersonal

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TITLE

Attribute	Description
Name	TITLE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FSTNAME

Attribute	Description
Name	FSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MIDNAME

Attribute	Description
Name	MIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LSTNAME

Attribute	Description
Name	LSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

GUARDIAN

Attribute	Description
Name	GUARDIAN
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 105

TOP

MINOR

Attribute	Description
Name	MINOR
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

SEX

Attribute	Description
Name	SEX
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: M,F

TOP

NATIONID

Attribute	Description
Name	NATIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

PPTNO

Attribute	Description
Name	PPTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

PPTISSDT

Attribute	Description
Name	PPTISSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PPTEXPDT

Attribute	Description
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DADD1

Attribute	Description
Name	DADD1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

DADD2

Attribute	Description	
Name	DADD2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

DADD3

Attribute	Description	
Name	DADD3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

TEL

Attribute	Description	
Name	TEL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

FAX

Attribute	Description	
Name	FAX	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PADD1

Attribute	Description
Name	PADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PADD2

Attribute	Description
Name	PADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PADD3

Attribute	Description
Name	PADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DCNTRY

Attribute	Description
Name	DCNTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

PCNTRY

Attribute	Description
Name	PCNTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

RESSTATUS

Attribute	Description
Name	RESSTATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: R,N

TOP

CUSTPREFIX1

Attribute	Description
Name	CUSTPREFIX1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

CUSTPREFIX2

Attribute	Description
Name	CUSTPREFIX2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

MOBNUM

Attribute	**Description**
Name	MOBNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SBMTAGEPROOF

Attribute	**Description**
Name	SBMTAGEPROOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,P,V

TOP

CUST_COMM_MODE

Attribute	**Description**
Name	CUST_COMM_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,E

TOP

LAST_UPD_DT

Attribute	**Description**
Name	LAST_UPD_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Custdomestic

Attribute	Description
Name	Custdomestic
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EDUSTAT

Attribute	Description
Name	EDUSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,U,G,P

TOP

MARITALSTAT

Attribute	Description
Name	MARITALSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,M,D,R,P,E,T

TOP

SPNAME

Attribute	Description
Name	SPNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SPEMPSTATUS

Attribute	Description
Name	SPEMPSTATUS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,T,S,U,R,P,N,O

TOP

DEPCHILD

Attribute	**Description**
Name	DEPCHILD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEPOTH

Attribute	**Description**
Name	DEPOTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOMODATE

Attribute	**Description**
Name	ACCOMODATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,O

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Custprof

Attribute	Description
Name	Custprof
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EMPSTAT

Attribute	Description
Name	EMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

EMPTENURE

Attribute	Description
Name	EMPTENURE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RETIREAGE

Attribute	Description
Name	RETIREAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PREVDESIG

Attribute	Description
Name	PREVDESIG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

PREVEMP

Attribute	Description	
Name	PREVEMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CURRDESIG

Attribute	Description	
Name	CURRDESIG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CURREMP

Attribute	Description	
Name	CURREMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ADD1

Attribute	Description	
Name	ADD1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADD3

Attribute	Description
Name	ADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TELEX

Attribute	Description
Name	TELEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FAX

Attribute	Description
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

SALARY

Attribute	Description
Name	SALARY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHER1

Attribute	Description
Name	OTHER1
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RENT

Attribute	Description
Name	RENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSURANCE

Attribute	Description
Name	INSURANCE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANPMNT

Attribute	Description
Name	LOANPMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHEXP

Attribute	Description
Name	OTHEXP
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HOUSEVAL

Attribute	Description
Name	HOUSEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CRCARD

Attribute	Description
Name	CRCARD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMTCCY1

Attribute	Description
Name	AMTCCY1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

EMPLOYER_DESC

Attribute	Description
Name	EMPLOYER_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

EMP_DESC

Attribute	Description

Name	EMP_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Custcorp

Attribute	**Description**
Name	Custcorp
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CORPNAME

Attribute	**Description**
Name	CORPNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NATIONID

Attribute	**Description**
Name	NATIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REGADD1

Attribute	**Description**
Name	REGADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REGADD2

Attribute	**Description**
Name	REGADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REGADD3

Attribute	**Description**
Name	REGADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INCORPDT

Attribute	**Description**
Name	INCORPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CAPITAL

Attribute	**Description**
Name	CAPITAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETWORTH

Attribute	**Description**
Name	NETWORTH

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INCORPCNTRY

Attribute	**Description**
Name	INCORPCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REGCNTRY

Attribute	**Description**
Name	REGCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMTCCY

Attribute	**Description**
Name	AMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CORPDESC

Attribute	**Description**
Name	CORPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Custcorpdir

Attribute	**Description**
Name	Custcorpdir
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DIRNAME

Attribute	**Description**
Name	DIRNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TEL

Attribute	**Description**
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

NADDR1

Attribute	Description
Name	NADDR1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR2

Attribute	Description
Name	NADDR2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR3

Attribute	Description
Name	NADDR3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR4

Attribute	Description
Name	NADDR4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDR1

Attribute	Description

Name	ADDR1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRY

Attribute	Description
Name	COUNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXID

Attribute	Description
Name	TAXID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MOBNO

Attribute	Description
Name	MOBNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Issuerdet

Attribute	Description
Name	Issuerdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OVERLIMIT

Attribute	Description
Name	OVERLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OVERLMTCCY

Attribute	**Description**
Name	OVERLMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Issuerlmts

Attribute	**Description**
Name	Issuerlmts
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CLTRLTYP

Attribute	**Description**
Name	CLTRLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 70

TOP

LMTAMT

Attribute	**Description**
Name	LMTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LMTCCY

Attribute	Description
Name	LMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ISSID

Attribute	Description
Name	ISSID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Custgrp

Attribute	Description
Name	Custgrp
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

GRPNO

Attribute	Description
Name	GRPNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RELATION

Attribute	Description

Name	RELATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Custshhold

Attribute	**Description**
Name	Custshhold
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SHHOLDID

Attribute	**Description**
Name	SHHOLDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SHHOLDPCT

Attribute	**Description**
Name	SHHOLDPCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHRHLDRNAME

Attribute	**Description**
Name	SHRHLDRNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Clsccyrest

Attribute	Description
Name	Clsccyrest
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Bic

Attribute	Description
Name	Bic
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC

Attribute	Description
Name	ACC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BICCD

Attribute	Description
Name	BICCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

Linkedac

Attribute	Description
Name	Linkedac
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

VRFD

Attribute	Description
Name	VRFD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LINKEDACCNO

Attribute	Description
Name	LINKEDACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	30

TOP

LINKEDACCIBAN

Attribute	Description	
Name	LINKEDACCIBAN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LINKEDACCBIC

Attribute	Description	
Name	LINKEDACCBIC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

JointVenture

Attribute	Description	
Name	JointVenture	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PARTYID

Attribute	Description	
Name	PARTYID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PARTYRATIO

Attribute	Description
Name	PARTYRATIO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Custdoc-Chklist

Attribute	Description
Name	Custdoc-Chklist
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHECKED

Attribute	Description
Name	CHECKED
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Doctype-Remarks

Attribute	Description
Name	Doctype-Remarks
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARK1

Attribute	Description
Name	REMARK1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK2

Attribute	Description
Name	REMARK2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK3

Attribute	Description
Name	REMARK3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK4

Attribute	Description
Name	REMARK4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK5

Attribute	Description
Name	REMARK5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK6

Attribute	Description
Name	REMARK6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK7

Attribute	Description
Name	REMARK7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK8

Attribute	Description
Name	REMARK8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK9

Attribute	Description
Name	REMARK9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK10

Attribute	Description
Name	REMARK10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

Custmis

Attribute	Description
Name	Custmis
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates Management Information System Group.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CUST

Attribute	**Description**
Name	CUST
Datatype	String
Description	Indicates the Customer.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRNCD

Attribute	**Description**
Name	BRNCD
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Custchnglog

Attribute	**Description**
Name	Custchnglog
Datatype	
Description	Indicates the Customer Change Log.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	**Description**
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	Indicates the Old MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	Indicates the New MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Baltrnsfrlog

Attribute	Description
Name	Baltrnsfrlog
Datatype	
Description	Indicates the Balance Transfer Log.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String

Description	Indicates the Branch Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDCD

Attribute	**Description**
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	**Description**
Name	FINYR
Datatype	String
Description	Indicates the Financial Year.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNDT

Attribute	**Description**
Name	TXNDT
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

GLCODE

Attribute	**Description**
Name	GLCODE
Datatype	String
Description	Indicates the GL Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

ORACLE

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	Indicates the Old MIS Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	Indicates the New MIS Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TRNIND

Attribute	Description
Name	TRNIND
Datatype	String
Description	Indicates Transfer Identification Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	Attribute: minOccurs — Description: 0

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate.
Attributes	Attribute: minOccurs — Description: 0

TOP

Dfltcd

Attribute	Description
Name	Dfltcd
Datatype	
Description	Indicates the Customer MIS Classes.
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	Attribute: minOccurs — Description: 1

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCD

Attribute	**Description**
Name	MISCD
Datatype	String
Description	Indicates the MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Dfltcda

Attribute	**Description**
Name	Dfltcda
Datatype	
Description	Indicates the Composite MIS Classes.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	**Description**
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCD

Attribute	**Description**
Name	MISCD
Datatype	String
Description	Indicates the MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Custloghead

Attribute	Description
Name	Custloghead
Datatype	
Description	Indicates the Customer Log Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Jointcustomer

Attribute	Description
Name	Jointcustomer
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Custjoint

Attribute	Description
Name	Custjoint
Datatype	
Description	Indicates Customer Joint.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTPREFIX

Attribute	Description
Name	CUSTPREFIX
Datatype	String
Description	Indicates the Customer Prefix.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FRSTNAME

Attribute	Description
Name	FRSTNAME
Datatype	String
Description	Indicates the First Name.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

MIDNAME

Attribute	Description
Name	MIDNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

LASTNAME

Attribute	Description
Name	LASTNAME
Datatype	String
Description	Indicates the Last Name.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SEX

Attribute	Description
Name	SEX
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,F

TOP

PPNO

Attribute	Description
Name	PPNO
Datatype	String
Description	Indicates Passport Number.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

PPTISSDT

Attribute	Description
Name	PPTISSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PPTEXPDT

Attribute	Description
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ADD2

Attribute	Description	
Name	ADD2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ADD3

Attribute	Description	
Name	ADD3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

TEL

Attribute	Description	
Name	TEL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

EMAIL

Attribute	Description	
Name	EMAIL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TOP

SSN

Attribute	Description
Name	SSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

DECEASED

Attribute	Description
Name	DECEASED
Datatype	String
Description	Indicates whether Deceased or not. The value should be either D or N.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,N

TOP

RESISTAT

Attribute	Description
Name	RESISTAT
Datatype	String
Description	Indicates the Resistant Status. The value could be either R or N.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / R,N

TOP

Cust-Acc-Det

Attribute	Description
Name	Cust-Acc-Det
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Diary-Mst

Attribute	**Description**
Name	Diary-Mst
Datatype	
Description	Indicates Diary Master.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INSTRNO

Attribute	**Description**
Name	INSTRNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

UNTTYP

Attribute	**Description**
Name	UNTTYP
Datatype	String
Description	Indicates Unit Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

UNTVAL

Attribute	**Description**
Name	UNTVAL
Datatype	String
Description	Indicates Unit Value
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INSTR

Attribute	Description
Name	INSTR
Datatype	String
Description	Indicates Instructions
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

INSTRTYPE

Attribute	Description
Name	INSTRTYPE
Datatype	String
Description	Indicates Instruction Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

EXEDAYS

Attribute	Description
Name	EXEDAYS
Datatype	Number
Description	Indicates Execution Days
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXEMONTHS

Attribute	Description
Name	EXEMONTHS
Datatype	Number
Description	Indicates Execution Months
Attributes	Attribute: minOccurs, Description: 0

TOP

EXEYEARS

Attribute	Description
Name	EXEYEARS
Datatype	Number
Description	Indicates Execution Years
Attributes	Attribute: minOccurs, Description: 0

TOP

MNTHENDFLG

Attribute	Description
Name	MNTHENDFLG
Datatype	String
Description	Indicates Month End Flag. Flag Can be either Y or N.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

HLDRULE

Attribute	Description
Name	HLDRULE
Datatype	String
Description	Indicates Holiday Rule
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 1

TOP

FRSTDUEDT

Attribute	Description
Name	FRSTDUEDT
Datatype	Date
Description	Indicates First Due Date.
Attributes	Attribute: minOccurs, Description: 0

TOP

NXTDUEDT

Attribute	Description
Name	NXTDUEDT
Datatype	Date
Description	Indicates Next Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NXTEXEDT

Attribute	Description
Name	NXTEXEDT
Datatype	Date
Description	Indicates Next Execution Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONDELEM

Attribute	Description
Name	CONDELEM
Datatype	String
Description	Indicates Condition Elements.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

OPRTR

Attribute	Description
Name	OPRTR
Datatype	String
Description	Indicates Operator.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

CONDVAL

Attribute	Description
Name	CONDVAL
Datatype	Number
Description	Indicates Condition Value.

Attributes	Attribute	Description
	minOccurs	0

TOP

ACCOFCR

Attribute	Description
Name	ACCOFCR
Datatype	String
Description	Indicates Account Officer.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

SPLINSTRTYP

Attribute	Description
Name	SPLINSTRTYP
Datatype	String
Description	Indicates Special Instruction Type.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	Indicates Expiry Date.
Attributes	Attribute: minOccurs — Description: 0

TOP

SPLINSTR

Attribute	Description
Name	SPLINSTR
Datatype	String
Description	Indicates Special Instructions.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

Custaccdet

Attribute	Description
Name	Custaccdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkage details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Indicates the customer

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Indicate relations
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicate,include relationship Y:yes N:no
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	Indicates description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Custacdetail

Attribute	Description
Name	Custacdetail
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTTEXT

Attribute	Description
Name	CUSTTEXT
Datatype	
Description	Include customer details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	Indicates sequence number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String

Description	Indicate text description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Sttms-Debit

Attribute	**Description**
Name	Sttms-Debit
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	Indicates the Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACTNO

Attribute	Description
Name	ACTNO
Datatype	String
Description	Indicates the Account Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Sttms-Detail

Attribute	Description
Name	Sttms-Detail
Datatype	
Description	Indicates Customer Details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description

Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REQUEST_REFERENCE_NO

Attribute	Description
Name	REQUEST_REFERENCE_NO
Datatype	String
Description	Indicates the Request Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CARDNO

Attribute	Description
Name	CARDNO
Datatype	String
Description	Indicates the Card Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 19

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	Indicates the Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CARD_PRODUCT

Attribute	Description
Name	CARD_PRODUCT
Datatype	String
Description	Indicates the Product code.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRIMARY_CARD

Attribute	**Description**
Name	PRIMARY_CARD
Datatype	String
Description	Indicates the Primary Card Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NAME_ON_CARD

Attribute	**Description**
Name	NAME_ON_CARD
Datatype	String
Description	Indicates the Name on Card.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

OWNER_ID_NO

Attribute	**Description**
Name	OWNER_ID_NO
Datatype	String
Description	Indicates the Owner ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

CARD_ISSUED_DT

Attribute	**Description**
Name	CARD_ISSUED_DT
Datatype	Date
Description	Indicates the Card Issue Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CARD_EXPIRY_DT

Attribute	Description
Name	CARD_EXPIRY_DT
Datatype	Date
Description	Indicates the Card Expiry Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_STATUS

Attribute	Description
Name	CARD_STATUS
Datatype	String
Description	Indicates the Card Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	Indicates the Record Stat.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTH_STAT

Attribute	Description
Name	AUTH_STAT
Datatype	String
Description	Indicates the Auth Stat.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CARD_BIN

Attribute	Description
Name	CARD_BIN

Datatype	String
Description	Indicates the Card Bin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CUST_AC_NO

Attribute	**Description**
Name	CUST_AC_NO
Datatype	String
Description	Indicates the Customer Account Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Extsys-Ws-Master

Attribute	**Description**
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	**Description**
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXTWSRESP

Attribute	**Description**
Name	EXTWSRESP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

Stvws-Cust-Trntax

Attribute	Description
Name	Stvws-Cust-Trntax
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Sttms-Cust-Trn-Tax

Attribute	Description
Name	Sttms-Cust-Trn-Tax
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TAX_SCHEME

Attribute	Description
Name	TAX_SCHEME
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

TXN_TAX_EXEMPTED

Attribute	**Description**
Name	TXN_TAX_EXEMPTED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TXN_TAX_EXEMPTION_PERCENT

Attribute	**Description**
Name	TXN_TAX_EXEMPTION_PERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXN_TAX_EFF_DATE

Attribute	**Description**
Name	TXN_TAX_EFF_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXN_TAX_EXEMPTION_REASON

Attribute	**Description**
Name	TXN_TAX_EXEMPTION_REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Customer-IO
CUSTNO
CHECKER
CHECKERSTAMP
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Customer-IO

Attribute	Description
Name	Customer-IO
Datatype	
Description	

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.11.3.ST-AuthorizeCustomer-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Customer-Full*
    - *NAME*
    - *ADDRLN1*
    - *ADDRLN3*
    - *ADDRLN2*
    - *ADDRLN4*
    - *SWIFTCD*
    - *FAX*
    - *COUNTRY*
    - *NLTY*
    - *LANG*
    - *EXPCNTRY*
    - *UIDNAME*
    - *UIDVAL*
    - *LOC*
    - *FROZEN*
    - *DEAD*
    - *WHRUNKN*
    - *GRPCD*

CHGGRP
CUSTCLGGRP
TAXGROUP
CCATEG
EXPCAT
CUSTCLASSFN
FXNETTCUST
XREF
MEDIA
SSN
CIFSTAT
CIFSTATSNC
MAILRSREQD
CLSPARTICIPANT
CRMCUST
ISSUCUST
TRSRYCUST
CUSTNO
SNAME
LBRN
CTYPE
FULLNAME
AMLCUSTGRP
AMLREQD
FLGUTLTYPRVDR
UTLTYPRVDRID
CHKDIGITVALREQD
ALGID
CONSTAXCERTRQD
INDTAXCERTRQD
HOACNO
RISKPRFL
DRCAT
FTACCASOF
UDF1
UDF2
UDF3
UDF4
UDF5
UDFLBL1
UDFLBL2
UDFLBL3
UDFLBL4
UDFLBL5

FXCUSTCLRILIM
OVRLIM
FX_CLEAN_RISK
CRRATE
REVDT
LIMCCY
SECCUSTCLRILIM
SECCLRILIM
SECCUSTPSRILIM
SECPSRILIM
CUSTUNADV
RISKCATEG
CLSCCYALLWD
NETTREQD
LIABUNADV
MT920
RELPRICING
FLGJOINT
KYCSTAT
SSTAFF
UPTYPE
KYC_REFNO
JOINT_VENTURE
PRIVATE_CUSTOMER
LC_COLLAT_PCT
ISELCMCUST
ELCMCUSTNO
ALT_CUST_NO
DETERIORATION_DATE
CHQ_TAX_EXEMPT_1
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Custpersonal
- *TITLE*
- *FSTNAME*
- *MIDNAME*
- *LSTNAME*
- *DOB*
- *GUARDIAN*

MINOR
SEX
NATIONID
PPTNO
PPTISSDT
PPTEXPDT
DADD1
DADD2
DADD3
TEL
FAX
EMAIL
PADD1
PADD2
PADD3
DCNTRY
PCNTRY
RESSTATUS
CUSTPREFIX1
CUSTPREFIX2
MOBNUM
SBMTAGEPROOF
CUST_COMM_MODE
LAST_UPD_DT
Custdomestic
- *EDUSTAT*
- *MARITALSTAT*
- *SPNAME*
- *SPEMPSTATUS*
- *DEPCHILD*
- *DEPOTH*
- *ACCOMODATE*
- *CUSTNO*

Custprof
- *EMPSTAT*
- *EMPTENURE*
- *RETIREAGE*
- *PREVDESIG*
- *PREVEMP*
- *CURRDESIG*
- *CURREMP*
- *ADD1*
- *ADD2*
- *ADD3*

TEL
TELEX
FAX
EMAIL
SALARY
OTHER1
RENT
INSURANCE
LOANPMNT
OTHEXP
HOUSEVAL
CRCARD
CNTY
AMTCCY1
CUSTNO
EMPLOYER_DESC
EMP_DESC
Custcorp
CORPNAME
NATIONID
REGADD1
REGADD2
REGADD3
INCORPDT
CAPITAL
NETWORTH
INCORPCNTRY
REGCNTRY
AMTCCY
CORPDESC
CUSTNO
Custcorpdir
DIRNAME
TEL
NADDR1
NADDR2
NADDR3
NADDR4
ADDR1
ADDRS2
ADDRS3
COUNTRY
TAXID
MOBNO

- *EMAIL*
- *Issuerdet*
  - *OVERLIMIT*
  - *CUSTNO*
  - *OVERLMTCCY*
  - *Issuerlmts*
    - *CLTRLTYP*
    - *LMTAMT*
    - *LMTCCY*
    - *ISSID*
- *Custgrp*
  - *GRPNO*
  - *RELATION*
- *Custshhold*
  - *SHHOLDID*
  - *SHHOLDPCT*
  - *SHRHLDRNAME*
- *Clsccyrest*
  - *CCY*
  - *DESC*
- *Bic*
  - *ACC*
  - *BICCD*
- *Linkedac*
  - *VRFD*
  - *LINKEDACCNO*
  - *LINKEDACCIBAN*
  - *LINKEDACCBIC*
- *JointVenture*
  - *PARTYID*
  - *PARTYRATIO*
  - *PARTYNAME*
- *Custdoc-Chklist*
  - *DOCUMENT_TYPE*
  - *CHECKED*
- *Doctype-Remarks*
  - *REMARK1*
  - *REMARK2*
  - *REMARK3*
  - *REMARK4*
  - *REMARK5*
  - *REMARK6*
  - *REMARK7*
  - *REMARK8*

- *REMARK9*
- *REMARK10*
- *Custmis*
  - *MISGRP*
  - *CUST*
  - *BRNCD*
  - *Custchnglog*
    - *MISCLS*
    - *TXNDT*
    - *OLDMISCD*
    - *NWMISCD*
  - *Baltrnsfrlog*
    - *BRN*
    - *PRDCD*
    - *FINYR*
    - *TXNDT*
    - *GLCODE*
    - *MISCLS*
    - *OLDMISCD*
    - *NWMISCD*
    - *TRNIND*
    - *CCY*
    - *AMT*
    - *XRATE*
  - *Dfltcd*
    - *MISCLS*
    - *MISCD*
  - *Dfltcda*
    - *MISCLS*
    - *MISCD*
  - *Custloghead*
- *Jointcustomer*
  - *CUSTNO*
  - *Custjoint*
    - *CUSTPREFIX*
    - *FRSTNAME*
    - *MIDNAME*
    - *LASTNAME*
    - *DOB*
    - *SEX*
    - *PPNO*
    - *PPTISSDT*
    - *PPTEXPDT*
    - *ADD1*

ADD2
ADD3
TEL
EMAIL
SSN
DECEASED
RESISTAT
Cust-Acc-Det
CUSTNO
Diary-Mst
INSTRNO
UNTTYP
UNTVAL
BRN
INSTR
INSTRTYPE
EXEDAYS
EXEMONTHS
EXEYEARS
MNTHENDFLG
HLDRULE
FRSTDUEDT
NXTDUEDT
NXTEXEDT
CONDELEM
OPRTR
CONDVAL
ACCOFCR
SPLINSTRTYP
EXPDT
SPLINSTR
Custaccdet
CUSTNO
BRNCD
Relationship-Linkage
CUSTOMER
RELATIONSHIP
INHERIT
DESCP
Custacdetail
CUSTNO
CUSTTEXT
SEQNO
CUSTNO

TDESC
UDFDETAILS
FLDNAM
FLDVAL
Sttms-Debit
BRANCH_CODE
CUST_NO
ACTNO
Sttms-Detail
BRANCH_CODE
REQUEST_REFERENCE_NO
CARDNO
CUST_NO
CARD_PRODUCT
PRIMARY_CARD
NAME_ON_CARD
OWNER_ID_NO
CARD_ISSUED_DT
CARD_EXPIRY_DT
CARD_STATUS
RECORD_STAT
AUTH_STAT
CARD_BIN
CUST_AC_NO
Extsys-Ws-Master
Extsys-Ws-Details
EXTWSRESP
USERREMARKS
Stvws-Cust-Trntax
CUSTOMER_NO
Sttms-Cust-Trn-Tax
TAX_SCHEME
TXN_TAX_EXEMPTED
TXN_TAX_EXEMPTION_PERCENT
TXN_TAX_EFF_DATE
TXN_TAX_EXEMPTION_REASON
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Customer-Full

Attribute	Description

Name	Customer-Full
Datatype	
Description	

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

ADDRLN1

Attribute	Description	
Name	ADDRLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN3

Attribute	Description	
Name	ADDRLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN2

Attribute	Description	
Name	ADDRLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN4

Attribute	Description

Name	ADDRLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SWIFTCD

Attribute	**Description**
Name	SWIFTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FAX

Attribute	**Description**
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRY

Attribute	**Description**
Name	COUNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NLTY

Attribute	**Description**
Name	NLTY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXPCNTRY

Attribute	Description
Name	EXPCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

UIDNAME

Attribute	Description
Name	UIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

UIDVAL

Attribute	Description
Name	UIDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOC

Attribute	**Description**
Name	LOC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FROZEN

Attribute	**Description**
Name	FROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEAD

Attribute	**Description**
Name	DEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

WHRUNKN

Attribute	**Description**
Name	WHRUNKN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CHGGRP

Attribute	Description
Name	CHGGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CUSTCLGGRP

Attribute	Description
Name	CUSTCLGGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAXGROUP

Attribute	Description
Name	TAXGROUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CCATEG

Attribute	Description
Name	CCATEG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

CUSTCLASSFN

Attribute	Description
Name	CUSTCLASSFN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

FXNETTCUST

Attribute	Description
Name	FXNETTCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

XREF

Attribute	Description
Name	XREF

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MEDIA

Attribute	**Description**
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SSN

Attribute	**Description**
Name	SSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

CIFSTAT

Attribute	**Description**
Name	CIFSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CIFSTATSNC

Attribute	**Description**
Name	CIFSTATSNC
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MAILRSREQD

Attribute	Description
Name	MAILRSREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CLSPARTICIPANT

Attribute	Description
Name	CLSPARTICIPANT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CRMCUST

Attribute	Description
Name	CRMCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ISSUCUST

Attribute	Description
Name	ISSUCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TRSRYCUST

Attribute	Description	
Name	TRSRYCUST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SNAME

Attribute	Description	
Name	SNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LBRN

Attribute	Description	
Name	LBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CTYPE

Attribute	Description
Name	CTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,C,B

TOP

FULLNAME

Attribute	Description
Name	FULLNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

AMLCUSTGRP

Attribute	Description
Name	AMLCUSTGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

AMLREQD

Attribute	Description
Name	AMLREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FLGUTLTYPRVDR

Attribute	Description
Name	FLGUTLTYPRVDR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UTLTYPRVDRID

Attribute	**Description**
Name	UTLTYPRVDRID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKDIGITVALREQD

Attribute	**Description**
Name	CHKDIGITVALREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALGID

Attribute	**Description**
Name	ALGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CONSTAXCERTRQD

Attribute	**Description**
Name	CONSTAXCERTRQD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INDTAXCERTRQD

Attribute	Description	
Name	INDTAXCERTRQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

HOACNO

Attribute	Description	
Name	HOACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RISKPRFL

Attribute	Description	
Name	RISKPRFL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

DRCAT

Attribute	Description	
Name	DRCAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FTACCASOF

Attribute	Description	
Name	FTACCASOF	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,M,D

TOP

UDF1

Attribute	Description	
Name	UDF1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

TOP

UDF2

Attribute	Description	
Name	UDF2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

TOP

UDF3

Attribute	Description	
Name	UDF3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

UDF4

Attribute	Description
Name	UDF4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

UDF5

Attribute	Description
Name	UDF5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL1

Attribute	Description
Name	UDFLBL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL2

Attribute	Description
Name	UDFLBL2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL3

Attribute	Description
Name	UDFLBL3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDFLBL4

Attribute	Description
Name	UDFLBL4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDFLBL5

Attribute	Description
Name	UDFLBL5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

FXCUSTCLRILIM

Attribute	Description
Name	FXCUSTCLRILIM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

OVRLIM

Attribute	Description
Name	OVRLIM
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

FX_CLEAN_RISK

Attribute	Description
Name	FX_CLEAN_RISK
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CRRATE

Attribute	Description
Name	CRRATE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

REVDT

Attribute	Description
Name	REVDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIMCCY

Attribute	Description
Name	LIMCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

SECCUSTCLRILIM

Attribute	Description
Name	SECCUSTCLRILIM

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCLRILIM

Attribute	Description
Name	SECCLRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCUSTPSRILIM

Attribute	Description
Name	SECCUSTPSRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECPSRILIM

Attribute	Description
Name	SECPSRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTUNADV

Attribute	Description
Name	CUSTUNADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RISKCATEG

Attribute	Description
Name	RISKCATEG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CLSCCYALLWD

Attribute	**Description**
Name	CLSCCYALLWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

NETTREQD

Attribute	**Description**
Name	NETTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIABUNADV

Attribute	**Description**
Name	LIABUNADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MT920

Attribute	**Description**
Name	MT920
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RELPRICING

Attribute	**Description**
Name	RELPRICING
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FLGJOINT

Attribute	**Description**
Name	FLGJOINT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

KYCSTAT

Attribute	**Description**
Name	KYCSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,N,F

TOP

SSTAFF

Attribute	**Description**
Name	SSTAFF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

UPTYPE

Attribute	Description
Name	UPTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

KYC_REFNO

Attribute	Description
Name	KYC_REFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

JOINT_VENTURE

Attribute	Description
Name	JOINT_VENTURE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PRIVATE_CUSTOMER

Attribute	Description
Name	PRIVATE_CUSTOMER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

LC_COLLAT_PCT

Attribute	Description
Name	LC_COLLAT_PCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISELCMCUST

Attribute	Description
Name	ISELCMCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ELCMCUSTNO

Attribute	Description
Name	ELCMCUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ALT_CUST_NO

Attribute	Description
Name	ALT_CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DETERIORATION_DATE

Attribute	Description
Name	DETERIORATION_DATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHQ_TAX_EXEMPT_1

Attribute	Description
Name	CHQ_TAX_EXEMPT_1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

Custpersonal

Attribute	Description
Name	Custpersonal
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TITLE

Attribute	Description
Name	TITLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FSTNAME

Attribute	Description
Name	FSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MIDNAME

Attribute	Description
Name	MIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LSTNAME

Attribute	Description
Name	LSTNAME
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GUARDIAN

Attribute	Description
Name	GUARDIAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MINOR

Attribute	Description
Name	MINOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SEX

Attribute	Description
Name	SEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,F

TOP

NATIONID

Attribute	Description
Name	NATIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PPTNO

Attribute	Description
Name	PPTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PPTISSDT

Attribute	Description
Name	PPTISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PPTEXPDT

Attribute	Description
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DADD1

Attribute	Description
Name	DADD1
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DADD2

Attribute	Description
Name	DADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DADD3

Attribute	Description
Name	DADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FAX

Attribute	Description
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EMAIL

Attribute	**Description**
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PADD1

Attribute	**Description**
Name	PADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PADD2

Attribute	**Description**
Name	PADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PADD3

Attribute	**Description**
Name	PADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DCNTRY

Attribute	Description
Name	DCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PCNTRY

Attribute	Description
Name	PCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RESSTATUS

Attribute	Description
Name	RESSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / R,N

TOP

CUSTPREFIX1

Attribute	Description
Name	CUSTPREFIX1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

CUSTPREFIX2

Attribute	Description
Name	CUSTPREFIX2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

MOBNUM

Attribute	Description
Name	MOBNUM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SBMTAGEPROOF

Attribute	Description
Name	SBMTAGEPROOF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,P,V

TOP

CUST_COMM_MODE

Attribute	Description
Name	CUST_COMM_MODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,E

TOP

LAST_UPD_DT

Attribute	Description
Name	LAST_UPD_DT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Custdomestic

Attribute	Description
Name	Custdomestic
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

EDUSTAT

Attribute	Description
Name	EDUSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,U,G,P

TOP

MARITALSTAT

Attribute	Description
Name	MARITALSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: S,M,D,R,P,E,T

TOP

SPNAME

Attribute	Description
Name	SPNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SPEMPSTATUS

Attribute	Description
Name	SPEMPSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,T,S,U,R,P,N,O

TOP

DEPCHILD

Attribute	Description
Name	DEPCHILD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEPOTH

Attribute	Description
Name	DEPOTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOMODATE

Attribute	Description
Name	ACCOMODATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,O

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	9

TOP

Custprof

Attribute	Description	
Name	Custprof	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

EMPSTAT

Attribute	Description	
Name	EMPSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

EMPTENURE

Attribute	Description	
Name	EMPTENURE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

RETIREAGE

Attribute	Description	
Name	RETIREAGE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PREVDESIG

Attribute	Description
Name	PREVDESIG
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PREVEMP

Attribute	Description	
Name	PREVEMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CURRDESIG

Attribute	Description	
Name	CURRDESIG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CURREMP

Attribute	Description	
Name	CURREMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADD1

Attribute	Description	
Name	ADD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ADD2

Attribute	Description	
Name	ADD2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ADD3

Attribute	Description	
Name	ADD3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

TEL

Attribute	Description	
Name	TEL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

TELEX

Attribute	Description	
Name	TELEX	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

FAX

Attribute	Description
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

SALARY

Attribute	Description
Name	SALARY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHER1

Attribute	Description
Name	OTHER1
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RENT

Attribute	Description
Name	RENT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

INSURANCE

Attribute	Description
Name	INSURANCE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LOANPMNT

Attribute	Description
Name	LOANPMNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

OTHEXP

Attribute	Description
Name	OTHEXP
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

HOUSEVAL

Attribute	Description
Name	HOUSEVAL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CRCARD

Attribute	Description
Name	CRCARD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMTCCY1

Attribute	Description
Name	AMTCCY1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

EMPLOYER_DESC

Attribute	Description
Name	EMPLOYER_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

EMP_DESC

Attribute	Description
Name	EMP_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

Custcorp

Attribute	Description
Name	Custcorp
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CORPNAME

Attribute	Description
Name	CORPNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

NATIONID

Attribute	Description
Name	NATIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REGADD1

Attribute	Description
Name	REGADD1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REGADD2

Attribute	**Description**
Name	REGADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REGADD3

Attribute	**Description**
Name	REGADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INCORPDT

Attribute	**Description**
Name	INCORPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CAPITAL

Attribute	**Description**
Name	CAPITAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETWORTH

Attribute	Description
Name	NETWORTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INCORPCNTRY

Attribute	Description
Name	INCORPCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REGCNTRY

Attribute	Description
Name	REGCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CORPDESC

Attribute	Description
Name	CORPDESC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Custcorpdir

Attribute	Description
Name	Custcorpdir
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DIRNAME

Attribute	Description
Name	DIRNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR1

Attribute	Description
Name	NADDR1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR2

Attribute	Description
Name	NADDR2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR3

Attribute	Description
Name	NADDR3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR4

Attribute	Description
Name	NADDR4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRY

Attribute	Description
Name	COUNTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

TAXID

Attribute	Description
Name	TAXID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MOBNO

Attribute	**Description**
Name	MOBNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EMAIL

Attribute	**Description**
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Issuerdet

Attribute	**Description**
Name	Issuerdet
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OVERLIMIT

Attribute	**Description**
Name	OVERLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

OVERLMTCCY

Attribute	Description
Name	OVERLMTCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

Issuerlmts

Attribute	Description
Name	Issuerlmts
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CLTRLTYP

Attribute	Description
Name	CLTRLTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 70

TOP

LMTAMT

Attribute	Description
Name	LMTAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LMTCCY

Attribute	**Description**
Name	LMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ISSID

Attribute	**Description**
Name	ISSID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Custgrp

Attribute	**Description**
Name	Custgrp
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

GRPNO

Attribute	**Description**
Name	GRPNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RELATION

Attribute	Description
Name	RELATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Custshhold

Attribute	Description
Name	Custshhold
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SHHOLDID

Attribute	Description
Name	SHHOLDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SHHOLDPCT

Attribute	Description
Name	SHHOLDPCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHRHLDRNAME

Attribute	Description
Name	SHRHLDRNAME
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Clsccyrest

Attribute	Description
Name	Clsccyrest
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Bic

Attribute	Description
Name	Bic
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BICCD

Attribute	Description
Name	BICCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

Linkedac

Attribute	Description
Name	Linkedac
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

VRFD

Attribute	Description
Name	VRFD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LINKEDACCNO

Attribute	Description

Name	LINKEDACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

LINKEDACCIBAN

Attribute	**Description**
Name	LINKEDACCIBAN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINKEDACCBIC

Attribute	**Description**
Name	LINKEDACCBIC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

JointVenture

Attribute	**Description**
Name	JointVenture
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTYID

Attribute	**Description**
Name	PARTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	9

TOP

PARTYRATIO

Attribute	Description
Name	PARTYRATIO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 1

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

Custdoc-Chklist

Attribute	Description
Name	Custdoc-Chklist
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

CHECKED

Attribute	Description

Name	CHECKED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Doctype-Remarks

Attribute	**Description**
Name	Doctype-Remarks
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARK1

Attribute	**Description**
Name	REMARK1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 225

TOP

REMARK2

Attribute	**Description**
Name	REMARK2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 225

TOP

REMARK3

Attribute	**Description**
Name	REMARK3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	225

TOP

REMARK4

Attribute	Description
Name	REMARK4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK5

Attribute	Description
Name	REMARK5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK6

Attribute	Description
Name	REMARK6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK7

Attribute	Description
Name	REMARK7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK8

Attribute	Description
Name	REMARK8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK9

Attribute	Description
Name	REMARK9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK10

Attribute	Description
Name	REMARK10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

Custmis

Attribute	Description
Name	Custmis
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP

Datatype	String
Description	Indicates Management Information System Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CUST

Attribute	Description
Name	CUST
Datatype	String
Description	Indicates the Customer.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Custchnglog

Attribute	Description
Name	Custchnglog
Datatype	
Description	Indicates the Customer Change Log.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	Indicates the Old MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	Indicates the New MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Baltrnsfrlog

Attribute	Description
Name	Baltrnsfrlog
Datatype	
Description	Indicates the Balance Transfer Log.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRN

Attribute	Description

Name	BRN
Datatype	String
Description	Indicates the Branch Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDCD

Attribute	**Description**
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	**Description**
Name	FINYR
Datatype	String
Description	Indicates the Financial Year.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNDT

Attribute	**Description**
Name	TXNDT
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

GLCODE

Attribute	**Description**
Name	GLCODE
Datatype	String
Description	Indicates the GL Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 9

TOP

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	Indicates the Old MIS Code.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	Indicates the New MIS Code.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

TRNIND

Attribute	Description
Name	TRNIND
Datatype	String
Description	Indicates Transfer Identification Number.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Dfltcd

Attribute	Description
Name	Dfltcd
Datatype	
Description	Indicates the Customer MIS Classes.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MISCD

Attribute	Description	
Name	MISCD	
Datatype	String	
Description	Indicates the MIS Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Dfltcda

Attribute	Description	
Name	Dfltcda	
Datatype		
Description	Indicates the Composite MIS Classes.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MISCLS

Attribute	Description	
Name	MISCLS	
Datatype	String	
Description	Indicates the MIS Class.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MISCD

Attribute	Description	
Name	MISCD	
Datatype	String	
Description	Indicates the MIS Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Custloghead

Attribute	Description
Name	Custloghead
Datatype	
Description	Indicates the Customer Log Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Jointcustomer

Attribute	Description
Name	Jointcustomer
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Custjoint

Attribute	Description
Name	Custjoint
Datatype	
Description	Indicates Customer Joint.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTPREFIX

Attribute	Description
Name	CUSTPREFIX
Datatype	String
Description	Indicates the Customer Prefix.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FRSTNAME

Attribute	Description
Name	FRSTNAME
Datatype	String
Description	Indicates the First Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MIDNAME

Attribute	Description
Name	MIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LASTNAME

Attribute	Description
Name	LASTNAME
Datatype	String
Description	Indicates the Last Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SEX

Attribute	Description
Name	SEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,F

TOP

PPNO

Attribute	Description
Name	PPNO
Datatype	String
Description	Indicates Passport Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PPTISSDT

Attribute	Description
Name	PPTISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PPTEXPDT

Attribute	Description
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADD2

Attribute	Description	
Name	ADD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADD3

Attribute	Description	
Name	ADD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

TEL

Attribute	Description	
Name	TEL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EMAIL

Attribute	Description	
Name	EMAIL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	255

TOP

SSN

Attribute	Description	
Name	SSN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	11

TOP

DECEASED

Attribute	Description	
Name	DECEASED	
Datatype	String	
Description	Indicates whether Deceased or not. The value should be either D or N.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,N

TOP

RESISTAT

Attribute	Description	
Name	RESISTAT	
Datatype	String	
Description	Indicates the Resistant Status. The value could be either R or N.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	R,N

TOP

Cust-Acc-Det

Attribute	Description	
Name	Cust-Acc-Det	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Diary-Mst

Attribute	Description
Name	Diary-Mst
Datatype	
Description	Indicates Diary Master.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

UNTTYP

Attribute	Description
Name	UNTTYP
Datatype	String
Description	Indicates Unit Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

UNTVAL

Attribute	Description
Name	UNTVAL
Datatype	String

Description	Indicates Unit Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BRN

Attribute	**Description**
Name	BRN
Datatype	String
Description	Indicates the Branch Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INSTR

Attribute	**Description**
Name	INSTR
Datatype	String
Description	Indicates Instructions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

INSTRTYPE

Attribute	**Description**
Name	INSTRTYPE
Datatype	String
Description	Indicates Instruction Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

EXEDAYS

Attribute	**Description**
Name	EXEDAYS
Datatype	Number
Description	Indicates Execution Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXEMONTHS

Attribute	Description
Name	EXEMONTHS
Datatype	Number
Description	Indicates Execution Months
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXEYEARS

Attribute	Description
Name	EXEYEARS
Datatype	Number
Description	Indicates Execution Years
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MNTHENDFLG

Attribute	Description
Name	MNTHENDFLG
Datatype	String
Description	Indicates Month End Flag. Flag Can be either Y or N.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

HLDRULE

Attribute	Description
Name	HLDRULE
Datatype	String
Description	Indicates Holiday Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FRSTDUEDT

Attribute	Description
Name	FRSTDUEDT
Datatype	Date
Description	Indicates First Due Date.

Attributes	Attribute	Description
	minOccurs	0

TOP

NXTDUEDT

Attribute	Description
Name	NXTDUEDT
Datatype	Date
Description	Indicates Next Due Date
Attributes	Attribute: minOccurs — Description: 0

TOP

NXTEXEDT

Attribute	Description
Name	NXTEXEDT
Datatype	Date
Description	Indicates Next Execution Date.
Attributes	Attribute: minOccurs — Description: 0

TOP

CONDELEM

Attribute	Description
Name	CONDELEM
Datatype	String
Description	Indicates Condition Elements.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

OPRTR

Attribute	Description
Name	OPRTR
Datatype	String
Description	Indicates Operator.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2

TOP

CONDVAL

Attribute	Description
Name	CONDVAL

Datatype	Number
Description	Indicates Condition Value.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOFCR

Attribute	Description
Name	ACCOFCR
Datatype	String
Description	Indicates Account Officer.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPLINSTRTYP

Attribute	Description
Name	SPLINSTRTYP
Datatype	String
Description	Indicates Special Instruction Type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	Indicates Expiry Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPLINSTR

Attribute	Description
Name	SPLINSTR
Datatype	String
Description	Indicates Special Instructions.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Custaccdet

Attribute	Description
Name	Custaccdet
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkage details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String

Description	Indicates the customer
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RELATIONSHIP

Attribute	**Description**
Name	RELATIONSHIP
Datatype	String
Description	Indicate relations
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

INHERIT

Attribute	**Description**
Name	INHERIT
Datatype	String
Description	Indicate,include relationship Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DESCP

Attribute	**Description**
Name	DESCP
Datatype	String
Description	Indicates description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Custacdetail

Attribute	**Description**
Name	Custacdetail
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

CUSTTEXT

Attribute	Description
Name	CUSTTEXT
Datatype	
Description	Include customer details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	Indicates sequence number
Attributes	Attribute: minOccurs — Description: 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

TDESC

Attribute	Description

Name	TDESC
Datatype	String
Description	Indicate text description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

Sttms-Debit

Attribute	**Description**
Name	Sttms-Debit
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	Indicates the Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACTNO

Attribute	Description
Name	ACTNO
Datatype	String
Description	Indicates the Account Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Sttms-Detail

Attribute	Description
Name	Sttms-Detail
Datatype	
Description	Indicates Customer Details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description

Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REQUEST_REFERENCE_NO

Attribute	Description
Name	REQUEST_REFERENCE_NO
Datatype	String
Description	Indicates the Request Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CARDNO

Attribute	Description
Name	CARDNO
Datatype	String
Description	Indicates the Card Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 19

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	Indicates the Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CARD_PRODUCT

Attribute	Description
Name	CARD_PRODUCT
Datatype	String
Description	Indicates the Product code.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRIMARY_CARD

Attribute	Description	
Name	PRIMARY_CARD	
Datatype	String	
Description	Indicates the Primary Card Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NAME_ON_CARD

Attribute	Description	
Name	NAME_ON_CARD	
Datatype	String	
Description	Indicates the Name on Card.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

OWNER_ID_NO

Attribute	Description	
Name	OWNER_ID_NO	
Datatype	String	
Description	Indicates the Owner ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

CARD_ISSUED_DT

Attribute	Description	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Indicates the Card Issue Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CARD_EXPIRY_DT

Attribute	Description
Name	CARD_EXPIRY_DT
Datatype	Date
Description	Indicates the Card Expiry Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_STATUS

Attribute	Description
Name	CARD_STATUS
Datatype	String
Description	Indicates the Card Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	Indicates the Record Stat.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTH_STAT

Attribute	Description
Name	AUTH_STAT
Datatype	String
Description	Indicates the Auth Stat.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CARD_BIN

Attribute	Description
Name	CARD_BIN

Datatype	String
Description	Indicates the Card Bin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CUST_AC_NO

Attribute	**Description**
Name	CUST_AC_NO
Datatype	String
Description	Indicates the Customer Account Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Extsys-Ws-Master

Attribute	**Description**
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	**Description**
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXTWSRESP

Attribute	**Description**
Name	EXTWSRESP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

Stvws-Cust-Trntax

Attribute	Description
Name	Stvws-Cust-Trntax
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Sttms-Cust-Trn-Tax

Attribute	Description
Name	Sttms-Cust-Trn-Tax
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TAX_SCHEME

Attribute	Description
Name	TAX_SCHEME
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

TXN_TAX_EXEMPTED

Attribute	**Description**
Name	TXN_TAX_EXEMPTED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TXN_TAX_EXEMPTION_PERCENT

Attribute	**Description**
Name	TXN_TAX_EXEMPTION_PERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXN_TAX_EFF_DATE

Attribute	**Description**
Name	TXN_TAX_EFF_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXN_TAX_EXEMPTION_REASON

Attribute	**Description**
Name	TXN_TAX_EXEMPTION_REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Customer-PK*
      - *CUSTNO*
    - *Customer-IO*
      - *CUSTNO*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Customer-PK

Attribute	Description
Name	Customer-PK
Datatype	
Description	

TOP

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Customer-IO

Attribute	Description
Name	Customer-IO
Datatype	
Description	

TOP

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.12.AuthorizeTDAmountBlock

AuthorizeTDAmountBlock

2.12.1.ST-AuthorizeTDAmountBlock-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-Full*
    - *ACC*
    - *AMTBLKNO*
    - *AMT*
    - *EXPDATE*
    - *REM*
    - *ABLKTYPE*
    - *REFERENCE_NO*
    - *HPCODE*
    - *EFFDATE*
    - *HOLDDESC*
    - *BRANCH*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Amount-Blocks-Full

Attribute	Description
Name	Amount-Blocks-Full
Datatype	
Description	

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTBLKNO

Attribute	Description	
Name	AMTBLKNO	
Datatype	String	
Description	Indicates the Amount Block Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

EXPDATE

Attribute	Description	
Name	EXPDATE	
Datatype	Date	
Description	Indicates the Expiry Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ABLKTYPE

Attribute	Description
Name	ABLKTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,S,P,E,A,C,B,D

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 40

TOP

HPCODE

Attribute	Description
Name	HPCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	Attribute: minOccurs, Description: 0

TOP

HOLDDESC

Attribute	Description
Name	HOLDDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 255

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length, Description: 3 Restrictions: pattern, Description: [a-zA-Z_0-9]{3}

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.12.2.ST-AuthorizeTDAmountBlock-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-IO*
    - *AMTBLKNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	

Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Amount-Blocks-IO

Attribute	Description
Name	Amount-Blocks-IO
Datatype	
Description	

TOP

AMTBLKNO

Attribute	Description	
Name	AMTBLKNO	
Datatype	String	
Description	Indicates the Amount Block Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

2.12.3.ST-AuthorizeTDAmountBlock-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-Full*
    - *ACC*
    - *AMTBLKNO*
    - *AMT*
    - *EXPDATE*
    - *REM*
    - *ABLKTYPE*
    - *REFERENCE_NO*
    - *HPCODE*
    - *EFFDATE*
    - *HOLDDESC*
    - *BRANCH*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String

Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Amount-Blocks-Full

Attribute	Description
Name	Amount-Blocks-Full
Datatype	
Description	

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTBLKNO

Attribute	Description	
Name	AMTBLKNO	
Datatype	String	
Description	Indicates the Amount Block Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ABLKTYPE

Attribute	Description
Name	ABLKTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,S,P,E,A,C,B,D

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 40

TOP

HPCODE

Attribute	Description
Name	HPCODE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HOLDDESC

Attribute	Description
Name	HOLDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description

Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Amount-Blocks-PK*
      - *AMTBLKNO*
    - *Amount-Blocks-IO*
      - *AMTBLKNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Amount-Blocks-PK

Attribute	Description
Name	Amount-Blocks-PK
Datatype	
Description	

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Amount-Blocks-IO

Attribute	Description
Name	Amount-Blocks-IO
Datatype	
Description	

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.13.CloseCustomer

Closure of Customer

2.13.1.ST-CloseCustomer-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Customer-Full*
    - *NAME*
    - *ADDRLN1*
    - *ADDRLN3*
    - *ADDRLN2*
    - *ADDRLN4*
    - *SWIFTCD*
    - *FAX*
    - *COUNTRY*
    - *NLTY*
    - *LANG*
    - *EXPCNTRY*
    - *UIDNAME*
    - *UIDVAL*
    - *LOC*
    - *FROZEN*

DEAD
WHRUNKN
GRPCD
CHGGRP
CUSTCLGGRP
TAXGROUP
CCATEG
EXPCAT
CUSTCLASSFN
FXNETTCUST
XREF
MEDIA
SSN
CIFSTAT
CIFSTATSNC
MAILRSREQD
CLSPARTICIPANT
CRMCUST
ISSUCUST
TRSRYCUST
CUSTNO
SNAME
LBRN
CTYPE
FULLNAME
AMLCUSTGRP
AMLREQD
FLGUTLTYPRVDR
UTLTYPRVDRID
CHKDIGITVALREQD
ALGID
CONSTAXCERTRQD
INDTAXCERTRQD
HOACNO
RISKPRFL
DRCAT
FTACCASOF
UDF1
UDF2
UDF3
UDF4
UDF5
UDFLBL1
UDFLBL2

UDFLBL3
UDFLBL4
UDFLBL5
FXCUSTCLRILIM
OVRLIM
FX_CLEAN_RISK
CRRATE
REVDT
LIMCCY
SECCUSTCLRILIM
SECCLRILIM
SECCUSTPSRILIM
SECPSRILIM
CUSTUNADV
RISKCATEG
CLSCCYALLWD
NETTREQD
LIABUNADV
MT920
RELPRICING
FLGJOINT
KYCSTAT
SSTAFF
UPTYPE
KYC_REFNO
JOINT_VENTURE
PRIVATE_CUSTOMER
LC_COLLAT_PCT
ISELCMCUST
ELCMCUSTNO
ALT_CUST_NO
DETERIORATION_DATE
CHQ_TAX_EXEMPT_1
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Custpersonal
- *TITLE*
- *FSTNAME*
- *MIDNAME*

LSTNAME
DOB
GUARDIAN
MINOR
SEX
NATIONID
PPTNO
PPTISSDT
PPTEXPDT
DADD1
DADD2
DADD3
TEL
FAX
EMAIL
PADD1
PADD2
PADD3
DCNTRY
PCNTRY
RESSTATUS
CUSTPREFIX1
CUSTPREFIX2
MOBNUM
SBMTAGEPROOF
CUST_COMM_MODE
LAST_UPD_DT
Custdomestic
- *EDUSTAT*
- *MARITALSTAT*
- *SPNAME*
- *SPEMPSTATUS*
- *DEPCHILD*
- *DEPOTH*
- *ACCOMODATE*
- *CUSTNO*

Custprof
- *EMPSTAT*
- *EMPTENURE*
- *RETIREAGE*
- *PREVDESIG*
- *PREVEMP*
- *CURRDESIG*
- *CURREMP*

ADD1
ADD2
ADD3
TEL
TELEX
FAX
EMAIL
SALARY
OTHER1
RENT
INSURANCE
LOANPMNT
OTHEXP
HOUSEVAL
CRCARD
CNTY
AMTCCY1
CUSTNO
EMPLOYER_DESC
EMP_DESC

Custcorp

CORPNAME
NATIONID
REGADD1
REGADD2
REGADD3
INCORPDT
CAPITAL
NETWORTH
INCORPCNTRY
REGCNTRY
AMTCCY
CORPDESC
CUSTNO
Custcorpdir

DIRNAME
TEL
NADDR1
NADDR2
NADDR3
NADDR4
ADDR1
ADDRS2
ADDRS3

COUNTRY
TAXID
MOBNO
EMAIL
Issuerdet
OVERLIMIT
CUSTNO
OVERLMTCCY
Issuerlmts
CLTRLTYP
LMTAMT
LMTCCY
ISSID
Custgrp
GRPNO
RELATION
Custshhold
SHHOLDID
SHHOLDPCT
SHRHLDRNAME
Clsccyrest
CCY
DESC
Bic
ACC
BICCD
Linkedac
VRFD
LINKEDACCNO
LINKEDACCIBAN
LINKEDACCBIC
JointVenture
PARTYID
PARTYRATIO
PARTYNAME
Custdoc-Chklist
DOCUMENT_TYPE
CHECKED
Doctype-Remarks
REMARK1
REMARK2
REMARK3
REMARK4
REMARK5

- *REMARK6*
- *REMARK7*
- *REMARK8*
- *REMARK9*
- *REMARK10*

Custmis

- *MISGRP*
- *CUST*
- *BRNCD*
- *Custchnglog*
  - *MISCLS*
  - *TXNDT*
  - *OLDMISCD*
  - *NWMISCD*
- *Baltrnsfrlog*
  - *BRN*
  - *PRDCD*
  - *FINYR*
  - *TXNDT*
  - *GLCODE*
  - *MISCLS*
  - *OLDMISCD*
  - *NWMISCD*
  - *TRNIND*
  - *CCY*
  - *AMT*
  - *XRATE*
- *Dfltcd*
  - *MISCLS*
  - *MISCD*
- *Dfltcda*
  - *MISCLS*
  - *MISCD*
- *Custloghead*

Jointcustomer

- *CUSTNO*
- *Custjoint*
  - *CUSTPREFIX*
  - *FRSTNAME*
  - *MIDNAME*
  - *LASTNAME*
  - *DOB*
  - *SEX*
  - *PPNO*

PPTISSDT

PPTEXPDT

ADD1

ADD2

ADD3

TEL

EMAIL

SSN

DECEASED

RESISTAT

Cust-Acc-Det

CUSTNO

Diary-Mst

INSTRNO

UNTTYP

UNTVAL

BRN

INSTR

INSTRTYPE

EXEDAYS

EXEMONTHS

EXEYEARS

MNTHENDFLG

HLDRULE

FRSTDUEDT

NXTDUEDT

NXTEXEDT

CONDELEM

OPRTR

CONDVAL

ACCOFCR

SPLINSTRTYP

EXPDT

SPLINSTR

Custaccdet

CUSTNO

BRNCD

Relationship-Linkage

CUSTOMER

RELATIONSHIP

INHERIT

DESCP

Custacdetail

CUSTNO

CUSTTEXT

SEQNO

CUSTNO

TDESC

UDFDETAILS

FLDNAM

FLDVAL

Sttms-Debit

BRANCH_CODE

CUST_NO

ACTNO

Sttms-Detail

BRANCH_CODE

REQUEST_REFERENCE_NO

CARDNO

CUST_NO

CARD_PRODUCT

PRIMARY_CARD

NAME_ON_CARD

OWNER_ID_NO

CARD_ISSUED_DT

CARD_EXPIRY_DT

CARD_STATUS

RECORD_STAT

AUTH_STAT

CARD_BIN

CUST_AC_NO

Extsys-Ws-Master

Extsys-Ws-Details

EXTWSRESP

USERREMARKS

Stvws-Cust-Trntax

CUSTOMER_NO

Sttms-Cust-Trn-Tax

TAX_SCHEME

TXN_TAX_EXEMPTED

TXN_TAX_EXEMPTION_PERCENT

TXN_TAX_EFF_DATE

TXN_TAX_EXEMPTION_REASON

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Customer-Full

Attribute	Description
Name	Customer-Full
Datatype	
Description	

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

ADDRLN1

Attribute	Description	
Name	ADDRLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN3

Attribute	Description	
Name	ADDRLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN2

Attribute	Description	
Name	ADDRLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN4

Attribute	Description
Name	ADDRLN4
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SWIFTCD

Attribute	Description
Name	SWIFTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FAX

Attribute	Description
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRY

Attribute	Description
Name	COUNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NLTY

Attribute	Description
Name	NLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	3

TOP

LANG

Attribute	Description	
Name	LANG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

TOP

EXPCNTRY

Attribute	Description	
Name	EXPCNTRY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

UIDNAME

Attribute	Description	
Name	UIDNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

UIDVAL

Attribute	Description	
Name	UIDVAL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

LOC

Attribute	Description
Name	LOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FROZEN

Attribute	Description
Name	FROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEAD

Attribute	Description
Name	DEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

WHRUNKN

Attribute	Description
Name	WHRUNKN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CHGGRP

Attribute	Description
Name	CHGGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CUSTCLGGRP

Attribute	Description
Name	CUSTCLGGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAXGROUP

Attribute	Description
Name	TAXGROUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CCATEG

Attribute	Description
Name	CCATEG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EXPCAT

Attribute	**Description**
Name	EXPCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUSTCLASSFN

Attribute	**Description**
Name	CUSTCLASSFN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

FXNETTCUST

Attribute	**Description**
Name	FXNETTCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

XREF

Attribute	**Description**
Name	XREF
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SSN

Attribute	Description
Name	SSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

CIFSTAT

Attribute	Description
Name	CIFSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CIFSTATSNC

Attribute	Description
Name	CIFSTATSNC
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAILRSREQD

Attribute	Description
Name	MAILRSREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLSPARTICIPANT

Attribute	Description
Name	CLSPARTICIPANT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CRMCUST

Attribute	Description
Name	CRMCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ISSUCUST

Attribute	Description
Name	ISSUCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRSRYCUST

Attribute	Description
Name	TRSRYCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

SNAME

Attribute	Description
Name	SNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 20

TOP

LBRN

Attribute	Description
Name	LBRN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CTYPE

Attribute	Description
Name	CTYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,C,B

TOP

FULLNAME

Attribute	Description
Name	FULLNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

AMLCUSTGRP

Attribute	Description
Name	AMLCUSTGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

AMLREQD

Attribute	Description
Name	AMLREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FLGUTLTYPRVDR

Attribute	Description
Name	FLGUTLTYPRVDR
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

UTLTYPRVDRID

Attribute	Description	
Name	UTLTYPRVDRID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHKDIGITVALREQD

Attribute	Description	
Name	CHKDIGITVALREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALGID

Attribute	Description	
Name	ALGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CONSTAXCERTRQD

Attribute	Description	
Name	CONSTAXCERTRQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

INDTAXCERTRQD

Attribute	**Description**
Name	INDTAXCERTRQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOACNO

Attribute	**Description**
Name	HOACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RISKPRFL

Attribute	**Description**
Name	RISKPRFL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DRCAT

Attribute	**Description**
Name	DRCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FTACCASOF

Attribute	Description
Name	FTACCASOF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,M,D

TOP

UDF1

Attribute	Description
Name	UDF1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDF2

Attribute	Description
Name	UDF2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDF3

Attribute	Description
Name	UDF3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

UDF4

Attribute	Description
Name	UDF4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

UDF5

Attribute	Description
Name	UDF5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDFLBL1

Attribute	Description
Name	UDFLBL1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDFLBL2

Attribute	Description
Name	UDFLBL2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDFLBL3

Attribute	Description
Name	UDFLBL3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL4

Attribute	Description
Name	UDFLBL4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL5

Attribute	Description
Name	UDFLBL5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

FXCUSTCLRILIM

Attribute	Description
Name	FXCUSTCLRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OVRLIM

Attribute	Description
Name	OVRLIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FX_CLEAN_RISK

Attribute	Description
Name	FX_CLEAN_RISK
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CRRATE

Attribute	Description
Name	CRRATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

REVDT

Attribute	Description
Name	REVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIMCCY

Attribute	Description
Name	LIMCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SECCUSTCLRILIM

Attribute	Description
Name	SECCUSTCLRILIM
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SECCLRILIM

Attribute	Description
Name	SECCLRILIM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SECCUSTPSRILIM

Attribute	Description
Name	SECCUSTPSRILIM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SECPSRILIM

Attribute	Description
Name	SECPSRILIM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CUSTUNADV

Attribute	Description
Name	CUSTUNADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

RISKCATEG

Attribute	Description
Name	RISKCATEG
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CLSCCYALLWD

Attribute	Description
Name	CLSCCYALLWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

NETTREQD

Attribute	Description
Name	NETTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIABUNADV

Attribute	Description
Name	LIABUNADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MT920

Attribute	Description
Name	MT920
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

RELPRICING

Attribute	Description	
Name	RELPRICING	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

FLGJOINT

Attribute	Description	
Name	FLGJOINT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

KYCSTAT

Attribute	Description	
Name	KYCSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	V,N,F

TOP

SSTAFF

Attribute	Description	
Name	SSTAFF	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

UPTYPE

Attribute	Description
Name	UPTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

KYC_REFNO

Attribute	Description
Name	KYC_REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

JOINT_VENTURE

Attribute	Description
Name	JOINT_VENTURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIVATE_CUSTOMER

Attribute	Description
Name	PRIVATE_CUSTOMER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LC_COLLAT_PCT

Attribute	Description
Name	LC_COLLAT_PCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISELCMCUST

Attribute	Description
Name	ISELCMCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ELCMCUSTNO

Attribute	Description
Name	ELCMCUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ALT_CUST_NO

Attribute	Description
Name	ALT_CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DETERIORATION_DATE

Attribute	Description
Name	DETERIORATION_DATE
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CHQ_TAX_EXEMPT_1

Attribute	Description	
Name	CHQ_TAX_EXEMPT_1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Custpersonal

Attribute	Description
Name	Custpersonal

ORACLE

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TITLE

Attribute	Description
Name	TITLE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FSTNAME

Attribute	Description
Name	FSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MIDNAME

Attribute	Description
Name	MIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LSTNAME

Attribute	Description
Name	LSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

DOB

Attribute	Description	
Name	DOB	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

GUARDIAN

Attribute	Description	
Name	GUARDIAN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

MINOR

Attribute	Description	
Name	MINOR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

SEX

Attribute	Description	
Name	SEX	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	M,F

TOP

NATIONID

Attribute	Description
Name	NATIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PPTNO

Attribute	Description
Name	PPTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PPTISSDT

Attribute	Description
Name	PPTISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PPTEXPDT

Attribute	Description
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DADD1

Attribute	Description
Name	DADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

DADD2

Attribute	Description	
Name	DADD2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

DADD3

Attribute	Description	
Name	DADD3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

TEL

Attribute	Description	
Name	TEL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

FAX

Attribute	Description	
Name	FAX	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PADD1

Attribute	Description
Name	PADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PADD2

Attribute	Description
Name	PADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PADD3

Attribute	Description
Name	PADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DCNTRY

Attribute	Description
Name	DCNTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

PCNTRY

Attribute	Description
Name	PCNTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

RESSTATUS

Attribute	Description
Name	RESSTATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: R,N

TOP

CUSTPREFIX1

Attribute	Description
Name	CUSTPREFIX1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

CUSTPREFIX2

Attribute	Description
Name	CUSTPREFIX2

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

MOBNUM

Attribute	**Description**
Name	MOBNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SBMTAGEPROOF

Attribute	**Description**
Name	SBMTAGEPROOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,P,V

TOP

CUST_COMM_MODE

Attribute	**Description**
Name	CUST_COMM_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,E

TOP

LAST_UPD_DT

Attribute	**Description**
Name	LAST_UPD_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Custdomestic

Attribute	Description
Name	Custdomestic
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EDUSTAT

Attribute	Description
Name	EDUSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,U,G,P

TOP

MARITALSTAT

Attribute	Description
Name	MARITALSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,M,D,R,P,E,T

TOP

SPNAME

Attribute	Description
Name	SPNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SPEMPSTATUS

Attribute	Description
Name	SPEMPSTATUS

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,S,U,R,P,N,O

TOP

DEPCHILD

Attribute	**Description**
Name	DEPCHILD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEPOTH

Attribute	**Description**
Name	DEPOTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCOMODATE

Attribute	**Description**
Name	ACCOMODATE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,C,O

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Custprof

Attribute	Description
Name	Custprof
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EMPSTAT

Attribute	Description
Name	EMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

EMPTENURE

Attribute	Description
Name	EMPTENURE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RETIREAGE

Attribute	Description
Name	RETIREAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PREVDESIG

Attribute	Description
Name	PREVDESIG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

PREVEMP

Attribute	Description
Name	PREVEMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CURRDESIG

Attribute	Description
Name	CURRDESIG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CURREMP

Attribute	Description
Name	CURREMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADD3

Attribute	Description
Name	ADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TELEX

Attribute	Description
Name	TELEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FAX

Attribute	Description
Name	FAX
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

SALARY

Attribute	Description
Name	SALARY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

OTHER1

Attribute	Description
Name	OTHER1
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RENT

Attribute	Description
Name	RENT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

INSURANCE

Attribute	Description
Name	INSURANCE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LOANPMNT

Attribute	Description
Name	LOANPMNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

OTHEXP

Attribute	Description
Name	OTHEXP
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

HOUSEVAL

Attribute	Description
Name	HOUSEVAL
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

CRCARD

Attribute	Description
Name	CRCARD
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMTCCY1

Attribute	Description
Name	AMTCCY1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

EMPLOYER_DESC

Attribute	Description
Name	EMPLOYER_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

EMP_DESC

Attribute	Description

Name	EMP_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Custcorp

Attribute	**Description**
Name	Custcorp
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CORPNAME

Attribute	**Description**
Name	CORPNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NATIONID

Attribute	**Description**
Name	NATIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REGADD1

Attribute	**Description**
Name	REGADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

REGADD2

Attribute	Description	
Name	REGADD2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

REGADD3

Attribute	Description	
Name	REGADD3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INCORPDT

Attribute	Description	
Name	INCORPDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

CAPITAL

Attribute	Description	
Name	CAPITAL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

NETWORTH

Attribute	Description
Name	NETWORTH

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INCORPCNTRY

Attribute	Description
Name	INCORPCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REGCNTRY

Attribute	Description
Name	REGCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CORPDESC

Attribute	Description
Name	CORPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

Custcorpdir

Attribute	Description
Name	Custcorpdir
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

DIRNAME

Attribute	Description
Name	DIRNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

NADDR1

Attribute	Description
Name	NADDR1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR2

Attribute	Description
Name	NADDR2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR3

Attribute	Description
Name	NADDR3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR4

Attribute	Description
Name	NADDR4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDR1

Attribute	Description

Name	ADDR1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	**Description**
Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS3

Attribute	**Description**
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRY

Attribute	**Description**
Name	COUNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXID

Attribute	**Description**
Name	TAXID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MOBNO

Attribute	Description
Name	MOBNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Issuerdet

Attribute	Description
Name	Issuerdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OVERLIMIT

Attribute	Description
Name	OVERLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO

ORACLE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OVERLMTCCY

Attribute	**Description**
Name	OVERLMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Issuerlmts

Attribute	**Description**
Name	Issuerlmts
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CLTRLTYP

Attribute	**Description**
Name	CLTRLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 70

TOP

LMTAMT

Attribute	**Description**
Name	LMTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LMTCCY

Attribute	Description
Name	LMTCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ISSID

Attribute	Description
Name	ISSID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

Custgrp

Attribute	Description
Name	Custgrp
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

GRPNO

Attribute	Description
Name	GRPNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

RELATION

Attribute	Description

Name	RELATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Custshhold

Attribute	Description
Name	Custshhold
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SHHOLDID

Attribute	Description
Name	SHHOLDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SHHOLDPCT

Attribute	Description
Name	SHHOLDPCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHRHLDRNAME

Attribute	Description
Name	SHRHLDRNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Clsccyrest

Attribute	Description
Name	Clsccyrest
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Bic

Attribute	Description
Name	Bic
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC

Attribute	Description
Name	ACC

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BICCD

Attribute	**Description**
Name	BICCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

Linkedac

Attribute	**Description**
Name	Linkedac
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VRFD

Attribute	**Description**
Name	VRFD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LINKEDACCNO

Attribute	**Description**
Name	LINKEDACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	30

TOP

LINKEDACCIBAN

Attribute	Description	
Name	LINKEDACCIBAN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LINKEDACCBIC

Attribute	Description	
Name	LINKEDACCBIC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

JointVenture

Attribute	Description	
Name	JointVenture	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PARTYID

Attribute	Description	
Name	PARTYID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PARTYRATIO

Attribute	Description
Name	PARTYRATIO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Custdoc-Chklist

Attribute	Description
Name	Custdoc-Chklist
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHECKED

Attribute	Description
Name	CHECKED
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Doctype-Remarks

Attribute	Description
Name	Doctype-Remarks
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARK1

Attribute	Description
Name	REMARK1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK2

Attribute	Description
Name	REMARK2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK3

Attribute	Description
Name	REMARK3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK4

Attribute	Description
Name	REMARK4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK5

Attribute	Description
Name	REMARK5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK6

Attribute	Description
Name	REMARK6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK7

Attribute	Description
Name	REMARK7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK8

Attribute	Description
Name	REMARK8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK9

Attribute	Description
Name	REMARK9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK10

Attribute	Description
Name	REMARK10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

Custmis

Attribute	Description
Name	Custmis
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates Management Information System Group.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CUST

Attribute	**Description**
Name	CUST
Datatype	String
Description	Indicates the Customer.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRNCD

Attribute	**Description**
Name	BRNCD
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Custchnglog

Attribute	**Description**
Name	Custchnglog
Datatype	
Description	Indicates the Customer Change Log.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	**Description**
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	Indicates the Old MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	Indicates the New MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Baltrnsfrlog

Attribute	Description
Name	Baltrnsfrlog
Datatype	
Description	Indicates the Balance Transfer Log.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String

Description	Indicates the Branch Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDCD

Attribute	**Description**
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	**Description**
Name	FINYR
Datatype	String
Description	Indicates the Financial Year.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNDT

Attribute	**Description**
Name	TXNDT
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

GLCODE

Attribute	**Description**
Name	GLCODE
Datatype	String
Description	Indicates the GL Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

ORACLE

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	Indicates the Old MIS Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	Indicates the New MIS Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TRNIND

Attribute	Description
Name	TRNIND
Datatype	String
Description	Indicates Transfer Identification Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	Attribute: minOccurs — Description: 0

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate.
Attributes	Attribute: minOccurs — Description: 0

TOP

Dfltcd

Attribute	Description
Name	Dfltcd
Datatype	
Description	Indicates the Customer MIS Classes.
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	Attribute: minOccurs — Description: 1

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCD

Attribute	**Description**
Name	MISCD
Datatype	String
Description	Indicates the MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Dfltcda

Attribute	**Description**
Name	Dfltcda
Datatype	
Description	Indicates the Composite MIS Classes.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	**Description**
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCD

Attribute	**Description**
Name	MISCD
Datatype	String
Description	Indicates the MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Custloghead

Attribute	Description
Name	Custloghead
Datatype	
Description	Indicates the Customer Log Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Jointcustomer

Attribute	Description
Name	Jointcustomer
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Custjoint

Attribute	Description
Name	Custjoint
Datatype	
Description	Indicates Customer Joint.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTPREFIX

Attribute	Description
Name	CUSTPREFIX
Datatype	String
Description	Indicates the Customer Prefix.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FRSTNAME

Attribute	Description
Name	FRSTNAME
Datatype	String
Description	Indicates the First Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MIDNAME

Attribute	Description
Name	MIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LASTNAME

Attribute	Description
Name	LASTNAME
Datatype	String
Description	Indicates the Last Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SEX

Attribute	Description
Name	SEX
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,F

TOP

PPNO

Attribute	Description
Name	PPNO
Datatype	String
Description	Indicates Passport Number.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

PPTISSDT

Attribute	Description
Name	PPTISSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PPTEXPDT

Attribute	Description
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADD3

Attribute	Description
Name	ADD3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

SSN

Attribute	Description
Name	SSN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

DECEASED

Attribute	Description
Name	DECEASED
Datatype	String
Description	Indicates whether Deceased or not. The value should be either D or N.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,N

TOP

RESISTAT

Attribute	Description
Name	RESISTAT
Datatype	String
Description	Indicates the Resistant Status. The value could be either R or N.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: R,N

TOP

Cust-Acc-Det

Attribute	Description
Name	Cust-Acc-Det
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Diary-Mst

Attribute	**Description**
Name	Diary-Mst
Datatype	
Description	Indicates Diary Master.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSTRNO

Attribute	**Description**
Name	INSTRNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

UNTTYP

Attribute	**Description**
Name	UNTTYP
Datatype	String
Description	Indicates Unit Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

UNTVAL

Attribute	**Description**
Name	UNTVAL
Datatype	String
Description	Indicates Unit Value
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description	Indicates the Branch Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

INSTR

Attribute	Description	
Name	INSTR	
Datatype	String	
Description	Indicates Instructions	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

INSTRTYPE

Attribute	Description	
Name	INSTRTYPE	
Datatype	String	
Description	Indicates Instruction Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

EXEDAYS

Attribute	Description	
Name	EXEDAYS	
Datatype	Number	
Description	Indicates Execution Days	
Attributes	Attribute	Description
	minOccurs	0

TOP

EXEMONTHS

Attribute	Description
Name	EXEMONTHS
Datatype	Number
Description	Indicates Execution Months
Attributes	Attribute: minOccurs, Description: 0

TOP

EXEYEARS

Attribute	Description
Name	EXEYEARS
Datatype	Number
Description	Indicates Execution Years
Attributes	Attribute: minOccurs, Description: 0

TOP

MNTHENDFLG

Attribute	Description
Name	MNTHENDFLG
Datatype	String
Description	Indicates Month End Flag. Flag Can be either Y or N.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

HLDRULE

Attribute	Description
Name	HLDRULE
Datatype	String
Description	Indicates Holiday Rule
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 1

TOP

FRSTDUEDT

Attribute	Description
Name	FRSTDUEDT
Datatype	Date
Description	Indicates First Due Date.
Attributes	Attribute: minOccurs, Description: 0

TOP

NXTDUEDT

Attribute	Description
Name	NXTDUEDT
Datatype	Date
Description	Indicates Next Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NXTEXEDT

Attribute	Description
Name	NXTEXEDT
Datatype	Date
Description	Indicates Next Execution Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONDELEM

Attribute	Description
Name	CONDELEM
Datatype	String
Description	Indicates Condition Elements.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

OPRTR

Attribute	Description
Name	OPRTR
Datatype	String
Description	Indicates Operator.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

CONDVAL

Attribute	Description
Name	CONDVAL
Datatype	Number
Description	Indicates Condition Value.

Attributes	Attribute	Description
	minOccurs	0

TOP

ACCOFCR

Attribute	Description	
Name	ACCOFCR	
Datatype	String	
Description	Indicates Account Officer.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SPLINSTRTYP

Attribute	Description	
Name	SPLINSTRTYP	
Datatype	String	
Description	Indicates Special Instruction Type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

EXPDT

Attribute	Description	
Name	EXPDT	
Datatype	Date	
Description	Indicates Expiry Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPLINSTR

Attribute	Description	
Name	SPLINSTR	
Datatype	String	
Description	Indicates Special Instructions.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Custaccdet

Attribute	Description
Name	Custaccdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkage details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Indicates the customer

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Indicate relations
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicate,include relationship Y:yes N:no
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	Indicates description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Custacdetail

Attribute	Description
Name	Custacdetail
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTTEXT

Attribute	Description
Name	CUSTTEXT
Datatype	
Description	Include customer details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	Indicates sequence number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String

Description	Indicate text description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Sttms-Debit

Attribute	**Description**
Name	Sttms-Debit
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	Indicates the Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACTNO

Attribute	Description
Name	ACTNO
Datatype	String
Description	Indicates the Account Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Sttms-Detail

Attribute	Description
Name	Sttms-Detail
Datatype	
Description	Indicates Customer Details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description

Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REQUEST_REFERENCE_NO

Attribute	**Description**
Name	REQUEST_REFERENCE_NO
Datatype	String
Description	Indicates the Request Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CARDNO

Attribute	**Description**
Name	CARDNO
Datatype	String
Description	Indicates the Card Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 19

TOP

CUST_NO

Attribute	**Description**
Name	CUST_NO
Datatype	String
Description	Indicates the Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CARD_PRODUCT

Attribute	**Description**
Name	CARD_PRODUCT
Datatype	String
Description	Indicates the Product code.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRIMARY_CARD

Attribute	Description	
Name	PRIMARY_CARD	
Datatype	String	
Description	Indicates the Primary Card Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NAME_ON_CARD

Attribute	Description	
Name	NAME_ON_CARD	
Datatype	String	
Description	Indicates the Name on Card.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

OWNER_ID_NO

Attribute	Description	
Name	OWNER_ID_NO	
Datatype	String	
Description	Indicates the Owner ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

CARD_ISSUED_DT

Attribute	Description	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Indicates the Card Issue Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CARD_EXPIRY_DT

Attribute	Description
Name	CARD_EXPIRY_DT
Datatype	Date
Description	Indicates the Card Expiry Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CARD_STATUS

Attribute	Description
Name	CARD_STATUS
Datatype	String
Description	Indicates the Card Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	Indicates the Record Stat.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTH_STAT

Attribute	Description
Name	AUTH_STAT
Datatype	String
Description	Indicates the Auth Stat.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CARD_BIN

Attribute	Description
Name	CARD_BIN

Datatype	String
Description	Indicates the Card Bin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CUST_AC_NO

Attribute	**Description**
Name	CUST_AC_NO
Datatype	String
Description	Indicates the Customer Account Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Extsys-Ws-Master

Attribute	**Description**
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	**Description**
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXTWSRESP

Attribute	**Description**
Name	EXTWSRESP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

Stvws-Cust-Trntax

Attribute	Description
Name	Stvws-Cust-Trntax
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Sttms-Cust-Trn-Tax

Attribute	Description
Name	Sttms-Cust-Trn-Tax
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TAX_SCHEME

Attribute	Description
Name	TAX_SCHEME
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

TXN_TAX_EXEMPTED

Attribute	**Description**
Name	TXN_TAX_EXEMPTED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TXN_TAX_EXEMPTION_PERCENT

Attribute	**Description**
Name	TXN_TAX_EXEMPTION_PERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXN_TAX_EFF_DATE

Attribute	**Description**
Name	TXN_TAX_EFF_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXN_TAX_EXEMPTION_REASON

Attribute	**Description**
Name	TXN_TAX_EXEMPTION_REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Customer-IO
CUSTNO
MAKER
MAKERSTAMP
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Customer-IO

Attribute	Description
Name	Customer-IO
Datatype	
Description	

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.13.3.ST-CloseCustomer-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Customer-Full*
    - *NAME*
    - *ADDRLN1*
    - *ADDRLN3*
    - *ADDRLN2*
    - *ADDRLN4*
    - *SWIFTCD*
    - *FAX*
    - *COUNTRY*
    - *NLTY*
    - *LANG*
    - *EXPCNTRY*
    - *UIDNAME*
    - *UIDVAL*
    - *LOC*
    - *FROZEN*
    - *DEAD*
    - *WHRUNKN*
    - *GRPCD*

CHGGRP
CUSTCLGGRP
TAXGROUP
CCATEG
EXPCAT
CUSTCLASSFN
FXNETTCUST
XREF
MEDIA
SSN
CIFSTAT
CIFSTATSNC
MAILRSREQD
CLSPARTICIPANT
CRMCUST
ISSUCUST
TRSRYCUST
CUSTNO
SNAME
LBRN
CTYPE
FULLNAME
AMLCUSTGRP
AMLREQD
FLGUTLTYPRVDR
UTLTYPRVDRID
CHKDIGITVALREQD
ALGID
CONSTAXCERTRQD
INDTAXCERTRQD
HOACNO
RISKPRFL
DRCAT
FTACCASOF
UDF1
UDF2
UDF3
UDF4
UDF5
UDFLBL1
UDFLBL2
UDFLBL3
UDFLBL4
UDFLBL5

FXCUSTCLRILIM
OVRLIM
FX_CLEAN_RISK
CRRATE
REVDT
LIMCCY
SECCUSTCLRILIM
SECCLRILIM
SECCUSTPSRILIM
SECPSRILIM
CUSTUNADV
RISKCATEG
CLSCCYALLWD
NETTREQD
LIABUNADV
MT920
RELPRICING
FLGJOINT
KYCSTAT
SSTAFF
UPTYPE
KYC_REFNO
JOINT_VENTURE
PRIVATE_CUSTOMER
LC_COLLAT_PCT
ISELCMCUST
ELCMCUSTNO
ALT_CUST_NO
DETERIORATION_DATE
CHQ_TAX_EXEMPT_1
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Custpersonal
- *TITLE*
- *FSTNAME*
- *MIDNAME*
- *LSTNAME*
- *DOB*
- *GUARDIAN*

MINOR
SEX
NATIONID
PPTNO
PPTISSDT
PPTEXPDT
DADD1
DADD2
DADD3
TEL
FAX
EMAIL
PADD1
PADD2
PADD3
DCNTRY
PCNTRY
RESSTATUS
CUSTPREFIX1
CUSTPREFIX2
MOBNUM
SBMTAGEPROOF
CUST_COMM_MODE
LAST_UPD_DT
Custdomestic
- *EDUSTAT*
- *MARITALSTAT*
- *SPNAME*
- *SPEMPSTATUS*
- *DEPCHILD*
- *DEPOTH*
- *ACCOMODATE*
- *CUSTNO*

Custprof
- *EMPSTAT*
- *EMPTENURE*
- *RETIREAGE*
- *PREVDESIG*
- *PREVEMP*
- *CURRDESIG*
- *CURREMP*
- *ADD1*
- *ADD2*
- *ADD3*

TEL
TELEX
FAX
EMAIL
SALARY
OTHER1
RENT
INSURANCE
LOANPMNT
OTHEXP
HOUSEVAL
CRCARD
CNTY
AMTCCY1
CUSTNO
EMPLOYER_DESC
EMP_DESC
Custcorp
CORPNAME
NATIONID
REGADD1
REGADD2
REGADD3
INCORPDT
CAPITAL
NETWORTH
INCORPCNTRY
REGCNTRY
AMTCCY
CORPDESC
CUSTNO
Custcorpdir
DIRNAME
TEL
NADDR1
NADDR2
NADDR3
NADDR4
ADDR1
ADDRS2
ADDRS3
COUNTRY
TAXID
MOBNO

- *EMAIL*
- *Issuerdet*
  - *OVERLIMIT*
  - *CUSTNO*
  - *OVERLMTCCY*
  - *Issuerlmts*
    - *CLTRLTYP*
    - *LMTAMT*
    - *LMTCCY*
    - *ISSID*
- *Custgrp*
  - *GRPNO*
  - *RELATION*
- *Custshhold*
  - *SHHOLDID*
  - *SHHOLDPCT*
  - *SHRHLDRNAME*
- *Clsccyrest*
  - *CCY*
  - *DESC*
- *Bic*
  - *ACC*
  - *BICCD*
- *Linkedac*
  - *VRFD*
  - *LINKEDACCNO*
  - *LINKEDACCIBAN*
  - *LINKEDACCBIC*
- *JointVenture*
  - *PARTYID*
  - *PARTYRATIO*
  - *PARTYNAME*
- *Custdoc-Chklist*
  - *DOCUMENT_TYPE*
  - *CHECKED*
- *Doctype-Remarks*
  - *REMARK1*
  - *REMARK2*
  - *REMARK3*
  - *REMARK4*
  - *REMARK5*
  - *REMARK6*
  - *REMARK7*
  - *REMARK8*

- *REMARK9*
- *REMARK10*

Custmis

- *MISGRP*
- *CUST*
- *BRNCD*
- *Custchnglog*
  - *MISCLS*
  - *TXNDT*
  - *OLDMISCD*
  - *NWMISCD*
- *Baltrnsfrlog*
  - *BRN*
  - *PRDCD*
  - *FINYR*
  - *TXNDT*
  - *GLCODE*
  - *MISCLS*
  - *OLDMISCD*
  - *NWMISCD*
  - *TRNIND*
  - *CCY*
  - *AMT*
  - *XRATE*
- *Dfltcd*
  - *MISCLS*
  - *MISCD*
- *Dfltcda*
  - *MISCLS*
  - *MISCD*
- *Custloghead*

Jointcustomer

- *CUSTNO*
- *Custjoint*
  - *CUSTPREFIX*
  - *FRSTNAME*
  - *MIDNAME*
  - *LASTNAME*
  - *DOB*
  - *SEX*
  - *PPNO*
  - *PPTISSDT*
  - *PPTEXPDT*
  - *ADD1*

ADD2

ADD3

TEL

EMAIL

SSN

DECEASED

RESISTAT

Cust-Acc-Det

CUSTNO

Diary-Mst

INSTRNO

UNTTYP

UNTVAL

BRN

INSTR

INSTRTYPE

EXEDAYS

EXEMONTHS

EXEYEARS

MNTHENDFLG

HLDRULE

FRSTDUEDT

NXTDUEDT

NXTEXEDT

CONDELEM

OPRTR

CONDVAL

ACCOFCR

SPLINSTRTYP

EXPDT

SPLINSTR

Custaccdet

CUSTNO

BRNCD

Relationship-Linkage

CUSTOMER

RELATIONSHIP

INHERIT

DESCP

Custacdetail

CUSTNO

CUSTTEXT

SEQNO

CUSTNO

TDESC
UDFDETAILS
FLDNAM
FLDVAL
Sttms-Debit
BRANCH_CODE
CUST_NO
ACTNO
Sttms-Detail
BRANCH_CODE
REQUEST_REFERENCE_NO
CARDNO
CUST_NO
CARD_PRODUCT
PRIMARY_CARD
NAME_ON_CARD
OWNER_ID_NO
CARD_ISSUED_DT
CARD_EXPIRY_DT
CARD_STATUS
RECORD_STAT
AUTH_STAT
CARD_BIN
CUST_AC_NO
Extsys-Ws-Master
Extsys-Ws-Details
EXTWSRESP
USERREMARKS
Stvws-Cust-Trntax
CUSTOMER_NO
Sttms-Cust-Trn-Tax
TAX_SCHEME
TXN_TAX_EXEMPTED
TXN_TAX_EXEMPTION_PERCENT
TXN_TAX_EFF_DATE
TXN_TAX_EXEMPTION_REASON
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Customer-Full

Attribute	Description

Name	Customer-Full
Datatype	
Description	

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

ADDRLN1

Attribute	Description	
Name	ADDRLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN3

Attribute	Description	
Name	ADDRLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN2

Attribute	Description	
Name	ADDRLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN4

Attribute	Description

Name	ADDRLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SWIFTCD

Attribute	**Description**
Name	SWIFTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FAX

Attribute	**Description**
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRY

Attribute	**Description**
Name	COUNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NLTY

Attribute	**Description**
Name	NLTY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXPCNTRY

Attribute	Description
Name	EXPCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

UIDNAME

Attribute	Description
Name	UIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

UIDVAL

Attribute	Description
Name	UIDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

LOC

Attribute	Description	
Name	LOC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

FROZEN

Attribute	Description	
Name	FROZEN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

DEAD

Attribute	Description	
Name	DEAD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

WHRUNKN

Attribute	Description	
Name	WHRUNKN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CHGGRP

Attribute	Description
Name	CHGGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CUSTCLGGRP

Attribute	Description
Name	CUSTCLGGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAXGROUP

Attribute	Description
Name	TAXGROUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CCATEG

Attribute	Description
Name	CCATEG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

CUSTCLASSFN

Attribute	Description
Name	CUSTCLASSFN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

FXNETTCUST

Attribute	Description
Name	FXNETTCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

XREF

Attribute	Description
Name	XREF

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SSN

Attribute	Description
Name	SSN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CIFSTAT

Attribute	Description
Name	CIFSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CIFSTATSNC

Attribute	Description
Name	CIFSTATSNC
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MAILRSREQD

Attribute	Description
Name	MAILRSREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CLSPARTICIPANT

Attribute	Description
Name	CLSPARTICIPANT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CRMCUST

Attribute	Description
Name	CRMCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ISSUCUST

Attribute	Description
Name	ISSUCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TRSRYCUST

Attribute	Description
Name	TRSRYCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

SNAME

Attribute	Description
Name	SNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 20

TOP

LBRN

Attribute	Description
Name	LBRN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CTYPE

Attribute	Description
Name	CTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: I,C,B

TOP

FULLNAME

Attribute	Description
Name	FULLNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

AMLCUSTGRP

Attribute	Description
Name	AMLCUSTGRP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

AMLREQD

Attribute	Description
Name	AMLREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

FLGUTLTYPRVDR

Attribute	Description
Name	FLGUTLTYPRVDR

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UTLTYPRVDRID

Attribute	Description
Name	UTLTYPRVDRID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKDIGITVALREQD

Attribute	Description
Name	CHKDIGITVALREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALGID

Attribute	Description
Name	ALGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CONSTAXCERTRQD

Attribute	Description
Name	CONSTAXCERTRQD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INDTAXCERTRQD

Attribute	Description	
Name	INDTAXCERTRQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

HOACNO

Attribute	Description	
Name	HOACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RISKPRFL

Attribute	Description	
Name	RISKPRFL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

DRCAT

Attribute	Description	
Name	DRCAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FTACCASOF

Attribute	Description	
Name	FTACCASOF	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,M,D

TOP

UDF1

Attribute	Description	
Name	UDF1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

TOP

UDF2

Attribute	Description	
Name	UDF2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

TOP

UDF3

Attribute	Description	
Name	UDF3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

UDF4

Attribute	Description
Name	UDF4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

UDF5

Attribute	Description
Name	UDF5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL1

Attribute	Description
Name	UDFLBL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL2

Attribute	Description
Name	UDFLBL2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL3

Attribute	Description
Name	UDFLBL3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDFLBL4

Attribute	Description
Name	UDFLBL4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDFLBL5

Attribute	Description
Name	UDFLBL5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

FXCUSTCLRILIM

Attribute	Description
Name	FXCUSTCLRILIM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

OVRLIM

Attribute	Description
Name	OVRLIM
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

FX_CLEAN_RISK

Attribute	Description
Name	FX_CLEAN_RISK
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CRRATE

Attribute	Description
Name	CRRATE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

REVDT

Attribute	Description
Name	REVDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIMCCY

Attribute	Description
Name	LIMCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

SECCUSTCLRILIM

Attribute	Description
Name	SECCUSTCLRILIM

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCLRILIM

Attribute	Description
Name	SECCLRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCUSTPSRILIM

Attribute	Description
Name	SECCUSTPSRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECPSRILIM

Attribute	Description
Name	SECPSRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTUNADV

Attribute	Description
Name	CUSTUNADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RISKCATEG

Attribute	Description
Name	RISKCATEG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CLSCCYALLWD

Attribute	**Description**
Name	CLSCCYALLWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

NETTREQD

Attribute	**Description**
Name	NETTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIABUNADV

Attribute	**Description**
Name	LIABUNADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MT920

Attribute	**Description**
Name	MT920
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RELPRICING

Attribute	**Description**
Name	RELPRICING
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FLGJOINT

Attribute	**Description**
Name	FLGJOINT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

KYCSTAT

Attribute	**Description**
Name	KYCSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,N,F

TOP

SSTAFF

Attribute	**Description**
Name	SSTAFF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UPTYPE

Attribute	**Description**
Name	UPTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

KYC_REFNO

Attribute	**Description**
Name	KYC_REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

JOINT_VENTURE

Attribute	**Description**
Name	JOINT_VENTURE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIVATE_CUSTOMER

Attribute	**Description**
Name	PRIVATE_CUSTOMER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LC_COLLAT_PCT

Attribute	Description
Name	LC_COLLAT_PCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISELCMCUST

Attribute	Description
Name	ISELCMCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ELCMCUSTNO

Attribute	Description
Name	ELCMCUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ALT_CUST_NO

Attribute	Description
Name	ALT_CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DETERIORATION_DATE

Attribute	Description
Name	DETERIORATION_DATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHQ_TAX_EXEMPT_1

Attribute	Description
Name	CHQ_TAX_EXEMPT_1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Custpersonal

Attribute	Description
Name	Custpersonal
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TITLE

Attribute	Description
Name	TITLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FSTNAME

Attribute	Description
Name	FSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MIDNAME

Attribute	Description
Name	MIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LSTNAME

Attribute	Description
Name	LSTNAME
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GUARDIAN

Attribute	Description
Name	GUARDIAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MINOR

Attribute	Description
Name	MINOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SEX

Attribute	Description
Name	SEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,F

TOP

NATIONID

Attribute	Description
Name	NATIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

PPTNO

Attribute	Description
Name	PPTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

PPTISSDT

Attribute	Description
Name	PPTISSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PPTEXPDT

Attribute	Description
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DADD1

Attribute	Description
Name	DADD1
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DADD2

Attribute	Description
Name	DADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DADD3

Attribute	Description
Name	DADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FAX

Attribute	Description
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

PADD1

Attribute	Description
Name	PADD1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

PADD2

Attribute	Description
Name	PADD2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

PADD3

Attribute	Description
Name	PADD3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

DCNTRY

Attribute	Description
Name	DCNTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

PCNTRY

Attribute	Description
Name	PCNTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

RESSTATUS

Attribute	Description
Name	RESSTATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: R,N

TOP

CUSTPREFIX1

Attribute	Description
Name	CUSTPREFIX1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

CUSTPREFIX2

Attribute	Description
Name	CUSTPREFIX2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

MOBNUM

Attribute	Description
Name	MOBNUM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SBMTAGEPROOF

Attribute	Description
Name	SBMTAGEPROOF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,P,V

TOP

CUST_COMM_MODE

Attribute	Description
Name	CUST_COMM_MODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,E

TOP

LAST_UPD_DT

Attribute	Description
Name	LAST_UPD_DT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Custdomestic

Attribute	Description
Name	Custdomestic
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

EDUSTAT

Attribute	Description
Name	EDUSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,U,G,P

TOP

MARITALSTAT

Attribute	Description
Name	MARITALSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: S,M,D,R,P,E,T

TOP

SPNAME

Attribute	Description
Name	SPNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SPEMPSTATUS

Attribute	Description
Name	SPEMPSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,T,S,U,R,P,N,O

TOP

DEPCHILD

Attribute	Description
Name	DEPCHILD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEPOTH

Attribute	Description
Name	DEPOTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOMODATE

Attribute	Description
Name	ACCOMODATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,O

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	9

TOP

Custprof

Attribute	Description	
Name	Custprof	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EMPSTAT

Attribute	Description	
Name	EMPSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

EMPTENURE

Attribute	Description	
Name	EMPTENURE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RETIREAGE

Attribute	Description	
Name	RETIREAGE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PREVDESIG

Attribute	Description
Name	PREVDESIG
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PREVEMP

Attribute	Description
Name	PREVEMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURRDESIG

Attribute	Description
Name	CURRDESIG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURREMP

Attribute	Description
Name	CURREMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADD2

Attribute	**Description**
Name	ADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADD3

Attribute	**Description**
Name	ADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TEL

Attribute	**Description**
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TELEX

Attribute	**Description**
Name	TELEX
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FAX

Attribute	Description
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

SALARY

Attribute	Description
Name	SALARY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHER1

Attribute	Description
Name	OTHER1
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RENT

Attribute	Description
Name	RENT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

INSURANCE

Attribute	Description
Name	INSURANCE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LOANPMNT

Attribute	Description
Name	LOANPMNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

OTHEXP

Attribute	Description
Name	OTHEXP
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

HOUSEVAL

Attribute	Description
Name	HOUSEVAL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CRCARD

Attribute	Description
Name	CRCARD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMTCCY1

Attribute	Description
Name	AMTCCY1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

EMPLOYER_DESC

Attribute	Description
Name	EMPLOYER_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

EMP_DESC

Attribute	Description
Name	EMP_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

Custcorp

Attribute	Description
Name	Custcorp
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CORPNAME

Attribute	Description
Name	CORPNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

NATIONID

Attribute	Description
Name	NATIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REGADD1

Attribute	Description
Name	REGADD1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REGADD2

Attribute	**Description**
Name	REGADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REGADD3

Attribute	**Description**
Name	REGADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INCORPDT

Attribute	**Description**
Name	INCORPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CAPITAL

Attribute	**Description**
Name	CAPITAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETWORTH

Attribute	Description
Name	NETWORTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INCORPCNTRY

Attribute	Description
Name	INCORPCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REGCNTRY

Attribute	Description
Name	REGCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CORPDESC

Attribute	Description
Name	CORPDESC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Custcorpdir

Attribute	Description
Name	Custcorpdir
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DIRNAME

Attribute	Description
Name	DIRNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR1

Attribute	Description
Name	NADDR1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR2

Attribute	Description
Name	NADDR2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR3

Attribute	Description
Name	NADDR3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR4

Attribute	Description
Name	NADDR4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRY

Attribute	Description
Name	COUNTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

TAXID

Attribute	Description
Name	TAXID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MOBNO

Attribute	**Description**
Name	MOBNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EMAIL

Attribute	**Description**
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Issuerdet

Attribute	**Description**
Name	Issuerdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OVERLIMIT

Attribute	**Description**
Name	OVERLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OVERLMTCCY

Attribute	Description
Name	OVERLMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Issuerlmts

Attribute	Description
Name	Issuerlmts
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CLTRLTYP

Attribute	Description
Name	CLTRLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 70

TOP

LMTAMT

Attribute	Description
Name	LMTAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LMTCCY

Attribute	Description
Name	LMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ISSID

Attribute	Description
Name	ISSID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Custgrp

Attribute	Description
Name	Custgrp
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

GRPNO

Attribute	Description
Name	GRPNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RELATION

Attribute	Description
Name	RELATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Custshhold

Attribute	Description
Name	Custshhold
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SHHOLDID

Attribute	Description
Name	SHHOLDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SHHOLDPCT

Attribute	Description
Name	SHHOLDPCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHRHLDRNAME

Attribute	Description
Name	SHRHLDRNAME
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Clsccyrest

Attribute	Description
Name	Clsccyrest
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Bic

Attribute	Description
Name	Bic
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BICCD

Attribute	Description
Name	BICCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

Linkedac

Attribute	Description
Name	Linkedac
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

VRFD

Attribute	Description
Name	VRFD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LINKEDACCNO

Attribute	Description

Name	LINKEDACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

LINKEDACCIBAN

Attribute	**Description**
Name	LINKEDACCIBAN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINKEDACCBIC

Attribute	**Description**
Name	LINKEDACCBIC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

JointVenture

Attribute	**Description**
Name	JointVenture
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTYID

Attribute	**Description**
Name	PARTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	9

TOP

PARTYRATIO

Attribute	Description
Name	PARTYRATIO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 1

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

Custdoc-Chklist

Attribute	Description
Name	Custdoc-Chklist
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

CHECKED

Attribute	Description

Name	CHECKED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Doctype-Remarks

Attribute	**Description**
Name	Doctype-Remarks
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARK1

Attribute	**Description**
Name	REMARK1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK2

Attribute	**Description**
Name	REMARK2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK3

Attribute	**Description**
Name	REMARK3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	225

TOP

REMARK4

Attribute	Description
Name	REMARK4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK5

Attribute	Description
Name	REMARK5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK6

Attribute	Description
Name	REMARK6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK7

Attribute	Description
Name	REMARK7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK8

Attribute	Description
Name	REMARK8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK9

Attribute	Description
Name	REMARK9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK10

Attribute	Description
Name	REMARK10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

Custmis

Attribute	Description
Name	Custmis
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP

Datatype	String
Description	Indicates Management Information System Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CUST

Attribute	Description
Name	CUST
Datatype	String
Description	Indicates the Customer.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Custchnglog

Attribute	Description
Name	Custchnglog
Datatype	
Description	Indicates the Customer Change Log.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	Indicates the Old MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	Indicates the New MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Baltrnsfrlog

Attribute	Description
Name	Baltrnsfrlog
Datatype	
Description	Indicates the Balance Transfer Log.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRN

Attribute	Description

Name	BRN
Datatype	String
Description	Indicates the Branch Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDCD

Attribute	**Description**
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	**Description**
Name	FINYR
Datatype	String
Description	Indicates the Financial Year.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNDT

Attribute	**Description**
Name	TXNDT
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

GLCODE

Attribute	**Description**
Name	GLCODE
Datatype	String
Description	Indicates the GL Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 9

TOP

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	Indicates the Old MIS Code.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	Indicates the New MIS Code.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

TRNIND

Attribute	Description
Name	TRNIND
Datatype	String
Description	Indicates Transfer Identification Number.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Dfltcd

Attribute	Description
Name	Dfltcd
Datatype	
Description	Indicates the Customer MIS Classes.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MISCD

Attribute	Description	
Name	MISCD	
Datatype	String	
Description	Indicates the MIS Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Dfltcda

Attribute	Description	
Name	Dfltcda	
Datatype		
Description	Indicates the Composite MIS Classes.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MISCLS

Attribute	Description	
Name	MISCLS	
Datatype	String	
Description	Indicates the MIS Class.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MISCD

Attribute	Description	
Name	MISCD	
Datatype	String	
Description	Indicates the MIS Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Custloghead

Attribute	Description
Name	Custloghead
Datatype	
Description	Indicates the Customer Log Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Jointcustomer

Attribute	Description
Name	Jointcustomer
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Custjoint

Attribute	Description
Name	Custjoint
Datatype	
Description	Indicates Customer Joint.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTPREFIX

Attribute	Description
Name	CUSTPREFIX
Datatype	String
Description	Indicates the Customer Prefix.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FRSTNAME

Attribute	Description
Name	FRSTNAME
Datatype	String
Description	Indicates the First Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MIDNAME

Attribute	Description
Name	MIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LASTNAME

Attribute	Description
Name	LASTNAME
Datatype	String
Description	Indicates the Last Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SEX

Attribute	Description
Name	SEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,F

TOP

PPNO

Attribute	Description
Name	PPNO
Datatype	String
Description	Indicates Passport Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PPTISSDT

Attribute	Description
Name	PPTISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PPTEXPDT

Attribute	Description
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADD2

Attribute	Description	
Name	ADD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADD3

Attribute	Description	
Name	ADD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

TEL

Attribute	Description	
Name	TEL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EMAIL

Attribute	Description	
Name	EMAIL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	255

TOP

SSN

Attribute	Description	
Name	SSN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	11

TOP

DECEASED

Attribute	Description	
Name	DECEASED	
Datatype	String	
Description	Indicates whether Deceased or not. The value should be either D or N.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,N

TOP

RESISTAT

Attribute	Description	
Name	RESISTAT	
Datatype	String	
Description	Indicates the Resistant Status. The value could be either R or N.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	R,N

TOP

Cust-Acc-Det

Attribute	Description	
Name	Cust-Acc-Det	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Diary-Mst

Attribute	Description
Name	Diary-Mst
Datatype	
Description	Indicates Diary Master.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

UNTTYP

Attribute	Description
Name	UNTTYP
Datatype	String
Description	Indicates Unit Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

UNTVAL

Attribute	Description
Name	UNTVAL
Datatype	String

Description	Indicates Unit Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BRN

Attribute	**Description**
Name	BRN
Datatype	String
Description	Indicates the Branch Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INSTR

Attribute	**Description**
Name	INSTR
Datatype	String
Description	Indicates Instructions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

INSTRTYPE

Attribute	**Description**
Name	INSTRTYPE
Datatype	String
Description	Indicates Instruction Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

EXEDAYS

Attribute	**Description**
Name	EXEDAYS
Datatype	Number
Description	Indicates Execution Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXEMONTHS

Attribute	Description
Name	EXEMONTHS
Datatype	Number
Description	Indicates Execution Months
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXEYEARS

Attribute	Description
Name	EXEYEARS
Datatype	Number
Description	Indicates Execution Years
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MNTHENDFLG

Attribute	Description
Name	MNTHENDFLG
Datatype	String
Description	Indicates Month End Flag. Flag Can be either Y or N.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

HLDRULE

Attribute	Description
Name	HLDRULE
Datatype	String
Description	Indicates Holiday Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FRSTDUEDT

Attribute	Description
Name	FRSTDUEDT
Datatype	Date
Description	Indicates First Due Date.

Attributes	Attribute	Description
	minOccurs	0

TOP

NXTDUEDT

Attribute	Description
Name	NXTDUEDT
Datatype	Date
Description	Indicates Next Due Date
Attributes	Attribute: minOccurs — Description: 0

TOP

NXTEXEDT

Attribute	Description
Name	NXTEXEDT
Datatype	Date
Description	Indicates Next Execution Date.
Attributes	Attribute: minOccurs — Description: 0

TOP

CONDELEM

Attribute	Description
Name	CONDELEM
Datatype	String
Description	Indicates Condition Elements.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

OPRTR

Attribute	Description
Name	OPRTR
Datatype	String
Description	Indicates Operator.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2

TOP

CONDVAL

Attribute	Description
Name	CONDVAL

Datatype	Number
Description	Indicates Condition Value.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOFCR

Attribute	Description
Name	ACCOFCR
Datatype	String
Description	Indicates Account Officer.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPLINSTRTYP

Attribute	Description
Name	SPLINSTRTYP
Datatype	String
Description	Indicates Special Instruction Type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	Indicates Expiry Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPLINSTR

Attribute	Description
Name	SPLINSTR
Datatype	String
Description	Indicates Special Instructions.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Custaccdet

Attribute	Description
Name	Custaccdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkage details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String

Description	Indicates the customer
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RELATIONSHIP

Attribute	**Description**
Name	RELATIONSHIP
Datatype	String
Description	Indicate relations
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

INHERIT

Attribute	**Description**
Name	INHERIT
Datatype	String
Description	Indicate,include relationship Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DESCP

Attribute	**Description**
Name	DESCP
Datatype	String
Description	Indicates description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Custacdetail

Attribute	**Description**
Name	Custacdetail
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTTEXT

Attribute	Description	
Name	CUSTTEXT	
Datatype		
Description	Include customer details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SEQNO

Attribute	Description	
Name	SEQNO	
Datatype	Number	
Description	Indicates sequence number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TDESC

Attribute	Description

ORACLE

Name	TDESC
Datatype	String
Description	Indicate text description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

Sttms-Debit

Attribute	**Description**
Name	Sttms-Debit
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	Indicates the Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACTNO

Attribute	Description
Name	ACTNO
Datatype	String
Description	Indicates the Account Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Sttms-Detail

Attribute	Description
Name	Sttms-Detail
Datatype	
Description	Indicates Customer Details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description

ORACLE

Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REQUEST_REFERENCE_NO

Attribute	Description
Name	REQUEST_REFERENCE_NO
Datatype	String
Description	Indicates the Request Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CARDNO

Attribute	Description
Name	CARDNO
Datatype	String
Description	Indicates the Card Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 19

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	Indicates the Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CARD_PRODUCT

Attribute	Description
Name	CARD_PRODUCT
Datatype	String
Description	Indicates the Product code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRIMARY_CARD

Attribute	**Description**	
Name	PRIMARY_CARD	
Datatype	String	
Description	Indicates the Primary Card Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NAME_ON_CARD

Attribute	**Description**	
Name	NAME_ON_CARD	
Datatype	String	
Description	Indicates the Name on Card.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

OWNER_ID_NO

Attribute	**Description**	
Name	OWNER_ID_NO	
Datatype	String	
Description	Indicates the Owner ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

CARD_ISSUED_DT

Attribute	**Description**	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Indicates the Card Issue Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CARD_EXPIRY_DT

Attribute	Description
Name	CARD_EXPIRY_DT
Datatype	Date
Description	Indicates the Card Expiry Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_STATUS

Attribute	Description
Name	CARD_STATUS
Datatype	String
Description	Indicates the Card Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	Indicates the Record Stat.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTH_STAT

Attribute	Description
Name	AUTH_STAT
Datatype	String
Description	Indicates the Auth Stat.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CARD_BIN

Attribute	Description
Name	CARD_BIN

Datatype	String
Description	Indicates the Card Bin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CUST_AC_NO

Attribute	**Description**
Name	CUST_AC_NO
Datatype	String
Description	Indicates the Customer Account Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Extsys-Ws-Master

Attribute	**Description**
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	**Description**
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXTWSRESP

Attribute	**Description**
Name	EXTWSRESP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

Stvws-Cust-Trntax

Attribute	Description
Name	Stvws-Cust-Trntax
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Sttms-Cust-Trn-Tax

Attribute	Description
Name	Sttms-Cust-Trn-Tax
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TAX_SCHEME

Attribute	Description
Name	TAX_SCHEME
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

TXN_TAX_EXEMPTED

Attribute	**Description**
Name	TXN_TAX_EXEMPTED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TXN_TAX_EXEMPTION_PERCENT

Attribute	**Description**
Name	TXN_TAX_EXEMPTION_PERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXN_TAX_EFF_DATE

Attribute	**Description**
Name	TXN_TAX_EFF_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXN_TAX_EXEMPTION_REASON

Attribute	**Description**
Name	TXN_TAX_EXEMPTION_REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Customer-PK*
      - *CUSTNO*
    - *Customer-IO*
      - *CUSTNO*
      - *MAKER*
      - *MAKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Customer-PK

Attribute	Description
Name	Customer-PK
Datatype	
Description	

TOP

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Customer-IO

Attribute	Description
Name	Customer-IO
Datatype	
Description	

TOP

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.14.CloseTDAmountBlock

CloseTDAmountBlock

2.14.1.ST-CloseTDAmountBlock-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-Full*
    - *ACC*
    - *AMTBLKNO*
    - *AMT*
    - *EXPDATE*
    - *REM*
    - *ABLKTYPE*
    - *REFERENCE_NO*
    - *HPCODE*
    - *EFFDATE*
    - *HOLDDESC*
    - *BRANCH*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Amount-Blocks-Full

Attribute	Description
Name	Amount-Blocks-Full
Datatype	
Description	

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTBLKNO

Attribute	Description	
Name	AMTBLKNO	
Datatype	String	
Description	Indicates the Amount Block Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

EXPDATE

Attribute	Description	
Name	EXPDATE	
Datatype	Date	
Description	Indicates the Expiry Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ABLKTYPE

Attribute	Description
Name	ABLKTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,S,P,E,A,C,B,D

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 40

TOP

HPCODE

Attribute	Description
Name	HPCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

HOLDDESC

Attribute	Description
Name	HOLDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	Restrictions: maxLength — Description: 105 Restrictions: minLength — Description: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255 Restrictions: minLength — Description: 0

TOP

2.14.2.ST-CloseTDAmountBlock-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-IO*
    - *AMTBLKNO*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration — Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0 Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0 Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	Restrictions: maxLength — Description: 12 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	

Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Amount-Blocks-IO

Attribute	Description
Name	Amount-Blocks-IO
Datatype	
Description	

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description

<table>
<tr><td>Name</td><td>MODNO</td></tr>
<tr><td>Datatype</td><td>Number</td></tr>
<tr><td>Description</td><td>Indicates Modification number i.e. the number of times the record has been modified.</td></tr>
<tr><td>Attributes</td><td><table>
<tr><th>Attribute</th><th>Description</th></tr>
<tr><td>minOccurs</td><td>0</td></tr>
</table></td></tr>
<tr><td>Restrictions</td><td><table>
<tr><th>Restrictions</th><th>Description</th></tr>
<tr><td>totalDigits</td><td>22</td></tr>
</table></td></tr>
</table>

TOP

2.14.3.ST-CloseTDAmountBlock-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-Full*
    - *ACC*
    - *AMTBLKNO*
    - *AMT*
    - *EXPDATE*
    - *REM*
    - *ABLKTYPE*
    - *REFERENCE_NO*
    - *HPCODE*
    - *EFFDATE*
    - *HOLDDESC*
    - *BRANCH*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String

Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Amount-Blocks-Full

Attribute	Description
Name	Amount-Blocks-Full
Datatype	
Description	

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTBLKNO

Attribute	Description	
Name	AMTBLKNO	
Datatype	String	
Description	Indicates the Amount Block Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ABLKTYPE

Attribute	Description
Name	ABLKTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,S,P,E,A,C,B,D

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 40

TOP

HPCODE

Attribute	Description
Name	HPCODE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HOLDDESC

Attribute	Description
Name	HOLDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description

Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Amount-Blocks-PK*
      - *AMTBLKNO*
    - *Amount-Blocks-IO*
      - *AMTBLKNO*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Amount-Blocks-PK

Attribute	Description
Name	Amount-Blocks-PK
Datatype	
Description	

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Amount-Blocks-IO

Attribute	Description
Name	Amount-Blocks-IO
Datatype	
Description	

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.15.CreateCustomer

Input of Customer

2.15.1.ST-CreateCustomer-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Customer-Full*
    - *NAME*
    - *ADDRLN1*
    - *ADDRLN3*
    - *ADDRLN2*
    - *ADDRLN4*
    - *SWIFTCD*
    - *FAX*
    - *COUNTRY*
    - *NLTY*
    - *LANG*
    - *EXPCNTRY*
    - *UIDNAME*
    - *UIDVAL*
    - *LOC*
    - *FROZEN*

DEAD
WHRUNKN
GRPCD
CHGGRP
CUSTCLGGRP
TAXGROUP
CCATEG
EXPCAT
CUSTCLASSFN
FXNETTCUST
XREF
MEDIA
SSN
CIFSTAT
CIFSTATSNC
MAILRSREQD
CLSPARTICIPANT
CRMCUST
ISSUCUST
TRSRYCUST
CUSTNO
SNAME
LBRN
CTYPE
FULLNAME
AMLCUSTGRP
AMLREQD
FLGUTLTYPRVDR
UTLTYPRVDRID
CHKDIGITVALREQD
ALGID
CONSTAXCERTRQD
INDTAXCERTRQD
HOACNO
RISKPRFL
DRCAT
FTACCASOF
UDF1
UDF2
UDF3
UDF4
UDF5
UDFLBL1
UDFLBL2

UDFLBL3
UDFLBL4
UDFLBL5
FXCUSTCLRILIM
OVRLIM
FX_CLEAN_RISK
CRRATE
REVDT
LIMCCY
SECCUSTCLRILIM
SECCLRILIM
SECCUSTPSRILIM
SECPSRILIM
CUSTUNADV
RISKCATEG
CLSCCYALLWD
NETTREQD
LIABUNADV
MT920
RELPRICING
FLGJOINT
KYCSTAT
SSTAFF
UPTYPE
KYC_REFNO
JOINT_VENTURE
PRIVATE_CUSTOMER
LC_COLLAT_PCT
ISELCMCUST
ELCMCUSTNO
ALT_CUST_NO
DETERIORATION_DATE
CHQ_TAX_EXEMPT_1
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Custpersonal
- *TITLE*
- *FSTNAME*
- *MIDNAME*

LSTNAME
DOB
GUARDIAN
MINOR
SEX
NATIONID
PPTNO
PPTISSDT
PPTEXPDT
DADD1
DADD2
DADD3
TEL
FAX
EMAIL
PADD1
PADD2
PADD3
DCNTRY
PCNTRY
RESSTATUS
CUSTPREFIX1
CUSTPREFIX2
MOBNUM
SBMTAGEPROOF
CUST_COMM_MODE
LAST_UPD_DT
Custdomestic
- *EDUSTAT*
- *MARITALSTAT*
- *SPNAME*
- *SPEMPSTATUS*
- *DEPCHILD*
- *DEPOTH*
- *ACCOMODATE*
- *CUSTNO*

Custprof
- *EMPSTAT*
- *EMPTENURE*
- *RETIREAGE*
- *PREVDESIG*
- *PREVEMP*
- *CURRDESIG*
- *CURREMP*

ADD1
ADD2
ADD3
TEL
TELEX
FAX
EMAIL
SALARY
OTHER1
RENT
INSURANCE
LOANPMNT
OTHEXP
HOUSEVAL
CRCARD
CNTY
AMTCCY1
CUSTNO
EMPLOYER_DESC
EMP_DESC

Custcorp

CORPNAME
NATIONID
REGADD1
REGADD2
REGADD3
INCORPDT
CAPITAL
NETWORTH
INCORPCNTRY
REGCNTRY
AMTCCY
CORPDESC
CUSTNO
Custcorpdir

DIRNAME
TEL
NADDR1
NADDR2
NADDR3
NADDR4
ADDR1
ADDRS2
ADDRS3

COUNTRY
TAXID
MOBNO
EMAIL
Issuerdet
OVERLIMIT
CUSTNO
OVERLMTCCY
Issuerlmts
CLTRLTYP
LMTAMT
LMTCCY
ISSID
Custgrp
GRPNO
RELATION
Custshhold
SHHOLDID
SHHOLDPCT
SHRHLDRNAME
Clsccyrest
CCY
DESC
Bic
ACC
BICCD
Linkedac
VRFD
LINKEDACCNO
LINKEDACCIBAN
LINKEDACCBIC
JointVenture
PARTYID
PARTYRATIO
PARTYNAME
Custdoc-Chklist
DOCUMENT_TYPE
CHECKED
Doctype-Remarks
REMARK1
REMARK2
REMARK3
REMARK4
REMARK5

- *REMARK6*
- *REMARK7*
- *REMARK8*
- *REMARK9*
- *REMARK10*

Custmis

- *MISGRP*
- *CUST*
- *BRNCD*
- *Custchnglog*
  - *MISCLS*
  - *TXNDT*
  - *OLDMISCD*
  - *NWMISCD*
- *Baltrnsfrlog*
  - *BRN*
  - *PRDCD*
  - *FINYR*
  - *TXNDT*
  - *GLCODE*
  - *MISCLS*
  - *OLDMISCD*
  - *NWMISCD*
  - *TRNIND*
  - *CCY*
  - *AMT*
  - *XRATE*
- *Dfltcd*
  - *MISCLS*
  - *MISCD*
- *Dfltcda*
  - *MISCLS*
  - *MISCD*
- *Custloghead*

Jointcustomer

- *CUSTNO*
- *Custjoint*
  - *CUSTPREFIX*
  - *FRSTNAME*
  - *MIDNAME*
  - *LASTNAME*
  - *DOB*
  - *SEX*
  - *PPNO*

PPTISSDT
PPTEXPDT
ADD1
ADD2
ADD3
TEL
EMAIL
SSN
DECEASED
RESISTAT
Cust-Acc-Det
CUSTNO
Diary-Mst
INSTRNO
UNTTYP
UNTVAL
BRN
INSTR
INSTRTYPE
EXEDAYS
EXEMONTHS
EXEYEARS
MNTHENDFLG
HLDRULE
FRSTDUEDT
NXTDUEDT
NXTEXEDT
CONDELEM
OPRTR
CONDVAL
ACCOFCR
SPLINSTRTYP
EXPDT
SPLINSTR
Custaccdet
CUSTNO
BRNCD
Relationship-Linkage
CUSTOMER
RELATIONSHIP
INHERIT
DESCP
Custacdetail
CUSTNO

CUSTTEXT

SEQNO

CUSTNO

TDESC

UDFDETAILS

FLDNAM

FLDVAL

Sttms-Debit

BRANCH_CODE

CUST_NO

ACTNO

Sttms-Detail

BRANCH_CODE

REQUEST_REFERENCE_NO

CARDNO

CUST_NO

CARD_PRODUCT

PRIMARY_CARD

NAME_ON_CARD

OWNER_ID_NO

CARD_ISSUED_DT

CARD_EXPIRY_DT

CARD_STATUS

RECORD_STAT

AUTH_STAT

CARD_BIN

CUST_AC_NO

Extsys-Ws-Master

Extsys-Ws-Details

EXTWSRESP

USERREMARKS

Stvws-Cust-Trntax

CUSTOMER_NO

Sttms-Cust-Trn-Tax

TAX_SCHEME

TXN_TAX_EXEMPTED

TXN_TAX_EXEMPTION_PERCENT

TXN_TAX_EFF_DATE

TXN_TAX_EXEMPTION_REASON

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Customer-Full

Attribute	Description
Name	Customer-Full
Datatype	
Description	

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

ADDRLN1

Attribute	Description	
Name	ADDRLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN3

Attribute	Description	
Name	ADDRLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN2

Attribute	Description	
Name	ADDRLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN4

Attribute	Description
Name	ADDRLN4
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SWIFTCD

Attribute	Description
Name	SWIFTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FAX

Attribute	Description
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRY

Attribute	Description
Name	COUNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NLTY

Attribute	Description
Name	NLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LANG

Attribute	**Description**
Name	LANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXPCNTRY

Attribute	**Description**
Name	EXPCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

UIDNAME

Attribute	**Description**
Name	UIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

UIDVAL

Attribute	**Description**
Name	UIDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOC

Attribute	Description
Name	LOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FROZEN

Attribute	Description
Name	FROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEAD

Attribute	Description
Name	DEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

WHRUNKN

Attribute	Description
Name	WHRUNKN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

CHGGRP

Attribute	Description
Name	CHGGRP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

CUSTCLGGRP

Attribute	Description
Name	CUSTCLGGRP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TAXGROUP

Attribute	Description
Name	TAXGROUP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

CCATEG

Attribute	Description
Name	CCATEG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EXPCAT

Attribute	**Description**
Name	EXPCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUSTCLASSFN

Attribute	**Description**
Name	CUSTCLASSFN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

FXNETTCUST

Attribute	**Description**
Name	FXNETTCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

XREF

Attribute	**Description**
Name	XREF
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SSN

Attribute	Description
Name	SSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

CIFSTAT

Attribute	Description
Name	CIFSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CIFSTATSNC

Attribute	Description
Name	CIFSTATSNC
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAILRSREQD

Attribute	Description
Name	MAILRSREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLSPARTICIPANT

Attribute	Description
Name	CLSPARTICIPANT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CRMCUST

Attribute	Description
Name	CRMCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ISSUCUST

Attribute	Description
Name	ISSUCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRSRYCUST

Attribute	Description
Name	TRSRYCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

SNAME

Attribute	Description
Name	SNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 20

TOP

LBRN

Attribute	Description
Name	LBRN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CTYPE

Attribute	Description
Name	CTYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,C,B

TOP

FULLNAME

Attribute	Description
Name	FULLNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

AMLCUSTGRP

Attribute	Description
Name	AMLCUSTGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

AMLREQD

Attribute	Description
Name	AMLREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FLGUTLTYPRVDR

Attribute	Description
Name	FLGUTLTYPRVDR
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

UTLTYPRVDRID

Attribute	Description	
Name	UTLTYPRVDRID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHKDIGITVALREQD

Attribute	Description	
Name	CHKDIGITVALREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALGID

Attribute	Description	
Name	ALGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CONSTAXCERTRQD

Attribute	Description	
Name	CONSTAXCERTRQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

INDTAXCERTRQD

Attribute	**Description**
Name	INDTAXCERTRQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HOACNO

Attribute	**Description**
Name	HOACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RISKPRFL

Attribute	**Description**
Name	RISKPRFL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DRCAT

Attribute	**Description**
Name	DRCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FTACCASOF

Attribute	Description
Name	FTACCASOF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,M,D

TOP

UDF1

Attribute	Description
Name	UDF1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDF2

Attribute	Description
Name	UDF2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDF3

Attribute	Description
Name	UDF3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

UDF4

Attribute	Description
Name	UDF4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

UDF5

Attribute	Description
Name	UDF5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDFLBL1

Attribute	Description
Name	UDFLBL1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDFLBL2

Attribute	Description
Name	UDFLBL2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDFLBL3

Attribute	Description
Name	UDFLBL3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL4

Attribute	Description
Name	UDFLBL4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL5

Attribute	Description
Name	UDFLBL5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

FXCUSTCLRILIM

Attribute	Description
Name	FXCUSTCLRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OVRLIM

Attribute	Description
Name	OVRLIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FX_CLEAN_RISK

Attribute	Description
Name	FX_CLEAN_RISK
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CRRATE

Attribute	Description
Name	CRRATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

REVDT

Attribute	Description
Name	REVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIMCCY

Attribute	Description
Name	LIMCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SECCUSTCLRILIM

Attribute	Description
Name	SECCUSTCLRILIM
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SECCLRILIM

Attribute	Description
Name	SECCLRILIM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SECCUSTPSRILIM

Attribute	Description
Name	SECCUSTPSRILIM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SECPSRILIM

Attribute	Description
Name	SECPSRILIM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CUSTUNADV

Attribute	Description
Name	CUSTUNADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

RISKCATEG

Attribute	Description
Name	RISKCATEG
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CLSCCYALLWD

Attribute	Description
Name	CLSCCYALLWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

NETTREQD

Attribute	Description
Name	NETTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIABUNADV

Attribute	Description
Name	LIABUNADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MT920

Attribute	Description
Name	MT920
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RELPRICING

Attribute	**Description**
Name	RELPRICING
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FLGJOINT

Attribute	**Description**
Name	FLGJOINT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

KYCSTAT

Attribute	**Description**
Name	KYCSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,N,F

TOP

SSTAFF

Attribute	**Description**
Name	SSTAFF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UPTYPE

Attribute	Description
Name	UPTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

KYC_REFNO

Attribute	Description
Name	KYC_REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

JOINT_VENTURE

Attribute	Description
Name	JOINT_VENTURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIVATE_CUSTOMER

Attribute	Description
Name	PRIVATE_CUSTOMER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LC_COLLAT_PCT

Attribute	Description
Name	LC_COLLAT_PCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISELCMCUST

Attribute	Description
Name	ISELCMCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ELCMCUSTNO

Attribute	Description
Name	ELCMCUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ALT_CUST_NO

Attribute	Description
Name	ALT_CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DETERIORATION_DATE

Attribute	Description
Name	DETERIORATION_DATE
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CHQ_TAX_EXEMPT_1

Attribute	Description	
Name	CHQ_TAX_EXEMPT_1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Custpersonal

Attribute	Description
Name	Custpersonal

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TITLE

Attribute	Description
Name	TITLE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FSTNAME

Attribute	Description
Name	FSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MIDNAME

Attribute	Description
Name	MIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LSTNAME

Attribute	Description
Name	LSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

DOB

Attribute	Description	
Name	DOB	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

GUARDIAN

Attribute	Description	
Name	GUARDIAN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

MINOR

Attribute	Description	
Name	MINOR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

SEX

Attribute	Description	
Name	SEX	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	M,F

TOP

NATIONID

Attribute	Description
Name	NATIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

PPTNO

Attribute	Description
Name	PPTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

PPTISSDT

Attribute	Description
Name	PPTISSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PPTEXPDT

Attribute	Description
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DADD1

Attribute	Description
Name	DADD1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DADD2

Attribute	**Description**
Name	DADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DADD3

Attribute	**Description**
Name	DADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TEL

Attribute	**Description**
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FAX

Attribute	**Description**
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PADD1

Attribute	Description
Name	PADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PADD2

Attribute	Description
Name	PADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PADD3

Attribute	Description
Name	PADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DCNTRY

Attribute	Description
Name	DCNTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

PCNTRY

Attribute	Description
Name	PCNTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

RESSTATUS

Attribute	Description
Name	RESSTATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: R,N

TOP

CUSTPREFIX1

Attribute	Description
Name	CUSTPREFIX1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

CUSTPREFIX2

Attribute	Description
Name	CUSTPREFIX2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

MOBNUM

Attribute	**Description**
Name	MOBNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SBMTAGEPROOF

Attribute	**Description**
Name	SBMTAGEPROOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,P,V

TOP

CUST_COMM_MODE

Attribute	**Description**
Name	CUST_COMM_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,E

TOP

LAST_UPD_DT

Attribute	**Description**
Name	LAST_UPD_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Custdomestic

Attribute	Description
Name	Custdomestic
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EDUSTAT

Attribute	Description
Name	EDUSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,U,G,P

TOP

MARITALSTAT

Attribute	Description
Name	MARITALSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,M,D,R,P,E,T

TOP

SPNAME

Attribute	Description
Name	SPNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SPEMPSTATUS

Attribute	Description
Name	SPEMPSTATUS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,T,S,U,R,P,N,O

TOP

DEPCHILD

Attribute	**Description**
Name	DEPCHILD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEPOTH

Attribute	**Description**
Name	DEPOTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOMODATE

Attribute	**Description**
Name	ACCOMODATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,O

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Custprof

Attribute	Description
Name	Custprof
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EMPSTAT

Attribute	Description
Name	EMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

EMPTENURE

Attribute	Description
Name	EMPTENURE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RETIREAGE

Attribute	Description
Name	RETIREAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PREVDESIG

Attribute	Description
Name	PREVDESIG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

PREVEMP

Attribute	Description	
Name	PREVEMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CURRDESIG

Attribute	Description	
Name	CURRDESIG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CURREMP

Attribute	Description	
Name	CURREMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ADD1

Attribute	Description	
Name	ADD1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADD3

Attribute	Description
Name	ADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TELEX

Attribute	Description
Name	TELEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FAX

Attribute	Description
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

SALARY

Attribute	Description
Name	SALARY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHER1

Attribute	Description
Name	OTHER1
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RENT

Attribute	Description
Name	RENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSURANCE

Attribute	Description
Name	INSURANCE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LOANPMNT

Attribute	Description
Name	LOANPMNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

OTHEXP

Attribute	Description
Name	OTHEXP
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

HOUSEVAL

Attribute	Description
Name	HOUSEVAL
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

CRCARD

Attribute	Description
Name	CRCARD
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMTCCY1

Attribute	Description
Name	AMTCCY1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

EMPLOYER_DESC

Attribute	Description
Name	EMPLOYER_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

EMP_DESC

Attribute	Description

Name	EMP_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Custcorp

Attribute	**Description**
Name	Custcorp
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CORPNAME

Attribute	**Description**
Name	CORPNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NATIONID

Attribute	**Description**
Name	NATIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REGADD1

Attribute	**Description**
Name	REGADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

REGADD2

Attribute	Description	
Name	REGADD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REGADD3

Attribute	Description	
Name	REGADD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INCORPDT

Attribute	Description	
Name	INCORPDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CAPITAL

Attribute	Description	
Name	CAPITAL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETWORTH

Attribute	Description
Name	NETWORTH

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INCORPCNTRY

Attribute	**Description**
Name	INCORPCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REGCNTRY

Attribute	**Description**
Name	REGCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMTCCY

Attribute	**Description**
Name	AMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CORPDESC

Attribute	**Description**
Name	CORPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255

TOP

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

TOP

Custcorpdir

Attribute	Description	
Name	Custcorpdir	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

DIRNAME

Attribute	Description	
Name	DIRNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

TEL

Attribute	Description	
Name	TEL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

NADDR1

Attribute	Description
Name	NADDR1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR2

Attribute	Description
Name	NADDR2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR3

Attribute	Description
Name	NADDR3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR4

Attribute	Description
Name	NADDR4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDR1

Attribute	Description

Name	ADDR1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRS2

Attribute	**Description**
Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRS3

Attribute	**Description**
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRY

Attribute	**Description**
Name	COUNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXID

Attribute	**Description**
Name	TAXID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MOBNO

Attribute	Description
Name	MOBNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Issuerdet

Attribute	Description
Name	Issuerdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OVERLIMIT

Attribute	Description
Name	OVERLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OVERLMTCCY

Attribute	**Description**
Name	OVERLMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Issuerlmts

Attribute	**Description**
Name	Issuerlmts
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CLTRLTYP

Attribute	**Description**
Name	CLTRLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 70

TOP

LMTAMT

Attribute	**Description**
Name	LMTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LMTCCY

Attribute	Description
Name	LMTCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ISSID

Attribute	Description
Name	ISSID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

Custgrp

Attribute	Description
Name	Custgrp
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

GRPNO

Attribute	Description
Name	GRPNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

RELATION

Attribute	Description

Name	RELATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Custshhold

Attribute	**Description**
Name	Custshhold
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SHHOLDID

Attribute	**Description**
Name	SHHOLDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SHHOLDPCT

Attribute	**Description**
Name	SHHOLDPCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHRHLDRNAME

Attribute	**Description**
Name	SHRHLDRNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Clsccyrest

Attribute	Description
Name	Clsccyrest
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Bic

Attribute	Description
Name	Bic
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC

Attribute	Description
Name	ACC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BICCD

Attribute	**Description**
Name	BICCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

Linkedac

Attribute	**Description**
Name	Linkedac
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

VRFD

Attribute	**Description**
Name	VRFD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LINKEDACCNO

Attribute	**Description**
Name	LINKEDACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	30

TOP

LINKEDACCIBAN

Attribute	Description	
Name	LINKEDACCIBAN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LINKEDACCBIC

Attribute	Description	
Name	LINKEDACCBIC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

JointVenture

Attribute	Description	
Name	JointVenture	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

PARTYID

Attribute	Description	
Name	PARTYID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

PARTYRATIO

Attribute	Description
Name	PARTYRATIO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Custdoc-Chklist

Attribute	Description
Name	Custdoc-Chklist
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHECKED

Attribute	Description
Name	CHECKED
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Doctype-Remarks

Attribute	Description	
Name	Doctype-Remarks	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REMARK1

Attribute	Description	
Name	REMARK1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	225

TOP

REMARK2

Attribute	Description	
Name	REMARK2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	225

TOP

REMARK3

Attribute	Description	
Name	REMARK3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	225

TOP

REMARK4

Attribute	Description
Name	REMARK4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK5

Attribute	Description
Name	REMARK5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK6

Attribute	Description
Name	REMARK6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK7

Attribute	Description
Name	REMARK7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK8

Attribute	Description
Name	REMARK8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK9

Attribute	Description
Name	REMARK9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK10

Attribute	Description
Name	REMARK10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

Custmis

Attribute	Description
Name	Custmis
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates Management Information System Group.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CUST

Attribute	**Description**
Name	CUST
Datatype	String
Description	Indicates the Customer.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRNCD

Attribute	**Description**
Name	BRNCD
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Custchnglog

Attribute	**Description**
Name	Custchnglog
Datatype	
Description	Indicates the Customer Change Log.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	**Description**
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	Indicates the Old MIS Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	Indicates the New MIS Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Baltrnsfrlog

Attribute	Description
Name	Baltrnsfrlog
Datatype	
Description	Indicates the Balance Transfer Log.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String

Description	Indicates the Branch Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDCD

Attribute	**Description**
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	**Description**
Name	FINYR
Datatype	String
Description	Indicates the Financial Year.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNDT

Attribute	**Description**
Name	TXNDT
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

GLCODE

Attribute	**Description**
Name	GLCODE
Datatype	String
Description	Indicates the GL Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	Indicates the Old MIS Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	Indicates the New MIS Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TRNIND

Attribute	Description
Name	TRNIND
Datatype	String
Description	Indicates Transfer Identification Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	Attribute: minOccurs — Description: 0

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate.
Attributes	Attribute: minOccurs — Description: 0

TOP

Dfltcd

Attribute	Description
Name	Dfltcd
Datatype	
Description	Indicates the Customer MIS Classes.
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	Attribute: minOccurs — Description: 1

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCD

Attribute	**Description**
Name	MISCD
Datatype	String
Description	Indicates the MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Dfltcda

Attribute	**Description**
Name	Dfltcda
Datatype	
Description	Indicates the Composite MIS Classes.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	**Description**
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCD

Attribute	**Description**
Name	MISCD
Datatype	String
Description	Indicates the MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Custloghead

Attribute	Description
Name	Custloghead
Datatype	
Description	Indicates the Customer Log Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Jointcustomer

Attribute	Description
Name	Jointcustomer
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Custjoint

Attribute	Description
Name	Custjoint
Datatype	
Description	Indicates Customer Joint.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTPREFIX

Attribute	Description
Name	CUSTPREFIX
Datatype	String
Description	Indicates the Customer Prefix.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FRSTNAME

Attribute	**Description**
Name	FRSTNAME
Datatype	String
Description	Indicates the First Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MIDNAME

Attribute	**Description**
Name	MIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LASTNAME

Attribute	**Description**
Name	LASTNAME
Datatype	String
Description	Indicates the Last Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOB

Attribute	**Description**
Name	DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SEX

Attribute	Description
Name	SEX
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,F

TOP

PPNO

Attribute	Description
Name	PPNO
Datatype	String
Description	Indicates Passport Number.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

PPTISSDT

Attribute	Description
Name	PPTISSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PPTEXPDT

Attribute	Description
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ADD2

Attribute	Description	
Name	ADD2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ADD3

Attribute	Description	
Name	ADD3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

TEL

Attribute	Description	
Name	TEL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

EMAIL

Attribute	Description	
Name	EMAIL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TOP

SSN

Attribute	Description
Name	SSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

DECEASED

Attribute	Description
Name	DECEASED
Datatype	String
Description	Indicates whether Deceased or not. The value should be either D or N.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,N

TOP

RESISTAT

Attribute	Description
Name	RESISTAT
Datatype	String
Description	Indicates the Resistant Status. The value could be either R or N.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / R,N

TOP

Cust-Acc-Det

Attribute	Description
Name	Cust-Acc-Det
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Diary-Mst

Attribute	**Description**
Name	Diary-Mst
Datatype	
Description	Indicates Diary Master.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSTRNO

Attribute	**Description**
Name	INSTRNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

UNTTYP

Attribute	**Description**
Name	UNTTYP
Datatype	String
Description	Indicates Unit Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

UNTVAL

Attribute	**Description**
Name	UNTVAL
Datatype	String
Description	Indicates Unit Value
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch Code.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

INSTR

Attribute	Description
Name	INSTR
Datatype	String
Description	Indicates Instructions
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 2000

TOP

INSTRTYPE

Attribute	Description
Name	INSTRTYPE
Datatype	String
Description	Indicates Instruction Type
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

EXEDAYS

Attribute	Description
Name	EXEDAYS
Datatype	Number
Description	Indicates Execution Days
Attributes	Attribute: minOccurs; Description: 0

TOP

EXEMONTHS

Attribute	Description
Name	EXEMONTHS
Datatype	Number
Description	Indicates Execution Months
Attributes	Attribute: minOccurs, Description: 0

TOP

EXEYEARS

Attribute	Description
Name	EXEYEARS
Datatype	Number
Description	Indicates Execution Years
Attributes	Attribute: minOccurs, Description: 0

TOP

MNTHENDFLG

Attribute	Description
Name	MNTHENDFLG
Datatype	String
Description	Indicates Month End Flag. Flag Can be either Y or N.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

HLDRULE

Attribute	Description
Name	HLDRULE
Datatype	String
Description	Indicates Holiday Rule
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 1

TOP

FRSTDUEDT

Attribute	Description
Name	FRSTDUEDT
Datatype	Date
Description	Indicates First Due Date.
Attributes	Attribute: minOccurs, Description: 0

TOP

NXTDUEDT

Attribute	Description
Name	NXTDUEDT
Datatype	Date
Description	Indicates Next Due Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTEXEDT

Attribute	Description
Name	NXTEXEDT
Datatype	Date
Description	Indicates Next Execution Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONDELEM

Attribute	Description
Name	CONDELEM
Datatype	String
Description	Indicates Condition Elements.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

OPRTR

Attribute	Description
Name	OPRTR
Datatype	String
Description	Indicates Operator.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CONDVAL

Attribute	Description
Name	CONDVAL
Datatype	Number
Description	Indicates Condition Value.

Attributes	Attribute	Description
	minOccurs	0

TOP

ACCOFCR

Attribute	Description	
Name	ACCOFCR	
Datatype	String	
Description	Indicates Account Officer.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SPLINSTRTYP

Attribute	Description	
Name	SPLINSTRTYP	
Datatype	String	
Description	Indicates Special Instruction Type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

EXPDT

Attribute	Description	
Name	EXPDT	
Datatype	Date	
Description	Indicates Expiry Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPLINSTR

Attribute	Description	
Name	SPLINSTR	
Datatype	String	
Description	Indicates Special Instructions.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Custaccdet

Attribute	Description
Name	Custaccdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkage details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Indicates the customer

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Indicate relations
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicate,include relationship Y:yes N:no
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	Indicates description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Custacdetail

Attribute	Description
Name	Custacdetail
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTTEXT

Attribute	Description
Name	CUSTTEXT
Datatype	
Description	Include customer details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	Indicates sequence number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String

Description	Indicate text description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Sttms-Debit

Attribute	**Description**
Name	Sttms-Debit
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	Indicates the Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACTNO

Attribute	Description
Name	ACTNO
Datatype	String
Description	Indicates the Account Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Sttms-Detail

Attribute	Description
Name	Sttms-Detail
Datatype	
Description	Indicates Customer Details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description

Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REQUEST_REFERENCE_NO

Attribute	**Description**
Name	REQUEST_REFERENCE_NO
Datatype	String
Description	Indicates the Request Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CARDNO

Attribute	**Description**
Name	CARDNO
Datatype	String
Description	Indicates the Card Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 19

TOP

CUST_NO

Attribute	**Description**
Name	CUST_NO
Datatype	String
Description	Indicates the Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CARD_PRODUCT

Attribute	**Description**
Name	CARD_PRODUCT
Datatype	String
Description	Indicates the Product code.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRIMARY_CARD

Attribute	**Description**	
Name	PRIMARY_CARD	
Datatype	String	
Description	Indicates the Primary Card Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NAME_ON_CARD

Attribute	**Description**	
Name	NAME_ON_CARD	
Datatype	String	
Description	Indicates the Name on Card.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

OWNER_ID_NO

Attribute	**Description**	
Name	OWNER_ID_NO	
Datatype	String	
Description	Indicates the Owner ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

CARD_ISSUED_DT

Attribute	**Description**	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Indicates the Card Issue Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CARD_EXPIRY_DT

Attribute	Description
Name	CARD_EXPIRY_DT
Datatype	Date
Description	Indicates the Card Expiry Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_STATUS

Attribute	Description
Name	CARD_STATUS
Datatype	String
Description	Indicates the Card Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	Indicates the Record Stat.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTH_STAT

Attribute	Description
Name	AUTH_STAT
Datatype	String
Description	Indicates the Auth Stat.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CARD_BIN

Attribute	Description
Name	CARD_BIN

Datatype	String
Description	Indicates the Card Bin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CUST_AC_NO

Attribute	**Description**
Name	CUST_AC_NO
Datatype	String
Description	Indicates the Customer Account Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Extsys-Ws-Master

Attribute	**Description**
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	**Description**
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXTWSRESP

Attribute	**Description**
Name	EXTWSRESP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

Stvws-Cust-Trntax

Attribute	Description
Name	Stvws-Cust-Trntax
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Sttms-Cust-Trn-Tax

Attribute	Description
Name	Sttms-Cust-Trn-Tax
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TAX_SCHEME

Attribute	Description
Name	TAX_SCHEME
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

TXN_TAX_EXEMPTED

Attribute	**Description**
Name	TXN_TAX_EXEMPTED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TXN_TAX_EXEMPTION_PERCENT

Attribute	**Description**
Name	TXN_TAX_EXEMPTION_PERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXN_TAX_EFF_DATE

Attribute	**Description**
Name	TXN_TAX_EFF_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXN_TAX_EXEMPTION_REASON

Attribute	**Description**
Name	TXN_TAX_EXEMPTION_REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

2.15.2.ST-CreateCustomer-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Customer-IO*
    - *NAME*
    - *ADDRLN1*
    - *ADDRLN3*
    - *ADDRLN2*
    - *ADDRLN4*
    - *SWIFTCD*
    - *FAX*
    - *COUNTRY*
    - *NLTY*
    - *LANG*
    - *EXPCNTRY*
    - *UIDNAME*
    - *UIDVAL*
    - *LOC*
    - *FROZEN*
    - *DEAD*
    - *WHRUNKN*
    - *GRPCD*

CHGGRP
CUSTCLGGRP
TAXGROUP
CCATEG
EXPCAT
CUSTCLASSFN
FXNETTCUST
XREF
MEDIA
SSN
CIFSTAT
CIFSTATSNC
MAILRSREQD
CLSPARTICIPANT
CRMCUST
ISSUCUST
TRSRYCUST
CUSTNO
SNAME
CTYPE
FULLNAME
AMLCUSTGRP
AMLREQD
FLGUTLTYPRVDR
UTLTYPRVDRID
CHKDIGITVALREQD
ALGID
CONSTAXCERTRQD
INDTAXCERTRQD
HOACNO
RISKPRFL
DRCAT
FTACCASOF
UDF1
UDF2
UDF3
UDF4
UDF5
FXCUSTCLRILIM
OVRLIM
FX_CLEAN_RISK
CRRATE
REVDT
LIMCCY

SECCUSTCLRILIM
SECCLRILIM
SECCUSTPSRILIM
SECPSRILIM
CUSTUNADV
RISKCATEG
CLSCCYALLWD
NETTREQD
LIABUNADV
MT920
RELPRICING
FLGJOINT
KYCSTAT
SSTAFF
UPTYPE
KYC_REFNO
JOINT_VENTURE
PRIVATE_CUSTOMER
LC_COLLAT_PCT
ISELCMCUST
ELCMCUSTNO
ALT_CUST_NO
DETERIORATION_DATE
CHQ_TAX_EXEMPT_1
Custpersonal
- *TITLE*
- *FSTNAME*
- *MIDNAME*
- *LSTNAME*
- *DOB*
- *GUARDIAN*
- *MINOR*
- *SEX*
- *NATIONID*
- *PPTNO*
- *PPTISSDT*
- *PPTEXPDT*
- *DADD1*
- *DADD2*
- *DADD3*
- *TEL*
- *FAX*
- *EMAIL*
- *PADD1*

PADD2
PADD3
DCNTRY
PCNTRY
RESSTATUS
CUSTPREFIX1
CUSTPREFIX2
MOBNUM
SBMTAGEPROOF
CUST_COMM_MODE
Custdomestic
- *EDUSTAT*
- *MARITALSTAT*
- *SPNAME*
- *SPEMPSTATUS*
- *DEPCHILD*
- *DEPOTH*
- *ACCOMODATE*
- *CUSTNO*

Custprof
- *EMPSTAT*
- *EMPTENURE*
- *RETIREAGE*
- *PREVDESIG*
- *PREVEMP*
- *CURRDESIG*
- *CURREMP*
- *ADD1*
- *ADD2*
- *ADD3*
- *TEL*
- *TELEX*
- *FAX*
- *EMAIL*
- *SALARY*
- *OTHER1*
- *RENT*
- *INSURANCE*
- *LOANPMNT*
- *OTHEXP*
- *HOUSEVAL*
- *CRCARD*
- *CNTY*
- *AMTCCY1*

CUSTNO

EMPLOYER_DESC

EMP_DESC

Custcorp

CORPNAME

NATIONID

REGADD1

REGADD2

REGADD3

INCORPDT

CAPITAL

NETWORTH

INCORPCNTRY

REGCNTRY

AMTCCY

CORPDESC

CUSTNO

Custcorpdir

DIRNAME

TEL

NADDR1

NADDR2

NADDR3

NADDR4

ADDR1

ADDRS2

ADDRS3

TAXID

EMAIL

Issuerdet

OVERLIMIT

CUSTNO

OVERLMTCCY

Issuerlmts

CLTRLTYP

LMTAMT

LMTCCY

ISSID

Custgrp

GRPNO

RELATION

Custshhold

SHHOLDID

SHHOLDPCT

SHRHLDRNAME

Clsccyrest

CCY

DESC

Bic

ACC

BICCD

Linkedac

VRFD

LINKEDACCNO

LINKEDACCIBAN

LINKEDACCBIC

JointVenture

PARTYID

PARTYRATIO

Custdoc-Chklist

DOCUMENT_TYPE

CHECKED

Doctype-Remarks

REMARK1

REMARK2

REMARK3

REMARK4

REMARK5

REMARK6

REMARK7

REMARK8

REMARK9

REMARK10

Custmis

MISGRP

CUSTNO

Custchnglog

Baltrnsfrlog

Dfltcd

MISCD

Dfltcda

MISCD

Jointcustomer

CUSTNO

Custjoint

CUSTPREFIX

FRSTNAME

MIDNAME

LASTNAME
DOB
SEX
PPNO
PPTISSDT
PPTEXPDT
ADD1
ADD2
ADD3
TEL
EMAIL
DECEASED
RESISTAT
Cust-Acc-Det
CUSTNO
Diary-Mst
INSTRNO
UNTTYP
UNTVAL
BRN
INSTR
INSTRTYPE
EXEDAYS
EXEMONTHS
EXEYEARS
MNTHENDFLG
HLDRULE
FRSTDUEDT
NXTDUEDT
NXTEXEDT
CONDELEM
OPRTR
CONDVAL
ACCOFCR
SPLINSTRTYP
EXPDT
SPLINSTR
Custaccdet
CUSTNO
Relationship-Linkage
CUSTOMER
RELATIONSHIP
INHERIT
DESCP

Custacdetail

CUSTNO

CUSTTEXT

SEQNO

CUSTNO

TDESC

UDFDETAILS

FLDNAM

FLDVAL

Sttms-Debit

BRANCH_CODE

CUST_NO

ACTNO

Sttms-Detail

BRANCH_CODE

REQUEST_REFERENCE_NO

CARDNO

CUST_NO

CARD_PRODUCT

PRIMARY_CARD

NAME_ON_CARD

OWNER_ID_NO

CARD_ISSUED_DT

CARD_EXPIRY_DT

CARD_STATUS

RECORD_STAT

AUTH_STAT

CARD_BIN

CUST_AC_NO

Extsys-Ws-Master

KEYID

Extsys-Ws-Details

USERREMARKS

Stvws-Cust-Trntax

CUSTOMER_NO

Sttms-Cust-Trn-Tax

TAX_SCHEME

TXN_TAX_EXEMPTED

TXN_TAX_EXEMPTION_PERCENT

TXN_TAX_EFF_DATE

TXN_TAX_EXEMPTION_REASON

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Customer-IO

Attribute	Description
Name	Customer-IO
Datatype	
Description	

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

ADDRLN1

Attribute	Description	
Name	ADDRLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN3

Attribute	Description	
Name	ADDRLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN2

Attribute	Description	
Name	ADDRLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN4

Attribute	Description
Name	ADDRLN4
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SWIFTCD

Attribute	**Description**
Name	SWIFTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FAX

Attribute	**Description**
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRY

Attribute	**Description**
Name	COUNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NLTY

Attribute	**Description**
Name	NLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	3

TOP

LANG

Attribute	Description	
Name	LANG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

TOP

EXPCNTRY

Attribute	Description	
Name	EXPCNTRY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

UIDNAME

Attribute	Description	
Name	UIDNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

UIDVAL

Attribute	Description	
Name	UIDVAL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

LOC

Attribute	Description
Name	LOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FROZEN

Attribute	Description
Name	FROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEAD

Attribute	Description
Name	DEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

WHRUNKN

Attribute	Description
Name	WHRUNKN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

CHGGRP

Attribute	Description
Name	CHGGRP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

CUSTCLGGRP

Attribute	Description
Name	CUSTCLGGRP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TAXGROUP

Attribute	Description
Name	TAXGROUP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

CCATEG

Attribute	Description
Name	CCATEG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EXPCAT

Attribute	**Description**
Name	EXPCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUSTCLASSFN

Attribute	**Description**
Name	CUSTCLASSFN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

FXNETTCUST

Attribute	**Description**
Name	FXNETTCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

XREF

Attribute	**Description**
Name	XREF
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SSN

Attribute	Description
Name	SSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

CIFSTAT

Attribute	Description
Name	CIFSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CIFSTATSNC

Attribute	Description
Name	CIFSTATSNC
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAILRSREQD

Attribute	Description
Name	MAILRSREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLSPARTICIPANT

Attribute	Description
Name	CLSPARTICIPANT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CRMCUST

Attribute	Description
Name	CRMCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ISSUCUST

Attribute	Description
Name	ISSUCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRSRYCUST

Attribute	Description
Name	TRSRYCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

SNAME

Attribute	Description
Name	SNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 20

TOP

CTYPE

Attribute	Description
Name	CTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: I,C,B

TOP

FULLNAME

Attribute	Description
Name	FULLNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

AMLCUSTGRP

Attribute	Description
Name	AMLCUSTGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

AMLREQD

Attribute	Description
Name	AMLREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FLGUTLTYPRVDR

Attribute	Description
Name	FLGUTLTYPRVDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UTLTYPRVDRID

Attribute	Description
Name	UTLTYPRVDRID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHKDIGITVALREQD

Attribute	Description	
Name	CHKDIGITVALREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALGID

Attribute	Description	
Name	ALGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CONSTAXCERTRQD

Attribute	Description	
Name	CONSTAXCERTRQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INDTAXCERTRQD

Attribute	Description	
Name	INDTAXCERTRQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

HOACNO

Attribute	Description	
Name	HOACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RISKPRFL

Attribute	Description	
Name	RISKPRFL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

DRCAT

Attribute	Description	
Name	DRCAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FTACCASOF

Attribute	Description	
Name	FTACCASOF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,D

TOP

UDF1

Attribute	Description
Name	UDF1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDF2

Attribute	Description
Name	UDF2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDF3

Attribute	Description
Name	UDF3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

UDF4

Attribute	Description
Name	UDF4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

UDF5

Attribute	Description
Name	UDF5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

FXCUSTCLRILIM

Attribute	Description
Name	FXCUSTCLRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OVRLIM

Attribute	Description
Name	OVRLIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FX_CLEAN_RISK

Attribute	Description
Name	FX_CLEAN_RISK
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CRRATE

Attribute	Description
Name	CRRATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

REVDT

Attribute	Description
Name	REVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIMCCY

Attribute	Description
Name	LIMCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SECCUSTCLRILIM

Attribute	Description
Name	SECCUSTCLRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCLRILIM

Attribute	Description
Name	SECCLRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCUSTPSRILIM

Attribute	Description
Name	SECCUSTPSRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECPSRILIM

Attribute	Description
Name	SECPSRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTUNADV

Attribute	Description
Name	CUSTUNADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RISKCATEG

Attribute	Description
Name	RISKCATEG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CLSCCYALLWD

Attribute	Description
Name	CLSCCYALLWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

NETTREQD

Attribute	Description
Name	NETTREQD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIABUNADV

Attribute	**Description**
Name	LIABUNADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MT920

Attribute	**Description**
Name	MT920
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RELPRICING

Attribute	**Description**
Name	RELPRICING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FLGJOINT

Attribute	**Description**
Name	FLGJOINT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

KYCSTAT

Attribute	Description
Name	KYCSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / V,N,F

TOP

SSTAFF

Attribute	Description
Name	SSTAFF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UPTYPE

Attribute	Description
Name	UPTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

KYC_REFNO

Attribute	Description
Name	KYC_REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

JOINT_VENTURE

Attribute	**Description**
Name	JOINT_VENTURE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIVATE_CUSTOMER

Attribute	**Description**
Name	PRIVATE_CUSTOMER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LC_COLLAT_PCT

Attribute	**Description**
Name	LC_COLLAT_PCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ISELCMCUST

Attribute	**Description**
Name	ISELCMCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ELCMCUSTNO

Attribute	Description
Name	ELCMCUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ALT_CUST_NO

Attribute	Description
Name	ALT_CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DETERIORATION_DATE

Attribute	Description
Name	DETERIORATION_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHQ_TAX_EXEMPT_1

Attribute	Description
Name	CHQ_TAX_EXEMPT_1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Custpersonal

Attribute	Description
Name	Custpersonal
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

TITLE

Attribute	Description	
Name	TITLE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FSTNAME

Attribute	Description	
Name	FSTNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MIDNAME

Attribute	Description	
Name	MIDNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

LSTNAME

Attribute	Description	
Name	LSTNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GUARDIAN

Attribute	Description
Name	GUARDIAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MINOR

Attribute	Description
Name	MINOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SEX

Attribute	Description
Name	SEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,F

TOP

NATIONID

Attribute	Description
Name	NATIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PPTNO

Attribute	**Description**
Name	PPTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PPTISSDT

Attribute	**Description**
Name	PPTISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PPTEXPDT

Attribute	**Description**
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DADD1

Attribute	**Description**
Name	DADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DADD2

Attribute	Description
Name	DADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DADD3

Attribute	Description
Name	DADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FAX

Attribute	Description
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

PADD1

Attribute	Description
Name	PADD1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

PADD2

Attribute	Description
Name	PADD2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

PADD3

Attribute	Description
Name	PADD3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

DCNTRY

Attribute	Description
Name	DCNTRY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PCNTRY

Attribute	**Description**
Name	PCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RESSTATUS

Attribute	**Description**
Name	RESSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / R,N

TOP

CUSTPREFIX1

Attribute	**Description**
Name	CUSTPREFIX1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

CUSTPREFIX2

Attribute	**Description**
Name	CUSTPREFIX2
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

MOBNUM

Attribute	Description
Name	MOBNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SBMTAGEPROOF

Attribute	Description
Name	SBMTAGEPROOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,P,V

TOP

CUST_COMM_MODE

Attribute	Description
Name	CUST_COMM_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,E

TOP

Custdomestic

Attribute	Description
Name	Custdomestic
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EDUSTAT

Attribute	Description
Name	EDUSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,U,G,P

TOP

MARITALSTAT

Attribute	Description
Name	MARITALSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: S,M,D,R,P,E,T

TOP

SPNAME

Attribute	Description
Name	SPNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SPEMPSTATUS

Attribute	Description
Name	SPEMPSTATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: F,T,S,U,R,P,N,O

TOP

DEPCHILD

Attribute	Description
Name	DEPCHILD

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEPOTH

Attribute	Description
Name	DEPOTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOMODATE

Attribute	Description
Name	ACCOMODATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,O

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Custprof

Attribute	Description
Name	Custprof
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EMPSTAT

Attribute	Description
Name	EMPSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

EMPTENURE

Attribute	Description
Name	EMPTENURE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RETIREAGE

Attribute	Description
Name	RETIREAGE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PREVDESIG

Attribute	Description
Name	PREVDESIG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

PREVEMP

Attribute	Description
Name	PREVEMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CURRDESIG

Attribute	**Description**
Name	CURRDESIG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CURREMP

Attribute	**Description**
Name	CURREMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADD1

Attribute	**Description**
Name	ADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADD2

Attribute	**Description**
Name	ADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADD3

Attribute	Description
Name	ADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TELEX

Attribute	Description
Name	TELEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FAX

Attribute	Description
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

SALARY

Attribute	Description
Name	SALARY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHER1

Attribute	Description
Name	OTHER1
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RENT

Attribute	Description
Name	RENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSURANCE

Attribute	Description
Name	INSURANCE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANPMNT

Attribute	Description
Name	LOANPMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OTHEXP

Attribute	Description
Name	OTHEXP
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

HOUSEVAL

Attribute	Description
Name	HOUSEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CRCARD

Attribute	Description
Name	CRCARD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMTCCY1

Attribute	Description
Name	AMTCCY1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

EMPLOYER_DESC

Attribute	Description
Name	EMPLOYER_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 22

TOP

EMP_DESC

Attribute	Description
Name	EMP_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

Custcorp

Attribute	Description
Name	Custcorp
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CORPNAME

Attribute	Description
Name	CORPNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NATIONID

Attribute	Description
Name	NATIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REGADD1

Attribute	Description
Name	REGADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REGADD2

Attribute	Description
Name	REGADD2
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REGADD3

Attribute	Description
Name	REGADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INCORPDT

Attribute	Description
Name	INCORPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CAPITAL

Attribute	Description
Name	CAPITAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NETWORTH

Attribute	Description
Name	NETWORTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INCORPCNTRY

Attribute	Description
Name	INCORPCNTRY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REGCNTRY

Attribute	**Description**
Name	REGCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMTCCY

Attribute	**Description**
Name	AMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CORPDESC

Attribute	**Description**
Name	CORPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Custcorpdir

Attribute	Description
Name	Custcorpdir
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs = unbounded; minOccurs = 0

TOP

DIRNAME

Attribute	Description
Name	DIRNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: maxLength = 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: maxLength = 105

TOP

NADDR1

Attribute	Description
Name	NADDR1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: maxLength = 105

TOP

NADDR2

Attribute	Description
Name	NADDR2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR3

Attribute	Description
Name	NADDR3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR4

Attribute	Description
Name	NADDR4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

TAXID

Attribute	Description
Name	TAXID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

Issuerdet

Attribute	Description
Name	Issuerdet

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OVERLIMIT

Attribute	Description
Name	OVERLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OVERLMTCCY

Attribute	Description
Name	OVERLMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Issuerlmts

Attribute	Description
Name	Issuerlmts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLTRLTYP

Attribute	Description
Name	CLTRLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 70

TOP

LMTAMT

Attribute	Description
Name	LMTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LMTCCY

Attribute	Description
Name	LMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ISSID

Attribute	Description
Name	ISSID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Custgrp

Attribute	Description
Name	Custgrp
Datatype	

Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

GRPNO

Attribute	**Description**	
Name	GRPNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RELATION

Attribute	**Description**	
Name	RELATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Custshhold

Attribute	**Description**	
Name	Custshhold	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SHHOLDID

Attribute	**Description**	
Name	SHHOLDID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SHHOLDPCT

Attribute	Description
Name	SHHOLDPCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHRHLDRNAME

Attribute	Description
Name	SHRHLDRNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Clsccyrest

Attribute	Description
Name	Clsccyrest
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Bic

Attribute	**Description**
Name	Bic
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC

Attribute	**Description**
Name	ACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BICCD

Attribute	**Description**
Name	BICCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

Linkedac

Attribute	**Description**
Name	Linkedac
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VRFD

Attribute	Description
Name	VRFD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LINKEDACCNO

Attribute	Description
Name	LINKEDACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LINKEDACCIBAN

Attribute	Description
Name	LINKEDACCIBAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LINKEDACCBIC

Attribute	Description
Name	LINKEDACCBIC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

JointVenture

Attribute	Description
Name	JointVenture
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PARTYRATIO

Attribute	Description
Name	PARTYRATIO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

Custdoc-Chklist

Attribute	Description
Name	Custdoc-Chklist
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

CHECKED

Attribute	Description
Name	CHECKED
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Doctype-Remarks

Attribute	Description
Name	Doctype-Remarks
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REMARK1

Attribute	Description
Name	REMARK1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK2

Attribute	Description
Name	REMARK2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK3

Attribute	Description
Name	REMARK3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK4

Attribute	Description
Name	REMARK4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK5

Attribute	Description
Name	REMARK5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK6

Attribute	Description
Name	REMARK6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK7

Attribute	Description
Name	REMARK7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK8

Attribute	**Description**
Name	REMARK8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK9

Attribute	**Description**
Name	REMARK9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK10

Attribute	**Description**
Name	REMARK10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

Custmis

Attribute	**Description**
Name	Custmis
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates the MIS Group.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

Custchnglog

Attribute	Description
Name	Custchnglog
Datatype	
Description	Indicates the Customer Change Log.
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

Baltrnsfrlog

Attribute	Description
Name	Baltrnsfrlog
Datatype	
Description	Indicates the Balance Transfer Log.
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

Dfltcd

Attribute	Description
Name	Dfltcd
Datatype	
Description	Indicates the Customer MIS Classes.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates the MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Dfltcda

Attribute	Description
Name	Dfltcda
Datatype	
Description	Indicates the Composite MIS Classes.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates the MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Jointcustomer

Attribute	Description
Name	Jointcustomer
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Custjoint

Attribute	Description	
Name	Custjoint	
Datatype		
Description	Indicates the Customer Joint.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CUSTPREFIX

Attribute	Description	
Name	CUSTPREFIX	
Datatype	String	
Description	Indicates the Customer Prefix.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FRSTNAME

Attribute	Description	
Name	FRSTNAME	
Datatype	String	
Description	Indicates the First Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MIDNAME

Attribute	Description
Name	MIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LASTNAME

Attribute	Description
Name	LASTNAME
Datatype	String
Description	Indicates the Last Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SEX

Attribute	Description
Name	SEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,F

TOP

PPNO

Attribute	Description
Name	PPNO
Datatype	String

Description	Indicates the Passport Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PPTISSDT

Attribute	**Description**
Name	PPTISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PPTEXPDT

Attribute	**Description**
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	**Description**
Name	ADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADD2

Attribute	**Description**
Name	ADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADD3

Attribute	Description
Name	ADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DECEASED

Attribute	Description
Name	DECEASED
Datatype	String
Description	Indicates whether deceased or not. The value can be either D or N.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,N

TOP

RESISTAT

Attribute	Description

Name	RESISTAT
Datatype	String
Description	Indicates the Resident Status. The Value Could be either R or N.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,N

TOP

Cust-Acc-Det

Attribute	Description
Name	Cust-Acc-Det
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Diary-Mst

Attribute	Description
Name	Diary-Mst
Datatype	
Description	Indicates Diary Master.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	Indicates Instrument Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

ORACLE

TOP

UNTTYP

Attribute	Description
Name	UNTTYP
Datatype	String
Description	Indicates Unit Type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

UNTVAL

Attribute	Description
Name	UNTVAL
Datatype	String
Description	Indicates Unit Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INSTR

Attribute	Description
Name	INSTR
Datatype	String
Description	Indicates Instructions.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

INSTRTYPE

Attribute	Description
Name	INSTRTYPE
Datatype	String
Description	Indicates Instruction Type.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 1

TOP

EXEDAYS

Attribute	Description
Name	EXEDAYS
Datatype	Number
Description	Indicates Execution Days.
Attributes	Attribute: minOccurs, Description: 0

TOP

EXEMONTHS

Attribute	Description
Name	EXEMONTHS
Datatype	Number
Description	Indicates Execution Months.
Attributes	Attribute: minOccurs, Description: 0

TOP

EXEYEARS

Attribute	Description
Name	EXEYEARS
Datatype	Number
Description	Indicates Execution years.
Attributes	Attribute: minOccurs, Description: 0

TOP

MNTHENDFLG

Attribute	Description
Name	MNTHENDFLG
Datatype	String
Description	Indicates Month End Flag. The flag should be either Y or N.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

HLDRULE

Attribute	Description
Name	HLDRULE
Datatype	String
Description	Indicates Holiday Rule.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FRSTDUEDT

Attribute	Description
Name	FRSTDUEDT
Datatype	Date
Description	Indicates First Due date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTDUEDT

Attribute	Description
Name	NXTDUEDT
Datatype	Date
Description	Indicates Next Due date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTEXEDT

Attribute	Description
Name	NXTEXEDT
Datatype	Date
Description	Indicates Next Execution Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONDELEM

Attribute	Description
Name	CONDELEM
Datatype	String
Description	Indicates Condition Elements.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

OPRTR

Attribute	**Description**
Name	OPRTR
Datatype	String
Description	Indicates Operator.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

CONDVAL

Attribute	**Description**
Name	CONDVAL
Datatype	Number
Description	Indicates Condition Value.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCOFCR

Attribute	**Description**
Name	ACCOFCR
Datatype	String
Description	Indicates Account Officer.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SPLINSTRTYP

Attribute	**Description**
Name	SPLINSTRTYP
Datatype	String
Description	Indicates Special Instruction Type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	Indicates Expiry date.
Attributes	Attribute: minOccurs, Description: 0

TOP

SPLINSTR

Attribute	Description
Name	SPLINSTR
Datatype	String
Description	Indicates Special Instruction.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 255

TOP

Custaccdet

Attribute	Description
Name	Custaccdet
Datatype	
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 1
Restrictions	Restrictions: maxLength, Description: 9

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkage details.

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Indicates the customer
Attributes	Attribute: minOccurs / Description: 1
Restrictions	Restrictions: maxLength / Description: 9

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Indicate relations
Attributes	Attribute: minOccurs / Description: 1
Restrictions	Restrictions: maxLength / Description: 10

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicate,include relationship Y:yes N:no
Attributes	Attribute: minOccurs / Description: 0
Restrictions	Restrictions: enumeration / Description: Y,N

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	Indicates description
Attributes	Attribute: minOccurs / Description: 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

Custacdetail

Attribute	Description	
Name	Custacdetail	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTTEXT

Attribute	Description	
Name	CUSTTEXT	
Datatype		
Description	Include customer details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SEQNO

Attribute	Description	
Name	SEQNO	
Datatype	Number	
Description	Indicates sequence number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TDESC

Attribute	**Description**
Name	TDESC
Datatype	String
Description	Indicate text description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Sttms-Debit

Attribute	Description
Name	Sttms-Debit
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	Indicates the Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACTNO

Attribute	Description
Name	ACTNO
Datatype	String
Description	Indicates the Account Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Sttms-Detail

Attribute	Description
Name	Sttms-Detail

Datatype	
Description	Indicates Customer Details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRANCH_CODE

Attribute	**Description**
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REQUEST_REFERENCE_NO

Attribute	**Description**
Name	REQUEST_REFERENCE_NO
Datatype	String
Description	Indicates the Request Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CARDNO

Attribute	**Description**
Name	CARDNO
Datatype	String
Description	Indicates the Card Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 19

TOP

CUST_NO

Attribute	**Description**
Name	CUST_NO
Datatype	String
Description	Indicates the Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

CARD_PRODUCT

Attribute	Description	
Name	CARD_PRODUCT	
Datatype	String	
Description	Indicates the Product code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

PRIMARY_CARD

Attribute	Description	
Name	PRIMARY_CARD	
Datatype	String	
Description	Indicates the Primary Card Number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

NAME_ON_CARD

Attribute	Description	
Name	NAME_ON_CARD	
Datatype	String	
Description	Indicates the Name on Card.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

OWNER_ID_NO

Attribute	Description	
Name	OWNER_ID_NO	
Datatype	String	
Description	Indicates the Owner ID.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

TOP

CARD_ISSUED_DT

Attribute	Description
Name	CARD_ISSUED_DT
Datatype	Date
Description	Indicates the Card Issue Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CARD_EXPIRY_DT

Attribute	Description
Name	CARD_EXPIRY_DT
Datatype	Date
Description	Indicates the Card Expiry Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CARD_STATUS

Attribute	Description
Name	CARD_STATUS
Datatype	String
Description	Indicates the Card Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	Indicates the Record Stat.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTH_STAT

Attribute	Description
Name	AUTH_STAT
Datatype	String
Description	Indicates the Auth Stat.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CARD_BIN

Attribute	**Description**
Name	CARD_BIN
Datatype	String
Description	Indicates the Card Bin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CUST_AC_NO

Attribute	**Description**
Name	CUST_AC_NO
Datatype	String
Description	Indicates the Customer Account Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Extsys-Ws-Master

Attribute	**Description**
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

KEYID

Attribute	**Description**
Name	KEYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 200

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Stvws-Cust-Trntax

Attribute	Description
Name	Stvws-Cust-Trntax
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Sttms-Cust-Trn-Tax

Attribute	Description
Name	Sttms-Cust-Trn-Tax
Datatype	

Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

TAX_SCHEME

Attribute	Description	
Name	TAX_SCHEME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

TXN_TAX_EXEMPTED

Attribute	Description	
Name	TXN_TAX_EXEMPTED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TXN_TAX_EXEMPTION_PERCENT

Attribute	Description	
Name	TXN_TAX_EXEMPTION_PERCENT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXN_TAX_EFF_DATE

Attribute	Description	
Name	TXN_TAX_EFF_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXN_TAX_EXEMPTION_REASON

Attribute	Description
Name	TXN_TAX_EXEMPTION_REASON
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

2.15.3.ST-CreateCustomer-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Customer-Full*
    - *NAME*
    - *ADDRLN1*
    - *ADDRLN3*
    - *ADDRLN2*
    - *ADDRLN4*
    - *SWIFTCD*
    - *FAX*
    - *COUNTRY*
    - *NLTY*
    - *LANG*
    - *EXPCNTRY*
    - *UIDNAME*
    - *UIDVAL*
    - *LOC*
    - *FROZEN*
    - *DEAD*
    - *WHRUNKN*
    - *GRPCD*

CHGGRP
CUSTCLGGRP
TAXGROUP
CCATEG
EXPCAT
CUSTCLASSFN
FXNETTCUST
XREF
MEDIA
SSN
CIFSTAT
CIFSTATSNC
MAILRSREQD
CLSPARTICIPANT
CRMCUST
ISSUCUST
TRSRYCUST
CUSTNO
SNAME
LBRN
CTYPE
FULLNAME
AMLCUSTGRP
AMLREQD
FLGUTLTYPRVDR
UTLTYPRVDRID
CHKDIGITVALREQD
ALGID
CONSTAXCERTRQD
INDTAXCERTRQD
HOACNO
RISKPRFL
DRCAT
FTACCASOF
UDF1
UDF2
UDF3
UDF4
UDF5
UDFLBL1
UDFLBL2
UDFLBL3
UDFLBL4
UDFLBL5

FXCUSTCLRILIM
OVRLIM
FX_CLEAN_RISK
CRRATE
REVDT
LIMCCY
SECCUSTCLRILIM
SECCLRILIM
SECCUSTPSRILIM
SECPSRILIM
CUSTUNADV
RISKCATEG
CLSCCYALLWD
NETTREQD
LIABUNADV
MT920
RELPRICING
FLGJOINT
KYCSTAT
SSTAFF
UPTYPE
KYC_REFNO
JOINT_VENTURE
PRIVATE_CUSTOMER
LC_COLLAT_PCT
ISELCMCUST
ELCMCUSTNO
ALT_CUST_NO
DETERIORATION_DATE
CHQ_TAX_EXEMPT_1
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Custpersonal
- *TITLE*
- *FSTNAME*
- *MIDNAME*
- *LSTNAME*
- *DOB*
- *GUARDIAN*

MINOR
SEX
NATIONID
PPTNO
PPTISSDT
PPTEXPDT
DADD1
DADD2
DADD3
TEL
FAX
EMAIL
PADD1
PADD2
PADD3
DCNTRY
PCNTRY
RESSTATUS
CUSTPREFIX1
CUSTPREFIX2
MOBNUM
SBMTAGEPROOF
CUST_COMM_MODE
LAST_UPD_DT
Custdomestic
- *EDUSTAT*
- *MARITALSTAT*
- *SPNAME*
- *SPEMPSTATUS*
- *DEPCHILD*
- *DEPOTH*
- *ACCOMODATE*
- *CUSTNO*

Custprof
- *EMPSTAT*
- *EMPTENURE*
- *RETIREAGE*
- *PREVDESIG*
- *PREVEMP*
- *CURRDESIG*
- *CURREMP*
- *ADD1*
- *ADD2*
- *ADD3*

TEL
TELEX
FAX
EMAIL
SALARY
OTHER1
RENT
INSURANCE
LOANPMNT
OTHEXP
HOUSEVAL
CRCARD
CNTY
AMTCCY1
CUSTNO
EMPLOYER_DESC
EMP_DESC
Custcorp
CORPNAME
NATIONID
REGADD1
REGADD2
REGADD3
INCORPDT
CAPITAL
NETWORTH
INCORPCNTRY
REGCNTRY
AMTCCY
CORPDESC
CUSTNO
Custcorpdir
DIRNAME
TEL
NADDR1
NADDR2
NADDR3
NADDR4
ADDR1
ADDRS2
ADDRS3
COUNTRY
TAXID
MOBNO

EMAIL

Issuerdet

OVERLIMIT

CUSTNO

OVERLMTCCY

Issuerlmts

CLTRLTYP

LMTAMT

LMTCCY

ISSID

Custgrp

GRPNO

RELATION

Custshhold

SHHOLDID

SHHOLDPCT

SHRHLDRNAME

Clsccyrest

CCY

DESC

Bic

ACC

BICCD

Linkedac

VRFD

LINKEDACCNO

LINKEDACCIBAN

LINKEDACCBIC

JointVenture

PARTYID

PARTYRATIO

PARTYNAME

Custdoc-Chklist

DOCUMENT_TYPE

CHECKED

Doctype-Remarks

REMARK1

REMARK2

REMARK3

REMARK4

REMARK5

REMARK6

REMARK7

REMARK8

- *REMARK9*
- *REMARK10*

Custmis

- *MISGRP*
- *CUST*
- *BRNCD*
- *Custchnglog*
  - *MISCLS*
  - *TXNDT*
  - *OLDMISCD*
  - *NWMISCD*
- *Baltrnsfrlog*
  - *BRN*
  - *PRDCD*
  - *FINYR*
  - *TXNDT*
  - *GLCODE*
  - *MISCLS*
  - *OLDMISCD*
  - *NWMISCD*
  - *TRNIND*
  - *CCY*
  - *AMT*
  - *XRATE*
- *Dfltcd*
  - *MISCLS*
  - *MISCD*
- *Dfltcda*
  - *MISCLS*
  - *MISCD*
- *Custloghead*

Jointcustomer

- *CUSTNO*
- *Custjoint*
  - *CUSTPREFIX*
  - *FRSTNAME*
  - *MIDNAME*
  - *LASTNAME*
  - *DOB*
  - *SEX*
  - *PPNO*
  - *PPTISSDT*
  - *PPTEXPDT*
  - *ADD1*

ADD2

ADD3

TEL

EMAIL

SSN

DECEASED

RESISTAT

Cust-Acc-Det

CUSTNO

Diary-Mst

INSTRNO

UNTTYP

UNTVAL

BRN

INSTR

INSTRTYPE

EXEDAYS

EXEMONTHS

EXEYEARS

MNTHENDFLG

HLDRULE

FRSTDUEDT

NXTDUEDT

NXTEXEDT

CONDELEM

OPRTR

CONDVAL

ACCOFCR

SPLINSTRTYP

EXPDT

SPLINSTR

Custaccdet

CUSTNO

BRNCD

Relationship-Linkage

CUSTOMER

RELATIONSHIP

INHERIT

DESCP

Custacdetail

CUSTNO

CUSTTEXT

SEQNO

CUSTNO

TDESC

UDFDETAILS

FLDNAM

FLDVAL

Sttms-Debit

BRANCH_CODE

CUST_NO

ACTNO

Sttms-Detail

BRANCH_CODE

REQUEST_REFERENCE_NO

CARDNO

CUST_NO

CARD_PRODUCT

PRIMARY_CARD

NAME_ON_CARD

OWNER_ID_NO

CARD_ISSUED_DT

CARD_EXPIRY_DT

CARD_STATUS

RECORD_STAT

AUTH_STAT

CARD_BIN

CUST_AC_NO

Extsys-Ws-Master

Extsys-Ws-Details

EXTWSRESP

USERREMARKS

Stvws-Cust-Trntax

CUSTOMER_NO

Sttms-Cust-Trn-Tax

TAX_SCHEME

TXN_TAX_EXEMPTED

TXN_TAX_EXEMPTION_PERCENT

TXN_TAX_EFF_DATE

TXN_TAX_EXEMPTION_REASON

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Customer-Full

Attribute	Description

Name	Customer-Full
Datatype	
Description	

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

ADDRLN1

Attribute	Description	
Name	ADDRLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN3

Attribute	Description	
Name	ADDRLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN2

Attribute	Description	
Name	ADDRLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN4

Attribute	Description

Name	ADDRLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SWIFTCD

Attribute	**Description**
Name	SWIFTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FAX

Attribute	**Description**
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRY

Attribute	**Description**
Name	COUNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NLTY

Attribute	**Description**
Name	NLTY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXPCNTRY

Attribute	Description
Name	EXPCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

UIDNAME

Attribute	Description
Name	UIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

UIDVAL

Attribute	Description
Name	UIDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

LOC

Attribute	Description	
Name	LOC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

FROZEN

Attribute	Description	
Name	FROZEN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

DEAD

Attribute	Description	
Name	DEAD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

WHRUNKN

Attribute	Description	
Name	WHRUNKN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CHGGRP

Attribute	Description
Name	CHGGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CUSTCLGGRP

Attribute	Description
Name	CUSTCLGGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAXGROUP

Attribute	Description
Name	TAXGROUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CCATEG

Attribute	Description
Name	CCATEG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

CUSTCLASSFN

Attribute	Description
Name	CUSTCLASSFN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

FXNETTCUST

Attribute	Description
Name	FXNETTCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

XREF

Attribute	Description
Name	XREF

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MEDIA

Attribute	**Description**
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SSN

Attribute	**Description**
Name	SSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

CIFSTAT

Attribute	**Description**
Name	CIFSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CIFSTATSNC

Attribute	**Description**
Name	CIFSTATSNC
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MAILRSREQD

Attribute	Description
Name	MAILRSREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CLSPARTICIPANT

Attribute	Description
Name	CLSPARTICIPANT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CRMCUST

Attribute	Description
Name	CRMCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ISSUCUST

Attribute	Description
Name	ISSUCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TRSRYCUST

Attribute	Description
Name	TRSRYCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SNAME

Attribute	Description
Name	SNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LBRN

Attribute	Description
Name	LBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CTYPE

Attribute	Description
Name	CTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: I,C,B

TOP

FULLNAME

Attribute	Description
Name	FULLNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

AMLCUSTGRP

Attribute	Description
Name	AMLCUSTGRP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

AMLREQD

Attribute	Description
Name	AMLREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

FLGUTLTYPRVDR

Attribute	Description
Name	FLGUTLTYPRVDR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UTLTYPRVDRID

Attribute	**Description**
Name	UTLTYPRVDRID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKDIGITVALREQD

Attribute	**Description**
Name	CHKDIGITVALREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALGID

Attribute	**Description**
Name	ALGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CONSTAXCERTRQD

Attribute	**Description**
Name	CONSTAXCERTRQD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INDTAXCERTRQD

Attribute	Description	
Name	INDTAXCERTRQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

HOACNO

Attribute	Description	
Name	HOACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RISKPRFL

Attribute	Description	
Name	RISKPRFL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

DRCAT

Attribute	Description	
Name	DRCAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FTACCASOF

Attribute	Description	
Name	FTACCASOF	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,M,D

TOP

UDF1

Attribute	Description	
Name	UDF1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

TOP

UDF2

Attribute	Description	
Name	UDF2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

TOP

UDF3

Attribute	Description	
Name	UDF3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

UDF4

Attribute	Description
Name	UDF4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

UDF5

Attribute	Description
Name	UDF5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL1

Attribute	Description
Name	UDFLBL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL2

Attribute	Description
Name	UDFLBL2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL3

Attribute	Description
Name	UDFLBL3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDFLBL4

Attribute	Description
Name	UDFLBL4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDFLBL5

Attribute	Description
Name	UDFLBL5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

FXCUSTCLRILIM

Attribute	Description
Name	FXCUSTCLRILIM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

OVRLIM

Attribute	Description
Name	OVRLIM
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

FX_CLEAN_RISK

Attribute	Description
Name	FX_CLEAN_RISK
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CRRATE

Attribute	Description
Name	CRRATE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

REVDT

Attribute	Description
Name	REVDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIMCCY

Attribute	Description
Name	LIMCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

SECCUSTCLRILIM

Attribute	Description
Name	SECCUSTCLRILIM

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCLRILIM

Attribute	Description
Name	SECCLRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCUSTPSRILIM

Attribute	Description
Name	SECCUSTPSRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECPSRILIM

Attribute	Description
Name	SECPSRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTUNADV

Attribute	Description
Name	CUSTUNADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RISKCATEG

Attribute	Description
Name	RISKCATEG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CLSCCYALLWD

Attribute	**Description**
Name	CLSCCYALLWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

NETTREQD

Attribute	**Description**
Name	NETTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIABUNADV

Attribute	**Description**
Name	LIABUNADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MT920

Attribute	**Description**
Name	MT920
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RELPRICING

Attribute	Description	
Name	RELPRICING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

FLGJOINT

Attribute	Description	
Name	FLGJOINT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

KYCSTAT

Attribute	Description	
Name	KYCSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	V,N,F

TOP

SSTAFF

Attribute	Description	
Name	SSTAFF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UPTYPE

Attribute	**Description**
Name	UPTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

KYC_REFNO

Attribute	**Description**
Name	KYC_REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

JOINT_VENTURE

Attribute	**Description**
Name	JOINT_VENTURE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIVATE_CUSTOMER

Attribute	**Description**
Name	PRIVATE_CUSTOMER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LC_COLLAT_PCT

Attribute	Description
Name	LC_COLLAT_PCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISELCMCUST

Attribute	Description
Name	ISELCMCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ELCMCUSTNO

Attribute	Description
Name	ELCMCUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ALT_CUST_NO

Attribute	Description
Name	ALT_CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DETERIORATION_DATE

Attribute	Description
Name	DETERIORATION_DATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHQ_TAX_EXEMPT_1

Attribute	Description
Name	CHQ_TAX_EXEMPT_1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

Custpersonal

Attribute	Description
Name	Custpersonal
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TITLE

Attribute	Description
Name	TITLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FSTNAME

Attribute	Description
Name	FSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MIDNAME

Attribute	Description
Name	MIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LSTNAME

Attribute	Description
Name	LSTNAME
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

GUARDIAN

Attribute	Description
Name	GUARDIAN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

MINOR

Attribute	Description
Name	MINOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

SEX

Attribute	Description
Name	SEX
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,F

TOP

NATIONID

Attribute	Description
Name	NATIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PPTNO

Attribute	Description
Name	PPTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PPTISSDT

Attribute	Description
Name	PPTISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PPTEXPDT

Attribute	Description
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DADD1

Attribute	Description
Name	DADD1
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DADD2

Attribute	Description
Name	DADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DADD3

Attribute	Description
Name	DADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FAX

Attribute	Description
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

PADD1

Attribute	Description
Name	PADD1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

PADD2

Attribute	Description
Name	PADD2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

PADD3

Attribute	Description
Name	PADD3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

DCNTRY

Attribute	Description
Name	DCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PCNTRY

Attribute	Description
Name	PCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RESSTATUS

Attribute	Description
Name	RESSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / R,N

TOP

CUSTPREFIX1

Attribute	Description
Name	CUSTPREFIX1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

CUSTPREFIX2

Attribute	Description
Name	CUSTPREFIX2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

MOBNUM

Attribute	Description
Name	MOBNUM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SBMTAGEPROOF

Attribute	Description
Name	SBMTAGEPROOF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,P,V

TOP

CUST_COMM_MODE

Attribute	Description
Name	CUST_COMM_MODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,E

TOP

LAST_UPD_DT

Attribute	Description
Name	LAST_UPD_DT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Custdomestic

Attribute	Description
Name	Custdomestic
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

EDUSTAT

Attribute	Description
Name	EDUSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,U,G,P

TOP

MARITALSTAT

Attribute	Description
Name	MARITALSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: S,M,D,R,P,E,T

TOP

SPNAME

Attribute	Description
Name	SPNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SPEMPSTATUS

Attribute	Description
Name	SPEMPSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,T,S,U,R,P,N,O

TOP

DEPCHILD

Attribute	Description
Name	DEPCHILD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEPOTH

Attribute	Description
Name	DEPOTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOMODATE

Attribute	Description
Name	ACCOMODATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,O

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	9

TOP

Custprof

Attribute	Description	
Name	Custprof	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EMPSTAT

Attribute	Description	
Name	EMPSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

EMPTENURE

Attribute	Description	
Name	EMPTENURE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RETIREAGE

Attribute	Description	
Name	RETIREAGE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PREVDESIG

Attribute	Description
Name	PREVDESIG
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PREVEMP

Attribute	Description	
Name	PREVEMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CURRDESIG

Attribute	Description	
Name	CURRDESIG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CURREMP

Attribute	Description	
Name	CURREMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADD1

Attribute	Description	
Name	ADD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ADD2

Attribute	Description	
Name	ADD2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ADD3

Attribute	Description	
Name	ADD3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

TEL

Attribute	Description	
Name	TEL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

TELEX

Attribute	Description	
Name	TELEX	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

FAX

Attribute	Description
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

SALARY

Attribute	Description
Name	SALARY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHER1

Attribute	Description
Name	OTHER1
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RENT

Attribute	Description
Name	RENT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

INSURANCE

Attribute	Description
Name	INSURANCE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LOANPMNT

Attribute	Description
Name	LOANPMNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

OTHEXP

Attribute	Description
Name	OTHEXP
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

HOUSEVAL

Attribute	Description
Name	HOUSEVAL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CRCARD

Attribute	Description
Name	CRCARD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMTCCY1

Attribute	Description
Name	AMTCCY1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

EMPLOYER_DESC

Attribute	Description
Name	EMPLOYER_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

EMP_DESC

Attribute	Description
Name	EMP_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

Custcorp

Attribute	Description
Name	Custcorp
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CORPNAME

Attribute	Description
Name	CORPNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

NATIONID

Attribute	Description
Name	NATIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REGADD1

Attribute	Description
Name	REGADD1
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REGADD2

Attribute	Description
Name	REGADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REGADD3

Attribute	Description
Name	REGADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INCORPDT

Attribute	Description
Name	INCORPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CAPITAL

Attribute	Description
Name	CAPITAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NETWORTH

Attribute	Description
Name	NETWORTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INCORPCNTRY

Attribute	Description
Name	INCORPCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REGCNTRY

Attribute	Description
Name	REGCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CORPDESC

Attribute	Description
Name	CORPDESC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Custcorpdir

Attribute	Description
Name	Custcorpdir
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DIRNAME

Attribute	Description
Name	DIRNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR1

Attribute	Description
Name	NADDR1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR2

Attribute	Description
Name	NADDR2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR3

Attribute	Description
Name	NADDR3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR4

Attribute	Description
Name	NADDR4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRY

Attribute	Description
Name	COUNTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

TAXID

Attribute	Description
Name	TAXID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MOBNO

Attribute	**Description**
Name	MOBNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EMAIL

Attribute	**Description**
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Issuerdet

Attribute	**Description**
Name	Issuerdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OVERLIMIT

Attribute	**Description**
Name	OVERLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OVERLMTCCY

Attribute	Description
Name	OVERLMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Issuerlmts

Attribute	Description
Name	Issuerlmts
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CLTRLTYP

Attribute	Description
Name	CLTRLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 70

TOP

LMTAMT

Attribute	Description
Name	LMTAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LMTCCY

Attribute	**Description**
Name	LMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ISSID

Attribute	**Description**
Name	ISSID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Custgrp

Attribute	**Description**
Name	Custgrp
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

GRPNO

Attribute	**Description**
Name	GRPNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RELATION

Attribute	Description
Name	RELATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Custshhold

Attribute	Description
Name	Custshhold
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SHHOLDID

Attribute	Description
Name	SHHOLDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SHHOLDPCT

Attribute	Description
Name	SHHOLDPCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHRHLDRNAME

Attribute	Description
Name	SHRHLDRNAME
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Clsccyrest

Attribute	Description
Name	Clsccyrest
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Bic

Attribute	Description
Name	Bic
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BICCD

Attribute	Description
Name	BICCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

Linkedac

Attribute	Description
Name	Linkedac
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

VRFD

Attribute	Description
Name	VRFD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LINKEDACCNO

Attribute	Description

Name	LINKEDACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LINKEDACCIBAN

Attribute	**Description**
Name	LINKEDACCIBAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LINKEDACCBIC

Attribute	**Description**
Name	LINKEDACCBIC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

JointVenture

Attribute	**Description**
Name	JointVenture
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PARTYID

Attribute	**Description**
Name	PARTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	9

TOP

PARTYRATIO

Attribute	Description
Name	PARTYRATIO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 1

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

Custdoc-Chklist

Attribute	Description
Name	Custdoc-Chklist
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

CHECKED

Attribute	Description

Name	CHECKED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Doctype-Remarks

Attribute	**Description**
Name	Doctype-Remarks
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARK1

Attribute	**Description**
Name	REMARK1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK2

Attribute	**Description**
Name	REMARK2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK3

Attribute	**Description**
Name	REMARK3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	225

TOP

REMARK4

Attribute	Description
Name	REMARK4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK5

Attribute	Description
Name	REMARK5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK6

Attribute	Description
Name	REMARK6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK7

Attribute	Description
Name	REMARK7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK8

Attribute	Description
Name	REMARK8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK9

Attribute	Description
Name	REMARK9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK10

Attribute	Description
Name	REMARK10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

Custmis

Attribute	Description
Name	Custmis
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP

Datatype	String
Description	Indicates Management Information System Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CUST

Attribute	Description
Name	CUST
Datatype	String
Description	Indicates the Customer.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Custchnglog

Attribute	Description
Name	Custchnglog
Datatype	
Description	Indicates the Customer Change Log.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	9

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	Attribute: minOccurs — Description: 1

TOP

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	Indicates the Old MIS Code.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	Indicates the New MIS Code.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

Baltrnsfrlog

Attribute	Description
Name	Baltrnsfrlog
Datatype	
Description	Indicates the Balance Transfer Log.
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

BRN

Attribute	Description

Name	BRN
Datatype	String
Description	Indicates the Branch Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDCD

Attribute	**Description**
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	**Description**
Name	FINYR
Datatype	String
Description	Indicates the Financial Year.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNDT

Attribute	**Description**
Name	TXNDT
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

GLCODE

Attribute	**Description**
Name	GLCODE
Datatype	String
Description	Indicates the GL Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 9

TOP

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	Indicates the Old MIS Code.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	Indicates the New MIS Code.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

TRNIND

Attribute	Description
Name	TRNIND
Datatype	String
Description	Indicates Transfer Identification Number.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Dfltcd

Attribute	Description
Name	Dfltcd
Datatype	
Description	Indicates the Customer MIS Classes.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MISCD

Attribute	Description	
Name	MISCD	
Datatype	String	
Description	Indicates the MIS Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Dfltcda

Attribute	Description	
Name	Dfltcda	
Datatype		
Description	Indicates the Composite MIS Classes.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MISCLS

Attribute	Description	
Name	MISCLS	
Datatype	String	
Description	Indicates the MIS Class.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MISCD

Attribute	Description	
Name	MISCD	
Datatype	String	
Description	Indicates the MIS Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Custloghead

Attribute	Description
Name	Custloghead
Datatype	
Description	Indicates the Customer Log Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Jointcustomer

Attribute	Description
Name	Jointcustomer
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Custjoint

Attribute	Description
Name	Custjoint
Datatype	
Description	Indicates Customer Joint.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTPREFIX

Attribute	Description
Name	CUSTPREFIX
Datatype	String
Description	Indicates the Customer Prefix.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FRSTNAME

Attribute	Description
Name	FRSTNAME
Datatype	String
Description	Indicates the First Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MIDNAME

Attribute	Description
Name	MIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LASTNAME

Attribute	Description
Name	LASTNAME
Datatype	String
Description	Indicates the Last Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SEX

Attribute	Description
Name	SEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,F

TOP

PPNO

Attribute	Description
Name	PPNO
Datatype	String
Description	Indicates Passport Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PPTISSDT

Attribute	Description
Name	PPTISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PPTEXPDT

Attribute	Description
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADD3

Attribute	Description
Name	ADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255

TOP

SSN

Attribute	Description	
Name	SSN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	11

TOP

DECEASED

Attribute	Description	
Name	DECEASED	
Datatype	String	
Description	Indicates whether Deceased or not. The value should be either D or N.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,N

TOP

RESISTAT

Attribute	Description	
Name	RESISTAT	
Datatype	String	
Description	Indicates the Resistant Status. The value could be either R or N.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	R,N

TOP

Cust-Acc-Det

Attribute	Description	
Name	Cust-Acc-Det	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

Diary-Mst

Attribute	Description
Name	Diary-Mst
Datatype	
Description	Indicates Diary Master.
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	Indicates Instrument Number
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 16

TOP

UNTTYP

Attribute	Description
Name	UNTTYP
Datatype	String
Description	Indicates Unit Type
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

UNTVAL

Attribute	Description
Name	UNTVAL
Datatype	String

Description	Indicates Unit Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BRN

Attribute	**Description**
Name	BRN
Datatype	String
Description	Indicates the Branch Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INSTR

Attribute	**Description**
Name	INSTR
Datatype	String
Description	Indicates Instructions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

INSTRTYPE

Attribute	**Description**
Name	INSTRTYPE
Datatype	String
Description	Indicates Instruction Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

EXEDAYS

Attribute	**Description**
Name	EXEDAYS
Datatype	Number
Description	Indicates Execution Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXEMONTHS

Attribute	Description
Name	EXEMONTHS
Datatype	Number
Description	Indicates Execution Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXEYEARS

Attribute	Description
Name	EXEYEARS
Datatype	Number
Description	Indicates Execution Years
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MNTHENDFLG

Attribute	Description
Name	MNTHENDFLG
Datatype	String
Description	Indicates Month End Flag. Flag Can be either Y or N.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HLDRULE

Attribute	Description
Name	HLDRULE
Datatype	String
Description	Indicates Holiday Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRSTDUEDT

Attribute	Description
Name	FRSTDUEDT
Datatype	Date
Description	Indicates First Due Date.

Attributes	Attribute	Description
	minOccurs	0

TOP

NXTDUEDT

Attribute	Description
Name	NXTDUEDT
Datatype	Date
Description	Indicates Next Due Date
Attributes	Attribute: minOccurs; Description: 0

TOP

NXTEXEDT

Attribute	Description
Name	NXTEXEDT
Datatype	Date
Description	Indicates Next Execution Date.
Attributes	Attribute: minOccurs; Description: 0

TOP

CONDELEM

Attribute	Description
Name	CONDELEM
Datatype	String
Description	Indicates Condition Elements.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 20

TOP

OPRTR

Attribute	Description
Name	OPRTR
Datatype	String
Description	Indicates Operator.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 2

TOP

CONDVAL

Attribute	Description
Name	CONDVAL

Datatype	Number
Description	Indicates Condition Value.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOFCR

Attribute	Description
Name	ACCOFCR
Datatype	String
Description	Indicates Account Officer.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPLINSTRTYP

Attribute	Description
Name	SPLINSTRTYP
Datatype	String
Description	Indicates Special Instruction Type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	Indicates Expiry Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPLINSTR

Attribute	Description
Name	SPLINSTR
Datatype	String
Description	Indicates Special Instructions.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Custaccdet

Attribute	Description
Name	Custaccdet
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkage details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String

Description	Indicates the customer
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RELATIONSHIP

Attribute	**Description**
Name	RELATIONSHIP
Datatype	String
Description	Indicate relations
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

INHERIT

Attribute	**Description**
Name	INHERIT
Datatype	String
Description	Indicate,include relationship Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DESCP

Attribute	**Description**
Name	DESCP
Datatype	String
Description	Indicates description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Custacdetail

Attribute	**Description**
Name	Custacdetail
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

CUSTTEXT

Attribute	Description
Name	CUSTTEXT
Datatype	
Description	Include customer details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	Indicates sequence number
Attributes	Attribute: minOccurs — Description: 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

TDESC

Attribute	Description

Name	TDESC
Datatype	String
Description	Indicate text description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

Sttms-Debit

Attribute	**Description**
Name	Sttms-Debit
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	Indicates the Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACTNO

Attribute	Description
Name	ACTNO
Datatype	String
Description	Indicates the Account Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Sttms-Detail

Attribute	Description
Name	Sttms-Detail
Datatype	
Description	Indicates Customer Details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description

Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REQUEST_REFERENCE_NO

Attribute	**Description**
Name	REQUEST_REFERENCE_NO
Datatype	String
Description	Indicates the Request Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CARDNO

Attribute	**Description**
Name	CARDNO
Datatype	String
Description	Indicates the Card Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 19

TOP

CUST_NO

Attribute	**Description**
Name	CUST_NO
Datatype	String
Description	Indicates the Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CARD_PRODUCT

Attribute	**Description**
Name	CARD_PRODUCT
Datatype	String
Description	Indicates the Product code.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRIMARY_CARD

Attribute	Description	
Name	PRIMARY_CARD	
Datatype	String	
Description	Indicates the Primary Card Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NAME_ON_CARD

Attribute	Description	
Name	NAME_ON_CARD	
Datatype	String	
Description	Indicates the Name on Card.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

OWNER_ID_NO

Attribute	Description	
Name	OWNER_ID_NO	
Datatype	String	
Description	Indicates the Owner ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

CARD_ISSUED_DT

Attribute	Description	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Indicates the Card Issue Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CARD_EXPIRY_DT

Attribute	Description
Name	CARD_EXPIRY_DT
Datatype	Date
Description	Indicates the Card Expiry Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CARD_STATUS

Attribute	Description
Name	CARD_STATUS
Datatype	String
Description	Indicates the Card Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	Indicates the Record Stat.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTH_STAT

Attribute	Description
Name	AUTH_STAT
Datatype	String
Description	Indicates the Auth Stat.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CARD_BIN

Attribute	Description
Name	CARD_BIN

Datatype	String
Description	Indicates the Card Bin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CUST_AC_NO

Attribute	**Description**
Name	CUST_AC_NO
Datatype	String
Description	Indicates the Customer Account Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Extsys-Ws-Master

Attribute	**Description**
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	**Description**
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXTWSRESP

Attribute	**Description**
Name	EXTWSRESP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

Stvws-Cust-Trntax

Attribute	Description
Name	Stvws-Cust-Trntax
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Sttms-Cust-Trn-Tax

Attribute	Description
Name	Sttms-Cust-Trn-Tax
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TAX_SCHEME

Attribute	Description
Name	TAX_SCHEME
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

TXN_TAX_EXEMPTED

Attribute	**Description**
Name	TXN_TAX_EXEMPTED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TXN_TAX_EXEMPTION_PERCENT

Attribute	**Description**
Name	TXN_TAX_EXEMPTION_PERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXN_TAX_EFF_DATE

Attribute	**Description**
Name	TXN_TAX_EFF_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXN_TAX_EXEMPTION_REASON

Attribute	**Description**
Name	TXN_TAX_EXEMPTION_REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.15.4.ST-CreateCustomer-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Customer-PK*
      - *CUSTNO*
    - *Customer-IO*
      - *NAME*
      - *ADDRLN1*
      - *ADDRLN3*
      - *ADDRLN2*
      - *ADDRLN4*
      - *SWIFTCD*
      - *FAX*
      - *COUNTRY*
      - *NLTY*
      - *LANG*
      - *EXPCNTRY*
      - *UIDNAME*
      - *UIDVAL*
      - *LOC*
      - *FROZEN*

DEAD
WHRUNKN
GRPCD
CHGGRP
CUSTCLGGRP
TAXGROUP
CCATEG
EXPCAT
CUSTCLASSFN
FXNETTCUST
XREF
MEDIA
SSN
CIFSTAT
CIFSTATSNC
MAILRSREQD
CLSPARTICIPANT
CRMCUST
ISSUCUST
TRSRYCUST
CUSTNO
SNAME
CTYPE
FULLNAME
AMLCUSTGRP
AMLREQD
FLGUTLTYPRVDR
UTLTYPRVDRID
CHKDIGITVALREQD
ALGID
CONSTAXCERTRQD
INDTAXCERTRQD
HOACNO
RISKPRFL
DRCAT
FTACCASOF
UDF1
UDF2
UDF3
UDF4
UDF5
FXCUSTCLRILIM
OVRLIM
FX_CLEAN_RISK

CRRATE
REVDT
LIMCCY
SECCUSTCLRILIM
SECCLRILIM
SECCUSTPSRILIM
SECPSRILIM
CUSTUNADV
RISKCATEG
CLSCCYALLWD
NETTREQD
LIABUNADV
MT920
RELPRICING
FLGJOINT
KYCSTAT
SSTAFF
UPTYPE
KYC_REFNO
JOINT_VENTURE
PRIVATE_CUSTOMER
LC_COLLAT_PCT
ISELCMCUST
ELCMCUSTNO
ALT_CUST_NO
DETERIORATION_DATE
CHQ_TAX_EXEMPT_1
Custpersonal
- *TITLE*
- *FSTNAME*
- *MIDNAME*
- *LSTNAME*
- *DOB*
- *GUARDIAN*
- *MINOR*
- *SEX*
- *NATIONID*
- *PPTNO*
- *PPTISSDT*
- *PPTEXPDT*
- *DADD1*
- *DADD2*
- *DADD3*
- *TEL*

FAX
EMAIL
PADD1
PADD2
PADD3
DCNTRY
PCNTRY
RESSTATUS
CUSTPREFIX1
CUSTPREFIX2
MOBNUM
SBMTAGEPROOF
CUST_COMM_MODE
Custdomestic
- *EDUSTAT*
- *MARITALSTAT*
- *SPNAME*
- *SPEMPSTATUS*
- *DEPCHILD*
- *DEPOTH*
- *ACCOMODATE*
- *CUSTNO*

Custprof
- *EMPSTAT*
- *EMPTENURE*
- *RETIREAGE*
- *PREVDESIG*
- *PREVEMP*
- *CURRDESIG*
- *CURREMP*
- *ADD1*
- *ADD2*
- *ADD3*
- *TEL*
- *TELEX*
- *FAX*
- *EMAIL*
- *SALARY*
- *OTHER1*
- *RENT*
- *INSURANCE*
- *LOANPMNT*
- *OTHEXP*
- *HOUSEVAL*

CRCARD
CNTY
AMTCCY1
CUSTNO
EMPLOYER_DESC
EMP_DESC
Custcorp
CORPNAME
NATIONID
REGADD1
REGADD2
REGADD3
INCORPDT
CAPITAL
NETWORTH
INCORPCNTRY
REGCNTRY
AMTCCY
CORPDESC
CUSTNO
Custcorpdir
DIRNAME
TEL
NADDR1
NADDR2
NADDR3
NADDR4
ADDR1
ADDRS2
ADDRS3
TAXID
EMAIL
Issuerdet
OVERLIMIT
CUSTNO
OVERLMTCCY
Issuerlmts
CLTRLTYP
LMTAMT
LMTCCY
ISSID
Custgrp
GRPNO
RELATION

Custshhold

SHHOLDID

SHHOLDPCT

SHRHLDRNAME

Clsccyrest

CCY

DESC

Bic

ACC

BICCD

Linkedac

VRFD

LINKEDACCNO

LINKEDACCIBAN

LINKEDACCBIC

JointVenture

PARTYID

PARTYRATIO

Custdoc-Chklist

DOCUMENT_TYPE

CHECKED

Doctype-Remarks

REMARK1

REMARK2

REMARK3

REMARK4

REMARK5

REMARK6

REMARK7

REMARK8

REMARK9

REMARK10

Custmis

MISGRP

CUSTNO

Custchnglog

Baltrnsfrlog

Dfltcd

MISCD

Dfltcda

MISCD

Jointcustomer

CUSTNO

Custjoint

CUSTPREFIX

FRSTNAME

MIDNAME

LASTNAME

DOB

SEX

PPNO

PPTISSDT

PPTEXPDT

ADD1

ADD2

ADD3

TEL

EMAIL

DECEASED

RESISTAT

Cust-Acc-Det

CUSTNO

Diary-Mst

INSTRNO

UNTTYP

UNTVAL

BRN

INSTR

INSTRTYPE

EXEDAYS

EXEMONTHS

EXEYEARS

MNTHENDFLG

HLDRULE

FRSTDUEDT

NXTDUEDT

NXTEXEDT

CONDELEM

OPRTR

CONDVAL

ACCOFCR

SPLINSTRTYP

EXPDT

SPLINSTR

Custaccdet

CUSTNO

Relationship-Linkage

CUSTOMER

RELATIONSHIP

INHERIT

DESCP

Custacdetail

CUSTNO

CUSTTEXT

SEQNO

CUSTNO

TDESC

UDFDETAILS

FLDNAM

FLDVAL

Sttms-Debit

BRANCH_CODE

CUST_NO

ACTNO

Sttms-Detail

BRANCH_CODE

REQUEST_REFERENCE_NO

CARDNO

CUST_NO

CARD_PRODUCT

PRIMARY_CARD

NAME_ON_CARD

OWNER_ID_NO

CARD_ISSUED_DT

CARD_EXPIRY_DT

CARD_STATUS

RECORD_STAT

AUTH_STAT

CARD_BIN

CUST_AC_NO

Extsys-Ws-Master

KEYID

Extsys-Ws-Details

USERREMARKS

Stvws-Cust-Trntax

CUSTOMER_NO

Sttms-Cust-Trn-Tax

TAX_SCHEME

TXN_TAX_EXEMPTED

TXN_TAX_EXEMPTION_PERCENT

TXN_TAX_EFF_DATE

TXN_TAX_EXEMPTION_REASON

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Customer-PK

Attribute	Description
Name	Customer-PK
Datatype	
Description	

TOP

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Customer-IO

Attribute	Description
Name	Customer-IO
Datatype	
Description	

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

ADDRLN1

Attribute	Description
Name	ADDRLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLN3

Attribute	Description
Name	ADDRLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLN2

Attribute	Description
Name	ADDRLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLN4

Attribute	Description
Name	ADDRLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SWIFTCD

Attribute	Description

Name	SWIFTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FAX

Attribute	**Description**
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRY

Attribute	**Description**
Name	COUNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NLTY

Attribute	**Description**
Name	NLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LANG

Attribute	**Description**
Name	LANG
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

EXPCNTRY

Attribute	Description
Name	EXPCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

UIDNAME

Attribute	Description
Name	UIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

UIDVAL

Attribute	Description
Name	UIDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOC

Attribute	Description
Name	LOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FROZEN

Attribute	**Description**
Name	FROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DEAD

Attribute	**Description**
Name	DEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

WHRUNKN

Attribute	**Description**
Name	WHRUNKN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

GRPCD

Attribute	**Description**
Name	GRPCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHGGRP

Attribute	Description
Name	CHGGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CUSTCLGGRP

Attribute	Description
Name	CUSTCLGGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAXGROUP

Attribute	Description
Name	TAXGROUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CCATEG

Attribute	Description
Name	CCATEG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

CUSTCLASSFN

Attribute	Description
Name	CUSTCLASSFN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

FXNETTCUST

Attribute	Description
Name	FXNETTCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

MEDIA

Attribute	Description
Name	MEDIA

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SSN

Attribute	**Description**
Name	SSN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CIFSTAT

Attribute	**Description**
Name	CIFSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CIFSTATSNC

Attribute	**Description**
Name	CIFSTATSNC
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAILRSREQD

Attribute	**Description**
Name	MAILRSREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

CLSPARTICIPANT

Attribute	Description	
Name	CLSPARTICIPANT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

CRMCUST

Attribute	Description	
Name	CRMCUST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

ISSUCUST

Attribute	Description	
Name	ISSUCUST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

TRSRYCUST

Attribute	Description	
Name	TRSRYCUST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

SNAME

Attribute	Description
Name	SNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 20

TOP

CTYPE

Attribute	Description
Name	CTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: I,C,B

TOP

FULLNAME

Attribute	Description
Name	FULLNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

AMLCUSTGRP

Attribute	Description
Name	AMLCUSTGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

AMLREQD

Attribute	Description
Name	AMLREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FLGUTLTYPRVDR

Attribute	Description
Name	FLGUTLTYPRVDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UTLTYPRVDRID

Attribute	Description
Name	UTLTYPRVDRID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKDIGITVALREQD

Attribute	Description
Name	CHKDIGITVALREQD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALGID

Attribute	Description
Name	ALGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CONSTAXCERTRQD

Attribute	Description
Name	CONSTAXCERTRQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INDTAXCERTRQD

Attribute	Description
Name	INDTAXCERTRQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

HOACNO

Attribute	Description
Name	HOACNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RISKPRFL

Attribute	Description
Name	RISKPRFL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DRCAT

Attribute	Description
Name	DRCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FTACCASOF

Attribute	Description
Name	FTACCASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,M,D

TOP

UDF1

Attribute	Description
Name	UDF1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	150

TOP

UDF2

Attribute	Description	
Name	UDF2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

TOP

UDF3

Attribute	Description	
Name	UDF3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

UDF4

Attribute	Description	
Name	UDF4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

UDF5

Attribute	Description	
Name	UDF5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

TOP

FXCUSTCLRILIM

Attribute	Description
Name	FXCUSTCLRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OVRLIM

Attribute	Description
Name	OVRLIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FX_CLEAN_RISK

Attribute	Description
Name	FX_CLEAN_RISK
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CRRATE

Attribute	Description
Name	CRRATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

REVDT

Attribute	Description
Name	REVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIMCCY

Attribute	Description
Name	LIMCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SECCUSTCLRILIM

Attribute	Description
Name	SECCUSTCLRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCLRILIM

Attribute	Description
Name	SECCLRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCUSTPSRILIM

Attribute	Description
Name	SECCUSTPSRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECPSRILIM

Attribute	Description
Name	SECPSRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTUNADV

Attribute	Description
Name	CUSTUNADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RISKCATEG

Attribute	Description
Name	RISKCATEG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CLSCCYALLWD

Attribute	Description
Name	CLSCCYALLWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

NETTREQD

Attribute	Description
Name	NETTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIABUNADV

Attribute	Description
Name	LIABUNADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MT920

Attribute	Description
Name	MT920
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

RELPRICING

Attribute	Description
Name	RELPRICING
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

FLGJOINT

Attribute	Description
Name	FLGJOINT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

KYCSTAT

Attribute	Description
Name	KYCSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / V,N,F

TOP

SSTAFF

Attribute	**Description**
Name	SSTAFF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UPTYPE

Attribute	**Description**
Name	UPTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

KYC_REFNO

Attribute	**Description**
Name	KYC_REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

JOINT_VENTURE

Attribute	**Description**
Name	JOINT_VENTURE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIVATE_CUSTOMER

Attribute	Description	
Name	PRIVATE_CUSTOMER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LC_COLLAT_PCT

Attribute	Description	
Name	LC_COLLAT_PCT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ISELCMCUST

Attribute	Description	
Name	ISELCMCUST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ELCMCUSTNO

Attribute	Description	
Name	ELCMCUSTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ALT_CUST_NO

Attribute	Description
Name	ALT_CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DETERIORATION_DATE

Attribute	Description
Name	DETERIORATION_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHQ_TAX_EXEMPT_1

Attribute	Description
Name	CHQ_TAX_EXEMPT_1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Custpersonal

Attribute	Description
Name	Custpersonal
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TITLE

Attribute	Description
Name	TITLE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FSTNAME

Attribute	Description
Name	FSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MIDNAME

Attribute	Description
Name	MIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LSTNAME

Attribute	Description
Name	LSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GUARDIAN

Attribute	Description
Name	GUARDIAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MINOR

Attribute	Description
Name	MINOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SEX

Attribute	Description
Name	SEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,F

TOP

NATIONID

Attribute	Description
Name	NATIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PPTNO

Attribute	Description
Name	PPTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

PPTISSDT

Attribute	Description
Name	PPTISSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PPTEXPDT

Attribute	Description
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DADD1

Attribute	Description
Name	DADD1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

DADD2

Attribute	Description
Name	DADD2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

DADD3

Attribute	Description	
Name	DADD3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

TEL

Attribute	Description	
Name	TEL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

FAX

Attribute	Description	
Name	FAX	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

EMAIL

Attribute	Description	
Name	EMAIL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TOP

PADD1

Attribute	Description
Name	PADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PADD2

Attribute	Description
Name	PADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PADD3

Attribute	Description
Name	PADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DCNTRY

Attribute	Description
Name	DCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PCNTRY

Attribute	Description
Name	PCNTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

RESSTATUS

Attribute	Description
Name	RESSTATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: R,N

TOP

CUSTPREFIX1

Attribute	Description
Name	CUSTPREFIX1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

CUSTPREFIX2

Attribute	Description
Name	CUSTPREFIX2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

MOBNUM

Attribute	Description
Name	MOBNUM

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SBMTAGEPROOF

Attribute	Description
Name	SBMTAGEPROOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,P,V

TOP

CUST_COMM_MODE

Attribute	Description
Name	CUST_COMM_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,E

TOP

Custdomestic

Attribute	Description
Name	Custdomestic
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EDUSTAT

Attribute	Description
Name	EDUSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,U,G,P

TOP

MARITALSTAT

Attribute	Description
Name	MARITALSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,M,D,R,P,E,T

TOP

SPNAME

Attribute	Description
Name	SPNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SPEMPSTATUS

Attribute	Description
Name	SPEMPSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,T,S,U,R,P,N,O

TOP

DEPCHILD

Attribute	Description
Name	DEPCHILD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEPOTH

Attribute	Description
Name	DEPOTH

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOMODATE

Attribute	Description
Name	ACCOMODATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,O

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Custprof

Attribute	Description
Name	Custprof
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EMPSTAT

Attribute	Description
Name	EMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

EMPTENURE

Attribute	Description
Name	EMPTENURE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RETIREAGE

Attribute	Description
Name	RETIREAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PREVDESIG

Attribute	Description
Name	PREVDESIG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PREVEMP

Attribute	Description
Name	PREVEMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURRDESIG

Attribute	Description
Name	CURRDESIG
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CURREMP

Attribute	Description
Name	CURREMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADD3

Attribute	Description
Name	ADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TEL

Attribute	**Description**
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TELEX

Attribute	**Description**
Name	TELEX
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FAX

Attribute	**Description**
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EMAIL

Attribute	**Description**
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

SALARY

Attribute	Description	
Name	SALARY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OTHER1

Attribute	Description	
Name	OTHER1	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RENT

Attribute	Description	
Name	RENT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSURANCE

Attribute	Description	
Name	INSURANCE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LOANPMNT

Attribute	Description	
Name	LOANPMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OTHEXP

Attribute	Description
Name	OTHEXP
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HOUSEVAL

Attribute	Description
Name	HOUSEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CRCARD

Attribute	Description
Name	CRCARD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMTCCY1

Attribute	Description
Name	AMTCCY1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

TOP

EMPLOYER_DESC

Attribute	Description	
Name	EMPLOYER_DESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	22

TOP

EMP_DESC

Attribute	Description	
Name	EMP_DESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

TOP

Custcorp

Attribute	Description	
Name	Custcorp	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

CORPNAME

Attribute	Description
Name	CORPNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

NATIONID

Attribute	Description
Name	NATIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REGADD1

Attribute	Description
Name	REGADD1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REGADD2

Attribute	Description
Name	REGADD2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REGADD3

Attribute	Description
Name	REGADD3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INCORPDT

Attribute	**Description**
Name	INCORPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CAPITAL

Attribute	**Description**
Name	CAPITAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NETWORTH

Attribute	**Description**
Name	NETWORTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INCORPCNTRY

Attribute	**Description**
Name	INCORPCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REGCNTRY

Attribute	Description
Name	REGCNTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CORPDESC

Attribute	Description
Name	CORPDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

Custcorpdir

Attribute	Description
Name	Custcorpdir

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DIRNAME

Attribute	**Description**
Name	DIRNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TEL

Attribute	**Description**
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

NADDR1

Attribute	**Description**
Name	NADDR1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

NADDR2

Attribute	**Description**
Name	NADDR2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

NADDR3

Attribute	Description	
Name	NADDR3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

NADDR4

Attribute	Description	
Name	NADDR4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ADDR1

Attribute	Description	
Name	ADDR1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ADDRS2

Attribute	Description	
Name	ADDRS2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

TAXID

Attribute	Description
Name	TAXID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

Issuerdet

Attribute	Description
Name	Issuerdet
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

OVERLIMIT

Attribute	Description
Name	OVERLIMIT

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OVERLMTCCY

Attribute	Description
Name	OVERLMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Issuerlmts

Attribute	Description
Name	Issuerlmts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLTRLTYP

Attribute	Description
Name	CLTRLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 70

TOP

LMTAMT

Attribute	Description
Name	LMTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LMTCCY

Attribute	Description
Name	LMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ISSID

Attribute	Description
Name	ISSID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Custgrp

Attribute	Description
Name	Custgrp
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

GRPNO

Attribute	Description
Name	GRPNO
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RELATION

Attribute	Description
Name	RELATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Custshhold

Attribute	Description
Name	Custshhold
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SHHOLDID

Attribute	Description
Name	SHHOLDID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SHHOLDPCT

Attribute	Description
Name	SHHOLDPCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SHRHLDRNAME

Attribute	Description
Name	SHRHLDRNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

Clsccyrest

Attribute	Description
Name	Clsccyrest
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

Bic

Attribute	Description

Name	Bic
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC

Attribute	**Description**
Name	ACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BICCD

Attribute	**Description**
Name	BICCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

Linkedac

Attribute	**Description**
Name	Linkedac
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VRFD

Attribute	**Description**
Name	VRFD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

LINKEDACCNO

Attribute	Description	
Name	LINKEDACCNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

LINKEDACCIBAN

Attribute	Description	
Name	LINKEDACCIBAN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

LINKEDACCBIC

Attribute	Description	
Name	LINKEDACCBIC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

JointVenture

Attribute	Description	
Name	JointVenture	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

PARTYRATIO

Attribute	Description
Name	PARTYRATIO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 1

TOP

Custdoc-Chklist

Attribute	Description
Name	Custdoc-Chklist
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

CHECKED

Attribute	Description
Name	CHECKED
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Doctype-Remarks

Attribute	Description	
Name	Doctype-Remarks	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REMARK1

Attribute	Description	
Name	REMARK1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	225

TOP

REMARK2

Attribute	Description	
Name	REMARK2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	225

TOP

REMARK3

Attribute	Description	
Name	REMARK3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	225

TOP

REMARK4

Attribute	Description
Name	REMARK4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK5

Attribute	Description
Name	REMARK5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK6

Attribute	Description
Name	REMARK6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK7

Attribute	Description
Name	REMARK7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK8

Attribute	Description
Name	REMARK8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK9

Attribute	Description
Name	REMARK9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK10

Attribute	Description
Name	REMARK10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

Custmis

Attribute	Description
Name	Custmis
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates the MIS Group.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Custchnglog

Attribute	Description
Name	Custchnglog
Datatype	
Description	Indicates the Customer Change Log.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Baltrnsfrlog

Attribute	Description
Name	Baltrnsfrlog
Datatype	
Description	Indicates the Balance Transfer Log.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Dfltcd

Attribute	Description
Name	Dfltcd
Datatype	
Description	Indicates the Customer MIS Classes.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates the MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Dfltcda

Attribute	Description
Name	Dfltcda
Datatype	
Description	Indicates the Composite MIS Classes.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates the MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Jointcustomer

Attribute	Description
Name	Jointcustomer
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Custjoint

Attribute	Description
Name	Custjoint
Datatype	
Description	Indicates the Customer Joint.
Attributes	**Attribute** / **Description**: maxOccurs = unbounded; minOccurs = 0

TOP

CUSTPREFIX

Attribute	Description
Name	CUSTPREFIX
Datatype	String
Description	Indicates the Customer Prefix.
Attributes	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: maxLength = 10

TOP

FRSTNAME

Attribute	Description
Name	FRSTNAME
Datatype	String
Description	Indicates the First Name.
Attributes	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: maxLength = 105

TOP

MIDNAME

Attribute	Description
Name	MIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: maxLength = 105

TOP

LASTNAME

Attribute	Description
Name	LASTNAME
Datatype	String
Description	Indicates the Last Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SEX

Attribute	Description
Name	SEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,F

TOP

PPNO

Attribute	Description
Name	PPNO
Datatype	String
Description	Indicates the Passport Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PPTISSDT

Attribute	Description
Name	PPTISSDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PPTEXPDT

Attribute	Description
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADD3

Attribute	Description
Name	ADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DECEASED

Attribute	Description
Name	DECEASED
Datatype	String
Description	Indicates whether deceased or not. The value can be either D or N.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,N

TOP

RESISTAT

Attribute	Description
Name	RESISTAT
Datatype	String
Description	Indicates the Resident Status. The Value Could be either R or N.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / R,N

TOP

Cust-Acc-Det

Attribute	Description
Name	Cust-Acc-Det
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Diary-Mst

Attribute	Description
Name	Diary-Mst
Datatype	
Description	Indicates Diary Master.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	Indicates Instrument Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

UNTTYP

Attribute	Description
Name	UNTTYP
Datatype	String
Description	Indicates Unit Type.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

UNTVAL

Attribute	Description
Name	UNTVAL
Datatype	String
Description	Indicates Unit Value.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates Branch Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INSTR

Attribute	Description
Name	INSTR
Datatype	String
Description	Indicates Instructions.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

INSTRTYPE

Attribute	Description
Name	INSTRTYPE
Datatype	String
Description	Indicates Instruction Type.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

EXEDAYS

Attribute	Description
Name	EXEDAYS
Datatype	Number
Description	Indicates Execution Days.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXEMONTHS

Attribute	Description
Name	EXEMONTHS
Datatype	Number
Description	Indicates Execution Months.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXEYEARS

Attribute	Description
Name	EXEYEARS
Datatype	Number
Description	Indicates Execution years.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MNTHENDFLG

Attribute	Description
Name	MNTHENDFLG
Datatype	String
Description	Indicates Month End Flag. The flag should be either Y or N.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HLDRULE

Attribute	Description
Name	HLDRULE
Datatype	String
Description	Indicates Holiday Rule.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

FRSTDUEDT

Attribute	Description
Name	FRSTDUEDT
Datatype	Date
Description	Indicates First Due date.
Attributes	Attribute: minOccurs; Description: 0

TOP

NXTDUEDT

Attribute	Description
Name	NXTDUEDT
Datatype	Date
Description	Indicates Next Due date.
Attributes	Attribute: minOccurs; Description: 0

TOP

NXTEXEDT

Attribute	Description
Name	NXTEXEDT
Datatype	Date
Description	Indicates Next Execution Date.
Attributes	Attribute: minOccurs; Description: 0

TOP

CONDELEM

Attribute	Description
Name	CONDELEM
Datatype	String
Description	Indicates Condition Elements.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 20

TOP

OPRTR

Attribute	Description
Name	OPRTR

Datatype	String
Description	Indicates Operator.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2

TOP

CONDVAL

Attribute	Description
Name	CONDVAL
Datatype	Number
Description	Indicates Condition Value.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOFCR

Attribute	Description
Name	ACCOFCR
Datatype	String
Description	Indicates Account Officer.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPLINSTRTYP

Attribute	Description
Name	SPLINSTRTYP
Datatype	String
Description	Indicates Special Instruction Type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	Indicates Expiry date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPLINSTR

Attribute	Description
Name	SPLINSTR
Datatype	String
Description	Indicates Special Instruction.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Custaccdet

Attribute	Description
Name	Custaccdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkage details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String

Description	Indicates the customer
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RELATIONSHIP

Attribute	**Description**
Name	RELATIONSHIP
Datatype	String
Description	Indicate relations
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

INHERIT

Attribute	**Description**
Name	INHERIT
Datatype	String
Description	Indicate,include relationship Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DESCP

Attribute	**Description**
Name	DESCP
Datatype	String
Description	Indicates description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Custacdetail

Attribute	**Description**
Name	Custacdetail
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

CUSTTEXT

Attribute	Description
Name	CUSTTEXT
Datatype	
Description	Include customer details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	Indicates sequence number
Attributes	Attribute: minOccurs — Description: 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

TDESC

Attribute	Description

Name	TDESC
Datatype	String
Description	Indicate text description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

Sttms-Debit

Attribute	**Description**
Name	Sttms-Debit
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	Indicates the Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACTNO

Attribute	Description
Name	ACTNO
Datatype	String
Description	Indicates the Account Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Sttms-Detail

Attribute	Description
Name	Sttms-Detail
Datatype	
Description	Indicates Customer Details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description

Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REQUEST_REFERENCE_NO

Attribute	**Description**
Name	REQUEST_REFERENCE_NO
Datatype	String
Description	Indicates the Request Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CARDNO

Attribute	**Description**
Name	CARDNO
Datatype	String
Description	Indicates the Card Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 19

TOP

CUST_NO

Attribute	**Description**
Name	CUST_NO
Datatype	String
Description	Indicates the Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CARD_PRODUCT

Attribute	**Description**
Name	CARD_PRODUCT
Datatype	String
Description	Indicates the Product code.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRIMARY_CARD

Attribute	Description	
Name	PRIMARY_CARD	
Datatype	String	
Description	Indicates the Primary Card Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NAME_ON_CARD

Attribute	Description	
Name	NAME_ON_CARD	
Datatype	String	
Description	Indicates the Name on Card.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

OWNER_ID_NO

Attribute	Description	
Name	OWNER_ID_NO	
Datatype	String	
Description	Indicates the Owner ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

CARD_ISSUED_DT

Attribute	Description	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Indicates the Card Issue Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CARD_EXPIRY_DT

Attribute	Description
Name	CARD_EXPIRY_DT
Datatype	Date
Description	Indicates the Card Expiry Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CARD_STATUS

Attribute	Description
Name	CARD_STATUS
Datatype	String
Description	Indicates the Card Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	Indicates the Record Stat.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTH_STAT

Attribute	Description
Name	AUTH_STAT
Datatype	String
Description	Indicates the Auth Stat.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CARD_BIN

Attribute	Description
Name	CARD_BIN

Datatype	String
Description	Indicates the Card Bin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CUST_AC_NO

Attribute	**Description**
Name	CUST_AC_NO
Datatype	String
Description	Indicates the Customer Account Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Extsys-Ws-Master

Attribute	**Description**
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

KEYID

Attribute	**Description**
Name	KEYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 200

TOP

Extsys-Ws-Details

Attribute	**Description**
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

Stvws-Cust-Trntax

Attribute	Description
Name	Stvws-Cust-Trntax
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Sttms-Cust-Trn-Tax

Attribute	Description
Name	Sttms-Cust-Trn-Tax
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TAX_SCHEME

Attribute	Description
Name	TAX_SCHEME
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

TXN_TAX_EXEMPTED

Attribute	**Description**
Name	TXN_TAX_EXEMPTED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TXN_TAX_EXEMPTION_PERCENT

Attribute	**Description**
Name	TXN_TAX_EXEMPTION_PERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXN_TAX_EFF_DATE

Attribute	**Description**
Name	TXN_TAX_EFF_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXN_TAX_EXEMPTION_REASON

Attribute	**Description**
Name	TXN_TAX_EXEMPTION_REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.16.CreateTDAmountBlock

CreateTDAmountBlock

2.16.1.ST-CreateTDAmountBlock-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-Full*
    - *ACC*
    - *AMTBLKNO*
    - *AMT*
    - *EXPDATE*
    - *REM*
    - *ABLKTYPE*
    - *REFERENCE_NO*
    - *HPCODE*
    - *EFFDATE*
    - *HOLDDESC*
    - *BRANCH*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Amount-Blocks-Full

Attribute	Description
Name	Amount-Blocks-Full
Datatype	
Description	

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTBLKNO

Attribute	Description	
Name	AMTBLKNO	
Datatype	String	
Description	Indicates the Amount Block Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

EXPDATE

Attribute	Description	
Name	EXPDATE	
Datatype	Date	
Description	Indicates the Expiry Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ABLKTYPE

Attribute	Description
Name	ABLKTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,S,P,E,A,C,B,D

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 40

TOP

HPCODE

Attribute	Description
Name	HPCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

HOLDDESC

Attribute	Description
Name	HOLDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.16.2.ST-CreateTDAmountBlock-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-IO*
    - *ACC*
    - *AMTBLKNO*
    - *AMT*
    - *EXPDATE*
    - *REM*
    - *ABLKTYPE*
    - *REFERENCE_NO*
    - *HPCODE*
    - *EFFDATE*
    - *BRANCH*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Amount-Blocks-IO

Attribute	Description
Name	Amount-Blocks-IO
Datatype	
Description	

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ABLKTYPE

Attribute	Description
Name	ABLKTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,S,P,E,A,C,B,D

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 40

TOP

HPCODE

Attribute	Description
Name	HPCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.16.3.ST-CreateTDAmountBlock-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-Full*
    - *ACC*
    - *AMTBLKNO*
    - *AMT*
    - *EXPDATE*
    - *REM*
    - *ABLKTYPE*
    - *REFERENCE_NO*
    - *HPCODE*
    - *EFFDATE*
    - *HOLDDESC*
    - *BRANCH*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String

Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Amount-Blocks-Full

Attribute	Description
Name	Amount-Blocks-Full
Datatype	
Description	

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTBLKNO

Attribute	Description	
Name	AMTBLKNO	
Datatype	String	
Description	Indicates the Amount Block Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date
Attributes	Attribute: minOccurs, Description: 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 255

TOP

ABLKTYPE

Attribute	Description
Name	ABLKTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: F,S,P,E,A,C,B,D

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 40

TOP

HPCODE

Attribute	Description
Name	HPCODE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HOLDDESC

Attribute	Description
Name	HOLDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description

Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.16.4.ST-CreateTDAmountBlock-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Amount-Blocks-PK*
      - *AMTBLKNO*
    - *Amount-Blocks-IO*
      - *ACC*
      - *AMTBLKNO*
      - *AMT*
      - *EXPDATE*
      - *REM*
      - *ABLKTYPE*
      - *REFERENCE_NO*
      - *HPCODE*
      - *EFFDATE*
      - *BRANCH*
      - *UDFDETAILS*
        - *FLDNAM*
        - *FLDVAL*
  - *FCUBS_ERROR_RESP*
    - *ERROR*

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Amount-Blocks-PK

Attribute	Description
Name	Amount-Blocks-PK
Datatype	
Description	

TOP

AMTBLKNO

Attribute	Description	
Name	AMTBLKNO	
Datatype	String	
Description	Indicates the Amount Block Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Amount-Blocks-IO

Attribute	Description
Name	Amount-Blocks-IO
Datatype	
Description	

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTBLKNO

Attribute	Description

Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ABLKTYPE

Attribute	Description
Name	ABLKTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,S,P,E,A,C,B,D

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 40

TOP

HPCODE

Attribute	Description
Name	HPCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	

Description	UDF Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.17.DeleteCustomer

Deletion of Customer

2.17.1.ST-DeleteCustomer-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Customer-Full*
    - *NAME*
    - *ADDRLN1*
    - *ADDRLN3*
    - *ADDRLN2*
    - *ADDRLN4*
    - *SWIFTCD*
    - *FAX*
    - *COUNTRY*
    - *NLTY*
    - *LANG*
    - *EXPCNTRY*
    - *UIDNAME*
    - *UIDVAL*
    - *LOC*
    - *FROZEN*

DEAD
WHRUNKN
GRPCD
CHGGRP
CUSTCLGGRP
TAXGROUP
CCATEG
EXPCAT
CUSTCLASSFN
FXNETTCUST
XREF
MEDIA
SSN
CIFSTAT
CIFSTATSNC
MAILRSREQD
CLSPARTICIPANT
CRMCUST
ISSUCUST
TRSRYCUST
CUSTNO
SNAME
LBRN
CTYPE
FULLNAME
AMLCUSTGRP
AMLREQD
FLGUTLTYPRVDR
UTLTYPRVDRID
CHKDIGITVALREQD
ALGID
CONSTAXCERTRQD
INDTAXCERTRQD
HOACNO
RISKPRFL
DRCAT
FTACCASOF
UDF1
UDF2
UDF3
UDF4
UDF5
UDFLBL1
UDFLBL2

UDFLBL3
UDFLBL4
UDFLBL5
FXCUSTCLRILIM
OVRLIM
FX_CLEAN_RISK
CRRATE
REVDT
LIMCCY
SECCUSTCLRILIM
SECCLRILIM
SECCUSTPSRILIM
SECPSRILIM
CUSTUNADV
RISKCATEG
CLSCCYALLWD
NETTREQD
LIABUNADV
MT920
RELPRICING
FLGJOINT
KYCSTAT
SSTAFF
UPTYPE
KYC_REFNO
JOINT_VENTURE
PRIVATE_CUSTOMER
LC_COLLAT_PCT
ISELCMCUST
ELCMCUSTNO
ALT_CUST_NO
DETERIORATION_DATE
CHQ_TAX_EXEMPT_1
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Custpersonal
- *TITLE*
- *FSTNAME*
- *MIDNAME*

LSTNAME
DOB
GUARDIAN
MINOR
SEX
NATIONID
PPTNO
PPTISSDT
PPTEXPDT
DADD1
DADD2
DADD3
TEL
FAX
EMAIL
PADD1
PADD2
PADD3
DCNTRY
PCNTRY
RESSTATUS
CUSTPREFIX1
CUSTPREFIX2
MOBNUM
SBMTAGEPROOF
CUST_COMM_MODE
LAST_UPD_DT
Custdomestic
- *EDUSTAT*
- *MARITALSTAT*
- *SPNAME*
- *SPEMPSTATUS*
- *DEPCHILD*
- *DEPOTH*
- *ACCOMODATE*
- *CUSTNO*

Custprof
- *EMPSTAT*
- *EMPTENURE*
- *RETIREAGE*
- *PREVDESIG*
- *PREVEMP*
- *CURRDESIG*
- *CURREMP*

ADD1
ADD2
ADD3
TEL
TELEX
FAX
EMAIL
SALARY
OTHER1
RENT
INSURANCE
LOANPMNT
OTHEXP
HOUSEVAL
CRCARD
CNTY
AMTCCY1
CUSTNO
EMPLOYER_DESC
EMP_DESC

Custcorp

CORPNAME
NATIONID
REGADD1
REGADD2
REGADD3
INCORPDT
CAPITAL
NETWORTH
INCORPCNTRY
REGCNTRY
AMTCCY
CORPDESC
CUSTNO
Custcorpdir

DIRNAME
TEL
NADDR1
NADDR2
NADDR3
NADDR4
ADDR1
ADDRS2
ADDRS3

COUNTRY
TAXID
MOBNO
EMAIL
Issuerdet
OVERLIMIT
CUSTNO
OVERLMTCCY
Issuerlmts
CLTRLTYP
LMTAMT
LMTCCY
ISSID
Custgrp
GRPNO
RELATION
Custshhold
SHHOLDID
SHHOLDPCT
SHRHLDRNAME
Clsccyrest
CCY
DESC
Bic
ACC
BICCD
Linkedac
VRFD
LINKEDACCNO
LINKEDACCIBAN
LINKEDACCBIC
JointVenture
PARTYID
PARTYRATIO
PARTYNAME
Custdoc-Chklist
DOCUMENT_TYPE
CHECKED
Doctype-Remarks
REMARK1
REMARK2
REMARK3
REMARK4
REMARK5

- *REMARK6*
- *REMARK7*
- *REMARK8*
- *REMARK9*
- *REMARK10*

Custmis

- *MISGRP*
- *CUST*
- *BRNCD*
- *Custchnglog*
  - *MISCLS*
  - *TXNDT*
  - *OLDMISCD*
  - *NWMISCD*
- *Baltrnsfrlog*
  - *BRN*
  - *PRDCD*
  - *FINYR*
  - *TXNDT*
  - *GLCODE*
  - *MISCLS*
  - *OLDMISCD*
  - *NWMISCD*
  - *TRNIND*
  - *CCY*
  - *AMT*
  - *XRATE*
- *Dfltcd*
  - *MISCLS*
  - *MISCD*
- *Dfltcda*
  - *MISCLS*
  - *MISCD*
- *Custloghead*

Jointcustomer

- *CUSTNO*
- *Custjoint*
  - *CUSTPREFIX*
  - *FRSTNAME*
  - *MIDNAME*
  - *LASTNAME*
  - *DOB*
  - *SEX*
  - *PPNO*

PPTISSDT

PPTEXPDT

ADD1

ADD2

ADD3

TEL

EMAIL

SSN

DECEASED

RESISTAT

Cust-Acc-Det

CUSTNO

Diary-Mst

INSTRNO

UNTTYP

UNTVAL

BRN

INSTR

INSTRTYPE

EXEDAYS

EXEMONTHS

EXEYEARS

MNTHENDFLG

HLDRULE

FRSTDUEDT

NXTDUEDT

NXTEXEDT

CONDELEM

OPRTR

CONDVAL

ACCOFCR

SPLINSTRTYP

EXPDT

SPLINSTR

Custaccdet

CUSTNO

BRNCD

Relationship-Linkage

CUSTOMER

RELATIONSHIP

INHERIT

DESCP

Custacdetail

CUSTNO

CUSTTEXT

SEQNO

CUSTNO

TDESC

UDFDETAILS

FLDNAM

FLDVAL

Sttms-Debit

BRANCH_CODE

CUST_NO

ACTNO

Sttms-Detail

BRANCH_CODE

REQUEST_REFERENCE_NO

CARDNO

CUST_NO

CARD_PRODUCT

PRIMARY_CARD

NAME_ON_CARD

OWNER_ID_NO

CARD_ISSUED_DT

CARD_EXPIRY_DT

CARD_STATUS

RECORD_STAT

AUTH_STAT

CARD_BIN

CUST_AC_NO

Extsys-Ws-Master

Extsys-Ws-Details

EXTWSRESP

USERREMARKS

Stvws-Cust-Trntax

CUSTOMER_NO

Sttms-Cust-Trn-Tax

TAX_SCHEME

TXN_TAX_EXEMPTED

TXN_TAX_EXEMPTION_PERCENT

TXN_TAX_EFF_DATE

TXN_TAX_EXEMPTION_REASON

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Customer-Full

Attribute	Description
Name	Customer-Full
Datatype	
Description	

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

ADDRLN1

Attribute	Description	
Name	ADDRLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN3

Attribute	Description	
Name	ADDRLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN2

Attribute	Description	
Name	ADDRLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN4

Attribute	Description
Name	ADDRLN4
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SWIFTCD

Attribute	Description
Name	SWIFTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FAX

Attribute	Description
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRY

Attribute	Description
Name	COUNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NLTY

Attribute	Description
Name	NLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	3

TOP

LANG

Attribute	Description	
Name	LANG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

TOP

EXPCNTRY

Attribute	Description	
Name	EXPCNTRY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

UIDNAME

Attribute	Description	
Name	UIDNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

UIDVAL

Attribute	Description	
Name	UIDVAL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

LOC

Attribute	Description
Name	LOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FROZEN

Attribute	Description
Name	FROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEAD

Attribute	Description
Name	DEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

WHRUNKN

Attribute	Description
Name	WHRUNKN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

CHGGRP

Attribute	Description
Name	CHGGRP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

CUSTCLGGRP

Attribute	Description
Name	CUSTCLGGRP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TAXGROUP

Attribute	Description
Name	TAXGROUP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

CCATEG

Attribute	Description
Name	CCATEG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EXPCAT

Attribute	**Description**
Name	EXPCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUSTCLASSFN

Attribute	**Description**
Name	CUSTCLASSFN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

FXNETTCUST

Attribute	**Description**
Name	FXNETTCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

XREF

Attribute	**Description**
Name	XREF
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SSN

Attribute	Description
Name	SSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

CIFSTAT

Attribute	Description
Name	CIFSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CIFSTATSNC

Attribute	Description
Name	CIFSTATSNC
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAILRSREQD

Attribute	Description
Name	MAILRSREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLSPARTICIPANT

Attribute	Description
Name	CLSPARTICIPANT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CRMCUST

Attribute	Description
Name	CRMCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ISSUCUST

Attribute	Description
Name	ISSUCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRSRYCUST

Attribute	Description
Name	TRSRYCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

SNAME

Attribute	Description
Name	SNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 20

TOP

LBRN

Attribute	Description
Name	LBRN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CTYPE

Attribute	Description
Name	CTYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,C,B

TOP

FULLNAME

Attribute	**Description**
Name	FULLNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

AMLCUSTGRP

Attribute	**Description**
Name	AMLCUSTGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

AMLREQD

Attribute	**Description**
Name	AMLREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FLGUTLTYPRVDR

Attribute	**Description**
Name	FLGUTLTYPRVDR
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

UTLTYPRVDRID

Attribute	Description	
Name	UTLTYPRVDRID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHKDIGITVALREQD

Attribute	Description	
Name	CHKDIGITVALREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALGID

Attribute	Description	
Name	ALGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CONSTAXCERTRQD

Attribute	Description	
Name	CONSTAXCERTRQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

INDTAXCERTRQD

Attribute	Description	
Name	INDTAXCERTRQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

HOACNO

Attribute	Description	
Name	HOACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RISKPRFL

Attribute	Description	
Name	RISKPRFL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

DRCAT

Attribute	Description	
Name	DRCAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FTACCASOF

Attribute	Description
Name	FTACCASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,M,D

TOP

UDF1

Attribute	Description
Name	UDF1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDF2

Attribute	Description
Name	UDF2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDF3

Attribute	Description
Name	UDF3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

UDF4

Attribute	Description
Name	UDF4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

UDF5

Attribute	Description
Name	UDF5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDFLBL1

Attribute	Description
Name	UDFLBL1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDFLBL2

Attribute	Description
Name	UDFLBL2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDFLBL3

Attribute	Description
Name	UDFLBL3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL4

Attribute	Description
Name	UDFLBL4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL5

Attribute	Description
Name	UDFLBL5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

FXCUSTCLRILIM

Attribute	Description
Name	FXCUSTCLRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OVRLIM

Attribute	Description
Name	OVRLIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FX_CLEAN_RISK

Attribute	Description
Name	FX_CLEAN_RISK
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CRRATE

Attribute	Description
Name	CRRATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

REVDT

Attribute	Description
Name	REVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIMCCY

Attribute	Description
Name	LIMCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SECCUSTCLRILIM

Attribute	Description
Name	SECCUSTCLRILIM
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SECCLRILIM

Attribute	Description
Name	SECCLRILIM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SECCUSTPSRILIM

Attribute	Description
Name	SECCUSTPSRILIM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SECPSRILIM

Attribute	Description
Name	SECPSRILIM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CUSTUNADV

Attribute	Description
Name	CUSTUNADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

RISKCATEG

Attribute	Description
Name	RISKCATEG
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CLSCCYALLWD

Attribute	Description
Name	CLSCCYALLWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

NETTREQD

Attribute	Description
Name	NETTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIABUNADV

Attribute	Description
Name	LIABUNADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MT920

Attribute	Description
Name	MT920
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

RELPRICING

Attribute	Description	
Name	RELPRICING	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

FLGJOINT

Attribute	Description	
Name	FLGJOINT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

KYCSTAT

Attribute	Description	
Name	KYCSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	V,N,F

TOP

SSTAFF

Attribute	Description	
Name	SSTAFF	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

UPTYPE

Attribute	Description
Name	UPTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

KYC_REFNO

Attribute	Description
Name	KYC_REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

JOINT_VENTURE

Attribute	Description
Name	JOINT_VENTURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIVATE_CUSTOMER

Attribute	Description
Name	PRIVATE_CUSTOMER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LC_COLLAT_PCT

Attribute	Description
Name	LC_COLLAT_PCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISELCMCUST

Attribute	Description
Name	ISELCMCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ELCMCUSTNO

Attribute	Description
Name	ELCMCUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ALT_CUST_NO

Attribute	Description
Name	ALT_CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DETERIORATION_DATE

Attribute	Description
Name	DETERIORATION_DATE
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CHQ_TAX_EXEMPT_1

Attribute	Description	
Name	CHQ_TAX_EXEMPT_1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Custpersonal

Attribute	Description
Name	Custpersonal

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TITLE

Attribute	Description
Name	TITLE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FSTNAME

Attribute	Description
Name	FSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MIDNAME

Attribute	Description
Name	MIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LSTNAME

Attribute	Description
Name	LSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

DOB

Attribute	Description	
Name	DOB	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

GUARDIAN

Attribute	Description	
Name	GUARDIAN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

MINOR

Attribute	Description	
Name	MINOR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

SEX

Attribute	Description	
Name	SEX	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	M,F

TOP

NATIONID

Attribute	Description
Name	NATIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

PPTNO

Attribute	Description
Name	PPTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

PPTISSDT

Attribute	Description
Name	PPTISSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PPTEXPDT

Attribute	Description
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DADD1

Attribute	Description
Name	DADD1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

DADD2

Attribute	Description	
Name	DADD2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

DADD3

Attribute	Description	
Name	DADD3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

TEL

Attribute	Description	
Name	TEL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

FAX

Attribute	Description	
Name	FAX	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PADD1

Attribute	Description
Name	PADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PADD2

Attribute	Description
Name	PADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PADD3

Attribute	Description
Name	PADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DCNTRY

Attribute	Description
Name	DCNTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

PCNTRY

Attribute	Description
Name	PCNTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

RESSTATUS

Attribute	Description
Name	RESSTATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: R,N

TOP

CUSTPREFIX1

Attribute	Description
Name	CUSTPREFIX1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

CUSTPREFIX2

Attribute	Description
Name	CUSTPREFIX2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

MOBNUM

Attribute	**Description**
Name	MOBNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SBMTAGEPROOF

Attribute	**Description**
Name	SBMTAGEPROOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,P,V

TOP

CUST_COMM_MODE

Attribute	**Description**
Name	CUST_COMM_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,E

TOP

LAST_UPD_DT

Attribute	**Description**
Name	LAST_UPD_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Custdomestic

Attribute	Description
Name	Custdomestic
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EDUSTAT

Attribute	Description
Name	EDUSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,U,G,P

TOP

MARITALSTAT

Attribute	Description
Name	MARITALSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,M,D,R,P,E,T

TOP

SPNAME

Attribute	Description
Name	SPNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SPEMPSTATUS

Attribute	Description
Name	SPEMPSTATUS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,T,S,U,R,P,N,O

TOP

DEPCHILD

Attribute	**Description**
Name	DEPCHILD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEPOTH

Attribute	**Description**
Name	DEPOTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOMODATE

Attribute	**Description**
Name	ACCOMODATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,O

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Custprof

Attribute	Description
Name	Custprof
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EMPSTAT

Attribute	Description
Name	EMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

EMPTENURE

Attribute	Description
Name	EMPTENURE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RETIREAGE

Attribute	Description
Name	RETIREAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PREVDESIG

Attribute	Description
Name	PREVDESIG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

PREVEMP

Attribute	Description
Name	PREVEMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CURRDESIG

Attribute	Description
Name	CURRDESIG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CURREMP

Attribute	Description
Name	CURREMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADD3

Attribute	Description
Name	ADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TELEX

Attribute	Description
Name	TELEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FAX

Attribute	Description
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

SALARY

Attribute	Description
Name	SALARY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHER1

Attribute	Description
Name	OTHER1
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RENT

Attribute	Description
Name	RENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSURANCE

Attribute	Description
Name	INSURANCE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LOANPMNT

Attribute	Description
Name	LOANPMNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

OTHEXP

Attribute	Description
Name	OTHEXP
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

HOUSEVAL

Attribute	Description
Name	HOUSEVAL
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

CRCARD

Attribute	Description
Name	CRCARD
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMTCCY1

Attribute	Description
Name	AMTCCY1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

EMPLOYER_DESC

Attribute	Description
Name	EMPLOYER_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

EMP_DESC

Attribute	Description

Name	EMP_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Custcorp

Attribute	**Description**
Name	Custcorp
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CORPNAME

Attribute	**Description**
Name	CORPNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NATIONID

Attribute	**Description**
Name	NATIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REGADD1

Attribute	**Description**
Name	REGADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

REGADD2

Attribute	Description	
Name	REGADD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REGADD3

Attribute	Description	
Name	REGADD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INCORPDT

Attribute	Description	
Name	INCORPDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CAPITAL

Attribute	Description	
Name	CAPITAL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETWORTH

Attribute	Description
Name	NETWORTH

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INCORPCNTRY

Attribute	**Description**
Name	INCORPCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REGCNTRY

Attribute	**Description**
Name	REGCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMTCCY

Attribute	**Description**
Name	AMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CORPDESC

Attribute	**Description**
Name	CORPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255

TOP

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

TOP

Custcorpdir

Attribute	Description	
Name	Custcorpdir	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

DIRNAME

Attribute	Description	
Name	DIRNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

TEL

Attribute	Description	
Name	TEL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

NADDR1

Attribute	Description
Name	NADDR1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR2

Attribute	Description
Name	NADDR2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR3

Attribute	Description
Name	NADDR3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR4

Attribute	Description
Name	NADDR4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDR1

Attribute	Description

Name	ADDR1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	**Description**
Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS3

Attribute	**Description**
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRY

Attribute	**Description**
Name	COUNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXID

Attribute	**Description**
Name	TAXID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MOBNO

Attribute	Description
Name	MOBNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Issuerdet

Attribute	Description
Name	Issuerdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OVERLIMIT

Attribute	Description
Name	OVERLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OVERLMTCCY

Attribute	**Description**
Name	OVERLMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Issuerlmts

Attribute	**Description**
Name	Issuerlmts
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CLTRLTYP

Attribute	**Description**
Name	CLTRLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 70

TOP

LMTAMT

Attribute	**Description**
Name	LMTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LMTCCY

Attribute	Description
Name	LMTCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ISSID

Attribute	Description
Name	ISSID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

Custgrp

Attribute	Description
Name	Custgrp
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

GRPNO

Attribute	Description
Name	GRPNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

RELATION

Attribute	Description

Name	RELATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Custshhold

Attribute	**Description**
Name	Custshhold
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SHHOLDID

Attribute	**Description**
Name	SHHOLDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SHHOLDPCT

Attribute	**Description**
Name	SHHOLDPCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHRHLDRNAME

Attribute	**Description**
Name	SHRHLDRNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Clsccyrest

Attribute	Description
Name	Clsccyrest
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Bic

Attribute	Description
Name	Bic
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC

Attribute	Description
Name	ACC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BICCD

Attribute	Description
Name	BICCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

Linkedac

Attribute	Description
Name	Linkedac
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

VRFD

Attribute	Description
Name	VRFD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LINKEDACCNO

Attribute	Description
Name	LINKEDACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	30

TOP

LINKEDACCIBAN

Attribute	Description	
Name	LINKEDACCIBAN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

LINKEDACCBIC

Attribute	Description	
Name	LINKEDACCBIC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

JointVenture

Attribute	Description	
Name	JointVenture	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

PARTYID

Attribute	Description	
Name	PARTYID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

TOP

PARTYRATIO

Attribute	Description
Name	PARTYRATIO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Custdoc-Chklist

Attribute	Description
Name	Custdoc-Chklist
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHECKED

Attribute	Description
Name	CHECKED
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Doctype-Remarks

Attribute	Description
Name	Doctype-Remarks
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARK1

Attribute	Description
Name	REMARK1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK2

Attribute	Description
Name	REMARK2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK3

Attribute	Description
Name	REMARK3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK4

Attribute	Description
Name	REMARK4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK5

Attribute	Description
Name	REMARK5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK6

Attribute	Description
Name	REMARK6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK7

Attribute	Description
Name	REMARK7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK8

Attribute	Description
Name	REMARK8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK9

Attribute	Description
Name	REMARK9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK10

Attribute	Description
Name	REMARK10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

Custmis

Attribute	Description
Name	Custmis
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates Management Information System Group.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CUST

Attribute	**Description**
Name	CUST
Datatype	String
Description	Indicates the Customer.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRNCD

Attribute	**Description**
Name	BRNCD
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Custchnglog

Attribute	**Description**
Name	Custchnglog
Datatype	
Description	Indicates the Customer Change Log.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	**Description**
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	Indicates the Old MIS Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	Indicates the New MIS Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Baltrnsfrlog

Attribute	Description
Name	Baltrnsfrlog
Datatype	
Description	Indicates the Balance Transfer Log.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String

Description	Indicates the Branch Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDCD

Attribute	**Description**
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	**Description**
Name	FINYR
Datatype	String
Description	Indicates the Financial Year.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNDT

Attribute	**Description**
Name	TXNDT
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

GLCODE

Attribute	**Description**
Name	GLCODE
Datatype	String
Description	Indicates the GL Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	Indicates the Old MIS Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	Indicates the New MIS Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TRNIND

Attribute	Description
Name	TRNIND
Datatype	String
Description	Indicates Transfer Identification Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	Attribute: minOccurs — Description: 0

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate.
Attributes	Attribute: minOccurs — Description: 0

TOP

Dfltcd

Attribute	Description
Name	Dfltcd
Datatype	
Description	Indicates the Customer MIS Classes.
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	Attribute: minOccurs — Description: 1

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCD

Attribute	**Description**
Name	MISCD
Datatype	String
Description	Indicates the MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Dfltcda

Attribute	**Description**
Name	Dfltcda
Datatype	
Description	Indicates the Composite MIS Classes.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	**Description**
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCD

Attribute	**Description**
Name	MISCD
Datatype	String
Description	Indicates the MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Custloghead

Attribute	Description
Name	Custloghead
Datatype	
Description	Indicates the Customer Log Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Jointcustomer

Attribute	Description
Name	Jointcustomer
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Custjoint

Attribute	Description
Name	Custjoint
Datatype	
Description	Indicates Customer Joint.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTPREFIX

Attribute	Description
Name	CUSTPREFIX
Datatype	String
Description	Indicates the Customer Prefix.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FRSTNAME

Attribute	Description
Name	FRSTNAME
Datatype	String
Description	Indicates the First Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MIDNAME

Attribute	Description
Name	MIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LASTNAME

Attribute	Description
Name	LASTNAME
Datatype	String
Description	Indicates the Last Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SEX

Attribute	Description
Name	SEX
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,F

TOP

PPNO

Attribute	Description
Name	PPNO
Datatype	String
Description	Indicates Passport Number.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

PPTISSDT

Attribute	Description
Name	PPTISSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PPTEXPDT

Attribute	Description
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ADD2

Attribute	Description	
Name	ADD2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ADD3

Attribute	Description	
Name	ADD3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

TEL

Attribute	Description	
Name	TEL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

EMAIL

Attribute	Description	
Name	EMAIL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TOP

SSN

Attribute	Description
Name	SSN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

DECEASED

Attribute	Description
Name	DECEASED
Datatype	String
Description	Indicates whether Deceased or not. The value should be either D or N.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,N

TOP

RESISTAT

Attribute	Description
Name	RESISTAT
Datatype	String
Description	Indicates the Resistant Status. The value could be either R or N.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: R,N

TOP

Cust-Acc-Det

Attribute	Description
Name	Cust-Acc-Det
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Diary-Mst

Attribute	**Description**
Name	Diary-Mst
Datatype	
Description	Indicates Diary Master.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSTRNO

Attribute	**Description**
Name	INSTRNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

UNTTYP

Attribute	**Description**
Name	UNTTYP
Datatype	String
Description	Indicates Unit Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

UNTVAL

Attribute	**Description**
Name	UNTVAL
Datatype	String
Description	Indicates Unit Value
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description	Indicates the Branch Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

INSTR

Attribute	Description	
Name	INSTR	
Datatype	String	
Description	Indicates Instructions	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

INSTRTYPE

Attribute	Description	
Name	INSTRTYPE	
Datatype	String	
Description	Indicates Instruction Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

EXEDAYS

Attribute	Description	
Name	EXEDAYS	
Datatype	Number	
Description	Indicates Execution Days	
Attributes	Attribute	Description
	minOccurs	0

TOP

EXEMONTHS

Attribute	Description
Name	EXEMONTHS
Datatype	Number
Description	Indicates Execution Months
Attributes	Attribute: minOccurs, Description: 0

TOP

EXEYEARS

Attribute	Description
Name	EXEYEARS
Datatype	Number
Description	Indicates Execution Years
Attributes	Attribute: minOccurs, Description: 0

TOP

MNTHENDFLG

Attribute	Description
Name	MNTHENDFLG
Datatype	String
Description	Indicates Month End Flag. Flag Can be either Y or N.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

HLDRULE

Attribute	Description
Name	HLDRULE
Datatype	String
Description	Indicates Holiday Rule
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 1

TOP

FRSTDUEDT

Attribute	Description
Name	FRSTDUEDT
Datatype	Date
Description	Indicates First Due Date.
Attributes	Attribute: minOccurs, Description: 0

TOP

NXTDUEDT

Attribute	Description
Name	NXTDUEDT
Datatype	Date
Description	Indicates Next Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NXTEXEDT

Attribute	Description
Name	NXTEXEDT
Datatype	Date
Description	Indicates Next Execution Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONDELEM

Attribute	Description
Name	CONDELEM
Datatype	String
Description	Indicates Condition Elements.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

OPRTR

Attribute	Description
Name	OPRTR
Datatype	String
Description	Indicates Operator.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

CONDVAL

Attribute	Description
Name	CONDVAL
Datatype	Number
Description	Indicates Condition Value.

Attributes	Attribute	Description
	minOccurs	0

TOP

ACCOFCR

Attribute	Description	
Name	ACCOFCR	
Datatype	String	
Description	Indicates Account Officer.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SPLINSTRTYP

Attribute	Description	
Name	SPLINSTRTYP	
Datatype	String	
Description	Indicates Special Instruction Type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

EXPDT

Attribute	Description	
Name	EXPDT	
Datatype	Date	
Description	Indicates Expiry Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPLINSTR

Attribute	Description	
Name	SPLINSTR	
Datatype	String	
Description	Indicates Special Instructions.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Custaccdet

Attribute	Description
Name	Custaccdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkage details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Indicates the customer

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Indicate relations
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicate,include relationship Y:yes N:no
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	Indicates description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Custacdetail

Attribute	Description
Name	Custacdetail
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTTEXT

Attribute	Description
Name	CUSTTEXT
Datatype	
Description	Include customer details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	Indicates sequence number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String

Description	Indicate text description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Sttms-Debit

Attribute	**Description**
Name	Sttms-Debit
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	Indicates the Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACTNO

Attribute	Description
Name	ACTNO
Datatype	String
Description	Indicates the Account Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Sttms-Detail

Attribute	Description
Name	Sttms-Detail
Datatype	
Description	Indicates Customer Details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description

Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REQUEST_REFERENCE_NO

Attribute	Description
Name	REQUEST_REFERENCE_NO
Datatype	String
Description	Indicates the Request Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CARDNO

Attribute	Description
Name	CARDNO
Datatype	String
Description	Indicates the Card Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 19

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	Indicates the Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CARD_PRODUCT

Attribute	Description
Name	CARD_PRODUCT
Datatype	String
Description	Indicates the Product code.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRIMARY_CARD

Attribute	Description	
Name	PRIMARY_CARD	
Datatype	String	
Description	Indicates the Primary Card Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NAME_ON_CARD

Attribute	Description	
Name	NAME_ON_CARD	
Datatype	String	
Description	Indicates the Name on Card.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

OWNER_ID_NO

Attribute	Description	
Name	OWNER_ID_NO	
Datatype	String	
Description	Indicates the Owner ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

CARD_ISSUED_DT

Attribute	Description	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Indicates the Card Issue Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CARD_EXPIRY_DT

Attribute	Description
Name	CARD_EXPIRY_DT
Datatype	Date
Description	Indicates the Card Expiry Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CARD_STATUS

Attribute	Description
Name	CARD_STATUS
Datatype	String
Description	Indicates the Card Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	Indicates the Record Stat.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTH_STAT

Attribute	Description
Name	AUTH_STAT
Datatype	String
Description	Indicates the Auth Stat.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CARD_BIN

Attribute	Description
Name	CARD_BIN

Datatype	String
Description	Indicates the Card Bin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CUST_AC_NO

Attribute	**Description**
Name	CUST_AC_NO
Datatype	String
Description	Indicates the Customer Account Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Extsys-Ws-Master

Attribute	**Description**
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	**Description**
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXTWSRESP

Attribute	**Description**
Name	EXTWSRESP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

Stvws-Cust-Trntax

Attribute	Description
Name	Stvws-Cust-Trntax
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Sttms-Cust-Trn-Tax

Attribute	Description
Name	Sttms-Cust-Trn-Tax
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TAX_SCHEME

Attribute	Description
Name	TAX_SCHEME
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

TXN_TAX_EXEMPTED

Attribute	**Description**
Name	TXN_TAX_EXEMPTED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TXN_TAX_EXEMPTION_PERCENT

Attribute	**Description**
Name	TXN_TAX_EXEMPTION_PERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXN_TAX_EFF_DATE

Attribute	**Description**
Name	TXN_TAX_EFF_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXN_TAX_EXEMPTION_REASON

Attribute	**Description**
Name	TXN_TAX_EXEMPTION_REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

2.17.2.ST-DeleteCustomer-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Customer-IO*
    - *CUSTNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration — Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0 Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0 Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	Restrictions: maxLength — Description: 12 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	

Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Customer-IO

Attribute	Description
Name	Customer-IO
Datatype	
Description	

TOP

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

2.17.3.ST-DeleteCustomer-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Customer-Full*
    - *NAME*
    - *ADDRLN1*
    - *ADDRLN3*
    - *ADDRLN2*
    - *ADDRLN4*
    - *SWIFTCD*
    - *FAX*
    - *COUNTRY*
    - *NLTY*
    - *LANG*
    - *EXPCNTRY*
    - *UIDNAME*
    - *UIDVAL*
    - *LOC*
    - *FROZEN*
    - *DEAD*
    - *WHRUNKN*
    - *GRPCD*

CHGGRP
CUSTCLGGRP
TAXGROUP
CCATEG
EXPCAT
CUSTCLASSFN
FXNETTCUST
XREF
MEDIA
SSN
CIFSTAT
CIFSTATSNC
MAILRSREQD
CLSPARTICIPANT
CRMCUST
ISSUCUST
TRSRYCUST
CUSTNO
SNAME
LBRN
CTYPE
FULLNAME
AMLCUSTGRP
AMLREQD
FLGUTLTYPRVDR
UTLTYPRVDRID
CHKDIGITVALREQD
ALGID
CONSTAXCERTRQD
INDTAXCERTRQD
HOACNO
RISKPRFL
DRCAT
FTACCASOF
UDF1
UDF2
UDF3
UDF4
UDF5
UDFLBL1
UDFLBL2
UDFLBL3
UDFLBL4
UDFLBL5

FXCUSTCLRILIM
OVRLIM
FX_CLEAN_RISK
CRRATE
REVDT
LIMCCY
SECCUSTCLRILIM
SECCLRILIM
SECCUSTPSRILIM
SECPSRILIM
CUSTUNADV
RISKCATEG
CLSCCYALLWD
NETTREQD
LIABUNADV
MT920
RELPRICING
FLGJOINT
KYCSTAT
SSTAFF
UPTYPE
KYC_REFNO
JOINT_VENTURE
PRIVATE_CUSTOMER
LC_COLLAT_PCT
ISELCMCUST
ELCMCUSTNO
ALT_CUST_NO
DETERIORATION_DATE
CHQ_TAX_EXEMPT_1
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Custpersonal
- *TITLE*
- *FSTNAME*
- *MIDNAME*
- *LSTNAME*
- *DOB*
- *GUARDIAN*

MINOR
SEX
NATIONID
PPTNO
PPTISSDT
PPTEXPDT
DADD1
DADD2
DADD3
TEL
FAX
EMAIL
PADD1
PADD2
PADD3
DCNTRY
PCNTRY
RESSTATUS
CUSTPREFIX1
CUSTPREFIX2
MOBNUM
SBMTAGEPROOF
CUST_COMM_MODE
LAST_UPD_DT
Custdomestic
- *EDUSTAT*
- *MARITALSTAT*
- *SPNAME*
- *SPEMPSTATUS*
- *DEPCHILD*
- *DEPOTH*
- *ACCOMODATE*
- *CUSTNO*

Custprof
- *EMPSTAT*
- *EMPTENURE*
- *RETIREAGE*
- *PREVDESIG*
- *PREVEMP*
- *CURRDESIG*
- *CURREMP*
- *ADD1*
- *ADD2*
- *ADD3*

TEL
TELEX
FAX
EMAIL
SALARY
OTHER1
RENT
INSURANCE
LOANPMNT
OTHEXP
HOUSEVAL
CRCARD
CNTY
AMTCCY1
CUSTNO
EMPLOYER_DESC
EMP_DESC
Custcorp
CORPNAME
NATIONID
REGADD1
REGADD2
REGADD3
INCORPDT
CAPITAL
NETWORTH
INCORPCNTRY
REGCNTRY
AMTCCY
CORPDESC
CUSTNO
Custcorpdir
DIRNAME
TEL
NADDR1
NADDR2
NADDR3
NADDR4
ADDR1
ADDRS2
ADDRS3
COUNTRY
TAXID
MOBNO

EMAIL

Issuerdet

OVERLIMIT

CUSTNO

OVERLMTCCY

Issuerlmts

CLTRLTYP

LMTAMT

LMTCCY

ISSID

Custgrp

GRPNO

RELATION

Custshhold

SHHOLDID

SHHOLDPCT

SHRHLDRNAME

Clsccyrest

CCY

DESC

Bic

ACC

BICCD

Linkedac

VRFD

LINKEDACCNO

LINKEDACCIBAN

LINKEDACCBIC

JointVenture

PARTYID

PARTYRATIO

PARTYNAME

Custdoc-Chklist

DOCUMENT_TYPE

CHECKED

Doctype-Remarks

REMARK1

REMARK2

REMARK3

REMARK4

REMARK5

REMARK6

REMARK7

REMARK8

REMARK9
REMARK10
Custmis
MISGRP
CUST
BRNCD
Custchnglog
MISCLS
TXNDT
OLDMISCD
NWMISCD
Baltrnsfrlog
BRN
PRDCD
FINYR
TXNDT
GLCODE
MISCLS
OLDMISCD
NWMISCD
TRNIND
CCY
AMT
XRATE
Dfltcd
MISCLS
MISCD
Dfltcda
MISCLS
MISCD
Custloghead
Jointcustomer
CUSTNO
Custjoint
CUSTPREFIX
FRSTNAME
MIDNAME
LASTNAME
DOB
SEX
PPNO
PPTISSDT
PPTEXPDT
ADD1

ADD2
ADD3
TEL
EMAIL
SSN
DECEASED
RESISTAT
Cust-Acc-Det
CUSTNO
Diary-Mst
INSTRNO
UNTTYP
UNTVAL
BRN
INSTR
INSTRTYPE
EXEDAYS
EXEMONTHS
EXEYEARS
MNTHENDFLG
HLDRULE
FRSTDUEDT
NXTDUEDT
NXTEXEDT
CONDELEM
OPRTR
CONDVAL
ACCOFCR
SPLINSTRTYP
EXPDT
SPLINSTR
Custaccdet
CUSTNO
BRNCD
Relationship-Linkage
CUSTOMER
RELATIONSHIP
INHERIT
DESCP
Custacdetail
CUSTNO
CUSTTEXT
SEQNO
CUSTNO

TDESC
UDFDETAILS
FLDNAM
FLDVAL
Sttms-Debit
BRANCH_CODE
CUST_NO
ACTNO
Sttms-Detail
BRANCH_CODE
REQUEST_REFERENCE_NO
CARDNO
CUST_NO
CARD_PRODUCT
PRIMARY_CARD
NAME_ON_CARD
OWNER_ID_NO
CARD_ISSUED_DT
CARD_EXPIRY_DT
CARD_STATUS
RECORD_STAT
AUTH_STAT
CARD_BIN
CUST_AC_NO
Extsys-Ws-Master
Extsys-Ws-Details
EXTWSRESP
USERREMARKS
Stvws-Cust-Trntax
CUSTOMER_NO
Sttms-Cust-Trn-Tax
TAX_SCHEME
TXN_TAX_EXEMPTED
TXN_TAX_EXEMPTION_PERCENT
TXN_TAX_EFF_DATE
TXN_TAX_EXEMPTION_REASON
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Customer-Full

Attribute	Description

Name	Customer-Full
Datatype	
Description	

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

ADDRLN1

Attribute	Description	
Name	ADDRLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN3

Attribute	Description	
Name	ADDRLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN2

Attribute	Description	
Name	ADDRLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN4

Attribute	Description

Name	ADDRLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SWIFTCD

Attribute	**Description**
Name	SWIFTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FAX

Attribute	**Description**
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRY

Attribute	**Description**
Name	COUNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NLTY

Attribute	**Description**
Name	NLTY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXPCNTRY

Attribute	Description
Name	EXPCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

UIDNAME

Attribute	Description
Name	UIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

UIDVAL

Attribute	Description
Name	UIDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

LOC

Attribute	Description	
Name	LOC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

FROZEN

Attribute	Description	
Name	FROZEN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

DEAD

Attribute	Description	
Name	DEAD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

WHRUNKN

Attribute	Description	
Name	WHRUNKN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CHGGRP

Attribute	Description
Name	CHGGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CUSTCLGGRP

Attribute	Description
Name	CUSTCLGGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAXGROUP

Attribute	Description
Name	TAXGROUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CCATEG

Attribute	Description
Name	CCATEG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

CUSTCLASSFN

Attribute	Description
Name	CUSTCLASSFN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

FXNETTCUST

Attribute	Description
Name	FXNETTCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

XREF

Attribute	Description
Name	XREF

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MEDIA

Attribute	**Description**
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SSN

Attribute	**Description**
Name	SSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

CIFSTAT

Attribute	**Description**
Name	CIFSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CIFSTATSNC

Attribute	**Description**
Name	CIFSTATSNC
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MAILRSREQD

Attribute	Description
Name	MAILRSREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CLSPARTICIPANT

Attribute	Description
Name	CLSPARTICIPANT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CRMCUST

Attribute	Description
Name	CRMCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ISSUCUST

Attribute	Description
Name	ISSUCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TRSRYCUST

Attribute	Description	
Name	TRSRYCUST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SNAME

Attribute	Description	
Name	SNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LBRN

Attribute	Description	
Name	LBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CTYPE

Attribute	Description
Name	CTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: I,C,B

TOP

FULLNAME

Attribute	Description
Name	FULLNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

AMLCUSTGRP

Attribute	Description
Name	AMLCUSTGRP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

AMLREQD

Attribute	Description
Name	AMLREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

FLGUTLTYPRVDR

Attribute	Description
Name	FLGUTLTYPRVDR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UTLTYPRVDRID

Attribute	**Description**
Name	UTLTYPRVDRID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKDIGITVALREQD

Attribute	**Description**
Name	CHKDIGITVALREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALGID

Attribute	**Description**
Name	ALGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CONSTAXCERTRQD

Attribute	**Description**
Name	CONSTAXCERTRQD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INDTAXCERTRQD

Attribute	Description	
Name	INDTAXCERTRQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

HOACNO

Attribute	Description	
Name	HOACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RISKPRFL

Attribute	Description	
Name	RISKPRFL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

DRCAT

Attribute	Description	
Name	DRCAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FTACCASOF

Attribute	Description	
Name	FTACCASOF	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,M,D

TOP

UDF1

Attribute	Description	
Name	UDF1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

TOP

UDF2

Attribute	Description	
Name	UDF2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

TOP

UDF3

Attribute	Description	
Name	UDF3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

UDF4

Attribute	Description
Name	UDF4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

UDF5

Attribute	Description
Name	UDF5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL1

Attribute	Description
Name	UDFLBL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL2

Attribute	Description
Name	UDFLBL2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL3

Attribute	Description
Name	UDFLBL3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDFLBL4

Attribute	Description
Name	UDFLBL4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDFLBL5

Attribute	Description
Name	UDFLBL5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

FXCUSTCLRILIM

Attribute	Description
Name	FXCUSTCLRILIM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

OVRLIM

Attribute	Description
Name	OVRLIM
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

FX_CLEAN_RISK

Attribute	Description
Name	FX_CLEAN_RISK
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CRRATE

Attribute	Description
Name	CRRATE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

REVDT

Attribute	Description
Name	REVDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIMCCY

Attribute	Description
Name	LIMCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

SECCUSTCLRILIM

Attribute	Description
Name	SECCUSTCLRILIM

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCLRILIM

Attribute	Description
Name	SECCLRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCUSTPSRILIM

Attribute	Description
Name	SECCUSTPSRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECPSRILIM

Attribute	Description
Name	SECPSRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTUNADV

Attribute	Description
Name	CUSTUNADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RISKCATEG

Attribute	Description
Name	RISKCATEG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CLSCCYALLWD

Attribute	**Description**
Name	CLSCCYALLWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

NETTREQD

Attribute	**Description**
Name	NETTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIABUNADV

Attribute	**Description**
Name	LIABUNADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MT920

Attribute	**Description**
Name	MT920
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RELPRICING

Attribute	Description	
Name	RELPRICING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

FLGJOINT

Attribute	Description	
Name	FLGJOINT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

KYCSTAT

Attribute	Description	
Name	KYCSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	V,N,F

TOP

SSTAFF

Attribute	Description	
Name	SSTAFF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

UPTYPE

Attribute	Description
Name	UPTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

KYC_REFNO

Attribute	Description
Name	KYC_REFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

JOINT_VENTURE

Attribute	Description
Name	JOINT_VENTURE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PRIVATE_CUSTOMER

Attribute	Description
Name	PRIVATE_CUSTOMER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

LC_COLLAT_PCT

Attribute	Description
Name	LC_COLLAT_PCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISELCMCUST

Attribute	Description
Name	ISELCMCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ELCMCUSTNO

Attribute	Description
Name	ELCMCUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ALT_CUST_NO

Attribute	Description
Name	ALT_CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DETERIORATION_DATE

Attribute	Description
Name	DETERIORATION_DATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHQ_TAX_EXEMPT_1

Attribute	Description
Name	CHQ_TAX_EXEMPT_1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

Custpersonal

Attribute	Description
Name	Custpersonal
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TITLE

Attribute	Description
Name	TITLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FSTNAME

Attribute	Description
Name	FSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MIDNAME

Attribute	Description
Name	MIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LSTNAME

Attribute	Description
Name	LSTNAME
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GUARDIAN

Attribute	Description
Name	GUARDIAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MINOR

Attribute	Description
Name	MINOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SEX

Attribute	Description
Name	SEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,F

TOP

NATIONID

Attribute	Description
Name	NATIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PPTNO

Attribute	Description
Name	PPTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PPTISSDT

Attribute	Description
Name	PPTISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PPTEXPDT

Attribute	Description
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DADD1

Attribute	Description
Name	DADD1
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DADD2

Attribute	Description
Name	DADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DADD3

Attribute	Description
Name	DADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FAX

Attribute	Description
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

PADD1

Attribute	Description
Name	PADD1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

PADD2

Attribute	Description
Name	PADD2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

PADD3

Attribute	Description
Name	PADD3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

DCNTRY

Attribute	Description
Name	DCNTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

PCNTRY

Attribute	Description
Name	PCNTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

RESSTATUS

Attribute	Description
Name	RESSTATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: R,N

TOP

CUSTPREFIX1

Attribute	Description
Name	CUSTPREFIX1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

CUSTPREFIX2

Attribute	Description
Name	CUSTPREFIX2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

MOBNUM

Attribute	Description
Name	MOBNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SBMTAGEPROOF

Attribute	Description
Name	SBMTAGEPROOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,P,V

TOP

CUST_COMM_MODE

Attribute	Description
Name	CUST_COMM_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,E

TOP

LAST_UPD_DT

Attribute	Description
Name	LAST_UPD_DT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Custdomestic

Attribute	Description
Name	Custdomestic
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

EDUSTAT

Attribute	Description
Name	EDUSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,U,G,P

TOP

MARITALSTAT

Attribute	Description
Name	MARITALSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: S,M,D,R,P,E,T

TOP

SPNAME

Attribute	Description
Name	SPNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SPEMPSTATUS

Attribute	Description
Name	SPEMPSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,T,S,U,R,P,N,O

TOP

DEPCHILD

Attribute	Description
Name	DEPCHILD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEPOTH

Attribute	Description
Name	DEPOTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOMODATE

Attribute	Description
Name	ACCOMODATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,O

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Custprof

Attribute	Description
Name	Custprof
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EMPSTAT

Attribute	Description
Name	EMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

EMPTENURE

Attribute	Description
Name	EMPTENURE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RETIREAGE

Attribute	Description
Name	RETIREAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVDESIG

Attribute	Description
Name	PREVDESIG
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PREVEMP

Attribute	Description
Name	PREVEMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURRDESIG

Attribute	Description
Name	CURRDESIG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURREMP

Attribute	Description
Name	CURREMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADD2

Attribute	**Description**
Name	ADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADD3

Attribute	**Description**
Name	ADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TEL

Attribute	**Description**
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TELEX

Attribute	**Description**
Name	TELEX
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FAX

Attribute	Description
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

SALARY

Attribute	Description
Name	SALARY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHER1

Attribute	Description
Name	OTHER1
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RENT

Attribute	Description
Name	RENT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

INSURANCE

Attribute	Description
Name	INSURANCE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LOANPMNT

Attribute	Description
Name	LOANPMNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

OTHEXP

Attribute	Description
Name	OTHEXP
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

HOUSEVAL

Attribute	Description
Name	HOUSEVAL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CRCARD

Attribute	Description
Name	CRCARD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMTCCY1

Attribute	Description
Name	AMTCCY1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

EMPLOYER_DESC

Attribute	Description
Name	EMPLOYER_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

EMP_DESC

Attribute	Description
Name	EMP_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

Custcorp

Attribute	Description
Name	Custcorp
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CORPNAME

Attribute	Description
Name	CORPNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

NATIONID

Attribute	Description
Name	NATIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REGADD1

Attribute	Description
Name	REGADD1
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REGADD2

Attribute	Description
Name	REGADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REGADD3

Attribute	Description
Name	REGADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INCORPDT

Attribute	Description
Name	INCORPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CAPITAL

Attribute	Description
Name	CAPITAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NETWORTH

Attribute	Description
Name	NETWORTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INCORPCNTRY

Attribute	Description
Name	INCORPCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REGCNTRY

Attribute	Description
Name	REGCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CORPDESC

Attribute	Description
Name	CORPDESC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Custcorpdir

Attribute	Description
Name	Custcorpdir
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DIRNAME

Attribute	Description
Name	DIRNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR1

Attribute	Description
Name	NADDR1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR2

Attribute	Description
Name	NADDR2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR3

Attribute	Description
Name	NADDR3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR4

Attribute	Description
Name	NADDR4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRY

Attribute	Description
Name	COUNTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

TAXID

Attribute	Description
Name	TAXID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MOBNO

Attribute	**Description**
Name	MOBNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EMAIL

Attribute	**Description**
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Issuerdet

Attribute	**Description**
Name	Issuerdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OVERLIMIT

Attribute	**Description**
Name	OVERLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

OVERLMTCCY

Attribute	Description
Name	OVERLMTCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

Issuerlmts

Attribute	Description
Name	Issuerlmts
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CLTRLTYP

Attribute	Description
Name	CLTRLTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 70

TOP

LMTAMT

Attribute	Description
Name	LMTAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LMTCCY

Attribute	Description
Name	LMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ISSID

Attribute	Description
Name	ISSID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Custgrp

Attribute	Description
Name	Custgrp
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

GRPNO

Attribute	Description
Name	GRPNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RELATION

Attribute	Description
Name	RELATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Custshhold

Attribute	Description
Name	Custshhold
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SHHOLDID

Attribute	Description
Name	SHHOLDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SHHOLDPCT

Attribute	Description
Name	SHHOLDPCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHRHLDRNAME

Attribute	Description
Name	SHRHLDRNAME
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Clsccyrest

Attribute	Description
Name	Clsccyrest
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Bic

Attribute	Description
Name	Bic
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BICCD

Attribute	Description
Name	BICCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

Linkedac

Attribute	Description
Name	Linkedac
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

VRFD

Attribute	Description
Name	VRFD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LINKEDACCNO

Attribute	Description

Name	LINKEDACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LINKEDACCIBAN

Attribute	**Description**
Name	LINKEDACCIBAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LINKEDACCBIC

Attribute	**Description**
Name	LINKEDACCBIC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

JointVenture

Attribute	**Description**
Name	JointVenture
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PARTYID

Attribute	**Description**
Name	PARTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PARTYRATIO

Attribute	Description
Name	PARTYRATIO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Custdoc-Chklist

Attribute	Description
Name	Custdoc-Chklist
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHECKED

Attribute	Description

Name	CHECKED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Doctype-Remarks

Attribute	**Description**
Name	Doctype-Remarks
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARK1

Attribute	**Description**
Name	REMARK1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK2

Attribute	**Description**
Name	REMARK2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK3

Attribute	**Description**
Name	REMARK3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	225

TOP

REMARK4

Attribute	Description
Name	REMARK4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK5

Attribute	Description
Name	REMARK5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK6

Attribute	Description
Name	REMARK6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK7

Attribute	Description
Name	REMARK7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK8

Attribute	Description
Name	REMARK8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK9

Attribute	Description
Name	REMARK9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK10

Attribute	Description
Name	REMARK10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

Custmis

Attribute	Description
Name	Custmis
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP

Datatype	String
Description	Indicates Management Information System Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CUST

Attribute	Description
Name	CUST
Datatype	String
Description	Indicates the Customer.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Custchnglog

Attribute	Description
Name	Custchnglog
Datatype	
Description	Indicates the Customer Change Log.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	Indicates the Old MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	Indicates the New MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Baltrnsfrlog

Attribute	Description
Name	Baltrnsfrlog
Datatype	
Description	Indicates the Balance Transfer Log.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRN

Attribute	Description

Name	BRN
Datatype	String
Description	Indicates the Branch Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PRDCD

Attribute	**Description**
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FINYR

Attribute	**Description**
Name	FINYR
Datatype	String
Description	Indicates the Financial Year.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNDT

Attribute	**Description**
Name	TXNDT
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

GLCODE

Attribute	**Description**
Name	GLCODE
Datatype	String
Description	Indicates the GL Code.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	Indicates the Old MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	Indicates the New MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TRNIND

Attribute	Description
Name	TRNIND
Datatype	String
Description	Indicates Transfer Identification Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Dfltcd

Attribute	Description
Name	Dfltcd
Datatype	
Description	Indicates the Customer MIS Classes.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MISCD

Attribute	Description	
Name	MISCD	
Datatype	String	
Description	Indicates the MIS Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Dfltcda

Attribute	Description	
Name	Dfltcda	
Datatype		
Description	Indicates the Composite MIS Classes.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MISCLS

Attribute	Description	
Name	MISCLS	
Datatype	String	
Description	Indicates the MIS Class.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MISCD

Attribute	Description	
Name	MISCD	
Datatype	String	
Description	Indicates the MIS Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Custloghead

Attribute	Description
Name	Custloghead
Datatype	
Description	Indicates the Customer Log Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Jointcustomer

Attribute	Description
Name	Jointcustomer
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Custjoint

Attribute	Description
Name	Custjoint
Datatype	
Description	Indicates Customer Joint.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTPREFIX

Attribute	Description
Name	CUSTPREFIX
Datatype	String
Description	Indicates the Customer Prefix.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FRSTNAME

Attribute	Description
Name	FRSTNAME
Datatype	String
Description	Indicates the First Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MIDNAME

Attribute	Description
Name	MIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LASTNAME

Attribute	Description
Name	LASTNAME
Datatype	String
Description	Indicates the Last Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SEX

Attribute	Description
Name	SEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,F

TOP

PPNO

Attribute	Description
Name	PPNO
Datatype	String
Description	Indicates Passport Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PPTISSDT

Attribute	Description
Name	PPTISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PPTEXPDT

Attribute	Description
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADD3

Attribute	Description
Name	ADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255

TOP

SSN

Attribute	Description	
Name	SSN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	11

TOP

DECEASED

Attribute	Description	
Name	DECEASED	
Datatype	String	
Description	Indicates whether Deceased or not. The value should be either D or N.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,N

TOP

RESISTAT

Attribute	Description	
Name	RESISTAT	
Datatype	String	
Description	Indicates the Resistant Status. The value could be either R or N.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	R,N

TOP

Cust-Acc-Det

Attribute	Description	
Name	Cust-Acc-Det	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

Diary-Mst

Attribute	Description
Name	Diary-Mst
Datatype	
Description	Indicates Diary Master.
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	Indicates Instrument Number
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 16

TOP

UNTTYP

Attribute	Description
Name	UNTTYP
Datatype	String
Description	Indicates Unit Type
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

UNTVAL

Attribute	Description
Name	UNTVAL
Datatype	String

Description	Indicates Unit Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BRN

Attribute	**Description**
Name	BRN
Datatype	String
Description	Indicates the Branch Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INSTR

Attribute	**Description**
Name	INSTR
Datatype	String
Description	Indicates Instructions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

INSTRTYPE

Attribute	**Description**
Name	INSTRTYPE
Datatype	String
Description	Indicates Instruction Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

EXEDAYS

Attribute	**Description**
Name	EXEDAYS
Datatype	Number
Description	Indicates Execution Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXEMONTHS

Attribute	Description
Name	EXEMONTHS
Datatype	Number
Description	Indicates Execution Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXEYEARS

Attribute	Description
Name	EXEYEARS
Datatype	Number
Description	Indicates Execution Years
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MNTHENDFLG

Attribute	Description
Name	MNTHENDFLG
Datatype	String
Description	Indicates Month End Flag. Flag Can be either Y or N.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HLDRULE

Attribute	Description
Name	HLDRULE
Datatype	String
Description	Indicates Holiday Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRSTDUEDT

Attribute	Description
Name	FRSTDUEDT
Datatype	Date
Description	Indicates First Due Date.

Attributes	Attribute	Description
	minOccurs	0

TOP

NXTDUEDT

Attribute	Description
Name	NXTDUEDT
Datatype	Date
Description	Indicates Next Due Date
Attributes	Attribute: minOccurs — Description: 0

TOP

NXTEXEDT

Attribute	Description
Name	NXTEXEDT
Datatype	Date
Description	Indicates Next Execution Date.
Attributes	Attribute: minOccurs — Description: 0

TOP

CONDELEM

Attribute	Description
Name	CONDELEM
Datatype	String
Description	Indicates Condition Elements.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

OPRTR

Attribute	Description
Name	OPRTR
Datatype	String
Description	Indicates Operator.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2

TOP

CONDVAL

Attribute	Description
Name	CONDVAL

Datatype	Number
Description	Indicates Condition Value.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOFCR

Attribute	Description
Name	ACCOFCR
Datatype	String
Description	Indicates Account Officer.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPLINSTRTYP

Attribute	Description
Name	SPLINSTRTYP
Datatype	String
Description	Indicates Special Instruction Type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	Indicates Expiry Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPLINSTR

Attribute	Description
Name	SPLINSTR
Datatype	String
Description	Indicates Special Instructions.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Custaccdet

Attribute	Description
Name	Custaccdet
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkage details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String

Description	Indicates the customer
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RELATIONSHIP

Attribute	**Description**
Name	RELATIONSHIP
Datatype	String
Description	Indicate relations
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

INHERIT

Attribute	**Description**
Name	INHERIT
Datatype	String
Description	Indicate,include relationship Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DESCP

Attribute	**Description**
Name	DESCP
Datatype	String
Description	Indicates description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Custacdetail

Attribute	**Description**
Name	Custacdetail
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

CUSTTEXT

Attribute	Description
Name	CUSTTEXT
Datatype	
Description	Include customer details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	Indicates sequence number
Attributes	Attribute: minOccurs — Description: 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

TDESC

Attribute	Description

ORACLE

Name	TDESC
Datatype	String
Description	Indicate text description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

Sttms-Debit

Attribute	**Description**
Name	Sttms-Debit
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	Indicates the Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACTNO

Attribute	Description
Name	ACTNO
Datatype	String
Description	Indicates the Account Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Sttms-Detail

Attribute	Description
Name	Sttms-Detail
Datatype	
Description	Indicates Customer Details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description

Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REQUEST_REFERENCE_NO

Attribute	**Description**
Name	REQUEST_REFERENCE_NO
Datatype	String
Description	Indicates the Request Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CARDNO

Attribute	**Description**
Name	CARDNO
Datatype	String
Description	Indicates the Card Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 19

TOP

CUST_NO

Attribute	**Description**
Name	CUST_NO
Datatype	String
Description	Indicates the Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CARD_PRODUCT

Attribute	**Description**
Name	CARD_PRODUCT
Datatype	String
Description	Indicates the Product code.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRIMARY_CARD

Attribute	**Description**
Name	PRIMARY_CARD
Datatype	String
Description	Indicates the Primary Card Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NAME_ON_CARD

Attribute	**Description**
Name	NAME_ON_CARD
Datatype	String
Description	Indicates the Name on Card.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

OWNER_ID_NO

Attribute	**Description**
Name	OWNER_ID_NO
Datatype	String
Description	Indicates the Owner ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

CARD_ISSUED_DT

Attribute	**Description**
Name	CARD_ISSUED_DT
Datatype	Date
Description	Indicates the Card Issue Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CARD_EXPIRY_DT

Attribute	Description
Name	CARD_EXPIRY_DT
Datatype	Date
Description	Indicates the Card Expiry Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CARD_STATUS

Attribute	Description
Name	CARD_STATUS
Datatype	String
Description	Indicates the Card Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	Indicates the Record Stat.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTH_STAT

Attribute	Description
Name	AUTH_STAT
Datatype	String
Description	Indicates the Auth Stat.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CARD_BIN

Attribute	Description
Name	CARD_BIN

Datatype	String
Description	Indicates the Card Bin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CUST_AC_NO

Attribute	**Description**
Name	CUST_AC_NO
Datatype	String
Description	Indicates the Customer Account Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Extsys-Ws-Master

Attribute	**Description**
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	**Description**
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXTWSRESP

Attribute	**Description**
Name	EXTWSRESP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

Stvws-Cust-Trntax

Attribute	Description
Name	Stvws-Cust-Trntax
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Sttms-Cust-Trn-Tax

Attribute	Description
Name	Sttms-Cust-Trn-Tax
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TAX_SCHEME

Attribute	Description
Name	TAX_SCHEME
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

TXN_TAX_EXEMPTED

Attribute	**Description**
Name	TXN_TAX_EXEMPTED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TXN_TAX_EXEMPTION_PERCENT

Attribute	**Description**
Name	TXN_TAX_EXEMPTION_PERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXN_TAX_EFF_DATE

Attribute	**Description**
Name	TXN_TAX_EFF_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXN_TAX_EXEMPTION_REASON

Attribute	**Description**
Name	TXN_TAX_EXEMPTION_REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Customer-PK*
      - *CUSTNO*
    - *Customer-IO*
      - *CUSTNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Customer-PK

Attribute	Description
Name	Customer-PK
Datatype	
Description	

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Customer-IO

Attribute	Description
Name	Customer-IO
Datatype	
Description	

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.18.DeleteTDAmountBlock

DeleteTDAmountBlock

2.18.1.ST-DeleteTDAmountBlock-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-Full*
    - *ACC*
    - *AMTBLKNO*
    - *AMT*
    - *EXPDATE*
    - *REM*
    - *ABLKTYPE*
    - *REFERENCE_NO*
    - *HPCODE*
    - *EFFDATE*
    - *HOLDDESC*
    - *BRANCH*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Amount-Blocks-Full

Attribute	Description
Name	Amount-Blocks-Full
Datatype	
Description	

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTBLKNO

Attribute	Description	
Name	AMTBLKNO	
Datatype	String	
Description	Indicates the Amount Block Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

EXPDATE

Attribute	Description	
Name	EXPDATE	
Datatype	Date	
Description	Indicates the Expiry Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ABLKTYPE

Attribute	Description
Name	ABLKTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,S,P,E,A,C,B,D

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 40

TOP

HPCODE

Attribute	Description
Name	HPCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	Attribute: minOccurs, Description: 0

TOP

HOLDDESC

Attribute	Description
Name	HOLDDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 255

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length, Description: 3 Restrictions: pattern, Description: [a-zA-Z_0-9]{3}

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.18.2.ST-DeleteTDAmountBlock-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-IO*
    - *AMTBLKNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration — Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0 Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0 Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	Restrictions: maxLength — Description: 12 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	

Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Amount-Blocks-IO

Attribute	Description
Name	Amount-Blocks-IO
Datatype	
Description	

TOP

AMTBLKNO

Attribute	Description	
Name	AMTBLKNO	
Datatype	String	
Description	Indicates the Amount Block Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

2.18.3.ST-DeleteTDAmountBlock-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-Full*
    - *ACC*
    - *AMTBLKNO*
    - *AMT*
    - *EXPDATE*
    - *REM*
    - *ABLKTYPE*
    - *REFERENCE_NO*
    - *HPCODE*
    - *EFFDATE*
    - *HOLDDESC*
    - *BRANCH*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String

Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Amount-Blocks-Full

Attribute	Description
Name	Amount-Blocks-Full
Datatype	
Description	

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTBLKNO

Attribute	Description	
Name	AMTBLKNO	
Datatype	String	
Description	Indicates the Amount Block Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date
Attributes	Attribute: minOccurs, Description: 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 255

TOP

ABLKTYPE

Attribute	Description
Name	ABLKTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: F,S,P,E,A,C,B,D

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 40

TOP

HPCODE

Attribute	Description
Name	HPCODE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HOLDDESC

Attribute	Description
Name	HOLDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description

Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Amount-Blocks-PK*
      - *AMTBLKNO*
    - *Amount-Blocks-IO*
      - *AMTBLKNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Amount-Blocks-PK

Attribute	Description
Name	Amount-Blocks-PK
Datatype	
Description	

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Amount-Blocks-IO

Attribute	Description
Name	Amount-Blocks-IO
Datatype	
Description	

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.19.ModifyCustomer

ModifyCustomer

2.19.1.ST-ModifyCustomer-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Customer-Full*
    - *NAME*
    - *ADDRLN1*
    - *ADDRLN3*
    - *ADDRLN2*
    - *ADDRLN4*
    - *SWIFTCD*
    - *FAX*
    - *COUNTRY*
    - *NLTY*
    - *LANG*
    - *EXPCNTRY*
    - *UIDNAME*
    - *UIDVAL*
    - *LOC*
    - *FROZEN*

DEAD
WHRUNKN
GRPCD
CHGGRP
CUSTCLGGRP
TAXGROUP
CCATEG
EXPCAT
CUSTCLASSFN
FXNETTCUST
XREF
MEDIA
SSN
CIFSTAT
CIFSTATSNC
MAILRSREQD
CLSPARTICIPANT
CRMCUST
ISSUCUST
TRSRYCUST
CUSTNO
SNAME
LBRN
CTYPE
FULLNAME
AMLCUSTGRP
AMLREQD
FLGUTLTYPRVDR
UTLTYPRVDRID
CHKDIGITVALREQD
ALGID
CONSTAXCERTRQD
INDTAXCERTRQD
HOACNO
RISKPRFL
DRCAT
FTACCASOF
UDF1
UDF2
UDF3
UDF4
UDF5
UDFLBL1
UDFLBL2

UDFLBL3
UDFLBL4
UDFLBL5
FXCUSTCLRILIM
OVRLIM
FX_CLEAN_RISK
CRRATE
REVDT
LIMCCY
SECCUSTCLRILIM
SECCLRILIM
SECCUSTPSRILIM
SECPSRILIM
CUSTUNADV
RISKCATEG
CLSCCYALLWD
NETTREQD
LIABUNADV
MT920
RELPRICING
FLGJOINT
KYCSTAT
SSTAFF
UPTYPE
KYC_REFNO
JOINT_VENTURE
PRIVATE_CUSTOMER
LC_COLLAT_PCT
ISELCMCUST
ELCMCUSTNO
ALT_CUST_NO
DETERIORATION_DATE
CHQ_TAX_EXEMPT_1
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Custpersonal
- *TITLE*
- *FSTNAME*
- *MIDNAME*

LSTNAME
DOB
GUARDIAN
MINOR
SEX
NATIONID
PPTNO
PPTISSDT
PPTEXPDT
DADD1
DADD2
DADD3
TEL
FAX
EMAIL
PADD1
PADD2
PADD3
DCNTRY
PCNTRY
RESSTATUS
CUSTPREFIX1
CUSTPREFIX2
MOBNUM
SBMTAGEPROOF
CUST_COMM_MODE
LAST_UPD_DT
Custdomestic
- *EDUSTAT*
- *MARITALSTAT*
- *SPNAME*
- *SPEMPSTATUS*
- *DEPCHILD*
- *DEPOTH*
- *ACCOMODATE*
- *CUSTNO*

Custprof
- *EMPSTAT*
- *EMPTENURE*
- *RETIREAGE*
- *PREVDESIG*
- *PREVEMP*
- *CURRDESIG*
- *CURREMP*

ADD1
ADD2
ADD3
TEL
TELEX
FAX
EMAIL
SALARY
OTHER1
RENT
INSURANCE
LOANPMNT
OTHEXP
HOUSEVAL
CRCARD
CNTY
AMTCCY1
CUSTNO
EMPLOYER_DESC
EMP_DESC

Custcorp

CORPNAME
NATIONID
REGADD1
REGADD2
REGADD3
INCORPDT
CAPITAL
NETWORTH
INCORPCNTRY
REGCNTRY
AMTCCY
CORPDESC
CUSTNO
Custcorpdir

DIRNAME
TEL
NADDR1
NADDR2
NADDR3
NADDR4
ADDR1
ADDRS2
ADDRS3

COUNTRY
TAXID
MOBNO
EMAIL
Issuerdet
OVERLIMIT
CUSTNO
OVERLMTCCY
Issuerlmts
CLTRLTYP
LMTAMT
LMTCCY
ISSID
Custgrp
GRPNO
RELATION
Custshhold
SHHOLDID
SHHOLDPCT
SHRHLDRNAME
Clsccyrest
CCY
DESC
Bic
ACC
BICCD
Linkedac
VRFD
LINKEDACCNO
LINKEDACCIBAN
LINKEDACCBIC
JointVenture
PARTYID
PARTYRATIO
PARTYNAME
Custdoc-Chklist
DOCUMENT_TYPE
CHECKED
Doctype-Remarks
REMARK1
REMARK2
REMARK3
REMARK4
REMARK5

- *REMARK6*
- *REMARK7*
- *REMARK8*
- *REMARK9*
- *REMARK10*

Custmis

- *MISGRP*
- *CUST*
- *BRNCD*
- *Custchnglog*
  - *MISCLS*
  - *TXNDT*
  - *OLDMISCD*
  - *NWMISCD*
- *Baltrnsfrlog*
  - *BRN*
  - *PRDCD*
  - *FINYR*
  - *TXNDT*
  - *GLCODE*
  - *MISCLS*
  - *OLDMISCD*
  - *NWMISCD*
  - *TRNIND*
  - *CCY*
  - *AMT*
  - *XRATE*
- *Dfltcd*
  - *MISCLS*
  - *MISCD*
- *Dfltcda*
  - *MISCLS*
  - *MISCD*
- *Custloghead*

Jointcustomer

- *CUSTNO*
- *Custjoint*
  - *CUSTPREFIX*
  - *FRSTNAME*
  - *MIDNAME*
  - *LASTNAME*
  - *DOB*
  - *SEX*
  - *PPNO*

PPTISSDT
PPTEXPDT
ADD1
ADD2
ADD3
TEL
EMAIL
SSN
DECEASED
RESISTAT
Cust-Acc-Det
CUSTNO
Diary-Mst
INSTRNO
UNTTYP
UNTVAL
BRN
INSTR
INSTRTYPE
EXEDAYS
EXEMONTHS
EXEYEARS
MNTHENDFLG
HLDRULE
FRSTDUEDT
NXTDUEDT
NXTEXEDT
CONDELEM
OPRTR
CONDVAL
ACCOFCR
SPLINSTRTYP
EXPDT
SPLINSTR
Custaccdet
CUSTNO
BRNCD
Relationship-Linkage
CUSTOMER
RELATIONSHIP
INHERIT
DESCP
Custacdetail
CUSTNO

CUSTTEXT

SEQNO

CUSTNO

TDESC

UDFDETAILS

FLDNAM

FLDVAL

Sttms-Debit

BRANCH_CODE

CUST_NO

ACTNO

Sttms-Detail

BRANCH_CODE

REQUEST_REFERENCE_NO

CARDNO

CUST_NO

CARD_PRODUCT

PRIMARY_CARD

NAME_ON_CARD

OWNER_ID_NO

CARD_ISSUED_DT

CARD_EXPIRY_DT

CARD_STATUS

RECORD_STAT

AUTH_STAT

CARD_BIN

CUST_AC_NO

Extsys-Ws-Master

Extsys-Ws-Details

EXTWSRESP

USERREMARKS

Stvws-Cust-Trntax

CUSTOMER_NO

Sttms-Cust-Trn-Tax

TAX_SCHEME

TXN_TAX_EXEMPTED

TXN_TAX_EXEMPTION_PERCENT

TXN_TAX_EFF_DATE

TXN_TAX_EXEMPTION_REASON

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Customer-Full

Attribute	Description
Name	Customer-Full
Datatype	
Description	

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

ADDRLN1

Attribute	Description	
Name	ADDRLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN3

Attribute	Description	
Name	ADDRLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN2

Attribute	Description	
Name	ADDRLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN4

Attribute	Description
Name	ADDRLN4
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SWIFTCD

Attribute	Description
Name	SWIFTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FAX

Attribute	Description
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRY

Attribute	Description
Name	COUNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NLTY

Attribute	Description
Name	NLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	3

TOP

LANG

Attribute	Description	
Name	LANG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

TOP

EXPCNTRY

Attribute	Description	
Name	EXPCNTRY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

UIDNAME

Attribute	Description	
Name	UIDNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

UIDVAL

Attribute	Description	
Name	UIDVAL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

LOC

Attribute	Description
Name	LOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FROZEN

Attribute	Description
Name	FROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEAD

Attribute	Description
Name	DEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

WHRUNKN

Attribute	Description
Name	WHRUNKN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CHGGRP

Attribute	Description
Name	CHGGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CUSTCLGGRP

Attribute	Description
Name	CUSTCLGGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAXGROUP

Attribute	Description
Name	TAXGROUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CCATEG

Attribute	Description
Name	CCATEG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EXPCAT

Attribute	**Description**
Name	EXPCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUSTCLASSFN

Attribute	**Description**
Name	CUSTCLASSFN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

FXNETTCUST

Attribute	**Description**
Name	FXNETTCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

XREF

Attribute	**Description**
Name	XREF
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SSN

Attribute	Description
Name	SSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

CIFSTAT

Attribute	Description
Name	CIFSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CIFSTATSNC

Attribute	Description
Name	CIFSTATSNC
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAILRSREQD

Attribute	Description
Name	MAILRSREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLSPARTICIPANT

Attribute	Description
Name	CLSPARTICIPANT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CRMCUST

Attribute	Description
Name	CRMCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ISSUCUST

Attribute	Description
Name	ISSUCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRSRYCUST

Attribute	Description
Name	TRSRYCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

SNAME

Attribute	Description
Name	SNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 20

TOP

LBRN

Attribute	Description
Name	LBRN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CTYPE

Attribute	Description
Name	CTYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,C,B

TOP

FULLNAME

Attribute	Description
Name	FULLNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

AMLCUSTGRP

Attribute	Description
Name	AMLCUSTGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

AMLREQD

Attribute	Description
Name	AMLREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FLGUTLTYPRVDR

Attribute	Description
Name	FLGUTLTYPRVDR
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

UTLTYPRVDRID

Attribute	Description	
Name	UTLTYPRVDRID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHKDIGITVALREQD

Attribute	Description	
Name	CHKDIGITVALREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALGID

Attribute	Description	
Name	ALGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CONSTAXCERTRQD

Attribute	Description	
Name	CONSTAXCERTRQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

INDTAXCERTRQD

Attribute	Description
Name	INDTAXCERTRQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

HOACNO

Attribute	Description
Name	HOACNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RISKPRFL

Attribute	Description
Name	RISKPRFL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

DRCAT

Attribute	Description
Name	DRCAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FTACCASOF

Attribute	Description
Name	FTACCASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,M,D

TOP

UDF1

Attribute	Description
Name	UDF1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDF2

Attribute	Description
Name	UDF2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDF3

Attribute	Description
Name	UDF3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

UDF4

Attribute	Description
Name	UDF4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

UDF5

Attribute	Description
Name	UDF5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDFLBL1

Attribute	Description
Name	UDFLBL1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDFLBL2

Attribute	Description
Name	UDFLBL2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDFLBL3

Attribute	Description
Name	UDFLBL3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL4

Attribute	Description
Name	UDFLBL4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL5

Attribute	Description
Name	UDFLBL5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

FXCUSTCLRILIM

Attribute	Description
Name	FXCUSTCLRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OVRLIM

Attribute	Description
Name	OVRLIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FX_CLEAN_RISK

Attribute	Description
Name	FX_CLEAN_RISK
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CRRATE

Attribute	Description
Name	CRRATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

REVDT

Attribute	Description
Name	REVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIMCCY

Attribute	Description
Name	LIMCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SECCUSTCLRILIM

Attribute	Description
Name	SECCUSTCLRILIM
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SECCLRILIM

Attribute	Description
Name	SECCLRILIM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SECCUSTPSRILIM

Attribute	Description
Name	SECCUSTPSRILIM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SECPSRILIM

Attribute	Description
Name	SECPSRILIM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CUSTUNADV

Attribute	Description
Name	CUSTUNADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

RISKCATEG

Attribute	Description
Name	RISKCATEG
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CLSCCYALLWD

Attribute	**Description**	
Name	CLSCCYALLWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D

TOP

NETTREQD

Attribute	**Description**	
Name	NETTREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIABUNADV

Attribute	**Description**	
Name	LIABUNADV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MT920

Attribute	**Description**	
Name	MT920	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RELPRICING

Attribute	**Description**
Name	RELPRICING
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FLGJOINT

Attribute	**Description**
Name	FLGJOINT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

KYCSTAT

Attribute	**Description**
Name	KYCSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,N,F

TOP

SSTAFF

Attribute	**Description**
Name	SSTAFF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UPTYPE

Attribute	Description
Name	UPTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

KYC_REFNO

Attribute	Description
Name	KYC_REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

JOINT_VENTURE

Attribute	Description
Name	JOINT_VENTURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIVATE_CUSTOMER

Attribute	Description
Name	PRIVATE_CUSTOMER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LC_COLLAT_PCT

Attribute	Description
Name	LC_COLLAT_PCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISELCMCUST

Attribute	Description
Name	ISELCMCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ELCMCUSTNO

Attribute	Description
Name	ELCMCUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ALT_CUST_NO

Attribute	Description
Name	ALT_CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DETERIORATION_DATE

Attribute	Description
Name	DETERIORATION_DATE
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CHQ_TAX_EXEMPT_1

Attribute	Description	
Name	CHQ_TAX_EXEMPT_1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Custpersonal

Attribute	Description
Name	Custpersonal

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TITLE

Attribute	Description
Name	TITLE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FSTNAME

Attribute	Description
Name	FSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MIDNAME

Attribute	Description
Name	MIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LSTNAME

Attribute	Description
Name	LSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

GUARDIAN

Attribute	Description
Name	GUARDIAN
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 105

TOP

MINOR

Attribute	Description
Name	MINOR
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

SEX

Attribute	Description
Name	SEX
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: M,F

TOP

NATIONID

Attribute	Description
Name	NATIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PPTNO

Attribute	Description
Name	PPTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PPTISSDT

Attribute	Description
Name	PPTISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PPTEXPDT

Attribute	Description
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DADD1

Attribute	Description
Name	DADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

DADD2

Attribute	Description	
Name	DADD2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

DADD3

Attribute	Description	
Name	DADD3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

TEL

Attribute	Description	
Name	TEL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

FAX

Attribute	Description	
Name	FAX	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PADD1

Attribute	Description
Name	PADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PADD2

Attribute	Description
Name	PADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PADD3

Attribute	Description
Name	PADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DCNTRY

Attribute	Description
Name	DCNTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

PCNTRY

Attribute	Description
Name	PCNTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

RESSTATUS

Attribute	Description
Name	RESSTATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: R,N

TOP

CUSTPREFIX1

Attribute	Description
Name	CUSTPREFIX1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

CUSTPREFIX2

Attribute	Description
Name	CUSTPREFIX2

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

MOBNUM

Attribute	**Description**
Name	MOBNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SBMTAGEPROOF

Attribute	**Description**
Name	SBMTAGEPROOF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,P,V

TOP

CUST_COMM_MODE

Attribute	**Description**
Name	CUST_COMM_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,E

TOP

LAST_UPD_DT

Attribute	**Description**
Name	LAST_UPD_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Custdomestic

Attribute	Description
Name	Custdomestic
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EDUSTAT

Attribute	Description
Name	EDUSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,U,G,P

TOP

MARITALSTAT

Attribute	Description
Name	MARITALSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,M,D,R,P,E,T

TOP

SPNAME

Attribute	Description
Name	SPNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SPEMPSTATUS

Attribute	Description
Name	SPEMPSTATUS

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / F,T,S,U,R,P,N,O

TOP

DEPCHILD

Attribute	**Description**
Name	DEPCHILD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DEPOTH

Attribute	**Description**
Name	DEPOTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCOMODATE

Attribute	**Description**
Name	ACCOMODATE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,C,O

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Custprof

Attribute	Description
Name	Custprof
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EMPSTAT

Attribute	Description
Name	EMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

EMPTENURE

Attribute	Description
Name	EMPTENURE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RETIREAGE

Attribute	Description
Name	RETIREAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PREVDESIG

Attribute	Description
Name	PREVDESIG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

PREVEMP

Attribute	Description
Name	PREVEMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CURRDESIG

Attribute	Description
Name	CURRDESIG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CURREMP

Attribute	Description
Name	CURREMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADD3

Attribute	Description
Name	ADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TELEX

Attribute	Description
Name	TELEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FAX

Attribute	Description
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

SALARY

Attribute	Description
Name	SALARY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHER1

Attribute	Description
Name	OTHER1
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RENT

Attribute	Description
Name	RENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSURANCE

Attribute	Description
Name	INSURANCE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LOANPMNT

Attribute	Description
Name	LOANPMNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

OTHEXP

Attribute	Description
Name	OTHEXP
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

HOUSEVAL

Attribute	Description
Name	HOUSEVAL
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

CRCARD

Attribute	Description
Name	CRCARD
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMTCCY1

Attribute	Description
Name	AMTCCY1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

EMPLOYER_DESC

Attribute	Description
Name	EMPLOYER_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

EMP_DESC

Attribute	Description

Name	EMP_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Custcorp

Attribute	**Description**
Name	Custcorp
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CORPNAME

Attribute	**Description**
Name	CORPNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

NATIONID

Attribute	**Description**
Name	NATIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REGADD1

Attribute	**Description**
Name	REGADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

REGADD2

Attribute	Description	
Name	REGADD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REGADD3

Attribute	Description	
Name	REGADD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INCORPDT

Attribute	Description	
Name	INCORPDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CAPITAL

Attribute	Description	
Name	CAPITAL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETWORTH

Attribute	Description
Name	NETWORTH

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INCORPCNTRY

Attribute	**Description**
Name	INCORPCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REGCNTRY

Attribute	**Description**
Name	REGCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMTCCY

Attribute	**Description**
Name	AMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CORPDESC

Attribute	**Description**
Name	CORPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255

TOP

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

TOP

Custcorpdir

Attribute	Description	
Name	Custcorpdir	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

DIRNAME

Attribute	Description	
Name	DIRNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

TEL

Attribute	Description	
Name	TEL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

NADDR1

Attribute	Description
Name	NADDR1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR2

Attribute	Description
Name	NADDR2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR3

Attribute	Description
Name	NADDR3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR4

Attribute	Description
Name	NADDR4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDR1

Attribute	Description

Name	ADDR1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRY

Attribute	Description
Name	COUNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXID

Attribute	Description
Name	TAXID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MOBNO

Attribute	Description
Name	MOBNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Issuerdet

Attribute	Description
Name	Issuerdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OVERLIMIT

Attribute	Description
Name	OVERLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OVERLMTCCY

Attribute	**Description**
Name	OVERLMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Issuerlmts

Attribute	**Description**
Name	Issuerlmts
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CLTRLTYP

Attribute	**Description**
Name	CLTRLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 70

TOP

LMTAMT

Attribute	**Description**
Name	LMTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LMTCCY

Attribute	Description
Name	LMTCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ISSID

Attribute	Description
Name	ISSID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

Custgrp

Attribute	Description
Name	Custgrp
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

GRPNO

Attribute	Description
Name	GRPNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

RELATION

Attribute	Description

Name	RELATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Custshhold

Attribute	**Description**
Name	Custshhold
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SHHOLDID

Attribute	**Description**
Name	SHHOLDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SHHOLDPCT

Attribute	**Description**
Name	SHHOLDPCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHRHLDRNAME

Attribute	**Description**
Name	SHRHLDRNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Clsccyrest

Attribute	Description
Name	Clsccyrest
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Bic

Attribute	Description
Name	Bic
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC

Attribute	Description
Name	ACC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BICCD

Attribute	Description
Name	BICCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

Linkedac

Attribute	Description
Name	Linkedac
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

VRFD

Attribute	Description
Name	VRFD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LINKEDACCNO

Attribute	Description
Name	LINKEDACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	30

TOP

LINKEDACCIBAN

Attribute	Description	
Name	LINKEDACCIBAN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

LINKEDACCBIC

Attribute	Description	
Name	LINKEDACCBIC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

JointVenture

Attribute	Description	
Name	JointVenture	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

PARTYID

Attribute	Description	
Name	PARTYID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

TOP

PARTYRATIO

Attribute	Description
Name	PARTYRATIO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Custdoc-Chklist

Attribute	Description
Name	Custdoc-Chklist
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHECKED

Attribute	Description
Name	CHECKED
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Doctype-Remarks

Attribute	Description
Name	Doctype-Remarks
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARK1

Attribute	Description
Name	REMARK1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK2

Attribute	Description
Name	REMARK2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK3

Attribute	Description
Name	REMARK3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK4

Attribute	Description
Name	REMARK4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK5

Attribute	Description
Name	REMARK5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK6

Attribute	Description
Name	REMARK6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK7

Attribute	Description
Name	REMARK7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK8

Attribute	Description
Name	REMARK8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK9

Attribute	Description
Name	REMARK9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK10

Attribute	Description
Name	REMARK10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

Custmis

Attribute	Description
Name	Custmis
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates Management Information System Group.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CUST

Attribute	**Description**
Name	CUST
Datatype	String
Description	Indicates the Customer.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRNCD

Attribute	**Description**
Name	BRNCD
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Custchnglog

Attribute	**Description**
Name	Custchnglog
Datatype	
Description	Indicates the Customer Change Log.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	**Description**
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	Indicates the Old MIS Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	Indicates the New MIS Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Baltrnsfrlog

Attribute	Description
Name	Baltrnsfrlog
Datatype	
Description	Indicates the Balance Transfer Log.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String

Description	Indicates the Branch Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDCD

Attribute	**Description**
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	**Description**
Name	FINYR
Datatype	String
Description	Indicates the Financial Year.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNDT

Attribute	**Description**
Name	TXNDT
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

GLCODE

Attribute	**Description**
Name	GLCODE
Datatype	String
Description	Indicates the GL Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	Indicates the Old MIS Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	Indicates the New MIS Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TRNIND

Attribute	Description
Name	TRNIND
Datatype	String
Description	Indicates Transfer Identification Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	Attribute: minOccurs — Description: 0

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate.
Attributes	Attribute: minOccurs — Description: 0

TOP

Dfltcd

Attribute	Description
Name	Dfltcd
Datatype	
Description	Indicates the Customer MIS Classes.
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	Attribute: minOccurs — Description: 1

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCD

Attribute	**Description**
Name	MISCD
Datatype	String
Description	Indicates the MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Dfltcda

Attribute	**Description**
Name	Dfltcda
Datatype	
Description	Indicates the Composite MIS Classes.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	**Description**
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCD

Attribute	**Description**
Name	MISCD
Datatype	String
Description	Indicates the MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Custloghead

Attribute	Description
Name	Custloghead
Datatype	
Description	Indicates the Customer Log Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Jointcustomer

Attribute	Description
Name	Jointcustomer
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Custjoint

Attribute	Description
Name	Custjoint
Datatype	
Description	Indicates Customer Joint.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTPREFIX

Attribute	Description
Name	CUSTPREFIX
Datatype	String
Description	Indicates the Customer Prefix.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FRSTNAME

Attribute	**Description**
Name	FRSTNAME
Datatype	String
Description	Indicates the First Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MIDNAME

Attribute	**Description**
Name	MIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LASTNAME

Attribute	**Description**
Name	LASTNAME
Datatype	String
Description	Indicates the Last Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOB

Attribute	**Description**
Name	DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SEX

Attribute	Description
Name	SEX
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,F

TOP

PPNO

Attribute	Description
Name	PPNO
Datatype	String
Description	Indicates Passport Number.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

PPTISSDT

Attribute	Description
Name	PPTISSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PPTEXPDT

Attribute	Description
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ADD2

Attribute	Description	
Name	ADD2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ADD3

Attribute	Description	
Name	ADD3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

TEL

Attribute	Description	
Name	TEL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

EMAIL

Attribute	Description	
Name	EMAIL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TOP

SSN

Attribute	Description
Name	SSN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

DECEASED

Attribute	Description
Name	DECEASED
Datatype	String
Description	Indicates whether Deceased or not. The value should be either D or N.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,N

TOP

RESISTAT

Attribute	Description
Name	RESISTAT
Datatype	String
Description	Indicates the Resistant Status. The value could be either R or N.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: R,N

TOP

Cust-Acc-Det

Attribute	Description
Name	Cust-Acc-Det
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Diary-Mst

Attribute	**Description**
Name	Diary-Mst
Datatype	
Description	Indicates Diary Master.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSTRNO

Attribute	**Description**
Name	INSTRNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

UNTTYP

Attribute	**Description**
Name	UNTTYP
Datatype	String
Description	Indicates Unit Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

UNTVAL

Attribute	**Description**
Name	UNTVAL
Datatype	String
Description	Indicates Unit Value
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch Code.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

INSTR

Attribute	Description
Name	INSTR
Datatype	String
Description	Indicates Instructions
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

INSTRTYPE

Attribute	Description
Name	INSTRTYPE
Datatype	String
Description	Indicates Instruction Type
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

EXEDAYS

Attribute	Description
Name	EXEDAYS
Datatype	Number
Description	Indicates Execution Days
Attributes	Attribute: minOccurs — Description: 0

TOP

EXEMONTHS

Attribute	Description
Name	EXEMONTHS
Datatype	Number
Description	Indicates Execution Months
Attributes	Attribute: minOccurs, Description: 0

TOP

EXEYEARS

Attribute	Description
Name	EXEYEARS
Datatype	Number
Description	Indicates Execution Years
Attributes	Attribute: minOccurs, Description: 0

TOP

MNTHENDFLG

Attribute	Description
Name	MNTHENDFLG
Datatype	String
Description	Indicates Month End Flag. Flag Can be either Y or N.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

HLDRULE

Attribute	Description
Name	HLDRULE
Datatype	String
Description	Indicates Holiday Rule
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 1

TOP

FRSTDUEDT

Attribute	Description
Name	FRSTDUEDT
Datatype	Date
Description	Indicates First Due Date.
Attributes	Attribute: minOccurs, Description: 0

TOP

NXTDUEDT

Attribute	Description
Name	NXTDUEDT
Datatype	Date
Description	Indicates Next Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NXTEXEDT

Attribute	Description
Name	NXTEXEDT
Datatype	Date
Description	Indicates Next Execution Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONDELEM

Attribute	Description
Name	CONDELEM
Datatype	String
Description	Indicates Condition Elements.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

OPRTR

Attribute	Description
Name	OPRTR
Datatype	String
Description	Indicates Operator.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

CONDVAL

Attribute	Description
Name	CONDVAL
Datatype	Number
Description	Indicates Condition Value.

Attributes	Attribute	Description
	minOccurs	0

TOP

ACCOFCR

Attribute	Description	
Name	ACCOFCR	
Datatype	String	
Description	Indicates Account Officer.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SPLINSTRTYP

Attribute	Description	
Name	SPLINSTRTYP	
Datatype	String	
Description	Indicates Special Instruction Type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

EXPDT

Attribute	Description	
Name	EXPDT	
Datatype	Date	
Description	Indicates Expiry Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPLINSTR

Attribute	Description	
Name	SPLINSTR	
Datatype	String	
Description	Indicates Special Instructions.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Custaccdet

Attribute	Description
Name	Custaccdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkage details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Indicates the customer

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Indicate relations
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicate,include relationship Y:yes N:no
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	Indicates description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Custacdetail

Attribute	Description
Name	Custacdetail
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTTEXT

Attribute	Description
Name	CUSTTEXT
Datatype	
Description	Include customer details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	Indicates sequence number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String

Description	Indicate text description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Sttms-Debit

Attribute	**Description**
Name	Sttms-Debit
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	Indicates the Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACTNO

Attribute	Description
Name	ACTNO
Datatype	String
Description	Indicates the Account Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Sttms-Detail

Attribute	Description
Name	Sttms-Detail
Datatype	
Description	Indicates Customer Details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description

Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REQUEST_REFERENCE_NO

Attribute	**Description**
Name	REQUEST_REFERENCE_NO
Datatype	String
Description	Indicates the Request Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CARDNO

Attribute	**Description**
Name	CARDNO
Datatype	String
Description	Indicates the Card Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 19

TOP

CUST_NO

Attribute	**Description**
Name	CUST_NO
Datatype	String
Description	Indicates the Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CARD_PRODUCT

Attribute	**Description**
Name	CARD_PRODUCT
Datatype	String
Description	Indicates the Product code.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRIMARY_CARD

Attribute	**Description**
Name	PRIMARY_CARD
Datatype	String
Description	Indicates the Primary Card Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NAME_ON_CARD

Attribute	**Description**
Name	NAME_ON_CARD
Datatype	String
Description	Indicates the Name on Card.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

OWNER_ID_NO

Attribute	**Description**
Name	OWNER_ID_NO
Datatype	String
Description	Indicates the Owner ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

CARD_ISSUED_DT

Attribute	**Description**
Name	CARD_ISSUED_DT
Datatype	Date
Description	Indicates the Card Issue Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CARD_EXPIRY_DT

Attribute	Description
Name	CARD_EXPIRY_DT
Datatype	Date
Description	Indicates the Card Expiry Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CARD_STATUS

Attribute	Description
Name	CARD_STATUS
Datatype	String
Description	Indicates the Card Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	Indicates the Record Stat.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTH_STAT

Attribute	Description
Name	AUTH_STAT
Datatype	String
Description	Indicates the Auth Stat.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CARD_BIN

Attribute	Description
Name	CARD_BIN

Datatype	String
Description	Indicates the Card Bin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CUST_AC_NO

Attribute	**Description**
Name	CUST_AC_NO
Datatype	String
Description	Indicates the Customer Account Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Extsys-Ws-Master

Attribute	**Description**
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	**Description**
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXTWSRESP

Attribute	**Description**
Name	EXTWSRESP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

Stvws-Cust-Trntax

Attribute	Description
Name	Stvws-Cust-Trntax
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Sttms-Cust-Trn-Tax

Attribute	Description
Name	Sttms-Cust-Trn-Tax
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TAX_SCHEME

Attribute	Description
Name	TAX_SCHEME
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

TXN_TAX_EXEMPTED

Attribute	**Description**
Name	TXN_TAX_EXEMPTED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TXN_TAX_EXEMPTION_PERCENT

Attribute	**Description**
Name	TXN_TAX_EXEMPTION_PERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXN_TAX_EFF_DATE

Attribute	**Description**
Name	TXN_TAX_EFF_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXN_TAX_EXEMPTION_REASON

Attribute	**Description**
Name	TXN_TAX_EXEMPTION_REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

2.19.2.ST-ModifyCustomer-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Customer-IO*
    - *NAME*
    - *ADDRLN1*
    - *ADDRLN3*
    - *ADDRLN2*
    - *ADDRLN4*
    - *SWIFTCD*
    - *FAX*
    - *COUNTRY*
    - *NLTY*
    - *LANG*
    - *EXPCNTRY*
    - *UIDNAME*
    - *UIDVAL*
    - *LOC*
    - *FROZEN*
    - *DEAD*
    - *WHRUNKN*
    - *GRPCD*

CHGGRP
CUSTCLGGRP
TAXGROUP
CCATEG
EXPCAT
CUSTCLASSFN
FXNETTCUST
XREF
MEDIA
SSN
CIFSTAT
CIFSTATSNC
MAILRSREQD
CLSPARTICIPANT
CRMCUST
ISSUCUST
TRSRYCUST
CUSTNO
SNAME
LBRN
CTYPE
LIABID
FULLNAME
AMLCUSTGRP
AMLREQD
FLGUTLTYPRVDR
UTLTYPRVDRID
CHKDIGITVALREQD
ALGID
CONSTAXCERTRQD
INDTAXCERTRQD
HOACNO
RISKPRFL
DRCAT
FTACCASOF
UDF1
UDF2
UDF3
UDF4
UDF5
UDFLBL1
UDFLBL2
UDFLBL3
UDFLBL4

UDFLBL5
FXCUSTCLRILIM
OVRLIM
FX_CLEAN_RISK
CRRATE
REVDT
LIMCCY
SECCUSTCLRILIM
SECCLRILIM
SECCUSTPSRILIM
SECPSRILIM
CUSTUNADV
RISKCATEG
CLSCCYALLWD
NETTREQD
LIABUNADV
MT920
RELPRICING
FLGJOINT
KYCSTAT
SSTAFF
KYC_REFNO
JOINT_VENTURE
PRIVATE_CUSTOMER
LC_COLLAT_PCT
ISELCMCUST
ALT_CUST_NO
DETERIORATION_DATE
MAKER
MAKERSTAMP
Custpersonal
- *TITLE*
- *FSTNAME*
- *MIDNAME*
- *LSTNAME*
- *DOB*
- *GUARDIAN*
- *MINOR*
- *SEX*
- *NATIONID*
- *PPTNO*
- *PPTISSDT*
- *PPTEXPDT*
- *DADD1*

DADD2
DADD3
TEL
FAX
EMAIL
PADD1
PADD2
PADD3
DCNTRY
PCNTRY
RESSTATUS
CUSTPREFIX1
CUSTPREFIX2
MOBNUM
SBMTAGEPROOF
CUST_COMM_MODE
Custdomestic
- *EDUSTAT*
- *MARITALSTAT*
- *SPNAME*
- *SPEMPSTATUS*
- *DEPCHILD*
- *DEPOTH*
- *ACCOMODATE*

Custprof
- *EMPSTAT*
- *EMPTENURE*
- *RETIREAGE*
- *PREVDESIG*
- *PREVEMP*
- *CURRDESIG*
- *CURREMP*
- *ADD1*
- *ADD2*
- *ADD3*
- *TEL*
- *TELEX*
- *FAX*
- *EMAIL*
- *SALARY*
- *OTHER1*
- *RENT*
- *INSURANCE*
- *LOANPMNT*

OTHEXP
HOUSEVAL
CRCARD
CNTY
AMTCCY1
Custcorp
CORPNAME
NATIONID
REGADD1
REGADD2
REGADD3
INCORPDT
CAPITAL
NETWORTH
INCORPCNTRY
REGCNTRY
AMTCCY
CORPDESC
Custcorpdir
DIRNAME
CUSTNO
TEL
NADDR1
NADDR2
NADDR3
NADDR4
ADDR1
ADDRS2
ADDRS3
COUNTRY
TAXID
MOBNO
EMAIL
Issuerdet
OVERLIMIT
OVERLMTCCY
Issuerlmts
CLTRLTYP
LMTAMT
LMTCCY
ISSID
Custgrp
GRPNO
RELATION

Custshhold

- *SHHOLDID*
- *SHHOLDPCT*
- *SHRHLDRNAME*

Clsccyrest

- *CCY*
- *DESC*

Bic

- *ACC*
- *BICCD*

Linkedac

- *VRFD*
- *LINKEDACCNO*
- *LINKEDACCIBAN*
- *LINKEDACCBIC*

JointVenture

- *CUSTOMER_NO*
- *PARTYID*
- *PARTYRATIO*
- *PARTYNAME*

Custdoc-Chklist

- *CUSTOMER_NO*
- *DOCUMENT_TYPE*
- *CHECKED*

Doctype-Remarks

- *CUSTOMER_NO*
- *REMARK1*
- *REMARK2*
- *REMARK3*
- *REMARK4*
- *REMARK5*
- *REMARK6*
- *REMARK7*
- *REMARK8*
- *REMARK9*
- *REMARK10*

Custmis

- *MISGRP*
- *CUSTMIS1*
- *CUSTMIS2*
- *CUSTMIS3*
- *CUSTMIS4*
- *CUSTMIS5*
- *CUSTMIS6*

CUSTMIS7
CUSTMIS8
CUSTMIS9
CUSTMIS10
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
CUSTNO
Custchnglog
MISCLS
TXNDT
OLDMISCD
NWMISCD
Baltrnsfrlog
BRN
PRDCD
FINYR
TXNDT
GLCODE
MISCLS
OLDMISCD
NWMISCD
TRNIND
CCY
XRATE
Dfltcd
Dfltcda
Jointcustomer
CUSTNO
Custjoint
CUSTPREFIX
FRSTNAME
MIDNAME
LASTNAME
DOB
SEX
PPNO

PPTISSDT

PPTEXPDT

ADD1

ADD2

ADD3

TEL

EMAIL

DECEASED

RESISTAT

Cust-Acc-Det

CUSTNO

Diary-Mst

INSTRNO

UNTTYP

UNTVAL

BRN

INSTR

INSTRTYPE

EXEDAYS

EXEMONTHS

EXEYEARS

MNTHENDFLG

HLDRULE

FRSTDUEDT

NXTDUEDT

NXTEXEDT

CONDELEM

OPRTR

CONDVAL

ACCOFCR

SPLINSTRTYP

EXPDT

SPLINSTR

Custaccdet

CUSTNO

Relationship-Linkage

CUSTOMER

RELATIONSHIP

INHERIT

DESCP

Custacdetail

CUSTNO

CUSTTEXT

SEQNO

CUSTNO

TDESC

UDFDETAILS

FLDNAM

FLDVAL

Sttms-Debit

BRANCH_CODE

CUST_NO

ACTNO

Extsys-Ws-Master

KEYID

Stvws-Cust-Trntax

CUSTOMER_NO

Sttms-Cust-Trn-Tax

TAX_SCHEME

TXN_TAX_EXEMPTED

TXN_TAX_EXEMPTION_PERCENT

TXN_TAX_EFF_DATE

TXN_TAX_EXEMPTION_REASON

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Customer-IO

Attribute	Description
Name	Customer-IO
Datatype	
Description	

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

ADDRLN1

Attribute	Description	
Name	ADDRLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN3

Attribute	Description
Name	ADDRLN3
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN2

Attribute	Description	
Name	ADDRLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN4

Attribute	Description	
Name	ADDRLN4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SWIFTCD

Attribute	Description	
Name	SWIFTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

FAX

Attribute	Description	
Name	FAX	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

COUNTRY

Attribute	Description	
Name	COUNTRY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

NLTY

Attribute	Description	
Name	NLTY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

LANG

Attribute	Description	
Name	LANG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

EXPCNTRY

Attribute	Description	
Name	EXPCNTRY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

UIDNAME

Attribute	Description
Name	UIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

UIDVAL

Attribute	Description
Name	UIDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOC

Attribute	Description
Name	LOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FROZEN

Attribute	Description
Name	FROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEAD

Attribute	Description
Name	DEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

WHRUNKN

Attribute	Description
Name	WHRUNKN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CHGGRP

Attribute	Description
Name	CHGGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CUSTCLGGRP

Attribute	Description
Name	CUSTCLGGRP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAXGROUP

Attribute	**Description**
Name	TAXGROUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CCATEG

Attribute	**Description**
Name	CCATEG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EXPCAT

Attribute	**Description**
Name	EXPCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUSTCLASSFN

Attribute	**Description**
Name	CUSTCLASSFN
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

FXNETTCUST

Attribute	Description
Name	FXNETTCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SSN

Attribute	Description
Name	SSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	11

TOP

CIFSTAT

Attribute	Description	
Name	CIFSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

CIFSTATSNC

Attribute	Description	
Name	CIFSTATSNC	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

MAILRSREQD

Attribute	Description	
Name	MAILRSREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

CLSPARTICIPANT

Attribute	Description	
Name	CLSPARTICIPANT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

CRMCUST

Attribute	Description
Name	CRMCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ISSUCUST

Attribute	Description
Name	ISSUCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TRSRYCUST

Attribute	Description
Name	TRSRYCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

SNAME

Attribute	Description
Name	SNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LBRN

Attribute	**Description**
Name	LBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CTYPE

Attribute	**Description**
Name	CTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,C,B

TOP

LIABID

Attribute	**Description**
Name	LIABID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

FULLNAME

Attribute	**Description**
Name	FULLNAME
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

AMLCUSTGRP

Attribute	Description
Name	AMLCUSTGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

AMLREQD

Attribute	Description
Name	AMLREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FLGUTLTYPRVDR

Attribute	Description
Name	FLGUTLTYPRVDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UTLTYPRVDRID

Attribute	Description
Name	UTLTYPRVDRID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

CHKDIGITVALREQD

Attribute	Description	
Name	CHKDIGITVALREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALGID

Attribute	Description	
Name	ALGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CONSTAXCERTRQD

Attribute	Description	
Name	CONSTAXCERTRQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INDTAXCERTRQD

Attribute	Description	
Name	INDTAXCERTRQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

HOACNO

Attribute	Description
Name	HOACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RISKPRFL

Attribute	Description
Name	RISKPRFL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DRCAT

Attribute	Description
Name	DRCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FTACCASOF

Attribute	Description
Name	FTACCASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,M,D

TOP

UDF1

Attribute	Description
Name	UDF1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDF2

Attribute	Description
Name	UDF2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDF3

Attribute	Description
Name	UDF3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

UDF4

Attribute	Description
Name	UDF4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

UDF5

Attribute	Description
Name	UDF5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL1

Attribute	Description
Name	UDFLBL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL2

Attribute	Description
Name	UDFLBL2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL3

Attribute	Description
Name	UDFLBL3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL4

Attribute	Description
Name	UDFLBL4
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

UDFLBL5

Attribute	Description
Name	UDFLBL5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

FXCUSTCLRILIM

Attribute	Description
Name	FXCUSTCLRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OVRLIM

Attribute	Description
Name	OVRLIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FX_CLEAN_RISK

Attribute	Description
Name	FX_CLEAN_RISK
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CRRATE

Attribute	Description
Name	CRRATE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

REVDT

Attribute	Description
Name	REVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIMCCY

Attribute	Description
Name	LIMCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SECCUSTCLRILIM

Attribute	Description
Name	SECCUSTCLRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCLRILIM

Attribute	Description
Name	SECCLRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCUSTPSRILIM

Attribute	Description
Name	SECCUSTPSRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECPSRILIM

Attribute	Description
Name	SECPSRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTUNADV

Attribute	Description
Name	CUSTUNADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RISKCATEG

Attribute	Description
Name	RISKCATEG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CLSCCYALLWD

Attribute	Description
Name	CLSCCYALLWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

NETTREQD

Attribute	**Description**
Name	NETTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIABUNADV

Attribute	**Description**
Name	LIABUNADV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MT920

Attribute	**Description**
Name	MT920
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RELPRICING

Attribute	**Description**
Name	RELPRICING
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FLGJOINT

Attribute	Description
Name	FLGJOINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

KYCSTAT

Attribute	Description
Name	KYCSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / V,N,F

TOP

SSTAFF

Attribute	Description
Name	SSTAFF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

KYC_REFNO

Attribute	Description
Name	KYC_REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

JOINT_VENTURE

Attribute	Description
Name	JOINT_VENTURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIVATE_CUSTOMER

Attribute	Description
Name	PRIVATE_CUSTOMER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LC_COLLAT_PCT

Attribute	Description
Name	LC_COLLAT_PCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISELCMCUST

Attribute	Description
Name	ISELCMCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALT_CUST_NO

Attribute	Description
Name	ALT_CUST_NO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

DETERIORATION_DATE

Attribute	Description	
Name	DETERIORATION_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Custpersonal

Attribute	Description	
Name	Custpersonal	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TITLE

Attribute	Description
Name	TITLE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FSTNAME

Attribute	Description
Name	FSTNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

MIDNAME

Attribute	Description
Name	MIDNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

LSTNAME

Attribute	Description
Name	LSTNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

DOB

Attribute	Description
Name	DOB

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GUARDIAN

Attribute	Description
Name	GUARDIAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MINOR

Attribute	Description
Name	MINOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SEX

Attribute	Description
Name	SEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,F

TOP

NATIONID

Attribute	Description
Name	NATIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

PPTNO

Attribute	Description	
Name	PPTNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

PPTISSDT

Attribute	Description	
Name	PPTISSDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PPTEXPDT

Attribute	Description	
Name	PPTEXPDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

DADD1

Attribute	Description	
Name	DADD1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

DADD2

Attribute	Description
Name	DADD2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DADD3

Attribute	**Description**
Name	DADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TEL

Attribute	**Description**
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FAX

Attribute	**Description**
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EMAIL

Attribute	**Description**
Name	EMAIL
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PADD1

Attribute	Description
Name	PADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PADD2

Attribute	Description
Name	PADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PADD3

Attribute	Description
Name	PADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DCNTRY

Attribute	Description
Name	DCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PCNTRY

Attribute	**Description**
Name	PCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RESSTATUS

Attribute	**Description**
Name	RESSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,N

TOP

CUSTPREFIX1

Attribute	**Description**
Name	CUSTPREFIX1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

CUSTPREFIX2

Attribute	**Description**
Name	CUSTPREFIX2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

MOBNUM

Attribute	Description
Name	MOBNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SBMTAGEPROOF

Attribute	Description
Name	SBMTAGEPROOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,P,V

TOP

CUST_COMM_MODE

Attribute	Description
Name	CUST_COMM_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,E

TOP

Custdomestic

Attribute	Description
Name	Custdomestic
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EDUSTAT

Attribute	Description
Name	EDUSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	N,U,G,P

TOP

MARITALSTAT

Attribute	Description	
Name	MARITALSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,M,D,R,P,E,T

TOP

SPNAME

Attribute	Description	
Name	SPNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SPEMPSTATUS

Attribute	Description	
Name	SPEMPSTATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,T,S,U,R,P,N,O

TOP

DEPCHILD

Attribute	Description	
Name	DEPCHILD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEPOTH

Attribute	Description
Name	DEPOTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOMODATE

Attribute	Description
Name	ACCOMODATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,O

TOP

Custprof

Attribute	Description
Name	Custprof
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EMPSTAT

Attribute	Description
Name	EMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

EMPTENURE

Attribute	Description
Name	EMPTENURE
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

RETIREAGE

Attribute	Description
Name	RETIREAGE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PREVDESIG

Attribute	Description
Name	PREVDESIG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

PREVEMP

Attribute	Description
Name	PREVEMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CURRDESIG

Attribute	Description
Name	CURRDESIG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CURREMP

Attribute	Description
Name	CURREMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADD3

Attribute	Description
Name	ADD3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

TEL

Attribute	Description
Name	TEL

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TELEX

Attribute	Description
Name	TELEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FAX

Attribute	Description
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

SALARY

Attribute	Description
Name	SALARY
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

OTHER1

Attribute	Description	
Name	OTHER1	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RENT

Attribute	Description	
Name	RENT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSURANCE

Attribute	Description	
Name	INSURANCE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LOANPMNT

Attribute	Description	
Name	LOANPMNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OTHEXP

Attribute	Description	
Name	OTHEXP	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

HOUSEVAL

Attribute	Description
Name	HOUSEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CRCARD

Attribute	Description
Name	CRCARD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMTCCY1

Attribute	Description
Name	AMTCCY1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Custcorp

Attribute	Description
Name	Custcorp
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CORPNAME

Attribute	Description	
Name	CORPNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

NATIONID

Attribute	Description	
Name	NATIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REGADD1

Attribute	Description	
Name	REGADD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REGADD2

Attribute	Description	
Name	REGADD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REGADD3

Attribute	Description	
Name	REGADD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INCORPDT

Attribute	Description	
Name	INCORPDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CAPITAL

Attribute	Description	
Name	CAPITAL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NETWORTH

Attribute	Description	
Name	NETWORTH	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INCORPCNTRY

Attribute	Description	
Name	INCORPCNTRY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REGCNTRY

Attribute	**Description**
Name	REGCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMTCCY

Attribute	**Description**
Name	AMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CORPDESC

Attribute	**Description**
Name	CORPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Custcorpdir

Attribute	**Description**
Name	Custcorpdir
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

DIRNAME

Attribute	Description
Name	DIRNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR1

Attribute	Description
Name	NADDR1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR2

Attribute	Description

Name	NADDR2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR3

Attribute	Description
Name	NADDR3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR4

Attribute	Description
Name	NADDR4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRY

Attribute	Description
Name	COUNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXID

Attribute	Description
Name	TAXID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MOBNO

Attribute	Description
Name	MOBNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Issuerdet

Attribute	Description
Name	Issuerdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OVERLIMIT

Attribute	Description
Name	OVERLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OVERLMTCCY

Attribute	Description
Name	OVERLMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Issuerlmts

Attribute	Description
Name	Issuerlmts
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	1

TOP

CLTRLTYP

Attribute	Description	
Name	CLTRLTYP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	70

TOP

LMTAMT

Attribute	Description	
Name	LMTAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

LMTCCY

Attribute	Description	
Name	LMTCCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

ISSID

Attribute	Description	
Name	ISSID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

Custgrp

Attribute	Description
Name	Custgrp
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

GRPNO

Attribute	Description
Name	GRPNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RELATION

Attribute	Description
Name	RELATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Custshhold

Attribute	Description
Name	Custshhold
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

SHHOLDID

Attribute	Description
Name	SHHOLDID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SHHOLDPCT

Attribute	Description
Name	SHHOLDPCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs = 0

TOP

SHRHLDRNAME

Attribute	Description
Name	SHRHLDRNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: maxLength = 20

TOP

Clsccyrest

Attribute	Description
Name	Clsccyrest
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs = unbounded; minOccurs = 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs = 0
Restrictions	**Restrictions** / **Description**: maxLength = 3

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Bic

Attribute	Description
Name	Bic
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BICCD

Attribute	Description
Name	BICCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

Linkedac

Attribute	Description
Name	Linkedac

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VRFD

Attribute	Description
Name	VRFD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LINKEDACCNO

Attribute	Description
Name	LINKEDACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

LINKEDACCIBAN

Attribute	Description
Name	LINKEDACCIBAN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINKEDACCBIC

Attribute	Description
Name	LINKEDACCBIC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

JointVenture

Attribute	Description
Name	JointVenture
Datatype	
Description	
Attributes	Attribute: Description maxOccurs: unbounded minOccurs: 0

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description maxLength: 9

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 9

TOP

PARTYRATIO

Attribute	Description
Name	PARTYRATIO
Datatype	Number
Description	
Attributes	Attribute: Description minOccurs: 0

TOP

PARTYNAME

Attribute	Description

Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Custdoc-Chklist

Attribute	**Description**
Name	Custdoc-Chklist
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTOMER_NO

Attribute	**Description**
Name	CUSTOMER_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

DOCUMENT_TYPE

Attribute	**Description**
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CHECKED

Attribute	**Description**
Name	CHECKED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Doctype-Remarks

Attribute	Description
Name	Doctype-Remarks
Datatype	
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

REMARK1

Attribute	Description
Name	REMARK1
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 225

TOP

REMARK2

Attribute	Description
Name	REMARK2
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 225

TOP

REMARK3

Attribute	Description
Name	REMARK3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK4

Attribute	Description
Name	REMARK4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK5

Attribute	Description
Name	REMARK5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK6

Attribute	Description
Name	REMARK6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK7

Attribute	Description
Name	REMARK7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK8

Attribute	**Description**
Name	REMARK8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK9

Attribute	**Description**
Name	REMARK9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK10

Attribute	**Description**
Name	REMARK10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

Custmis

Attribute	**Description**
Name	Custmis
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MISGRP

Attribute	Description	
Name	MISGRP	
Datatype	String	
Description	Indicates the MIS Group.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CUSTMIS1

Attribute	Description	
Name	CUSTMIS1	
Datatype	String	
Description	Indicates the Customer MIS 1.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTMIS2

Attribute	Description	
Name	CUSTMIS2	
Datatype	String	
Description	Indicates the Customer MIS 2.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTMIS3

Attribute	Description	
Name	CUSTMIS3	
Datatype	String	
Description	Indicates the Customer MIS 3.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTMIS4

Attribute	Description
Name	CUSTMIS4
Datatype	String
Description	Indicates the Customer MIS 4.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTMIS5

Attribute	Description
Name	CUSTMIS5
Datatype	String
Description	Indicates the Customer MIS 5.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTMIS6

Attribute	Description
Name	CUSTMIS6
Datatype	String
Description	Indicates the Customer MIS 6.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTMIS7

Attribute	Description
Name	CUSTMIS7
Datatype	String
Description	Indicates the Customer MIS 7.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTMIS8

Attribute	Description
Name	CUSTMIS8
Datatype	String
Description	Indicates the Customer MIS 8.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTMIS9

Attribute	Description
Name	CUSTMIS9
Datatype	String
Description	Indicates the Customer MIS 9.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTMIS10

Attribute	Description
Name	CUSTMIS10
Datatype	String
Description	Indicates the Customer MIS 10.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the Composite MIS 1.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2

Datatype	String
Description	Indicates the Composite MIS 2.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS3

Attribute	**Description**
Name	COMPMIS3
Datatype	String
Description	Indicates the Composite MIS 3.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS4

Attribute	**Description**
Name	COMPMIS4
Datatype	String
Description	Indicates the Composite MIS 4.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS5

Attribute	**Description**
Name	COMPMIS5
Datatype	String
Description	Indicates the Composite MIS 5.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS6

Attribute	**Description**
Name	COMPMIS6
Datatype	String
Description	Indicates the Composite MIS 6.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS7

Attribute	**Description**	
Name	COMPMIS7	
Datatype	String	
Description	Indicates the Composite MIS 7.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description	Indicates the Composite MIS 8.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description	Indicates the Composite MIS 9.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	**Description**	
Name	COMPMIS10	
Datatype	String	
Description	Indicates the Composite MIS 10.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Custchnglog

Attribute	**Description**
Name	Custchnglog
Datatype	
Description	Indicates the Customer Change Log.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

MISCLS

Attribute	**Description**
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNDT

Attribute	**Description**
Name	TXNDT
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

OLDMISCD

Attribute	**Description**

Name	OLDMISCD
Datatype	String
Description	Indicates the Old MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	Indicates the New MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Baltrnsfrlog

Attribute	Description
Name	Baltrnsfrlog
Datatype	
Description	Indicates the Balance Transfer Log.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	**Description**
Name	FINYR
Datatype	String
Description	Indicates the Financial year.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNDT

Attribute	**Description**
Name	TXNDT
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

GLCODE

Attribute	**Description**
Name	GLCODE
Datatype	String
Description	Indicates the GL Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCLS

Attribute	**Description**
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	Indicates the Old MIS Code.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	Indicates the New MIS Code.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

TRNIND

Attribute	Description
Name	TRNIND
Datatype	String
Description	Indicates Transfer Identification Number.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

XRATE

Attribute	Description
Name	XRATE

Datatype	Number
Description	Indicates the Exchange Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Dfltcd

Attribute	**Description**
Name	Dfltcd
Datatype	
Description	Indicates the Customer MIS Classes.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Dfltcda

Attribute	**Description**
Name	Dfltcda
Datatype	
Description	Indicates the Composite MIS Classes.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Jointcustomer

Attribute	**Description**
Name	Jointcustomer
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Custjoint

Attribute	Description
Name	Custjoint
Datatype	
Description	Indicates the Customer Joint.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTPREFIX

Attribute	Description
Name	CUSTPREFIX
Datatype	String
Description	Indicates the Customer Prefix.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FRSTNAME

Attribute	Description
Name	FRSTNAME
Datatype	String
Description	Indicates the First Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MIDNAME

Attribute	Description
Name	MIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LASTNAME

Attribute	Description
Name	LASTNAME
Datatype	String

Description	Indicates the Last Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOB

Attribute	**Description**
Name	DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SEX

Attribute	**Description**
Name	SEX
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,F

TOP

PPNO

Attribute	**Description**
Name	PPNO
Datatype	String
Description	Indicates the Passport Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

PPTISSDT

Attribute	**Description**
Name	PPTISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PPTEXPDT

Attribute	Description
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADD3

Attribute	Description
Name	ADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EMAIL

Attribute	**Description**
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DECEASED

Attribute	**Description**
Name	DECEASED
Datatype	String
Description	Indicates whether Deceased or not. The value should be either D or N.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,N

TOP

RESISTAT

Attribute	**Description**
Name	RESISTAT
Datatype	String
Description	Indicates the Resident Status. The Value could be either R or N.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,N

TOP

Cust-Acc-Det

Attribute	**Description**
Name	Cust-Acc-Det
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Diary-Mst

Attribute	Description
Name	Diary-Mst
Datatype	
Description	Indicates Diary Master.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	Indicates Instrument Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

UNTTYP

Attribute	Description
Name	UNTTYP
Datatype	String
Description	Indicates Unit Type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

UNTVAL

Attribute	Description

Name	UNTVAL
Datatype	String
Description	Indicates Unit Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INSTR

Attribute	Description
Name	INSTR
Datatype	String
Description	Indicates Instructions.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

INSTRTYPE

Attribute	Description
Name	INSTRTYPE
Datatype	String
Description	Indicates Instruction Type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

EXEDAYS

Attribute	Description
Name	EXEDAYS
Datatype	Number
Description	Indicates Execution days.

Attributes	Attribute	Description
	minOccurs	0

TOP

EXEMONTHS

Attribute	Description
Name	EXEMONTHS
Datatype	Number
Description	Indicates Execution Months.
Attributes	Attribute: minOccurs — Description: 0

TOP

EXEYEARS

Attribute	Description
Name	EXEYEARS
Datatype	Number
Description	Indicates Execution years.
Attributes	Attribute: minOccurs — Description: 0

TOP

MNTHENDFLG

Attribute	Description
Name	MNTHENDFLG
Datatype	String
Description	Indicates Month End Flag. Flag Value can be either Y or N.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

HLDRULE

Attribute	Description
Name	HLDRULE
Datatype	String
Description	Indicates Holiday Rule.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

FRSTDUEDT

Attribute	Description
Name	FRSTDUEDT

Datatype	Date
Description	Indicates First Due date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NXTDUEDT

Attribute	**Description**
Name	NXTDUEDT
Datatype	Date
Description	Indicates Next Due Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NXTEXEDT

Attribute	**Description**
Name	NXTEXEDT
Datatype	Date
Description	Indicates Next Execution Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONDELEM

Attribute	**Description**
Name	CONDELEM
Datatype	String
Description	Indicates Condition Elements.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

OPRTR

Attribute	**Description**
Name	OPRTR
Datatype	String
Description	Indicates Operator.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

CONDVAL

Attribute	Description
Name	CONDVAL
Datatype	Number
Description	Indicates Condition Value.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOFCR

Attribute	Description
Name	ACCOFCR
Datatype	String
Description	Indicates Account Officer.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPLINSTRTYP

Attribute	Description
Name	SPLINSTRTYP
Datatype	String
Description	Indicates Special Instruction Type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	Indicates Expiry Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPLINSTR

Attribute	Description
Name	SPLINSTR
Datatype	String
Description	Indicates special Instruction.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Custaccdet

Attribute	**Description**
Name	Custaccdet
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Relationship-Linkage

Attribute	**Description**
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkage details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTOMER

Attribute	**Description**
Name	CUSTOMER
Datatype	String
Description	Indicates the customer
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RELATIONSHIP

Attribute	**Description**

Name	RELATIONSHIP
Datatype	String
Description	Indicate relations
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

INHERIT

Attribute	**Description**
Name	INHERIT
Datatype	String
Description	Indicate,include relationship Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DESCP

Attribute	**Description**
Name	DESCP
Datatype	String
Description	Indicates description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Custacdetail

Attribute	**Description**
Name	Custacdetail
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTTEXT

Attribute	Description
Name	CUSTTEXT
Datatype	
Description	Include customer details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	Indicate sequence number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String
Description	Indicate text description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Sttms-Debit

Attribute	Description
Name	Sttms-Debit
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch code.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUST_NO

Attribute	Description	
Name	CUST_NO	
Datatype	String	
Description	Indicates the Customer Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

ACTNO

Attribute	Description	
Name	ACTNO	
Datatype	String	
Description	Indicates the Account Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

Extsys-Ws-Master

Attribute	Description	
Name	Extsys-Ws-Master	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

KEYID

Attribute	Description	
Name	KEYID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	200

TOP

Stvws-Cust-Trntax

Attribute	Description
Name	Stvws-Cust-Trntax
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Sttms-Cust-Trn-Tax

Attribute	Description
Name	Sttms-Cust-Trn-Tax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TAX_SCHEME

Attribute	Description
Name	TAX_SCHEME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

TXN_TAX_EXEMPTED

Attribute	Description
Name	TXN_TAX_EXEMPTED
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TXN_TAX_EXEMPTION_PERCENT

Attribute	Description
Name	TXN_TAX_EXEMPTION_PERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXN_TAX_EFF_DATE

Attribute	Description
Name	TXN_TAX_EFF_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXN_TAX_EXEMPTION_REASON

Attribute	Description
Name	TXN_TAX_EXEMPTION_REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

2.19.3.ST-ModifyCustomer-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Customer-Full*
    - *NAME*
    - *ADDRLN1*
    - *ADDRLN3*
    - *ADDRLN2*
    - *ADDRLN4*
    - *SWIFTCD*
    - *FAX*
    - *COUNTRY*
    - *NLTY*
    - *LANG*
    - *EXPCNTRY*
    - *UIDNAME*
    - *UIDVAL*
    - *LOC*
    - *FROZEN*
    - *DEAD*
    - *WHRUNKN*
    - *GRPCD*

CHGGRP
CUSTCLGGRP
TAXGROUP
CCATEG
EXPCAT
CUSTCLASSFN
FXNETTCUST
XREF
MEDIA
SSN
CIFSTAT
CIFSTATSNC
MAILRSREQD
CLSPARTICIPANT
CRMCUST
ISSUCUST
TRSRYCUST
CUSTNO
SNAME
LBRN
CTYPE
FULLNAME
AMLCUSTGRP
AMLREQD
FLGUTLTYPRVDR
UTLTYPRVDRID
CHKDIGITVALREQD
ALGID
CONSTAXCERTRQD
INDTAXCERTRQD
HOACNO
RISKPRFL
DRCAT
FTACCASOF
UDF1
UDF2
UDF3
UDF4
UDF5
UDFLBL1
UDFLBL2
UDFLBL3
UDFLBL4
UDFLBL5

FXCUSTCLRILIM
OVRLIM
FX_CLEAN_RISK
CRRATE
REVDT
LIMCCY
SECCUSTCLRILIM
SECCLRILIM
SECCUSTPSRILIM
SECPSRILIM
CUSTUNADV
RISKCATEG
CLSCCYALLWD
NETTREQD
LIABUNADV
MT920
RELPRICING
FLGJOINT
KYCSTAT
SSTAFF
UPTYPE
KYC_REFNO
JOINT_VENTURE
PRIVATE_CUSTOMER
LC_COLLAT_PCT
ISELCMCUST
ELCMCUSTNO
ALT_CUST_NO
DETERIORATION_DATE
CHQ_TAX_EXEMPT_1
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Custpersonal
- *TITLE*
- *FSTNAME*
- *MIDNAME*
- *LSTNAME*
- *DOB*
- *GUARDIAN*

MINOR
SEX
NATIONID
PPTNO
PPTISSDT
PPTEXPDT
DADD1
DADD2
DADD3
TEL
FAX
EMAIL
PADD1
PADD2
PADD3
DCNTRY
PCNTRY
RESSTATUS
CUSTPREFIX1
CUSTPREFIX2
MOBNUM
SBMTAGEPROOF
CUST_COMM_MODE
LAST_UPD_DT
Custdomestic
- *EDUSTAT*
- *MARITALSTAT*
- *SPNAME*
- *SPEMPSTATUS*
- *DEPCHILD*
- *DEPOTH*
- *ACCOMODATE*
- *CUSTNO*

Custprof
- *EMPSTAT*
- *EMPTENURE*
- *RETIREAGE*
- *PREVDESIG*
- *PREVEMP*
- *CURRDESIG*
- *CURREMP*
- *ADD1*
- *ADD2*
- *ADD3*

TEL
TELEX
FAX
EMAIL
SALARY
OTHER1
RENT
INSURANCE
LOANPMNT
OTHEXP
HOUSEVAL
CRCARD
CNTY
AMTCCY1
CUSTNO
EMPLOYER_DESC
EMP_DESC
Custcorp
CORPNAME
NATIONID
REGADD1
REGADD2
REGADD3
INCORPDT
CAPITAL
NETWORTH
INCORPCNTRY
REGCNTRY
AMTCCY
CORPDESC
CUSTNO
Custcorpdir
DIRNAME
TEL
NADDR1
NADDR2
NADDR3
NADDR4
ADDR1
ADDRS2
ADDRS3
COUNTRY
TAXID
MOBNO

EMAIL

Issuerdet

OVERLIMIT

CUSTNO

OVERLMTCCY

Issuerlmts

CLTRLTYP

LMTAMT

LMTCCY

ISSID

Custgrp

GRPNO

RELATION

Custshhold

SHHOLDID

SHHOLDPCT

SHRHLDRNAME

Clsccyrest

CCY

DESC

Bic

ACC

BICCD

Linkedac

VRFD

LINKEDACCNO

LINKEDACCIBAN

LINKEDACCBIC

JointVenture

PARTYID

PARTYRATIO

PARTYNAME

Custdoc-Chklist

DOCUMENT_TYPE

CHECKED

Doctype-Remarks

REMARK1

REMARK2

REMARK3

REMARK4

REMARK5

REMARK6

REMARK7

REMARK8

- *REMARK9*
- *REMARK10*

Custmis

- *MISGRP*
- *CUST*
- *BRNCD*
- *Custchnglog*
  - *MISCLS*
  - *TXNDT*
  - *OLDMISCD*
  - *NWMISCD*
- *Baltrnsfrlog*
  - *BRN*
  - *PRDCD*
  - *FINYR*
  - *TXNDT*
  - *GLCODE*
  - *MISCLS*
  - *OLDMISCD*
  - *NWMISCD*
  - *TRNIND*
  - *CCY*
  - *AMT*
  - *XRATE*
- *Dfltcd*
  - *MISCLS*
  - *MISCD*
- *Dfltcda*
  - *MISCLS*
  - *MISCD*
- *Custloghead*

Jointcustomer

- *CUSTNO*
- *Custjoint*
  - *CUSTPREFIX*
  - *FRSTNAME*
  - *MIDNAME*
  - *LASTNAME*
  - *DOB*
  - *SEX*
  - *PPNO*
  - *PPTISSDT*
  - *PPTEXPDT*
  - *ADD1*

ADD2

ADD3

TEL

EMAIL

SSN

DECEASED

RESISTAT

Cust-Acc-Det

CUSTNO

Diary-Mst

INSTRNO

UNTTYP

UNTVAL

BRN

INSTR

INSTRTYPE

EXEDAYS

EXEMONTHS

EXEYEARS

MNTHENDFLG

HLDRULE

FRSTDUEDT

NXTDUEDT

NXTEXEDT

CONDELEM

OPRTR

CONDVAL

ACCOFCR

SPLINSTRTYP

EXPDT

SPLINSTR

Custaccdet

CUSTNO

BRNCD

Relationship-Linkage

CUSTOMER

RELATIONSHIP

INHERIT

DESCP

Custacdetail

CUSTNO

CUSTTEXT

SEQNO

CUSTNO

TDESC
UDFDETAILS
FLDNAM
FLDVAL
Sttms-Debit
BRANCH_CODE
CUST_NO
ACTNO
Sttms-Detail
BRANCH_CODE
REQUEST_REFERENCE_NO
CARDNO
CUST_NO
CARD_PRODUCT
PRIMARY_CARD
NAME_ON_CARD
OWNER_ID_NO
CARD_ISSUED_DT
CARD_EXPIRY_DT
CARD_STATUS
RECORD_STAT
AUTH_STAT
CARD_BIN
CUST_AC_NO
Extsys-Ws-Master
Extsys-Ws-Details
EXTWSRESP
USERREMARKS
Stvws-Cust-Trntax
CUSTOMER_NO
Sttms-Cust-Trn-Tax
TAX_SCHEME
TXN_TAX_EXEMPTED
TXN_TAX_EXEMPTION_PERCENT
TXN_TAX_EFF_DATE
TXN_TAX_EXEMPTION_REASON
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Customer-Full

Attribute	Description

Name	Customer-Full
Datatype	
Description	

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

ADDRLN1

Attribute	Description	
Name	ADDRLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN3

Attribute	Description	
Name	ADDRLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN2

Attribute	Description	
Name	ADDRLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN4

Attribute	Description

Name	ADDRLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SWIFTCD

Attribute	**Description**
Name	SWIFTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FAX

Attribute	**Description**
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRY

Attribute	**Description**
Name	COUNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NLTY

Attribute	**Description**
Name	NLTY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXPCNTRY

Attribute	Description
Name	EXPCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

UIDNAME

Attribute	Description
Name	UIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

UIDVAL

Attribute	Description
Name	UIDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

LOC

Attribute	Description	
Name	LOC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

FROZEN

Attribute	Description	
Name	FROZEN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

DEAD

Attribute	Description	
Name	DEAD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

WHRUNKN

Attribute	Description	
Name	WHRUNKN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CHGGRP

Attribute	Description
Name	CHGGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CUSTCLGGRP

Attribute	Description
Name	CUSTCLGGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAXGROUP

Attribute	Description
Name	TAXGROUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CCATEG

Attribute	Description
Name	CCATEG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

CUSTCLASSFN

Attribute	Description
Name	CUSTCLASSFN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

FXNETTCUST

Attribute	Description
Name	FXNETTCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

XREF

Attribute	Description
Name	XREF

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MEDIA

Attribute	**Description**
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SSN

Attribute	**Description**
Name	SSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

CIFSTAT

Attribute	**Description**
Name	CIFSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CIFSTATSNC

Attribute	**Description**
Name	CIFSTATSNC
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MAILRSREQD

Attribute	Description
Name	MAILRSREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CLSPARTICIPANT

Attribute	Description
Name	CLSPARTICIPANT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CRMCUST

Attribute	Description
Name	CRMCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ISSUCUST

Attribute	Description
Name	ISSUCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TRSRYCUST

Attribute	Description
Name	TRSRYCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SNAME

Attribute	Description
Name	SNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LBRN

Attribute	Description
Name	LBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CTYPE

Attribute	Description
Name	CTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,C,B

TOP

FULLNAME

Attribute	Description
Name	FULLNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

AMLCUSTGRP

Attribute	Description
Name	AMLCUSTGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

AMLREQD

Attribute	Description
Name	AMLREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FLGUTLTYPRVDR

Attribute	Description
Name	FLGUTLTYPRVDR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UTLTYPRVDRID

Attribute	**Description**
Name	UTLTYPRVDRID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKDIGITVALREQD

Attribute	**Description**
Name	CHKDIGITVALREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALGID

Attribute	**Description**
Name	ALGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CONSTAXCERTRQD

Attribute	**Description**
Name	CONSTAXCERTRQD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INDTAXCERTRQD

Attribute	Description	
Name	INDTAXCERTRQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

HOACNO

Attribute	Description	
Name	HOACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RISKPRFL

Attribute	Description	
Name	RISKPRFL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

DRCAT

Attribute	Description	
Name	DRCAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FTACCASOF

Attribute	Description	
Name	FTACCASOF	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,M,D

TOP

UDF1

Attribute	Description	
Name	UDF1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

TOP

UDF2

Attribute	Description	
Name	UDF2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

TOP

UDF3

Attribute	Description	
Name	UDF3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

UDF4

Attribute	Description
Name	UDF4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

UDF5

Attribute	Description
Name	UDF5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL1

Attribute	Description
Name	UDFLBL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL2

Attribute	Description
Name	UDFLBL2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL3

Attribute	Description
Name	UDFLBL3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDFLBL4

Attribute	Description
Name	UDFLBL4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDFLBL5

Attribute	Description
Name	UDFLBL5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

FXCUSTCLRILIM

Attribute	Description
Name	FXCUSTCLRILIM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

OVRLIM

Attribute	Description
Name	OVRLIM
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

FX_CLEAN_RISK

Attribute	Description
Name	FX_CLEAN_RISK
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CRRATE

Attribute	Description
Name	CRRATE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

REVDT

Attribute	Description
Name	REVDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIMCCY

Attribute	Description
Name	LIMCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

SECCUSTCLRILIM

Attribute	Description
Name	SECCUSTCLRILIM

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCLRILIM

Attribute	Description
Name	SECCLRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCUSTPSRILIM

Attribute	Description
Name	SECCUSTPSRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECPSRILIM

Attribute	Description
Name	SECPSRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTUNADV

Attribute	Description
Name	CUSTUNADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RISKCATEG

Attribute	Description
Name	RISKCATEG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CLSCCYALLWD

Attribute	**Description**
Name	CLSCCYALLWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

NETTREQD

Attribute	**Description**
Name	NETTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIABUNADV

Attribute	**Description**
Name	LIABUNADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MT920

Attribute	**Description**
Name	MT920
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RELPRICING

Attribute	Description	
Name	RELPRICING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

FLGJOINT

Attribute	Description	
Name	FLGJOINT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

KYCSTAT

Attribute	Description	
Name	KYCSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	V,N,F

TOP

SSTAFF

Attribute	Description	
Name	SSTAFF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UPTYPE

Attribute	**Description**
Name	UPTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

KYC_REFNO

Attribute	**Description**
Name	KYC_REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

JOINT_VENTURE

Attribute	**Description**
Name	JOINT_VENTURE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIVATE_CUSTOMER

Attribute	**Description**
Name	PRIVATE_CUSTOMER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LC_COLLAT_PCT

Attribute	Description
Name	LC_COLLAT_PCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISELCMCUST

Attribute	Description
Name	ISELCMCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ELCMCUSTNO

Attribute	Description
Name	ELCMCUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ALT_CUST_NO

Attribute	Description
Name	ALT_CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DETERIORATION_DATE

Attribute	Description
Name	DETERIORATION_DATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHQ_TAX_EXEMPT_1

Attribute	Description
Name	CHQ_TAX_EXEMPT_1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

Custpersonal

Attribute	Description
Name	Custpersonal
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TITLE

Attribute	Description
Name	TITLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FSTNAME

Attribute	Description
Name	FSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MIDNAME

Attribute	Description
Name	MIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LSTNAME

Attribute	Description
Name	LSTNAME
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GUARDIAN

Attribute	Description
Name	GUARDIAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MINOR

Attribute	Description
Name	MINOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SEX

Attribute	Description
Name	SEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,F

TOP

NATIONID

Attribute	Description
Name	NATIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PPTNO

Attribute	Description
Name	PPTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PPTISSDT

Attribute	Description
Name	PPTISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PPTEXPDT

Attribute	Description
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DADD1

Attribute	Description
Name	DADD1
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DADD2

Attribute	Description
Name	DADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DADD3

Attribute	Description
Name	DADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FAX

Attribute	Description
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

EMAIL

Attribute	Description	
Name	EMAIL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TOP

PADD1

Attribute	Description	
Name	PADD1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

PADD2

Attribute	Description	
Name	PADD2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

PADD3

Attribute	Description	
Name	PADD3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

DCNTRY

Attribute	Description
Name	DCNTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

PCNTRY

Attribute	Description
Name	PCNTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

RESSTATUS

Attribute	Description
Name	RESSTATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: R,N

TOP

CUSTPREFIX1

Attribute	Description
Name	CUSTPREFIX1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

CUSTPREFIX2

Attribute	Description
Name	CUSTPREFIX2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

MOBNUM

Attribute	Description
Name	MOBNUM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SBMTAGEPROOF

Attribute	Description
Name	SBMTAGEPROOF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,P,V

TOP

CUST_COMM_MODE

Attribute	Description
Name	CUST_COMM_MODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,E

TOP

LAST_UPD_DT

Attribute	Description
Name	LAST_UPD_DT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Custdomestic

Attribute	Description
Name	Custdomestic
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

EDUSTAT

Attribute	Description
Name	EDUSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,U,G,P

TOP

MARITALSTAT

Attribute	Description
Name	MARITALSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: S,M,D,R,P,E,T

TOP

SPNAME

Attribute	Description
Name	SPNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SPEMPSTATUS

Attribute	Description
Name	SPEMPSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,T,S,U,R,P,N,O

TOP

DEPCHILD

Attribute	Description
Name	DEPCHILD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEPOTH

Attribute	Description
Name	DEPOTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOMODATE

Attribute	Description
Name	ACCOMODATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,O

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	9

TOP

Custprof

Attribute	Description	
Name	Custprof	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EMPSTAT

Attribute	Description	
Name	EMPSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

EMPTENURE

Attribute	Description	
Name	EMPTENURE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RETIREAGE

Attribute	Description	
Name	RETIREAGE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PREVDESIG

Attribute	Description
Name	PREVDESIG
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PREVEMP

Attribute	Description
Name	PREVEMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURRDESIG

Attribute	Description
Name	CURRDESIG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURREMP

Attribute	Description
Name	CURREMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ADD2

Attribute	Description	
Name	ADD2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ADD3

Attribute	Description	
Name	ADD3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

TEL

Attribute	Description	
Name	TEL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

TELEX

Attribute	Description	
Name	TELEX	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

FAX

Attribute	Description
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

SALARY

Attribute	Description
Name	SALARY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHER1

Attribute	Description
Name	OTHER1
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RENT

Attribute	Description
Name	RENT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

INSURANCE

Attribute	Description
Name	INSURANCE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LOANPMNT

Attribute	Description
Name	LOANPMNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

OTHEXP

Attribute	Description
Name	OTHEXP
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

HOUSEVAL

Attribute	Description
Name	HOUSEVAL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CRCARD

Attribute	Description
Name	CRCARD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

AMTCCY1

Attribute	Description
Name	AMTCCY1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

EMPLOYER_DESC

Attribute	Description
Name	EMPLOYER_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 22

TOP

EMP_DESC

Attribute	Description
Name	EMP_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

Custcorp

Attribute	Description
Name	Custcorp
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CORPNAME

Attribute	Description
Name	CORPNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

NATIONID

Attribute	Description
Name	NATIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REGADD1

Attribute	Description
Name	REGADD1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REGADD2

Attribute	**Description**
Name	REGADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REGADD3

Attribute	**Description**
Name	REGADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INCORPDT

Attribute	**Description**
Name	INCORPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CAPITAL

Attribute	**Description**
Name	CAPITAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETWORTH

Attribute	Description
Name	NETWORTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INCORPCNTRY

Attribute	Description
Name	INCORPCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REGCNTRY

Attribute	Description
Name	REGCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CORPDESC

Attribute	Description
Name	CORPDESC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Custcorpdir

Attribute	Description
Name	Custcorpdir
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DIRNAME

Attribute	Description
Name	DIRNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR1

Attribute	Description
Name	NADDR1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

NADDR2

Attribute	Description
Name	NADDR2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

NADDR3

Attribute	Description
Name	NADDR3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

NADDR4

Attribute	Description
Name	NADDR4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRY

Attribute	Description
Name	COUNTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

TAXID

Attribute	Description
Name	TAXID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MOBNO

Attribute	**Description**
Name	MOBNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EMAIL

Attribute	**Description**
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Issuerdet

Attribute	**Description**
Name	Issuerdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OVERLIMIT

Attribute	**Description**
Name	OVERLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OVERLMTCCY

Attribute	Description
Name	OVERLMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Issuerlmts

Attribute	Description
Name	Issuerlmts
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CLTRLTYP

Attribute	Description
Name	CLTRLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 70

TOP

LMTAMT

Attribute	Description
Name	LMTAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LMTCCY

Attribute	Description
Name	LMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ISSID

Attribute	Description
Name	ISSID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Custgrp

Attribute	Description
Name	Custgrp
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

GRPNO

Attribute	Description
Name	GRPNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RELATION

Attribute	Description
Name	RELATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Custshhold

Attribute	Description
Name	Custshhold
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SHHOLDID

Attribute	Description
Name	SHHOLDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SHHOLDPCT

Attribute	Description
Name	SHHOLDPCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHRHLDRNAME

Attribute	Description
Name	SHRHLDRNAME
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Clsccyrest

Attribute	Description
Name	Clsccyrest
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Bic

Attribute	Description
Name	Bic
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BICCD

Attribute	Description
Name	BICCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

Linkedac

Attribute	Description
Name	Linkedac
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

VRFD

Attribute	Description
Name	VRFD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LINKEDACCNO

Attribute	Description

Name	LINKEDACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

LINKEDACCIBAN

Attribute	**Description**
Name	LINKEDACCIBAN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINKEDACCBIC

Attribute	**Description**
Name	LINKEDACCBIC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

JointVenture

Attribute	**Description**
Name	JointVenture
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTYID

Attribute	**Description**
Name	PARTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	9

TOP

PARTYRATIO

Attribute	Description
Name	PARTYRATIO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 1

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

Custdoc-Chklist

Attribute	Description
Name	Custdoc-Chklist
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

CHECKED

Attribute	Description

Name	CHECKED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Doctype-Remarks

Attribute	**Description**
Name	Doctype-Remarks
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARK1

Attribute	**Description**
Name	REMARK1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK2

Attribute	**Description**
Name	REMARK2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK3

Attribute	**Description**
Name	REMARK3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	225

TOP

REMARK4

Attribute	Description
Name	REMARK4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK5

Attribute	Description
Name	REMARK5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK6

Attribute	Description
Name	REMARK6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK7

Attribute	Description
Name	REMARK7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK8

Attribute	Description
Name	REMARK8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK9

Attribute	Description
Name	REMARK9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK10

Attribute	Description
Name	REMARK10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

Custmis

Attribute	Description
Name	Custmis
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP

Datatype	String
Description	Indicates Management Information System Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CUST

Attribute	**Description**
Name	CUST
Datatype	String
Description	Indicates the Customer.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRNCD

Attribute	**Description**
Name	BRNCD
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Custchnglog

Attribute	**Description**
Name	Custchnglog
Datatype	
Description	Indicates the Customer Change Log.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	**Description**
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	Indicates the Old MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	Indicates the New MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Baltrnsfrlog

Attribute	Description
Name	Baltrnsfrlog
Datatype	
Description	Indicates the Balance Transfer Log.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRN

Attribute	Description

Name	BRN
Datatype	String
Description	Indicates the Branch Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PRDCD

Attribute	**Description**
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FINYR

Attribute	**Description**
Name	FINYR
Datatype	String
Description	Indicates the Financial Year.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNDT

Attribute	**Description**
Name	TXNDT
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

GLCODE

Attribute	**Description**
Name	GLCODE
Datatype	String
Description	Indicates the GL Code.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 9

TOP

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	Indicates the Old MIS Code.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	Indicates the New MIS Code.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

TRNIND

Attribute	Description
Name	TRNIND
Datatype	String
Description	Indicates Transfer Identification Number.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Dfltcd

Attribute	Description
Name	Dfltcd
Datatype	
Description	Indicates the Customer MIS Classes.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MISCD

Attribute	Description	
Name	MISCD	
Datatype	String	
Description	Indicates the MIS Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Dfltcda

Attribute	Description	
Name	Dfltcda	
Datatype		
Description	Indicates the Composite MIS Classes.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MISCLS

Attribute	Description	
Name	MISCLS	
Datatype	String	
Description	Indicates the MIS Class.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MISCD

Attribute	Description	
Name	MISCD	
Datatype	String	
Description	Indicates the MIS Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Custloghead

Attribute	Description
Name	Custloghead
Datatype	
Description	Indicates the Customer Log Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Jointcustomer

Attribute	Description
Name	Jointcustomer
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Custjoint

Attribute	Description
Name	Custjoint
Datatype	
Description	Indicates Customer Joint.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTPREFIX

Attribute	Description
Name	CUSTPREFIX
Datatype	String
Description	Indicates the Customer Prefix.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FRSTNAME

Attribute	Description
Name	FRSTNAME
Datatype	String
Description	Indicates the First Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MIDNAME

Attribute	Description
Name	MIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LASTNAME

Attribute	Description
Name	LASTNAME
Datatype	String
Description	Indicates the Last Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SEX

Attribute	Description
Name	SEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,F

TOP

PPNO

Attribute	Description
Name	PPNO
Datatype	String
Description	Indicates Passport Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PPTISSDT

Attribute	Description
Name	PPTISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PPTEXPDT

Attribute	Description
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADD3

Attribute	Description
Name	ADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255

TOP

SSN

Attribute	Description	
Name	SSN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	11

TOP

DECEASED

Attribute	Description	
Name	DECEASED	
Datatype	String	
Description	Indicates whether Deceased or not. The value should be either D or N.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	D,N

TOP

RESISTAT

Attribute	Description	
Name	RESISTAT	
Datatype	String	
Description	Indicates the Resistant Status. The value could be either R or N.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	R,N

TOP

Cust-Acc-Det

Attribute	Description	
Name	Cust-Acc-Det	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

Diary-Mst

Attribute	Description
Name	Diary-Mst
Datatype	
Description	Indicates Diary Master.
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	Indicates Instrument Number
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 16

TOP

UNTTYP

Attribute	Description
Name	UNTTYP
Datatype	String
Description	Indicates Unit Type
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

UNTVAL

Attribute	Description
Name	UNTVAL
Datatype	String

Description	Indicates Unit Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BRN

Attribute	**Description**
Name	BRN
Datatype	String
Description	Indicates the Branch Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INSTR

Attribute	**Description**
Name	INSTR
Datatype	String
Description	Indicates Instructions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

INSTRTYPE

Attribute	**Description**
Name	INSTRTYPE
Datatype	String
Description	Indicates Instruction Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

EXEDAYS

Attribute	**Description**
Name	EXEDAYS
Datatype	Number
Description	Indicates Execution Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXEMONTHS

Attribute	Description
Name	EXEMONTHS
Datatype	Number
Description	Indicates Execution Months
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXEYEARS

Attribute	Description
Name	EXEYEARS
Datatype	Number
Description	Indicates Execution Years
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MNTHENDFLG

Attribute	Description
Name	MNTHENDFLG
Datatype	String
Description	Indicates Month End Flag. Flag Can be either Y or N.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

HLDRULE

Attribute	Description
Name	HLDRULE
Datatype	String
Description	Indicates Holiday Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FRSTDUEDT

Attribute	Description
Name	FRSTDUEDT
Datatype	Date
Description	Indicates First Due Date.

Attributes	Attribute	Description
	minOccurs	0

TOP

NXTDUEDT

Attribute	Description
Name	NXTDUEDT
Datatype	Date
Description	Indicates Next Due Date
Attributes	Attribute: minOccurs — Description: 0

TOP

NXTEXEDT

Attribute	Description
Name	NXTEXEDT
Datatype	Date
Description	Indicates Next Execution Date.
Attributes	Attribute: minOccurs — Description: 0

TOP

CONDELEM

Attribute	Description
Name	CONDELEM
Datatype	String
Description	Indicates Condition Elements.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

OPRTR

Attribute	Description
Name	OPRTR
Datatype	String
Description	Indicates Operator.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2

TOP

CONDVAL

Attribute	Description
Name	CONDVAL

Datatype	Number
Description	Indicates Condition Value.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOFCR

Attribute	Description
Name	ACCOFCR
Datatype	String
Description	Indicates Account Officer.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPLINSTRTYP

Attribute	Description
Name	SPLINSTRTYP
Datatype	String
Description	Indicates Special Instruction Type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	Indicates Expiry Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPLINSTR

Attribute	Description
Name	SPLINSTR
Datatype	String
Description	Indicates Special Instructions.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Custaccdet

Attribute	Description
Name	Custaccdet
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkage details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String

Description	Indicates the customer
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RELATIONSHIP

Attribute	**Description**
Name	RELATIONSHIP
Datatype	String
Description	Indicate relations
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

INHERIT

Attribute	**Description**
Name	INHERIT
Datatype	String
Description	Indicate,include relationship Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DESCP

Attribute	**Description**
Name	DESCP
Datatype	String
Description	Indicates description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Custacdetail

Attribute	**Description**
Name	Custacdetail
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

CUSTTEXT

Attribute	Description
Name	CUSTTEXT
Datatype	
Description	Include customer details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	Indicates sequence number
Attributes	Attribute: minOccurs — Description: 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

TDESC

Attribute	Description

Name	TDESC
Datatype	String
Description	Indicate text description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

Sttms-Debit

Attribute	**Description**
Name	Sttms-Debit
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	Indicates the Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACTNO

Attribute	Description
Name	ACTNO
Datatype	String
Description	Indicates the Account Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Sttms-Detail

Attribute	Description
Name	Sttms-Detail
Datatype	
Description	Indicates Customer Details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description

Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REQUEST_REFERENCE_NO

Attribute	**Description**
Name	REQUEST_REFERENCE_NO
Datatype	String
Description	Indicates the Request Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CARDNO

Attribute	**Description**
Name	CARDNO
Datatype	String
Description	Indicates the Card Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 19

TOP

CUST_NO

Attribute	**Description**
Name	CUST_NO
Datatype	String
Description	Indicates the Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CARD_PRODUCT

Attribute	**Description**
Name	CARD_PRODUCT
Datatype	String
Description	Indicates the Product code.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRIMARY_CARD

Attribute	Description	
Name	PRIMARY_CARD	
Datatype	String	
Description	Indicates the Primary Card Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NAME_ON_CARD

Attribute	Description	
Name	NAME_ON_CARD	
Datatype	String	
Description	Indicates the Name on Card.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

OWNER_ID_NO

Attribute	Description	
Name	OWNER_ID_NO	
Datatype	String	
Description	Indicates the Owner ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

CARD_ISSUED_DT

Attribute	Description	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Indicates the Card Issue Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CARD_EXPIRY_DT

Attribute	Description
Name	CARD_EXPIRY_DT
Datatype	Date
Description	Indicates the Card Expiry Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CARD_STATUS

Attribute	Description
Name	CARD_STATUS
Datatype	String
Description	Indicates the Card Status.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	Indicates the Record Stat.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTH_STAT

Attribute	Description
Name	AUTH_STAT
Datatype	String
Description	Indicates the Auth Stat.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CARD_BIN

Attribute	Description
Name	CARD_BIN

Datatype	String
Description	Indicates the Card Bin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CUST_AC_NO

Attribute	**Description**
Name	CUST_AC_NO
Datatype	String
Description	Indicates the Customer Account Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Extsys-Ws-Master

Attribute	**Description**
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	**Description**
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXTWSRESP

Attribute	**Description**
Name	EXTWSRESP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

Stvws-Cust-Trntax

Attribute	Description
Name	Stvws-Cust-Trntax
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Sttms-Cust-Trn-Tax

Attribute	Description
Name	Sttms-Cust-Trn-Tax
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TAX_SCHEME

Attribute	Description
Name	TAX_SCHEME
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

TXN_TAX_EXEMPTED

Attribute	**Description**
Name	TXN_TAX_EXEMPTED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TXN_TAX_EXEMPTION_PERCENT

Attribute	**Description**
Name	TXN_TAX_EXEMPTION_PERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXN_TAX_EFF_DATE

Attribute	**Description**
Name	TXN_TAX_EFF_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXN_TAX_EXEMPTION_REASON

Attribute	**Description**
Name	TXN_TAX_EXEMPTION_REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.19.4.ST-ModifyCustomer-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Customer-PK*
      - *CUSTNO*
    - *Customer-IO*
      - *NAME*
      - *ADDRLN1*
      - *ADDRLN3*
      - *ADDRLN2*
      - *ADDRLN4*
      - *SWIFTCD*
      - *FAX*
      - *COUNTRY*
      - *NLTY*
      - *LANG*
      - *EXPCNTRY*
      - *UIDNAME*
      - *UIDVAL*
      - *LOC*
      - *FROZEN*

DEAD
WHRUNKN
GRPCD
CHGGRP
CUSTCLGGRP
TAXGROUP
CCATEG
EXPCAT
CUSTCLASSFN
FXNETTCUST
XREF
MEDIA
SSN
CIFSTAT
CIFSTATSNC
MAILRSREQD
CLSPARTICIPANT
CRMCUST
ISSUCUST
TRSRYCUST
CUSTNO
SNAME
LBRN
CTYPE
LIABID
FULLNAME
AMLCUSTGRP
AMLREQD
FLGUTLTYPRVDR
UTLTYPRVDRID
CHKDIGITVALREQD
ALGID
CONSTAXCERTRQD
INDTAXCERTRQD
HOACNO
RISKPRFL
DRCAT
FTACCASOF
UDF1
UDF2
UDF3
UDF4
UDF5
UDFLBL1

UDFLBL2
UDFLBL3
UDFLBL4
UDFLBL5
FXCUSTCLRILIM
OVRLIM
FX_CLEAN_RISK
CRRATE
REVDT
LIMCCY
SECCUSTCLRILIM
SECCLRILIM
SECCUSTPSRILIM
SECPSRILIM
CUSTUNADV
RISKCATEG
CLSCCYALLWD
NETTREQD
LIABUNADV
MT920
RELPRICING
FLGJOINT
KYCSTAT
SSTAFF
KYC_REFNO
JOINT_VENTURE
PRIVATE_CUSTOMER
LC_COLLAT_PCT
ISELCMCUST
ALT_CUST_NO
DETERIORATION_DATE
MAKER
MAKERSTAMP
Custpersonal
- *TITLE*
- *FSTNAME*
- *MIDNAME*
- *LSTNAME*
- *DOB*
- *GUARDIAN*
- *MINOR*
- *SEX*
- *NATIONID*
- *PPTNO*

PPTISSDT
PPTEXPDT
DADD1
DADD2
DADD3
TEL
FAX
EMAIL
PADD1
PADD2
PADD3
DCNTRY
PCNTRY
RESSTATUS
CUSTPREFIX1
CUSTPREFIX2
MOBNUM
SBMTAGEPROOF
CUST_COMM_MODE
Custdomestic
- *EDUSTAT*
- *MARITALSTAT*
- *SPNAME*
- *SPEMPSTATUS*
- *DEPCHILD*
- *DEPOTH*
- *ACCOMODATE*

Custprof
- *EMPSTAT*
- *EMPTENURE*
- *RETIREAGE*
- *PREVDESIG*
- *PREVEMP*
- *CURRDESIG*
- *CURREMP*
- *ADD1*
- *ADD2*
- *ADD3*
- *TEL*
- *TELEX*
- *FAX*
- *EMAIL*
- *SALARY*
- *OTHER1*

RENT
INSURANCE
LOANPMNT
OTHEXP
HOUSEVAL
CRCARD
CNTY
AMTCCY1
Custcorp
CORPNAME
NATIONID
REGADD1
REGADD2
REGADD3
INCORPDT
CAPITAL
NETWORTH
INCORPCNTRY
REGCNTRY
AMTCCY
CORPDESC
Custcorpdir
DIRNAME
CUSTNO
TEL
NADDR1
NADDR2
NADDR3
NADDR4
ADDR1
ADDRS2
ADDRS3
COUNTRY
TAXID
MOBNO
EMAIL
Issuerdet
OVERLIMIT
OVERLMTCCY
Issuerlmts
CLTRLTYP
LMTAMT
LMTCCY
ISSID

Custgrp

- *GRPNO*
- *RELATION*

Custshhold

- *SHHOLDID*
- *SHHOLDPCT*
- *SHRHLDRNAME*

Clsccyrest

- *CCY*
- *DESC*

Bic

- *ACC*
- *BICCD*

Linkedac

- *VRFD*
- *LINKEDACCNO*
- *LINKEDACCIBAN*
- *LINKEDACCBIC*

JointVenture

- *CUSTOMER_NO*
- *PARTYID*
- *PARTYRATIO*
- *PARTYNAME*

Custdoc-Chklist

- *CUSTOMER_NO*
- *DOCUMENT_TYPE*
- *CHECKED*

Doctype-Remarks

- *CUSTOMER_NO*
- *REMARK1*
- *REMARK2*
- *REMARK3*
- *REMARK4*
- *REMARK5*
- *REMARK6*
- *REMARK7*
- *REMARK8*
- *REMARK9*
- *REMARK10*

Custmis

- *MISGRP*
- *CUSTMIS1*
- *CUSTMIS2*
- *CUSTMIS3*

- *CUSTMIS4*
- *CUSTMIS5*
- *CUSTMIS6*
- *CUSTMIS7*
- *CUSTMIS8*
- *CUSTMIS9*
- *CUSTMIS10*
- *COMPMIS1*
- *COMPMIS2*
- *COMPMIS3*
- *COMPMIS4*
- *COMPMIS5*
- *COMPMIS6*
- *COMPMIS7*
- *COMPMIS8*
- *COMPMIS9*
- *COMPMIS10*
- *CUSTNO*
- *Custchnglog*
  - *MISCLS*
  - *TXNDT*
  - *OLDMISCD*
  - *NWMISCD*
- *Baltrnsfrlog*
  - *BRN*
  - *PRDCD*
  - *FINYR*
  - *TXNDT*
  - *GLCODE*
  - *MISCLS*
  - *OLDMISCD*
  - *NWMISCD*
  - *TRNIND*
  - *CCY*
  - *XRATE*
- *Dfltcd*
- *Dfltcda*

Jointcustomer

- *CUSTNO*
- *Custjoint*
  - *CUSTPREFIX*
  - *FRSTNAME*
  - *MIDNAME*
  - *LASTNAME*

DOB

SEX

PPNO

PPTISSDT

PPTEXPDT

ADD1

ADD2

ADD3

TEL

EMAIL

DECEASED

RESISTAT

Cust-Acc-Det

CUSTNO

Diary-Mst

INSTRNO

UNTTYP

UNTVAL

BRN

INSTR

INSTRTYPE

EXEDAYS

EXEMONTHS

EXEYEARS

MNTHENDFLG

HLDRULE

FRSTDUEDT

NXTDUEDT

NXTEXEDT

CONDELEM

OPRTR

CONDVAL

ACCOFCR

SPLINSTRTYP

EXPDT

SPLINSTR

Custaccdet

CUSTNO

Relationship-Linkage

CUSTOMER

RELATIONSHIP

INHERIT

DESCP

Custacdetail

CUSTNO

CUSTTEXT

SEQNO

CUSTNO

TDESC

UDFDETAILS

FLDNAM

FLDVAL

Sttms-Debit

BRANCH_CODE

CUST_NO

ACTNO

Extsys-Ws-Master

KEYID

Stvws-Cust-Trntax

CUSTOMER_NO

Sttms-Cust-Trn-Tax

TAX_SCHEME

TXN_TAX_EXEMPTED

TXN_TAX_EXEMPTION_PERCENT

TXN_TAX_EFF_DATE

TXN_TAX_EXEMPTION_REASON

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Customer-PK

Attribute	Description
Name	Customer-PK
Datatype	
Description	

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Customer-IO

Attribute	Description
Name	Customer-IO
Datatype	
Description	

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

ADDRLN1

Attribute	Description	
Name	ADDRLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN3

Attribute	Description	
Name	ADDRLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN2

Attribute	Description
Name	ADDRLN2
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN4

Attribute	Description	
Name	ADDRLN4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SWIFTCD

Attribute	Description	
Name	SWIFTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

FAX

Attribute	Description	
Name	FAX	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRY

Attribute	Description	
Name	COUNTRY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	3

TOP

NLTY

Attribute	Description	
Name	NLTY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

LANG

Attribute	Description	
Name	LANG	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

EXPCNTRY

Attribute	Description	
Name	EXPCNTRY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

UIDNAME

Attribute	Description	
Name	UIDNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

UIDVAL

Attribute	Description
Name	UIDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LOC

Attribute	Description
Name	LOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FROZEN

Attribute	Description
Name	FROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEAD

Attribute	Description
Name	DEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

WHRUNKN

Attribute	Description
Name	WHRUNKN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

CHGGRP

Attribute	Description
Name	CHGGRP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

CUSTCLGGRP

Attribute	Description
Name	CUSTCLGGRP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TAXGROUP

Attribute	Description
Name	TAXGROUP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CCATEG

Attribute	Description
Name	CCATEG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUSTCLASSFN

Attribute	Description
Name	CUSTCLASSFN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

FXNETTCUST

Attribute	Description
Name	FXNETTCUST
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SSN

Attribute	Description
Name	SSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

CIFSTAT

Attribute	Description
Name	CIFSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

CIFSTATSNC

Attribute	Description
Name	CIFSTATSNC
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAILRSREQD

Attribute	Description
Name	MAILRSREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CLSPARTICIPANT

Attribute	Description
Name	CLSPARTICIPANT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CRMCUST

Attribute	Description
Name	CRMCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ISSUCUST

Attribute	Description
Name	ISSUCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TRSRYCUST

Attribute	Description
Name	TRSRYCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

SNAME

Attribute	Description
Name	SNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

LBRN

Attribute	Description
Name	LBRN

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CTYPE

Attribute	**Description**
Name	CTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,C,B

TOP

LIABID

Attribute	**Description**
Name	LIABID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

FULLNAME

Attribute	**Description**
Name	FULLNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

AMLCUSTGRP

Attribute	**Description**
Name	AMLCUSTGRP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

AMLREQD

Attribute	Description
Name	AMLREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FLGUTLTYPRVDR

Attribute	Description
Name	FLGUTLTYPRVDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UTLTYPRVDRID

Attribute	Description
Name	UTLTYPRVDRID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKDIGITVALREQD

Attribute	Description
Name	CHKDIGITVALREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

ALGID

Attribute	Description	
Name	ALGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

CONSTAXCERTRQD

Attribute	Description	
Name	CONSTAXCERTRQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

INDTAXCERTRQD

Attribute	Description	
Name	INDTAXCERTRQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

HOACNO

Attribute	Description	
Name	HOACNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RISKPRFL

Attribute	Description	
Name	RISKPRFL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

DRCAT

Attribute	Description	
Name	DRCAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FTACCASOF

Attribute	Description	
Name	FTACCASOF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,M,D

TOP

UDF1

Attribute	Description	
Name	UDF1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

UDF2

Attribute	Description
Name	UDF2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDF3

Attribute	Description
Name	UDF3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

UDF4

Attribute	Description
Name	UDF4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

UDF5

Attribute	Description
Name	UDF5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDFLBL1

Attribute	Description
Name	UDFLBL1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL2

Attribute	Description
Name	UDFLBL2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL3

Attribute	Description
Name	UDFLBL3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL4

Attribute	Description
Name	UDFLBL4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL5

Attribute	Description
Name	UDFLBL5
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

FXCUSTCLRILIM

Attribute	Description
Name	FXCUSTCLRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OVRLIM

Attribute	Description
Name	OVRLIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FX_CLEAN_RISK

Attribute	Description
Name	FX_CLEAN_RISK
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CRRATE

Attribute	Description
Name	CRRATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

REVDT

Attribute	Description
Name	REVDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIMCCY

Attribute	**Description**
Name	LIMCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SECCUSTCLRILIM

Attribute	**Description**
Name	SECCUSTCLRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCLRILIM

Attribute	**Description**
Name	SECCLRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCUSTPSRILIM

Attribute	**Description**
Name	SECCUSTPSRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECPSRILIM

Attribute	**Description**
Name	SECPSRILIM

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTUNADV

Attribute	Description
Name	CUSTUNADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RISKCATEG

Attribute	Description
Name	RISKCATEG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CLSCCYALLWD

Attribute	Description
Name	CLSCCYALLWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

NETTREQD

Attribute	Description
Name	NETTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

LIABUNADV

Attribute	Description	
Name	LIABUNADV	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

MT920

Attribute	Description	
Name	MT920	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

RELPRICING

Attribute	Description	
Name	RELPRICING	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

FLGJOINT

Attribute	Description	
Name	FLGJOINT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

KYCSTAT

Attribute	Description
Name	KYCSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / V,N,F

TOP

SSTAFF

Attribute	Description
Name	SSTAFF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

KYC_REFNO

Attribute	Description
Name	KYC_REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

JOINT_VENTURE

Attribute	Description
Name	JOINT_VENTURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIVATE_CUSTOMER

Attribute	Description
Name	PRIVATE_CUSTOMER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LC_COLLAT_PCT

Attribute	Description
Name	LC_COLLAT_PCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISELCMCUST

Attribute	Description
Name	ISELCMCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALT_CUST_NO

Attribute	Description
Name	ALT_CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DETERIORATION_DATE

Attribute	Description
Name	DETERIORATION_DATE
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

Custpersonal

Attribute	Description
Name	Custpersonal
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TITLE

Attribute	Description
Name	TITLE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FSTNAME

Attribute	Description
Name	FSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MIDNAME

Attribute	Description
Name	MIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LSTNAME

Attribute	Description
Name	LSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GUARDIAN

Attribute	Description
Name	GUARDIAN
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MINOR

Attribute	Description
Name	MINOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SEX

Attribute	Description
Name	SEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,F

TOP

NATIONID

Attribute	Description
Name	NATIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PPTNO

Attribute	Description
Name	PPTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

PPTISSDT

Attribute	Description
Name	PPTISSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PPTEXPDT

Attribute	Description
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DADD1

Attribute	Description
Name	DADD1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

DADD2

Attribute	Description
Name	DADD2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

DADD3

Attribute	Description
Name	DADD3

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FAX

Attribute	Description
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PADD1

Attribute	Description
Name	PADD1
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PADD2

Attribute	Description
Name	PADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PADD3

Attribute	Description
Name	PADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DCNTRY

Attribute	Description
Name	DCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PCNTRY

Attribute	Description
Name	PCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RESSTATUS

Attribute	**Description**
Name	RESSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,N

TOP

CUSTPREFIX1

Attribute	**Description**
Name	CUSTPREFIX1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

CUSTPREFIX2

Attribute	**Description**
Name	CUSTPREFIX2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

MOBNUM

Attribute	**Description**
Name	MOBNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SBMTAGEPROOF

Attribute	Description
Name	SBMTAGEPROOF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,P,V

TOP

CUST_COMM_MODE

Attribute	Description
Name	CUST_COMM_MODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,E

TOP

Custdomestic

Attribute	Description
Name	Custdomestic
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

EDUSTAT

Attribute	Description
Name	EDUSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,U,G,P

TOP

MARITALSTAT

Attribute	Description
Name	MARITALSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	S,M,D,R,P,E,T

TOP

SPNAME

Attribute	Description	
Name	SPNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SPEMPSTATUS

Attribute	Description	
Name	SPEMPSTATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	F,T,S,U,R,P,N,O

TOP

DEPCHILD

Attribute	Description	
Name	DEPCHILD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DEPOTH

Attribute	Description	
Name	DEPOTH	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACCOMODATE

Attribute	Description
Name	ACCOMODATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,O

TOP

Custprof

Attribute	Description
Name	Custprof
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EMPSTAT

Attribute	Description
Name	EMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

EMPTENURE

Attribute	Description
Name	EMPTENURE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RETIREAGE

Attribute	Description
Name	RETIREAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PREVDESIG

Attribute	Description
Name	PREVDESIG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

PREVEMP

Attribute	Description
Name	PREVEMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CURRDESIG

Attribute	Description
Name	CURRDESIG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CURREMP

Attribute	Description
Name	CURREMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADD3

Attribute	Description
Name	ADD3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

TELEX

Attribute	Description
Name	TELEX

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FAX

Attribute	Description
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

SALARY

Attribute	Description
Name	SALARY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHER1

Attribute	Description
Name	OTHER1
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RENT

Attribute	Description
Name	RENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSURANCE

Attribute	Description
Name	INSURANCE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANPMNT

Attribute	Description
Name	LOANPMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHEXP

Attribute	Description
Name	OTHEXP
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HOUSEVAL

Attribute	Description
Name	HOUSEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CRCARD

Attribute	Description
Name	CRCARD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMTCCY1

Attribute	Description
Name	AMTCCY1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Custcorp

Attribute	Description
Name	Custcorp
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CORPNAME

Attribute	Description
Name	CORPNAME
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

NATIONID

Attribute	Description	
Name	NATIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REGADD1

Attribute	Description	
Name	REGADD1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REGADD2

Attribute	Description	
Name	REGADD2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REGADD3

Attribute	Description	
Name	REGADD3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

INCORPDT

Attribute	Description
Name	INCORPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CAPITAL

Attribute	Description
Name	CAPITAL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NETWORTH

Attribute	Description
Name	NETWORTH
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

INCORPCNTRY

Attribute	Description
Name	INCORPCNTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

REGCNTRY

Attribute	Description
Name	REGCNTRY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CORPDESC

Attribute	Description
Name	CORPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Custcorpdir

Attribute	Description
Name	Custcorpdir
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

DIRNAME

Attribute	Description
Name	DIRNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR1

Attribute	Description
Name	NADDR1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR2

Attribute	Description
Name	NADDR2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR3

Attribute	Description
Name	NADDR3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

NADDR4

Attribute	Description
Name	NADDR4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRY

Attribute	**Description**
Name	COUNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TAXID

Attribute	**Description**
Name	TAXID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MOBNO

Attribute	**Description**
Name	MOBNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EMAIL

Attribute	**Description**
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255

TOP

Issuerdet

Attribute	Description	
Name	Issuerdet	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OVERLIMIT

Attribute	Description	
Name	OVERLIMIT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

OVERLMTCCY

Attribute	Description	
Name	OVERLMTCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Issuerlmts

Attribute	Description	
Name	Issuerlmts	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

CLTRLTYP

Attribute	Description
Name	CLTRLTYP
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 70

TOP

LMTAMT

Attribute	**Description**
Name	LMTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LMTCCY

Attribute	**Description**
Name	LMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ISSID

Attribute	**Description**
Name	ISSID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Custgrp

Attribute	**Description**
Name	Custgrp
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

GRPNO

Attribute	Description
Name	GRPNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RELATION

Attribute	Description
Name	RELATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Custshhold

Attribute	Description
Name	Custshhold
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

SHHOLDID

Attribute	Description
Name	SHHOLDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SHHOLDPCT

Attribute	Description

Name	SHHOLDPCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHRHLDRNAME

Attribute	**Description**
Name	SHRHLDRNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Clsccyrest

Attribute	**Description**
Name	Clsccyrest
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Bic

Attribute	Description
Name	Bic
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BICCD

Attribute	Description
Name	BICCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

Linkedac

Attribute	Description
Name	Linkedac
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VRFD

Attribute	Description
Name	VRFD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LINKEDACCNO

Attribute	**Description**
Name	LINKEDACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LINKEDACCIBAN

Attribute	**Description**
Name	LINKEDACCIBAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LINKEDACCBIC

Attribute	**Description**
Name	LINKEDACCBIC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

JointVenture

Attribute	**Description**
Name	JointVenture
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

PARTYRATIO

Attribute	Description
Name	PARTYRATIO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

Custdoc-Chklist

Attribute	Description
Name	Custdoc-Chklist
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHECKED

Attribute	Description
Name	CHECKED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Doctype-Remarks

Attribute	Description
Name	Doctype-Remarks

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REMARK1

Attribute	Description
Name	REMARK1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 225

TOP

REMARK2

Attribute	Description
Name	REMARK2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 225

TOP

REMARK3

Attribute	Description
Name	REMARK3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	225

TOP

REMARK4

Attribute	Description
Name	REMARK4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK5

Attribute	Description
Name	REMARK5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK6

Attribute	Description
Name	REMARK6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK7

Attribute	Description
Name	REMARK7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK8

Attribute	Description
Name	REMARK8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK9

Attribute	Description
Name	REMARK9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK10

Attribute	Description
Name	REMARK10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

Custmis

Attribute	Description
Name	Custmis
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP

Datatype	String
Description	Indicates the MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CUSTMIS1

Attribute	Description
Name	CUSTMIS1
Datatype	String
Description	Indicates the Customer MIS 1.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTMIS2

Attribute	Description
Name	CUSTMIS2
Datatype	String
Description	Indicates the Customer MIS 2.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTMIS3

Attribute	Description
Name	CUSTMIS3
Datatype	String
Description	Indicates the Customer MIS 3.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTMIS4

Attribute	Description
Name	CUSTMIS4
Datatype	String
Description	Indicates the Customer MIS 4.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTMIS5

Attribute	**Description**	
Name	CUSTMIS5	
Datatype	String	
Description	Indicates the Customer MIS 5.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTMIS6

Attribute	**Description**	
Name	CUSTMIS6	
Datatype	String	
Description	Indicates the Customer MIS 6.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTMIS7

Attribute	**Description**	
Name	CUSTMIS7	
Datatype	String	
Description	Indicates the Customer MIS 7.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTMIS8

Attribute	**Description**	
Name	CUSTMIS8	
Datatype	String	
Description	Indicates the Customer MIS 8.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	9

TOP

CUSTMIS9

Attribute	Description
Name	CUSTMIS9
Datatype	String
Description	Indicates the Customer MIS 9.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

CUSTMIS10

Attribute	Description
Name	CUSTMIS10
Datatype	String
Description	Indicates the Customer MIS 10.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the Composite MIS 1.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the Composite MIS 2.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the Composite MIS 3.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the Composite MIS 4.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the Composite MIS 5.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the Composite MIS 6.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the Composite MIS 7.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the Composite MIS 8.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the Composite MIS 9.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the Composite MIS 10.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNO

Attribute	Description
Name	CUSTNO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Custchnglog

Attribute	Description
Name	Custchnglog
Datatype	
Description	Indicates the Customer Change Log.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	Indicates the Old MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	Indicates the New MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Baltrnsfrlog

Attribute	Description
Name	Baltrnsfrlog
Datatype	
Description	Indicates the Balance Transfer Log.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	Description

Name	FINYR
Datatype	String
Description	Indicates the Financial year.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates the GL Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	Indicates the Old MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NWMISCD

Attribute	**Description**
Name	NWMISCD
Datatype	String
Description	Indicates the New MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TRNIND

Attribute	**Description**
Name	TRNIND
Datatype	String
Description	Indicates Transfer Identification Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

XRATE

Attribute	**Description**
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Dfltcd

Attribute	Description
Name	Dfltcd
Datatype	
Description	Indicates the Customer MIS Classes.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Dfltcda

Attribute	Description
Name	Dfltcda
Datatype	
Description	Indicates the Composite MIS Classes.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Jointcustomer

Attribute	Description
Name	Jointcustomer
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Custjoint

Attribute	Description
Name	Custjoint
Datatype	
Description	Indicates the Customer Joint.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTPREFIX

Attribute	Description
Name	CUSTPREFIX
Datatype	String
Description	Indicates the Customer Prefix.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FRSTNAME

Attribute	Description
Name	FRSTNAME
Datatype	String
Description	Indicates the First Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MIDNAME

Attribute	Description
Name	MIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LASTNAME

Attribute	Description
Name	LASTNAME
Datatype	String
Description	Indicates the Last Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SEX

Attribute	Description
Name	SEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,F

TOP

PPNO

Attribute	Description
Name	PPNO
Datatype	String
Description	Indicates the Passport Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PPTISSDT

Attribute	Description
Name	PPTISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PPTEXPDT

Attribute	Description
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADD3

Attribute	Description
Name	ADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

DECEASED

Attribute	Description
Name	DECEASED
Datatype	String
Description	Indicates whether Deceased or not. The value should be either D or N.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,N

TOP

RESISTAT

Attribute	Description
Name	RESISTAT
Datatype	String
Description	Indicates the Resident Status. The Value could be either R or N.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / R,N

TOP

Cust-Acc-Det

Attribute	Description
Name	Cust-Acc-Det
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Diary-Mst

Attribute	Description	
Name	Diary-Mst	
Datatype		
Description	Indicates Diary Master.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

INSTRNO

Attribute	Description	
Name	INSTRNO	
Datatype	String	
Description	Indicates Instrument Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

UNTTYP

Attribute	Description	
Name	UNTTYP	
Datatype	String	
Description	Indicates Unit Type.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

UNTVAL

Attribute	Description	
Name	UNTVAL	
Datatype	String	
Description	Indicates Unit Value.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String
Description	Indicates the Branch Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

INSTR

Attribute	Description
Name	INSTR
Datatype	String
Description	Indicates Instructions.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

INSTRTYPE

Attribute	Description
Name	INSTRTYPE
Datatype	String
Description	Indicates Instruction Type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

EXEDAYS

Attribute	Description
Name	EXEDAYS
Datatype	Number
Description	Indicates Execution days.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXEMONTHS

Attribute	Description
Name	EXEMONTHS

Datatype	Number
Description	Indicates Execution Months.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXEYEARS

Attribute	Description
Name	EXEYEARS
Datatype	Number
Description	Indicates Execution years.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MNTHENDFLG

Attribute	Description
Name	MNTHENDFLG
Datatype	String
Description	Indicates Month End Flag. Flag Value can be either Y or N.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

HLDRULE

Attribute	Description
Name	HLDRULE
Datatype	String
Description	Indicates Holiday Rule.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

FRSTDUEDT

Attribute	Description
Name	FRSTDUEDT
Datatype	Date
Description	Indicates First Due date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NXTDUEDT

Attribute	Description
Name	NXTDUEDT
Datatype	Date
Description	Indicates Next Due Date.
Attributes	Attribute: minOccurs, Description: 0

TOP

NXTEXEDT

Attribute	Description
Name	NXTEXEDT
Datatype	Date
Description	Indicates Next Execution Date.
Attributes	Attribute: minOccurs, Description: 0

TOP

CONDELEM

Attribute	Description
Name	CONDELEM
Datatype	String
Description	Indicates Condition Elements.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 20

TOP

OPRTR

Attribute	Description
Name	OPRTR
Datatype	String
Description	Indicates Operator.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 2

TOP

CONDVAL

Attribute	Description
Name	CONDVAL
Datatype	Number
Description	Indicates Condition Value.
Attributes	Attribute: minOccurs, Description: 0

TOP

ACCOFCR

Attribute	Description
Name	ACCOFCR
Datatype	String
Description	Indicates Account Officer.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPLINSTRTYP

Attribute	Description
Name	SPLINSTRTYP
Datatype	String
Description	Indicates Special Instruction Type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	Indicates Expiry Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPLINSTR

Attribute	Description
Name	SPLINSTR
Datatype	String
Description	Indicates special Instruction.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Custaccdet

Attribute	Description
Name	Custaccdet

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkage details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Indicates the customer
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Indicate relations
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicate,include relationship Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	Indicates description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Custacdetail

Attribute	Description
Name	Custacdetail
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTTEXT

Attribute	Description
Name	CUSTTEXT
Datatype	
Description	Include customer details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	Indicate sequence number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String
Description	Indicate text description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	Restrictions: maxLength = 105; minLength = 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	Attribute: minOccurs = 0
Restrictions	Restrictions: maxLength = 255; minLength = 0

TOP

Sttms-Debit

Attribute	Description
Name	Sttms-Debit
Datatype	
Description	
Attributes	Attribute: minOccurs = 0

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch code.
Attributes	Attribute: minOccurs = 0
Restrictions	Restrictions: maxLength = 3

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	Indicates the Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACTNO

Attribute	Description
Name	ACTNO
Datatype	String
Description	Indicates the Account Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

KEYID

Attribute	Description
Name	KEYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 200

TOP

Stvws-Cust-Trntax

Attribute	Description
Name	Stvws-Cust-Trntax
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Sttms-Cust-Trn-Tax

Attribute	Description
Name	Sttms-Cust-Trn-Tax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TAX_SCHEME

Attribute	Description
Name	TAX_SCHEME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

TXN_TAX_EXEMPTED

Attribute	Description
Name	TXN_TAX_EXEMPTED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TXN_TAX_EXEMPTION_PERCENT

Attribute	Description
Name	TXN_TAX_EXEMPTION_PERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXN_TAX_EFF_DATE

Attribute	Description
Name	TXN_TAX_EFF_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXN_TAX_EXEMPTION_REASON

Attribute	Description
Name	TXN_TAX_EXEMPTION_REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.20.ModifyTDAmountBlock

ModifyTDAmountBlock

2.20.1.ST-ModifyTDAmountBlock-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-Full*
    - *ACC*
    - *AMTBLKNO*
    - *AMT*
    - *EXPDATE*
    - *REM*
    - *ABLKTYPE*
    - *REFERENCE_NO*
    - *HPCODE*
    - *EFFDATE*
    - *HOLDDESC*
    - *BRANCH*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Amount-Blocks-Full

Attribute	Description
Name	Amount-Blocks-Full
Datatype	
Description	

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTBLKNO

Attribute	Description	
Name	AMTBLKNO	
Datatype	String	
Description	Indicates the Amount Block Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

EXPDATE

Attribute	Description	
Name	EXPDATE	
Datatype	Date	
Description	Indicates the Expiry Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ABLKTYPE

Attribute	Description
Name	ABLKTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,S,P,E,A,C,B,D

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 40

TOP

HPCODE

Attribute	Description
Name	HPCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

HOLDDESC

Attribute	Description
Name	HOLDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies whether the record is authorized or not	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	UDF Details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

TOP

2.20.2.ST-ModifyTDAmountBlock-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-IO*
    - *ACC*
    - *AMTBLKNO*
    - *AMT*
    - *EXPDATE*
    - *REM*
    - *EFFDATE*
    - *MODNO*
    - *UDFDETAILS*
      - *FLDNAM*
      - *FLDVAL*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length 3; pattern [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0; nillable true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description

Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Amount-Blocks-IO

Attribute	Description
Name	Amount-Blocks-IO
Datatype	
Description	

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account Number

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

TOP

2.20.3.ST-ModifyTDAmountBlock-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-Full*
    - *ACC*
    - *AMTBLKNO*
    - *AMT*
    - *EXPDATE*
    - *REM*
    - *ABLKTYPE*
    - *REFERENCE_NO*
    - *HPCODE*
    - *EFFDATE*
    - *HOLDDESC*
    - *BRANCH*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String

Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Amount-Blocks-Full

Attribute	Description
Name	Amount-Blocks-Full
Datatype	
Description	

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTBLKNO

Attribute	Description	
Name	AMTBLKNO	
Datatype	String	
Description	Indicates the Amount Block Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ABLKTYPE

Attribute	Description
Name	ABLKTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,S,P,E,A,C,B,D

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 40

TOP

HPCODE

Attribute	Description
Name	HPCODE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HOLDDESC

Attribute	Description
Name	HOLDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description

Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.20.4.ST-ModifyTDAmountBlock-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Amount-Blocks-PK*
      - *AMTBLKNO*
    - *Amount-Blocks-IO*
      - *ACC*
      - *AMTBLKNO*
      - *AMT*
      - *EXPDATE*
      - *REM*
      - *EFFDATE*
      - *MODNO*
      - *UDFDETAILS*
        - *FLDNAM*
        - *FLDVAL*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Amount-Blocks-PK

Attribute	Description
Name	Amount-Blocks-PK
Datatype	
Description	

TOP

AMTBLKNO

Attribute	Description	
Name	AMTBLKNO	
Datatype	String	
Description	Indicates the Amount Block Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Amount-Blocks-IO

Attribute	Description
Name	Amount-Blocks-IO
Datatype	
Description	

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTBLKNO

Attribute	Description

Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** totalDigits / 22

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.21.QueryCustomer

Query of Customer

2.21.1.ST-QueryCustomer-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Customer-IO*
    - *CUSTNO*
    - *ALT_CUST_NO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Customer-IO

Attribute	Description
Name	Customer-IO
Datatype	
Description	

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ALT_CUST_NO

Attribute	Description
Name	ALT_CUST_NO
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>20</td></tr></table>

TOP

2.21.2.ST-QueryCustomer-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Customer-IO*
      - *CUSTNO*
      - *ALT_CUST_NO*
    - *Customer-Full*
      - *NAME*
      - *ADDRLN1*
      - *ADDRLN3*
      - *ADDRLN2*
      - *ADDRLN4*
      - *SWIFTCD*
      - *FAX*
      - *COUNTRY*
      - *NLTY*
      - *LANG*
      - *EXPCNTRY*
      - *UIDNAME*
      - *UIDVAL*
      - *LOC*

FROZEN
DEAD
WHRUNKN
GRPCD
CHGGRP
CUSTCLGGRP
TAXGROUP
CCATEG
EXPCAT
CUSTCLASSFN
FXNETTCUST
XREF
MEDIA
SSN
CIFSTAT
CIFSTATSNC
MAILRSREQD
CLSPARTICIPANT
CRMCUST
ISSUCUST
TRSRYCUST
CUSTNO
SNAME
LBRN
CTYPE
FULLNAME
AMLCUSTGRP
AMLREQD
FLGUTLTYPRVDR
UTLTYPRVDRID
CHKDIGITVALREQD
ALGID
CONSTAXCERTRQD
INDTAXCERTRQD
HOACNO
RISKPRFL
DRCAT
FTACCASOF
UDF1
UDF2
UDF3
UDF4
UDF5
UDFLBL1

UDFLBL2
UDFLBL3
UDFLBL4
UDFLBL5
FXCUSTCLRILIM
OVRLIM
FX_CLEAN_RISK
CRRATE
REVDT
LIMCCY
SECCUSTCLRILIM
SECCLRILIM
SECCUSTPSRILIM
SECPSRILIM
CUSTUNADV
RISKCATEG
CLSCCYALLWD
NETTREQD
LIABUNADV
MT920
RELPRICING
FLGJOINT
KYCSTAT
SSTAFF
UPTYPE
KYC_REFNO
JOINT_VENTURE
PRIVATE_CUSTOMER
LC_COLLAT_PCT
ISELCMCUST
ELCMCUSTNO
ALT_CUST_NO
DETERIORATION_DATE
CHQ_TAX_EXEMPT_1
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Custpersonal
- *TITLE*
- *FSTNAME*

MIDNAME
LSTNAME
DOB
GUARDIAN
MINOR
SEX
NATIONID
PPTNO
PPTISSDT
PPTEXPDT
DADD1
DADD2
DADD3
TEL
FAX
EMAIL
PADD1
PADD2
PADD3
DCNTRY
PCNTRY
RESSTATUS
CUSTPREFIX1
CUSTPREFIX2
MOBNUM
SBMTAGEPROOF
CUST_COMM_MODE
LAST_UPD_DT
Custdomestic
- *EDUSTAT*
- *MARITALSTAT*
- *SPNAME*
- *SPEMPSTATUS*
- *DEPCHILD*
- *DEPOTH*
- *ACCOMODATE*
- *CUSTNO*

Custprof
- *EMPSTAT*
- *EMPTENURE*
- *RETIREAGE*
- *PREVDESIG*
- *PREVEMP*
- *CURRDESIG*

CURREMP
ADD1
ADD2
ADD3
TEL
TELEX
FAX
EMAIL
SALARY
OTHER1
RENT
INSURANCE
LOANPMNT
OTHEXP
HOUSEVAL
CRCARD
CNTY
AMTCCY1
CUSTNO
EMPLOYER_DESC
EMP_DESC
Custcorp
CORPNAME
NATIONID
REGADD1
REGADD2
REGADD3
INCORPDT
CAPITAL
NETWORTH
INCORPCNTRY
REGCNTRY
AMTCCY
CORPDESC
CUSTNO
Custcorpdir
DIRNAME
TEL
NADDR1
NADDR2
NADDR3
NADDR4
ADDR1
ADDRS2

- *ADDRS3*
- *COUNTRY*
- *TAXID*
- *MOBNO*
- *EMAIL*
- *Issuerdet*
  - *OVERLIMIT*
  - *CUSTNO*
  - *OVERLMTCCY*
  - *Issuerlmts*
    - *CLTRLTYP*
    - *LMTAMT*
    - *LMTCCY*
    - *ISSID*
- *Custgrp*
  - *GRPNO*
  - *RELATION*
- *Custshhold*
  - *SHHOLDID*
  - *SHHOLDPCT*
  - *SHRHLDRNAME*
- *Clsccyrest*
  - *CCY*
  - *DESC*
- *Bic*
  - *ACC*
  - *BICCD*
- *Linkedac*
  - *VRFD*
  - *LINKEDACCNO*
  - *LINKEDACCIBAN*
  - *LINKEDACCBIC*
- *JointVenture*
  - *PARTYID*
  - *PARTYRATIO*
  - *PARTYNAME*
- *Custdoc-Chklist*
  - *DOCUMENT_TYPE*
  - *CHECKED*
- *Doctype-Remarks*
  - *REMARK1*
  - *REMARK2*
  - *REMARK3*
  - *REMARK4*

- *REMARK5*
- *REMARK6*
- *REMARK7*
- *REMARK8*
- *REMARK9*
- *REMARK10*

Custmis

- *MISGRP*
- *CUST*
- *BRNCD*
- *Custchnglog*
  - *MISCLS*
  - *TXNDT*
  - *OLDMISCD*
  - *NWMISCD*
- *Baltrnsfrlog*
  - *BRN*
  - *PRDCD*
  - *FINYR*
  - *TXNDT*
  - *GLCODE*
  - *MISCLS*
  - *OLDMISCD*
  - *NWMISCD*
  - *TRNIND*
  - *CCY*
  - *AMT*
  - *XRATE*
- *Dfltcd*
  - *MISCLS*
  - *MISCD*
- *Dfltcda*
  - *MISCLS*
  - *MISCD*
- *Custloghead*

Jointcustomer

- *CUSTNO*
- *Custjoint*
  - *CUSTPREFIX*
  - *FRSTNAME*
  - *MIDNAME*
  - *LASTNAME*
  - *DOB*
  - *SEX*

PPNO
PPTISSDT
PPTEXPDT
ADD1
ADD2
ADD3
TEL
EMAIL
SSN
DECEASED
RESISTAT
Cust-Acc-Det
CUSTNO
Diary-Mst
INSTRNO
UNTTYP
UNTVAL
BRN
INSTR
INSTRTYPE
EXEDAYS
EXEMONTHS
EXEYEARS
MNTHENDFLG
HLDRULE
FRSTDUEDT
NXTDUEDT
NXTEXEDT
CONDELEM
OPRTR
CONDVAL
ACCOFCR
SPLINSTRTYP
EXPDT
SPLINSTR
Custaccdet
CUSTNO
BRNCD
Relationship-Linkage
CUSTOMER
RELATIONSHIP
INHERIT
DESCP
Custacdetail

CUSTNO
CUSTTEXT
SEQNO
CUSTNO
TDESC
UDFDETAILS
FLDNAM
FLDVAL
Sttms-Debit
BRANCH_CODE
CUST_NO
ACTNO
Sttms-Detail
BRANCH_CODE
REQUEST_REFERENCE_NO
CARDNO
CUST_NO
CARD_PRODUCT
PRIMARY_CARD
NAME_ON_CARD
OWNER_ID_NO
CARD_ISSUED_DT
CARD_EXPIRY_DT
CARD_STATUS
RECORD_STAT
AUTH_STAT
CARD_BIN
CUST_AC_NO
Extsys-Ws-Master
Extsys-Ws-Details
EXTWSRESP
USERREMARKS
Stvws-Cust-Trntax
CUSTOMER_NO
Sttms-Cust-Trn-Tax
TAX_SCHEME
TXN_TAX_EXEMPTED
TXN_TAX_EXEMPTION_PERCENT
TXN_TAX_EFF_DATE
TXN_TAX_EXEMPTION_REASON
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Customer-IO

Attribute	Description
Name	Customer-IO
Datatype	
Description	

TOP

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

ALT_CUST_NO

Attribute	Description	
Name	ALT_CUST_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

Customer-Full

Attribute	Description
Name	Customer-Full
Datatype	
Description	

TOP

NAME

Attribute	Description

Name	NAME
Datatype	String
Description	

TOP

ADDRLN1

Attribute	Description
Name	ADDRLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLN3

Attribute	Description
Name	ADDRLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLN2

Attribute	Description
Name	ADDRLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRLN4

Attribute	Description
Name	ADDRLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SWIFTCD

Attribute	Description
Name	SWIFTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FAX

Attribute	Description
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRY

Attribute	Description
Name	COUNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NLTY

Attribute	Description
Name	NLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

EXPCNTRY

Attribute	Description
Name	EXPCNTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

UIDNAME

Attribute	Description
Name	UIDNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

UIDVAL

Attribute	Description
Name	UIDVAL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

LOC

Attribute	Description
Name	LOC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FROZEN

Attribute	**Description**
Name	FROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEAD

Attribute	**Description**
Name	DEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

WHRUNKN

Attribute	**Description**
Name	WHRUNKN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

GRPCD

Attribute	**Description**
Name	GRPCD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CHGGRP

Attribute	Description
Name	CHGGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CUSTCLGGRP

Attribute	Description
Name	CUSTCLGGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAXGROUP

Attribute	Description
Name	TAXGROUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CCATEG

Attribute	Description
Name	CCATEG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	10

TOP

EXPCAT

Attribute	Description	
Name	EXPCAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

CUSTCLASSFN

Attribute	Description	
Name	CUSTCLASSFN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

FXNETTCUST

Attribute	Description	
Name	FXNETTCUST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SSN

Attribute	Description
Name	SSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

CIFSTAT

Attribute	Description
Name	CIFSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CIFSTATSNC

Attribute	Description
Name	CIFSTATSNC
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAILRSREQD

Attribute	Description
Name	MAILRSREQD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLSPARTICIPANT

Attribute	**Description**
Name	CLSPARTICIPANT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CRMCUST

Attribute	**Description**
Name	CRMCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ISSUCUST

Attribute	**Description**
Name	ISSUCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRSRYCUST

Attribute	**Description**
Name	TRSRYCUST
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SNAME

Attribute	Description
Name	SNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LBRN

Attribute	Description
Name	LBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CTYPE

Attribute	Description
Name	CTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	I,C,B

TOP

FULLNAME

Attribute	Description
Name	FULLNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

AMLCUSTGRP

Attribute	Description
Name	AMLCUSTGRP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

AMLREQD

Attribute	Description
Name	AMLREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

FLGUTLTYPRVDR

Attribute	Description
Name	FLGUTLTYPRVDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

UTLTYPRVDRID

Attribute	Description
Name	UTLTYPRVDRID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKDIGITVALREQD

Attribute	Description
Name	CHKDIGITVALREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALGID

Attribute	Description
Name	ALGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CONSTAXCERTRQD

Attribute	Description
Name	CONSTAXCERTRQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INDTAXCERTRQD

Attribute	Description
Name	INDTAXCERTRQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

HOACNO

Attribute	Description
Name	HOACNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RISKPRFL

Attribute	Description
Name	RISKPRFL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

DRCAT

Attribute	Description
Name	DRCAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FTACCASOF

Attribute	Description
Name	FTACCASOF

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,M,D

TOP

UDF1

Attribute	**Description**
Name	UDF1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDF2

Attribute	**Description**
Name	UDF2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDF3

Attribute	**Description**
Name	UDF3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

UDF4

Attribute	**Description**
Name	UDF4
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

UDF5

Attribute	Description
Name	UDF5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL1

Attribute	Description
Name	UDFLBL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL2

Attribute	Description
Name	UDFLBL2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL3

Attribute	Description
Name	UDFLBL3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	150

TOP

UDFLBL4

Attribute	Description
Name	UDFLBL4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDFLBL5

Attribute	Description
Name	UDFLBL5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

FXCUSTCLRILIM

Attribute	Description
Name	FXCUSTCLRILIM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

OVRLIM

Attribute	Description
Name	OVRLIM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FX_CLEAN_RISK

Attribute	Description
Name	FX_CLEAN_RISK

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CRRATE

Attribute	Description
Name	CRRATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

REVDT

Attribute	Description
Name	REVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIMCCY

Attribute	Description
Name	LIMCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SECCUSTCLRILIM

Attribute	Description
Name	SECCUSTCLRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCLRILIM

Attribute	Description
Name	SECCLRILIM
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

SECCUSTPSRILIM

Attribute	Description
Name	SECCUSTPSRILIM
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

SECPSRILIM

Attribute	Description
Name	SECPSRILIM
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

CUSTUNADV

Attribute	Description
Name	CUSTUNADV
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

RISKCATEG

Attribute	Description
Name	RISKCATEG
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 4

TOP

CLSCCYALLWD

Attribute	Description
Name	CLSCCYALLWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

NETTREQD

Attribute	Description
Name	NETTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIABUNADV

Attribute	Description
Name	LIABUNADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MT920

Attribute	Description
Name	MT920
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RELPRICING

Attribute	Description
Name	RELPRICING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FLGJOINT

Attribute	Description
Name	FLGJOINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

KYCSTAT

Attribute	Description
Name	KYCSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / V,N,F

TOP

SSTAFF

Attribute	Description
Name	SSTAFF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UPTYPE

Attribute	Description
Name	UPTYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

KYC_REFNO

Attribute	**Description**
Name	KYC_REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

JOINT_VENTURE

Attribute	**Description**
Name	JOINT_VENTURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIVATE_CUSTOMER

Attribute	**Description**
Name	PRIVATE_CUSTOMER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LC_COLLAT_PCT

Attribute	**Description**
Name	LC_COLLAT_PCT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

ISELCMCUST

Attribute	Description	
Name	ISELCMCUST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ELCMCUSTNO

Attribute	Description	
Name	ELCMCUSTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ALT_CUST_NO

Attribute	Description	
Name	ALT_CUST_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

DETERIORATION_DATE

Attribute	Description	
Name	DETERIORATION_DATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHQ_TAX_EXEMPT_1

Attribute	Description
Name	CHQ_TAX_EXEMPT_1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Custpersonal

Attribute	**Description**
Name	Custpersonal
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TITLE

Attribute	Description
Name	TITLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FSTNAME

Attribute	Description
Name	FSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MIDNAME

Attribute	Description
Name	MIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LSTNAME

Attribute	Description
Name	LSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GUARDIAN

Attribute	Description
Name	GUARDIAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MINOR

Attribute	Description
Name	MINOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SEX

Attribute	Description
Name	SEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,F

TOP

NATIONID

Attribute	Description
Name	NATIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PPTNO

Attribute	Description
Name	PPTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PPTISSDT

Attribute	Description
Name	PPTISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PPTEXPDT

Attribute	Description
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DADD1

Attribute	Description
Name	DADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DADD2

Attribute	Description
Name	DADD2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

DADD3

Attribute	Description
Name	DADD3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

FAX

Attribute	Description
Name	FAX
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

EMAIL

Attribute	Description
Name	EMAIL

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PADD1

Attribute	Description
Name	PADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PADD2

Attribute	Description
Name	PADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PADD3

Attribute	Description
Name	PADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DCNTRY

Attribute	Description
Name	DCNTRY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PCNTRY

Attribute	Description	
Name	PCNTRY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

RESSTATUS

Attribute	Description	
Name	RESSTATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,N

TOP

CUSTPREFIX1

Attribute	Description	
Name	CUSTPREFIX1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

CUSTPREFIX2

Attribute	Description	
Name	CUSTPREFIX2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	30

TOP

MOBNUM

Attribute	Description
Name	MOBNUM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SBMTAGEPROOF

Attribute	Description
Name	SBMTAGEPROOF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,P,V

TOP

CUST_COMM_MODE

Attribute	Description
Name	CUST_COMM_MODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,E

TOP

LAST_UPD_DT

Attribute	Description
Name	LAST_UPD_DT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Custdomestic

Attribute	Description
Name	Custdomestic

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EDUSTAT

Attribute	Description
Name	EDUSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / N,U,G,P

TOP

MARITALSTAT

Attribute	Description
Name	MARITALSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,M,D,R,P,E,T

TOP

SPNAME

Attribute	Description
Name	SPNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SPEMPSTATUS

Attribute	Description
Name	SPEMPSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	F,T,S,U,R,P,N,O

TOP

DEPCHILD

Attribute	Description
Name	DEPCHILD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DEPOTH

Attribute	Description
Name	DEPOTH
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ACCOMODATE

Attribute	Description
Name	ACCOMODATE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: S,C,O

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

Custprof

Attribute	Description
Name	Custprof

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EMPSTAT

Attribute	Description
Name	EMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

EMPTENURE

Attribute	Description
Name	EMPTENURE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RETIREAGE

Attribute	Description
Name	RETIREAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREVDESIG

Attribute	Description
Name	PREVDESIG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PREVEMP

Attribute	Description
Name	PREVEMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CURRDESIG

Attribute	Description
Name	CURRDESIG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CURREMP

Attribute	Description
Name	CURREMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADD2

Attribute	Description
Name	ADD2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADD3

Attribute	Description
Name	ADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TELEX

Attribute	Description
Name	TELEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FAX

Attribute	Description
Name	FAX
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

SALARY

Attribute	Description
Name	SALARY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHER1

Attribute	Description
Name	OTHER1
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RENT

Attribute	Description
Name	RENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSURANCE

Attribute	Description
Name	INSURANCE

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANPMNT

Attribute	Description
Name	LOANPMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHEXP

Attribute	Description
Name	OTHEXP
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HOUSEVAL

Attribute	Description
Name	HOUSEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CRCARD

Attribute	Description
Name	CRCARD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMTCCY1

Attribute	Description
Name	AMTCCY1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

EMPLOYER_DESC

Attribute	Description
Name	EMPLOYER_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

EMP_DESC

Attribute	Description
Name	EMP_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1000

TOP

Custcorp

Attribute	Description	
Name	Custcorp	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

CORPNAME

Attribute	Description	
Name	CORPNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

NATIONID

Attribute	Description	
Name	NATIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

REGADD1

Attribute	Description	
Name	REGADD1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

REGADD2

Attribute	Description
Name	REGADD2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REGADD3

Attribute	Description
Name	REGADD3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INCORPDT

Attribute	Description
Name	INCORPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CAPITAL

Attribute	Description
Name	CAPITAL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NETWORTH

Attribute	Description
Name	NETWORTH
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

INCORPCNTRY

Attribute	Description
Name	INCORPCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REGCNTRY

Attribute	Description
Name	REGCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CORPDESC

Attribute	Description
Name	CORPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Custcorpdir

Attribute	Description
Name	Custcorpdir
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DIRNAME

Attribute	Description
Name	DIRNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR1

Attribute	Description
Name	NADDR1
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

NADDR2

Attribute	Description
Name	NADDR2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

NADDR3

Attribute	Description
Name	NADDR3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

NADDR4

Attribute	Description
Name	NADDR4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRY

Attribute	Description
Name	COUNTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

TAXID

Attribute	Description
Name	TAXID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

MOBNO

Attribute	Description
Name	MOBNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Issuerdet

Attribute	Description
Name	Issuerdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OVERLIMIT

Attribute	Description
Name	OVERLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OVERLMTCCY

Attribute	**Description**
Name	OVERLMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Issuerlmts

Attribute	**Description**
Name	Issuerlmts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLTRLTYP

Attribute	**Description**
Name	CLTRLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 70

TOP

LMTAMT

Attribute	**Description**
Name	LMTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LMTCCY

Attribute	**Description**

Name	LMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ISSID

Attribute	**Description**
Name	ISSID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Custgrp

Attribute	**Description**
Name	Custgrp
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

GRPNO

Attribute	**Description**
Name	GRPNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RELATION

Attribute	**Description**
Name	RELATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

Custshhold

Attribute	Description	
Name	Custshhold	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SHHOLDID

Attribute	Description	
Name	SHHOLDID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SHHOLDPCT

Attribute	Description	
Name	SHHOLDPCT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SHRHLDRNAME

Attribute	Description	
Name	SHRHLDRNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

Clsccyrest

Attribute	Description

Name	Clsccyrest
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Bic

Attribute	**Description**
Name	Bic
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC

Attribute	**Description**
Name	ACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

BICCD

Attribute	Description
Name	BICCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

Linkedac

Attribute	Description
Name	Linkedac
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

VRFD

Attribute	Description
Name	VRFD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

LINKEDACCNO

Attribute	Description
Name	LINKEDACCNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

LINKEDACCIBAN

Attribute	Description
Name	LINKEDACCIBAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LINKEDACCBIC

Attribute	Description
Name	LINKEDACCBIC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

JointVenture

Attribute	Description
Name	JointVenture
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYRATIO

Attribute	Description
Name	PARTYRATIO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Custdoc-Chklist

Attribute	Description
Name	Custdoc-Chklist
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHECKED

Attribute	Description
Name	CHECKED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Doctype-Remarks

Attribute	Description
Name	Doctype-Remarks
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARK1

Attribute	Description
Name	REMARK1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK2

Attribute	Description
Name	REMARK2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK3

Attribute	Description
Name	REMARK3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK4

Attribute	Description
Name	REMARK4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK5

Attribute	**Description**
Name	REMARK5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK6

Attribute	**Description**
Name	REMARK6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK7

Attribute	**Description**
Name	REMARK7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK8

Attribute	**Description**
Name	REMARK8
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	225

TOP

REMARK9

Attribute	Description
Name	REMARK9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK10

Attribute	Description
Name	REMARK10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

Custmis

Attribute	Description
Name	Custmis
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates Management Information System Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CUST

Attribute	Description
Name	CUST
Datatype	String
Description	Indicates the Customer.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Custchnglog

Attribute	Description
Name	Custchnglog
Datatype	
Description	Indicates the Customer Change Log.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNDT

Attribute	Description

Name	TXNDT
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

OLDMISCD

Attribute	**Description**
Name	OLDMISCD
Datatype	String
Description	Indicates the Old MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NWMISCD

Attribute	**Description**
Name	NWMISCD
Datatype	String
Description	Indicates the New MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Baltrnsfrlog

Attribute	**Description**
Name	Baltrnsfrlog
Datatype	
Description	Indicates the Balance Transfer Log.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRN

Attribute	**Description**
Name	BRN
Datatype	String
Description	Indicates the Branch Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FINYR

Attribute	Description
Name	FINYR
Datatype	String
Description	Indicates the Financial Year.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

GLCODE

Attribute	Description
Name	GLCODE
Datatype	String
Description	Indicates the GL Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCLS

Attribute	Description
Name	MISCLS

Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	Indicates the Old MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	Indicates the New MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TRNIND

Attribute	Description
Name	TRNIND
Datatype	String
Description	Indicates Transfer Identification Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Dfltcd

Attribute	Description
Name	Dfltcd
Datatype	
Description	Indicates the Customer MIS Classes.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MISCD

Attribute	Description

Name	MISCD
Datatype	String
Description	Indicates the MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Dfltcda

Attribute	Description
Name	Dfltcda
Datatype	
Description	Indicates the Composite MIS Classes.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates the MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Custloghead

Attribute	Description
Name	Custloghead
Datatype	
Description	Indicates the Customer Log Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Jointcustomer

Attribute	Description
Name	Jointcustomer
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Custjoint

Attribute	Description
Name	Custjoint
Datatype	
Description	Indicates Customer Joint.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTPREFIX

Attribute	Description
Name	CUSTPREFIX
Datatype	String
Description	Indicates the Customer Prefix.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FRSTNAME

Attribute	Description
Name	FRSTNAME
Datatype	String

Description	Indicates the First Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MIDNAME

Attribute	**Description**
Name	MIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LASTNAME

Attribute	**Description**
Name	LASTNAME
Datatype	String
Description	Indicates the Last Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOB

Attribute	**Description**
Name	DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SEX

Attribute	**Description**
Name	SEX
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,F

TOP

PPNO

Attribute	Description
Name	PPNO
Datatype	String
Description	Indicates Passport Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PPTISSDT

Attribute	Description
Name	PPTISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PPTEXPDT

Attribute	Description
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADD3

Attribute	Description
Name	ADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

SSN

Attribute	Description
Name	SSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

DECEASED

Attribute	**Description**
Name	DECEASED
Datatype	String
Description	Indicates whether Deceased or not. The value should be either D or N.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,N

TOP

RESISTAT

Attribute	**Description**
Name	RESISTAT
Datatype	String
Description	Indicates the Resistant Status. The value could be either R or N.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,N

TOP

Cust-Acc-Det

Attribute	**Description**
Name	Cust-Acc-Det
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Diary-Mst

Attribute	Description
Name	Diary-Mst
Datatype	
Description	Indicates Diary Master.
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	Indicates Instrument Number
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 16

TOP

UNTTYP

Attribute	Description
Name	UNTTYP
Datatype	String
Description	Indicates Unit Type
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

UNTVAL

Attribute	Description
Name	UNTVAL
Datatype	String
Description	Indicates Unit Value
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String

Description	Indicates the Branch Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INSTR

Attribute	**Description**
Name	INSTR
Datatype	String
Description	Indicates Instructions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

INSTRTYPE

Attribute	**Description**
Name	INSTRTYPE
Datatype	String
Description	Indicates Instruction Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

EXEDAYS

Attribute	**Description**
Name	EXEDAYS
Datatype	Number
Description	Indicates Execution Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXEMONTHS

Attribute	**Description**
Name	EXEMONTHS
Datatype	Number
Description	Indicates Execution Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXEYEARS

Attribute	Description
Name	EXEYEARS
Datatype	Number
Description	Indicates Execution Years
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MNTHENDFLG

Attribute	Description
Name	MNTHENDFLG
Datatype	String
Description	Indicates Month End Flag. Flag Can be either Y or N.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HLDRULE

Attribute	Description
Name	HLDRULE
Datatype	String
Description	Indicates Holiday Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRSTDUEDT

Attribute	Description
Name	FRSTDUEDT
Datatype	Date
Description	Indicates First Due Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NXTDUEDT

Attribute	Description
Name	NXTDUEDT
Datatype	Date
Description	Indicates Next Due Date

Attributes	Attribute	Description
	minOccurs	0

TOP

NXTEXEDT

Attribute	Description
Name	NXTEXEDT
Datatype	Date
Description	Indicates Next Execution Date.
Attributes	Attribute: minOccurs — Description: 0

TOP

CONDELEM

Attribute	Description
Name	CONDELEM
Datatype	String
Description	Indicates Condition Elements.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

OPRTR

Attribute	Description
Name	OPRTR
Datatype	String
Description	Indicates Operator.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2

TOP

CONDVAL

Attribute	Description
Name	CONDVAL
Datatype	Number
Description	Indicates Condition Value.
Attributes	Attribute: minOccurs — Description: 0

TOP

ACCOFCR

Attribute	Description
Name	ACCOFCR

Datatype	String
Description	Indicates Account Officer.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPLINSTRTYP

Attribute	Description
Name	SPLINSTRTYP
Datatype	String
Description	Indicates Special Instruction Type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	Indicates Expiry Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPLINSTR

Attribute	Description
Name	SPLINSTR
Datatype	String
Description	Indicates Special Instructions.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Custaccdet

Attribute	Description
Name	Custaccdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkage details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Indicates the customer
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RELATIONSHIP

Attribute	Description

Name	RELATIONSHIP
Datatype	String
Description	Indicate relations
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

INHERIT

Attribute	**Description**
Name	INHERIT
Datatype	String
Description	Indicate,include relationship Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DESCP

Attribute	**Description**
Name	DESCP
Datatype	String
Description	Indicates description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Custacdetail

Attribute	**Description**
Name	Custacdetail
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTTEXT

Attribute	Description
Name	CUSTTEXT
Datatype	
Description	Include customer details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	Indicates sequence number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String
Description	Indicate text description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></table>

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></table>

TOP

Sttms-Debit

Attribute	Description
Name	Sttms-Debit
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch code.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	Indicates the Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACTNO

Attribute	Description
Name	ACTNO
Datatype	String
Description	Indicates the Account Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Sttms-Detail

Attribute	Description
Name	Sttms-Detail
Datatype	
Description	Indicates Customer Details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REQUEST_REFERENCE_NO

Attribute	Description
Name	REQUEST_REFERENCE_NO
Datatype	String
Description	Indicates the Request Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CARDNO

Attribute	Description
Name	CARDNO
Datatype	String
Description	Indicates the Card Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 19

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	Indicates the Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CARD_PRODUCT

Attribute	Description
Name	CARD_PRODUCT
Datatype	String
Description	Indicates the Product code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRIMARY_CARD

Attribute	Description
Name	PRIMARY_CARD
Datatype	String
Description	Indicates the Primary Card Number.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 1

TOP

NAME_ON_CARD

Attribute	Description
Name	NAME_ON_CARD
Datatype	String
Description	Indicates the Name on Card.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 35

TOP

OWNER_ID_NO

Attribute	Description
Name	OWNER_ID_NO
Datatype	String
Description	Indicates the Owner ID.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 150

TOP

CARD_ISSUED_DT

Attribute	Description
Name	CARD_ISSUED_DT
Datatype	Date
Description	Indicates the Card Issue Date.
Attributes	Attribute: minOccurs, Description: 0

TOP

CARD_EXPIRY_DT

Attribute	Description
Name	CARD_EXPIRY_DT
Datatype	Date
Description	Indicates the Card Expiry Date.

Attributes	Attribute	Description
	minOccurs	0

TOP

CARD_STATUS

Attribute	Description	
Name	CARD_STATUS	
Datatype	String	
Description	Indicates the Card Status.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECORD_STAT

Attribute	Description	
Name	RECORD_STAT	
Datatype	String	
Description	Indicates the Record Stat.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

AUTH_STAT

Attribute	Description	
Name	AUTH_STAT	
Datatype	String	
Description	Indicates the Auth Stat.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

CARD_BIN

Attribute	Description	
Name	CARD_BIN	
Datatype	String	
Description	Indicates the Card Bin.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

CUST_AC_NO

Attribute	Description
Name	CUST_AC_NO
Datatype	String
Description	Indicates the Customer Account Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Stvws-Cust-Trntax

Attribute	**Description**
Name	Stvws-Cust-Trntax
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTOMER_NO

Attribute	**Description**
Name	CUSTOMER_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Sttms-Cust-Trn-Tax

Attribute	**Description**
Name	Sttms-Cust-Trn-Tax
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TAX_SCHEME

Attribute	**Description**
Name	TAX_SCHEME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

TXN_TAX_EXEMPTED

Attribute	Description
Name	TXN_TAX_EXEMPTED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TXN_TAX_EXEMPTION_PERCENT

Attribute	Description
Name	TXN_TAX_EXEMPTION_PERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXN_TAX_EFF_DATE

Attribute	Description
Name	TXN_TAX_EFF_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXN_TAX_EXEMPTION_REASON

Attribute	Description
Name	TXN_TAX_EXEMPTION_REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.22.QueryCustomerStat

QueryCustomerStat

2.22.1.ST-QueryCustomerStat-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Cumulative-IO*
    - *CUSTOMER_NO*
    - *CUSTOMER_ACC_NO*
    - *BRANCH_CODE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0; nillable true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 128 Restrictions: pattern; Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Cumulative-IO

Attribute	Description
Name	Cumulative-IO
Datatype	
Description	

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	Indicates Customer Number.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

Restrictions	Restrictions	Description
	maxLength	9

TOP

CUSTOMER_ACC_NO

Attribute	Description	
Name	CUSTOMER_ACC_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description	Indicates the Branch Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

2.22.2.ST-QueryCustomerStat-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Cumulative-IO*
      - *CUSTOMER_NO*
      - *CUSTOMER_ACC_NO*
      - *BRANCH_CODE*
    - *Cumulative-Full*
      - *CUSTOMER_NO*
      - *CUSTOMER_ACC_NO*
      - *CURRENCY*
      - *CUSTOMER_NAME*
      - *BRANCH_CODE*
      - *SIMPLE_AVG_BALANCE*
      - *MIN_BAL*
      - *MAX_BAL*
      - *NO_DR_TRANSACTIONS*
      - *NO_CR_TRANSACTIONS*
      - *DR_AVG*
      - *CR_AVG*
      - *NO_RET_CHEQUES*

DAYS_IN_DEBIT
DAYS_IN_CREDIT
TOT_BAL
NO_OVERDRAFT
DR_AVG_MONTHLY
CR_AVG_MONTHLY
MONTHLY_AVG
Monthly
SIMPLE_AVG_BAL
MIN_BAL
MAX_BAL
NO_DR_TRANSACTIONS
NO_CR_TRANSACTION
CLOSING_BAL
DR_INT
NSF
CHG_TR
DB_CHK_RTD
VISA_DB
LAST_DEBIT
LAST_CREDIT
LAST_OVERDRAFT
DAYS_IN_DEBIT
DR_AVG_MONTHLY
DAYS_XOD
MONTHLY_AVG
NO_OVERDRAFT
DAYS_IN_CREDIT
CR_AVG_MONTHLY
CUSTOMER_NO
CUST_AC_NO
CCY
CUSTOMER_NAME
BRANCH_CODE
TOT_BAL
DR_AVG
CR_AVG
XOD_AVG
RUN_DATE
NO_RET_CHEQUES
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Cumulative-IO

Attribute	Description
Name	Cumulative-IO
Datatype	
Description	

TOP

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description	Indicates Customer Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTOMER_ACC_NO

Attribute	Description	
Name	CUSTOMER_ACC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description	Indicates the Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

Cumulative-Full

Attribute	Description
Name	Cumulative-Full
Datatype	
Description	

TOP

CUSTOMER_NO

Attribute	Description	
Name	CUSTOMER_NO	
Datatype	String	
Description	Indicates Customer Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTOMER_ACC_NO

Attribute	Description	
Name	CUSTOMER_ACC_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	String	
Description	Indicates Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTOMER_NAME

Attribute	Description
Name	CUSTOMER_NAME
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BRANCH_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description	Indicates the Branch Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SIMPLE_AVG_BALANCE

Attribute	Description	
Name	SIMPLE_AVG_BALANCE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MIN_BAL

Attribute	Description	
Name	MIN_BAL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MAX_BAL

Attribute	Description	
Name	MAX_BAL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NO_DR_TRANSACTIONS

Attribute	Description
Name	NO_DR_TRANSACTIONS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NO_CR_TRANSACTIONS

Attribute	Description
Name	NO_CR_TRANSACTIONS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DR_AVG

Attribute	Description
Name	DR_AVG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CR_AVG

Attribute	Description
Name	CR_AVG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NO_RET_CHEQUES

Attribute	Description
Name	NO_RET_CHEQUES
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYS_IN_DEBIT

Attribute	Description
Name	DAYS_IN_DEBIT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

DAYS_IN_CREDIT

Attribute	Description
Name	DAYS_IN_CREDIT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TOT_BAL

Attribute	Description
Name	TOT_BAL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NO_OVERDRAFT

Attribute	Description
Name	NO_OVERDRAFT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DR_AVG_MONTHLY

Attribute	Description
Name	DR_AVG_MONTHLY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CR_AVG_MONTHLY

Attribute	Description
Name	CR_AVG_MONTHLY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MONTHLY_AVG

Attribute	Description
Name	MONTHLY_AVG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Monthly

Attribute	Description
Name	Monthly
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

SIMPLE_AVG_BAL

Attribute	Description
Name	SIMPLE_AVG_BAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MIN_BAL

Attribute	Description
Name	MIN_BAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAX_BAL

Attribute	Description
Name	MAX_BAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NO_DR_TRANSACTIONS

Attribute	Description
Name	NO_DR_TRANSACTIONS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NO_CR_TRANSACTION

Attribute	Description
Name	NO_CR_TRANSACTION
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLOSING_BAL

Attribute	Description
Name	CLOSING_BAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DR_INT

Attribute	Description
Name	DR_INT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NSF

Attribute	Description
Name	NSF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CHG_TR

Attribute	Description
Name	CHG_TR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DB_CHK_RTD

Attribute	Description
Name	DB_CHK_RTD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VISA_DB

Attribute	Description
Name	VISA_DB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LAST_DEBIT

Attribute	Description
Name	LAST_DEBIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LAST_CREDIT

Attribute	Description
Name	LAST_CREDIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LAST_OVERDRAFT

Attribute	Description
Name	LAST_OVERDRAFT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYS_IN_DEBIT

Attribute	Description
Name	DAYS_IN_DEBIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DR_AVG_MONTHLY

Attribute	Description
Name	DR_AVG_MONTHLY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYS_XOD

Attribute	Description
Name	DAYS_XOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MONTHLY_AVG

Attribute	Description
Name	MONTHLY_AVG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NO_OVERDRAFT

Attribute	Description
Name	NO_OVERDRAFT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DAYS_IN_CREDIT

Attribute	Description
Name	DAYS_IN_CREDIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CR_AVG_MONTHLY

Attribute	Description
Name	CR_AVG_MONTHLY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	Indicates Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUST_AC_NO

Attribute	Description
Name	CUST_AC_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTOMER_NAME

Attribute	Description
Name	CUSTOMER_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TOT_BAL

Attribute	Description
Name	TOT_BAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DR_AVG

Attribute	Description
Name	DR_AVG

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CR_AVG

Attribute	Description
Name	CR_AVG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

XOD_AVG

Attribute	Description
Name	XOD_AVG
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RUN_DATE

Attribute	Description
Name	RUN_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NO_RET_CHEQUES

Attribute	Description
Name	NO_RET_CHEQUES
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.23.QueryTDAmountBlock

QueryTDAmountBlock

2.23.1.ST-QueryTDAmountBlock-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-IO*
    - *AMTBLKNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Amount-Blocks-IO

Attribute	Description
Name	Amount-Blocks-IO
Datatype	
Description	

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

2.23.2.ST-QueryTDAmountBlock-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Amount-Blocks-IO*
      - *AMTBLKNO*
    - *Amount-Blocks-Full*
      - *ACC*
      - *AMTBLKNO*
      - *AMT*
      - *EXPDATE*
      - *REM*
      - *ABLKTYPE*
      - *REFERENCE_NO*
      - *HPCODE*
      - *EFFDATE*
      - *HOLDDESC*
      - *BRANCH*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0; nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength 12; pattern [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length 3; pattern [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0; nillable true

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Amount-Blocks-IO

Attribute	Description
Name	Amount-Blocks-IO
Datatype	
Description	

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Amount-Blocks-Full

Attribute	Description
Name	Amount-Blocks-Full
Datatype	
Description	

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ABLKTYPE

Attribute	Description
Name	ABLKTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,S,P,E,A,C,B,D

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 40

TOP

HPCODE

Attribute	Description
Name	HPCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HOLDDESC

Attribute	Description
Name	HOLDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description

Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.24.QueryUIDCustomer

QueryUIDCustomer

2.24.1.ST-QueryUIDCustomer-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Queryuidcustomer-IO*
    - *UIDVAL*
    - *UIDNAME*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for a request to query a customer based on unique key id and avalue

TOP

Queryuidcustomer-IO

Attribute	Description
Name	Queryuidcustomer-IO
Datatype	
Description	

TOP

UIDVAL

Attribute	Description
Name	UIDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

UIDNAME

Attribute	Description
Name	UIDNAME
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>
Restrictions	<table><tr><th>Restrictions</th><th>Description</th></tr><tr><td>maxLength</td><td>255</td></tr></table>

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Queryuidcustomer-IO*
      - *UIDVAL*
      - *UIDNAME*
    - *Queryuidcustomer-Full*
      - *CUSTNO*
      - *UIDVAL*
      - *UIDNAME*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Queryuidcustomer-IO

Attribute	Description
Name	Queryuidcustomer-IO
Datatype	
Description	

TOP

UIDVAL

Attribute	Description	
Name	UIDVAL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

UIDNAME

Attribute	Description	
Name	UIDNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Queryuidcustomer-Full

Attribute	Description
Name	Queryuidcustomer-Full
Datatype	
Description	

TOP

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

UIDVAL

Attribute	Description
Name	UIDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

UIDNAME

Attribute	Description
Name	UIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String

Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.25.ReopenCustomer

Reopen of Customer

2.25.1.ST-ReopenCustomer-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Customer-Full*
    - *NAME*
    - *ADDRLN1*
    - *ADDRLN3*
    - *ADDRLN2*
    - *ADDRLN4*
    - *SWIFTCD*
    - *FAX*
    - *COUNTRY*
    - *NLTY*
    - *LANG*
    - *EXPCNTRY*
    - *UIDNAME*
    - *UIDVAL*
    - *LOC*
    - *FROZEN*

DEAD
WHRUNKN
GRPCD
CHGGRP
CUSTCLGGRP
TAXGROUP
CCATEG
EXPCAT
CUSTCLASSFN
FXNETTCUST
XREF
MEDIA
SSN
CIFSTAT
CIFSTATSNC
MAILRSREQD
CLSPARTICIPANT
CRMCUST
ISSUCUST
TRSRYCUST
CUSTNO
SNAME
LBRN
CTYPE
FULLNAME
AMLCUSTGRP
AMLREQD
FLGUTLTYPRVDR
UTLTYPRVDRID
CHKDIGITVALREQD
ALGID
CONSTAXCERTRQD
INDTAXCERTRQD
HOACNO
RISKPRFL
DRCAT
FTACCASOF
UDF1
UDF2
UDF3
UDF4
UDF5
UDFLBL1
UDFLBL2

UDFLBL3
UDFLBL4
UDFLBL5
FXCUSTCLRILIM
OVRLIM
FX_CLEAN_RISK
CRRATE
REVDT
LIMCCY
SECCUSTCLRILIM
SECCLRILIM
SECCUSTPSRILIM
SECPSRILIM
CUSTUNADV
RISKCATEG
CLSCCYALLWD
NETTREQD
LIABUNADV
MT920
RELPRICING
FLGJOINT
KYCSTAT
SSTAFF
UPTYPE
KYC_REFNO
JOINT_VENTURE
PRIVATE_CUSTOMER
LC_COLLAT_PCT
ISELCMCUST
ELCMCUSTNO
ALT_CUST_NO
DETERIORATION_DATE
CHQ_TAX_EXEMPT_1
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Custpersonal
- *TITLE*
- *FSTNAME*
- *MIDNAME*

LSTNAME
DOB
GUARDIAN
MINOR
SEX
NATIONID
PPTNO
PPTISSDT
PPTEXPDT
DADD1
DADD2
DADD3
TEL
FAX
EMAIL
PADD1
PADD2
PADD3
DCNTRY
PCNTRY
RESSTATUS
CUSTPREFIX1
CUSTPREFIX2
MOBNUM
SBMTAGEPROOF
CUST_COMM_MODE
LAST_UPD_DT
Custdomestic
- *EDUSTAT*
- *MARITALSTAT*
- *SPNAME*
- *SPEMPSTATUS*
- *DEPCHILD*
- *DEPOTH*
- *ACCOMODATE*
- *CUSTNO*

Custprof
- *EMPSTAT*
- *EMPTENURE*
- *RETIREAGE*
- *PREVDESIG*
- *PREVEMP*
- *CURRDESIG*
- *CURREMP*

ADD1
ADD2
ADD3
TEL
TELEX
FAX
EMAIL
SALARY
OTHER1
RENT
INSURANCE
LOANPMNT
OTHEXP
HOUSEVAL
CRCARD
CNTY
AMTCCY1
CUSTNO
EMPLOYER_DESC
EMP_DESC

Custcorp

CORPNAME
NATIONID
REGADD1
REGADD2
REGADD3
INCORPDT
CAPITAL
NETWORTH
INCORPCNTRY
REGCNTRY
AMTCCY
CORPDESC
CUSTNO
Custcorpdir

DIRNAME
TEL
NADDR1
NADDR2
NADDR3
NADDR4
ADDR1
ADDRS2
ADDRS3

COUNTRY
TAXID
MOBNO
EMAIL
Issuerdet
OVERLIMIT
CUSTNO
OVERLMTCCY
Issuerlmts
CLTRLTYP
LMTAMT
LMTCCY
ISSID
Custgrp
GRPNO
RELATION
Custshhold
SHHOLDID
SHHOLDPCT
SHRHLDRNAME
Clsccyrest
CCY
DESC
Bic
ACC
BICCD
Linkedac
VRFD
LINKEDACCNO
LINKEDACCIBAN
LINKEDACCBIC
JointVenture
PARTYID
PARTYRATIO
PARTYNAME
Custdoc-Chklist
DOCUMENT_TYPE
CHECKED
Doctype-Remarks
REMARK1
REMARK2
REMARK3
REMARK4
REMARK5

- *REMARK6*
- *REMARK7*
- *REMARK8*
- *REMARK9*
- *REMARK10*

Custmis

- *MISGRP*
- *CUST*
- *BRNCD*
- *Custchnglog*
  - *MISCLS*
  - *TXNDT*
  - *OLDMISCD*
  - *NWMISCD*
- *Baltrnsfrlog*
  - *BRN*
  - *PRDCD*
  - *FINYR*
  - *TXNDT*
  - *GLCODE*
  - *MISCLS*
  - *OLDMISCD*
  - *NWMISCD*
  - *TRNIND*
  - *CCY*
  - *AMT*
  - *XRATE*
- *Dfltcd*
  - *MISCLS*
  - *MISCD*
- *Dfltcda*
  - *MISCLS*
  - *MISCD*
- *Custloghead*

Jointcustomer

- *CUSTNO*
- *Custjoint*
  - *CUSTPREFIX*
  - *FRSTNAME*
  - *MIDNAME*
  - *LASTNAME*
  - *DOB*
  - *SEX*
  - *PPNO*

PPTISSDT

PPTEXPDT

ADD1

ADD2

ADD3

TEL

EMAIL

SSN

DECEASED

RESISTAT

Cust-Acc-Det

CUSTNO

Diary-Mst

INSTRNO

UNTTYP

UNTVAL

BRN

INSTR

INSTRTYPE

EXEDAYS

EXEMONTHS

EXEYEARS

MNTHENDFLG

HLDRULE

FRSTDUEDT

NXTDUEDT

NXTEXEDT

CONDELEM

OPRTR

CONDVAL

ACCOFCR

SPLINSTRTYP

EXPDT

SPLINSTR

Custaccdet

CUSTNO

BRNCD

Relationship-Linkage

CUSTOMER

RELATIONSHIP

INHERIT

DESCP

Custacdetail

CUSTNO

CUSTTEXT

SEQNO

CUSTNO

TDESC

UDFDETAILS

FLDNAM

FLDVAL

Sttms-Debit

BRANCH_CODE

CUST_NO

ACTNO

Sttms-Detail

BRANCH_CODE

REQUEST_REFERENCE_NO

CARDNO

CUST_NO

CARD_PRODUCT

PRIMARY_CARD

NAME_ON_CARD

OWNER_ID_NO

CARD_ISSUED_DT

CARD_EXPIRY_DT

CARD_STATUS

RECORD_STAT

AUTH_STAT

CARD_BIN

CUST_AC_NO

Extsys-Ws-Master

Extsys-Ws-Details

EXTWSRESP

USERREMARKS

Stvws-Cust-Trntax

CUSTOMER_NO

Sttms-Cust-Trn-Tax

TAX_SCHEME

TXN_TAX_EXEMPTED

TXN_TAX_EXEMPTION_PERCENT

TXN_TAX_EFF_DATE

TXN_TAX_EXEMPTION_REASON

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Customer-Full

Attribute	Description
Name	Customer-Full
Datatype	
Description	

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

ADDRLN1

Attribute	Description	
Name	ADDRLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN3

Attribute	Description	
Name	ADDRLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN2

Attribute	Description	
Name	ADDRLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN4

Attribute	Description
Name	ADDRLN4
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SWIFTCD

Attribute	Description
Name	SWIFTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FAX

Attribute	Description
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRY

Attribute	Description
Name	COUNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NLTY

Attribute	Description
Name	NLTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

LANG

Attribute	**Description**
Name	LANG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXPCNTRY

Attribute	**Description**
Name	EXPCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

UIDNAME

Attribute	**Description**
Name	UIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

UIDVAL

Attribute	**Description**
Name	UIDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOC

Attribute	Description
Name	LOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FROZEN

Attribute	Description
Name	FROZEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DEAD

Attribute	Description
Name	DEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

WHRUNKN

Attribute	Description
Name	WHRUNKN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

CHGGRP

Attribute	Description
Name	CHGGRP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

CUSTCLGGRP

Attribute	Description
Name	CUSTCLGGRP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TAXGROUP

Attribute	Description
Name	TAXGROUP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

CCATEG

Attribute	Description
Name	CCATEG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EXPCAT

Attribute	**Description**
Name	EXPCAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CUSTCLASSFN

Attribute	**Description**
Name	CUSTCLASSFN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

FXNETTCUST

Attribute	**Description**
Name	FXNETTCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

XREF

Attribute	**Description**
Name	XREF
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

MEDIA

Attribute	Description
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SSN

Attribute	Description
Name	SSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

CIFSTAT

Attribute	Description
Name	CIFSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CIFSTATSNC

Attribute	Description
Name	CIFSTATSNC
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAILRSREQD

Attribute	Description
Name	MAILRSREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLSPARTICIPANT

Attribute	Description
Name	CLSPARTICIPANT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CRMCUST

Attribute	Description
Name	CRMCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ISSUCUST

Attribute	Description
Name	ISSUCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRSRYCUST

Attribute	Description
Name	TRSRYCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

SNAME

Attribute	Description
Name	SNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 20

TOP

LBRN

Attribute	Description
Name	LBRN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CTYPE

Attribute	Description
Name	CTYPE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,C,B

TOP

FULLNAME

Attribute	Description
Name	FULLNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

AMLCUSTGRP

Attribute	Description
Name	AMLCUSTGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

AMLREQD

Attribute	Description
Name	AMLREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FLGUTLTYPRVDR

Attribute	Description
Name	FLGUTLTYPRVDR
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

UTLTYPRVDRID

Attribute	Description	
Name	UTLTYPRVDRID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHKDIGITVALREQD

Attribute	Description	
Name	CHKDIGITVALREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALGID

Attribute	Description	
Name	ALGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

CONSTAXCERTRQD

Attribute	Description	
Name	CONSTAXCERTRQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

INDTAXCERTRQD

Attribute	Description	
Name	INDTAXCERTRQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

HOACNO

Attribute	Description	
Name	HOACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RISKPRFL

Attribute	Description	
Name	RISKPRFL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

DRCAT

Attribute	Description	
Name	DRCAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FTACCASOF

Attribute	Description
Name	FTACCASOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,M,D

TOP

UDF1

Attribute	Description
Name	UDF1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDF2

Attribute	Description
Name	UDF2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDF3

Attribute	Description
Name	UDF3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

UDF4

Attribute	Description
Name	UDF4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

UDF5

Attribute	Description
Name	UDF5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDFLBL1

Attribute	Description
Name	UDFLBL1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDFLBL2

Attribute	Description
Name	UDFLBL2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDFLBL3

Attribute	Description
Name	UDFLBL3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL4

Attribute	Description
Name	UDFLBL4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL5

Attribute	Description
Name	UDFLBL5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

FXCUSTCLRILIM

Attribute	Description
Name	FXCUSTCLRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OVRLIM

Attribute	Description
Name	OVRLIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FX_CLEAN_RISK

Attribute	Description
Name	FX_CLEAN_RISK
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CRRATE

Attribute	Description
Name	CRRATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

REVDT

Attribute	Description
Name	REVDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIMCCY

Attribute	Description
Name	LIMCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SECCUSTCLRILIM

Attribute	Description
Name	SECCUSTCLRILIM
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SECCLRILIM

Attribute	Description
Name	SECCLRILIM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SECCUSTPSRILIM

Attribute	Description
Name	SECCUSTPSRILIM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SECPSRILIM

Attribute	Description
Name	SECPSRILIM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CUSTUNADV

Attribute	Description
Name	CUSTUNADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

RISKCATEG

Attribute	Description
Name	RISKCATEG
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

CLSCCYALLWD

Attribute	Description
Name	CLSCCYALLWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

NETTREQD

Attribute	Description
Name	NETTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIABUNADV

Attribute	Description
Name	LIABUNADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MT920

Attribute	Description
Name	MT920
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

RELPRICING

Attribute	Description	
Name	RELPRICING	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

FLGJOINT

Attribute	Description	
Name	FLGJOINT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

KYCSTAT

Attribute	Description	
Name	KYCSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	V,N,F

TOP

SSTAFF

Attribute	Description	
Name	SSTAFF	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

UPTYPE

Attribute	Description
Name	UPTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

KYC_REFNO

Attribute	Description
Name	KYC_REFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

JOINT_VENTURE

Attribute	Description
Name	JOINT_VENTURE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIVATE_CUSTOMER

Attribute	Description
Name	PRIVATE_CUSTOMER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LC_COLLAT_PCT

Attribute	Description
Name	LC_COLLAT_PCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISELCMCUST

Attribute	Description
Name	ISELCMCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ELCMCUSTNO

Attribute	Description
Name	ELCMCUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ALT_CUST_NO

Attribute	Description
Name	ALT_CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DETERIORATION_DATE

Attribute	Description
Name	DETERIORATION_DATE
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CHQ_TAX_EXEMPT_1

Attribute	Description	
Name	CHQ_TAX_EXEMPT_1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Custpersonal

Attribute	Description
Name	Custpersonal

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TITLE

Attribute	Description
Name	TITLE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FSTNAME

Attribute	Description
Name	FSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MIDNAME

Attribute	Description
Name	MIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LSTNAME

Attribute	Description
Name	LSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

GUARDIAN

Attribute	Description
Name	GUARDIAN
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 105

TOP

MINOR

Attribute	Description
Name	MINOR
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

SEX

Attribute	Description
Name	SEX
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: M,F

TOP

NATIONID

Attribute	Description
Name	NATIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

PPTNO

Attribute	Description
Name	PPTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

PPTISSDT

Attribute	Description
Name	PPTISSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PPTEXPDT

Attribute	Description
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DADD1

Attribute	Description
Name	DADD1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DADD2

Attribute	**Description**
Name	DADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DADD3

Attribute	**Description**
Name	DADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TEL

Attribute	**Description**
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

FAX

Attribute	**Description**
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PADD1

Attribute	Description
Name	PADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PADD2

Attribute	Description
Name	PADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PADD3

Attribute	Description
Name	PADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DCNTRY

Attribute	Description
Name	DCNTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

PCNTRY

Attribute	Description
Name	PCNTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

RESSTATUS

Attribute	Description
Name	RESSTATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: R,N

TOP

CUSTPREFIX1

Attribute	Description
Name	CUSTPREFIX1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

CUSTPREFIX2

Attribute	Description
Name	CUSTPREFIX2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

MOBNUM

Attribute	**Description**
Name	MOBNUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SBMTAGEPROOF

Attribute	**Description**
Name	SBMTAGEPROOF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,P,V

TOP

CUST_COMM_MODE

Attribute	**Description**
Name	CUST_COMM_MODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,E

TOP

LAST_UPD_DT

Attribute	**Description**
Name	LAST_UPD_DT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Custdomestic

Attribute	Description
Name	Custdomestic
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EDUSTAT

Attribute	Description
Name	EDUSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,U,G,P

TOP

MARITALSTAT

Attribute	Description
Name	MARITALSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,M,D,R,P,E,T

TOP

SPNAME

Attribute	Description
Name	SPNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SPEMPSTATUS

Attribute	Description
Name	SPEMPSTATUS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,T,S,U,R,P,N,O

TOP

DEPCHILD

Attribute	**Description**
Name	DEPCHILD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEPOTH

Attribute	**Description**
Name	DEPOTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOMODATE

Attribute	**Description**
Name	ACCOMODATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,O

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Custprof

Attribute	Description
Name	Custprof
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EMPSTAT

Attribute	Description
Name	EMPSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

EMPTENURE

Attribute	Description
Name	EMPTENURE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RETIREAGE

Attribute	Description
Name	RETIREAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PREVDESIG

Attribute	Description
Name	PREVDESIG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

PREVEMP

Attribute	Description
Name	PREVEMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CURRDESIG

Attribute	Description
Name	CURRDESIG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CURREMP

Attribute	Description
Name	CURREMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADD2

Attribute	Description
Name	ADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADD3

Attribute	Description
Name	ADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TELEX

Attribute	Description
Name	TELEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FAX

Attribute	Description
Name	FAX
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

SALARY

Attribute	Description
Name	SALARY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

OTHER1

Attribute	Description
Name	OTHER1
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RENT

Attribute	Description
Name	RENT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

INSURANCE

Attribute	Description
Name	INSURANCE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANPMNT

Attribute	Description
Name	LOANPMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHEXP

Attribute	Description
Name	OTHEXP
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HOUSEVAL

Attribute	Description
Name	HOUSEVAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CRCARD

Attribute	Description
Name	CRCARD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMTCCY1

Attribute	Description
Name	AMTCCY1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

EMPLOYER_DESC

Attribute	Description
Name	EMPLOYER_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

EMP_DESC

Attribute	Description

Name	EMP_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Custcorp

Attribute	**Description**
Name	Custcorp
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CORPNAME

Attribute	**Description**
Name	CORPNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NATIONID

Attribute	**Description**
Name	NATIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REGADD1

Attribute	**Description**
Name	REGADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REGADD2

Attribute	**Description**
Name	REGADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REGADD3

Attribute	**Description**
Name	REGADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INCORPDT

Attribute	**Description**
Name	INCORPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CAPITAL

Attribute	**Description**
Name	CAPITAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETWORTH

Attribute	**Description**
Name	NETWORTH

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INCORPCNTRY

Attribute	**Description**
Name	INCORPCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REGCNTRY

Attribute	**Description**
Name	REGCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMTCCY

Attribute	**Description**
Name	AMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CORPDESC

Attribute	**Description**
Name	CORPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255

TOP

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

TOP

Custcorpdir

Attribute	Description	
Name	Custcorpdir	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

DIRNAME

Attribute	Description	
Name	DIRNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

TEL

Attribute	Description	
Name	TEL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

NADDR1

Attribute	Description
Name	NADDR1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR2

Attribute	Description
Name	NADDR2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR3

Attribute	Description
Name	NADDR3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR4

Attribute	Description
Name	NADDR4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDR1

Attribute	Description

Name	ADDR1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRY

Attribute	Description
Name	COUNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TAXID

Attribute	Description
Name	TAXID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MOBNO

Attribute	Description
Name	MOBNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Issuerdet

Attribute	Description
Name	Issuerdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OVERLIMIT

Attribute	Description
Name	OVERLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OVERLMTCCY

Attribute	**Description**
Name	OVERLMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Issuerlmts

Attribute	**Description**
Name	Issuerlmts
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CLTRLTYP

Attribute	**Description**
Name	CLTRLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 70

TOP

LMTAMT

Attribute	**Description**
Name	LMTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LMTCCY

Attribute	Description
Name	LMTCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ISSID

Attribute	Description
Name	ISSID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

Custgrp

Attribute	Description
Name	Custgrp
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

GRPNO

Attribute	Description
Name	GRPNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

RELATION

Attribute	Description

Name	RELATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Custshhold

Attribute	Description
Name	Custshhold
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SHHOLDID

Attribute	Description
Name	SHHOLDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SHHOLDPCT

Attribute	Description
Name	SHHOLDPCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHRHLDRNAME

Attribute	Description
Name	SHRHLDRNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Clsccyrest

Attribute	Description
Name	Clsccyrest
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Bic

Attribute	Description
Name	Bic
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC

Attribute	Description
Name	ACC

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BICCD

Attribute	**Description**
Name	BICCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

Linkedac

Attribute	**Description**
Name	Linkedac
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VRFD

Attribute	**Description**
Name	VRFD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LINKEDACCNO

Attribute	**Description**
Name	LINKEDACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	30

TOP

LINKEDACCIBAN

Attribute	Description	
Name	LINKEDACCIBAN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

LINKEDACCBIC

Attribute	Description	
Name	LINKEDACCBIC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

JointVenture

Attribute	Description	
Name	JointVenture	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

PARTYID

Attribute	Description	
Name	PARTYID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

TOP

PARTYRATIO

Attribute	Description
Name	PARTYRATIO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Custdoc-Chklist

Attribute	Description
Name	Custdoc-Chklist
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CHECKED

Attribute	Description
Name	CHECKED
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Doctype-Remarks

Attribute	Description
Name	Doctype-Remarks
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARK1

Attribute	Description
Name	REMARK1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK2

Attribute	Description
Name	REMARK2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK3

Attribute	Description
Name	REMARK3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK4

Attribute	Description
Name	REMARK4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK5

Attribute	Description
Name	REMARK5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK6

Attribute	Description
Name	REMARK6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK7

Attribute	Description
Name	REMARK7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK8

Attribute	Description
Name	REMARK8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK9

Attribute	Description
Name	REMARK9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK10

Attribute	Description
Name	REMARK10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

Custmis

Attribute	Description
Name	Custmis
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates Management Information System Group.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CUST

Attribute	Description
Name	CUST
Datatype	String
Description	Indicates the Customer.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Custchnglog

Attribute	Description
Name	Custchnglog
Datatype	
Description	Indicates the Customer Change Log.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	Indicates the Old MIS Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	Indicates the New MIS Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Baltrnsfrlog

Attribute	Description
Name	Baltrnsfrlog
Datatype	
Description	Indicates the Balance Transfer Log.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BRN

Attribute	Description
Name	BRN
Datatype	String

Description	Indicates the Branch Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDCD

Attribute	**Description**
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	**Description**
Name	FINYR
Datatype	String
Description	Indicates the Financial Year.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNDT

Attribute	**Description**
Name	TXNDT
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

GLCODE

Attribute	**Description**
Name	GLCODE
Datatype	String
Description	Indicates the GL Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

ORACLE

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	Indicates the Old MIS Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	Indicates the New MIS Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TRNIND

Attribute	Description
Name	TRNIND
Datatype	String
Description	Indicates Transfer Identification Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	Attribute: minOccurs — Description: 0

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate.
Attributes	Attribute: minOccurs — Description: 0

TOP

Dfltcd

Attribute	Description
Name	Dfltcd
Datatype	
Description	Indicates the Customer MIS Classes.
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	Attribute: minOccurs — Description: 1

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCD

Attribute	**Description**
Name	MISCD
Datatype	String
Description	Indicates the MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Dfltcda

Attribute	**Description**
Name	Dfltcda
Datatype	
Description	Indicates the Composite MIS Classes.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	**Description**
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MISCD

Attribute	**Description**
Name	MISCD
Datatype	String
Description	Indicates the MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Custloghead

Attribute	Description
Name	Custloghead
Datatype	
Description	Indicates the Customer Log Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Jointcustomer

Attribute	Description
Name	Jointcustomer
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Custjoint

Attribute	Description
Name	Custjoint
Datatype	
Description	Indicates Customer Joint.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTPREFIX

Attribute	Description
Name	CUSTPREFIX
Datatype	String
Description	Indicates the Customer Prefix.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FRSTNAME

Attribute	Description
Name	FRSTNAME
Datatype	String
Description	Indicates the First Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MIDNAME

Attribute	Description
Name	MIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LASTNAME

Attribute	Description
Name	LASTNAME
Datatype	String
Description	Indicates the Last Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SEX

Attribute	Description
Name	SEX
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,F

TOP

PPNO

Attribute	Description
Name	PPNO
Datatype	String
Description	Indicates Passport Number.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

PPTISSDT

Attribute	Description
Name	PPTISSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PPTEXPDT

Attribute	Description
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ADD2

Attribute	Description	
Name	ADD2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ADD3

Attribute	Description	
Name	ADD3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

TEL

Attribute	Description	
Name	TEL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

EMAIL

Attribute	Description	
Name	EMAIL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TOP

SSN

Attribute	Description
Name	SSN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

DECEASED

Attribute	Description
Name	DECEASED
Datatype	String
Description	Indicates whether Deceased or not. The value should be either D or N.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,N

TOP

RESISTAT

Attribute	Description
Name	RESISTAT
Datatype	String
Description	Indicates the Resistant Status. The value could be either R or N.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: R,N

TOP

Cust-Acc-Det

Attribute	Description
Name	Cust-Acc-Det
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Diary-Mst

Attribute	**Description**
Name	Diary-Mst
Datatype	
Description	Indicates Diary Master.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSTRNO

Attribute	**Description**
Name	INSTRNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

UNTTYP

Attribute	**Description**
Name	UNTTYP
Datatype	String
Description	Indicates Unit Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

UNTVAL

Attribute	**Description**
Name	UNTVAL
Datatype	String
Description	Indicates Unit Value
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description	Indicates the Branch Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

INSTR

Attribute	Description	
Name	INSTR	
Datatype	String	
Description	Indicates Instructions	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

INSTRTYPE

Attribute	Description	
Name	INSTRTYPE	
Datatype	String	
Description	Indicates Instruction Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

EXEDAYS

Attribute	Description	
Name	EXEDAYS	
Datatype	Number	
Description	Indicates Execution Days	
Attributes	Attribute	Description
	minOccurs	0

TOP

EXEMONTHS

Attribute	Description
Name	EXEMONTHS
Datatype	Number
Description	Indicates Execution Months
Attributes	Attribute: minOccurs, Description: 0

TOP

EXEYEARS

Attribute	Description
Name	EXEYEARS
Datatype	Number
Description	Indicates Execution Years
Attributes	Attribute: minOccurs, Description: 0

TOP

MNTHENDFLG

Attribute	Description
Name	MNTHENDFLG
Datatype	String
Description	Indicates Month End Flag. Flag Can be either Y or N.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

HLDRULE

Attribute	Description
Name	HLDRULE
Datatype	String
Description	Indicates Holiday Rule
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 1

TOP

FRSTDUEDT

Attribute	Description
Name	FRSTDUEDT
Datatype	Date
Description	Indicates First Due Date.
Attributes	Attribute: minOccurs, Description: 0

TOP

NXTDUEDT

Attribute	Description
Name	NXTDUEDT
Datatype	Date
Description	Indicates Next Due Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NXTEXEDT

Attribute	Description
Name	NXTEXEDT
Datatype	Date
Description	Indicates Next Execution Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONDELEM

Attribute	Description
Name	CONDELEM
Datatype	String
Description	Indicates Condition Elements.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

OPRTR

Attribute	Description
Name	OPRTR
Datatype	String
Description	Indicates Operator.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2

TOP

CONDVAL

Attribute	Description
Name	CONDVAL
Datatype	Number
Description	Indicates Condition Value.

Attributes	Attribute	Description
	minOccurs	0

TOP

ACCOFCR

Attribute	Description
Name	ACCOFCR
Datatype	String
Description	Indicates Account Officer.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

SPLINSTRTYP

Attribute	Description
Name	SPLINSTRTYP
Datatype	String
Description	Indicates Special Instruction Type.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	Indicates Expiry Date.
Attributes	Attribute: minOccurs — Description: 0

TOP

SPLINSTR

Attribute	Description
Name	SPLINSTR
Datatype	String
Description	Indicates Special Instructions.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

Custaccdet

Attribute	Description
Name	Custaccdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkage details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String
Description	Indicates the customer

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RELATIONSHIP

Attribute	Description
Name	RELATIONSHIP
Datatype	String
Description	Indicate relations
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

INHERIT

Attribute	Description
Name	INHERIT
Datatype	String
Description	Indicate,include relationship Y:yes N:no
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DESCP

Attribute	Description
Name	DESCP
Datatype	String
Description	Indicates description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Custacdetail

Attribute	Description
Name	Custacdetail
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTTEXT

Attribute	Description
Name	CUSTTEXT
Datatype	
Description	Include customer details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SEQNO

Attribute	Description
Name	SEQNO
Datatype	Number
Description	Indicates sequence number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TDESC

Attribute	Description
Name	TDESC
Datatype	String

Description	Indicate text description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Sttms-Debit

Attribute	**Description**
Name	Sttms-Debit
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	Indicates the Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACTNO

Attribute	Description
Name	ACTNO
Datatype	String
Description	Indicates the Account Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Sttms-Detail

Attribute	Description
Name	Sttms-Detail
Datatype	
Description	Indicates Customer Details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description

Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REQUEST_REFERENCE_NO

Attribute	Description
Name	REQUEST_REFERENCE_NO
Datatype	String
Description	Indicates the Request Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CARDNO

Attribute	Description
Name	CARDNO
Datatype	String
Description	Indicates the Card Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 19

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	Indicates the Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CARD_PRODUCT

Attribute	Description
Name	CARD_PRODUCT
Datatype	String
Description	Indicates the Product code.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRIMARY_CARD

Attribute	Description	
Name	PRIMARY_CARD	
Datatype	String	
Description	Indicates the Primary Card Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

NAME_ON_CARD

Attribute	Description	
Name	NAME_ON_CARD	
Datatype	String	
Description	Indicates the Name on Card.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

OWNER_ID_NO

Attribute	Description	
Name	OWNER_ID_NO	
Datatype	String	
Description	Indicates the Owner ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

CARD_ISSUED_DT

Attribute	Description	
Name	CARD_ISSUED_DT	
Datatype	Date	
Description	Indicates the Card Issue Date.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CARD_EXPIRY_DT

Attribute	Description
Name	CARD_EXPIRY_DT
Datatype	Date
Description	Indicates the Card Expiry Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_STATUS

Attribute	Description
Name	CARD_STATUS
Datatype	String
Description	Indicates the Card Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	Indicates the Record Stat.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTH_STAT

Attribute	Description
Name	AUTH_STAT
Datatype	String
Description	Indicates the Auth Stat.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CARD_BIN

Attribute	Description
Name	CARD_BIN

Datatype	String
Description	Indicates the Card Bin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CUST_AC_NO

Attribute	**Description**
Name	CUST_AC_NO
Datatype	String
Description	Indicates the Customer Account Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Extsys-Ws-Master

Attribute	**Description**
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	**Description**
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXTWSRESP

Attribute	**Description**
Name	EXTWSRESP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

Stvws-Cust-Trntax

Attribute	Description
Name	Stvws-Cust-Trntax
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Sttms-Cust-Trn-Tax

Attribute	Description
Name	Sttms-Cust-Trn-Tax
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TAX_SCHEME

Attribute	Description
Name	TAX_SCHEME
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

TXN_TAX_EXEMPTED

Attribute	**Description**
Name	TXN_TAX_EXEMPTED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TXN_TAX_EXEMPTION_PERCENT

Attribute	**Description**
Name	TXN_TAX_EXEMPTION_PERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXN_TAX_EFF_DATE

Attribute	**Description**
Name	TXN_TAX_EFF_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXN_TAX_EXEMPTION_REASON

Attribute	**Description**
Name	TXN_TAX_EXEMPTION_REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Customer-IO
CUSTNO
MAKER
MAKERSTAMP
MODNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Customer-IO

Attribute	Description
Name	Customer-IO
Datatype	
Description	

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.25.3.ST-ReopenCustomer-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Customer-Full*
    - *NAME*
    - *ADDRLN1*
    - *ADDRLN3*
    - *ADDRLN2*
    - *ADDRLN4*
    - *SWIFTCD*
    - *FAX*
    - *COUNTRY*
    - *NLTY*
    - *LANG*
    - *EXPCNTRY*
    - *UIDNAME*
    - *UIDVAL*
    - *LOC*
    - *FROZEN*
    - *DEAD*
    - *WHRUNKN*
    - *GRPCD*

CHGGRP
CUSTCLGGRP
TAXGROUP
CCATEG
EXPCAT
CUSTCLASSFN
FXNETTCUST
XREF
MEDIA
SSN
CIFSTAT
CIFSTATSNC
MAILRSREQD
CLSPARTICIPANT
CRMCUST
ISSUCUST
TRSRYCUST
CUSTNO
SNAME
LBRN
CTYPE
FULLNAME
AMLCUSTGRP
AMLREQD
FLGUTLTYPRVDR
UTLTYPRVDRID
CHKDIGITVALREQD
ALGID
CONSTAXCERTRQD
INDTAXCERTRQD
HOACNO
RISKPRFL
DRCAT
FTACCASOF
UDF1
UDF2
UDF3
UDF4
UDF5
UDFLBL1
UDFLBL2
UDFLBL3
UDFLBL4
UDFLBL5

FXCUSTCLRILIM
OVRLIM
FX_CLEAN_RISK
CRRATE
REVDT
LIMCCY
SECCUSTCLRILIM
SECCLRILIM
SECCUSTPSRILIM
SECPSRILIM
CUSTUNADV
RISKCATEG
CLSCCYALLWD
NETTREQD
LIABUNADV
MT920
RELPRICING
FLGJOINT
KYCSTAT
SSTAFF
UPTYPE
KYC_REFNO
JOINT_VENTURE
PRIVATE_CUSTOMER
LC_COLLAT_PCT
ISELCMCUST
ELCMCUSTNO
ALT_CUST_NO
DETERIORATION_DATE
CHQ_TAX_EXEMPT_1
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Custpersonal
- *TITLE*
- *FSTNAME*
- *MIDNAME*
- *LSTNAME*
- *DOB*
- *GUARDIAN*

MINOR
SEX
NATIONID
PPTNO
PPTISSDT
PPTEXPDT
DADD1
DADD2
DADD3
TEL
FAX
EMAIL
PADD1
PADD2
PADD3
DCNTRY
PCNTRY
RESSTATUS
CUSTPREFIX1
CUSTPREFIX2
MOBNUM
SBMTAGEPROOF
CUST_COMM_MODE
LAST_UPD_DT
Custdomestic
- *EDUSTAT*
- *MARITALSTAT*
- *SPNAME*
- *SPEMPSTATUS*
- *DEPCHILD*
- *DEPOTH*
- *ACCOMODATE*
- *CUSTNO*

Custprof
- *EMPSTAT*
- *EMPTENURE*
- *RETIREAGE*
- *PREVDESIG*
- *PREVEMP*
- *CURRDESIG*
- *CURREMP*
- *ADD1*
- *ADD2*
- *ADD3*

TEL
TELEX
FAX
EMAIL
SALARY
OTHER1
RENT
INSURANCE
LOANPMNT
OTHEXP
HOUSEVAL
CRCARD
CNTY
AMTCCY1
CUSTNO
EMPLOYER_DESC
EMP_DESC
Custcorp
CORPNAME
NATIONID
REGADD1
REGADD2
REGADD3
INCORPDT
CAPITAL
NETWORTH
INCORPCNTRY
REGCNTRY
AMTCCY
CORPDESC
CUSTNO
Custcorpdir
DIRNAME
TEL
NADDR1
NADDR2
NADDR3
NADDR4
ADDR1
ADDRS2
ADDRS3
COUNTRY
TAXID
MOBNO

EMAIL

Issuerdet

OVERLIMIT

CUSTNO

OVERLMTCCY

Issuerlmts

CLTRLTYP

LMTAMT

LMTCCY

ISSID

Custgrp

GRPNO

RELATION

Custshhold

SHHOLDID

SHHOLDPCT

SHRHLDRNAME

Clsccyrest

CCY

DESC

Bic

ACC

BICCD

Linkedac

VRFD

LINKEDACCNO

LINKEDACCIBAN

LINKEDACCBIC

JointVenture

PARTYID

PARTYRATIO

PARTYNAME

Custdoc-Chklist

DOCUMENT_TYPE

CHECKED

Doctype-Remarks

REMARK1

REMARK2

REMARK3

REMARK4

REMARK5

REMARK6

REMARK7

REMARK8

- *REMARK9*
- *REMARK10*

Custmis

- *MISGRP*
- *CUST*
- *BRNCD*
- *Custchnglog*
  - *MISCLS*
  - *TXNDT*
  - *OLDMISCD*
  - *NWMISCD*
- *Baltrnsfrlog*
  - *BRN*
  - *PRDCD*
  - *FINYR*
  - *TXNDT*
  - *GLCODE*
  - *MISCLS*
  - *OLDMISCD*
  - *NWMISCD*
  - *TRNIND*
  - *CCY*
  - *AMT*
  - *XRATE*
- *Dfltcd*
  - *MISCLS*
  - *MISCD*
- *Dfltcda*
  - *MISCLS*
  - *MISCD*
- *Custloghead*

Jointcustomer

- *CUSTNO*
- *Custjoint*
  - *CUSTPREFIX*
  - *FRSTNAME*
  - *MIDNAME*
  - *LASTNAME*
  - *DOB*
  - *SEX*
  - *PPNO*
  - *PPTISSDT*
  - *PPTEXPDT*
  - *ADD1*

ADD2

ADD3

TEL

EMAIL

SSN

DECEASED

RESISTAT

Cust-Acc-Det

CUSTNO

Diary-Mst

INSTRNO

UNTTYP

UNTVAL

BRN

INSTR

INSTRTYPE

EXEDAYS

EXEMONTHS

EXEYEARS

MNTHENDFLG

HLDRULE

FRSTDUEDT

NXTDUEDT

NXTEXEDT

CONDELEM

OPRTR

CONDVAL

ACCOFCR

SPLINSTRTYP

EXPDT

SPLINSTR

Custaccdet

CUSTNO

BRNCD

Relationship-Linkage

CUSTOMER

RELATIONSHIP

INHERIT

DESCP

Custacdetail

CUSTNO

CUSTTEXT

SEQNO

CUSTNO

TDESC
UDFDETAILS
FLDNAM
FLDVAL
Sttms-Debit
BRANCH_CODE
CUST_NO
ACTNO
Sttms-Detail
BRANCH_CODE
REQUEST_REFERENCE_NO
CARDNO
CUST_NO
CARD_PRODUCT
PRIMARY_CARD
NAME_ON_CARD
OWNER_ID_NO
CARD_ISSUED_DT
CARD_EXPIRY_DT
CARD_STATUS
RECORD_STAT
AUTH_STAT
CARD_BIN
CUST_AC_NO
Extsys-Ws-Master
Extsys-Ws-Details
EXTWSRESP
USERREMARKS
Stvws-Cust-Trntax
CUSTOMER_NO
Sttms-Cust-Trn-Tax
TAX_SCHEME
TXN_TAX_EXEMPTED
TXN_TAX_EXEMPTION_PERCENT
TXN_TAX_EFF_DATE
TXN_TAX_EXEMPTION_REASON
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Customer-Full

Attribute	Description

Name	Customer-Full
Datatype	
Description	

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

ADDRLN1

Attribute	Description	
Name	ADDRLN1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN3

Attribute	Description	
Name	ADDRLN3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN2

Attribute	Description	
Name	ADDRLN2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRLN4

Attribute	Description

Name	ADDRLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SWIFTCD

Attribute	**Description**
Name	SWIFTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FAX

Attribute	**Description**
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRY

Attribute	**Description**
Name	COUNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NLTY

Attribute	**Description**
Name	NLTY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXPCNTRY

Attribute	Description
Name	EXPCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

UIDNAME

Attribute	Description
Name	UIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

UIDVAL

Attribute	Description
Name	UIDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

LOC

Attribute	Description	
Name	LOC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

FROZEN

Attribute	Description	
Name	FROZEN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

DEAD

Attribute	Description	
Name	DEAD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

WHRUNKN

Attribute	Description	
Name	WHRUNKN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

GRPCD

Attribute	Description
Name	GRPCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CHGGRP

Attribute	Description
Name	CHGGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CUSTCLGGRP

Attribute	Description
Name	CUSTCLGGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAXGROUP

Attribute	Description
Name	TAXGROUP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CCATEG

Attribute	Description
Name	CCATEG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

EXPCAT

Attribute	Description
Name	EXPCAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

CUSTCLASSFN

Attribute	Description
Name	CUSTCLASSFN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

FXNETTCUST

Attribute	Description
Name	FXNETTCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

XREF

Attribute	Description
Name	XREF

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

MEDIA

Attribute	**Description**
Name	MEDIA
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SSN

Attribute	**Description**
Name	SSN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

CIFSTAT

Attribute	**Description**
Name	CIFSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CIFSTATSNC

Attribute	**Description**
Name	CIFSTATSNC
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MAILRSREQD

Attribute	Description
Name	MAILRSREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CLSPARTICIPANT

Attribute	Description
Name	CLSPARTICIPANT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CRMCUST

Attribute	Description
Name	CRMCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ISSUCUST

Attribute	Description
Name	ISSUCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TRSRYCUST

Attribute	Description	
Name	TRSRYCUST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SNAME

Attribute	Description	
Name	SNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

LBRN

Attribute	Description	
Name	LBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CTYPE

Attribute	Description
Name	CTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: I,C,B

TOP

FULLNAME

Attribute	Description
Name	FULLNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

AMLCUSTGRP

Attribute	Description
Name	AMLCUSTGRP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

AMLREQD

Attribute	Description
Name	AMLREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

FLGUTLTYPRVDR

Attribute	Description
Name	FLGUTLTYPRVDR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

UTLTYPRVDRID

Attribute	**Description**
Name	UTLTYPRVDRID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKDIGITVALREQD

Attribute	**Description**
Name	CHKDIGITVALREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALGID

Attribute	**Description**
Name	ALGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CONSTAXCERTRQD

Attribute	**Description**
Name	CONSTAXCERTRQD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INDTAXCERTRQD

Attribute	Description	
Name	INDTAXCERTRQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

HOACNO

Attribute	Description	
Name	HOACNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RISKPRFL

Attribute	Description	
Name	RISKPRFL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

DRCAT

Attribute	Description	
Name	DRCAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FTACCASOF

Attribute	Description	
Name	FTACCASOF	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,M,D

TOP

UDF1

Attribute	Description	
Name	UDF1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

TOP

UDF2

Attribute	Description	
Name	UDF2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

TOP

UDF3

Attribute	Description	
Name	UDF3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

UDF4

Attribute	Description
Name	UDF4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

UDF5

Attribute	Description
Name	UDF5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL1

Attribute	Description
Name	UDFLBL1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL2

Attribute	Description
Name	UDFLBL2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

UDFLBL3

Attribute	Description
Name	UDFLBL3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDFLBL4

Attribute	Description
Name	UDFLBL4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

UDFLBL5

Attribute	Description
Name	UDFLBL5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

FXCUSTCLRILIM

Attribute	Description
Name	FXCUSTCLRILIM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

OVRLIM

Attribute	Description
Name	OVRLIM
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

FX_CLEAN_RISK

Attribute	Description
Name	FX_CLEAN_RISK
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CRRATE

Attribute	Description
Name	CRRATE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

REVDT

Attribute	Description
Name	REVDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIMCCY

Attribute	Description
Name	LIMCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

SECCUSTCLRILIM

Attribute	Description
Name	SECCUSTCLRILIM

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCLRILIM

Attribute	Description
Name	SECCLRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECCUSTPSRILIM

Attribute	Description
Name	SECCUSTPSRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SECPSRILIM

Attribute	Description
Name	SECPSRILIM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTUNADV

Attribute	Description
Name	CUSTUNADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RISKCATEG

Attribute	Description
Name	RISKCATEG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CLSCCYALLWD

Attribute	**Description**
Name	CLSCCYALLWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

NETTREQD

Attribute	**Description**
Name	NETTREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIABUNADV

Attribute	**Description**
Name	LIABUNADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MT920

Attribute	**Description**
Name	MT920
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RELPRICING

Attribute	Description	
Name	RELPRICING	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

FLGJOINT

Attribute	Description	
Name	FLGJOINT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

KYCSTAT

Attribute	Description	
Name	KYCSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	V,N,F

TOP

SSTAFF

Attribute	Description	
Name	SSTAFF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

UPTYPE

Attribute	Description
Name	UPTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

KYC_REFNO

Attribute	Description
Name	KYC_REFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

JOINT_VENTURE

Attribute	Description
Name	JOINT_VENTURE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PRIVATE_CUSTOMER

Attribute	Description
Name	PRIVATE_CUSTOMER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

LC_COLLAT_PCT

Attribute	Description
Name	LC_COLLAT_PCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISELCMCUST

Attribute	Description
Name	ISELCMCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ELCMCUSTNO

Attribute	Description
Name	ELCMCUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ALT_CUST_NO

Attribute	Description
Name	ALT_CUST_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DETERIORATION_DATE

Attribute	Description
Name	DETERIORATION_DATE

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHQ_TAX_EXEMPT_1

Attribute	Description
Name	CHQ_TAX_EXEMPT_1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

Custpersonal

Attribute	Description
Name	Custpersonal
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TITLE

Attribute	Description
Name	TITLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FSTNAME

Attribute	Description
Name	FSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MIDNAME

Attribute	Description
Name	MIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LSTNAME

Attribute	Description
Name	LSTNAME
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GUARDIAN

Attribute	Description
Name	GUARDIAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MINOR

Attribute	Description
Name	MINOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SEX

Attribute	Description
Name	SEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,F

TOP

NATIONID

Attribute	Description
Name	NATIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PPTNO

Attribute	Description
Name	PPTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PPTISSDT

Attribute	Description
Name	PPTISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PPTEXPDT

Attribute	Description
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DADD1

Attribute	Description
Name	DADD1
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DADD2

Attribute	Description
Name	DADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DADD3

Attribute	Description
Name	DADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FAX

Attribute	Description
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

PADD1

Attribute	Description
Name	PADD1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

PADD2

Attribute	Description
Name	PADD2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

PADD3

Attribute	Description
Name	PADD3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

DCNTRY

Attribute	Description
Name	DCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PCNTRY

Attribute	Description
Name	PCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RESSTATUS

Attribute	Description
Name	RESSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / R,N

TOP

CUSTPREFIX1

Attribute	Description
Name	CUSTPREFIX1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

CUSTPREFIX2

Attribute	Description
Name	CUSTPREFIX2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

MOBNUM

Attribute	Description
Name	MOBNUM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SBMTAGEPROOF

Attribute	Description
Name	SBMTAGEPROOF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,P,V

TOP

CUST_COMM_MODE

Attribute	Description
Name	CUST_COMM_MODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,E

TOP

LAST_UPD_DT

Attribute	Description
Name	LAST_UPD_DT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Custdomestic

Attribute	Description
Name	Custdomestic
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

EDUSTAT

Attribute	Description
Name	EDUSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: N,U,G,P

TOP

MARITALSTAT

Attribute	Description
Name	MARITALSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: S,M,D,R,P,E,T

TOP

SPNAME

Attribute	Description
Name	SPNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SPEMPSTATUS

Attribute	Description
Name	SPEMPSTATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,T,S,U,R,P,N,O

TOP

DEPCHILD

Attribute	Description
Name	DEPCHILD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DEPOTH

Attribute	Description
Name	DEPOTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOMODATE

Attribute	Description
Name	ACCOMODATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,C,O

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	9

TOP

Custprof

Attribute	Description	
Name	Custprof	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EMPSTAT

Attribute	Description	
Name	EMPSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

EMPTENURE

Attribute	Description	
Name	EMPTENURE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RETIREAGE

Attribute	Description	
Name	RETIREAGE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PREVDESIG

Attribute	Description
Name	PREVDESIG
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PREVEMP

Attribute	Description
Name	PREVEMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURRDESIG

Attribute	Description
Name	CURRDESIG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CURREMP

Attribute	Description
Name	CURREMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ADD2

Attribute	Description	
Name	ADD2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ADD3

Attribute	Description	
Name	ADD3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

TEL

Attribute	Description	
Name	TEL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

TELEX

Attribute	Description	
Name	TELEX	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

FAX

Attribute	Description
Name	FAX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EMAIL

Attribute	Description
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

SALARY

Attribute	Description
Name	SALARY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OTHER1

Attribute	Description
Name	OTHER1
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RENT

Attribute	Description
Name	RENT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

INSURANCE

Attribute	Description
Name	INSURANCE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LOANPMNT

Attribute	Description
Name	LOANPMNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

OTHEXP

Attribute	Description
Name	OTHEXP
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

HOUSEVAL

Attribute	Description
Name	HOUSEVAL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CRCARD

Attribute	Description
Name	CRCARD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMTCCY1

Attribute	Description
Name	AMTCCY1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

EMPLOYER_DESC

Attribute	Description
Name	EMPLOYER_DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

EMP_DESC

Attribute	Description
Name	EMP_DESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

Custcorp

Attribute	Description
Name	Custcorp
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CORPNAME

Attribute	Description
Name	CORPNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

NATIONID

Attribute	Description
Name	NATIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REGADD1

Attribute	Description
Name	REGADD1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REGADD2

Attribute	**Description**
Name	REGADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REGADD3

Attribute	**Description**
Name	REGADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INCORPDT

Attribute	**Description**
Name	INCORPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CAPITAL

Attribute	**Description**
Name	CAPITAL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETWORTH

Attribute	Description
Name	NETWORTH
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INCORPCNTRY

Attribute	Description
Name	INCORPCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

REGCNTRY

Attribute	Description
Name	REGCNTRY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMTCCY

Attribute	Description
Name	AMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CORPDESC

Attribute	Description
Name	CORPDESC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Custcorpdir

Attribute	Description
Name	Custcorpdir
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DIRNAME

Attribute	Description
Name	DIRNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TEL

Attribute	Description
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR1

Attribute	Description
Name	NADDR1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR2

Attribute	Description
Name	NADDR2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR3

Attribute	Description
Name	NADDR3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

NADDR4

Attribute	Description
Name	NADDR4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDR1

Attribute	Description
Name	ADDR1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRY

Attribute	Description
Name	COUNTRY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

TAXID

Attribute	Description
Name	TAXID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MOBNO

Attribute	**Description**
Name	MOBNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EMAIL

Attribute	**Description**
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Issuerdet

Attribute	**Description**
Name	Issuerdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OVERLIMIT

Attribute	**Description**
Name	OVERLIMIT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

OVERLMTCCY

Attribute	Description
Name	OVERLMTCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

Issuerlmts

Attribute	Description
Name	Issuerlmts
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CLTRLTYP

Attribute	Description
Name	CLTRLTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 70

TOP

LMTAMT

Attribute	Description
Name	LMTAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LMTCCY

Attribute	Description
Name	LMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ISSID

Attribute	Description
Name	ISSID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Custgrp

Attribute	Description
Name	Custgrp
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

GRPNO

Attribute	Description
Name	GRPNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RELATION

Attribute	Description
Name	RELATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Custshhold

Attribute	Description
Name	Custshhold
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SHHOLDID

Attribute	Description
Name	SHHOLDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SHHOLDPCT

Attribute	Description
Name	SHHOLDPCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHRHLDRNAME

Attribute	Description
Name	SHRHLDRNAME
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Clsccyrest

Attribute	Description
Name	Clsccyrest
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Bic

Attribute	Description
Name	Bic
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BICCD

Attribute	Description
Name	BICCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

Linkedac

Attribute	Description
Name	Linkedac
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

VRFD

Attribute	Description
Name	VRFD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LINKEDACCNO

Attribute	Description

Name	LINKEDACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LINKEDACCIBAN

Attribute	**Description**
Name	LINKEDACCIBAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

LINKEDACCBIC

Attribute	**Description**
Name	LINKEDACCBIC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

JointVenture

Attribute	**Description**
Name	JointVenture
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PARTYID

Attribute	**Description**
Name	PARTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	9

TOP

PARTYRATIO

Attribute	Description
Name	PARTYRATIO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 1

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

Custdoc-Chklist

Attribute	Description
Name	Custdoc-Chklist
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

DOCUMENT_TYPE

Attribute	Description
Name	DOCUMENT_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

CHECKED

Attribute	Description

Name	CHECKED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Doctype-Remarks

Attribute	**Description**
Name	Doctype-Remarks
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARK1

Attribute	**Description**
Name	REMARK1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK2

Attribute	**Description**
Name	REMARK2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK3

Attribute	**Description**
Name	REMARK3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	225

TOP

REMARK4

Attribute	Description
Name	REMARK4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK5

Attribute	Description
Name	REMARK5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK6

Attribute	Description
Name	REMARK6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK7

Attribute	Description
Name	REMARK7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 225

TOP

REMARK8

Attribute	Description
Name	REMARK8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK9

Attribute	Description
Name	REMARK9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

REMARK10

Attribute	Description
Name	REMARK10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 225

TOP

Custmis

Attribute	Description
Name	Custmis
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP

Datatype	String
Description	Indicates Management Information System Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CUST

Attribute	Description
Name	CUST
Datatype	String
Description	Indicates the Customer.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Custchnglog

Attribute	Description
Name	Custchnglog
Datatype	
Description	Indicates the Customer Change Log.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNDT

Attribute	Description
Name	TXNDT
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	Indicates the Old MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	Indicates the New MIS Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Baltrnsfrlog

Attribute	Description
Name	Baltrnsfrlog
Datatype	
Description	Indicates the Balance Transfer Log.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRN

Attribute	Description

Name	BRN
Datatype	String
Description	Indicates the Branch Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PRDCD

Attribute	**Description**
Name	PRDCD
Datatype	String
Description	Indicates the Product Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

FINYR

Attribute	**Description**
Name	FINYR
Datatype	String
Description	Indicates the Financial Year.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNDT

Attribute	**Description**
Name	TXNDT
Datatype	Date
Description	Indicates the Transaction Date.
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

GLCODE

Attribute	**Description**
Name	GLCODE
Datatype	String
Description	Indicates the GL Code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 9

TOP

OLDMISCD

Attribute	Description
Name	OLDMISCD
Datatype	String
Description	Indicates the Old MIS Code.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

NWMISCD

Attribute	Description
Name	NWMISCD
Datatype	String
Description	Indicates the New MIS Code.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9

TOP

TRNIND

Attribute	Description
Name	TRNIND
Datatype	String
Description	Indicates Transfer Identification Number.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates the Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	Indicates the Exchange Rate.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Dfltcd

Attribute	Description
Name	Dfltcd
Datatype	
Description	Indicates the Customer MIS Classes.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates the MIS Class.

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MISCD

Attribute	Description	
Name	MISCD	
Datatype	String	
Description	Indicates the MIS Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Dfltcda

Attribute	Description	
Name	Dfltcda	
Datatype		
Description	Indicates the Composite MIS Classes.	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MISCLS

Attribute	Description	
Name	MISCLS	
Datatype	String	
Description	Indicates the MIS Class.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MISCD

Attribute	Description	
Name	MISCD	
Datatype	String	
Description	Indicates the MIS Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	50

TOP

Custloghead

Attribute	Description
Name	Custloghead
Datatype	
Description	Indicates the Customer Log Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Jointcustomer

Attribute	Description
Name	Jointcustomer
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Custjoint

Attribute	Description
Name	Custjoint
Datatype	
Description	Indicates Customer Joint.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTPREFIX

Attribute	Description
Name	CUSTPREFIX
Datatype	String
Description	Indicates the Customer Prefix.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FRSTNAME

Attribute	Description
Name	FRSTNAME
Datatype	String
Description	Indicates the First Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MIDNAME

Attribute	Description
Name	MIDNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LASTNAME

Attribute	Description
Name	LASTNAME
Datatype	String
Description	Indicates the Last Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOB

Attribute	Description
Name	DOB
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SEX

Attribute	Description
Name	SEX
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,F

TOP

PPNO

Attribute	Description
Name	PPNO
Datatype	String
Description	Indicates Passport Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

PPTISSDT

Attribute	Description
Name	PPTISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PPTEXPDT

Attribute	Description
Name	PPTEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADD1

Attribute	Description
Name	ADD1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADD2

Attribute	**Description**
Name	ADD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADD3

Attribute	**Description**
Name	ADD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TEL

Attribute	**Description**
Name	TEL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EMAIL

Attribute	**Description**
Name	EMAIL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

SSN

Attribute	**Description**
Name	SSN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

DECEASED

Attribute	**Description**
Name	DECEASED
Datatype	String
Description	Indicates whether Deceased or not. The value should be either D or N.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,N

TOP

RESISTAT

Attribute	**Description**
Name	RESISTAT
Datatype	String
Description	Indicates the Resistant Status. The value could be either R or N.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,N

TOP

Cust-Acc-Det

Attribute	**Description**
Name	Cust-Acc-Det
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

Diary-Mst

Attribute	Description
Name	Diary-Mst
Datatype	
Description	Indicates Diary Master.
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	Indicates Instrument Number
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 16

TOP

UNTTYP

Attribute	Description
Name	UNTTYP
Datatype	String
Description	Indicates Unit Type
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

UNTVAL

Attribute	Description
Name	UNTVAL
Datatype	String

Description	Indicates Unit Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BRN

Attribute	**Description**
Name	BRN
Datatype	String
Description	Indicates the Branch Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

INSTR

Attribute	**Description**
Name	INSTR
Datatype	String
Description	Indicates Instructions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

INSTRTYPE

Attribute	**Description**
Name	INSTRTYPE
Datatype	String
Description	Indicates Instruction Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

EXEDAYS

Attribute	**Description**
Name	EXEDAYS
Datatype	Number
Description	Indicates Execution Days
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXEMONTHS

Attribute	Description
Name	EXEMONTHS
Datatype	Number
Description	Indicates Execution Months
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXEYEARS

Attribute	Description
Name	EXEYEARS
Datatype	Number
Description	Indicates Execution Years
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MNTHENDFLG

Attribute	Description
Name	MNTHENDFLG
Datatype	String
Description	Indicates Month End Flag. Flag Can be either Y or N.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

HLDRULE

Attribute	Description
Name	HLDRULE
Datatype	String
Description	Indicates Holiday Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

FRSTDUEDT

Attribute	Description
Name	FRSTDUEDT
Datatype	Date
Description	Indicates First Due Date.

Attributes	Attribute	Description
	minOccurs	0

TOP

NXTDUEDT

Attribute	Description
Name	NXTDUEDT
Datatype	Date
Description	Indicates Next Due Date
Attributes	Attribute: minOccurs — Description: 0

TOP

NXTEXEDT

Attribute	Description
Name	NXTEXEDT
Datatype	Date
Description	Indicates Next Execution Date.
Attributes	Attribute: minOccurs — Description: 0

TOP

CONDELEM

Attribute	Description
Name	CONDELEM
Datatype	String
Description	Indicates Condition Elements.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

OPRTR

Attribute	Description
Name	OPRTR
Datatype	String
Description	Indicates Operator.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2

TOP

CONDVAL

Attribute	Description
Name	CONDVAL

Datatype	Number
Description	Indicates Condition Value.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCOFCR

Attribute	Description
Name	ACCOFCR
Datatype	String
Description	Indicates Account Officer.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPLINSTRTYP

Attribute	Description
Name	SPLINSTRTYP
Datatype	String
Description	Indicates Special Instruction Type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	Indicates Expiry Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPLINSTR

Attribute	Description
Name	SPLINSTR
Datatype	String
Description	Indicates Special Instructions.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Custaccdet

Attribute	Description
Name	Custaccdet
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRNCD

Attribute	Description
Name	BRNCD
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Relationship-Linkage

Attribute	Description
Name	Relationship-Linkage
Datatype	
Description	Include relationship linkage details.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTOMER

Attribute	Description
Name	CUSTOMER
Datatype	String

Description	Indicates the customer
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RELATIONSHIP

Attribute	**Description**
Name	RELATIONSHIP
Datatype	String
Description	Indicate relations
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

INHERIT

Attribute	**Description**
Name	INHERIT
Datatype	String
Description	Indicate,include relationship Y:yes N:no
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DESCP

Attribute	**Description**
Name	DESCP
Datatype	String
Description	Indicates description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Custacdetail

Attribute	**Description**
Name	Custacdetail
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTTEXT

Attribute	Description	
Name	CUSTTEXT	
Datatype		
Description	Include customer details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SEQNO

Attribute	Description	
Name	SEQNO	
Datatype	Number	
Description	Indicates sequence number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TDESC

Attribute	Description

Name	TDESC
Datatype	String
Description	Indicate text description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

Sttms-Debit

Attribute	**Description**
Name	Sttms-Debit
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	Indicates the Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACTNO

Attribute	Description
Name	ACTNO
Datatype	String
Description	Indicates the Account Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Sttms-Detail

Attribute	Description
Name	Sttms-Detail
Datatype	
Description	Indicates Customer Details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BRANCH_CODE

Attribute	Description

Name	BRANCH_CODE
Datatype	String
Description	Indicates the Branch code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

REQUEST_REFERENCE_NO

Attribute	Description
Name	REQUEST_REFERENCE_NO
Datatype	String
Description	Indicates the Request Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CARDNO

Attribute	Description
Name	CARDNO
Datatype	String
Description	Indicates the Card Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 19

TOP

CUST_NO

Attribute	Description
Name	CUST_NO
Datatype	String
Description	Indicates the Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CARD_PRODUCT

Attribute	Description
Name	CARD_PRODUCT
Datatype	String
Description	Indicates the Product code.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRIMARY_CARD

Attribute	**Description**
Name	PRIMARY_CARD
Datatype	String
Description	Indicates the Primary Card Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

NAME_ON_CARD

Attribute	**Description**
Name	NAME_ON_CARD
Datatype	String
Description	Indicates the Name on Card.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

OWNER_ID_NO

Attribute	**Description**
Name	OWNER_ID_NO
Datatype	String
Description	Indicates the Owner ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

CARD_ISSUED_DT

Attribute	**Description**
Name	CARD_ISSUED_DT
Datatype	Date
Description	Indicates the Card Issue Date.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CARD_EXPIRY_DT

Attribute	Description
Name	CARD_EXPIRY_DT
Datatype	Date
Description	Indicates the Card Expiry Date.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CARD_STATUS

Attribute	Description
Name	CARD_STATUS
Datatype	String
Description	Indicates the Card Status.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECORD_STAT

Attribute	Description
Name	RECORD_STAT
Datatype	String
Description	Indicates the Record Stat.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTH_STAT

Attribute	Description
Name	AUTH_STAT
Datatype	String
Description	Indicates the Auth Stat.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CARD_BIN

Attribute	Description
Name	CARD_BIN

Datatype	String
Description	Indicates the Card Bin.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

CUST_AC_NO

Attribute	**Description**
Name	CUST_AC_NO
Datatype	String
Description	Indicates the Customer Account Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Extsys-Ws-Master

Attribute	**Description**
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	**Description**
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXTWSRESP

Attribute	**Description**
Name	EXTWSRESP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

Stvws-Cust-Trntax

Attribute	Description
Name	Stvws-Cust-Trntax
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTOMER_NO

Attribute	Description
Name	CUSTOMER_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Sttms-Cust-Trn-Tax

Attribute	Description
Name	Sttms-Cust-Trn-Tax
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TAX_SCHEME

Attribute	Description
Name	TAX_SCHEME
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

TXN_TAX_EXEMPTED

Attribute	**Description**
Name	TXN_TAX_EXEMPTED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TXN_TAX_EXEMPTION_PERCENT

Attribute	**Description**
Name	TXN_TAX_EXEMPTION_PERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXN_TAX_EFF_DATE

Attribute	**Description**
Name	TXN_TAX_EFF_DATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXN_TAX_EXEMPTION_REASON

Attribute	**Description**
Name	TXN_TAX_EXEMPTION_REASON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Customer-PK*
      - *CUSTNO*
    - *Customer-IO*
      - *CUSTNO*
      - *MAKER*
      - *MAKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Customer-PK

Attribute	Description
Name	Customer-PK
Datatype	
Description	

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Customer-IO

Attribute	Description
Name	Customer-IO
Datatype	
Description	

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.26.ReopenTDAmountBlock

ReopenTDAmountBlock

2.26.1.ST-ReopenTDAmountBlock-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-Full*
    - *ACC*
    - *AMTBLKNO*
    - *AMT*
    - *EXPDATE*
    - *REM*
    - *ABLKTYPE*
    - *REFERENCE_NO*
    - *HPCODE*
    - *EFFDATE*
    - *HOLDDESC*
    - *BRANCH*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Amount-Blocks-Full

Attribute	Description
Name	Amount-Blocks-Full
Datatype	
Description	

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTBLKNO

Attribute	Description	
Name	AMTBLKNO	
Datatype	String	
Description	Indicates the Amount Block Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

EXPDATE

Attribute	Description	
Name	EXPDATE	
Datatype	Date	
Description	Indicates the Expiry Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ABLKTYPE

Attribute	Description
Name	ABLKTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,S,P,E,A,C,B,D

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 40

TOP

HPCODE

Attribute	Description
Name	HPCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

HOLDDESC

Attribute	Description
Name	HOLDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	**Description**
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	**Description**
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.26.2.ST-ReopenTDAmountBlock-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-IO*
    - *AMTBLKNO*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0 Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	

Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Amount-Blocks-IO

Attribute	Description
Name	Amount-Blocks-IO
Datatype	
Description	

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	Description

<table>
<tr><td>Name</td><td>MODNO</td></tr>
<tr><td>Datatype</td><td>Number</td></tr>
<tr><td>Description</td><td>Indicates Modification number i.e. the number of times the record has been modified.</td></tr>
<tr><td>Attributes</td><td><table>
<tr><th>Attribute</th><th>Description</th></tr>
<tr><td>minOccurs</td><td>0</td></tr>
</table></td></tr>
<tr><td>Restrictions</td><td><table>
<tr><th>Restrictions</th><th>Description</th></tr>
<tr><td>totalDigits</td><td>22</td></tr>
</table></td></tr>
</table>

TOP

2.26.3.ST-ReopenTDAmountBlock-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amount-Blocks-Full*
    - *ACC*
    - *AMTBLKNO*
    - *AMT*
    - *EXPDATE*
    - *REM*
    - *ABLKTYPE*
    - *REFERENCE_NO*
    - *HPCODE*
    - *EFFDATE*
    - *HOLDDESC*
    - *BRANCH*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*
    - *TXNSTAT*
    - *AUTHSTAT*

UDFDETAILS
FLDNAM
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
	nillable	true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String

Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Amount-Blocks-Full

Attribute	Description
Name	Amount-Blocks-Full
Datatype	
Description	

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description	Indicates Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

AMTBLKNO

Attribute	Description	
Name	AMTBLKNO	
Datatype	String	
Description	Indicates the Amount Block Number.	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description	Indicates Amount	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	Date
Description	Indicates the Expiry Date
Attributes	Attribute: minOccurs, Description: 0

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	Indicates the Remarks.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 255

TOP

ABLKTYPE

Attribute	Description
Name	ABLKTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: F,S,P,E,A,C,B,D

TOP

REFERENCE_NO

Attribute	Description
Name	REFERENCE_NO
Datatype	String
Description	Indicates Reference Number
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 40

TOP

HPCODE

Attribute	Description
Name	HPCODE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

EFFDATE

Attribute	Description
Name	EFFDATE
Datatype	Date
Description	Indicates the Effective Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

HOLDDESC

Attribute	Description
Name	HOLDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description

Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAM

Attribute	Description
Name	FLDNAM
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Amount-Blocks-PK*
      - *AMTBLKNO*
    - *Amount-Blocks-IO*
      - *AMTBLKNO*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Amount-Blocks-PK

Attribute	Description
Name	Amount-Blocks-PK
Datatype	
Description	

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Amount-Blocks-IO

Attribute	Description
Name	Amount-Blocks-IO
Datatype	
Description	

TOP

AMTBLKNO

Attribute	Description
Name	AMTBLKNO
Datatype	String
Description	Indicates the Amount Block Number.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: totalDigits / 22

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

Customer Service
[April] [2014]

Oracle Financial Services software Limited
Oracle Park
Off Western Express Highway
Goregaon (East)
Mumbai, Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax:+91 22 6718 3001
www.oracle.com/financialservices/

Copyright © [2013], [2014], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of
this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any

kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.