

Oracle® Tuxedo

Application Runtime for Batch User's Guide



Release 22c

F89454-01

June 2024

The Oracle logo, consisting of a solid red square with the word "ORACLE" in white, uppercase, sans-serif font centered within it.

ORACLE®

Oracle Tuxedo Application Runtime for Batch User's Guide, Release 22c

F89454-01

Copyright © 2010, 2024, Oracle and/or its affiliates.

Primary Author: Priya Pathak

Contributing Authors: Tulika Das

Contributors: Maggie Li

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle®, Java, MySQL, and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

Preface

Documentation Accessibility	viii
Organization	viii

1 Overview of the Batch Runtime Environment

1.1 Oracle Tuxedo Application Runtime for Batch Presentation and Structure	1-1
1.1.1 Technical Functions	1-1
1.1.2 High-Level Functions	1-1
1.1.3 Interface-Level Functions	1-1
1.2 Script Execution Phases	1-2

2 Using Batch Runtime

2.1 Configuration Files	2-1
2.1.1 BatchRT.conf	2-1
2.1.2 Messages.conf	2-2
2.1.3 FunctionReturnCode.conf	2-2
2.1.4 ReturnCode.conf	2-2
2.1.5 Writer.conf	2-2
2.2 Setting Environment Variables	2-2
2.2.1 Environment Variables for EJR	2-2
2.2.2 Environment Variables for Native JCL	2-9
2.3 Configuring Batch Runtime in MP Mode	2-12
2.4 Creating a Script	2-13
2.4.1 General Structure of a Script	2-13
2.4.2 Script Example	2-14
2.4.3 Defining and Using Symbols	2-15
2.4.4 Creating a Step That Executes a Program	2-16
2.4.5 Application Program Abend Execution	2-16
2.4.6 Creating a Procedure	2-17
2.4.6.1 Creating an In-Stream Procedure	2-17
2.4.6.2 Creating an External Procedure	2-17
2.4.7 Using a Procedure	2-18

2.4.8	Modifying a Procedure at Execution Time	2-18
2.4.8.1	Using Overrides for File Assignments	2-19
2.5	Controlling Script Behavior	2-20
2.5.1	Conditioning the Execution of a Step	2-20
2.5.1.1	Using m_ConDlf, m_ConDElse, and m_ConDEndif	2-20
2.5.1.2	Using m_ConDExec	2-21
2.5.2	Controlling the Execution Flow	2-21
2.5.3	Changing Default Error Messages	2-22
2.6	Different Behaviors from z/OS	2-22
2.7	Using Files	2-22
2.7.1	Creating a File Definition	2-23
2.7.1.1	m_FileBuild Examples	2-23
2.7.1.2	m_FileAssign Examples	2-23
2.7.2	Assigning and Using Files	2-23
2.7.2.1	About DD DISP=MOD	2-24
2.7.3	Concurrent File Accessing Control	2-26
2.7.4	Using Generation Data Group (GDG)	2-26
2.7.4.1	GDG Management Functionalities	2-26
2.7.4.2	File-Based Management	2-32
2.7.4.3	DB-Based Management	2-32
2.7.4.4	Support for Data Control Block (DCB)	2-35
2.7.5	Using an In-Stream File	2-36
2.7.6	Using a Set of Concatenated Files	2-37
2.7.7	Using an External "sysin"	2-37
2.7.8	Deleting a File	2-37
2.7.9	RDB Files	2-37
2.7.10	Using an RDBMS Connection	2-38
2.8	Submitting a Job Using INTRDR Facility	2-39
2.9	Submitting a Job With EJР	2-40
2.10	User-Defined Entry/Exit	2-40
2.10.1	Configuration	2-41
2.11	Batch Runtime Logging	2-41
2.11.1	General Introduction	2-41
2.11.1.1	Log Message Format	2-41
2.11.1.2	Log Message Level	2-42
2.11.1.3	Log Level Control	2-42
2.11.1.4	Log File Structure	2-43
2.11.2	Log Header	2-43
2.11.2.1	Configuration	2-44
2.11.3	File Information Logging	2-45
2.11.3.1	Configuration	2-45
2.12	Using Batch Runtime With a Job Scheduler	2-47

2.13	Executing an SQL Request	2-47
2.14	Simple Application on COBOL-IT / BDB	2-47
2.15	Native JCL Job Execution	2-48
2.15.1	General Introduction	2-48
2.15.2	Configurations	2-48
2.15.3	Using JES Client to Manage JCL Jobs	2-48
2.15.3.1	Submitting a JCL Job	2-49
2.15.3.2	Printing Jobs	2-49
2.15.3.3	Holding/Releasing/Canceling/Purging a JCL Job	2-49
2.15.3.4	JCL Engine's Debug Trace File	2-49
2.15.4	Supporting Range for JCL Statements and Utilities	2-49
2.16	Native JCL Test Mode	2-51
2.16.1	General Introduction	2-52
2.16.2	Configurations	2-52
2.16.2.1	Environment Variables Configurations (Mandatory)	2-52
2.16.2.2	Native JCL Configuration File Configurations (Optional)	2-52
2.16.3	Using Client to Manage Test Mode	2-53
2.16.4	Test Mode Report Files	2-53
2.16.4.1	Individual Report File	2-54
2.16.4.2	Category Report File	2-56
2.16.4.3	Summary Report File	2-58
2.17	Network Job Entry (NJE) Support	2-61
2.17.1	General Introduction	2-61
2.17.2	Configurations	2-61
2.17.2.1	Job Execution Server Group	2-61
2.17.2.2	ON/OFF Setting of NJE Support	2-62
2.17.2.3	Environment Variable MT_TMP in MP Mode	2-62
2.17.2.4	Queue EXECGRP	2-62
2.17.3	NJE Job Sample	2-62
2.18	File Catalog Support	2-64
2.18.1	General Introduction	2-64
2.18.2	Database Table	2-64
2.18.3	Configuration Variables	2-65
2.18.4	External Shell Scripts	2-65
2.18.4.1	Description	2-65
2.18.4.2	Usage	2-66
2.18.4.3	Sample	2-66
2.18.4.4	DropTableCatalog[Oracle Db2].sh	2-66
2.18.5	External Dependency	2-66
2.19	Launching REXX EXECs	2-66
2.19.1	Setting MT_REXX_PATH	2-66
2.19.2	Launching REXX EXECs	2-66

2.19.3	TSO Batch Commands	2-67
2.20	COBOL Program Access to Oracle and TimesTen Database	2-67
2.20.1	Setting Environment Variables	2-67
2.20.2	Programming in COBOL	2-68
2.20.3	Preprocessing COBOL Programs	2-68
2.20.4	Examples	2-68
2.20.4.1	Example for Setting Environment Variables	2-69
2.20.4.2	Example for COBOL Programs Accessing to Oracle Database	2-69
2.20.4.3	Example for COBOL Programs Accessing to TimesTen Database	2-69
2.20.4.4	Example for Preprocessing COBOL Programs	2-69
2.20.4.5	Example for Compiling COBOL Programs (CIT)	2-70

3 Best Practices

3.1	Adapting z/OS Capabilities on a UNIX/Linux Environment	3-1
3.1.1	Defining Paths for Procedures, Includes and Programs	3-1
3.1.2	Prohibiting the Use of UNIX Commands	3-1
3.1.3	Avoiding the Use of File Overriding	3-2

4 Using Tuxedo Job Enqueueing Service (TuxJES)

4.1	Overview	4-1
4.1.1	Requirements	4-1
4.1.2	TuxJES Components	4-1
4.2	Configuring a TuxJES System	4-2
4.2.1	Setting up TuxJES as an Oracle Tuxedo Application (Using /Q)	4-2
4.2.1.1	Oracle Tuxedo Configuration File	4-2
4.2.1.2	Oracle Tuxedo /Q Queue Space and Queue Creation	4-5
4.2.1.3	File System Configuration	4-5
4.2.1.4	TuxJES Configuration File	4-5
4.2.1.5	TuxJES Security Configuration	4-8
4.2.1.6	TuxJES User Mapping File	4-9
4.2.2	Setting up TuxJES as an Oracle Tuxedo Application (Using Database)	4-9
4.2.2.1	Setting Up TuxJES	4-9
4.2.2.2	Setting Up Oracle Database	4-10
4.2.2.3	Setting Up DB2 Database	4-13
4.2.2.4	Setting Up BDB Database	4-15
4.2.3	Setting Up TuxJES in MP Mode	4-16
4.3	Using TuxJES	4-16
4.3.1	Submitting a Job	4-16
4.3.2	Displaying Job Information	4-17
4.3.2.1	Getting Job Status (Synchronous)	4-18

4.3.3	Holding a Job	4-19
4.3.4	Releasing a Job	4-19
4.3.5	Canceling a Job	4-20
4.3.6	Purging a Job	4-20
4.3.6.1	Automatic Job Purge	4-20
4.3.7	Displaying/Changing ARTJESINITIATOR Configuration	4-22
4.3.8	Controlling ARTJESINITIATOR Servers	4-22
4.3.8.1	Controlling ARTJESINITIATOR Servers (Synchronous)	4-23
4.3.9	Event Subscribing/Unsubscribing	4-24
4.4	Authorizing TuxJES Job Access	4-24
4.4.1	Configuring Job Access Authorization Mechanism	4-25
4.4.2	Using Job Operation Authorization Rules	4-25
4.4.2.1	Setting Rules	4-25
4.4.2.2	Processing Rules	4-27
4.4.2.3	Adding Comments to Rules	4-27
4.4.2.4	Examples	4-28
4.4.3	Using artjesadmin to Dynamically Change Job Access Authorization	4-29
4.5	Tracing TuxJES	4-29
4.5.1	Setting Environment Variables	4-30
4.5.2	Understanding TuxJES Trace File	4-30
4.5.3	Understanding TuxJES Trace Message Format	4-30
4.5.4	Understanding TuxJES Trace Message Level	4-31
4.5.5	Controlling TuxJES Trace Message Level	4-31
4.5.5.1	Using JESTRACE to Set TuxJES Trace Message Level	4-31
4.5.5.2	Using artjesadmin to Dynamically Change TuxJES Trace Message Level	4-31

5 Using ART BATCH ISPF

5.1	Overview	5-1
5.2	Prerequisites	5-1
5.3	Using ART Batch ISPF	5-1
5.3.1	Administering ART Batch	5-2
5.3.2	Controlling ART Batch Jobs	5-2

6 Debugging COBOL Programs

6.1	Debugging with Micro Focus COBOL	6-1
6.2	Debugging with COBOL-IT COBOL	6-1
6.3	Configuring for Debugging in Configuration File	6-2

Preface

The aim of the following guide is to help users understand and write Korn-Shell scripts to be used with the Batch Runtime, and how to use Tuxedo Job Enqueueing Service (TuxJES).

The guide covers the usual tasks that are performed within Korn-Shell scripts, whether they are the result of a conversion from z/OS JCL or newly written for the target platform. The guide also covers the usage of TuxJES.

- [Documentation Accessibility](#)
- [Organization](#)

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Organization

This guide is divided into four main chapters:

- **Overview of the Batch Runtime:** This chapter introduces the general principles of the Batch Runtime.
- **Using the Batch Runtime:** This chapter describes, through various examples, how to perform the usual tasks required to implement the Batch Runtime. This section describes how the different Oracle Tuxedo Application Runtime for Batch high-level functions can be assembled in order to create a single "step", and then how the different steps are assembled in order to create a complete Korn shell script
- **Best Practices:** This chapter provides guidance for preserving z/OS capabilities on the target platform.
- **Using TuxJES:** This chapter provides guidance for configuring and executing TuxJES.

For more information about Batch Runtime, specifically on how to code the different functions, see Oracle Tuxedo Application Runtime for Batch Reference Guide

1

Overview of the Batch Runtime Environment

This chapter contains the following topics:

- [Oracle Tuxedo Application Runtime for Batch Presentation and Structure](#)
- [Script Execution Phases](#)

1.1 Oracle Tuxedo Application Runtime for Batch Presentation and Structure

The purpose of the Batch Runtime is to provide functions enabling a robust production environment on a UNIX/Linux platform.

Oracle Tuxedo Application Runtime for Batch is composed of:

- [Technical Functions](#)
- [High-Level Functions](#)
- [Interface-Level Functions](#)

1.1.1 Technical Functions

The technical level contains simple one-action functions: easy to write, easy to maintain and easy to debug. For example, GDG (Generation Data Group) management belongs to this level. This technical level is the robust base of the Batch Runtime.

1.1.2 High-Level Functions

The high-level functions provide entry points to the Batch Runtime. This level homogenizes the behavior of functions, in order for them to be called in a production script. A high-level function follows a skeleton which provide robust logical workflow (execution on/off, options check, predefined return codes ...).

In this level, we find functions to:

- Manage files (creation, copy, assignation...)
- Launch programs (COBOL, executable ...)
- Databases (connection/disconnection/commit/rollback for program, SQL execution)
- Produce reports
- Run utilities

1.1.3 Interface-Level Functions

The interface level allow users to interact with the Batch Runtime job management: submission, holding and releasing, class management, reporting, monitoring ...

Oracle Tuxedo Application Runtime for Batch offers robust and useful production functions. With these functions, you can easily emulate JCL and JES2 features, and have extra features like "no exec mode", return code predefinition (customizable), internationalization.

Oracle Tuxedo Application Runtime for Batch uses a native shell interpreter for high level functions. This approach enables you to add new runtime functions for specific production needs

1.2 Script Execution Phases

When submitted for execution within the Batch Runtime, a Korn shell script is processed through three separate phases:

Input Phase

In this phase, the JOB card parameters are analyzed.

Conversion Phase

During this phase, the Batch Runtime performs the following actions:

- Expand all the external Korn shell scripts (procedures and/or includes) that are used within the script so as to produce a single complete script.
- Resolve all the symbols that are used in the script replacing them by their current values.

Execution Phase

The script is executed by the Batch Runtime.

2

Using Batch Runtime

This chapter contains the following topics:

- [Configuration Files](#)
- [Setting Environment Variables](#)
- [Configuring Batch Runtime in MP Mode](#)
- [Creating a Script](#)
- [Controlling Script Behavior](#)
- [Different Behaviors from z/OS](#)
- [Using Files](#)
- [Submitting a Job Using INTRDR Facility](#)
- [Submitting a Job With EJR](#)
- [User-Defined Entry/Exit](#)
- [Batch Runtime Logging](#)
- [Using Batch Runtime With a Job Scheduler](#)
- [Executing an SQL Request](#)
- [Simple Application on COBOL-IT / BDB](#)
- [Native JCL Job Execution](#)
- [Native JCL Test Mode](#)
- [Network Job Entry \(NJE\) Support](#)
- [File Catalog Support](#)
- [Launching REXX EXECs](#)
- [COBOL Program Access to Oracle and TimesTen Database](#)

2.1 Configuration Files

The Configuration files are implemented in the directory CONF of the RunTime Batch.

- [BatchRT.conf](#)
- [Messages.conf](#)
- [FunctionReturnCode.conf](#)
- [ReturnCode.conf](#)
- [Writer.conf](#)

2.1.1 BatchRT.conf

This file contains variables definition.

These variables must be set before using the RunTime Batch.

2.1.2 Messages.conf

This file contains messages used by RTBatch.

The messages may be translated in a local language.

2.1.3 FunctionReturnCode.conf

This file contains internal codes associated with a message.

2.1.4 ReturnCode.conf

This file contains return codes associated with a message and returned to the KSH script.

2.1.5 Writer.conf

This file contains usage and samples of writer.

Users can add their writers into this file.

2.2 Setting Environment Variables

Some variables (such as `ORACLE_SID`, `COBDIR`, `LIBPATH`, `COBPATH` ...) are shared variables between different components and are not described in this current document. For more information, see [Rehosting Workbench Installation Guide](#).

- [Environment Variables for EJR](#)
- [Environment Variables for Native JCL](#)

2.2.1 Environment Variables for EJR

The following table lists the environment variables that are used in the KSH scripts and must be defined before using the software.

Table 2-1 KSH Script Environment Variables

Variable	Usage
DATA	Directory for permanent files.
TMP	Directory for temporary application files.
SYSIN	Directory where the sysin are stored.
MT_JOB_NAME	Name of the job, managed by the Batch Runtime.
MT_JOB_PID	PID (process id) of the job, managed by the Batch Runtime.



Note:

For `DATA` and `TMP`, the full path can only contain `[a-zA-Z0-9_/.]`.

The following table lists the environment variables that are used by Batch Runtime and must be defined before using the software.

Table 2-2 Oracle Tuxedo Application Runtime for Batch Environment Variables

Variable	Usage
JESDIR	Directory where TuxJES is installed.
PROCLIB	Directory for PROC and INCLUDE files, used during the conversion phase.
MT_ACC_FILEPATH	File concurrency access, directory that contains the files AccLock and AccWait. These files must be created empty before running the Batch Runtime ().
MT_COBOL	Depending on the used COBOL, must contain: <ul style="list-style-type: none"> • "COBOL_MF" for Micro Focus COBOL • "COBOL_IT" for COBOL-IT • "COBOL_NONE" if users neither have any COBOL programs to run nor use any COBOL product; besides, with this setting, only GDG, LSEQ, Fixed length SEQ, and PDS files are supported.
MT_CTL_FILES	Directory where the control file (CTL) used by the function m_DBTableLoad (sqlldr with ORACLE, load and export with UDB).
MT_DSNUTILB_LOADUNLOAD	Indicates the working mode of m_DBTableLoad and m_DBTableUnload. When it is set to "yes", m_DBTableLoad and m_DBTableUnload call the COBOL programs; in this mode, the related data file for load/unload are in the same format as in z/OS for utility DSNUTILB (Load/Unload) and for utility DSNTIAUL (Unload). The COBOL program name could be: schema-table-L (DSNUTILB Load), schema-table-U (DSNUTILB Unload), or schema-table-u (DSNTIAUL Unload). When it is set to other values than "yes", "MT_CTL_FILES" are necessary for m_DBTableLoad and m_DBTableUnload.
MT_DB_DEFAULT_SCHEMA	Indicates the default schema for DB, When MT_DSNUTILB_LOADUNLOAD is set to "yes". The default value is "DEFSchema". This variable is used for specify the schema for COBOL programs "schema-table-L" and "schema-table-U".
MT_DB	Depending on the target data base, must contain: <ul style="list-style-type: none"> - "DB_ORACLE": means for ORACLE - "DB_DB2LUW": means for UDB
MT_DB_LOGIN	Database connection user.
MT_FROM_ADDRESS_MAIL	From-Address used by the function m_SendMail when the option "-f" is omitted.
MT_FTP_TEST	Variable used by the function m_Ftp to do the tranfer or not (test mode).
MT_GENERATION	A mandatory environment variable which indicates the directory to GDG technical functions. The default is directory GENERATION_FILE. To manage GDG files in database, you need to set the value to GENERATION_FILE_DB and configure MT_GDG_DB_ACCESS appropriately. If the value is specified as NULL or with an incorrect directory name, error occurs when using this environment variable.

Table 2-2 (Cont.) Oracle Tuxedo Application Runtime for Batch Environment Variables

Variable	Usage
MT_KSH	<p>Path of the used "ksh" (pdksh or ksh88 only).</p> <div style="border-left: 2px solid #0070C0; padding-left: 10px; margin-left: 20px;"> <p> Note:</p> <ul style="list-style-type: none"> Do not copy pdksh from other machines. You should either download the source code from official website and then build pdksh executable from it, or install pdksh through the official installer which is included in the corresponding OS release image. If you build pdksh from source code, recommend that you define the CPU frequency (CLK_TCK, in ksh_time.h) from 60HZ to 100HZ, as most modern Linux/UNIX platforms use 100 as their default CPU frequency. For more information about pdksh, see https://github.com/Orc/pdksh </div>
MT_LOG	Logs directory (without TuxJes).
MT_ROOT	Directory where the Batch Runtime application has been installed. (See the <i>BatchRT.conf</i> configuration file)
MT_SMTP_PORT	Port used by the functions m_Smtp and m_SendMail (localhost by default).
MT_SMTP_SERVER	Server used by the functions m_Smtp and m_SendMail (25 by default).
MT_SORT	Depending on the used SORT, must contain: <ul style="list-style-type: none"> - "SORT_MicroFocus" for Micro Focus Sort Utility - "SORT_SyncSort" for SyncSort Sort Utility - "SORT_CIT" for citsort utility
MT_SYSOUT	Sysout directory (without TuxJes).
MT_TMP	Directory for temporary internal files
MT_EXCI	EXCI Interface (Default is Oracle Tuxedo).
MT_JESDECRYPT	MT_JESDECRYPT must be set to jesdecrypt object file.
MT_EXCI_XA	Name of the resource manager for XA.
MT_EXCIGRPNAME	TUXEDO SRVGRP value of the ARTDPL server.



See Also:

For more information, see [BatchRT.conf](#)

**Note:**

For the following environment variables, the full path can only contain [a-zA-Z0-9_/.]

- JESDIR
- MT_KSH
- MT_LOG
- MT_REFINEDIR
- MT_SYSOUT
- MT_TMP

The following table lists optional environment variables used by Batch Runtime:

Table 2-3 Oracle Tuxedo Application Runtime for Batch Environment Variables (Optional)

Variable	Usage
MT_ACC_WAIT	Retry interval (seconds) to acquire file lock when a job tries to access a file that is locked by other jobs.
MT_ACC_MAXWAIT	Maximum wait time (seconds) to acquire file lock. If the lock is not acquired within such time, relevant file operation will fail.
MT_CATALOG_DB_LOGIN	Variable used with valid database login information to access Database file catalog. Its format is the same as MT_DB_LOGIN <div data-bbox="933 1157 979 1199" data-label="Image"></div> <div data-bbox="979 1159 1060 1190" data-label="Section-Header">Note:</div> <div data-bbox="976 1213 1440 1362" data-label="Text"> <p>It precedes MT_DB_LOGIN in accessing file catalog. If file catalog DB is the same as data DB, configuring MT_DB_LOGIN only is required; otherwise, both must be configured.</p> </div>
MT_CLEANUP_EMPTY_SYSOUT	Controls whether empty SYSOUT files are cleaned up at the end of job execution. <ul style="list-style-type: none"> • MT_CLEANUP_EMPTY_SYSOUT=Y: empty SYSOUT files are cleaned up. • MT_CLEANUP_EMPTY_SYSOUT=N: empty SYSOUT files are not cleaned up. The default value is Y.

Table 2-3 (Cont.) Oracle Tuxedo Application Runtime for Batch Environment Variables (Optional)

Variable	Usage
MT_CONFIG_FILE	<p>A variable to use the specified configuration file instead of the default configuration file <code>BatchRT.conf</code> under "ejr/CONF".</p> <ul style="list-style-type: none">For jobs submitted from EJR, export this variable in advance. You can restore the default configuration file <code>BatchRT.conf</code> by unsetting this variable.For jobs submitted from TUXJes, export this variable before restarting TuxJes servers. You can restore the default configuration file <code>BatchRT.conf</code> by unsetting this variable and then restarting TUXJes servers. <p>If this variable is not set, the configuration file <code>BatchRT.conf</code> under "ejr/CONF" will be used.</p>
MT_CPU_MON_STEP	<p>A variable used to enable CPU time usage monitor of step for all job. Set <code>MT_CPU_MON_STEP=yes</code> to enable CPU time usage monitor of step for all job.</p> <p>If <code>MT_CPU_MON_STEP</code> is not configured or its value is not equal "yes", this feature is disabled.</p>
MT_DB_LOGIN2	<p>Used with valid database login information to access database.</p> <p>If <code>MT_DB_LOGIN2</code> has a non-null value, BatchRT uses <code>runb2</code> (which supports parallel Oracle and DB2 access).</p>
MT_DB_SQL_PREPROCESS	<p>Specifies which DB preprocessor is executed before SQL is executed.</p> <p>The built-in DB2-to-Oracle SQL Converter is "<code>\${JESDIR}/tools/sql/oracle/BatchSQLConverter.sh</code>".</p>

Table 2-3 (Cont.) Oracle Tuxedo Application Runtime for Batch Environment Variables (Optional)

Variable	Usage
MT_DB2_SYSTEM_MAPPING	<p>Specifies a full file path. The file is used to store the mapping from "DB SYSTEM" to "DB connection credential string". The file format is:</p> <pre><DB SYSTEM NAME>:<DB TYPE>:<Connection String></pre> <ul style="list-style-type: none"> When <DB TYPE> is "ORA", the <connection string> format is <user>/<pwd>@<instance id>. For example, ORA01:ORA:tigger/scot@orains01 When <DB TYPE> is "DB2", the <connection string> format is <instance id> user <user> using <pwd>. For example, DB202:DB2:db2ins02 user tom using cat. <p>This file is accessed when "DB SYSTEM" is specified in the following EJR API: m_ProgramExec, m_DBTableLoad, m_DBTableUnload, m_ExecSQL, m_DSUTILB, and m_UtilityExec.</p> <div style="border: 1px solid #0070C0; padding: 10px; margin-top: 20px;"> <p> Note:</p> <p>When "DB SYSTEM" is specified in a nested way, only the outer setting takes effect. For example, in the following case, only "ORA01" takes effect (and "ORA02" is ignored).</p> <pre>m_FileAssign -i SYSIN m_ProgramExec -s ORA02 -b COBOL_PGM _end m_UtilityExec -s ORA01 SYSIN</pre> </div>
MT_DSNTIAUL	<p>If it is configured to "Y", Batch runtime provides you DSNTIAUL utility to unload data from Oracle Database tables. This utility has the same functionality as DSNTIAUL utility on mainframe with DB2. If it is configured to "N" or if it is not configured, Batch runtime executes SQL statement and writes the output to a specific file in plain text. The default value is "Y".</p>
MT_EJRLOG	<p>If it is configured to "Y", BatchRT generates an EJR log file and writes every phase's log to it. If it is configured to "N", BatchRT does not generate the EJR log file. The default value is "Y".</p>
MT_EXCI_PGM_LIST	<p>A list of executable programs. The programs are invoked by runbexci instead of runb. For each program in this list, whether or not -n is specified by m_ProgramExec, the program is invoked only by runbexci.</p> <p>The default value is empty; programs are separated by commas. For example:</p> <pre>MT_EXCI_PGM_LIST=PGM1,PGM2</pre>
MT_FTP_PASS	<p>Sets ftp password stored in jes security profile, and used at runtime.</p>
MT_GDG_DB_ACCESS	<p>A variable used with valid database login information to access Oracle Database for GDG management. For example, user/password@sid. Mandatory if MT_GENERATION is set to GENERATION_FILE_DB.</p>

Table 2-3 (Cont.) Oracle Tuxedo Application Runtime for Batch Environment Variables (Optional)

Variable	Usage
MT_GDG_DB_BUNCH_OPERATION	If configured to "Y", the GDG changes are committed using a single database access. If configured to "N", the GDG changes are committed using one or more database accesses. The default value is "N".
MT_GDG_USEDCB	A variable used to enable DCB support function for GDG. <ul style="list-style-type: none"> MT_GDG_USEDCB=Y: Create .dcb file for GDG (default behavior). In this mode, LSEQ or SEQ can be specified as file type of GDG members in m_FileAssign statement. MT_GDG_USEDCB=N: Don't create .dcb file for GDG. In this mode, file type of GDG members can only be LSEQ; whatever file type that you specify in m_FileAssign statement is ignored.
MT_META_DB	The database used for the file catalog and GDG meta data. The default is null <ul style="list-style-type: none"> DB_ORACLE for ORACLE DB_DB2LUW for UDB If MT_META_DB has a non-null value, BatchRT uses the database type defined in MT_META_DB for meta data. Otherwise, MT_DB is used.
MT_REFINEDIR	The full install path of Workbench refine, which will be invoked to convert a JCL job to a KSH job. For example: MT_REFINEDIR=/newspace/public/WB_Test/wb12110/refine
MT_REFINEDISTRIB	The value of environment variable REFINEDISTRIB, which is used when Workbench converts a JCL job. For example: <ul style="list-style-type: none"> MT_REFINEDISTRIB = Linux64: Set REFINEDISTRIB to Linux64 MT_REFINEDISTRIB = Linux32: Set REFINEDISTRIB to Linux32
MT_RUNB_SIGNAL_TO_TRAP	Contains all signals caused by running user application which will be handled by Batch Runtime. The default value is all the supporting signals. For example: MT_RUNB_SIGNAL_TO_TRAP=\${MT_RUNB_SIGNAL_TO_TRAP:-"1 2 3 4 6 7 8 11 13 14 15"}
MT_SYS_IO_REDIRECT	In BatchRT.conf this item is used to make runb redirect SYSIN and SYSOUT for COBOL program run by m_ProgramExec. <ul style="list-style-type: none"> If SYSIN is set, then the stdin for utility redirects to the file \${DD_SYSIN}. If SYSOUT is set, then the stdout and stderr for utility redirects to file \${DD_SYSOUT}. By default, MT_SYS_IO_REDIRECT=SYSIN, SYSOUT
MT_SYSLOG	In EJR mode, if it is configured to "Y", BatchRT generates a SYSLOG file. If it is configured to "N", BatchRT does not generate the SYSLOG file. The default value is "Y".
MT_SYSLOG_MILLISECOND	If it is configured to "Y", use hour, minute, second, or millisecond for Step Start Time and Step End Time in SYSLOG file. If it is configured to "N", use hour, minute, or second (millisecond cannot be used). The default value is "N".

Table 2-3 (Cont.) Oracle Tuxedo Application Runtime for Batch Environment Variables (Optional)

Variable	Usage
MT_USERENTRYEXIT	Controls whether user entry/exit function is enabled or not. <ul style="list-style-type: none"> MT_USERENTRYEXIT=Y: user entry/exit function is enabled. MT_USERENTRYEXIT=N: user entry/exit function is disabled. The default value is Y. For more information, see User-Defined Entry/Exit .
MT_UTILITY_LIST_UNSUPP ORT	A list of executable programs, programs that don't exist but users don't want to fail any jobs because of them. When <code>m_ProgramExec</code> invokes nonexistent programs, JOB will continue if those programs are specified in this list. For example: MT_UTILITY_LIST_UNSUPPORT=IEHINITT, IEHLIST, IEHMOVE, IEHS TATR, IEHPRGM, IEBCOMPR, IEBEDIT, IEBIMAGE, IEBUPDTE, IEBDG, IEBTPCH
MT_WB_HOSTNAME	The host name (or IP address), where Workbench is installed to be invoked to convert JCL job to KSH job. The value of MT_WB_HOSTNAME is null if Workbench is in localhost. User name is optional to be added. For example: <ul style="list-style-type: none"> MT_WB_HOSTNAME=host1: Set the value of MT_WB_HOSTNAME to host1 MT_WB_HOSTNAME=user1@host1: Set the value of MT_WB_HOSTNAME to user1@host1 <div style="border-left: 2px solid #0070C0; padding-left: 10px; margin-top: 10px;"> <p> Note:</p> <p>It is required to be set if Workbench is deployed on the remote machine while ARTJESCONV server is deployed on another machine.</p> </div>
MT_SORT_BY_EBCDIC	If configured to "Y", record-sequential ASCII files are sorted in EBCDIC order. If configured to "N", record-sequential ASCII files are sorted in ASCII order. The default value is "N".
MT_SIGN_EBCDIC	If configured to "Y", for numeric DISPLAY items with included signs, the signs are to be interpreted according to the EBCDIC convention. If configured to "N", for numeric DISPLAY items with included signs, the signs are to be interpreted according to the ASCII convention. The default value is "Y".
MT_PROG_RC_ABORT	This env controls dataset termination operation. Any return code greater than or equal to MT_PROG_RC_ABORT is considered as abort; any code less than MT_PROG_RC_ABORT is considered as commit. The default value is 1.

2.2.2 Environment Variables for Native JCL

The following lists the environment variables that are used by Native JCL Batch Runtime and must be defined before using the software:

Table 2-4 Oracle Tuxedo Application Runtime for Native JCL Batch Environment Variables

Variable	Usage
JESDIR	Directory where TuxJES is installed.
DATA	Directory for permanent files.
TMP	Directory for temporary application files.
PROCLIB	Directory used for search of PROC and INCLUDE files.
MT_ACC_FILEPATH	File concurrency access directory that contains the files AccLock and AccWait. These files must be created empty before you run Batch Runtime.
MT_COBOL	Depending on the used COBOL, must contain: <ul style="list-style-type: none"> • COBOL_MF: means using Micro Focus COBOL • COBOL_IT: means using COBO-IT COBOL
MT_DB	Depending on the target data base, must contain: <ul style="list-style-type: none"> • DB_ORACLE: means using Oracle • DB_DB2LUW: means using DB2
MT_DB_LOGIN	Database connection information.
MT_LOG	Logs directory.
MT_TMP	Directory for temporary internal files.

The following table lists optional environment variables used by Native JCL Batch Runtime.

Table 2-5 Oracle Tuxedo Application Runtime for Native JCL Batch Environment Variables (Optional)

Variable	Usage
DSNUTILB_PARALLEL_NUM	Sets the number of thread to insert records to table in the load process of utility DSNUTILB. Default value is 5.
JESTRACE	Control log output level. Its values could be one of the followings: ERROR, WARN, INFO, DEBUG, and DUMP. Default value is INFO.
MT_VOLUME_DEFAULT	When MT_VOLUME_DEFAULT is set to a non-empty value, catalog feature is enabled. It is used as volume value if there is no volume specified when a new dataset is created. If MT_VOLUME_DEFAULT is not set, catalog feature is disabled.
MT_E2A_FILE	Identifies a customer specified EBCDIC to ASCII mapping table file. The file format is one-line-one-char: 00;61 01;50 ...
MT_ACC_WAIT	Retry interval (seconds) to acquire file lock when a job tries to access a file locked by other job. The default value is 5.
MT_ACC_MAXWAIT	Maximum wait time (seconds) to acquire file lock. If the lock is not acquired within such time, relevant file operation fails. The default value is 0.

Table 2-5 (Cont.) Oracle Tuxedo Application Runtime for Native JCL Batch Environment Variables (Optional)

Variable	Usage
MT_DB_LOGIN2	Used with valid database login information to access database. If MT_DB_LOGIN2 has a non-null value, BatchRT uses parallel Oracle and DB2 access.
MT_DB2_SYSTEM_MAPPING	Specifies a full-path file name. The file is used to store the mapping from "DB SYSTEM" to "DB connection credential string". The file format is: <DB SYSTEM NAME>:<DB TYPE>:<Connection String> <ul style="list-style-type: none"> When <DB TYPE> is "ORA", the <connection string> format is <user>/<pwd>@<instance id>. For example, ORA01:ORA:tigger/scot@orains01 When <DB TYPE> is "DB2", the <connection string> format is:<instance id> user <user> using <pwd>. For example, DB202:DB2:db2ins02 user tom using cat. When MT_DB2_SYSTEM_MAPPING is defined, the feature of mapping from "DB SYSTEM" to "DB connection credential string" is enabled; otherwise, the feature is disabled.
MT_DSNTIAUL	If it is configured to "Y" or if it is not configured, Batch runtime provides you DSNTIAUL utility to unload data from Oracle Database tables. This utility has the same functionality as DSNTIAUL utility on mainframe with DB2. If it is configured to "N", Batch runtime executes SQL statement and writes the output to a specific file in plain text. The default value is "Y".
MT_SORT	Depending on the used SORT. It must contain <ul style="list-style-type: none"> SORT_MicroFocus for Micro Focus Sort Utility. SORT_SyncSort for SyncSort Sort Utility SORT_CIT for citsort utility If not specified, it depends on MT_COBOL. <ul style="list-style-type: none"> SORT_MicroFocus, if MT_COBOL=MF is set SORT_CIT, if MT_COBOL=IT is set
MT_SIGN_EBCDIC	Identifies how numeric DISPLAY items with included signs are interpreted: <ul style="list-style-type: none"> Y: Default. They are interpreted according to the EBCDIC convention. N: They are interpreted according to the ASCII convention.
MT_SORT_BY_EBCDIC	Identifies how record-sequential ASCII files are sorted: <ul style="list-style-type: none"> Y: Files are sorted in EBCDIC order. N: Default. Files are sorted in ASCII order.
MT_RUNB_SIGNAL_TO_TRAP	Lists all signals caused by running user application that BatchRT will handle. Values are separated by space, for example: MT_RUNB_SIGNAL_TO_TRAP="1 2 3 4 6 7 8 11 13 14 15"

Table 2-5 (Cont.) Oracle Tuxedo Application Runtime for Native JCL Batch Environment Variables (Optional)

Variable	Usage
MT_SYS_IO_REDIRECT	<p>Identifies whether SYSIN and SYSOUT are redirected for utilities that ARTCOBRUN runs.</p> <ul style="list-style-type: none"> • If SYSIN is set, the stdin for utility is redirect to file \${DD_SYSIN}. • If SYSOUT is set, the stdout and stderr for utility is redirect to file \${DD_SYSOUT}. • Both SYSIN and SYSOUT can be set at the same time, separated by comma, for example, "SYSIN, SYSOUT". <p>The default value is SYSOUT.</p>
MT_PROG_RC_ABORT	<p>Any return code greater than or equal to MT_PROG_RC_ABORT is considered as abort; any code less than MT_PROG_RC_ABORT is considered as commit.</p> <p>The default value is 1.</p>

2.3 Configuring Batch Runtime in MP Mode

Batch Runtime (EJR) will need to be specially configured so as to work well in MP mode if users want to either use EJR to run jobs, which may share resources (normally files), from different machines or configure a MP mode TuxJES domain and submit jobs from any node through the utility provided by TuxJES.

In the latter case, the job submitted from node A may be run by node B and the execution sequence is totally random. Similarly, these jobs submitted from different nodes may share resources.

This section clarifies the details of configuring Batch Runtime (EJR) to support MP mode.

1. All the resources should be put on a shared storage (NFS), which should have the same mount point on all machines in the domain, to ensure any file has the same path from the view of each node, because any job submitted from one machine may be run by another machine. For example, if users prefer to store all files under environment variable DATA described in above section, \${DATA} should point to the shared root directory where files are located and have the same value on all machines.
2. MT_ACC_FILEPATH should be located on shared storage (NFS), which should have same mount point on all machines in the domain, since the control files for file locking are put in this directory; in addition, users need to make sure AccLock and AccWait files under this directory can be read / written by the effective user of the process running the jobs
3. NLM (Network Lock Manager) needs to be enabled on the NFS server and all machines in the domain since some shared resources, which are located on NFS, need to be locked to prevent jobs from corrupting them. The configuration is not directly related to Batch Runtime but has close relationship in MP mode.
4. ARTJESADM server should be configured and started on each node in the MP domain to check, by other nodes, whether a job on this node is running or not. This is a part of the file lock mechanism in Batch Runtime. If either ARTJESADM server on one node dies abnormally or the node itself dies abnormally, the file lock owned by the job running on this node won't be released automatically; in this case, the utility artjescleanlock can be used to release the inactive file lock. For details of artjescleanlock, see [Using Tuxedo Job Enqueueing Service \(TuxJES\)](#).

2.4 Creating a Script

This section contains the following topics:

- [General Structure of a Script](#)
- [Script Example](#)
- [Defining and Using Symbols](#)
- [Creating a Step That Executes a Program](#)
- [Application Program Abend Execution](#)
- [Creating a Procedure](#)
- [Using a Procedure](#)
- [Modifying a Procedure at Execution Time](#)

2.4.1 General Structure of a Script

Oracle Tuxedo Application Runtime for Batch normalizes Korn shell script formats by proposing a script model where the different execution phases of a job are clearly identified.

Oracle Tuxedo Application Runtime for Batch scripts respect a specific format that allows the definition and the chaining of the different phases of the KSH (JOB).

Within Batch Runtime, a *phase* corresponds to an activity or a step on the source system.

A phase is identified by a label and delimited by the next phase.

At the end of each phase, the `JUMP_LABEL` variable is updated to give the label of the next phase to be executed.

In the following example, the last functional phase sets `JUMP_LABEL` to `JOBEND`: this label allows a normal termination of the job (exits from the phase loop).

The mandatory parts of the script (the beginning and end parts) are shown in bold and the functional part of the script (the middle part) in normal style as shown in the table below. The optional part of the script must contain the labels, branching and end of steps as described below. The items of the script to be modified are shown in italics.

Table 2-6 Script Structure

Script	Description
#!/usr/bin/ksh	-
m_JobBegin -j JOBNAME -s START -v 2.00	m_JobBegin is mandatory and must contain at least the following options: <ul style="list-style-type: none"> • -j: internal job name • -s: name of the first label to begin execution (usually should be START) • -v: Minimum version number of Batch Runtime required for this script (upward compatible).
while true ;do	The "while true; do" loop provides a mechanism to simulate the movement from one step to the next.
m_PhaseBegin	m_PhaseBegin enables parameters to be initialized at the beginning of a step.

Table 2-6 (Cont.) Script Structure

Script	Description
<code>case \${CURRENT_LABEL} in</code>	The case statement enables a branching to the current step.
<code>(START)</code>	The start label (used in the -s option of <code>m_JobBegin</code>)
<code>JUMP_LABEL=STEP1</code>	<code>JUMP_LABEL</code> is mandatory in all steps and gives the name of the next step.
<code>;;</code>	<code>;;</code> ends a step and are mandatory.
<code>(STEP1)</code>	A functional step begins with (LABEL); where LABEL is the name of the step.
<code>m_*</code> <code>m_*</code>	A typical step continues with a series of calls to Batch Runtime functions.
<code>JUMP_LABEL=STEP2</code>	There is always a branching to the next step (<code>JUMP_LABEL=</code>)
<code>;;</code>	And always the <code>;;</code> at the end of each step.
<code>(PENULTIMATESTEP)</code>	-
<code>m_*</code> <code>m_*</code>	The last functional step has the same format as the others, except...
<code>JUMP_LABEL=END_JOB</code> <code>;;</code>	For the label, which must point to <code>END_JOB</code> . The <code>_</code> is necessary, because the character is forbidden on z/OS.
<code>(END_JOB)</code> <code>break</code> <code>;;</code>	This step enables the processing loop to be broken.
<code>(*)</code> <code>m_RcSet \${MT_RC_ABORT:-S999}</code> <code>"Unknown label : \${</code> <code>{CURRENT_LABEL}"</code> <code>break</code> <code>;;</code> <code>esac</code>	This is a catch-all step that picks-up branching to unknown steps.
<code>m_PhaseEnd done</code>	<code>m_PhaseEnd</code> manages the end of a step including file management depending on disposition and return codes.
<code>m_JobEnd</code>	<code>m_JobEnd</code> manages the end of a job including clearing-up temporary files and returning completion code to job caller.

2.4.2 Script Example

Listing 2-1 Korn shell Script Example

```
#!/bin/ksh
#@(#)-----
#@(#) -
m_JobBegin -j METAW01D -s START -v 2.00 -c A
while true ;
do
m_PhaseBegin
case ${CURRENT_LABEL} in
(START)
```

```

# -----
# 1) 1st Step: DELVCUST
# Delete the existing file.
# 2) 2nd Step: DEFVCUST
# Allocates the Simple Sample Application VSAM customers file
# -----
#
# -Step 1: Delete...
JUMP_LABEL=DELVCUST
;;
(DELVCUST)
m_FileAssign -d OLD FDEL ${DATA}/METAW00.VSAM.CUSTOMER
m_FileDelete ${DD_FDEL}
m_RcSet 0
#
# -Step 2: Define...
JUMP_LABEL=DEFVCUST
;;
(DEFVCUST)
# IDCAMS DEFINE CLUSTER IDX
m_FileBuild -t IDX -r 266 -k 1+6 ${DATA}/METAW00.VSAM.CUSTOMER
JUMP_LABEL=END_JOB
;;
(ABORT)
break
;;
(END_JOB)
break
;;
(*)
m_RcSet ${MT_RC_ABORT} "Unknown label : ${JUMP_LABEL}"
break
;;
esac
m_PhaseEnd
done
m_JobEnd
#@ (#) -----

```

2.4.3 Defining and Using Symbols

Symbols are internal script variables that allow script statements to be easily modifiable. A value is assigned to a symbol through the `m_SymbolSet` function as shown in the listing below. To use a symbol, use the following syntax: `${symbol}`

Note:

The use of brackets (`[]`) instead of braces (`{}`) is to clearly distinguish symbols from standard Korn shell variables.

Listing 2-2 Symbol Use Examples

```
(STEP00)
m_SymbolSet VAR=40
JUMP_LABEL=STEP01
;;
(STEP01)
m_FileAssign -d SHR FILE01 ${DATA}/PJ01DDD.BT.QSAM.KBST00${VAR}
m_ProgramExec BAI001
```

2.4.4 Creating a Step That Executes a Program

A step (also called a phase) is generally a coherent set of calls to Batch Runtime functions that enables the execution of a functional (or technical) activity.

The most frequent steps are those that execute an application or utility program. These kind of steps are generally composed of one or several file assignment operations followed by the execution of the desired program. All the file assignments operations must precede the program execution operation shown in Listing below.

Listing 2-3 Application Program Execution Step Example

```
(STEPPR15)
m_FileAssign -d SHR INFIL ${DATA}/PJ01DDD.BT.QSAM.KBPRO099
m_FileAssign -d MOD OUTFIL ${DATA}/PJ01DDD.BT.QSAM.KBPRO001
m_OutputAssign -c "*" SYSOUT
m_FileAssign -i LOGIN
IN-STREAM DATA
_end
m_FileAssign -d MOD LOGOUT ${DATA}/PJ01DDD.BT.QSAM.KBPRO091
m_ProgramExec BPRAB001 "20071120"
JUMP_LABEL=END_JOB
;;
```

2.4.5 Application Program Abend Execution

ABEND routines, ILBOABN0, CEE3ABD and ART3ABD can be called from a running program to force it to abort and return the abend code to KSH script. For example, ILBOABN0 is supplied as both source and binary gnt file. It can be directly called by any user-defined COBOL program.

Listing 2-4 Application Program Abend Execution Example (KSH)

```
(STEPPR15)
m_ProgramExec USER
JUMP_LABEL=END_JOB
;;
```

Listing 2-5 USER.cbl Example

```
PROCEDURE DIVISION.
PROGRAM-BEGIN.
DISPLAY "USER: HELLO USER".
MOVE 2 TO RT-PARAM.
CALL "ILBOABN0" USING RT-PARAM.
```

```

DISPLAY "USER: CAN'T REACH HERE WHEN ILBOABN0 IS CALLED".
PROGRAM-DONE.
...

```

2.4.6 Creating a Procedure

Oracle Tuxedo Application Runtime for Batch offers a set of functions to define and use "procedures". These procedures follow generally the same principles as z/OS JCL procedures.

The advantages of procedures are:

- Write a set of tasks once and use it several times.
- Make this set of tasks dynamically modifiable.

Procedures can be of two types:

- **In-stream Procedures:** Included in the calling script, this kind of procedure can be used only in the current script.
- **External Procedures:** Coded in a separate source file, this kind of procedure can be used in multiple scripts.

The following topics describe how to create the above procedures:

- [Creating an In-Stream Procedure](#)
- [Creating an External Procedure](#)

2.4.6.1 Creating an In-Stream Procedure

Unlike the z/OS JCL convention, an in-stream procedure must be written after the end of the main JOB, that is: all the in-stream procedures belonging to a job must appear after the call to the function `m_JobEnd`.

An in-stream procedure in a Korn shell script always starts with a call to the `m_ProcBegin` function, followed by all the tasks composing the procedure and terminating with a call to the `m_ProcEnd` function. The following listing is an example:

Listing 2-6 In-stream Procedure Example

```

m_ProcBegin PROCA
JUMP_LABEL=STEPSA
;;
(STEPSA)
m_FileAssign -c "*" SYSPRINT
m_FileAssign -d SHR SYSUT1 ${DATA}/PJ01DDD.BT.DATA.PDSA/BIEAM00${SEQ}
m_FileAssign -d MOD SYSUT2 ${DATA}/PJ01DDD.BT.QSAM.KBIE0005
m_FileLoad ${DD_SYSUT1} ${DD_SYSUT2}
JUMP_LABEL=ENDPROC
;;
(ENDPROC)
m_ProcEnd

```

2.4.6.2 Creating an External Procedure

External procedures do not require the use of the `m_ProcBegin` and `m_ProcEnd` functions; simply code the tasks that are part of the procedure shown in the listing below.

In order to simplify the integration of a procedure's code with the calling job, always begin a procedure with:

```
JUMP_LABEL=FIRSTSTEP
;;
(FIRSTSTEP)
```

and end it with:

```
JUMP_LABEL=ENDPROC
;;
(ENDPROC)
```

Listing 2-7 External Procedure Example

```
JUMP_LABEL=PR2STEP1
;;
(PR2STEP1)
m_FileAssign -d SHR INFIL ${DATA}/PJ01DDD.BT.QSAM.KBPRI001
m_FileAssign -d MOD OUTFIL ${DATA}/PJ01DDD.BT.QSAM.KBPRO001
m_OutputAssign -c "*" SYSOUT
m_FileAssign -d SHR LOGIN ${DATA}/PJ01DDD.BT.SYSIN.SRC/BPRAS002
m_FileAssign -d MOD LOGOUT ${DATA}/PJ01DDD.BT.QSAM.KBPRO091
m_ProgramExec BPRAB002
JUMP_LABEL=ENDPROC
;;
(ENDPROC)
```

2.4.7 Using a Procedure

The use of a procedure inside a Korn shell script is made through a call to the `m_ProcInclude` function.

As described in [Script Execution Phases](#), during the Conversion Phase, a Korn shell script is expanded by including the procedure's code each time a call to the `m_ProcInclude` function is encountered. It is necessary that after this operation, the resulting expanded Korn shell script still respects the rules of the general structure of a script as defined in the [General Structure of a Script](#).

A procedure, either in-stream or external, can be used in any place inside a calling job provided that the above principals are respected shown in Listing below.

Listing 2-8 Call to the `m_ProcInclude` Function Example

```
...
(STEPPR14)
m_ProcInclude BPRAP009
JUMP_LABEL=STEPPR15
...
```

2.4.8 Modifying a Procedure at Execution Time

The execution of the tasks defined in a procedure can be modified in two different ways:

- Modifying symbols and/or parameters
- Symbols can be used inside a procedure and the values of these symbols can be specified when calling the procedure.

Listing 2-9 Defining Procedure Example

```
m_ProcBegin PROCE
JUMP_LABEL=STEPE
;;
(STEPE)
m_FileAssign -d SHR SYSUT1 ${DATA}/DATA.IN.PDS/DTS${SEQ}
m_FileAssign -d MOD SYSUT2 ${DATA}/DATA.OUT.PDS/DTS${SEQ}
m_FileLoad ${DD_SYSUT1} ${DD_SYSUT2}
JUMP_LABEL=ENDPROC
;;
(ENDPROC)
m_ProcEnd
```

Listing 2-10 Calling Procedure Example

```
(COPIERE)
m_ProcInclude PROCE SEQ="1"
JUMP_LABEL=COPIERF
;;
```

- [Using Overrides for File Assignments](#)

2.4.8.1 Using Overrides for File Assignments

As specified in [Best Practices](#), this way of coding procedures is provided mainly for supporting Korn shell scripts resulting from z/OS JCL translation and it is not recommended for Korn shell scripts newly written for the target platform.

The overriding of a file assignment is made using the `m_FileOverride` function that specifies a replacement for the assignment present in the procedure. The call to the `m_FileOverride` function must follow the call to the procedure in the calling script.

The following Listing shows how to replace the assignment of the logical file `SYSUT1` using the `m_FileOverride` function.

Listing 2-11 `m_FileOverride` Function Example

```
m_ProcBegin PROCE
JUMP_LABEL=STEPE
;;
(STEPE)
m_FileAssign -d SHR SYSUT1 ${DATA}/DATA.IN.PDS/DTS${SEQ}
m_FileAssign -d MOD SYSUT2 ${DATA}/DATA.OUT.PDS/DTS${SEQ}
m_FileLoad ${DD_SYSUT1} ${DD_SYSUT2}
JUMP_LABEL=ENDPROC
;;
(ENDPROC)
m_ProcEnd
```

Listing 2-12 m_FileOverride Procedure Call:

```
(COPIERE)
m_ProcInclude PROCE SEQ="1"
m_FileOverride -i -s STEPE SYSUT1
Overriding test data
_end
JUMP_LABEL=COPIERF
;;
```

2.5 Controlling Script Behavior

This section contains the following topics:

- [Conditioning the Execution of a Step](#)
- [Controlling the Execution Flow](#)
- [Changing Default Error Messages](#)

2.5.1 Conditioning the Execution of a Step

This section contains the following topics:

- [Using m_CondIf, m_CondElse, and m_CondEndif](#)
- [Using m_CondExec](#)

2.5.1.1 Using m_CondIf, m_CondElse, and m_CondEndif

The `m_CondIf`, `m_CondElse` and `m_CondEndif` functions can be used to condition the execution of one or several steps in a script. The behavior is similar to the z/OS JCL statement constructs `IF`, `THEN`, `ELSE` and `ENDIF`.

The `m_CondIf` function must always have a relational expression as a parameter as shown in the listing below. These functions can be nested up to 15 times.

Listing 2-13 m_CondIf, m_CondElse, and m_CondEndif Example

```
...
(STEPIF01)
m_FileAssign -d SHR INFIL ${DATA}/PJ01DDD.BT.QSAM.KBIF000
m_FileAssign -d MOD OUTFIL ${DATA}/PJ01DDD.BT.QSAM.KBIF001
m_ProgramExec BAX001
m_CondIf "STEPIF01.RC,LT,5"
JUMP_LABEL=STEPIF02
;;
(STEPIF02)
m_FileAssign -d SHR INFIL ${DATA}/PJ01DDD.BT.QSAM.KBIF001
m_FileAssign -d MOD OUTFIL ${DATA}/PJ01DDD.BT.QSAM.KBIF002
m_ProgramExec BAX002
m_CondElse
JUMP_LABEL=STEPIF03
;;
(STEPIF03)
m_FileAssign -d SHR INFIL ${DATA}/PJ01DDD.BT.QSAM.KBIF000
```

```
m_FileAssign -d MOD OUTFIL ${DATA}/PJ01DDD.BT.QSAM.KBIF003
m_ProgramExec BAX003
m_CondEndif
```

2.5.1.2 Using m_CondExec

The `m_CondExec` function is used to condition the execution of a step. The `m_CondExec` must have at least one condition as a parameter and can have several conditions at the same time. In case of multiple conditions, the step is executed only if all the conditions are satisfied.

A condition can be of three forms:

- Relational expression testing previous return codes:
`m_CondExec 4,LT,STEPEC01`
- EVEN: Indicates that the step is to be executed even if a previous step terminated abnormally:
`m_CondExec EVEN`
- ONLY: Indicates that the step is to be executed only if a previous step terminated abnormally:
`m_CondExec ONLY`

The `m_CondExec` function must be the first function to be called inside the concerned step as shown in the Listing below:

Listing 2-14 m_CondExec Example with Multiple Conditions

```
...
(STEPEC01)
m_FileAssign -d SHR INFIL ${DATA}/PJ01DDD.BT.QSAM.KBIF000
m_FileAssign -d MOD OUTFIL ${DATA}/PJ01DDD.BT.QSAM.KBIF001
m_ProgramExec BACC01
JUMP_LABEL=STEPEC02
;;
(STEPEC02)
m_FileAssign -d SHR INFIL ${DATA}/PJ01DDD.BT.QSAM.KBIF001
m_FileAssign -d MOD OUTFIL ${DATA}/PJ01DDD.BT.QSAM.KBIF002
m_ProgramExec BACC02
JUMP_LABEL=STEPEC03
;;
(STEPEC03)
m_CondExec 4,LT,STEPEC01 8,GT,STEPEC02 EVEN
m_FileAssign -d SHR INFIL ${DATA}/PJ01DDD.BT.QSAM.KBIF000
m_FileAssign -d MOD OUTFIL ${DATA}/PJ01DDD.BT.QSAM.KBIF003
```

2.5.2 Controlling the Execution Flow

The script's execution flow is determined, and can be controlled, in the following ways:

- The start label specified by the `m_JobBegin` function: this label is usually the first label in the script, but can be changed to any label present in the script if the user wants to start the script execution from a specific step.
- The value assigned to the `JUMP_LABEL` variable in each step: this assignment is mandatory in each step, but its value is not necessarily the label of the following step.

- The usage of the `m_CondExec`, `m_CondIf`, `m_CondElse` and `m_CondEndif` functions: see [Conditioning the Execution of a Step](#)
- The return codes and abnormal ends of steps.

2.5.3 Changing Default Error Messages

If Batch Runtime administrator wishes to change the default messages (to change the language for example), this can be done through a configuration file whose path is specified by the environment variable: `MT_DISPLAY_MESSAGE_FILE`.

This file is a CSV (comma separated values) file with a semicolon as a separator. Each record in this file describes a certain message and is composed of six fields:

1. Message identifier.
2. Functions that can display the message (can be a generic name using '*').
3. Level of display.
4. Destination of display.
5. Reserved for future use.
6. Message to be displayed.

2.6 Different Behaviors from z/OS

On z/OS, before one job is executed, JES checks its syntax. If any error is found, JES reports it and runs nothing of the job. For example, if there is a JCL statement applying “NEW” on generation(0) of a GDG, because NEW is not allowed to be applied to existing files, JES reports this error and does not run the job.

However, in ART for Batch, JCL job is converted to ksh job by Oracle Tuxedo ART Workbench at first, and ART for Batch only checks ksh script syntax in the converted ksh job. Grammar errors, if any, are detected when this statement runs, resulting in the fact that statements after the wrong statement are not executed, but statements before it are executed without being affected.

2.7 Using Files

This section contains the following topics:

- [Creating a File Definition](#)
- [Assigning and Using Files](#)
- [Concurrent File Accessing Control](#)
- [Using Generation Data Group \(GDG\)](#)
- [Using an In-Stream File](#)
- [Using a Set of Concatenated Files](#)
- [Using an External “sysin”](#)
- [Deleting a File](#)
- [RDB Files](#)
- [Using an RDBMS Connection](#)

2.7.1 Creating a File Definition

Files are created using the `m_FileBuild` or the `m_FileAssign` function.

Four file organizations are supported:

- Sequential file
- Line sequential file
- Relative file
- Indexed file

You must specify the file organization for the file being created. For indexed files, the length and the primary key specifications must also be mentioned.

- [m_FileBuild Examples](#)
- [m_FileAssign Examples](#)

2.7.1.1 m_FileBuild Examples

- Definition of a line sequential file

```
m_FileBuild -t LSEQ ${DATA}/PJ01DDD.BT.VSAM.ESDS.KBIDO004
```
- Definition of an indexed file with a record length of 266 bytes and a key starting at the first bytes and having a size of 6 bytes.

```
m_FileBuild -t IDX -r 266 -k 1+6 ${DATA}/METAW00.VSAM.CUSTOMER
```

2.7.1.2 m_FileAssign Examples

- Definition of a new sequential file with a record length of 80 bytes.

```
m_FileAssign -d NEW -t SEQ -r 80 ${DATA}/PJ01DDD.BT.VSAM.ESDS.KBIDO005
```

2.7.2 Assigning and Using Files

When using Batch Runtime, a file can be used either by a Batch Runtime function (for example: `m_FileSort`, `m_FileRename` etc.) or by a program, such as a COBOL program.

In both cases, before being used, a file must first be assigned. Files are assigned using the `m_FileAssign` function that:

- Specifies the DISP mode (Read or Write)
- Specifies if the file is a generation file
- Defines an environment variable linking the logical name of the file (IFN) with the real path to the file (EFN).

The environment variable defined via the `m_FileAssign` function is named: `DD_IFN`. This naming convention is due to the fact that it is the one used by Micro Focus COBOL to map internal file names to external file names.

Once a file is assigned, it can be passed as an argument to any of Batch Runtime functions handling files by using the `${DD_IFN}` variable.

For COBOL programs, the link is made implicitly by Micro Focus COBOL. COBOL-IT is compatible with Micro Focus COBOL regarding DD assignment.

Listing 2-15 Example of File Assignment

```
(STEPCP01)
m_FileAssign -d SHR INFIL ${DATA}/PJ01DDD.BT.QSAM.KBIDI001
m_FileAssign -d SHR OUTFIL ${DATA}/PJ01DDD.BT.VSAM.KBIDU001
m_FileLoad ${DD_INFIL} ${DD_OUTFIL}
...
```

Listing 2-16 Example of Using a File by a COBOL Program

```
(STEPCL1)
m_FileAssign -d OLD INFIL ${DATA}/PJ01DDD.BT.QSAM.KBIFI091
m_FileAssign -d MOD OUTFIL ${DATA}/PJ01DDD.BT.QSAM.KBIF091
m_ProgramExec BIFAB090
...
```

- [About DD DISP=MOD](#)

2.7.2.1 About DD DISP=MOD

Enhance ART/BatchRT to keep consistency with mainframe for DISP=MOD. That is, make the behavior of DISP=MOD on the target operation system of ART/BatchRT to be same with mainframe. Currently, BatchRT is depending on below 2 kinds of COBOL compile/runtime environment:

**Note:**

For VSAM data set DISP=MOD is always treated as DISP=OLD (file exist), and DISP=NEW(file doesn't exist) has been same with z/OS.

- [Micro Focus COBOL](#)
- [COBOL-IT](#)

2.7.2.1.1 Micro Focus COBOL

For Micro Focus COBOL, one new file handler (ARTEXTFH.gnt) is added to BatchRT. In order to have the correct behavior of DISP=MOD, user COBOL programs must be compiled with this file handler using the following option:

```
CALLFH ("ARTEXTFH")
```

If the compile option is not specified, then the write operation with the mode "open output", in the COBOL program, will erase the existing file contents. This is unexpected.

It is suggested to always add this compiler option when you compile COBOL programs. The following table lists the behavior of API which support DDN.

Table 2-7 Micro Focus COBOL DISP=MOD Behavior

API	DISP=MOD is allowed?		Read output file is allowed?	Result of write output file
	INPUT	OUTPUT		
-	INPUT	OUTPUT	-	-
m_FileRepro	YES	YES	NO such requirement	Appended
m_FilePrint	YES	YES	NO such requirement	Appended
m_FileSort	YES	YES	NO such requirement	Appended
m_ProgramExec: Other Program	YES	YES	YES	Appended
m_ProgramExec: Other Program	YES	YES	YES	Written but erase existing contents
All other API which support DDN	YES	YES	NO such requirement	NO such requirement

INPUT means INPUT file, only read operation will occur for INPUT file. Specify DISP=MOD is not reasonable for INPUT file, because no data will be written to INPUT file, but it's allowed, For INPUT file, DISP=MOD always act as DISP=OLD.

OUTPUT means OUTPUT file, read and write operation occur for OUTPUT file. All the data written to OUTPUT file will be appended to the original file regardless of open mode in COBOL program: "open output" or "open extend."

2.7.2.1.2 COBOL-IT

For COBOL-IT, there is no File Handle level support for DISP=MOD (like Micro Focus COBOL). So there is no special requirement for compiling COBOL program. The following table lists the behavior of API which support DDN.

Table 2-8 Micro Focus COBOL DISP=MOD Behavior

API	DISP=MOD is allowed?		Read output file is allowed?	Result of write output file
	INPUT	OUTPUT		
-	INPUT	OUTPUT	-	-
m_FileRepro	NO	YES	NO such requirement	Appended
m_FilePrint	NO	YES	NO such requirement	Appended
m_FileSort	NO	YES	NO such requirement	Appended
m_ProgramExec: COBOL Program	NO	YES	YES	Appended
m_ProgramExec: Other Program	NO	YES	YES	Written but erase existing contents
All other API which support DDN	NO	YES	NO such requirement	NO such requirement

INPUT means INPUT file, only read operation will occur for INPUT file. Specify DISP=MOD to INPUT file is not reasonable, and it's not allowed in COBOL-IT. if one INPUT file is assigned as DISP=MOD, its contents can't be read.

OUTPUT means OUTPUT file, read and write operation occur for OUTPUT file. All the data written to OUTPUT file will be appended to the original file regardless of open mode in COBOL program: "open output" or "open extend."

2.7.3 Concurrent File Accessing Control

Batch Runtime provides a lock mechanism to prevent one file from being written simultaneously in two jobs.

To enable the concurrent file access control, do the following:

1. Use environment variable `MT_ACC_FILEPATH` to specify a directory for the lock files required by concurrent access control mechanism.
2. Create two empty files, `AccLock` and `AccWait`, under the directory specified in step 1. Make sure the effective user executing jobs has read/write permission to these two files.

Note:

- The file names of `AccLock` and `AccWait` are case sensitive.
- When accessing generation files, a GDG rather than a generation file is locked. That is, a GDG is locked as a whole.
- Following two lines in `ejr/CONF/BatchRT.conf` should be commented out:
 `${MT_ACC_FILEPATH}/AccLock`
 `${MT_ACC_FILEPATH}/AccWait`

2.7.4 Using Generation Data Group (GDG)

Oracle Tuxedo Application Runtime for Batch allows you to manage Generation Data Group (GDG) files either based on file or based on database (DB). In file-based management way, Batch Runtime manages GDG files in separate "*.gens" files, and one "*.gens" corresponds to one GDG file. In DB-based management way, ART for Batch allows users to manage GDG information in Oracle database or DB2 database.

- [GDG Management Functionalities](#)
- [File-Based Management](#)
- [DB-Based Management](#)
- [Support for Data Control Block \(DCB\)](#)

2.7.4.1 GDG Management Functionalities

In order to emulate the notion of generation files present on the z/OS mainframe which is not a UNIX standard, Batch Runtime provides a set of functions to manage this type of file. These functions are available to both file-based management and DB-based management.

Note:

Copying or Renaming GDG is not supported.

- Defining and/or Redefining a GDG
- Adding Generation Files in a GDG
- Referring an Existing Generation Files in a GDG
- Deleting Generation Files in a GDG
- Deleting a GDG
- Cataloging a GDG
- Committing a GDG

2.7.4.1.1 Defining and/or Redefining a GDG

It is required to define a GDG before using it.

A GDG file is defined and/or redefined through `m_GenDefine`. The operation of defining or redefining a GDG is committed immediately and cannot be rolled back.

As shown in Listing below, the first line defines a GDG and sets its maximum generations to 15, the second line redefines the same GDG maximum generations to 30, the third line defines a GDG without specifying "-s" option (its maximum generations is set to 9999), the fourth line defines a GDG implicitly and sets its maximum generations to 9999, the fifth line defines a GDG use model file `$(DATA)/FILE`, which can be either a GDG file or a normal file.

Listing 2-17 Example of Defining and Redefining GDG Files

```
m_GenDefine -s 15 ${DATA}/PJ01DDD.BT.FILE1
m_GenDefine -s 30 -r ${DATA}/PJ01DDD.BT.FILE1
m_GenDefine ${DATA}/PJ01DDD.BT.FILE2
m_FileAssign -d NEW,CATLG -g +1 SYSUT2 ${DATA}/PJ01DDD.BT.FILE3
m_FileAssign -d NEW,CATLG -g +1 -S $(DATA)/FILE FILE1 $(DATA)/GDG
```

2.7.4.1.2 Adding Generation Files in a GDG

To add a new generation file (GDS) into a GDG, call `m_FileAssign` with "-d NEW/MOD,..." and "-g +n" parameters. GDS file types can be only LSEQ or SEQ.

There are four key points to add generation files in a GDG.

- Multiple generation files (GDS) can be added in one job or step discontinuously and disorderedly. See Listing 2-18 for an example.
- One generation number (GenNum) can be added only one time in a job. Listing 2-19 shows an incorrect usage.
- The filename of a newly created GDS is generated by the generation number specified in `m_FileAssign` in the format of `<current GDS number> + <GenNum>`. See Listing 2-20 for an example.
- In a job, if multiple generation files (GDS) are newly created, the GDS with the maximum RGN becomes the *current* GDS after the job finishes. See Listing 2-21 for an example.

Four examples as below elaborate those key points individually.

Listing 2-18 Example of Adding Multiple Generation Files Discontinuously and Disorderedly

```
(STEP1)
m_FileAssign -d NEW,KEEP,KEEP -g +1 SYSUT1 "$DATA/GDG1"
m_FileAssign -d MOD,KEEP,KEEP -g +5 SYSUT2 "$DATA/GDG1"
(STEP2)
m_FileAssign -d NEW,KEEP,KEEP -g +9 SYSUT1 "$DATA/GDG1"
m_FileAssign -d NEW,KEEP,KEEP -g +2 SYSUT2 "$DATA/GDG1"
```

The above example adds the following GDS files to GDG.

```
$DATA/GDG1.Gen.0001
$DATA/GDG1.Gen.0002
$DATA/GDG1.Gen.0005
$DATA/GDG1.Gen.0009
```

Listing 2-19 Example of Adding One Generation Number Multiple Times in a Job (Incorrect Usage)

```
(STEP1)
m_FileAssign -d NEW,KEEP,KEEP -g +1 SYSUT1 "$DATA/GDG1"
m_FileAssign -d NEW,KEEP,KEEP -g +5 SYSUT2 "$DATA/GDG1"
(STEP2)
m_FileAssign -d NEW,KEEP,KEEP -g +4 SYSUT1 "$DATA/GDG1"
m_FileAssign -d NEW,KEEP,KEEP -g +5 SYSUT2 "$DATA/GDG1"
```

The above example shows an incorrect usage, where generation number (+5) is added two times.

Listing 2-20 Example of Listing GDS Filenames

```
m_FileAssign -d NEW,KEEP,KEEP -g +1 SYSUT1 "$DATA/GDG1"
m_FileAssign -d MOD,KEEP,KEEP -g +5 SYSUT2 "$DATA/GDG1"
```

In the above example, suppose \$DATA/GDG1 has three GDS numbered as 1, 2, and 4, respectively. The corresponding GDS files are listed as below:

```
$DATA/GDG1.Gen.0001
$DATA/GDG1.Gen.0002
$DATA/GDG1.Gen.0004
```

After the above job runs, \$DATA/GDG1 has five GDS numbered as 1, 2, 4, 5, and 9, respectively. The corresponding GDS files are listed as below.

```
$DATA/GDG1.Gen.0001
$DATA/GDG1.Gen.0002
$DATA/GDG1.Gen.0004
$DATA/GDG1.Gen.0005
$DATA/GDG1.Gen.0009
```

Listing 2-21 Example of Defining the Current GDS

```
(STEP1)
m_FileAssign -d NEW,KEEP,KEEP -g +1 SYSUT1 "$DATA/GDG1"
m_FileAssign -d MOD,KEEP,KEEP -g +5 SYSUT2 "$DATA/GDG1"
(STEP2)
m_FileAssign -d NEW,KEEP,KEEP -g +2 SYSUT3 "$DATA/GDG1"
```

In the above example, the GDS whose RGN equals +5 becomes the *current* GDS, meaning its RGN becomes 0 after job finishes successfully.

2.7.4.1.3 Referring an Existing Generation Files in a GDG

To refer to an existing generation file (GDS) in a GDG, call `m_FileAssign` "-d OLD/SHR/MOD,..." and "-g 0", "-g all" or "-g -n" parameters. "-g 0" refers to the current generation, "-g all" refers to all generation files, "-g -n" refers to the generation file which is the nth generation counting backward from the current generation (as 0 generation).

When using relative generation number (RGN) to reference a GDS, note that the "relative generation number" means "relative position with the newest GDS whose generation number is 0".

For example, if GDG1 contains six GDS numbered as 1, 4, 6, 7, 9, and 10, respectively, the mapping of GN and RGN is listed as below:

GN	1	4	6	7	9	10
RGN	-5	-4	-3	-2	-1	0

In the following job, use `RGN=-1` to reference GDS whose GN equals 9 and use `RGN=-4` to reference GDS whose GN equals 4.

Listing 2-22 Example of Referencing Existing Generation Files

```
(STEP1)
m_FileAssign -d SHR,KEEP,KEEP -g -1 SYSUT1 "$DATA/GDG1"
m_FileAssign -d SHR,KEEP,KEEP -g -4 SYSUT2 "$DATA/GDG1"
```

If "DELETE" is specified in the `DISPOSITION` field of `m_FileAssign`, the corresponding GDS will be deleted after the current step finishes, resulting in a change of mapping between GN and RGN. The changed mapping will be visible in the next step.

For example, if GDG1 contains six GDS numbered as 1, 4, 6, 7, 9, and 10, respectively, the mapping of GN and RGN is listed as below.

GN	1	4	6	7	9	10
RGN	-5	-4	-3	-2	-1	0

In the following job, use `RGN=-1` to reference GDS whose GN equals 9 and use `RGN=-4` to reference GDS whose GN equals 4.

You can run a job as below.

Listing 2-23 Example of Referencing Existing Generation Files with DELETE Specified

```
(STEP1)
m_FileAssign -d OLD,DELETE,DELETE -g -1 SYSUT1 "$DATA/GDG1"
m_FileAssign -d OLD,DELETE,DELETE -g -4 SYSUT2 "$DATA/GDG1"
(STEP2)
m_FileAssign -d OLD,DELETE,DELETE -g -1 SYSUT1 "$DATA/GDG1"
m_FileAssign -d OLD,DELETE,DELETE -g -2 SYSUT2 "$DATA/GDG1"
```

In the above example, after STEP1 finishes, the mapping of GN and RGN becomes the one as below.

GN	1	6	7	10
RGN	-3	-2	-1	0

In STEP2, the GDS pointed by SYSUT1 (the GDS whose GN is 7) and the GDS pointed by SYSUT2 (the GDS whose GN is 6) are deleted.

After STEP2 finishes, the mapping of GN and RGN becomes the one as below:

GN	1	10
RGN	-1	0

2.7.4.1.4 Deleting Generation Files in a GDG

ART for Batch supports you to delete generation files, newly added or current existing, through the disposition of DD specified for m_FileAssign.

- Deleting Newly Added GDS (See Listing 2-24 for an example)
- Deleting Existing GDS (See Listing 2-25 for an example)

Listing 2-24 Deleting Newly Added GDS

```
(STEP1)
m_FileAssign -d NEW,DELETE,DELETE -g +1 SYSUT1 "$DATA/GDG1"
m_FileAssign -d NEW,DELETE,DELETE -g +5 SYSUT2 "$DATA/GDG1"
(STEP2)
m_FileAssign -d NEW,DELETE,DELETE -g +1 SYSUT1 "$DATA/GDG1"
m_FileAssign -d NEW,DELETE,DELETE -g +5 SYSUT2 "$DATA/GDG1"
```

In the above example, eventually, no GDS is added to GDG1.

Listing 2-25 Deleting Existing GDS

```
(STEP1)
m_FileAssign -d NEW,DELETE,DELETE -g -1 SYSUT1 "$DATA/GDG1"
m_FileAssign -d NEW,DELETE,DELETE -g -3 SYSUT2 "$DATA/GDG1"
(STEP2)
m_FileAssign -d NEW,DELETE,DELETE -g -1 SYSUT3 "$DATA/GDG1"
m_FileAssign -d NEW,DELETE,DELETE -g -3 SYSUT4 "$DATA/GDG1"
```

In the above example, GDG1 has six GDS numbered as 1, 4, 6, 7, 9, and 10, respectively. The GDS pointed by SYSUT1 (the GDS whose GN is 9), by SYSUT2 (the GDS whose GN is 6), by

SYSUT3 (the GDS file whose GN is 7), and by SYSUT4 (the GDS file whose GN is 1) are deleted.

 **Note:**

Removing a GDG's all GDS does not remove the GDG itself, but just result in the fact that the GDG contains 0 GDS.

2.7.4.1.5 Deleting a GDG

You can delete a GDG as a whole by calling `m_FileDelete` with the GDG base name, as shown in the listing below. In this way, all the GDG's GDS will be deleted accordingly. The operation of deleting GDG is committed immediately and cannot be rolled back.

Listing 2-26 Deleting a GDG

```
m_FileDelete ${DATA}/PJ01DDD.BT.GDG
```

2.7.4.1.6 Cataloging a GDG

Only GDG base can be cataloged; its GDS cannot be cataloged individually.

It is required to enable "file catalog" function in ART for Batch to catalog a GDG. Additionally, in catalog mode, the parameter `[-v volume]` specified in `m_FileAssign` is ignored.

 **Note:**

A GDG will be cataloged once it is defined.

2.7.4.1.7 Committing a GDG

All GDG having changes in the current step will be committed no matter if the current step successfully finishes.

Committing a GDG updates the information in GDG management system, such as Oracle DataBase or file (`*.gens`), and commits the temporary generation files; however, committing a GDG does not change the mapping relationship between GN and RGN, meaning, in one step of a job, a RGN always references to the same GDS.

For example, `GDG1` has six GDS numbered as 1, 4, 6, 7, 9, and 10, respectively.

Listing 2-27 Example of Committing a GDG

```
(STEP1)
m_FileAssign -d NEW,KEEP,KEEP -g +1 SYSUT1 "$DATA/GDG1"
m_FileAssign -d NEW,KEEP,KEEP -g +2 SYSUT2 "$DATA/GDG1"
m_FileAssign -d NEW,KEEP,KEEP -g -1 SYSUT3 "$DATA/GDG1"
(STEP2)
m_FileAssign -d NEW,KEEP,KEEP -g -1 SYSUT4 "$DATA/GDG1"
```

In STEP1, the mapping of GN and RGN (both in job and in GDG management system) becomes the one as below. SYSUT3 references to the GDS whose GN is 9.

GN	1	4	6	7	9	10	11	12
RGN	-5	-4	-3	-2	-1	0	1	2

In STEP2, the mapping of GN and RGN in GDG management system becomes the one as below.

GN	1	4	6	7	9	10	11	12
RGN	-7	-6	-5	-4	-3	-2	-1	0

However, the mapping of GN and RGN in the current running job is not changed; in the below example, SYSUT4 stills references to the GDS whose GN is 9 rather than the GDS whose GN is 11.

GN	1	4	6	7	9	10	11	12
RGN	-5	-4	-3	-2	-1	0	1	2

2.7.4.2 File-Based Management

This section contains the following topics:

- [Configuration](#)
- [Concurrency Control and Authorization](#)

2.7.4.2.1 Configuration

`MT_GENERATION` variable specifies the way of managing GDG files. To manage GDG in `*.gens` files, you need to set the value to `GENERATION_FILE`.

2.7.4.2.2 Concurrency Control and Authorization

In file-based GDG management mechanism, one GDG file can only be accessed by one job at any time, that is, a single GDG cannot be accessed by multiple jobs simultaneously. To access a GDG file, the file lock must be acquired by the existing internal function `mi_FileConcurrentAccessReservation`. File-based GDG management mechanism uses a file `*.gens` (`*` represents the GDG base name) to control concurrency and authorization. User access checking depends on whether the `*.gens` file can be accessed or not.

2.7.4.3 DB-Based Management

For DB-based management, Oracle Database and DB2 database are supported.



Note:

To enable this function, `MT_GENERATION` must be set to `GENERATION_FILE_DB`, `MT_DB` must be set to `DB_ORACLE` or `DB_DB2LUW` (or set `MT_META_DB` to `DB_ORACLE` or `DB_DB2LUW`), and `MT_GDG_DB_ACCESS` must be set to valid database connection string to access Oracle Database or DB2 database.

- [Database Tables](#)

- [Generation File Naming Rule](#)
- [Configuration Variables](#)
- [External Shell Scripts](#)
- [Concurrency Control and Authorization](#)
- [Exception Handling](#)

2.7.4.3.1 Database Tables

The following table shows the general defines for each GDG managed by Batch Runtime. In this table, each row represents a GDG. All GDG files share a single GDG_DETAIL table.

Table 2-9 GDG_DEFINE

Name	Type	Description
GDG_BASE_NAME	VARCHAR(1024)	Full path name of GDG. It cannot contain only a relative path relative to a single repository. The length of GDG_BASE_NAME is limited to 1024, i.e. the minimum of PATH_MAX on different UNIX platforms.
GDG_MAX_GEN	INT	Maximum number of generation files. It contains the upper limit of generations specified by -s option. -s option can be set in the range of 1-9999.
GDG_CUR_GEN	INT	GDG current generation number
Primary Key: GDG_BASE_NAME		

The following table shows the detailed information of all the GDG generation files. In this table, each row represents a generation file of a GDG.

Table 2-10 GDG_DETAIL

Name	Type	Description
GDG_BASE_NAME	VARCHAR(1024)	Full path of the GDG principal name.
GDG_REL_NUM	INT	Relative generation number of a generation file.
GDG_ABS_NUM	INT	Absolute generation number of a generation file.
GDG_JOB_ID	VARCHAR(8)	The ID of the job that creates the file.
GDG_JOB_NAME	VARCHAR(32)	The name of the job that creates the file.
GDG_STEP_NAME	VARCHAR(32)	The name of the step that creates the file.
GDG_CRE_TIME	TIMESTAMP	The timestamp when the file is created.
Primary Key: GDG_BASE_NAME+GDG_ABS_NUM		

GDG_FILE_NAME (the physical generation file name) is not stored in table GDG_DETAIL since it can be constructed from GDG_BASE_NAME in GDG_DEFINE and GDG_ABS_NUM in GDG_DETAIL.

**Note:**

To back up GDG information, you need to back up two database tables: `GDG_DEFINE` and `GDG_DETAIL`.

2.7.4.3.2 Generation File Naming Rule

The following table shows the rule of generation file name:

Table 2-11 Generation File Naming Rule

Condition	File Name	Description
<code>GDG_REL_NUM > 0</code>	<code>\${GDG_BASE_NAME}.Gen.\${GDG_ABS_NUM}.tmp</code>	Uncommitted
<code>GDG_REL_NUM <= 0</code>	<code>\${GDG_BASE_NAME}.Gen.\${GDG_ABS_NUM}</code>	Committed

2.7.4.3.3 Configuration Variables

`MT_GENERATION`

This variable specifies the way of managing GDG files. To manage GDG files in database, you need to set the value to `GENERATION_FILE_DB` and configure `MT_GDG_DB_ACCESS` appropriately.

`MT_GDG_DB_ACCESS`

This variable is used along with `MT_GENERATION` when it is set to `GENERATION_FILE_DB`, and must be set with the valid database login account. For accessing Oracle DB, it should be specified in the format of `userid/password@sid`, for example, `scott/password@orcl`.

`MT_GDG_DB_BUNCH_OPERATION`

Used along with `MT_GENERATION` when set to `GENERATION_FILE_DB`. It indicates how to commit GDG changes to database during the commit phase. If configured to "Y", the GDG changes are committed using a single database access. If configured to "N", the GDG changes are committed using one or more database accesses.

2.7.4.3.4 External Shell Scripts

You can use the two external shell scripts to create and drop the new database table automatically.

CreateTableGDG.sh

Description

Creates table `GDG_DEFINE` and `GDG_DETAIL` in database

Usage

```
CreateTableGDG.sh <DB_LOGIN_PARAMETER>
```

Sample

```
CreateTableGDG.sh scott/password@orcl
```

DropTableGDG.sh

Description

Drops table `GDG_DEFINE` and `GDG_DETAIL` from database.

Usage

```
DropTableGDG.sh <DB_LOGIN_ PARAMETER>
```

Sample

```
DropTableGDG.sh scott/password@orcl
```

2.7.4.3.5 Concurrency Control and Authorization

DB-based GDG management mechanism maintains the same concurrency control behavior as File-based GDG management mechanism, but has a different `*.ACS` (* represents the GDG base name) file format. In DB-based GDG management mechanism, you don't need to lock the tables mentioned in [Database Tables](#) as any job that accesses the rows corresponding to a GDG must firstly acquire the file lock of the GDG. That is to say, there is no need to perform concurrency control in the database access level. You cannot access database if you don't have access permission (read or write) to the corresponding `*.ACS` file. If you need to modify a GDG file, you must have write permissions to the generation files and the directory holding the generation files, and `MT_GDG_DB_ACCESS` must be configured correctly to have appropriate permissions to the tables mentioned in [Database Tables](#).

You can only copy DB-based GDG management description entirely and replace the file name.

2.7.4.3.6 Exception Handling

There are four kinds of information in DB-based GDG management mechanism:

- `GDG_DEFINE`
- `*.ACS` file
- `GDG_DETAIL`
- Physical file on disk

These information should be kept consistently for a GDG file. Batch Runtime checks the consistency from `GDG_DEFINE` to Physical files when a GDG file is accessed the first time in a job. If exceptions happen and result in inconsistency among these information, Batch Runtime terminates the current job and reports error.

This behavior is different from the existing file-based mechanism, which does not check the consistency but only reports exceptions encountered in the process.

2.7.4.4 Support for Data Control Block (DCB)

Both file-based GDG and DB-based GDG support Data Control Block (DCB).

- [Defining .dcb File](#)
- [Creating .dcb file](#)
- [Deleting .dcb file](#)

2.7.4.4.1 Defining .dcb File

`.dcb` file can have two values: `"-t <file type>"` and `"-r <record length>"`.

```
-t <file type>
```

-t <file type> must be LSEQ or SEQ in `m_FileAssign` to create the first generation file. If you don't specify any file type in `job ksh` file, LSEQ will be used by default.

-r <record length>

For SEQ file, the value is mandatory and must be a number or "number1-number2".

For LSEQ file, the value is optional. Once set, this value must be a number or "number1-number2".

Note:

If a GDG is created by `m_GenDefine` rather than `m_FileAssign`, `.dcb` file will not exist until the first generation file is created by `m_FileAssign -g +1`. Once `.dcb` file is created, its contents will not be changed by any other `m_FileAssign` statement afterwards, unless such `m_FileAssign` creates the first generation file again.

2.7.4.4.2 Creating .dcb file

Create `.dcb` file for GDG data set when the first generation file is created by `m_FileAssign -g +1`.

Note:

If a GDG is created by `m_GenDefine` rather than `m_FileAssign`, `.dcb` file will not exist until the first generation file is created by `m_FileAssign -g +1`. Once `.dcb` file is created, its contents will not be changed by any other `m_FileAssign` statement afterwards, unless such `m_FileAssign` creates the first generation file again.

2.7.4.4.3 Deleting .dcb file

If a GDG is deleted by `m_FileDelete`, the corresponding `.dcb` file will be deleted automatically.

However, if all generation files in one GDG are deleted while the GDG itself exists, the corresponding `.dcb` file will not be deleted.

2.7.5 Using an In-Stream File

To define and use a file whose data is written directly inside the Korn shell script, use the `m_FileAssign` function with the `-i` parameter. By default the string `_end` is the "end" delimiter of the in-stream flow as shown in Listing below:

Listing 2-28 In-stream Data Example

```
(STEP1)
m_FileAssign -i INFIL
data record 1
data record 2
```

```
...  
_end
```

2.7.6 Using a Set of Concatenated Files

To use a set of files as a concatenated input (which in z/OS JCL was coded as a DD card, where only the first one contains a label), use the `m_FileAssign` function with the `-C` parameter as shown in the Listing 2-29 below:

Listing 2-29 Using a Concatenated Set of Files Example

```
(STEPDD02)  
m_FileAssign -d SHR INF ${DATA}/PJ01DDD.BT.QSAM.KBDDI002  
m_FileAssign -d SHR -C ${DATA}/PJ01DDD.BT.QSAM.KBDDI001  
m_ProgramExec BDDAB001
```

2.7.7 Using an External “sysin”

To use an “external sysin” file which contains commands to be executed, use the `m_UtilityExec` function.

```
m_FileAssign -d OLD SYSIN ${SYSIN}/SYSIN/MUEX07  
m_UtilityExec
```

2.7.8 Deleting a File

Files (including generation files) can be deleted using the `m_FileDelete` function:

```
m_FileDelete ${DATA}/PJ01DDD.BT.QSAM.KBST0045
```

2.7.9 RDB Files

In a migration project from z/OS to UNIX/Linux, some permanent data files may be converted to relational tables. See the [File-to-Oracle](#) chapter of the Oracle Tuxedo Application Runtime Workbench.

When a file is converted to a relational table, this change has an impact on the components that use it. Specifically, when such a file is used in a z/OS JCL, the converted Korn shell script corresponding to that JCL should be able to handle operations that involve this file.

In order to keep the translated Korn shell script as standard as possible, this change is not handled in the translation process. Instead, all the management of this type of file is performed at execution time within Batch Runtime.

In other words, if in the z/OS JCL there was a file copy operation involving the converted file, this is translated to a standard copy operation for files in Batch Runtime, in other words an `m_FileLoad` operation).

The management of a file converted to a table is made possible through an RDB file. An RDB file is a file that has the same name as the file that is converted to a table but with an additional suffix: `.rdb`.

Each time a file-related function is executed by Batch Runtime, it checks whether the files were converted to table (through testing the presence of a corresponding `.rdb` file). If one of the files

concerned have been converted to a table, then the function operates the required intermediate operations (such as: unloading and reloading the table to a file) before performing the final action.

All of this management is transparent to the end-user.

2.7.10 Using an RDBMS Connection

When executing an application program that needs to connect to the RDBMS, the `-b` option must be used when calling the `m_ProgramExec` function.

Connection and disconnection (as well as the commit and rollback operations) are handled implicitly by Batch Runtime and can be defined using the following two methods:

- Set the environment variable `MT_DB_LOGIN` before booting the TuxJES system.

Note:

In this case, all executing jobs use this variable.

- Set its value in the TuxJES Security Configuration file for different users.

The `MT_DB_LOGIN` value must use the following form: `dbuser/dbpasswd[@ssid]` or `"/`.

Note:

`"/` should be used when the RDBMS is configured to allow the use of UNIX authentication and not RDBMS authentication, for the database connection user. Make sure the executable program can be found in `$PATH`.

Please check with the database administrator whether `"/` should be used or not.

The `-b` option must also be used if the main program executed does not directly use the RDBMS but one of its subsequent sub-programs does as shown in Listing below:

Listing 2-30 RDBMS Connection Example

```
(STEPDD02)
m_FileAssign -d MOD UTF ${DATA}/PJ01DDD.BT.QSAM.REP001
m_ProgramExec -b DBREP001
```

The `m_ProgramExec` function may submit three types of files.

- Generated code files (`.gnt` file extension) compiled from COBOL source code file. Make sure that the `.gnt` files can be found in `$COBPATH` (for Micro Focus COBOL) or `$COB_LIBRARY_PATH` (for COBOL-IT).
- Callable shared library (`.so` file extension) compiled from C source code file. Make sure the callable shared library file can be found at `$COBPATH` (for Micro Focus COBOL) or `$COB_LIBRARY_PATH` (for COBOL-IT), or at system library file search path like `LIBPATH`, `LD_LIBRARY_PATH`, and so on.

This type of file must have an entry function whose name is equal to the file name.

For example, callable shared library file `ProgA.so` must contain a function declared by one of the following:

- `ProgA(short* arglen, char* argstr)`: if you need parameters
- `ProgA()`: if you do not need parameters
- Any other types of executable program (such as system utilities, shell scripts, and third party utilities)
`m_ProgramExec` will determine the deliverable type of the program in the following sequence: COBOL program (`.gnt`), C program in callable shared library (`.so`), and other executable programs. Once a COBOL program is executed, `m_ProgramExec` will not execute other programs with the same name. For example, once `ProgA.gnt` is executed, `ProgA.so` or other programs named `ProgA` will not be executed.

For `.gnt` file and `.so` files, `m_ProgramExec` launches the `runb` program to run it. ART provides `runb` for the following:

- `$JESDIR/ejr_mf_ora` for combination of Micro Focus COBOL and Oracle database
- `$JESDIR/ejr_mf_db2` for combination of Micro Focus COBOL and DB2 database
- `$JESDIR/ejr_cit_ora` for combination of COBOL-IT and Oracle database
- `$JESDIR/ejr_cit_db2` for combination of COBOL-IT and DB2 database

If you do not use the above four types of combination, go to `$JESDIR/ejr` and run `make.sh` to generate your personalized `runb`.

The `runb` program, runtime compiled with database libraries, runs the `runbatch` program.

The `runbatch` program, is in charge to:

- do the connection to the database (if necessary)
- run the user program
- do the commit or rollback (if necessary)
- do the disconnection from the database (if necessary)

2.8 Submitting a Job Using INTRDR Facility

The `INTRDR` facility allows you to submit the contents of a `sysout` to TuxJES (see the [Using Tuxedo Job Enqueueing Service \(TuxJES\)](#) documentation). If TuxJES is not present, a command “`nohup EJR`” is used.

Example:

```
m_FileAssign -d SHR SYSUT1 ${DATA}/MTWART.JCL.INFO
m_OutputAssign -w INTRDR SYSUT2
m_FileRepro -i SYSUT1 -o SYSUT2
```

In this example, the contents of the file `${DATA}/MTWART.JCL.INFO` (ddname `SYSUT1`) are copied into the file (ddname `SYSUT2`) which is using the option `-w INTRDR`, and then this file (ddname `SYSUT2`) is submitted.

 **Note:**

The output file must contain valid ksh syntax.

INTRDR job which is generated by COBOL program can be submitted automatically in real time. Once a COBOL program closes INTRDR, the job INTRDR is submitted immediately without waiting for the current step to finish. To enable this feature, file handler ARTEXTFH.gnt needs to be linked to COBOL program.

- For Micro Focus COBOL, add the following compile option.
CALLFH ("ARTEXTFH")
- For COBOL-IT, add the following compile option.
flat-extfh=ARTEXTFH
flat-extfh-lib="<fullpath of ARTEXTFH.gnt>"
ARTEXTFH.gnt is placed at "\${MT_ROOT}/COBOL_IT/ARTEXTFH.gnt".

If this feature is not enabled, INTRDR jobs is submitted after the current step finishes.

 **Note:**

If the batch job script generated at runtime is in JCL language, it can't be submitted by INTRDR.

2.9 Submitting a Job With EJR

When using Batch Runtime, TuxJES can be used to launch jobs (see the [Using Tuxedo Job Enqueueing Service \(TuxJES\)](#) documentation), but a job can also be executed directly using the EJR spawner.

Before performing this type of execution, ensure that the entire context is correctly set. This includes environment variables and directories required by Batch Runtime.

Example of launching a job with EJR

```
# EJR DEFVCUST.ksh
```

For a complete description of the EJR spawner, please refer to the Oracle Tuxedo Application Runtime for Batch Reference Guide.

2.10 User-Defined Entry/Exit

Batch Runtime allows you to add custom pre- or post- actions for public APIs. For each `m_*` (* represents any function name) function, you can provide `m_*_Begin` and `m_*_End` function and put them in `ejr/USER_EXIT` directory. They are invoked automatically when a job execution entering or leaving an `m_*` API.

Whether an `m_*` API calls its user-defined entry/exit function depends on the existence of `m_*_Begin` and `m_*_End` under `ejr/USER_EXIT`.

A pair of general user entry/exit APIs, `mi_UserEntry` and `mi_UserExit`, are called at the entry and exit point of each external API. The argument to these APIs consists of the function name

in which they are called, and the original argument list of that function. You don't need to modify these two APIs, but just need to provide your custom entry/exit for `m_*` external APIs. `mi_UserEntry` and `mi_UserExit` are placed under `ejr/COMMON`.

 **Note:**

In user entry/exit function, users are not allowed to use any function provided by ART for Batch; however, in user's script, a return statement returns value to the caller and ART for Batch checks if calling user entry/exit function works successfully through the return code. Return code 0 continues the job; non-zero value terminates the job.

You are suggested not to call `exit` in user entry/exit function. Because In the framework, `exit` is aliased an internal function, `mif_ExitTrap`, which is invoked ultimately if `exit` in user entry/exit function is called. If `exit 0` is called, the framework does nothing and the job continues. However if `exit not_0` is called, then a global variable is set and may terminate the current job.

- [Configuration](#)

2.10.1 Configuration

You should include only one function in a single file with the same name as the function. For example, `m_*_Begin` or `m_*_End`. Further, you should put all such files under `ejr/USER_EXIT`.

You are not allowed to provide custom entry/exit functions for any `mi_` prefix function provided by Batch Runtime.

2.11 Batch Runtime Logging

This section contains the following topics:

- [General Introduction](#)
- [Log Header](#)
- [File Information Logging](#)

2.11.1 General Introduction

This section contains the following topics:

- [Log Message Format](#)
- [Log Message Level](#)
- [Log Level Control](#)
- [Log File Structure](#)

2.11.1.1 Log Message Format

Each log message defined in `CONF/Messages.conf` is composed of six fields, as listed in the Table 2-8 of the topic [COBOL-IT](#)

Table 2-12 Log Message Format

Field	Content
1	Message identifier
2	Functions that can display the message (generic name using *)
3	Level of display. Default value: 4
4	Destination of display (u,e,o). <ul style="list-style-type: none"> • U: User output • E: Error Output (stderr) • O: Standard output (stdout)
5	Header flag (0,1,b). Default value: 0 <ul style="list-style-type: none"> • 0: No header will be displayed • 1: A hard-coded header format will be displayed • b: Specific for exceptions messages Fatal/Error/Warning
6	The message to be displayed with possible dynamic values

The levels of these messages are set to 4 by default.

You can specify the message level of Batch Runtime to control whether to print these three messages in job log.

2.11.1.2 Log Message Level

Table 2-13 Log Message Level

Level	Message
1	FATAL only
2	Previous level and errors
3	Previous level and information
4	Previous level and file information log
5	Previous level and high level functions
6	Previous level and technical functions
7	Same as level 3 and high level functions which correspond to the <code>-d</code> regexp option
8	Same as 7 and technical level functions which correspond to the <code>-d</code> regexp option
9	Reserved

2.11.1.3 Log Level Control

The default level of displaying messages in job log is 3. You can also choose one of the following ways to change the level:

- Use `-v` option of EJR
- Use the environment variable `MT_DISPLAY_LEVEL`

The display level set by EJR can override the level set by `MT_DISPLAY_LEVEL`.

2.11.1.4 Log File Structure

For each launched job, Batch Runtime produces a log file containing information for each step that was executed. This log file has the following structure as shown in Listing below:

Listing 2-31 Log File Example

```
JOB Jobname BEGIN AT 20091212/22/09 120445
BEGIN PHASE Phase1
Log produced for Phase1
.....
.....
.....
END PHASE Phase1 (RC=Xnnnn, JOBRC=Xnnnn)
BEGIN PHASE Phase2
Log produced for Phase2
.....
.....
.....
END PHASE Phase2 (RC=Xnnnn, JOBRC=Xnnnn)
.....
.....
BEGIN PHASE END_JOB
.....
END PHASE END_JOB (RC=Xnnnn, JOBRC=Xnnnn)

JOB ENDED WITH CODE (C0000)}
Or
JOB ENDED ABNORMALLY WITH CODE (S990)}
```

When not using TuxJes, the log file is created under the `$(MT_LOG)` directory with the following name: `<Job name>_<TimeStamp>_<Job id>.log`

For more information, see [Using Tuxedo Job Enqueueing Service \(TuxJES\)](#).

2.11.2 Log Header

Batch Runtime logging functionality provides an informative log header in front of each log line, in the following format:

```
YYYYmmdd:HH:MM:SS:TuxSiteID:JobID:JobName:JobStepName
```

You can configure the format of log header, but should not impact any configuration and behavior of existing specific message header: type 0, 1 and b.

The following table shows the variables you can use for specifying the general log header:

Table 2-14 Variables for Specifying General Log Header

Variable	Description
MTI_SITE_ID	If the job is submitted from TuxJES, it is the logical machine ID configured for the machine by TuxJES, otherwise it's empty.

Table 2-14 (Cont.) Variables for Specifying General Log Header

Variable	Description
MTI_JOB_ID	If the job is submitted from TuxJES, it is the job ID assigned by JES.
MTI_JOB_NAME	Name of the job assigned by <code>m_JobBegin</code> in the job script.
MTI_STEP_NAME	Name of the current executing job step.
MTI_SCRIPT_NAME	Name of the job script.
MTI_PROC_NAME	Name of the proc when the code included from a PROC by <code>m_ProcInclude</code> is executing; empty otherwise.

- [Configuration](#)

2.11.2.1 Configuration

`MT_LOG_HEADER` is a new configuration variable added in `CONF/BatchRT.conf`, for example:

```
MT_LOG_HEADER='${date +%Y%m%d:%H%M%S}':${MTI_SITE_ID}:${MTI_JOB_NAME}:${MTI_JOB_ID}:${MTI_JOB_STEP}:'
```

If the value of `MT_LOG_HEADER` is not a null string, its contents are evaluated as a shell statement to get its real value to be printed as the log header, otherwise this feature is disabled.

Note:

The string that configured to `MT_LOG_HEADER` is treated as a shell statement in the source code, and is interpreted by "eval" command to generate the corresponding string used as log header:

Syntax inside: `eval mt_MessageHeader="\${MT_LOG_HEADER}\\"`

To configure this variable, you need to comply with the following rules:

- `MT_LOG_HEADER` must be a valid shell statement for "eval", and must be quoted by single quotation marks.
- All the variables used in `MT_LOG_HEADER` must be quoted by "\${}". For example:
`${ MTI_JOB_STEP }`
- All the command line used in `MT_LOG_HEADER` must be quoted by "\$()". For example: `$(date +%Y%m%d:%H%M%S')`

You can modify the above examples according to your format needs using only the variables listed in Table 2-10 of the topic [Database Tables](#).

This configuration variable is commented by default, you need to uncomment it to enable this feature.

2.11.3 File Information Logging

Logging system can logs the detailed file information in job log, as well as the information when a file is assigned to a DD and when it is released.

File assignment information is logged in the following functions:

`m_FileAssign`

File release information is logged in the following functions:

`m_PhaseEnd`

File information is logged in the following functions:

- `m_FileBuild`
- `m_FileClrData`
- `m_FileConcatenate`
- `m_FileCopy`
- `m_FileDelete`
- `m_FileEmpty`
- `m_FileExist`
- `m_FileLoad`
- `m_FileRename`
- `m_FilePrint`
- `m_FileRepro`

The following topic describes the configurations required to log detailed file information:

- [Configuration](#)

2.11.3.1 Configuration

This section contains the following files:

- [Messages.conf](#)
- [BatchRT.conf](#)

2.11.3.1.1 Messages.conf

The following message identifiers are defined in `CONF/Messages.conf` to support using of `mi_DisplayFormat` to write file assignment and file information [Log Message Format](#).

- `FileAssign;m_FileAssign;4;ueo;0;%s`
- `FileRelease;m_PhaseEnd;4;ueo;0;%s`
- `FileInfo;m_File*;4;ueo;0;%s`

 **Note:**

CONF/Messages.conf is not configurable. Do not edit this file.

The string "%s" at the end of each identifier represents it will be written to log file. You can configure its value using the following variables defined in CONF/Batch.conf. For more information, see the Table 2-12 of the topic [Log Message Format](#)

- MT_LOG_FILE_ASSIGN (**for** FileAssign)
- MT_LOG_FILE_RELEASE (**for** FileRelease)
- MT_LOG_FILE_INFO (**for** FileInfo)

2.11.3.1.2 BatchRT.conf

Three configuration variables should be defined in CONF/BatchRT.conf to determine the detailed file information format. With the placeholders listed in Table 2-11 in the topic [Generation File Naming Rule](#), you can configure file log information more flexibly.

Table 2-15 Placeholders

Placeholder	Description	Value and Sample
<%DDNAME%>	DD Name for the file being operated	SYSOUT1
<%FULLPATH%>	Full path for the file being operated	/local/simpjob/work/TEST001.Gen.00000001
<%FILEDISP%>	DISP for the file being operated	SHR or NEW

Table 2-16 Configuration Variables in CONF/BatchRT.conf

Name	Value and Sample	Available Placeholder
MT_LOG_FILE_ASSIGN	FileAssign: DDNAME=(<%DDNAME%>); FILEINFO=\$(ls -l --time-style='+%Y/%m/%d %H:%M:%S' --no-group <%FULLPATH%> '); FILEDISP=(<%FILEDISP%>)	<%DDNAME%> <%FULLPATH%> <%FILEDISP%>
MT_LOG_FILE_RELEASE	FileRelease: DDNAME=(<%DDNAME%>); FILEINFO=\$(ls -l --time-style='+%Y/%m/%d %H:%M:%S' --no-group <%FULLPATH%> '); FILEDISP=(<%FILEDISP%>)	<%DDNAME%> <%FULLPATH%> <%FILEDISP%>
MT_LOG_FILE_INFO	FILEINFO=\$(ls -l --time-style='+%Y/%m/%d %H:%M:%S' --no-group <%FULLPATH%>) leCopy source, FileCopy Destination, and FileDelete etc.	<%FULLPATH%>

To configure strings to these `MT_LOG_FILE_*` variables, replace the placeholders with corresponding values (just string replacement). The result is treated as a shell statement, and is interpreted by "eval" command to generate the corresponding string writing to log:

Syntax inside: `eval mt_FileInfo="\${MT_LOG_FILE_INFO}\\"`

To configure these variables, you need to comply with the following rules:

- After placeholders are replaced, `MT_LOG_FILE_*` must be a valid shell statement for "eval", and must be quoted by single quotation marks.
- Only the placeholders listed in Table3-11 can be used in `MT_LOG_FILE_*`
- All the command line used in `MT_LOG_HEADER` must be quoted by "\$ ()". For example:
`$(ls -l --time-style=+'%Y/%m/%d %H:%M:%S' --no-group <%FULLPATH%>)`

If the level of `FileInfo` message is equal to or less than the message level specified for Batch Runtime and `MT_LOG_FILE_*` is set to a null string, `FileInfo` message will not be displayed in job log. If `MT_LOG_FILE_*` is set to an incorrect command to make file information invisible, `FileInfo` message will not be displayed in job log as well, but the job execution will not be impacted.

Note:

You can customize these variables according to your format needs, but make sure the command is valid, otherwise the file information will not be logged.

2.12 Using Batch Runtime With a Job Scheduler

Entry points are provided in some functions (`m_JobBegin`, `m_JobEnd`, `m_PhaseBegin`, `m_PhaseEnd`) in order to insert specific actions to be made in relation with the selected Job Scheduler.

2.13 Executing an SQL Request

A SQL request may be executed using the function `m_ExecSQL`.

Depending on the target database, the function executes a "sqlplus" command with ORACLE database, or a "db2 -tsx" command with UDB.

Note:

The environment variable `MT_DB_LOGIN` must be set (database connection user login).

The `SYSIN` file must contain the SQL requests and the user has to verify the contents regarding the database target.

2.14 Simple Application on COBOL-IT / BDB

Batch COBOL programs compiled by COBOL-IT can access the indexed ISAM files which are converted from Mainframe VSAM files through the ART Workbench. VSAM files can be stored in BDB through COBOL-IT.

To enable this function in Batch runtime, do the followings during runtime:

- Compile COBOL programs by COBOL-IT compiler with specifying `bdb:yes`.
- Set `DB_HOME` correctly because it is required by BDB; `DB_HOME` points to a place where temporary files are put by BDB.
- Set the following environment variables before ART for Batch launches a job:
 - `export COB_EXTFH_INDEXED=BDBEXTFH`
 - `export COB_EXTFH_LIB=/path_to_Cobol-IT/lib/libbdbextfh.so` #For example,
`export COB_EXTFH_LIB=/opt/cobol-it-64/lib/libbdbextfh.so`
- Unset `COB_ENABLE_XA` environment variable before booting the TuxJES system.
`unset COB_ENABLE_XA`

 **Note:**

It is required to set `COB_ENABLE_XA` when you use COBOL-IT with ART CICS Runtime.

2.15 Native JCL Job Execution

This section contains the following topics:

- [General Introduction](#)
- [Configurations](#)
- [Using JES Client to Manage JCL Jobs](#)
- [Supporting Range for JCL Statements and Utilities](#)

2.15.1 General Introduction

Oracle Tuxedo ART Batch Runtime supports users to manage native JCL jobs without pre-conversion by ART Workbench.

2.15.2 Configurations

It is required to set TuxJES using database to manage job. See [Setting up TuxJES as an Oracle Tuxedo Application \(Using Database\)](#) for more information.

It is required to add following setting item to `jesconfig` file: `JOBLANG=JCL`.

All the environment variables described in [Setting Environment Variables](#) is also available for native JCL execution.

2.15.3 Using JES Client to Manage JCL Jobs

The usage is the same as KSH jobs:

- [Submitting a JCL Job](#)
- [Printing Jobs](#)
- [Holding/Releasing/Canceling/Purging a JCL Job](#)

- [JCL Engine's Debug Trace File](#)

2.15.3.1 Submitting a JCL Job

You can use option `-I` to submit a JCL job with the following usage.

- `artjesadmin -I JCLScriptName` (in the shell command line)
- `submitjob -I JCLScriptName` (in the `artjesadmin` console)

Also, you can specify `env file` when submitting job as below:

- `artjesadmin -o "-e <envfile_path>" -I JCLScriptName`
- `submitjob -o "-e <envfile_path>" -I JCLScriptName` (in the `artjesadmin` console)

All the items in this `env file` should conform to format "`<NAME>=<VALUE>`", such as

- `DATA=/home/testapp/data`
- `PROCLIB=${PROCLIB}:${APPDIR}/proc`
- `JESTRACE=DEBUG`

2.15.3.2 Printing Jobs

`[-t JCL|KSH]` is used as a filter with the following usage:

- Print all jobs: `printjob`
- Print JCL jobs: `printjob -t JCL`
- Print KSH jobs: `printjob -t KSH`

The column, job type, is added to the results with one of the following values:

- JCL for JCL jobs
- KSH for KSH jobs

Before the conversion phase completes, the JCL job name and class are null, and the priority is displayed as 0.

2.15.3.3 Holding/Releasing/Canceling/Purging a JCL Job

The usage is the same as KSH jobs.

2.15.3.4 JCL Engine's Debug Trace File

The JCL conversion log is `$JESROOT/<JOBID>/LOG/<JOBID>.trace`.

This trace file is only for debug purpose:

2.15.4 Supporting Range for JCL Statements and Utilities

Table 2-17 lists the supported JCL statement. Table 2-18 lists the supported utilities.

Table 2-17 Supported JCL Statement

Item	Sub-Item
DD Statement	Param DISP
	Param DUMMY
	Param SYSOUT=CLASS
	Param DCB/RECFM/LRECL
	Param DSN
	Param DSN (backward reference)
	Param DDNAME (forward reference)
	Param LIKE
	Temporary DD, &&TEMP
	Instream DD
	Concatenate DD
	Dataset MOD (append)
	Dataset catalog feature, and Param VOLUMN
	Dataset expire feature
	Duplicate DD in a single step
	Dataset exclusive (DD lock and unlock)
Special DD JOBLIB	
Special DD STEPLIB	
EXEC Statement	Param PARM
	Param COND
	Execute utility
	Execute COBOL program
	Execute COBOL program with param
JOB Statement	Param CLASS
	Param COND
	Param TYPERUN(COPY/HOLD/JCLHOLD/SCAN)
	Param MSGCLASS
	Param RESTART(*/*stepname/stepname.procstepname)
JCLLIB Statement	-
SET Statement	-
IF/ELSE/ENDIF Statement	-
INCLUDE Statement	-
OUTPUT Statement	-
JCL Variable	-
PROC/PEND Statement	-
PROC Invocation	Symbol override
	PARM override
	COND override
	DD override

Table 2-18 Supported Utilities

Utility	Description
DSNTEP2	Execute SQL DML
DSNTEP4	Execute SQL DML
DSNTIAUL	Execute SQL DML
DSNTIAD	Execute SQL DML
FTP	FTP Client
ICETOOL	Perform Multiple Purpose Dataset Operations
IEBUPDTE	Create or Modify PS/PDS
IEHLIST	List Entries in PDS/PDSE
IEHPROGM	Modify System Control Data
IKJEFT01	Launch Application
IKJEFT1A	
IKJEFT1B	
PKZIP	Compress Files into ZIP format
PKUNZIP	Ucompress Files in ZIP format
IEBDG	Create Dataset based on description
IEBGENER	Copy PS or member in PDS
IEBPTPCH	Prints or punches all, or selected portions of a sequential or partitioned data set or PDSE in a single step
IEBCOPY	Copy or Merge members in PDS/PDSE
FILEAID	Consolidates the functions of many standard IBM utilities
IEFBR14	Null Utility
SORT	Sort, merge or filter datasets
ICEGENER	Alias of IEBGENER
ICEMAN	Alias of SORT
IDCNOGFL	Alias of IDCAMS
IEBFR14	Alias of IEFBR14
IDCAMS	Generate and modify VSAM and Non-VSAM datasets
REXEC	Execute commands on remote host
DFSRR00	Invoke a BMP program in IMS
DSNUTILB	DB2 utility used to load/unload table

2.16 Native JCL Test Mode

This section contains the following topics:

- [General Introduction](#)
- [Configurations](#)
- [Using Client to Manage Test Mode](#)
- [Test Mode Report Files](#)

2.16.1 General Introduction

Native JCL Test Mode is a running mode of native JCL. This mode helps you analyze defects in user jobs/procs, find gaps in the use of the Native JCL feature, and detect environment dependency issues that block jobs from running.

2.16.2 Configurations

Configure as follows to use Native JCL Test Mode.

- [Environment Variables Configurations \(Mandatory\)](#)
- [Native JCL Configuration File Configurations \(Optional\)](#)

2.16.2.1 Environment Variables Configurations (Mandatory)

Set required environment variables before you submit a test mode job. The following table lists all the environment variables you must set.

Table 2-19 Environment Variables Required for Native JCL Test Mode

Environment Variable	Description
JESDIR	Directory where TuxJES is installed
JESROOT	Root directory for JES2 system
DATA	Directory for permanent files
PROCLIB	Directory for PROC and INCLUDE files
MT_COBOL	Specifies COBOL. Use one of the following values: <ul style="list-style-type: none"> • COBOL_MF: Micro Focus COBOL • COBOL_IT: COBOL-IT COBOL
MT_DB	Specifies target database. Use one of the following values: <ul style="list-style-type: none"> • DB_ORACLE: Oracle database • DB_DB2LUW: DB2 database
MT_LOG	Directory for logs
MT_TMP	Directory for temporary internal files
MT_SORT	Specifies SORT. Use one of the following values: <ul style="list-style-type: none"> • SORT_MicroFocus: Micro Foucs COBOL Sort Utility • SORT_SyncSort: Syncsort Sort Utility • SORT_CIT: COBOL-IT COBOL Sort utility

2.16.2.2 Native JCL Configuration File Configurations (Optional)

Configure the additional utilities that you need to use in native JCL configuration file. This configuration file is located under `${JESDIR}/jclexec/conf/JCLExecutor.conf`; its `ADDUTILITYLIST` item is used to define additional utility list.

For example, if you would like to define `MYUTILITY` utility, you should specify `ADDUTILITYLIST=MYUTILITY`; if you would like to define multiple utilities, you should specify `ADDUTILITYLIST=MYUTILITY1,MYUTILITY2,...`, using comma (',') to separate utilities.

2.16.3 Using Client to Manage Test Mode

You can use `artjclchk` tool to launch test mode for a job or a group of jobs. The command line syntax for the `artjclchk` tool is as follows:

```
artjclchk -d <destdir> [-i <job_file|job_dir>] [-p <parallel number>] [-r]
```

-d <destdir>

Specifies the destination directory to save output report files. There are three types of output report file; all of them are generated here. See Test Mode Report Files for more information.

-i <job_file|job_dir>

Specifies jobs to be analyzed in test mode. You can specify an individual job or a directory; if you specify a directory, all jobs under this directory are analyzed.

-p <parallel number>

Specifies the number of jobs that can be processed concurrently.

-r

Specifies to generate category report and summary report.

- If you specify `-r` but do not specify `-i`, this command generates category report and summary report for every individual report under `-d` directory.
- If you specify `-r` and specify `-i`, this command generates individual reports for all jobs that `-i` specifies, and then generates category report and summary report only for these individual reports.
- If you do not specify `-r`, category report and summary report are not generated.



Note:

If you run `artjclchk` tool twice with the same `-i` and `-d` option values, results from the second run will replace results from the first run.

2.16.4 Test Mode Report Files

There are three types of report files that `artjclchk` generates.

- **Individual Report File**
An individual report file is a job specific report file. `artjclchk` generates an individual report file for each job; anything found in the job is reported in this file.
- **Category Report File**
A category report file is organized according to the type of information. `artjclchk` generates a summary report file for each type of information; any occurrence falling in the category together with job location and line number is reported in this file.
- **Summary Report File**
A summary report file is a simplified version of category report. `artjclchk` generates it. Unlike category report file, summary report file only records the issues and issue occurrences. Summary report file has the same name with the corresponding category report file but without "Occurrences".

The following topics describe each of the reports in details:

- [Individual Report File](#)
- [Category Report File](#)
- [Summary Report File](#)

2.16.4.1 Individual Report File

An individual report file is a job specific report file. `artjclchk` generates an individual report file for each job; anything found in the job is reported in this file.

This file is named in the format of `<JOBFILENAME>.rpt` ; fields in each line are separated by comma. See the following tables for these fields.

- Table 2-20 lists fields for JCL element
- Table 2-21 lists fields for `IKJEFTxx` utilities
- Table 2-22 lists fields for other utilities

Table 2-20 Report Fields for JCL Elements

Field	Value	Description
TYPE	ROC	Identifies a PROC issue
	INCLUDE	Identifies an INCLUDE issue
	STATEMENT	Identifies a JCL statement issue
	PARAM	Identifies a JCL parameter issue
	SYMBOL	Identifies a JCL symbol issue
	UTILITY	Identifies a utility issue
	PROGRAM	Identifies a program issue
	DATASET	Identifies a dataset issue
	DD	Identifies a DD issue
	STEP	Identifies a STEP issue
	INTERNAL	Identifies an internal issue, such as memory fault, I/O defect, etc.
STATUS	FOUND NOTFOUND	Identifies if PROC, INCLUDE, PROGRAM, and DATASET objects are found or not found
	SUPPORTED UNSUPPORTED	Identifies if STATEMENT, PARAM, and UTILITY objects are supported or not supported
	DEFINED UNDEFINED	Identifies if SYMBOL object is defined or not defined
	IGNORED	Identifies STATEMENT or PARAM is recognized but ignored
	INVALID	Identifies STATEMENT or PARAM is unrecognized
	ERROR	Identifies a system/internal error is met
NAME	Object name	The object name. It can be PROC name, INCLUDE name, PROGRAM name, UTILITY name, PARAM name, DATASET name, or other object name
FILE	File location	Identifies file location
LINE	Line location	Identifies line location
JCL	JCL	Identify it is a JCL issue, not a utility issue

Table 2-20 (Cont.) Report Fields for JCL Elements

Field	Value	Description
DETAIL	Detailed information	The detailed description of this issue

Table 2-21 Report Fields for IKJEFTxx Utilities

Field	Value	Description
TYPE	COMMAND	Identifies a utility command issue
	PARAM	Identifies a utility parameter issue
	UTILITY	Identifies a utility issue
	PROGRAM	Identifies a program issue
	DD	Identifies a DD issue
	STEP	Identifies a STEP issue
	INTERNAL	Identifies an internal issue, such as memory fault, I/O defect, etc.
STATUS	FOUND NOTFOUND	Identifies if PROGRAM object is found or not found
	SUPPORTED UNSUPPORTED	Identifies if COMMAND, PARAM, and UTILITY objects are supported or not supported
	IGNORED	Identifies COMMAND or PARAM is recognized but ignored
	INVALID	Identifies COMMAND or PARAM is unrecognized
	ERROR	Identifies a system/internal error is met
NAME	Object name	The object name. It can be PROC name, INCLUDE name, PROGRAM name, UTILITY name, or other object name
FILE	File location	Identifies file location
LINE	Line location	Identifies line location. The FILE and LINE locations are related to JCL job itself, for example, the STEP location where the current utility is launched.
UTILITY	<UTILITYNAME>	Identifies the name of the utility that generates the report line, for example, IKJEFT01
DETAIL	Detailed information	The detailed description of this issue

Table 2-22 Report Fields for Other Utilities

Field	Value	Description
TYPE	COMMAND	Identifies a utility command issue
	PARAM	Identifies a utility parameter issue
	DD	Identifies a DD issue
	INTERNAL	Identifies an internal issue, such as memory fault, I/O defect, etc.
STATUS	SUPPORTED UNSUPPORTED	Identifies if COMMAND and PARAM objects are supported or not supported
	IGNORED	Identifies COMMAND or PARAM is recognized but ignored
	INVALID	Identifies COMMAND or PARAM is unrecognized

Table 2-22 (Cont.) Report Fields for Other Utilities

Field	Value	Description
	ERROR	Identifies a system/internal error is met
NAME	Object name	The object name. It can be PROC name, INCLUDE name, PROGRAM name, UTILITY name, or other object name
FILE	File location	Identifies file location
LINE	Line location	Identifies line location. The FILE and LINE locations are related to JCL job itself, for example, the STEP location where the current utility is launched.
UTILITY	<UTILITYNAME>	Identifies the name of the utility that generates the report line, for example, IEBGENER, SORT, and PKZIP
DETAIL	Detailed information	The detailed description of this issue

2.16.4.2 Category Report File

A category report file is organized according to the type of information. `artjclchk` generates a summary report file for each type of information; any occurrence falling in the category together with job location and line number is reported in this file.

The following reports will be generated:

- Missing Item Report**
 This is the category report file for missing items. This report file is named in the format "Missing_Item_<DATETIME>_Occurrences.csv". See Table 2-23 for its columns.
- Unsupported Item Report**
 This is the category report file for unsupported items. This report file is named in the format "Unsupported_Item_<DATETIME>_Occurrences.csv". See Table 2-24 for its columns.
- Ignored Item Report**
 This is the category report file for ignored items. This report file is named in the format "Ignored_Item_<DATETIME>_Occurrences.csv". See Table 2-25 for its columns.

Suspicious Code Defect Report

This is the category report file for ignored items. This report file is named in the format "Ignored_Item_<DATETIME>_Occurrences.csv". See Table 2-26 for its columns.

Missing Dataset Report

This is the category report file for missing dataset. This report file is named in the format "Missing_Dataset_<DATETIME>_Occurrences.csv". See Table 2-27 for its columns.

Internal Error Report

This is the category report file for internal error. This report file is named in the format "Add content". See Table 2-28 for its columns.

Supported Utility Report

This is the category report file for supported utilities. This report file is named in the format "Supported_UTILITY_<DATETIME>_Occurrences.csv". See Table 2-29 for its columns." . .

Table 2-23 Category Report File: Missing Item Report

Column Name	Description
Name	Name of the item which is missing.

Table 2-23 (Cont.) Category Report File: Missing Item Report

Column Name	Description
Type	Item type. It can be PROC, INCLUDE or PROGRAM.
File Location	Called file.
Line Number	Corresponding line number.

Table 2-24 Report File: Unsupported Item Report

Column Name	Description
Name	Name of the item which is missing.
Type	Item type. It can be PROC, INCLUDE or PROGRAM.
JCL/Utility	JCL or utility name.
File Location	Called file.
Line Number	Corresponding line number.
Description	Corresponding line number.

Table 2-25 Category Report File: Ignored Item Report

Column Name	Description
Name	Name of the item which is ignored.
Type	Item type. It can be STATEMENT, COMMAND or PARAM.
JCL/Utility	JCL or utility name.
File Location	Called file.
Line Number	Corresponding line number.

Table 2-26 Category Report File: Suspicious Code Defect Report

Column Name	Description
Statement	Invalid statement.
Type	Item type.
JCL/Utility	JCL or utility name.
File Location	Called file.
Line Number	Corresponding line number.
Description	Description for the error.

 **Note:**

The detected location may be not the real root cause but just the location where parsing failed. The actual code defect may be located in previous lines; when you check it, pay attention to the context where the error is reported.

Table 2-27 Category Report File: Missing Dataset Report

Column Name	Description
Dataset	The missing dataset name.
File Location	Called file.
Line Number	Corresponding line number.
DD	DD name.

Table 2-28 Category Report File: Internal Error Report

Column Name	Description
Error	The parameter which is unsupported, ignored, or invalid.
Type	Item type.
File Location	Called file.
Line Number	Corresponding line number.
Description	Description for the error.

Table 2-29 Category Report File: Supported Utility Report

Column Name	Description
Name	Utility name.

2.16.4.3 Summary Report File

A summary report file is a simplified version of category report. `artjclchk` generates it. Unlike category report file, summary report file only records the issues and issue occurrences. Summary report file has the same name with the corresponding category report file but without "Occurrences".

The following reports will be generated:

- **Missing Item Report**
This report file is named in the format "Missing_Item_<DATETIME>.csv". See [Table 2-30](#) for its columns.

 **Note:**

This is the simplified version of the "Missing Item Report" category report file.

- **Unsupported Item Report**
This report file is named in the format "Unsupported_Item_<DATETIME>.csv". See [Table 2-31](#) for its columns.

 **Note:**

This is the simplified version of the "Unsupported Item Report" category report file.

Ignored Item Report

This report file is named in the format "Ignored_Item_<DATETIME>.csv". See [Table 2-32](#) for its columns.

 **Note:**

This is the simplified version of the "[Ignored Item Report](#)" category report file.

- **Suspicious Code Defect Report**

This report file is named in the format "CodeDefect_<DATETIME>.csv". See [Table 2-33](#) for its columns.

 **Note:**

This is the simplified version of the "[Suspicious Code Defect Report](#)".

- **Missing Dataset Report**

This report file is named in the format "Missing_Dataset_<DATETIME>.csv". See [Table 2-34](#) for its columns.

 **Note:**

This is the simplified version of the "[Missing Dataset Report](#)" category report file.

- **Internal Error Report**

This report file is named in the format "Internal_Error_<DATETIME>.csv". See [Table 2-35](#) for its columns.

 **Note:**

This is the simplified version of the "[Internal Error Report](#)" category report file.

- **Supported Utility Report**

This report file is named in the format

"Supported_Utility_<DATETIME>.csv". See [Table 2-36](#) for its columns.

 **Note:**

This is the simplified version of the "[Supported Utility Report](#)" category report file.

Table 2-30 Summary Report File: Missing Item Report

Column Name	Description
Name	Name of the item which is missing.
Type	Item type. It can be PROC, INCLUDE or PROGRAM.
Occurrences	Repeated times.

Table 2-31 Summary Report File: Unsupported Item Report

Column Name	Description
Name	Name of the item which is unsupported.
Type	Item type. It can be UTILITY, STATEMENT, COMMAND or PARAM.
JCL/Utility	JCL or utility name.
Description	Description for the error.
Occurrences	Repeated times.

Table 2-32 Summary Report File: Ignored Item Report

Column Name	Description
Name	Name of the item which is ignored.
Type	Item type. It can be STATEMENT, COMMAND or PARAM.
JCL/Utility	JCL or utility name.
Occurrences	Repeated times.

Table 2-33 Suspicious Code Defect Report

Column Name	Description
Statement	Invalid statement.
Type	Item type.
JCL/Utility	JCL or utility name.
Description	Description for the error.
Occurrences	Repeated times.

Table 2-34 Summary Report File: Missing Dataset Report

Column Name	Description
Dataset	The missing dataset name.
DD	DD name.
Occurrences	Repeated times.

Table 2-35 Summary Report File: Internal Error Report

Column Name	Description
Error	The parameter which is unsupported, ignored, or invalid.
Type	Item type.
Description	Description for the error.
Occurrences	Repeated times.

Table 2-36 Summary Report File: Supported Utility Report

Column Name	Description
Name	Utility name.
Occurrences	Repeated times.

2.17 Network Job Entry (NJE) Support

This section contains the following topics:

- [General Introduction](#)
- [Configurations](#)
- [NJE Job Sample](#)

2.17.1 General Introduction

With NJE support, users can implement the following functionalities in Batch Runtime exactly as they do in JCL jobs.

- `/* ROUTE XEQ`
- `/* XEQ`
- `/* XMIT`

By `m_SetJobExecLocation` API of Batch Runtime, users can develop KSH jobs with NJE support. For example,

- Specify the server group, on which the job will be executed.
- In a job, transmit an in-stream job to another server group and make it run on that server group.

2.17.2 Configurations

This section contains the following topics:

- [Job Execution Server Group](#)
- [ON/OFF Setting of NJE Support](#)
- [Environment Variable MT_TMP in MP Mode](#)
- [Queue EXECGRP](#)

2.17.2.1 Job Execution Server Group

When specifying the server group name, which is specified as job execution group in API `m_JobSetExecLocation`, please ensure the following:

- The specified server group must exist in `ubbconfig` file of JES domain.
- At least one `ARTJESINITIATOR` server must be deployed in that server group.

2.17.2.2 ON/OFF Setting of NJE Support

There is a corresponding setting item in JES configuration file.

Table 2-37 Configurations in <APPDIR>/jesconfig

Name	Value	Default Value
NJESUPPORT	ON: Enable NJE support OFF: Disable NJE support	OFF

If NJE support is disabled in `jesconfig`, the statement `m_SetJobExecLocation <SvrGrpName>` is ignored by TuxJES and then the job may be executed by any `ARTJESINITIATOR` in any server group.

2.17.2.3 Environment Variable MT_TMP in MP Mode

In MP mode, `MT_TMP` needs to be configured on NFS, and all the nodes in tuxedo domain should have the same value of `MT_TMP` and share it.

`MT_TMP` can be configured in file `$MT_ROOT/CONF/BatchRT.conf`, or to export it as environment value before `tlisten` is started in each node.

2.17.2.4 Queue EXECGRP

If `NJESUPPORT` is enabled in `jesconfig`, a new queue named `EXECGRP` must be created in the existing queue space `JES2QSPACE`. If `EXECGRP` is not created, no jobs can be processed by JES.

2.17.3 NJE Job Sample

Listing 2-32 Sample of Specifying Job Execution Server Group (XEQ)

```
m_JobBegin -j SAMPLEJCL -s START -v 2.0 -c R
m_JobSetExecLocation "ATLANTA"
while true ;
do
m_PhaseBegin
case ${CURRENT_LABEL} in
(START)
# XEQ ATLANTA
JUMP_LABEL=STEP01
;;
(STEP01)
m_OutputAssign -c "*" SYSPRINT
m_FileAssign -i SYSIN
m_FileDelete ${DATA}/GBOM.J.PRD.ABOMJAW1.ABEND02
m_RcSet 0
_end
m_UtilityExec
JUMP_LABEL=END_JOB
;;
(END_JOB)
break
;;
```

```

(*)
m_RcSet ${MT_RC_ABORT:-S999} "Unknown label : ${CURRENT_LABEL}"
break
;;
esac
m_PhaseEnd
done
m_JobEnd

```

Listing 2-33 Sample of Transmitting and Submitting a Job to Another Server Group (XMIT)

```

m_JobBegin -j JOBA -s START -v 2.0
while true;
do
m_PhaseBegin
case ${CURRENT_LABEL} in
(START)
m_FileAssign -i -D \_DML_XMIT_TEST1 SYSIN
m_JobBegin -j TEST1 -s START -v 2.0 -c B
m_JobSetExecLocation "ATLANTA"
while true ;
do
m_PhaseBegin
case ${CURRENT_LABEL} in
(START)
JUMP_LABEL=STEP01
;;
(STEP01)
m_OutputAssign -c "*" SYSPRINT
m_FileAssign -i SYSIN
m_FileDelete ${DATA}/GBOM.J.PRD.ABOMJAW1.ABEND02
m_RcSet 0
_end

m_UtilityExec
JUMP_LABEL=END_JOB
;;
(END_JOB)
break
;;
(*)
m_RcSet ${MT_RC_ABORT:-S999} "Unknown label : ${CURRENT_LABEL}"
break
;;
esac
m_PhaseEnd
done
m_JobEnd
\_DML_XMIT_TEST1
m_ProgramExec artjesadmin -i ${DD_SYSIN}
JUMP_LABEL=END_JOB
;;
(END_JOB)
break

```

```

;;
(*)
m_RcSet ${MT_RC_ABORT:-S999} "Unknown label : {CURRENT_LABEL}"
break
;;
esac
m_PhaseEnd
done
m_JobEnd

```

In the above sample, job `TEST1` will be submitted by the current job and executed by the `ARTJESINITIATOR` which belongs to JES's Tuxedo server group `ATLANTA`.

2.18 File Catalog Support

This section contains the following topics:

- [General Introduction](#)
- [Database Table](#)
- [Configuration Variables](#)
- [External Shell Scripts](#)
- [External Dependency](#)

2.18.1 General Introduction

With file catalog support in Batch Runtime, users can access dataset under volumes. A volume is a dataset carrier and exists as a folder; each dataset should belong to a volume.

File catalog contains the mapping from each dataset to each volume. When referencing an existing and cataloged file on Mainframe, file catalog will be requested to find out the volume in which the file is located, and then the file will be accessed.

If file catalog functionality is disabled, the behavior in Batch Runtime remains the same as it is without such functionality.

2.18.2 Database Table

This table shows the general management for file catalog functionality by Batch Runtime. In this table, each row represents one file-to-volume mapping.

Table 2-38 Batch Runtime Catalog

Name	Type	Description
FILENAME	VARCHAR(256)	The file name. It cannot contain any slash.
VOLUME	VARCHAR(256)	The volume name. It cannot contain any slash.
VOLUME_ATTR	CHAR(1)	Reserved.
EXPDT_DATE	CHAR(7)	Expiration date of the file
CREATE_DATE	CHAR(7)	The date when the file is created.
FILE_TYPE	VARCHAR(8)	File organization.
JOB_ID	VARCHAR(8)	The ID of the job that creates the entry.

Table 2-38 (Cont.) Batch Runtime Catalog

Name	Type	Description
JOB_NAME	VARCHAR(32)	The name of the job that creates the entry.
STEP_NAME	VARCHAR(32)	The name of the step that creates the entry.
Primary Key: PK_ART_BATCH_CATALOG		

2.18.3 Configuration Variables

Four configuration variables are required to be added in BatchRT.conf or set as environment variables:

MT_USE_FILE_CATALOG

If it is set to yes (`MT_USE_FILE_CATALOG=yes`), the file catalog functionality is enabled; otherwise, the functionality is disabled.

MT_VOLUME_DEFAULT

If no volumes are specified when a new dataset is created, Batch Runtime uses the volume defined by `MT_VOLUME_DEFAULT`. `MT_VOLUME_DEFAULT` contains only one volume. For example, `MT_VOLUME_DEFAULT=volume1`.

MT_DB_LOGIN

This variable contains database access information. For Oracle, its value is "username/password@sid" (for example, "scott/password@gdg001").

For Db2, its value is "your-database USER your-username USING your-password" (for example, "db2linux USER db2svr USING db2svr").

MT_CATALOG_DB_LOGIN

This variable contains file catalog database access information. Its format is the same as `MT_DB_LOGIN`. Since the file catalog is stored in database, BatchRT must access it through `MT_DB_LOGIN` or `MT_CATALOG_DB_LOGIN`.

`MT_CATALOG_DB_LOGIN` precedes `MT_DB_LOGIN` in accessing file catalog. If file catalog DB is the same as data DB, configuring `MT_DB_LOGIN` only is required; otherwise, both must be configured.

2.18.4 External Shell Scripts

You can use `CreateTableCatalog[Oracle|Db2].sh` or `DropTableCatalog[Oracle|Db2].sh` to create or drop the new database table.

- [Description](#)
- [Usage](#)
- [Sample](#)
- [DropTableCatalog\[Oracle|Db2\].sh](#)

2.18.4.1 Description

Creates table `ART_BATCH_CATALOG` in database.

2.18.4.2 Usage

```
CreateTableCatalog[Oracle|Db2].sh <DB_LOGIN_PARAMETER>
```

2.18.4.3 Sample

```
CreateTableCatalogOracle.sh scott/password@orcl
```

2.18.4.4 DropTableCatalog[Oracle|Db2].sh

This section contains the following topics:

- [Description](#)
- [Usage](#)
- [Sample](#)

2.18.4.4.1 Description

Drops table `ART_BATCH_CATALOG` from database.

2.18.4.4.2 Usage

```
DropTableCatalog[Oracle|Db2].sh <DB_LOGIN_PARAMETER>
```

2.18.4.4.3 Sample

```
DropTableCatalogOracle.sh scott/password@orcl
```

2.18.5 External Dependency

To use file catalog functionality in Batch Runtime, File Converter and JCL Converter in ART Workbench should enable catalog functionality. For more information, please refer to [Oracle Tuxedo Application Rehosting Workbench User Guide](#).

2.19 Launching REXX EXECs

This section contains the following topics:

- [Setting MT_REXX_PATH](#)
- [Launching REXX EXECs](#)
- [TSO Batch Commands](#)

2.19.1 Setting MT_REXX_PATH

`MT_REXX_PATH` has no default value. It should be set with the main path where all REXX execs located in. Place REXX programs in proper subdirectories under `${MT_REXX_PATH}`. These subdirectories correspond to PDS on mainframe where REXX programs live.

2.19.2 Launching REXX EXECs

If `SYSEXEC` is defined, BatchRT accepts programs run by `m_ProgramExec` as REXX EXEC.

DD SYSEXEC specifies where to find object REXX programs.

2.19.3 TSO Batch Commands

All relevant REXX files (REXX APIs and TSO commands) are located in the `Batch_RT/tools/rexx` directory. The directory structure is as follows:

```
-- lib
/-- outtrap.rex
/ -- regis_tso_cmd
-- tso
/-- DELETE
/-- LISTDS
/- RENAME
/-- libTSO.so
```

`Batch_RT/tools/rexx/tso` is where TSO commands are located. REXX APIs should be put in the `Batch_RT/tools/rexx/lib` directory.



Note:

TSO commands provide a lock mechanism. Files accessed by TSO commands in a REXX program are locked when commands start. All file locks are released once TSO commands finish executing.

2.20 COBOL Program Access to Oracle and TimesTen Database

ART for Batch supports the following scenarios in this feature:

- COBOL program accesses to both Oracle database and TimesTen database
- COBOL program accesses only to TimesTen database

The following topics describe the procedure to access the Oracle and TimesTen Database:

- [Setting Environment Variables](#)
- [Programming in COBOL](#)
- [Preprocessing COBOL Programs](#)
- [Examples](#)

2.20.1 Setting Environment Variables

To enable this feature, you need to set the following environment variables:

Table 2-39 Required Environment Variables

Scenario	Environment Variables			
	MT_TT_CONN	MT_DB	MT_DB_LOGIN	MT_DB_LOGIN2
Oracle database and TimesTen database	Required.Specifies TimesTen connection name.	Required. Specifies ORA.	Required.Specifies Oracle connection credential.	Required. Specifies TimesTen connection credential.
TimesTen database only	Required.Specifies TimesTen connection name.	Required. Specifies ORA.	Required. Specifies TimesTen connection credential.	Not required

 **Note:**
 You only need to specify a pseudo connection name which is used to indicate that you are using only TimesTen. This name is not actually used in your COBOL program.

Also, you need to set the following environment variables.

- LD_LIBRARY_PATH should include TimesTen library and the bundled instant client library.
- TNS_ADMIN should be set to the directory containing file tnsnames.ora, in which both TimesTen and Oracle TNS information should be included. For more information, see [Oracle TimesTen In-Memory Database](#) documentation.

2.20.2 Programming in COBOL

All EXEC SQL statements to Oracle database does not need to specify connection name; however, all operations to TimesTen should specify the TimesTen connection name as it is set in MT_TT_CONN .

2.20.3 Preprocessing COBOL Programs

In this feature, all COBOL programs accessing Oracle database or TimesTen database should be processed by TimesTen Pro*COBOL.

2.20.4 Examples

The following are the list of examples:

- [Example for Setting Environment Variables](#)
- [Example for COBOL Programs Accessing to Oracle Database](#)
- [Example for COBOL Programs Accessing to TimesTen Database](#)
- [Example for Preprocessing COBOL Programs](#)
- [Example for Compiling COBOL Programs \(CIT\)](#)

2.20.4.1 Example for Setting Environment Variables

Listing 2-34 Example for Setting Environment Variables

```
export MT_TT_CONN=TTNAME1
export MT_DB=ORA
export MT_DB_LOGIN=user1/pass1@oracle
export MT_DB_LOGIN2=user2/pass2@tt
export TIMESTEN_HOME=/opt/TimesTen/tt
export LD_LIBRARY_PATH=${TIMESTEN_HOME}/lib:${TIMESTEN_HOME}/ttoracle_home/
instantclient_11_2:${LD_LIBRARY_PATH}
```

2.20.4.2 Example for COBOL Programs Accessing to Oracle Database

Listing 2-35 Example for COBOL Programs Accessing to Oracle Database

```
EXEC SQL
SELECT B
INTO :H-VALUE-B
FROM ORATBL01
END-EXEC.
```

2.20.4.3 Example for COBOL Programs Accessing to TimesTen Database

Listing 2-36 Example for COBOL Programs Accessing to TimesTen Database

```
EXEC SQL DECLARE TTNAME1 DATABASE END-EXEC.
EXEC SQL
AT TTNAME1
SELECT NAME
INTO :H-VALUE-NAME
FROM TTTBL01
END-EXEC.
```

2.20.4.4 Example for Preprocessing COBOL Programs

Listing 2-37 Example for Preprocessing COBOL Programs

```
export LD_LIBRARY_PATH=${TIMESTEN_HOME}/ttoracle_home/instantclient_11_2;${
TIMESTEN_HOME}/ttoracle_home/instantclient_11_2/sdk/procob sqlcheck=syntax
lname=SELECTTT.lis iname=SELECTDB.pco oname=SELECTDB.cob
```

2.20.4.5 Example for Compiling COBOL Programs (CIT)

Listing 2-38 Example for Compiling COBOL Programs (CIT)

```
cobc -fthread-safe -m -g -G -fmf-gnt SELECTDB.cob -w -fixed -ffcdreg -  
lcitextfh -t SELECTDB.lst -conf=cit.conf
```

3

Best Practices

This chapter contains the following topic:

- [Adapting z/OS Capabilities on a UNIX/Linux Environment](#)

3.1 Adapting z/OS Capabilities on a UNIX/Linux Environment

Due to the fact that the Batch Runtime is generally used to execute Korn shell scripts issued from the migration of a z/OS JCL asset, several specific features are provided in order to reproduce some capabilities of z/OS.

The usage of some of these functions may not have a lot of sense in the target platform when modifying migrated jobs or writing new ones.

In this chapter, we present some of these features along with other best practices that we recommend.

- [Defining Paths for Procedures, Includes and Programs](#)
- [Prohibiting the Use of UNIX Commands](#)
- [Avoiding the Use of File Overriding](#)

3.1.1 Defining Paths for Procedures, Includes and Programs

In z/OS JCLs, the following cards are used to define the libraries where procedures, includes and programs are stored:

- JOBLIB, STEPLIB for programs.
- JCLLIB for procedures and steps.

Oracle Tuxedo Application Runtime for Batch offers the functions `m_JobLibSet`, `m_StepLibSet` and `m_JclLibSet` as a replacement to these statements.

Even if these functions provide the same functionality, for modified and new jobs we encourage you to adopt the UNIX common rule which is to directly set the environment variables where the programs, procedures and includes are searched for.

The main variables to set are:

- `PATH` : environment variable that specifies where to find executable programs.
- `COBPATH` : environment variable that specifies where to find object COBOL programs.
- `PROCLIB` : environment variable that specifies where to find procedures and includes.

3.1.2 Prohibiting the Use of UNIX Commands

In order to trap every possible error or abnormal end, it is better to avoid using basic UNIX commands (for example: `cp / ls / ...`).

We recommend that you use only the functions provided by the Batch Runtime.

3.1.3 Avoiding the Use of File Overriding

In order to keep jobs simple and understandable, we recommend you avoid the using of file overriding mechanism in new or modified jobs.

4

Using Tuxedo Job Enqueueing Service (TuxJES)

This chapter contains the following topics:

- [Overview](#)
- [Configuring a TuxJES System](#)
- [Using TuxJES](#)
- [Authorizing TuxJES Job Access](#)
- [Tracing TuxJES](#)

4.1 Overview

TuxJES addresses the following batch job phases:

- Input
- Conversion
- Processing
- Purge

The batch job system is an important mainframe business application model. The Tuxedo Job Enqueueing Service (TuxJES), emulation application provides smooth mainframe application migration to open systems. TuxJES implements a subset of the mainframe JES2 functions (for example, submit a job, display a job, hold a job, release a job, and cancel a job).

- [Requirements](#)
- [TuxJES Components](#)

4.1.1 Requirements

TuxJES is an Oracle Tuxedo application; Oracle Tuxedo is required in order to run TuxJES.

A shared file system (for example, NFS), is required in order to deploy TuxJES in distributed environment.

4.1.2 TuxJES Components

TuxJES includes the following key components:

- `genjesprofile`
Generates the security profile for Oracle Tuxedo applications
- `genjesacl`
Generates the encrypted job access authorization configuration file for TuxJES system:
- `artjesadmin`
TuxJES command interface. It is an Oracle Tuxedo client

- ARTJESADM
TuxJES administration server. It is an Oracle Tuxedo server.
- ARTJESCONV
TuxJES conversion server. It is an Oracle Tuxedo server.
- ARTJESINITIATOR
JobTuxJES Initiator. It is an Oracle Tuxedo server.
- ARTJESPURGE
TuxJES purge server. It is an Oracle Tuxedo server.

For more information, see the Oracle Tuxedo Application Runtime for Batch Reference Guide

4.2 Configuring a TuxJES System

This section contains the following topics:

- [Setting up TuxJES as an Oracle Tuxedo Application \(Using /Q\)](#)
- [Setting up TuxJES as an Oracle Tuxedo Application \(Using Database\)](#)
- [Setting Up TuxJES in MP Mode](#)

4.2.1 Setting up TuxJES as an Oracle Tuxedo Application (Using /Q)

TuxJES is an Oracle Tuxedo application. Most of the TuxJES components are Oracle Tuxedo client or Oracle Tuxedo servers. You must first configure TuxJES as an Oracle Tuxedo application. The environment variable `JESDIR` must be configured correctly which points to the directory where TuxJES installed.

- [Oracle Tuxedo Configuration File](#)
- [Oracle Tuxedo /Q Queue Space and Queue Creation](#)
- [File System Configuration](#)
- [TuxJES Configuration File](#)
- [TuxJES Security Configuration](#)
- [TuxJES User Mapping File](#)

4.2.1.1 Oracle Tuxedo Configuration File

The following Listing shows an Oracle Tuxedo configuration file (`UBBCONFIG`) example segment for a TuxJES system.

Listing 1 Oracle Tuxedo UBBCONFIG File Example for the TuxJES System

```
*GROUPS
QG
LMID=L1 GRPNO=2 TMSNAME=TMS_QM TMSCOUNT=2
OPENINFO="TUXEDO/QM:/jes2queue/QUE:JES2QSPACE"
ARTG
LMID=L1 GRPNO=4
EVTG
LMID=L1 GRPNO=8
*SERVERS
DEFAULT:
CLOPT="-A"
```

```

TMQUEUE
SRVGRP = QG SRVID = 1
RESTART = Y CONV = N MAXGEN=10
CLOPT = "-s JES2QSPACE:TMQUEUE -- -t 5 "
ARTJESADM SRVGRP =ARTG SRVID = 1 MIN=1 MAX=1
CLOPT = "-A -- -i jesconfig"
ARTJESCONV SRVGRP =ARTG SRVID = 20 MIN=1 MAX=1
CLOPT = "-A --"
ARTJESINITIATOR SRVGRP =ARTG SRVID = 30
CLOPT = "-A -- -c ABCDEFG"
ARTJESPURGE SRVGRP =ARTG SRVID = 100
CLOPT = "-A --"

```

The following TuxJES servers should be included in the Oracle Tuxedo configuration file (UBBCONFIG):

- ARTJESADM
- ARTJESCONV
- ARTJESINITIATOR
- ARTJESPURGE



Note:

Multiple instances of ARTJESADM , ARTJESCONV, ARTJESINITIATOR and ARTJESPURGE can be configured.

For the TuxJES administration server `ARTJESADM`, a TuxJES configuration file should be specified using the `-i` option. In the Oracle Tuxedo configuration file (UBBCONFIG), `ARTJESADM` should be configured in front of `ARTJESCONV`, `ARTJESINITIATOR`, or `ARTJESPURGE` servers.

For more information, see the Oracle Tuxedo Application Runtime for Batch Reference Guide

TuxJES uses the Oracle Tuxedo `/Q` component, therefore an Oracle Tuxedo group with an Oracle Tuxedo messaging server `TMQUEUE` with `TMS_QM` configured is required in the `UBBCONFIG` file. The name of the `/Q` queue space should be configured as `JES2QSPACE`.

A TuxJES system can be either an Oracle Tuxedo SHM application which runs on a single machine, or an Oracle Tuxedo MP application which runs on multiple machines.

For more information on how to set up Oracle Tuxedo application, see Oracle Tuxedo related documentation.

- [Block Time in UBBCONFIG for TuxJES](#)

4.2.1.1.1 Block Time in UBBCONFIG for TuxJES

For job operations (except for job submission), you can specify the number of timeout periods for blocking messages and other system activities by setting the `SCANUNIT` and `BLOCKTIME` parameter. The value you assign must be a positive multiple of 5.

Table 4-1 Characteristics of the SCANUNIT and BLOCKTIME Parameters

Parameter	Characteristics
SCANUNIT	Controls the granularity of checking intervals and timeouts. SCANUNIT must be a multiple of 5 and between 0 and 60 seconds. Example: SCANUNIT 20 The default is 10.
BLOCKTIME	BLOCKTIME controls how much time can a message block before it times out. SCANUNIT * BLOCKTIME must not exceed 32767. The default time of SCANUNIT * BLOCKTIME is approximately 60 seconds.

Listing 2 Example Settings

```
*RESOURCES
IPCKEY 113333
DOMAINID jesdomain
MASTER SITE1
MODEL SHM
MAXACCESSERS 200
MAXSERVERS 50
NOTIFY SIGNAL
SCANUNIT 20
BLOCKTIME 50
```

In this example, sanity scans are performed in every 20 seconds and request block for no more than $20 * 50 = 1000$ seconds.

For job submission, timeout is not controlled by BLOCKTIME and SCANUNIT, it is specified in the artjesadmin command line, for example:

```
artjesadmin -t 60 -i JOBA
```

In this example, if submission of JOBA cannot be finished in 60 seconds, timeout will be returned.

TuxJES relies on /Q to store or retrieve messages which represent jobs. The timeout mechanism for /Q operations inside TuxJES is only controlled by MAXTRANTIME in UBBCONFIG RESOURCES section.

You should explicitly specify the MAXTRANTIME in UBBCONFIG; otherwise, Tuxedo automatically uses the default value (this value may vary depending on Tuxedo release).

Set this MAXTRANTIME value based on the specific system loading. The following example sets MAXTRANTIME to 5 minutes.

Listing 3 Example: Use MAXTRANTIME to Control Timeout

```
*RESOURCES
IPCKEY 133770
DOMAINID jessample
MASTER SITE1
```

```
MODEL SHM
MAXTRANTIME 300 # 300 seconds
```

For more information about `MAXTRANTIME` in `UBBCONFIG RESOURCES` section, see [UBBCONFIG\(5\)](#) in Tuxedo documentation.

If any timeout occurs on /Q operation, like `tpdequeue()` or `tpenqueue()`, you can adjust `MAXTRANTIME` to accommodate it.

4.2.1.2 Oracle Tuxedo /Q Queue Space and Queue Creation

A /Q queue space with name `JES2QSPACE` must be created for a TuxJES system (some /Q queues should be created within this queue space). TuxJES provides a sample shell script (`jesqinit`) to create the queue space (`JES2QSPACE`) and the queues. For more information, see the Oracle Tuxedo Application Runtime for Batch Reference Guide

4.2.1.3 File System Configuration

TuxJES uses a file system to communicate with Batch Execution Engine. A directory is created on the file system for the communication between TuxJES and Batch Execution Engine. The name of the directory should be specified in the TuxJES configuration file. This directory should reside at a shared file system (for example, NFS), if you want to deploy the TuxJES system on multiple machines.

4.2.1.4 TuxJES Configuration File

A configuration file can be specified for the TuxJES administration server `ARTJESADM`. The following parameters can be configured in the configuration file:

JESROOT

The root directory to store job information. It is a mandatory attribute. If this directory does not exist, `ARTJESADM` creates it automatically.

DEFAULTJOBCLASS

The default job class if the job class is not set in JCL. It is an optional attribute. The default job class is `A` if this attribute is not set.

DEFAULTJOBPRIORITY

The default job priority if the job priority is not set in JCL. It is an optional attribute. The default job priority is `0` if this attribute is not set.

DUPL_JOB=NODELAY

If it is not set, only one job can be in execution status for a job name. `NODELAY` will remove the dependency check. The default value is delay execution.

NJESUPPORT=ON

If it is not set, NJE support will be disabled and thus jobs cannot be run on the specified server group by Batch Runtime API `m_JobSetExecLocation`. The default value is `OFF`.

EVENTPOST=S,C,E,P,L,A

Specifies whether events are posted for a job at particular stages.

S: Job submission event.

C: Job conversion complete event.

E: Job execution complete event.

P: Job purge event.

L: Job cancel completed event.

A: all supported events

If `EVENTPOST` is not specified, no events are posted. The data buffer with event post is `FML32` type and the fields are defined in `tuxjes/include/jesflds.h`.

JES_ACL_FILE

The full path of job access authorization configuration file. This file can be plain or encrypted, see `JES_ACL_FILE_TYPE` for more information.

JES_ACL_FILE_TYPE

The format of `JES_ACL_FILE` file. It can be set as `PLAIN` or `ENCRYPTED` (case insensitive). The default value is `PLAIN`.

JES_ACL_MODE

The action when no matching rule is found for the tuple of user, operation, and job in `JES_ACL_FILE`. It can be set as `MAC` (Mandatory Access Control) or `DAC` (Discretionary Access Control). The default value is `MAC`.

JOBLANG

JCL or KSH.

JCL: support JCL job, user can only submit JCL job.

KSH: support KSH job, user can only submit KSH job.

Not set: act as if `KSH` is set.

JOBREPOSITORY

The path of the job repository where jobs are stored. The script file path inputted in job submitting may be a relative path in `JOBREPOSITORY` if it is set.

You can specify multiple path names, delimit them with a colon (:). For example, `JOBREPOSITORY=<path1>:<path2>:<path3>`. To find job to submit, Batch Runtime searches from these paths in the order that you specify (in `JOBREPOSITORY`). When finding a job name match, Batch Runtime stops searching, and submits this matched job.

PRIVILEGE_MODE

Specifies whether and how to enable the user substitution (See [TuxJES User Substitution](#)). The values are:

`NONE`: Default value. Indicates jobs are executed by the OS user who starts JES system. This is compatible with all previous implementations on JES system.

`USER_IDENTICAL`: Indicates jobs are executed by the Oracle Tuxedo user with which JES client joins JES system. Make sure that each Oracle Tuxedo user corresponds to an existing OS user before you choose this value.

USER_MAPPING: When this value is specified, the JES system looks up the TuxJES user mapping file and finds out the OS user corresponding to the Oracle Tuxedo user with which JES client joins JES system, and then appoints this OS user as the job executor.

USE_COBOL_SERVER

If it is set to **Y**, TuxJES COBOL server (`ARTJESCOBOLDB2MF/ARTJESCOBOLDB2CIT`) invokes user program; if it is set to **N** or if it is not set, TuxJES COBOL server does not invoke user program. `USE_COBOL_SERVER` configuration is only supported for JCL job in Database mode.

USER_MAPPING_FILE

The full path where TuxJES user mapping file is stored. It is used along with `PRIVILEGE_MODE` when its value is `USER_MAPPING`.

USE_DB

ORACLE or DB2.

ORACLE: Use Oracle Database to store job management data.

DB2: (not supported) Use DB2 Database to store job management data.

Not set: Use /Q to store job information.

SYSLOG=OFF, ON, DAILY, WEEKLY, MONTHLY

OFF: Specifies no logs.

ON: Specifies writing to `SYSLOG`. Default value. The `SYSLOG` is entitled "jessys.log". You can change its path from the default "\$JESROOT/jessys.log" to other directories by using `SYSLOG_PATH`.

DAILY: Specifies writing to `SYSLOG`. A new log file is created daily. The `SYSLOG` is entitled "jessys.log.<mmddy>". For example, the `SYSLOG` entitled "jessys.log.032715" stands for the log file created for the day of March 27, 2015. You can change its path from the default "\$JESROOT/jessyslog/jessys.log.<mmddy>" to other directories by using `SYSLOG_PATH`.

WEEKLY: Specifies writing to `SYSLOG`. A new log file is created weekly. The `SYSLOG` is entitled "jessys.log.<mmddy>", where the "dd" means the first day of current week (Sunday is the first day of the week). For example, the `SYSLOG` entitled "jessys.log.032215" stands for the log file created for the week from March 22, 2015 (Sunday) to March 28, 2015 (Saturday). You can change its path from the default "\$JESROOT/jessyslog/jessys.log.<mmddy>" to other directories by using `SYSLOG_PATH`.

MONTHLY: Specifies writing to `SYSLOG`. A new log file is created monthly. The `SYSLOG` is entitled "jessys.log.<mmddy>", where the "dd" means the first day of current month. For example, the `SYSLOG` entitled "jessys.log.030115" stands for the log file created for the month of March 2015. You can change its path from the default "\$JESROOT/jessyslog/jessys.log.<mmddy>" to other directories by using `SYSLOG_PATH`.

SYSLOG_PATH

Specifies the path of `SYSLOG` files.

When `SYSLOG=ON` is set, you get the `SYSLOG` entitled "\$SYSLOG_PATH/jessys.log" and located in the directory where you specify through this `SYSLOG_PATH`.

When `SYSLOG=DAILY, WEEKLY, MONTHLY` is set, you get the `SYSLOG` entitled "\$SYSLOG_PATH/jessys.log.<mmddy>" and located in the directory where you specify through this

SYSLOG_PATH. The "jessys.log.<mmddy>" confirms to the naming rules for SYSLOG=DAILY, WEEKLY, MONTHLY.

If you do not specify **SYSLOG_PATH**, the **SYSLOG** files are still located in `$JESROOT/jessyslog` (when **SYSLOG** is set to **DAILY**, **WEEKLY**, or **MONTHLY**) or `$JESROOT` (when **SYSLOG** is set to **ON**) by default.

QSPACE_THRESHOLD

Percentage: 1 ~ 99. This is a threshold value for queue space usage rate, while the usage of queue space reach this threshold, new job can be submitted but warning message will be shown in the output of `artjesadmin`. And auto purge will be performed if it is enabled. The default is 80.

AUTOPURGE

Integer number: 0 ~ 32767 ($2^{15}-1$).

0: Disable the automatic purging. Default value.

$N(>=1)$: Enable the automatic purging and purge the first finished N Jobs one time.

If $N>=(\text{size of OUTPUT queue})$, all the jobs in **OUTPUT** queue are purged.

AUTOPURGE_KEEFILES

ON: Backup folder `<JESROOT>/<JOB_ID>` to `<JESROOT>/<JOB_ID>.bak` while automatic purging, just delete the relevant message from "OUTPUT" queue.

If **AUTOPURGE=0**, this item is ignored. Default value.

OFF: Delete all the files belong to the job (in folder `<JESROOT>/<JOB_ID>`) while automatic purging.

Listing 4 jesconfig Example

```
JESROOT=/nfs/users/john_doe/jreroot
DEFAULTJOBCLASS=B
DEFAULTJOBPRIORITY=9
EVENTPOST=S,C,E,P,L,A
QSPACE_MAX_USAGE=80
AUTOPURGE=10
AUTOPURGE_KEEFILES=ON
```

Note:

If the usage rate of queue space reaches 80%, the first finished 10 jobs are automatically purged.

For the automatically purged job, all the files in folder "`<JESROOT>/<JOB_ID>`" is backed up as "`<JESROOT>/<JOB_ID>.bak`"

4.2.1.5 TuxJES Security Configuration

TuxJES leverages the Oracle Tuxedo security mechanism to implement authentication. If authentication is enabled, a security profile should be generated using the `genappprofile` utility

and it should be used as a `artjesadmin` parameter to access the TuxJES system. The user used in the profile will be the job owner. A job only can be administrated by its owner, such as cancel, purge, hold and release. A job can be viewed by everybody. If a job is without owner, it can be manipulated by everyone.

Even if an Oracle Tuxedo application does not have security configured, the `genjesprofile` utility still can be used to enforce job owner permission checking and store the database connection `MT_DB_LOGIN`.

Based on this security mechanism, ART for Batch provides a lightweight job access authorization mechanism to control user's job operation actions. This authorization only needs simple configuration without involving any authorization server or even third-party security product. For more information, see [Authorizing TuxJES Job Access](#).

4.2.1.6 TuxJES User Mapping File

User mapping file is loaded and takes effect when `PRIVILEGE_MODE` value is specified to `MAPPING_CREDENTIAL`. It defines the mapping relationship between Oracle Tuxedo users and OS users. Every line in the mapping file is in the format as below:

```
tuxedousername OSusername
```

It is recommended that the owner of user mapping file is root and the file permission is "`rw-----`".

The following Listing shows a segment example of user mapping file for the TuxJES system.

Listing 5 User Mapping File Example For the TuxJES System

```
tuxedouser1 OSuser1  
tuxedouser2 OSuser2
```

4.2.2 Setting up TuxJES as an Oracle Tuxedo Application (Using Database)

This section contains the following topics:

- [Setting Up TuxJES](#)
- [Setting Up Oracle Database](#)
- [Setting Up DB2 Database](#)
- [Setting Up BDB Database](#)

4.2.2.1 Setting Up TuxJES

As an alternative of `/Q`, TuxJES can use Database to store and manage metadata of Batch jobs. In this mode, TuxJES does not need `/Q` anymore, providing better performance and full data consistency.



Note:

Now only Oracle Database is supported.

- [UBBCONFIG](#)
- [JESCONFIG](#)

4.2.2.1.1 UBBCONFIG

TuxJES uses Database to store jobs rather than /Q; therefore, you do not need to use group for /Q and server `TMQUEUE/TMS_QM` any more. All other servers and groups are not impacted.

4.2.2.1.2 JESCONFIG

A new configuration item named `USE_DB` is added in `JESCONFIG` file to enable Database usage. The following table lists `USE_DB` values. Listing 6 shows an example.

Table 4-2 USE_DB Values

Name	Value	Description
USE_DB	ORACLE	Use Oracle Database to store job management data.
	DB2	Use DB2 as storage to store job information.
	BDB	Use BDB as storage to store job information.
	NOT SET	Use /Q to store job information.

Note:

- `autopurge` is not supported in Database mode; all the setting for `autopurge` will be ignored.
- NJE is not supported in Database mode.
- All other settings are the same as in /Q mode.

Listing 6 JESCONFIG Example

```
JESROOT=/nfs/users/john_doe/jreroot
USE_DB=ORACLE
DEFAULTJOBCLASS=B
DEFAULTJOBPRIORITY=9
EVENTPOST=S,C,E,P,L,A
```

4.2.2.2 Setting Up Oracle Database

This section contains the following topics:

- [Getting Database Credential](#)
- [Create Tables](#)
- [Set Up Database TAF for Oracle \(Optional\)](#)

4.2.2.2.1 Getting Database Credential

When using Database as storage, connection information is necessary. It is encrypted and stored in a separate hidden file under `JESROOT` directory (`JESROOT/.jessysprofile`). `gensysprofile` utility is used to generate this file.

Its usage is:

```
gensysprofile -d <JESROOT>
```

When `gensysprofile` is launched, you are prompted to enter the user name, password, (Database) server name, and DB schema. Show prompt on the screen:

Listing 7 Screen Prompt

User name:

Password:

Server name:

DB Schema (Optional):

(Database) Server name string indicates the location where Database server can be found and is normally the name of the Database instance. The syntax is the same as the one used to set the `TWO_TASK` environment variable. Its format is either of the following:

- `//host:port/server_name`
- `instance_name`

For example, you can use either `orcl12c`, or `//bej301420.cn.myexample.com:1522/orcl.cn.myexample.com`.

The output is a hidden file `.jessysprofile` under `JESROOT` directory.

DB Schema is an optional parameter for user to input. If it is specified, TuxJES stores and manages metadata of Batch jobs in specified schema.

Note:

- If your Database does not exist at the location and must go through `SQLNET` to connect to it, you should specify host, port, and server_name in the format of `//host:port/server_name`.
- Only JES administrator or OS root user can run `gensysprofile`.

4.2.2.2.2 Create Tables

To use Oracle Database to store job management data, you must first create table `JES2_JOBNUM` and `JES2_JOB_PARAM`. Two external shell scripts are provided for you to create and drop these two tables. The two scripts are located at `$JESDIR/tools`.

- `CreateTableJobDataOra.sh`
This shell script creates table `JES2_JOB_PARAM` and create index on field `JOBNAME`, `CLASS`, `PRTY`, `STATUS`, `SUBMITTIME`, `GRPID`, and `SRVID`; it also creates table `JES2_JOBNUM` and initialize the record in the `JES2_JOBNUM`. Schema name is an optional parameter. If schema name is specified, table `JES2_JOBNUM` and table `JES2_JOB_PARAM` are created in specified schema. Its usage is:

```
CreateTableJobDataOra.sh <DB_LOGIN_PARAMETER> <schema>
```

- `DropTableJobDataOra.sh`

This shell script drops table `JES2_JOBNUM` and table `JES2_JOB_PARAM`. Schema name is an optional parameter. If schema name is specified, table `JES2_JOBNUM` and table `JES2_JOB_PARAM` are dropped in specified schema. Its usage is:

```
DropTableJobDataOra.sh <DB_LOGIN_PARAMETER> <schema>
```

4.2.2.2.3 Set Up Database TAF for Oracle (Optional)

If Oracle Database TAF (Transparent Application Failure) is enabled, when Database server crashes, after Database recovery, TuxJES can provide service continuously with no need for restarting TuxJES domain. If TAF is not enabled, once Database connection is broken, you must restart TuxJES domain after Database recovery.

You can configure TAF on both the client side and the server side. If both are configured, server-side settings take precedence.

For TAF configuration, see *Oracle Database documentation* for more information. The following is simple description of TAF.

Configure TAF on the client side by including the `FAILOVER_MODE` parameter in the `CONNECT_DATA` portion of a connect descriptor.

Configuring TAF option on the client side requires you to add Oracle Net parameters to `tnsnames.ora` file. The parameter that drives the TAF option is the `FAILOVER_MODE` under the `CONNECT_DATA` section of a connect descriptor. `FAILOVER_MODE` may contain the following parameters:

Table 4-3 `tnsnames.ora` File Parameters

Parameter	Description
TYPE	Specifies the type of failover.
METHOD	Determinates how fast failover occurs from the primary node to the backup node.
BACKUP	Specifies a different net service name for backup connections.
RETRIES	Specifies the number of times to attempt to connect.
DELAY	Specifies the amount of time in seconds to wait between connect attempts.

The following Listing shows a sample. In this sample, failover type `session` and method `basic` are configured for `FAILOVER_MODE`.

Listing 8 Sample Configuration for Failover

```
TNSNAMES.ora
ART =
(DESCRIPTION =
(AADDRESS_LIST =
(ADDRESS = (PROTOCOL = TCP)(HOST = bej301738.cn.myexample.com)(PORT = 1521))
(LOAD_BALANCE = yes)
)
(CONNECT_DATA =
(SERVER = DEDICATED)
(SERVICE_NAME = art)
(FAILOVER_MODE =
(TYPE = session)
(METHOD = basic)
```

```
)
)
)
```

4.2.2.3 Setting Up DB2 Database



Note:

You should configure `USE_DB=DB2` in `JESCONFIG`. See [Setting Up TuxJES](#) for more information.

Do the followings to set up DB2 database:

- [Getting Database Credential](#)
- [Creating Tables](#)
- [Managing Job in DB2](#)

4.2.2.3.1 Getting Database Credential

When using Database as storage, connection information is necessary. It is encrypted and stored in a separate hidden file under `JESROOT` directory (`JESROOT/.jessysprofile`). Use `jessysprofile` utility to generate this file.

Its usage is:

```
jessysprofile -d <JESROOT>
```

Listing 9 shows a sample.

Listing 9 Sample for Getting DB2 Database Credential

```
jessysprofile -d /home/testuser1/work_batchrt/jesroot
jessysprofile will create a profile "/home/testuser1/work_batchrt/
jesroot/.jessysprofile"
User name (0~30 characters):db2b004
User Password (0~31 characters):
Confirm User Password (0~31 characters):
Database instance name:artbatch
DB Schema(Optional):db2b002
/home/testuser1/work_batchrt/jesroot/.jessysprofile is created successfully
```



Note:

DB Schema is an optional parameter for user to input. If it is specified, TuxJES stores and manages metadata of Batch jobs in specified schema.

4.2.2.3.2 Creating Tables

Use the following command line to create necessary tables in DB2.

```
$JESDIR/tools/CreateTableJobDataDb2.sh <DB CONN STRING> <schema>
```

You can use the following command line to remove these tables:

```
$JESDIR/tools/DropTableJobDataDb2.sh <DB CONN STRING> <schema>
```

The following Listing shows a sample for creating tables in DB2.

Listing 10 Sample for Creating Tables in DB2

```
$JESDIR/tools/CreateTableJobDataDb2.sh "artbatch user db2b004 using db2b004"
<<omit some msg here>>
db2 => db2 (cont.) => db2 (cont.) => CREATE TABLE JES2_JOBNUM ( JOBNUM INT )
DB20000I The SQL command completed successfully.

db2 => INSERT INTO JES2_JOBNUM VALUES ('0')
DB20000I The SQL command completed successfully.

db2 => db2 (cont.) => db2 (cont.) => db2 (cont.) => db2 (cont.) => db2
(cont.) => db2 (cont.) => db2 (cont.) => db2 (cont.) => db2 (cont.) => db2
(cont.) => db2 (cont.) => db2 (cont.) => db2 (cont.) => db2 (cont.) => db2
(cont.) => db2 (cont.) => db2 (cont.) => db2 (cont.) => db2 (cont.) => db2
(cont.) => db2 (cont.) => db2 (cont.) => db2 (cont.) => db2 (cont.) => db2
(cont.) => db2 (cont.) => db2 (cont.) => db2 (cont.) => db2 (cont.) => db2
(cont.) => db2 (cont.) => db2 (cont.) => db2 (cont.) => db2 (cont.) => db2
(cont.) => db2 (cont.) => db2 (cont.) => db2 (cont.) => db2 (cont.) => CREATE
TABLE JES2_JOB_PARAM ( JOBID INT NOT NULL, JOBNAME VARCHAR(32), CLASS INT,
PRTY INT, STATUS VARCHAR(32), SUBMITTIME INT, TYPRUN VARCHAR(8), OWNER
VARCHAR(32), JOBTYP VARCHAR(3), EXECGRP VARCHAR(32), MACHINE INT, GRPID INT,
SRVID INT, SRVPID INT, EXECTIME INT, ENDTIME INT, JOBPID INT, JOBR
VARCHAR(5), USRSEC INT, USRUSEC INT, SYSSEC INT, SYSUSEC INT, JOBSRIPT
VARCHAR(2048), EJROPTION VARCHAR(128), SHELLOPTIO VARCHAR(128), INPUTTYPE
INT, CLIENTMODE VARCHAR(32), CLTIDDATA1 INT, CLTIDDATA2 INT, CLTIDDATA3 INT,
CLTIDDATA4 INT, PROFILECONTENT VARCHAR(1024), JOBENV VARCHAR(1024), Reserve1
INT, Reserve2 INT, Reserve3 VARCHAR(128), Reserve4 VARCHAR(128), CONSTRAINT
PK_JES2_JOB_PARAM PRIMARY KEY (JOBID) )
DB20000I The SQL command completed successfully.

db2 => CREATE INDEX JES2_JOB_PARAM_JNAME on JES2_JOB_PARAM (JOBNAME)
DB20000I The SQL command completed successfully.

db2 => CREATE INDEX JES2_JOB_PARAM_CLASS on JES2_JOB_PARAM (CLASS ASC)
DB20000I The SQL command completed successfully.

db2 => CREATE INDEX JES2_JOB_PARAM_PRTY on JES2_JOB_PARAM (PRTY DESC)
DB20000I The SQL command completed successfully.

db2 => CREATE INDEX JES2_JOB_PARAM_STATUS on JES2_JOB_PARAM (STATUS)
DB20000I The SQL command completed successfully.

db2 => CREATE INDEX JES2_JOB_PARAM_SUBTIME on JES2_JOB_PARAM (SUBMITTIME ASC)
DB20000I The SQL command completed successfully.

db2 => CREATE INDEX JES2_JOB_PARAM_GRPID on JES2_JOB_PARAM (GRPID)
DB20000I The SQL command completed successfully.

db2 => CREATE INDEX JES2_JOB_PARAM_SRVID on JES2_JOB_PARAM (SRVID)
DB20000I The SQL command completed successfully.
```

```
db2 => commit
DB20000I The SQL command completed successfully.

db2 => DB20000I The TERMINATE command completed successfully.
```

4.2.2.3.3 Managing Job in DB2

Do the following to use this feature.

- **Setting DB2 Environment**
DB2 environment must be ready before you boot JES domain. Suggest using `db2profile`, such as `$source /home/db2b004/sql/lib/db2profile`, or setting `LD_LIBRARY_PATH` and `PATH` (and other DB2 environment variables one by one). See *DB2 documentation* for more information.
- **Booting JES Domain**
Run `tmboot` to start JES domain, and then use `artjesadmin` to submit or manage job.

4.2.2.4 Setting Up BDB Database



Note:

You should configure `USE_DB=BDB` in `JESCONFIG`. See *Setting Up TuxJES* for more information.

Do the followings to set up BDB database:

- [Getting Database Credential](#)
- [Creating Tables](#)

4.2.2.4.1 Getting Database Credential

When using Database as storage, connection information is necessary. It is encrypted and stored in a separate hidden file under `JESROOT` directory (`JESROOT/.jessysprofile`). Use `gensysprofile` utility to generate this file.

Its usage is:

```
gensysprofile -d <JESROOT>
```

Because there is no username and password in BDB, you should leave the `username` field and the `password` field blank and directly press `ENTER`. For the `instance name` field, you should input the file name of BDB DB file (and do not include path). For example, if BDB DB file is `"/home/testuser1/appdir/jesroot/jesbdb"`, the corresponding database instance name should be `"jesbdb"`.

4.2.2.4.2 Creating Tables

Use the following command line to create necessary tables in BDB. For BDB, the database is a file on disk, and this file must be placed in folder `<JESROOT>`.

```
$JESDIR/tools/CreateTableJobDataBdb.sh <BDB FILE FULL PATH>
```

For example,

```
$JESDIR/tools/CreateTableJobDataBdb.sh "/home/testuser1/appdir/jesroot/jesbdb"
```

You can use the following command line to remove these tables:

```
$JESDIR/tools/DropTableJobDataBdb.sh <BDB FILE PATH>
```

4.2.3 Setting Up TuxJES in MP Mode

TuxJES now can be easily configured within MP mode. For the purpose of running job, however, the configuration in both EJR and TuxJES need to be adjusted so that jobs can be run in parallel on different machines. This section clarifies the configuration mandatory for configuring Batch Runtime in MP mode.

Being shared by all the servers on different machines in a TuxJES domain, the data of jobs should be located on a shared storage (NFS), and can be accessible by all machines in the domain. In addition, the NFS should be mounted with the same mount point on all machines. Finally, `JESROOT` should be configured correctly on each node to point to the shared JES Root Directory. During runtime, all the TuxJES servers on any machine would write data to or get data from such shared `JESROOT`.

For the details of configuring EJR in MP mode, see “[Configuring Batch Runtime in MP Mode](#)” under “Using Batch Runtime”.

4.3 Using TuxJES

After the TuxJES system starts, you can use the `artjesadmin` utility to submit a job, hold a job, release a job, cancel a job, purge a job, display the job information, or subscribe event for job status change.

- [Submitting a Job](#)
- [Displaying Job Information](#)
- [Holding a Job](#)
- [Releasing a Job](#)
- [Canceling a Job](#)
- [Purging a Job](#)
- [Displaying/Changing ARTJESINITIATOR Configuration](#)
- [Controlling ARTJESINITIATOR Servers](#)
- [Event Subscribing/Unsubscribing](#)

4.3.1 Submitting a Job

You can submit a job using the `artjesadmin` subcommand `submitjob` :

```
submitjob (smj) -i|-I scriptfilename [-t timeout] [-o ejr option]
```

`-i scriptfilename`: **The script file.**

`-I scriptfilename`: **The option specified to submit JCL jobs.**

`-t timeout`: **Specifies to control the timeout threshold when submitting a job.**

`-o ejr option`: **Specifies the options passed to the EJR script file.**

You can submit a job synchronously by using `artjesadmin -y` option.

For more information, see `artjesadmin` in *Oracle Tuxedo Application Runtime for Batch Reference Guide*.

4.3.2 Displaying Job Information

You can display the information of a job or a series of jobs using the `artjesadmin` subcommand `printjob` :

```
printjob(ptj) -n jobname | -j jobid | -c job_class |-a [-v] [-m] | -l
```

`-n jobname`: Display jobs with given job name

`-j jobid`: Display a particular job information

`-c job_class`: Display a particular class jobs information

`-a`: Display all jobs

`-v`: Verbose mode

`-m`: Print the CPU time usage of each step in one JOB

`-l`: Display the number of jobs for each job class in each job status type



Note:

`-l` option is not supported when you use `/Q` to store and manage metadata of Batch jobs.

The output of the `printjob` subcommand includes:

- **JOBNAME**: The job Name
- **JobID**: The Job ID generated by TuxJES system
- **Owner**: The submission user of the job
- **PrtY**: Priority of the job
- **C**: Job Class
- **Status**: Job Status
 - EXECUTING: a job is running
 - CONVING: a job waiting for conversion
 - WAITING: a job waiting for execution
 - DONE: a job finished successfully
 - FAIL: a job finished but failed
 - HOLD_WAITING: a job is in hold state after conversion
 - HOLD_CONVING: a job is in hold state without conversion
 - INDOUBT: a job is in doubt state due to its initiator restarted
 - CANCELED: a job is canceled
- **Submit time**: The submit time of the job
- **Step**: The current running job step. It is only applicable to running jobs.

- **Type Run:** The `TYPRUN` definition of the job.
- **Machine:** Only for running/done/failed jobs. It is the machine name that the job is/was running on.
- **CPU usage:** The user CPU usage and system CPU usage for the job execution.
- **Result:** Job operation result, "OK" or error message.

 **Note:**

If there are too many jobs in JES2 system, printing all jobs' status in console may lead to time out; to avoid this situation, users need to configure long enough block time in `ubbconfig` of JES.

For more information about how to set block time, please refer to [Block Time in UBBCONFIG for TuxJES](#).

- [Getting Job Status \(Synchronous\)](#)

4.3.2.1 Getting Job Status (Synchronous)

You can get job status synchronously by using `artjesadmin` in the following format:

```
artjesadmin [-f [security_profile]] -p -j jobid
```

`-p` and `-j`

Option `-p` and `-j` are added to get job status without interaction in `artjesadmin` console.

Exit Code

The following table lists the exit codes for `artjesadmin` if `-p`.

Table 4-4 Exit Code

Exit Code	Description	Notes
0	Job is finished normally. Job status = DONE	A job is finished successfully.
1	Command execution fails.	The failure is caused by an internal error, a network error, or a syntax error.
3	Job status = FAIL	JOB execution fails.
4	Job status = CANCEL	A job is canceled.
5	Job status = CONVING	A job is waiting for conversion.
6	Job status = EXECUTING	A job is running.
7	Job status = HOLD_CONVING	A job is in hold state without conversion.
8	Job status = HOLD_WAITING	A job is in hold state after conversion.
9	Job status = WAITING	A job is waiting for execution.
10	Job status = DISCARD	This status will occur if <code>tpenqueue ()</code> fails.
11	Job status = INDOUBT	When a job is running, if JES server <code>ARTJESINITIATOR</code> is shutdown and then restarted, the job status will be INDOUBT.

Table 4-4 (Cont.) Exit Code

Exit Code	Description	Notes
22	Job doesn't exist.	N/A

Standard Output

Information shown in Table 5 is printed to stdout in the following format.

```
<JOBID>,<JOBNAME>,<JOBSTATUS>,<JOB RETURN CODE>
```

Table 4-5 Standard Output

Output Content	Description	Sample
<JOBID>	Job ID	00005097
<JOBNAME>	Job name	JOBA
<JOBSTATUS>	Job current status	DONE
<JOB RETURN CODE>	Job return code from EJRC (only available if a job has finished)	C000

Listing 11 Sample: Job has been Finished Normally

```
00000002,JOBA,DONE,C0000
```

Listing 12 Sample: Job is Finished but Fails

```
00000002,JOBA,FAILED,U0568
```

Listing 13 Sample: Job is Running

```
00000002,JOBA,EXECUTING
```

4.3.3 Holding a Job

You can hold a job or a series of jobs which are in `CONVING` or `WAITING` status using the `artjesadmin` subcommand `holdjob` :

```
holdjob(hj) -n job name | -j jobid | -c job_class | -a
```

-n jobname: hold jobs with given job name

-j jobid: hold a particular job

-c job_class: hold a particular class jobs

-a: hold all jobs

4.3.4 Releasing a Job

You can release a job or a series of jobs which are in `HOLD_WAITING` or `HOLD_CONVING` status using the `artjesadmin` subcommand `releasejob`:

```
releasejob(rlj) -n job name | -j jobid | -c job_class | -a
```

-n jobname: release jobs with given job name

-j jobid: release a particular job
-c job_class: release a particular class jobs
-a: release all jobs

4.3.5 Canceling a Job

You can cancel a job or a series of jobs using the `artjesadmin` subcommand `canceljob`:

```
canceljob(cj) -n job name | -j jobid | -c job_class | -a  
-n jobname: cancel jobs with given job name  
-j jobid: cancel a particular job  
-c job_class: cancel a particular class jobs  
-a: cancel all jobs
```

4.3.6 Purging a Job

You can purge a job or a series of jobs using the `artjesadmin` subcommand `purgejob` :

```
purgejob(pgj) -n job name | -j jobid | -c job class | -s job status | -a  
-n jobname: purge jobs with given job name  
-j jobid: purge a particular job  
-c job class: purge jobs with given job class  
-s job status: purge jobs with given job status  
-a: purge all jobs
```

Completed jobs in the `DONE` or `FAIL` status are moved to the purge queue. For other jobs, `purgejob` has same effect as `canceljob`. The `purgejob` command does not purge the job directly. The `ARTJESPURGE` server deletes the job from the TuxJES system.

- [Automatic Job Purge](#)

4.3.6.1 Automatic Job Purge

When all the "available space" in queue space is occupied, any new job can't be submitted. To enable new job submission, users need to manually purge some jobs to decrease the usage rate. But this may introduce inconvenience and big effort to the application administrator. Another enhancement, Automatic Purging, can be introduced. With automatic purging enabled, whenever queue space usage rate reaches the warn level threshold, a specified count of jobs in `OUTPUT` queue are purged automatically. Automatic purging can be enabled or disabled (by default), and users can choose to backup files of all the jobs purged automatically or delete them permanently.

 **Note:**

Auto purge only happen at the time point after one job is inserted into queue space successfully and the queue usage reach the warning threshold. If there is no job exists in the OUTPUT queue in this time point, no job will be purged automatically. As an extreme case, after one job is submitted, the status of queue space changed to "available space are all occupied" and "no job in OUTPUT queue", no job can be purged automatically by this last job submission, in this situation, auto purge will never be performed, user must purge some job manually, otherwise no new job can be submitted.

If job submission failed, auto purge will not be activated.

Auto purge doesn't impact the current job submission.

JES system doesn't do auto purge in the background in any other form, such as check with a fixed interval.

OEM integration using TSAMPlus plug-in supports auto-archive of job logs and sysouts. If the jobs are purged, the key job information and job logs are available in the EM management repository.

The check action for queue space usage only happen at the time point after one job is inserted into queue space successfully. Only job submission can activate this check action. If job submission failed, this check action will not be activated.

The check result does not impact the current job submission.

JES system does not check queue space usage in the background in any other form, such as check with a fixed interval.

- [Set Warning Threshold for Queue Space](#)

4.3.6.1.1 Set Warning Threshold for Queue Space

Set a warning threshold for usage rate of the queue space. This threshold can be configured in file "jesconfig". When submit a new job, JES will check current usage rate of the queue space, if it has reached the warning threshold:

1. Activate auto purge if it's enabled in jesconfig file
2. One line warning message is output to artjesadmin console following the "job submitted successfully" message, which indicate user to purge some jobs. Or show how many jobs has been auto purged (if auto purge is enabled).

This feature depends on one new feature of tuxedo /Q: return current queue space usage rate in percentage.

 **Note:**

The check action for queue space usage only happen at the time point after one job is inserted into queue space successfully. Only job submission can activate this check action.

If queue space is greater than warning threshold but is little than 100, that is "available space" has not been exhausted, new job submission is permitted, but warning message will be outputted in artjesadmin console.

If job submission failed, this check action will not be activated.

The check result doesn't impact the current job submission.

JES system does not check queue space usage in the background in any other form, such as check with a fixed interval.

4.3.7 Displaying/Changing ARTJESINITIATOR Configuration

You can display the number of maximum concurrent ARTJESINITIATOR server executing jobs using the `artjesadmin` subcommand **printconcurrent** :

```
printconcurrent(pco) -g groupname -i serverid
```

`-g groupname`: the Tuxedo group name of the ARTJESINITIATOR server

`-i serverid`: the Tuxedo server id of the ARTJESINITIATOR server

You can change the number of maximum concurrent ARTJESINITIATOR server executing jobs using the `artjesadmin` subcommand **changeconcurrent**:

```
changeconcurrent(chco) -g groupname -i serverid -n concurrent_num
```

`-g groupname`: the Tuxedo group name of the ARTJESINITIATOR server

`-i serverid`: the Tuxedo server id of the ARTJESINITIATOR server

`-n concurrent_num`: the number of maximum concurrent executing jobs

4.3.8 Controlling ARTJESINITIATOR Servers

You can display the number of ARTJESINITIATOR server executing jobs using the `artjesadmin` subcommand **showjobexec**:

```
showjobexec(she) [-n machine] | [-g groupid [-i serverid]]
```

-n machine

The Tuxedo logic machine name running ARTJESINITIATOR server.

-g groupid:

The Tuxedo group id of the ARTJESINITIATOR server

`-i serverid:`

The Tuxedo server id of the `ARTJESINITIATOR` server

 **Note:**

If no option is specified, executing jobs for all `ARTJESINITIATOR` servers are displayed.

You can stop `ARTJESINITIATOR` servers from picking up a new job to execute; however, servers continue finishing current jobs.

```
stopjobexec(ste) [-n machine] | [-g groupid [-i serverid]]
```

-n machine:

The Tuxedo logic machine name running `ARTJESINITIATOR` server.

-g groupid:

The Tuxedo group id of the `ARTJESINITIATOR` server.

-i serverid:

The Tuxedo server id of the `ARTJESINITIATOR` server.

 **Note:**

If no option is specified, all `ARTJESINITIATOR` servers stop picking up new jobs.

You can resume `ARTJESINITIATOR` server pick up and new job execution.

```
resumejobexec(rse) [-n machine] | [-g groupid [-i serverid]]
```

-n machine:

The Tuxedo logic machine name running `ARTJESINITIATOR` server.

-g groupid:

The Tuxedo group id of the `ARTJESINITIATOR` server

-i serverid:

The Tuxedo server id of the `ARTJESINITIATOR` server

 **Note:**

If no option is specified, all `ARTJESINITIATOR` servers resume.

- [Controlling `ARTJESINITIATOR` Servers \(Synchronous\)](#)

4.3.8.1 Controlling `ARTJESINITIATOR` Servers (Synchronous)

You can control `ARTJESINITIATOR` servers synchronously by using `artjesadmin` in the following format:

```
artjesadmin [-f [security_profile]] -x showjobexec|resumejobexec|stopjobexec
[[lmid=machine|grpId=groupid|grpId=groupid,srvid=serverid];...]
```

```
-x showjobexec [[lmid=machine|grpId=groupid|grpId=groupid,srvid=serverid];...]:
```

Displays the number of executing jobs for all `ARTJESINITIATOR` servers, logical machine servers, servers by group id, or servers by group id and server id.

```
-x stopjobexec [[lmid=machine|grpId=groupid|grpId=groupid,srvid=serverid];...]:
```

Stops pick up of new jobs to execute for all `ARTJESINITIATOR` servers, logical machine servers, servers by group id, or server by group id and server id.

```
-x resumejobexec [[lmid=machine|grpId=groupid|grpId=groupid,srvid=serverid];...]:
```

Resumes pick up of new jobs to execute for all `ARTJESINITIATOR` servers, logical machine servers, servers by group id, or server by group id and server id.

4.3.9 Event Subscribing/Unsubscribing

You can subscribe or unsubscribe job status change event using the `artjesadmin` subcommand `event`:

```
event (et) [-t C,E,P,L,A] on|off
```

C: job conversion complete event

E: job execution finish event

P: job purge event

L: job cancel completed event

A: all supported events. If the event is set to "on", A is the default.

on |off: The submission is on or off. the "on" setting can be used with the `-t` option.

After subscribing to an event, you are notified on the `artjesadmin` console when the corresponding event is generated.

4.4 Authorizing TuxJES Job Access

Based on TuxJES security mechanism, ART for Batch provides a lightweight job access authorization mechanism to control user's job operation actions. This authorization only needs simple configuration without involving any authorization server or even third-party security product.

In this mechanism, administrator can authorize particular user to do particular job operations, using TuxJES job operation authorization rules.

If an Oracle Tuxedo user is mapped to (or identical with) Unix/Linux `root`, it would be treated as a super user. This super user is allowed to do any job operation with no authorization checking performed.

- [Configuring Job Access Authorization Mechanism](#)
- [Using Job Operation Authorization Rules](#)
- [Using `artjesadmin` to Dynamically Change Job Access Authorization](#)

4.4.1 Configuring Job Access Authorization Mechanism

The following configurations are mandatory to enable TuxJES job access authorization mechanism.

- Set `JES_ACL_FILE` in `JESCONFIG`
This is to specify the full path of job access authorization configuration file. For example:
`JES_ACL_FILE=/home/user/simpjob/jesacl`
If `JES_ACL_FILE` cannot be opened successfully, or it contains invalid format rules, `ARTJESADM` cannot boot up.

Note:

Do not configure `JES_ACL_FILE` if you want to use other authorization servers such as `EAUTHSVR` or if you do not want to use any kind of authorization, because the configuration for the job access authorization mechanism has higher precedence than other standalone ACL authorization servers.
Besides the above `JES_ACL_FILE` configurations, you should set other configurations to enable TuxJES security mechanism. For example, set `PRIVILEGE_MODE` to `USER_IDENTICAL` or `USER_MAPPING` in `JESCONFIG`, and set `SECURITY` to `USER_AUTH`, `ACL`, or `MANDATORY_ACL` in `UBBCONFIG` file.

The following configurations are optional to use this mechanism.

- Set `JES_ACL_FILE_TYPE` to `PLAIN` (default) or `ENCRYPTED` in `JESCONFIG` to specify whether the `JES_ACL_FILE` is plain or encrypted.
- Set `JES_ACL_MODE` to `MAC` (default) or `DAC` in `JESCONFIG` to specify the action when no matching rule in the rule file is found. See Example for Using [JES_ACL_MODE](#) for an example.

Also, we use `genjesacl` tool to generate the encrypted rule file for TuxJES system.

For more information, see [ARTJESADM](#) and [genjesacl](#).

4.4.2 Using Job Operation Authorization Rules

This section has the following topics:

- [Setting Rules](#)
- [Processing Rules](#)
- [Adding Comments to Rules](#)
- [Examples](#)

4.4.2.1 Setting Rules

The `JES_ACL_FILE` file where you set rules can be plain or encrypted.

- [Plain JES_ACL_FILE File](#)
- [Encrypted JES_ACL_FILE file](#)

4.4.2.1.1 Plain JES_ACL_FILE File

Set job operation authorization rule in the plain text file that `JES_ACL_FILE` specifies. Use the following CSV format:

```
permission; user-list; operation-list; jobname-list
```

- `permission`
- `user-list`
- `operation-list`
- `jobname-list`

Here are some examples.

- Listing 14: In this example, user `tpuser1` is authorized to perform any kind of operation on any jobs.
- Listing 15: In this example, user `tpuser2` is authorized to operate on jobs with the `JOBZ` prefix in their name.
- Listing 16: In this example, no user is authorized to purge any jobs.

Listing 14 Example for Setting Rules

```
ALLOW; tpuser1; *; *
```

Listing 15 Example for Setting Rules

```
ALLOW; tpuser2; *; JOBZ*
```

Listing 16 Example for Setting Rules

```
DENY; *; PURGE; *
```

permission

Specifies `ALLOW` or `DENY` for the permission.

This field is case insensitive.

user-list

Specifies Oracle Tuxedo user name. When specifying user name, you should not only follow Oracle Tuxedo's naming requirements but also follow the below requirements.

- User name should not contain a semicolon (;).
- User name should not be just an asterisk (*).

Multiple users are separated by ":". An asterisk (*) means all Oracle Tuxedo users. Wildcards are not supported in this field. For example, `tpuser*` does not mean all users that have name starting with `tpuser`. For Oracle Tuxedo's naming requirements, see [Oracle Tuxedo Command Reference](#).

operation-list

Specifies job operations. The job operations could be `SUBMIT`, `CANCEL`, `PURGE`, `HOLD`, and `RELEASE`.

Among these five kinds of job operation, `SUBMIT` is the most important one and is the prerequisite of the following four kinds of job operation because if a user wants to cancel, purge, hold or release a job, TuxJES firstly checks whether the user is the owner of the job (only if the user is granted as `SUBMIT` and successfully submit a job, that user becomes the owner of this job and will own this job until it is purged out of TuxJES system).

Multiple operations are separated by ":". An asterisk (*) means all of these operations (equals to `SUBMIT:CANCEL:PURGE:HOLD:RELEASE`). Wildcards are not supported in this field. This field is case insensitive.

jobname-list

Specifies job names. The job name is not the file name of the job; it is the internal job name specified in `m_JobBegin` and translated from `/<NAME> JOB` statement in JCL.

Multiple job names are separated by ":". Wildcards "*" (for zero or more characters) and "?" (for only one character) are supported.

4.4.2.1.2 Encrypted JES_ACL_FILE file

If you set `JES_ACL_FILE_TYPE=ENCRYPTED`, you must configure the `JES_ACL_FILE` file as an encrypted file. This encrypted file can be generated by the `genjesacl` tool.

For more information, see [JESCONFIG](#) and [genjesacl](#).

4.4.2.2 Processing Rules

In terms of multiple matching rules, the first matching rule takes precedence. A matching rule means that the user, operation and job fields are all matched.

If no rule is found to match the user, operation and job, the configuration of `JES_ACL_MODE` in `JESCONFIG` file takes effect. If `JES_ACL_MODE` is not set, its default value `JES_ACL_MODE=MAC` takes effect, meaning that the operation is denied.

Listing 17 Example for Processing Rules

```
ALLOW; tpuser1;*;*
DENY; tpuser1;*; JOBA
```

Though the above two rules are both matching rules, the first matching rule takes precedence, meaning that user `tpuser1` is authorized to operate on `JOBA` and the second matching rule does not take effect.

If you want user `tpuser1` to operate all the jobs except for `JOBA`, exchange the sequence of the above two rules.

4.4.2.3 Adding Comments to Rules

The lines (ignoring leading space) starting with character `#` are considered as comments. For example:

```
# This is comment

# This is also comment.

ALLOW;tpuser1;*;JOBA:JOBB
```

Do not write comments right after the rule in the same line. For example, the #C in the following line is not considered as a comment.

```
ALLOW;tpuser1;*;JOBA:JOBBC
```

4.4.2.4 Examples

The following are the list of examples:

- [Example for Using Difference Ways to Set Rules](#)
- [Example for Using Wildcards to Set Rules](#)
- [Example for Using JES_ACL_MODE](#)

4.4.2.4.1 Example for Using Difference Ways to Set Rules

Suppose jobs whose names start with JOBAA, JOBBB and JOBCC need to be protected. You want to grant tpuser1 and tpuser2 for jobs whose names start with JOBAA, and grant tpuser3 and tpuser4 for jobs whose names start with JOBBB and JOBCC. All other jobs do not need to be protected.

The following rules can satisfy this requirement.

```
ALLOW;tpuser1:tpuser2;*;JOBAA*
ALLOW;tpuser3:tpuser4;*;JOBBB*:JOBCC*
DENY;*;*;JOBAA*:JOBBB*:JOBCC*
ALLOW;*;*;*
```

The following rules can also satisfy this requirement.

```
ALLOW;tpuser1:tpuser2;*;JOBAA*
ALLOW;tpuser3:tpuser4;*;JOBBB*:JOBCC*
DENY;*;*;JOBAA*:JOBBB*:JOBCC*
```

Then configure JES_ACL_MODE=DAC in JESCONFIG file.

4.4.2.4.2 Example for Using Wildcards to Set Rules

Suppose there are three Oracle Tuxedo users in the system: tpuser1, tpuser2, tpuser3; there are 30 jobs in the system: JOBX01-JOBX10, JOBY01-JOBY10, and JOBZ01-JOBZ10.

You want to grant tpuser1 and tpuser2 to operate all jobs, and grant tpuser3 to only operate 12 jobs: JOBX10, JOBY10, and JOBZ01-JOBZ10.

There are many solutions.

Option A:

```
DENY;tpuser3;*;JOBX0?:JOBY0?
ALLOW;*;*;*
```

Option B:

```
ALLOW;tpuser3;*;JOBX10:JOBY10:JOBZ*
ALLOW;tpuser1:tpuser2;*;*
```

In this case, Option A is not recommended because it authorizes the potential new user a high permission.

4.4.2.4.3 Example for Using JES_ACL_MODE

Suppose the rule file just contains one line.

```
ALLOW; tpuser1; *; JOBA
```

If user `tpuser1` wants to submit `JOBB` and user `tpuser2` wants to submit `JOBA`, there is no matching rule for these requirements; then the settings for `JES_ACL_MODE` take effect.

By default, `JES_ACL_MODE` is `MAC`, meaning that these actions would be denied; however, if you specify `JES_ACL_MODE` to `DAC`, the above operations will be allowed.

4.4.3 Using `artjesadmin` to Dynamically Change Job Access Authorization

You can dynamically change job access authorization, using `artjesadmin` command.

```
artjesadmin -f [security_profile] -x setjesacl  
aclfile=rulepath[,aclfiletype=PLAIN|ENCRYPTED[,aclmode=MAC|DAC]]
```

You can also use `artjesadmin sub` command.

```
setjesacl (sja) -f rulepath [-t PLAIN|ENCRYPTED] [-m MAC|DAC]
```

For example, to change the rule file of job access authorization to another file (`aclrule.new`) with `DAC` mode, you can use `artjesadmin` command as Listing 18 or use `artjesadmin sub` command as Listing 19.

Listing 18 Example of Using `artjesadmin` Command to Dynamically Change Job Access Authorization

```
artjesadmin -f jesprofile -x setjesacl aclfile=aclrule.new,aclmode=DAC
```

Listing 19 Example of Using `artjesadmin Sub` Command to Dynamically Change Job Access Authorization

```
artjesadmin -f jesprofile  
setjesacl -f aclrule.new -m DAC
```

4.5 Tracing TuxJES

ART for Batch supports you to trace messages (error messages, warning messages, information messages, and debugging messages) generated by TuxJES client and server. These messages are formatted and stored in TuxJES trace files; you can use four different trace levels (`ERROR`, `WARN`, `INFO`, and `DEBUG`) to determine which messages will be displayed.

- [Setting Environment Variables](#)
- [Understanding TuxJES Trace File](#)
- [Understanding TuxJES Trace Message Format](#)
- [Understanding TuxJES Trace Message Level](#)
- [Controlling TuxJES Trace Message Level](#)

4.5.1 Setting Environment Variables

Before running Batch Runtime, you can set the following environment variables:

Table 4-6 Available Environment Variables for Tracing TuxJES

Variable	Usage
JES_TRACE_PATH	The directory where TuxJES trace files are stored. The default directory is <code>\${APPDIR}/Logs</code> .
JESTRACE	<p>The display level of TuxJES trace messages. Set one of the following:</p> <ul style="list-style-type: none"> ERROR or error: TuxJES outputs error messages only. WARN or warn: TuxJES outputs error messages and warning messages. INFO or info: TuxJES outputs error messages, warning messages, and information messages. DEBUG or debug: TuxJES outputs all messages. <p>The default value is WARN.</p> <p>If JESTRACE is not defined or if it is specified with none of these values above, TuxJES assumes that JESTRACE is specified with WARN</p> <p>- TuxJES outputs error messages and warning messages.</p>

4.5.2 Understanding TuxJES Trace File

Every TuxJES server and client has its own TuxJES trace file. These trace files store trace messages generated by TuxJES client and server, including error messages, warning messages, information messages, and debugging messages.

By default, JES trace files are stored in `${APPDIR}/Logs` directory; before running Batch Runtime, you can change the directory by setting the environment variable `JES_TRACE_PATH`.

A TuxJES server's trace file is named with the combination of server name, group ID, server ID, and a fixed-suffix "jestrace". For example,

- ARTJESADM.1.1.jestrace is the `jestrace` file name of a ARTJESADM server; this server belongs to group 1 and its server ID is 1.
- ARTJESCONV.1.20.jestrace is the `jestrace` file name of a ARTJESCONV server; this server belongs to group 1 and its server ID is 20.

A TuxJES client's trace file is named with the client name and a fixed-suffix "jestrace". For example,

- artjesadmin.jestrace is the `jestrace` file name of a TuxJES client.

4.5.3 Understanding TuxJES Trace Message Format

A TuxJES trace message is composed of the following fields:

Table 4-7 TuxJES Trace Message Format

Field	Content
1	Process ID (PID)

Table 4-7 (Cont.) TuxJES Trace Message Format

Field	Content
2	Thread ID (TID)
3	Current timestamp
4	Trace message level. For more information, see Understanding TuxJES Trace Message Level and Controlling TuxJES Trace Message Level .
5	Functions that can display the message
6	The message to be displayed with possible dynamic values

4.5.4 Understanding TuxJES Trace Message Level

There are four TuxJES trace messages levels.

- **ERROR Level**
TuxJES outputs error messages only.
- **WARN Level (Default Level)**
TuxJES outputs error messages and warning messages.
- **INFO Level**
TuxJES outputs error messages, warning messages, and information messages.
- **DEBUG Level**
TuxJES outputs all messages.

4.5.5 Controlling TuxJES Trace Message Level

You can use environment variable `JESTRACE` to set the TuxJES trace message level, or use command `artjesadmin` to dynamically change it, determining which level of messages will be displayed.

- [Using JESTRACE to Set TuxJES Trace Message Level](#)
- [Using artjesadmin to Dynamically Change TuxJES Trace Message Level](#)

4.5.5.1 Using JESTRACE to Set TuxJES Trace Message Level

You should set environment variable `JESTRACE` before running Batch Runtime. Once you set `JESTRACE`, it will set the TuxJES trace message level of all TuxJES clients and servers that your `UBBCONFIG SERVERS` section specifies.

For more information about `JESTRACE`, see [Setting Environment Variables](#).

4.5.5.2 Using artjesadmin to Dynamically Change TuxJES Trace Message Level

You can dynamically change TuxJES trace message level, using `artjesadmin` command:

```
artjesadmin [-f [security_profile]] -x settracelevel [trclvl=trace_level[,
[lmid=machine|grpId=groupid|grpId=groupid,srvid=serverid];...]]
```

You can also use `artjesadmin` sub command:

```
settracelevel(stl) -t tracelevel [-n machine] | [-g groupid [-i serverid]]
```

The parameter `trclvl` and `-t` can be set as 0, 1, 2, or 3. 0 indicates `ERROR` level; 1 indicates `WARN` level; 2 indicates `INFO` level; 3 indicates `DEBUG` level.

If none of the `machine`, `groupid`, and `serverid` parameter is specified, the `artjesadmin` will change the TuxJES trace message level of the current client and all servers that your `UBBCONFIG SERVERS` section specifies. Once you specify one or more parameters, the `artjesadmin` will only change the TuxJES trace message level of the servers that you specifies; the current client will not be changed.

- **Example A:** Change TuxJES trace message level to `DEBUG` for the current client and all servers that your `UBBCONFIG SERVERS` section specifies. You can use `artjesadmin` command as Listing 20 or use `artjesadmin` sub command as Listing 21.
- **Example B:** Change TuxJES trace message level to `ERROR` for the TuxJES servers which are running on `SITE1` machine. You can use `artjesadmin` command as Listing 22 or use `artjesadmin` sub command as Listing 23
- **Example C:** Change TuxJES trace message level to `INFO` for all TuxJES administration servers that belong to group 1. You can use `artjesadmin` command as Listing 24 or use `artjesadmin` sub command as Listing 25
- **Example D:** Change TuxJES trace message level to `INFO` for a TuxJES administration server; this server belongs to group 1, and its server ID is 1. You can use `artjesadmin` command as Listing 26 or use `artjesadmin` sub command as Listing 27

For more information, see `artjesadmin` in *Oracle Tuxedo Application Runtime for Batch Reference Guide*.

Listing 20 Example A: artjesadmin Command

```
artjesadmin -x settracelevel trclvl=3
```

Listing 21 Example A: artjesadmin Sub Command

```
artjesadmin  
settracelevel -t 3
```

Listing 22 Example B: artjesadmin Command

```
artjesadmin -x settraceleveltrclvl=0,lmid=SITE1
```

Listing 23 Example B: artjesadmin Sub Command

```
artjesadmin  
settracelevel -t 0 -n SITE1
```

Listing 24 Example C: artjesadmin Command

```
artjesadmin -x settracelevel trclvl=2,grpId=1
```

Listing 25 Example C: artjesadmin Sub Command

```
artjesadmin  
settracelevel -t 2 -g 1
```

Listing 26 Example D: artjesadmin Command

```
artjesadmin -x settracelevel trclvl=2,grpId=1,srvid=1
```

Listing 27 Example D: artjesadmin Sub Command

```
artjesadmin  
settracelevel -t 2 -g 1 -i 1
```



See Also:

Oracle Tuxedo Application Runtime for Batch Reference Guide

5

Using ART BATCH ISPF

This chapter contains the following topics:

- [Overview](#)
- [Prerequisites](#)
- [Using ART Batch ISPF](#)

5.1 Overview

ART Batch ISPF functions much like the Interactive System Productivity Facility (ISPF) program. Instead of performing tasks by opening a command line and entering the correct command, all actions would be accessible via ART Batch ISPF. It is a very easy interface to use.

5.2 Prerequisites

1. Setup operation environment for ART JES2 batch system.
2. Start ISPF license daemon in the `twg1m` directory by running `./twg1m`.
3. Be sure that a shell script, `ISPF`, can be found in your `PATH` environment variable.
4. Copy all files under directories (`$JESDIR/tools/artispcf/msgs`, `$JESDIR/tools/artispcf/rexx`, and `$JESDIR/tools/artispcf/panels`) to the corresponding directory of the uni-SPF(`spf/msg`, `spf/rexx` and `spf/panels`).
5. Copy directory `$JESDIR/tools/artispcf/tools` to the directory of uni-SPF(`spf/tools`).



Note:

JESDIR is TuxJES installation directory.

5.3 Using ART Batch ISPF

Type `ISPF` and press Enter to invoke ISPF and display the main menu panel. It is a menu from which you select the facility that you wish to use. Then type “A” or “a” in the `COMMAND` field from the main menu to go to start ART BATCH ISPF.

With ART Batch ISPF, there is no need to work at the command line. You may choose the desired function by typing your selection in the panel `OPTION` or `COMMAND` fields.

From any panel, the `END` command returns you to the previous panel. The `RETURN` command takes you immediately to the Main Menu panel from any point in the system. `PF7` scrolls the display up. `PF8` scrolls the display down. `Tab` key moves the cursor to the beginning of the next input field. The `Back-tab` (`Shift + tab`) key moves the cursor to the beginning of the previous input field. Arrow keys to move the cursor.

In some panels, if the entry field contains text provided by system, you can type over it. Some commands are case-insensitive.

- [Administering ART Batch](#)
- [Controlling ART Batch Jobs](#)

5.3.1 Administering ART Batch

Follow the steps below to Administer the ART Batch:

1. Boot up JES system
2. Shut down JES system
3. Browse system logs (ULOG, jes system log file, stdout and stderr)
4. View or edit GDG files
5. View or edit file catalog and allocate a new file.
6. List or clean lock records in lock files.
7. Configure ART Batch, including `BatchRT.conf`, `jesconfig` file. Stop, start, and configure ARTJESINITIATOR servers.
8. Generate the security profile

5.3.2 Controlling ART Batch Jobs

You can control ART Batch jobs in the following ways:

1. Manage job scripts (view, edit, copy and submit a job)
2. Control job processing (cancel, hold, purge, release re-submit a job and change job priority)
3. Browse job log and output

6

Debugging COBOL Programs

ART for Batch supports user COBOL program in `runb/runbexci` debugging for Micro Focus COBOL and COBOL-IT COBOL.

- Debugging with Micro Focus COBOL
- Debugging with COBOL-IT COBOL (using `deet` tool)

You can configure all the jobs and programs that you want to debug in the configuration file `batchdebug.cfg`. Only these jobs/programs configured in this file could be debugged. See [Configuring for Debugging in Configuration File](#) for more information.

To support COBOL debug, all COBOL programs must be compiled to output with debug information. In particular, for Micro Focus COBOL, `.idy` file must exist.

- [Debugging with Micro Focus COBOL](#)
- [Debugging with COBOL-IT COBOL](#)
- [Configuring for Debugging in Configuration File](#)

6.1 Debugging with Micro Focus COBOL

Follow the steps below to debug with Micro Focus COBOL.

1. Create or modify `batchdebug.cfg` configuration file at `${JESROOT}`. See [Configuring for Debugging in Configuration File](#) for more information.
2. Start `anim` in a new terminal and the `anim` remains in waiting state.
3. Submit your job. It makes `Animator` attach to the started COBOL program.
4. Debug your COBOL programs.

Note:

At the end of debug session, you may need to detach `Animator` from the program that you just debug.

6.2 Debugging with COBOL-IT COBOL

Do the following steps to debug with COBOL-IT COBOL.

1. Create or modify `batchdebug.cfg` configuration file at `${JESROOT}`. See [Configuring for Debugging in Configuration File](#) for more information.
2. Submit your job. It hangs before COBOL program actually runs, waiting you to start debug session.

3. Use `vncserver` to start a VNC environment. In VNC xterm, start debug session with command `deet -p your DEBUGID`. It starts a `Deet` graphic UI and makes `Deet` attach to the COBOL program.
4. Debug this COBOL program in `Deet` graphic UI.



Note:

At the end of debug session, you may need to detach `Deet` from the program that you just debug.

For more information about `Deet` graphic UI, see *COBOL-IT COBOL documentation*.

6.3 Configuring for Debugging in Configuration File

Whenever you launch `runb` or `runbexci` to start a COBOL application program, ART for Batch checks configuration file `batchdebug.cfg` at `${JESROOT}` to determine whether to enable COBOL debug; therefore, to enable it, you should set this configuration file at the very beginning. Only the programs with the `DEBUGID` that you configure in `batchdebug.cfg` can be debugged.

The format of `batchdebug.cfg` is:

```
COBOL; DEBUGID;UserID;JobName;Program
```

Table 6-1 Debug Configuration Parameters

Field Name	Type	Value	Description
COBOL	Fix string	Mandatory	A fix string for identifying usage for COBOL debug.
DEBUGID	X(40) or 1 ~ 999999999	Mandatory	For Micro Focus COBOL application programs, <code>DEBUGID</code> is a string that is required for enabling animation in COBOL. It is a character string of up to 40 characters. The string can have alphanumeric characters and underscore. For COBOL-IT COBOL application programs, <code>DEBUGID</code> is a number ranging from 1 to 999999999.
UserID	X(30)	Mandatory	ART for Batch user ID who is to be diagnosed. Usually it is Oracle Tuxedo user name. * means all users.
JobName	X(32)	Mandatory	Job name which is to be diagnosed. * means all jobs.
Program	X(30)	Mandatory	COBOL program name which is to be diagnosed. It must be the entry COBOL program name. * means all programs..

Here are some examples.

- Listing 1 and Listing 2 are examples for debugging all programs in job `JOBA` submitted by user `A`.
- Listing 3 and Listing 4 are examples for debugging `program1` in all jobs.

Listing 1 Debugging All Programs in One Job (Micro Focus COBOL)

```
COBOL;debugid1;A;JOBA;*
```

Listing 2 Debugging All Programs in One Job (COBOL-IT COBOL)

```
COBOL;101; A; JOBA;*
```

Listing 3 Debugging One Program in All Jobs (Micro Focus COBOL)

```
COBOL;debugid2;*;*;program1
```

Listing 4 Debugging One Program in All Jobs (COBOL-IT COBOL)

```
COBOL;102;*;*;program1
```