

Oracle® Banking Cash Management Services Installation Guide



Release 14.7.5.0.0

G15698-01

September 2024

The Oracle logo, consisting of a solid red square with the word "ORACLE" in white, uppercase, sans-serif font centered within it.

ORACLE®

Copyright © 2020, 2024, Oracle and/or its affiliates.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle®, Java, MySQL, and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

1	<u>Database Setup</u>
2	<u>Product Installation using Installer</u>
3	<u>Domain and Cluster Configuration</u>
4	<u>Data Source Creation</u>
5	<u>Deployments</u>
6	<u>Restarts and Refresh</u>
7	<u>Logging Area</u>
	<u>Index</u>

Preface

- [Purpose](#)
- [Audience](#)
- [Documentation Accessibility](#)
- [Critical Patches](#)
- [Diversity and Inclusion](#)
- [Related Resources](#)
- [Conventions](#)
- [Acronyms and Abbreviations](#)

Purpose

This guide would help you to install the Oracle Banking Cash Management services on designated environment. It is assumed that all the prior setup is already done related with WebLogic installation, WebLogic managed server creation and Oracle Database installation. It is recommended to use dedicated managed server for each of the Oracle Banking Cash Management services.

Audience

This guide is intended for WebLogic admin or ops-web team who are responsible for installing the OFSS banking products.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customer access to and use of Oracle support services will be pursuant to the terms and conditions specified in their Oracle order for the applicable services.

Critical Patches

Oracle advises customers to get all their security vulnerability information from the Oracle Critical Patch Update Advisory, which is available at [Critical Patches, Security Alerts and Bulletins](#). All critical patches should be applied in a timely manner to ensure effective security, as strongly recommended by [Oracle Software Security Assurance](#).

Diversity and Inclusion

Oracle is fully committed to diversity and inclusion. Oracle respects and values having a diverse workforce that increases thought leadership and innovation. As part of our initiative to build a more inclusive culture that positively impacts our employees, customers, and partners,

we are working to remove insensitive terms from our products and documentation. We are also mindful of the necessity to maintain compatibility with our customers' existing technologies and the need to ensure continuity of service as Oracle's offerings and industry standards evolve. Because of these technical constraints, our effort to remove insensitive terms is ongoing and will take time and external cooperation.

Related Resources

The related documents are as follows:

- *Oracle Banking Cash Management Pre-Installation Guide*
- *Configuration and Deployment Guide*
- *Oracle Banking Cash Management Environment Variable Setup Guide*
- *Oracle Banking Cash Management User Interface Installation Guide*

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

Acronyms and Abbreviations

The list of the acronyms and abbreviations used in this guide are as follows:

Table Acronyms and Abbreviations

Abbreviation	Description
JDK	Java Development Kit
OSDC	Oracle Software Delivery Cloud
SMS	Security Management System

1

Database Setup

This topic describes the database setup for Oracle Banking Cash Management Installation.

Prerequisite

Before you proceed with the document, ensure Schema's are being created. It is recommended to have different schema for each application.

Database Schema Creation

Create the following database schema's. These schema names are recommended, but not mandatory.

- PLATO
- PLATO_UI_CONFIG
- PLATO_SECURITY
- PLATO_FEED
- PLATO_REPORT_SERVICE
- PLATORULE
- PLATOBATCH
- PLATO_PASSWORD
- COMMON_CORE
- PLATOALERTS
- PLATO_TRANSPORT
- PLATOORCH
- SMS
- OBSCFCM_ACCOUNTING
- OBSCFCM_ALERTS
- OBSCF_BATCH
- OBSCFCM_CHARGES
- OBSCFCM_CORE_SERVICES
- OBSCFCM_FILTER
- OBSCFCM_INSTRUMENTS
- OBSCFCM_RECON
- OBSCFCM_REPORT
- OBSCFCM_WORKFLOWS_CONDUCTOR
- OBSCFCM_MASTER_MAINTENANCE
- OBSCFCM_GENAI_INTEGRATION

- OBCM_CASHFLOW_FORECASTING
- OBCM_CASHFLOW_PROJECTION
- OBCM_CASHFLOW_PREDICTION
- OBCM_COLLECTION_MAINT
- OBCM_COLLECTIONS
- OBCM_REPORT_SERVICES

 **Note:**

For creating database schemas, refer to **Database Schema Creation** section in **Configuration and Deployment Guide**.

View Creation Grants (Oracle Banking Cash Management Cashflow Prediction)

The following grants are provided for Oracle Banking Cash Management Cashflow Prediction:

- grant create mining model to OBCM_CASHFLOW_PREDICTION;
- grant create any mining model to OBCM_CASHFLOW_PREDICTION;
- grant alter any mining model to OBCM_CASHFLOW_PREDICTION;
- grant drop any mining model to OBCM_CASHFLOW_PREDICTION;
- grant select any mining model to OBCM_CASHFLOW_PREDICTION;
- grant comment any mining model to OBCM_CASHFLOW_PREDICTION;
- grant execute on DBMS_DATA_MINING to OBCM_CASHFLOW_PREDICTION;
- grant create view to OBCM_CASHFLOW_PREDICTION;
- grant create table to OBCM_CASHFLOW_PREDICTION;
- grant drop table to OBCM_CASHFLOW_PREDICTION;
- grant create job to OBCM_CASHFLOW_PREDICTION;
- ALTER USER OBCM_CASHFLOW_PREDICTION ENABLE EDITIONS;

2

Product Installation using Installer

This topic describes the systematic information to install Oracle Banking Cash Management application using Installer.

Prerequisite

Before proceeding with installation setup, make sure that the database installation is completed and required schemas are created.

Installer Path

The following table provides the path of the installer in OSDC Package.

Application	Archive Name	OSDC Path
Oracle Banking Microservices Architecture	obma.zip	OBCM_14.7.5.0.0/Installer
Oracle Banking Cash Management	obcm.zip	
Oracle Banking Supply Chain Finance Cash Management	obscfcm.zip	



Note:

To install the application using installer, refer to **Oracle Banking Microservices Architecture Installer Guide**

3

Domain and Cluster Configuration

This topic describes the domain and cluster configuration for Oracle Banking Cash Management.

Pre-requisite

- Oracle Banking Microservices Architecture, SMS and Common core deployments are up and running. (Required)
- Machine should have Java JDK installed.
- Oracle Fusion Middleware has to be installed on the machine.



Note:

For the exact version to be installed, refer to the **Tech Stack** section in **Release Notes**

Domain Creation and Configuration

It is recommended to have different managed server in one domain for each application. For creating domain and cluster configuration, refer to **Create Domain and Cluster Configuration** section in **Configuration and Deployment Guide**

4


Data Source Creation

This topic describes about the data source creation for Oracle Banking Cash Management Installation.

Data Source Creation in WebLogic

Database and application setup for Oracle Banking Cash Management services has to be performed prior to deployment setup. The data sources for the respective micro-services must be created first before the application deployment. Each of the data source target to their corresponding servers on which the application will be deployed. The following sections explain the list of data sources required to be created for Oracle Banking Cash Management services and the steps to configure them in the server.

Figure 4-1 Data Source Creation



Data sources List

Database Connection Pool size to be defined - Oracle Banking Cash Management services pool configuration should be consistent with Oracle Banking Microservices Architecture services.

The following list of the data sources has to be created on each domain before deployment of the applications onto the managed servers.

Table 4-1 Data Sources List

Application	Data Source Name	Mapped Database Schema	Data source JNDI
obscfcm-account-maintenance	OBSCFCM_ACCOUNTING	OBSCFCM_ACCOUNTING	jdbc/OBSCFCM_ACCOUNTING
obscfcm-alerts-services	OBSCFCM_ALERTS	OBSCFCM_ALERTS	jdbc/OBSCFCM_ALERTS
obscfcm-eod-batch	PLATOBATCH	PLATOBATCH	jdbc/EODBATCH
	OBSCF_BATCH	OBSCF_BATCH	jdbc/EOD

Table 4-1 (Cont.) Data Sources List

Application	Data Source Name	Mapped Database Schema	Data source JNDI
	PLATOBATCH	PLATOBATCH	jdbc/PLATOBATCH
obscfcm-auto-recon-batch	OBSCFCM_RECON	OBSCFCM_RECON	jdbc/AUTORECONBAT CH
obscfcm-charges-services	OBSCFCM_CHARGES	OBSCFCM_CHARGES	jdbc/OBSCFCM_CHAR GES
obscfcm-core-services	OBSCFCM_CORE_SE RVICES	OBSCFCM_CORE_SE RVICES	jdbc/OBSCFCM_CORE _SERVICES
obscfcm-filter-services	OBSCFCM_FILTER	OBSCFCM_FILTER	jdbc/OBSCFCM_FILTE R
obscfcm-instruments- receivables-services	OBSCFCM_INSTRUME NTS	OBSCFCM_INSTRUME NTS	jdbc/OBSCFCM_INSTR UMENTS
obscfcm-manual-recon- services	OBSCFCM_RECON	OBSCFCM_RECON	jdbc/OBSCFCM_RECO N
obscfcm-report-services	OBSCFCM_REPORT	OBSCFCM_REPORT	jdbc/OBSCFCM_REPO RT
obscfcm-workflow- management-services	OBSCFCM_WORKFLO WS_CONDUCTOR	OBSCFCM_WORKFLO WS_CONDUCTOR	jdbc/OBSCFCM_WORK FLOWS_CONDUCT TOR
obscfcm-master- maintenance-services	OBSCFCM_MAINTENA NCE	OBSCFCM_MAINTENA NCE	jdbc/OBSCFCM_MAINT ENANCE
obscfcm-genai-integration- services	OBSCFCM_GENAI_INT TEGRATION	OBSCFCM_GENAI_INT TEGRATION	jdbc/OBSCFCM_GENAI
obcm-cashflow-forecasting- services	OBCM_CASHFLOW_F ORCAST	OBCM_CASHFLOW_F ORCAST	jdbc/OBCM_CASHFLO W_FORCAST
obcm-cashflow-projection- services	OBCM_CASHFLOW_P ROJECTION	OBCM_CASHFLOW_P ROJECTION	jdbc/OBCM_CASHFLO W_PROJECTION
obscfcm-batch-jobs	PLATOBATCH	PLATOBATCH	jdbc/OBSCFCM- BATCH-JOBS
obcm-collections-transaction- services	OBCM_COLLECTIONS	OBCM_COLLECTIONS	jdbc/OBCM_COLLECTI ONS
obcm-report-services	OBCM_REPORT	OBCM_REPORT	jdbc/OBCM_REPORT
obcm-collections- maintenance-services	OBCM_COLLECTION_ MAINT	OBCM_COLLECTION_ MAINT	Jdbc/OBCM_COLLECTI ON_MAINT
obcm-cashflow-prediction- services	OBCM_CASHFLOW_P REDICTION	OBCM_CASHFLOW_P REDICTION	jdbc/OBCM_CASHFLO W_PREDICTION

Table 4-1 (Cont.) Data Sources List

Application	Data Source Name	Mapped Database Schema	Data source JNDI
obcm-multilateral-netting-services	OBSCFCM_INSTRUMENTS	OBSCFCM_INSTRUMENTS	jdbc/OBSCFCM_INSTRUMENTS
To be mapped with all managed servers	PLATO	PLATO	jdbc/PLATO
	PLATO_UI_CONFIG	PLATO_UI_CONFIG	jdbc/PLATO_UI_CONFIG
	SMS	SMS	jdbc/sms
	CMNCORE	CMNCORE	jdbc/CMNCORE
	PLATOFEED	PLATOFEED	jdbc/PLATOFEED
	PLATOBATCH	PLATOBATCH	jdbc/PLATOBATCH
	PLATOTRANSPORT	PLATOTRANSPORT	jdbc/PLATOTRANSPORT
obcm-day0-service	OBCM_CASHFLOW_FORCAST	OBCM_CASHFLOW_FORCAST	jdbc/OBCM_CASHFLOW_FORCAST
	OBCM_COLLECTION_MAINT	OBCM_COLLECTION_MAINT	jdbc/OBCM_COLLECTION_MAINT
	OBSCFCM_MAINTENANCE	OBSCFCM_MAINTENANCE	jdbc/OBSCFCM_MAINTENANCE
	PLATOBATCH	PLATOBATCH	jdbc/PLATOBATCH
obscfcm-day0-service	OBSCFCM_ACCOUNTING	OBSCFCM_ACCOUNTING	jdbc/OBSCFCM_ACCOUNTING
	OBSCFCM_FILTER	OBSCFCM_FILTER	jdbc/OBSCFCM_FILTER
	OBSCFCM_INSTRUMENTS	OBSCFCM_INSTRUMENTS	jdbc/OBSCFCM_INSTRUMENTS
	OBSCFCM_RECON	OBSCFCM_RECON	jdbc/OBSCFCM_RECON
	PLATOBATCH	PLATOBATCH	jdbc/PLATOBATCH
	PLATO_SECURITY	PLATO_SECURITY	jdbc/PLATOSECURITY
	OBSCFCM_WORKFLOWS_CONDUCTOR	OBSCFCM_WORKFLOWS_CONDUCTOR	jdbc/OBSCFCM_WORKFLOWS_CONDUCTOR
	OBSCFCM_REPORT	OBSCFCM_REPORT	jdbc/OBSCFCM_REPORT
	OBSCFCM_MAINTENANCE	OBSCFCM_MAINTENANCE	jdbc/OBSCFCM_MAINTENANCE

**Note:**

For creating data source, refer to the **Create Datasource** section in **Configuration and Deployment Guide**.

5


Deployments

This topic describes about the deployments for Oracle Banking Cash Management Installation.

Prerequisite

The database setup and data sources creation have to be performed prior to the application deployment stage. Each of the services corresponds to a specific war file that needs to be deployed into the server. The following sections explain the list of war files of the Oracle Banking Cash Management service and the steps to deploy them into the server.

Figure 5-1 Deployments



- For any issues with fly configuration setup, refer to **High Availability Setup Guide**.
- For Oracle Banking Cash Management environment variables setup, refer to **Environment Variable Setup Guide**.
- If 'obscf-eod-batch' is already deployed, bring it down and deploy 'obscfcm-eod-batch' provided in the deployment list.

Deployments List

The following table provides the details of deployments required on each Server for the Oracle Banking Microservices Architecture application to run. Deploy one after other in the same given order.



Note:

INFRA Pre-requisites should be available before proceeding with the Application deployment process.

Application Startup and Deployment Sequence for new installation or Upgrades

- PLATO Domain <All Plato Infrastructure Services & Oracle banking Microservices Architecture Services should be deployed as per respective installation document>
- Common Core <All SMS, Common Core and Mid-Office Common Core services should be deployed as per respective installation document>

- Domain services
 - All the services in any order except for the below mentioned services which are to be deployed at the end in the order stated in the below list.
 - * obscfcm-master-maintenance
 - * obcm-day0-service
 - * obscfcm-day0-service
- The recommended list of managed server names and the application distribution on the targets are listed below. But not mandatory, provided the managed server is configured as per the sizing recommendations during the implementation phase.
- It is recommended to deploy obcm-collections-maintenance-services first and then deploy obcm-collections-transaction-services war while deploying Oracle Banking Cash Management Services.

 **Note:**

For the exact version and release numbers, refer to the OSDC file available as a part of the release.

Table 5-1 Deployments List

Application	Archive name	OSDC path	Targets
obcm-cashflow-forecasting-services	obcm-cashflow-forecasting-services-{version}.war	OBCM_{release} \OBCM_SERVICES\obcm-cashflow-forecasting-services-{version}\ARCHIVE	obcm_ms_1
obcm-cashflow-projection-services	obcm-cashflow-projection-services-{version}.war	OBCM_{release} \OBCM_SERVICES\obcm-cashflow-projection-services-{version}\ARCHIVE	obcm_ms_1
obcm-cashflow-prediction-services	obcm-cashflow-prediction-services-{version}.war	OBCM_{release} \OBCM_SERVICES\obcm-cashflow-prediction-services-{version}\ARCHIVE	obcm_ms_2
obcm-collections-maintenance-services	obcm-collections-maintenance-services-{version}.war	OBCM_{release} \OBCM_SERVICES\obcm-collections-maintenance-services-{version}\ARCHIVE	obcm_ms_2
obcm-collections-transaction-services	obcm-collections-transaction-services-{version}.war	OBCM_{release} \OBCM_SERVICES\obcm-collections-transaction-services-{version}\ARCHIVE	obcm_ms_1
obcm-report-services	obcm-report-services-{version}.war	OBCM_{release} \OBCM_SERVICES\obcm-report-services-{version}\ARCHIVE	obcm_ms_2
obcm-multilateral-netting-services	obcm-multilateral-netting-services-{version}.war	OBCM_{release} \OBCM_SERVICES\obcm-multilateral-netting-services-{version}\ARCHIVE	obcm_ms_2

Table 5-1 (Cont.) Deployments List

Application	Archive name	OSDC path	Targets
obscfcm-account-maintenance-services	obscfcm-account-maintenance-services-{version}.war	OBCM_{release} \OBCM_SERVICES\obscfcm-account-maintenance-services-{version}\ARCHIVE	obscfcm_ms_2
obscfcm-alerts-services	obscfcm-alerts-services-{version}.war	OBCM_{release} \OBCM_SERVICES\obscfcm-alerts-services-{version}\ARCHIVE	obscfcm_ms_1
obscfcm-batch-jobs	obscfcm-batch-jobs-{version}.war	OBCM_{release} \OBCM_SERVICES\obscfcm-batch-jobs-{version}\ARCHIVE	obscfcm_ms_2
obscfcm-chatbot-services	obscfcm-chatbot-services-{version}.war	OBCM_{release} \OBCM_SERVICES\obscfcm-chatbot-services-{version}\ARCHIVE	obscfcm_ms_1
obscfcm-eod-batch	obscfcm-eod-batch-{version}.war	OBCM_{release} \OBCM_SERVICES\obscfcm-eod-batch-{version}\ARCHIVE	obscfcm_ms_3
obscfcm-auto-recon-batch	obscfcm-auto-recon-batch-{version}.war	OBCM_{release} \OBCM_SERVICES\obscfcm-auto-recon-batch-{version}\ARCHIVE	obscfcm_ms_3
obscfcm-charges-services	obscfcm-charges-services-{version}.war	OBCM_{release} \OBCM_SERVICES\obscfcm-charges-services-{version}\ARCHIVE	obscfcm_ms_2
obscfcm-core-services	obscfcm-coreservices-{version}.war	OBCM_{release} \OBCM_SERVICES\obscfcm-core-services-{version}\ARCHIVE	obscfcm_ms_1
obscfcm-filter-services	obscfcm-filter-services - {version}.war	OBCM_{release} \OBCM_SERVICES\obscfcm-filter-services-{version}\ARCHIVE	obscfcm_ms_1
obscfcm-instruments-receivables-services	obscfcm-instruments-receivables-services-{version}.war	OBCM_{release} \OBCM_SERVICES\obscfcm-instruments-receivables-services-{version}\ARCHIVE	obscfcm_ms_3
obscfcm-manual-recon-services	obscfcm-manual-recon-services{version}.war	OBCM_{release} \OBCM_SERVICES\obscfcm-manual-recon-services-{version}\ARCHIVE	obscfcm_ms_2
obscfcm-report-services	obscfcm-report-services-{version}.war	OBCM_{release} \OBCM_SERVICES\obscfcm-report-services-{version}\ARCHIVE	obscfcm_ms_1
obscfcm-workflow-management-services	obscfcm-workflow-management-services-{version}.war	OBCM_{release} \OBCM_SERVICES\obscfcm-workflow-management-services-{version}\ARCHIVE	obscfcm_ms_3

Table 5-1 (Cont.) Deployments List

Application	Archive name	OSDC path	Targets
obscfcm-genai-integration-services	obscfcm-genai-integration-services-{version}.war	OBCM_{release} \OBCM_SERVICES\obscfcm-genai-integration-services-{version}\ARCHIVE	obscfcm_ms_2
obscfcm-master-maintenance-services	obscfcm-master-maintenance-services-{version}.war	OBCM_{release} \OBCM_SERVICES\obscfcm-master-maintenance-services-{version}\ARCHIVE	obscfcm_ms_3
obcm-day0-service	obcm-day0-service-{version}.war	OBCM_{release} \OBCM_SERVICES\obcm-day0-service-{version}\ARCHIVE	obcm_DAY0
obscfcm-day0-service	obscfcm-day0-service-{version}.war	OBCM_{release} \OBCM_SERVICES\obscfcm-day0-service-{version}\ARCHIVE	obscfcm_DAY0

6

Restarts and Refresh

This topic describes the procedure to restart and refresh the servers.

Once everything is deployed, the managed servers. And for each application call path “/refresh” for refreshing the configuration properties.



Note:

To restart the server, refer to **Restart Server** section in **Configuration and Deployment Guide**.

Restart Order

- Sequence in case of any configuration changes in the plato schema's -> properties table or server arguments (eg : port or host)
 - Restart the plato-config-service and plato-discovery-service.
 - Restart the impacted service
- Sequence in case of any configuration changes in the plato-ui-config schema (eg : port or host)
 - Restart plato-ui-config-service

Caching Impact

In case direct changes are done in database or coherence server is restarted then following services needs to be bounced:

1. Obscfcm-master-maintenance-services
2. Obscfcm-filter-service
3. Obscfcm-manual-recon-service
4. Obscfcm-core-service
5. Obcm-collections-maintenance-services
6. Obscfcm-charges-services

7

Logging Area

This topic describes about the logging area of Oracle Banking Microservices Architecture applications in WebLogic server.

Oracle Banking Microservices Architecture Application writes logs in the below area of the server:

```
<WEBLOGIC_DOMAIN_CONFIG_AREA>/ logs/plato-api-gateway.log
```

Let's assume a domain has been created `cm_domain` in the following area of the server:

```
/scratch/oracle/middleware/user_projects/domains/platoinfra_domain
```

Logging area for Plato would be `/scratch/oracle/middleware/user_projects/domains/cm_domain/logs`.

Index

D

Data Source Creation, [4-1](#)

Database Setup, [1-1](#)

Deployments, [5-1](#)

Domain and Cluster Configuration, [3-1](#)

L

Logging Area, [7-1](#)

P

Product Installation using Installer, [2-1](#)

R

Restarts and Refresh, [6-1](#)