

Oracle® Banking Corporate Lending

Common Core – Scheduler User Guide



Release 14.8.1.0.0
G46886-01
October 2025

ORACLE®

G46886-01

Copyright © 2007, 2025, Oracle and/or its affiliates.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle®, Java, MySQL, and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

Preface

Purpose	i
Acronyms and Abbreviations	i
Audience	ii
Basic Actions	ii
Critical Patches	iii
Conventions	iii
Diversity and Inclusion	iii
Documentation Accessibility	iii
Prerequisite	iii
Related Resources	iv
Screenshot Disclaimer	iv
Symbols and Icons	iv

1 Job Scheduling

1.1	Define Jobs	1
1.2	Schedule Jobs	4
1.3	Maintain Jobs	5
1.4	Notification Process	7
1.5	Process Notification Parameters	10
1.6	EMS Process with Scheduling Architecture	11
1.6.1	EMS Process	11
1.7	Approach	11

Index

Preface

This topic contains the following sub-topics:

- [Purpose](#)
- [Acronyms and Abbreviations](#)
- [Audience](#)
- [Basic Actions](#)
- [Critical Patches](#)
- [Conventions](#)
- [Diversity and Inclusion](#)
- [Documentation Accessibility](#)
- [Prerequisite](#)
- [Related Resources](#)
- [Screenshot Disclaimer](#)
- [Symbols and Icons](#)

Purpose

This manual is designed to get acquainted with the Job Scheduling process of Oracle FLEXCUBE Universal Banking.

To obtain information specific to a particular field, place the cursor on the relevant field and press **F1** on the keyboard.

Acronyms and Abbreviations

The list of the acronyms and abbreviations used in this guide are as follows:

Table 1 Abbreviations

Abbreviation	Description
EMS	Electronic Messaging Service
FCJ	Field Control Junction
JMS	Java Message Service
MDB	Message-Driven Bean
PLSQL	Procedural Language for SQL
SQL	Structured Query Language

Audience

This manual is intended for the following User/User Roles:

Table 2 Audience

Role	Function
Back office data entry clerk	Input functions for maintenance related to the interface.
Back office managers/officers	Authorization functions

Basic Actions

Table 3 List of Basic Actions

Action	Description
Approve	Click Approve to approve the initiated report. This button is displayed, once the user click Authorize .
Audit	Click Audit to view the maker details, checker details of the particular record, and record status. This button is displayed only for the records that are already created.
Authorize	Click Authorize to authorize the record created. A maker of the screen is not allowed to authorize the report. Only a checker can authorize a record. This button is displayed only for the already created records.
Close	Click Close to close a record. This action is available only when a record is created.
Confirm	Click Confirm to confirm the performed action.
Cancel	Click Cancel to cancel the performed action.
Compare	Click Compare to view the comparison through the field values of old record and the current record. This button is displayed in the widget, once the user click Authorize .
Collapse All	Click Collapse All to hide the details in the sections. This button is displayed, once the user click Compare .
Expand All	Click Expand All to expand and view all the details in the sections. This button is displayed, once the user click Compare .
New	Click New to add a new record. The system displays a new record to specify the required data. Note: The fields which are marked in asterisk red are mandatory fields.
OK	Click OK to confirm the details in the screen.
Save	Click Save to save the details entered or selected in the screen.
View	Click View to view the report details in a particular modification stage. This button is displayed in the widget, once the user click Authorize .
View Difference only	Click View Difference only to view a comparison through the field element values of old record and the current record, which has undergone changes. This button is displayed, once the user click Compare .

Critical Patches

Oracle advises customers to get all their security vulnerability information from the Oracle Critical Patch Update Advisory, which is available at [Critical Patches, Security Alerts and Bulletins](#). All critical patches should be applied in a timely manner to make sure effective security, as strongly recommended by [Oracle Software Security Assurance](#).

Conventions

The following text conventions are used in this document:

Table 4 Conventions and Meaning

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

Diversity and Inclusion

Oracle is fully committed to diversity and inclusion. Oracle respects and values having a diverse workforce that increases thought leadership and innovation. As part of our initiative to build a more inclusive culture that positively impacts our employees, customers, and partners, we are working to remove insensitive terms from our products and documentation. We are also mindful of the necessity to maintain compatibility with our customers' existing technologies and the need to ensure continuity of service as Oracle's offerings and industry standards evolve. Because of these technical constraints, our effort to remove insensitive terms is ongoing and will take time and external cooperation.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customer access to and use of Oracle support services will be pursuant to the terms and conditions specified in their Oracle order for the applicable services.

Prerequisite

Specify the **User ID** and **Password**, and login to **Home** screen.

Related Resources

For more information on any related features, refer to the following documents in the FLEXCUBE Universal Banking Documentation Library:

- Procedures User Guide
- Products User Guide
- Automated End of Day User Guide

Screenshot Disclaimer

Personal information used in the interface or documents is dummy and does not exist in the real world. It is only for reference purposes.

Symbols and Icons

The list of symbols and icons available on the screens are as follows:

Table 5 Symbols and Icons - Common

Symbol/Icon	Function
	Minimize
	Maximize
	Close
	Perform Search
	Open a list
	Navigate to the first record
	Navigate to the last record
	Navigate to the previous record
	Navigate to the next record
	Grid view
	List view

Table 5 (Cont.) Symbols and Icons - Common

Symbol/Icon	Function
	Refresh
	Click this icon to add a new row.
	Click this icon to delete a row, which is already added.
	Calendar
	Alerts
	Unlock Option
	View Option
	New
	Enter query
	Execute query
	Copy
	Delete
	Save
	Search
	Advanced search
	Clear all
	Reset
	Export
	Print

Table 5 (Cont.) Symbols and Icons - Common

Symbol/Icon	Function
	View Details
	Sorting

Table 6 Symbols and Icons - Widget

Symbol/Icon	Function
	Open status
	Unauthorized status
	Rejected status
	Closed status
	Authorized status
	Modification Number
	Hold
	Reverse
	Authorize
	Rollover

1

Job Scheduling

This topic describes the job scheduling process.

Job scheduling is the process where different tasks get executed at a pre-determined time or when the right event happens. A job scheduler is a system that can be integrated with other software systems to execute or notify other software components when a pre-determined, scheduled time arrives. The two types of job schedulers used in Oracle Banking Corporate Lending FCJ architecture are as follows:

- **Quartz** - Provides a scheduler interface to enable operations such as scheduling and unscheduling of jobs and starting, stopping, and pausing the scheduler
- **Flux** - Software component used for performing enterprise job scheduling

This topic contains the following sub-topics:

- [Define Jobs](#)
This topic explains systematic instructions to define jobs.
- [Schedule Jobs](#)
This topic provides the detailed information on schedule jobs.
- [Maintain Jobs](#)
This topic explains systematic instructions to maintain jobs.
- [Notification Process](#)
The topic describes overview of the notification process.
- [Process Notification Parameters](#)
This topic explains systematic instructions to process notification parameters.
- [EMS Process with Scheduling Architecture](#)
This topic provides the information of EMS process with Scheduling Architecture.
- [Approach](#)
This topic provides the approaches used in EMS Process.

1.1 Define Jobs

This topic explains systematic instructions to define jobs.

A job is a business activity that the system performs repeatedly on a timely basis. Oracle Banking Corporate Lending enables to define a job and schedule it using the **Job Maintenance** screen.

1. On **Homescreen**, type **STDJOBMT** in the text box, and click **Next**.
The **Job Maintenance** screen displays.

Figure 1-1 Job Maintenance

Job Maintenance

New Enter Query

Job Description

Job Code *
Job Description
Job Group
Job Type
Max Number Instances *
Scheduler SchedulerFactory
Trigger Type
Scheduler Type
Priority
Message Queue
Validate

Job Details

Cron Expression
Class Or Procedure
No of Submissions
Interval In Seconds
Trigger Listener
Active
Ds Name
Logging Required
Veto Blocked Trigger
Startup Mode

Parameter Details

Audit Exit

Figure 1-2 Job Details

Job Details

Job Name
Job Group
State
Next Fire Time
Scheduler

Search Results

Lock Columns 0

Job Name
Job Group
State
Next Fire Time
Scheduler
Error

No data to display.

Page 1 of 1 K < 1 > X

Pause Resume

Exit

2. On the **Job Maintenance** screen, specify the fields.

Note

The fields, which are marked with an asterisk, are mandatory.

For more information on fields, refer to the field description table.

Table 1-1 Job Maintenance - Field Description

Field	Description
Job Code	Specify the unique code to identify the job.
Job Description	Specify a brief description of what the job is supposed to do.
Job Group	Specify the job group name to represent the same group of jobs for identification.
Job Type	Select the type of job from the drop-down list: - PL/SQL - JAVA

Common Core – Scheduler User Guide
G46886-01
Copyright © 2007, 2025, Oracle and/or its affiliates.

November 4, 2025
Page 2 of 12

Table 1-1 (Cont.) Job Maintenance - Field Description

Field	Description
Max Number Instances	Specify the maximum number of instances that needs to be queued up. For example, If a job runs for more than the duration defined, the next instance of the same job will be ready for processing. This parameter defines the jobs behavior in such cases. If the job is maintained as STATEFUL, then the number of such missed instances will be queued up so that it would start executing once this long-running job ends. This field specifies the number of such job instances that needs to be queued up. If the job is maintained as STATELESS, it indicates the number of threads that can be executed in parallel. If the max number of instances is maintained as 0, no instances are queued or parallel processed till the current running instance is completed.
Scheduler	Specify the name of the scheduler. The system defaults the name to SchedulerFactory . However, the scheduler name can be modified. This signifies the scheduler name which is configured as part of infra.
Trigger Type	Select the type of trigger from the drop-down list: • Simple - Interval based jobs (that is every hour) • Cron: Time based jobs (that is Friday 4:30PM). Note: When the scheduler trigger type is set to CRON, and the parameter is TIMEZONE, then the system triggers the jobs based on the time zone set. If the TIMEZONE property is not available, then the server time zone will be used to trigger the scheduler job.
Scheduler Type	Select the type of scheduler from the drop-down list: • Quartz • Flux
Priority	Select the priority on which the system should execute the jobs in the scheduler from the drop-down list: • Normal • High • Low If two jobs with different priorities fire at the same time, then the system gives preference to the job with higher priority.
Message Queue	Specify the default JMS queue to which a job needs to send the message. Specify this only if the job has to send messages to JMS.
Cron Expression	Specify the corresponding Cron expression for a job with the trigger type as Cron . The user needs to do this to determine the time and interval of job firing.
Class or Procedure	Specify the Java class file name if the job type is Java or the PL/SQL procedure name if the job type is PL/SQL . This denotes which java class or PL/SQL procedure the system should call when a job fires.
Number of Submissions	Specify the number of times a job can fire before it is unscheduled from the scheduler. This applies only to trigger types maintained as Simple .
Interval In Seconds	Specify the time interval between jobs. This applies only to trigger types maintained as Simple .
Trigger Listener	Specify a java class as a trigger listener which will be notified of events such as before a job is fired, after a job is completed, and after misfired jobs.
Active	Check this box to set the job as active. The scheduler does not pick the inactive jobs for scheduling.

Table 1-1 (Cont.) Job Maintenance - Field Description

Field	Description
Ds Name	Specify the name of the database schema to which the job has to connect. This attribute is used in case of multi-instance deployment of Oracle Banking Corporate Lending application.
Logging Required	Check this box to indicate that system should log each firing of the job. This helps in logging the firing time of the job and key log info as part of that firing. This also enables tracking of each jobs firing times and helps in identifying miss-fired jobs.
Veto Blocked Trigger	Check this box to trigger a veto block.
Start up Mode	Specify the start up mode of the job from the drop-down list: • Auto - The job starts automatically when the Oracle Banking Corporate Lending application starts. • Manual - Start the job manually in the job controller by resuming the job.

Parameter Details: Specify the job specific parameters, which are passed to the job class or procedure at run time. The following details are captured here.

Table 1-2 Parameter Details - Field Description

Field	Description
Parameter Name	Specify the name of the job parameter. The parameter name specified here is passed to the job class or procedure at run time.
Data Type	Specify the data type of the parameter.
Parameter Value	Specify the value of the parameter.

3. Click **Exit** to end the transaction.

1.2 Schedule Jobs

This topic provides the detailed information on schedule jobs.

All jobs for scheduling are stored in a static data store and each job is associated with a name indicating where the job has to execute. Jobs are created in the Application Server and are scheduled based on this data.

Note

The job name should be unique across the schedulers available in the system.

When the application server starts, the job details from the static data store will get cached. These cached jobs will then be scheduled using either the quartz or flux scheduler.

For example, the notification process can be handled by the job schedulers as follows:

1. When a contract is created in Oracle Banking Corporate Lending, a database level trigger acting on the contract main table inserts details like base table name, primary key fields, primary key values and branch code into a notification log table and sets the process status of the inserted record as **U** (unprocessed).
2. The scheduled job polls the notification log table for unprocessed records and validates whether notification is required.

3. If notification is not required, then the process status is set to **N** (not required) in notification log table.
4. If notification is required then notifications are sent to the respective destination and the process status of the record is changed to **P** (Processed) in notification log table.

1.3 Maintain Jobs

This topic explains systematic instructions to maintain jobs.

Through the **Job Details** screen, the details of scheduled jobs can be viewed. On this screen, the user can pause or resume a job that has been scheduled, and also the user can submit the records as a job for replication in the branch database.

1. On **Homescreen**, type **SMSJBBRW** in the text box, and click **Next**.

The **Job Details** screen displays.

Figure 1-3 Job Details

2. On the **Job Details** screen, specify the fields.

Note

The fields, which are marked with an asterisk, are mandatory.

For more information on fields, refer to the field description table.

Table 1-3 Job Details - Field Description

Field	Description
Job Name	Click Search and select the name of the job from the list of values.
State	Click Search and select the state of the job. The following options are possible for Quartz schedulers: • Acquired • Waiting • Blocked • Paused
Scheduler	Click Search and select the scheduler to which the job has been assigned.

Table 1-3 (Cont.) Job Details - Field Description

Field	Description
Job Group	Click Search and select the group to which the job belongs.
Next Fire Time	Specify the time when the job is scheduled to be run next.

- Click **Search** after specifying the search criteria.

The system displays the records that match the search criteria:

- **Job Name**
 - **Job Group**
 - **State**
 - **Next Fire Time**
 - **Scheduler**
 - **Error**
- Click **Pause** to pause the job.
 - Click **Resume** to resume the paused job.

 Note

The fields, which are marked with an asterisk, are mandatory.

For more information on fields, refer to the field description table.

On clicking the **Resume**, the job is scheduled for its next fire time. A job can take any of the following states:

Table 1-4 Job State

State	Description
SCHEDULED	This indicates that the message is processed.
NOT SCHEDULED	This indicates that the message processing is not scheduled.
PAUSED	This indicates that the job is manually paused from executing.
ERROR	A job trigger arrives at the Internal Server Error state when the scheduler attempts to fire it, but cannot due to an error creating and executing its related job, hence pausing the job. Also, a job arrives at an ERROR state for the following reasons: • When the associated class for the job is not present in class path. • If the during setup, the queue has not been created, but a job has been created for that queue. • If call to the Scheduler EJB has failed. • If job related pooling tables are invalid.

Note

Each job is created with the **Location Code** maintained in the **sttm_flexbranch_loc** table runs for the respective branch location. If a new branch is added to the bank for branch replication then the application must be restarted to add that particular branch in the **Job Details** screen.

6. Click **Exit** to end the transaction.

1.4 Notification Process


The topic describes overview of the notification process.

The notification process is in two layers. In the first layer the notification process as part of jobs in the FCJ scheduler sends minimal data required for notification to an internal JMS queue. In the second layer the notification process as part of an MDB that listens on internal JMS queue builds final notifications and sends them to their intended destinations.

The Notification Process in Oracle Banking Corporate Lending using the jobs scheduler is as follows:

1. The trigger on the base table inserts key details into a static notification log table instead of Oracle AQ.
2. Once the Job is triggered, a request is sent to the EJB layer from the job execution class and the notification log table is polled for unprocessed records.
3. Each unprocessed record is locked.
4. The record is verified against the notification maintenance and checked whether notification is to be sent or not.
5. If a notification is to be sent, a pre-notification message XML is built and it is sent to internal notify_queue(JMS queue).
6. The job is then rescheduled to fire next time based on the previous execution.

Figure 1-4 Flow Chart of Notification Process in Scheduler




The notification process in MDB is as follows:

1. The Notification MDB listens on the internal notify JMS queue
2. On any message received, the MDB identifies which schema to connect using the JNDI name being present as part of the message XML.
3. Gateway notification processing package is called from MDB in order to build the actual notifications.

4. In MDB the notifications built is processed and sent to the destination specified in corresponding notification.
5. In case of any exception, the whole transaction is rolled back.
6. If all notifications are successfully processed then the transaction is committed.

Figure 1-5 Flow Chart of Notification Process in MDB



1.5 Process Notification Parameters

This topic explains systematic instructions to process notification parameters.

The user can view and amend certain notification parameters in Oracle Banking Corporate Lending using the **Gateway Notification Maintenance** screen.

1. On **Homescreen**, type **IFDNOTIF** in the text box, and click **Next**.

The **Gateway Notification Maintenance** screen displays.

Figure 1-6 Gateway Notification Maintenance

2. On the **Gateway Notification Maintenance** screen, specify the fields.

Note

The fields, which are marked with an asterisk, are mandatory.

For more information on fields, refer to the field description table.

Table 1-5 Gateway Notification Maintenance - Field Description

Field	Description
Notification Code	The system displays a unique code to identify a notification.
Description	The system displays a brief description of the notification. However, the description can be modified on this screen.
Operation	Select the type of operation for the notification from the drop-down list: • Insert - To indicate a new operation of notification function. • Update - To indicate a modification operation of notification.
Gateway Operation	Specify the gateway operation name to execute the query for the mentioned service.
Gateway Service	Specify the gateway service to be used to get the full screen response.
Request Node	Specify the gateway IO request node to be used in the querying operation.

Table 1-5 (Cont.) Gateway Notification Maintenance - Field Description

Field	Description
Specific Notification	Switch the toggle button to indicate the system to send a specific notification. The system handles any deviation from the generic notification process by creating specific triggers once this field is checked.
Full Screen Reply Required	Switch the toggle button to indicate that the full-screen notification response has to be sent. Otherwise, the primary key response notification is sent.
Head Office	Switch the toggle button to send notification only from head office.

3. Click **Exit** to end the transaction.

1.6 EMS Process with Scheduling Architecture

This topic provides the information of EMS process with Scheduling Architecture.

The topic contains following sub-topic:

- [EMS Process](#)
The topic describes the EMS process.

1.6.1 EMS Process

The topic describes the EMS process.

- **Incoming EMS Process**
A job is scheduled to poll the incoming folder on a timely basis. Once a message is received in the folder, the job picks the message and sends it to an internal JMS queue. An MDB listening on the queue will read the message and identifies the media and processes the message.
- **Outgoing EMS Process**
A job is scheduled to poll the outgoing messages that are generated but not handed off. Each messages polled will be sent to an internal JMS queue. An MDB, acting upon the internal JMS queue will pick the message from the queue and sends the message to the appropriate destination (Folder, e-mail, or JMS queue).

1.7 Approach

This topic provides the approaches used in EMS Process.

The Outgoing EMS Process happens in two layers.

The EMS process as part of jobs in FCJ scheduler, polls the outgoing message table of Oracle Banking Corporate Lending for generated and un-send messages. The job then sends minimal data about the message to be handed off, to an internal JMS queue.

The EMS process is part of an MDB that listens on the internal JMS queue to build the final message and to send to their intended destinations.

The Incoming EMS Process happens in two layers.

The EMS process as part of jobs in FCJ scheduler, which polls the pre-configured folder for messages and sends the messages read, to EMS internal queue.

The EMS process is part of an MDB, that listens to the internal JMS queue identifies the message from the queue, and calls the incoming messages service package in the backend to process the message. Additionally, the MDB can be made an independent unit to listen to external JMS to process incoming messages.

The Incoming EMS Process as part of the jobs scheduler is as follows:

Once the job is triggered, it polls for messages in a folder (Configured for incoming messages).

Each message is then sent to an internal JMS queue.

The job is then rescheduled to fire next time.

EMS processes in MDB are as follows:

An MDB that listens on the internal EMS incoming queue will receive the message.

The media details are identified and the incoming message processing package in the backend is called to process the message.

In case of any exception while processing, message will be sent to a deferred queue.

In case of messages directly arrive to the JMS queue instead of a folder; the same MDB will be configured to listen on a specific queue.

Index

I

IFDNOTIF - Gateway Notification Maintenance
Screen, [10](#)

S

SMSJBBRW - Job Details screen, [5](#)
STDJOBMT - Job Maintenance screen, [1](#)