Oracle® Banking Trade Finance Trade Finance Installer Prerequisite Document





Oracle Banking Trade Finance Trade Finance Installer Prerequisite Document, Release 14.7.5.0.0

G15567-01

Copyright © 2020, 2024, Oracle and/or its affiliates.

Primary Authors: (primary author), (primary author)

Contributing Authors: (contributing author), (contributing author)

Contributors: (contributor), (contributor)

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle®, Java, MySQL, and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

1 Installer Prerequisite Setup



1-1 Environment Property File Configuration

1-3



1

Installer Prerequisite Setup

The overview of this document is to share you the knowledge on how installer is designed.

Two installer modes have to be used during setup of environment:

GUI Installer

- Located under \INSTALLER\GUI
- GUI Installer is required for below activities:
 - Property File Creation
 - Basic Setup
 - Environment Property file configuration

2. Silent Installer

- Located under \INSTALLER\GUI
- Silent Installer will be required for below activities:
 - Database Setup
 - EAR Building

In Linux - For creating the property file

- 1. Following steps to set the variables:
 - export JAVA HOME=JAVA HOME path
 - export PATH=JAVA_HOME/bin:\$PATH
 - export ORACLE_HOME=ORACLE_HOME path
 - export PATH=ORACLE HOME/bin:\$PATH
- Now traverse to the path where FCUBSInstaller.sh file is present in the server.
- 3. Give access rights to the file and Run "./FCUBSInstaller.sh" file.
- **4.** Provide the necessary home path to set and launches the Installer.
- Run the "./FCUBSInstaller.sh" file in any graphical desktop sharing system like TigerVNC.

```
Tue May 16, 12:21 PM fmw12c
 🙉 Applications Places System 🌏 🍣 🗾
P-
                                                                       SOURCE : bash
File Edit View Scrolloack Bookmarks Settings Help

[fmw12c@whf00alm -]$ export JAVA_HOME-/scratch/app/java/jdk1.8.0_111/

[fmw12c@whf00alm -]$ export PATH=JAVA_HOME/bin:$PATH

[fmw12c@whf00alm -]$ export ORACLE_HOME-/scratch/fmw12c/app/fmw12c/product/12.1.0/dbhome_1/

[fmw12c@whf00alm -]$ export PATH=ORACLE_HOME/bin:$PATH

[fmw12c@whf00alm -]$ cd /scratch/work_area/INSTALLER/SOURCE/

[fmw12c@whf00alm SOURCE]$ ./FCUBSInstaller.sh
in beginning
Flex Cube UBS : Release 12.5.0.0.0 - Production on
Copyright (c) 2016, Oracle Financial Services Software Ltd. All rights reserved.
FLEXCUBE INSTALLER running in *** EXEC *** mode
______
Enter JAVA HOME Directory:
/scratch/app/java/jdk1.8<sup>°</sup>.0_111
Java Home Path has been set successfully.
nter Application Server Home:
/scratch/app/Oracle/Middleware/Oracle_Home/wlserver
WEBLOGIC Application Server Home has been set successfully.
Enter ORACLE Home Directory:
/scratch/fmw12c/app/fmw12c/product/12.1.0/dbhome_1
ORACLE Home has been set successfully.
 learing the compiled files.....
```

Source Structure:

The Installation can be done in different ways and Source Structure should be maintained as below:

The OBTF_OSDC.zip can be used without any modifications.

Environment Setup Steps:

Below are the sequence of steps to be followed during Environment Setup:

- 1. Property File Creation: (Refer: OBTF Installer Property File Creation.pdf)
 - Two property files are generated
 - "fcubs.properties", i.e. required for application EAR building.
 - "env.properties", i.e. common property required for environment setup.
- 2. Maintaining environment property file: (Refer next section)

Modification of the generated "env.properties", if required, is to be done in this step.

Database Setup: (Refer: OBTF_DB_Setup.pdf)

Database setup involves DDL Load, Object Compilation and Static Data Compilation. This is done using the silent installer.

4. Basic Setup: (Refer: OBTF_DB_Setup.pdf)

Post INC Load, basic setup has to be done. Basic Setup is done using GUI Installer.

Application EAR build: (Refer: OBTF_EAR_Building.pdf)

OBTF Application and Gateway EAR building can be done using the silent installer.

Figure 1-1 Environment Property File Configuration

```
#Thu Nov 16 15:05:27 IST 2017
EXTERNAL JSUIXML_REQUIRED=N

FUENS PROPERTIES PATH=D:/Projects/Project-Installer/125_core_support/SOFT/INSTALLER/SOFT/GUI/scheduler.properties

JAVA_HOME_d:/jdk8

DECENTRALIZED=N

RECENT BROWSE LOCATION=D:/Frojects/Project-Installer/Bugs/125-enhancement/New/propertyfile_testing/elcm-em/FCUBS/fcubs.properties

WEBLOGIC HOME-D:/Oracle/Middleware/Oracle_Home/wlserver

PATCHSST INSTALLATION=N

HOST ENTITY ID=-askMoirHHm7jbLfc1Tb6Fq677YD7f/xQ/lhDu0HcRIA=

DECENTRALIZED FCUBS PROPERTIES PATH=

CONNECTING STRING SMS-PDB123

GW PROPERTIES PATH=D:/Projects/Project-Installer/125_core_support/SOFT/INSTALLER/SOFT/logs/GW_WS_Prop.properties

CONNECTING STRING SMS-PDB123

GW PROPERTIES PATH=D:/Projects/Project-Installer/125_core_support/SOFT

SOURCE PATH=D:/Projects/Froject-Installer/125_core_support/SOFT

PASSNORD SMS-PXCS5x4BQT6dgrIMD7e2zA=

SYMMETRIC KEY=oraclefinancialsolutions

EAR DESITIANTION FATH=D:/Projects/Project-Installer/125_core_support/SOFT

EXTERNAL PROPERTY PATH=

PASSNORD SMS-PXCS5x4BQT6dgrIMD7e2zA==

PORT SMS-1S21

SCHEMA NAME ENTITY ID1=SC1

EXTERNAL JULXML PATH=

SERVICE NAME ENTITY ID1=CY97OtlQGGT/UCsy59Shyw==

PORT SMS-1S21

SCHEMA NAME SMS-FXCS5x4BQT6dgrIMD7e2zA==

EXTERNAL PROPERTY PATH REQUIRED=N

APPSERVER NOME_DI/Cracle/Middleware/Oracle Home/wlserver

SERVICE NAME_SMS-CYCOLOGOFT/CUS9SShyw==

HOST SMS-3KMO1+Hm7jbLfc1Tb6Fq67TVD7f/xQ/lhDu0HcRIA=

SCHEMA NAME_SMS-FXCS5x4BQT6dgrIMD7e2zA==

CONTEXT NAME_FCURSeOME

CONTEXT NAME_FCUR
```

Note:

A single property file is used for both DB Compilation and EAR build. Hence all the properties are located in a single property file. Some properties may not be applicable during a certain setup and those should not be modified (should be left with default values).

CONFIGPATH:

Absolute path to the folder containing the configuration files, is to be provided. Configuration files are located under \INSTALLER\SOFT\config\Application

JAVA_HOME

Absolute path to the home folder of JDK 1.8 is to be provided.

APPSERVER_HOME

Absolute path to the home folder of Application Server.

ORACLE_HOME

Absolute path to the home folder of Oracle Database Client is to be provided.

SOURCE PATH and EAR DESTINATION PATH

Specify the destination directory. Here destination path should be same as the source file path

FCUBS_PROPERTIES_PATH

Absolute path where the fcubs.properties file, is to be provided.

GW_PROPERTIES_PATH

Absolute path to the Gateway Properties file is to be provided.

APPLICATION_TYPE

Application Type is maintained as per the Application Name selected in the GUI Installer.

EAR_NAME

Specify a name for the Application to be created.

CONTEXT NAME

Specify a name for the Application Context

EXTERNAL_JSUIXML_REQUIRED

This field explains whether JS and UIXML folders are external or integrated within ear file.

It Holds values as 'Y' or 'N'. EXTERNAL_JSUIXML_REQUIRED=Y indicates that JS and UIXMLs are not within the ear file generated.

EXTERNAL JSUIXML PATH

This path is mandatory if EXTERNAL_JSUIXML_REQUIRED=Y. JS and UIXMLs generated during ear file creation should be placed in the path given.

WEBLOGIC_HOME

Absolute path to the home folder of weblogic.

PATCHSET_INSTALLATION

Parameter value will be 'N' for console and 'Y' for patchset installation.

EXTERNAL_PROPERTY_PATH_REQUIRED:

This field explains whether property file is external or integrated within ear file.



EXTERNAL PROPERTY PATH

This path is mandatory if EXTERNAL_PROPERTY_PATH_REQUIRED =Y.

SYMMETRIC KEY

This key is used for encryption logic.

The below parameters stores SMS Schema details:

HOST_SMS: Host name of SMS Schema will be stored in encrypted format.

SCHEMA_NAME_SMS: Schema name will be encrypted and stored

PASSWORD_SMS: Encrypted form of password will be saved against this parameter.

SERVICE_NAME_SMS: Encrypted form of Service name.

PORT_SMS: Contains Port number of SMS Schema.

CONNECTING_STRING_SMS: Encrypted connected String of SMS Schema.

ENTITY NOS: It stores the number of Entity Schemas required.

The below parameters stores Entity Schema details. This information will be captured for all the entities with respective entity name as suffix.

HOST_ENTITY_ID1: Host name of Entity Schema will be stored in encrypted format.

SCHEMA_NAME_ENTITY_ID1: Entity Schema name will be encrypted and stored.

PASSWORD ENTITY ID1: Encrypted form of password will be saved against this parameter.

SERVICE NAME ENTITY ID1: Encrypted form of Service name.

PORT_ENTITY_ID1: Contains Port number of first Entity Schema.

CONNECTING_STRING_ENTITY_ID1: Encrypted connected String of Entity Schema

COMPILE_IN_ALL_ENTITIES:

This parameter holds value as 'Y' or 'N'. If 'N' then necessary objects will be compiled in all the entities mentioned.



Paths have to be maintained with '/' separator as it is maintained only for WINDOWS. '\' slash is considered as an escape character so '/' slash is given in windows.

In the process of property file creation, when Save is clicked at the end, Property file is saved in \INSTALLER\GUI\LOGS.

On launch of GUI Installer for creating the property file , the env properties file gets generated which is present in \INSTALLER\SOURCE\logs path need to be manually copied to \INSTALLER\SOFT\logs path. This method is followed for EAR creation and Back-end build as it is done by the Silent Installer.

If PAYMENTS needs to install as Co-deployed along with OBTF then PAYMENTS folder from PAYMENTS OSDC zip should be placed parallel to OBTF folder in the OBTF OSDC zip.

INFRA inside PAYMENTS should be moved and merged with CORE INFRA.

Following are the examples to execute for EAR Run, Gateway EAR Run and DB Compile for both Windows and Linux.

For Queues and Queue Connection Factory, please refer to the Resources to be created document.

FOR LINUX	FOR WINDOWS	PRODUCT USED
SMSDBCompileRun.sh	SMSDBCompileRun.bat	SMS DB
TFEarRun.sh	TFEarRun.bat	TRADE FINANCE MANAGEMENT
TFDBCompileRun.sh	TFDBCompileRun.bat	TRADE FINANCE DB
TFGatewayEarRun.sh	TFGatewayEarRun.bat	TRADE FINANCE GATEWAYS (SOAP)
TFGatewayRestEarRun.sh	TFGatewayRestEarRun.bat	TRADE FINANCE GATEWAY (REST)

