Oracle Banking Trade Finance Resources to be Created



Release 14.7.6.0.0 G32579-01 April 2025

ORACLE

Oracle Banking Trade Finance Resources to be Created, Release 14.7.6.0.0

G32579-01

Copyright © 2007, 2025, Oracle and/or its affiliates.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle®, Java, MySQL, and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

Preface

| Purpose | iv |
|-----------------------------|----|
| Audience | iv |
| Documentation Accessibility | iv |
| Critical Patches | iv |
| Diversity and Inclusion | iv |
| Conventions | v |
| Related Resources | v |
| Screenshot Disclaimer | v |
| | |

1 RESOURCES TO BE CREATED ON APPLICATION SERVER

| 1.1 | Intro | duction | 1-1 |
|-----|-------|----------------------------------|-----|
| 1.2 | Reso | purce Types | 1-1 |
| 1.3 | Reso | purce prerequisites for Plug-ins | 1-1 |
| | 1.3.1 | Oracle Banking Trade Finance | 1-2 |
| | 1.3.2 | SMS | 1-3 |
| | 1.3.3 | Scheduler | 1-4 |
| | 1.3.4 | Gateway | 1-6 |
| | 1.3.5 | ELCM | 1-7 |
| | 1.3.6 | REST API services | 1-8 |



Preface

- Purpose
- Audience
- Documentation Accessibility
- Critical Patches
- Diversity and Inclusion
- Conventions
- Related Resources
- Screenshot Disclaimer

Purpose

This guide helps the user to create the required resources for Oracle Banking Trade Finance.

Audience

This guide is intended for anyone responsible for installing Oracle Banking Application.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc.

Access to Oracle Support

Oracle customer access to and use of Oracle support services will be pursuant to the terms and conditions specified in their Oracle order for the applicable services.

Critical Patches

Oracle advises customers to get all their security vulnerability information from the Oracle Critical Patch Update Advisory, which is available at Critical Patches, Security Alerts and Bulletins. All critical patches should be applied in a timely manner to ensure effective security, as strongly recommended by Oracle Software Security Assurance.

Diversity and Inclusion

Oracle is fully committed to diversity and inclusion. Oracle respects and values having a diverse workforce that increases thought leadership and innovation. As part of our initiative to build a more inclusive culture that positively impacts our employees, customers, and partners,



we are working to remove insensitive terms from our products and documentation. We are also mindful of the necessity to maintain compatibility with our customers' existing technologies and the need to ensure continuity of service as Oracle's offerings and industry standards evolve. Because of these technical constraints, our effort to remove insensitive terms is ongoing and will take time and external cooperation.

Conventions

The following text conventions are used in this document:

| Convention | Meaning |
|------------|--|
| boldface | Boldface type indicates graphical user interface elements associated with an action, or terms defined in text. |
| italic | Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values. |
| monospace | Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter. |

Related Resources

For more information, see these Oracle Banking Trade Finance resources:

- Oracle Banking Trade Finance Release Notes
- Oracle Banking Trade Finance Install & Upgrade

Screenshot Disclaimer

Personal information used in the interface or documents is dummy and does not exist in the real world. It is only for reference purposes.



1 RESOURCES TO BE CREATED ON APPLICATION SERVER

1.1 Introduction

This chapter explains list of resources to be created for OBTF application.

1.2 Resource Types

Configure the application server for Oracle Banking Trade Finance Application. Ensure that the following resources are available before deployment:

- Data source
- JMS resources
- Debug paths for host and branch



Note:

In case of Multi Entity, all data sources must be created separately for each entity. The JNDI name will be differentiated by suffixing entity name.

Examples: If Data source is 'jdbc/fcjDevDs' then jdbc/fcjDevDs+entity name will be lookup the application. (jdbc/fcjDevDs+entity name) jndi should be presented in application server

1.3 Resource prerequisites for Plug-ins

Resource prerequisites for different plug-ins are explained below. In case you wish to include a plug-in, ensure that the corresponding resources are created.

- Oracle Banking Trade Finance
- SMS
- Scheduler
- Gateway
- ELCM
- REST API services



1.3.1 Oracle Banking Trade Finance

OBTF needs below resources before deployment. Create the following queues and connection factories in the application server.

| | Table 1-1 | JMS | Connection | Factories |
|--|-----------|-----|------------|-----------|
|--|-----------|-----|------------|-----------|

| QCF Label | QCF |
|---------------------------------------|-----------------|
| Notify Destination QCF | NotifyDestQCF |
| Deferred QCF | DefferedDestQCF |
| Notify QCF | NOTIFY_MDB_QCF |
| Incoming QCF | EmsQcf |
| BIP QCF | BIPQCF |
| GI Upload QCF | GI_UPLOAD_QCF |
| Sanction Check QCF | SNCKREQQCF |
| <internally referred=""></internally> | ELMDBQCF |
| <internally referred=""></internally> | EL_NOTIFY_QCF |

Table 1-2 Queues

| QUEUE Label | QUEUE |
|----------------------------------|-------------------------------|
| Notify Destination Queue Name | NOTIFY_DEST_QUEUE |
| Deferred Queue Name | DEFFERED_DEST_QUEUE |
| Notify Queue Name | NOTIFY_QUEUE |
| Dead Letter Queue name | NOTIFY_QUEUE_DLQ |
| Incoming BackupQueue name | EMS_QUEUE_BACK |
| Incoming Dead Letter Queue name | EMS_QUEUE_DLQ |
| Incoming Queue Name | EMS_INQUEUE |
| Outgoing Queue Name | EMS_OUTQUEUE |
| SFMS Incoming Queue | SFMS_INQUEUE |
| RTGS Incoming Queue | RTGS_INQUEUE |
| BIP Queue Name | BIPREPORT_QUEUE |
| BIP Dead Letter Queue Name | INTERNAL_BIP_QUEUE_DLQ |
| BIPadvice Queue Name | BIPADVREPORT_QUEUE |
| BIPadvice Dead Letter Queue Name | INTERNAL_BIP_ADVICE_QUEUE_DLQ |
| GI Upload Queue Name | INTERNAL_GI_UPLOAD_QUEUE |
| GI Upload Dead Letter Queue Name | INTERNAL_GI_UPLOAD_DLQ |
| BulkerMDB Queue | EMS_BULKERQUE |
| Sanction Check Request Queue | SNCKREQ_QUEUE |
| Sanction Check Response Queue | SNCKRES_QUEUE |



Table 1-2 (Cont.) Queues

| QUEUE Label | QUEUE |
|---------------------------------------|-----------------|
| Sanction Check Listener Queue | SNCKASYNC_QUEUE |
| <internally referred=""></internally> | ELMDB_REQ_Q |
| <internally referred=""></internally> | ELMDB_RES_Q |
| <internally referred=""></internally> | ELMDB_DLQ |
| <internally referred=""></internally> | EL_NOTIFY_REQ_Q |
| <internally referred=""></internally> | EL_NOTIFY_RES_Q |
| <internally referred=""></internally> | EL_NOTIFY_DLQ |

Table 1-3 Data source

| Datasource Name | Datasource Label | Туре | Default Value |
|-----------------|----------------------|--------|---------------------|
| INIT_DATASOURCE | Data Source | NON-XA | jdbc/fcjdevDS |
| SCHEDULER_DS | Scheduler Datasource | ХА | jdbc/fcjSchedulerDS |

STOP

Note:

You need to create two more data sources for Oracle Banking Trade Finance

- <u>Scheduler</u>: You need to create XA data source for Oracle Banking Trade Finance with the JNDI name '_XA' for scheduler. For example, if the Oracle Banking Trade Finance HOST Non XA data source JNDI name is 'jdbc/fcjdevDS', then you need to create another data source for Oracle Banking Trade Finance with the JNDI name 'jdbc/fcjdevDS_XA'.
- <u>Batch Process</u>: You need to create data source for Oracle Banking Trade Finance with the JNDI name '_ASYNC for batch process. For example, if the Oracle Banking Trade Finance HOST Non XA data source JNDI name is 'jdbc/ fcjdevDS', then you need to create another data source for Oracle Banking Trade Finance with the JNDI name 'jdbc/fcjdevDS_ASYNC.

1.3.2 SMS

SMS needs below Data sources before deployment.

Table 1-4 DataSource

| Datasource Name | Datasource Label | Label Type | Default Value |
|-------------------------|------------------|------------|---------------|
| FCUBS_SMS_POOL_N AME | DataSource | NON-XA | jdbc/fcjdevDS |



1.3.3 Scheduler

If scheduler is included in the property file, create the following queues and connection factories in the application server.

In case of Remote Scheduler, create the following queues, connection factories and Datasources in the application server where scheduler EAR will be deployed.

Table 1-5 Connection Factories

| QCF Label | QCF |
|------------------------|-----------------|
| Notify Destination QCF | NotifyDestQCF |
| Deferred QCF | DefferedDestQCF |
| Notify QCF | NOTIFY_MDB_QCF |
| Incoming QCF | EmsQcf |
| BIP QCF | BIPQCF |
| Sanction Check QCF | SNCKREQQCF |
| GI Upload QCF | GI_UPLOAD_QCF |

All these must be XA enabled.

Table 1-6 Queues

| QUEUE Label | QUEUE |
|----------------------------------|-------------------------------|
| Notify Destination Queue | NOTIFY_DEST_QUEUE |
| Name | |
| Deferred Queue Name | DEFFERED_DEST_QUEUE |
| Notify Queue Name | NOTIFY_QUEUE |
| Dead Letter Queue name | NOTIFY_QUEUE_DLQ |
| Incoming BackupQueue name | EMS_QUEUE_BACK |
| Incoming Dead Letter Queue name | EMS_QUEUE_DLQ |
| Incoming Queue Name | EMS_INQUEUE |
| Outgoing Queue Name | EMS_OUTQUEUE |
| SFMS Incoming Queue | SFMS_INQUEUE |
| RTGS Incoming Queue | RTGS_INQUEUE |
| Sanction Check Request Queue | SNCKREQ_QUEUE |
| Sanction Check Response Queue | SNCKRES_QUEUE |
| Sanction Check Listener Queue | SNCKASYNC_QUEUE |
| BIP Queue Name | BIPREPORT_QUEUE |
| BIP Dead Letter Queue Name | INTERNAL_BIP_QUEUE_DLQ |
| BIPadvice Queue Name | BIPADVREPORT_QUEUE |
| BIPadvice Dead Letter Queue Name | INTERNAL_BIP_ADVICE_QUEUE_DLQ |
| GI Upload Queue Name | INTERNAL_GI_UPLOAD_QUEUE |



Table 1-6 (Cont.) Queues

| QUEUE Label | QUEUE |
|----------------------------------|------------------------|
| GI Upload Dead Letter Queue Name | INTERNAL_GI_UPLOAD_DLQ |

Topic Connection Factory

NotifyDestTCF

Торіс

• NOTIFY_DEST_TOPIC

To configure scheduler and EMS with MQ series, follow the steps given below.

- Create queues in MQ Series
- Create binding file
- Copy the MQ series JAR files to Oracle WebLogic domain library folder

Table 1-7 Datasources

| Datasource Name | Datasource Label | Туре | Default Value |
|-----------------|----------------------|--------|---------------------|
| INIT_DATASOURCE | Data Source | NON-XA | jdbc/fcjdevDS |
| SCHEDULER_DS | Scheduler Datasource | ХА | jdbc/fcjSchedulerDS |





Note:

You need to create another XA data source for Oracle Banking Trade Finance with the JNDI name '_XA' for Scheduler. For example, if the Oracle Banking Trade Finance HOST Non XA data source JNDI name is 'jdbc/fcjdevDS', then you need to create another data source for Oracle Banking Trade Finance with the JNDI name 'jdbc/fcjdevDS_XA'.

| Table 1-8 Security Provider Libraries | Table 1-8 | Security Provider Libraries |
|---------------------------------------|-----------|-----------------------------|
|---------------------------------------|-----------|-----------------------------|

| File Name | Download Location | Instructions |
|---|---|--|
| bcprov-jdk(Latest Qualified Version).jar | https:// www.bouncycastle.org/ latest_releases.html | Copy the file 'bcprov- jdk(Latest Qualified Version).jar' to the directory '{WL_JAVA_HOME}/jre/lib /ext' Here, 'WL_JAVA_HOME' is the Java root directory from which WebLogic server is running. Restart Oracle WebLogic server. |

For details on latest version of the software qualified with Oracle Banking Trade Finance, refer to the release certificate.

1.3.4 Gateway

If scheduler is included in the property file, create the following queues and connection factories in the application server.

| Table 1-9Connection Factories | Table 1-9 | Connection | Factories |
|-------------------------------|-----------|------------|-----------|
|-------------------------------|-----------|------------|-----------|

| QCF Label | QCF |
|-----------|--------|
| MDB QCF | MDBQCF |

All these must be XA enabled.

Table 1-10 Queues

| QUEUE Label | QUEUE |
|--------------------|--------------------|
| MDB Request Queue | MDB_QUEUE |
| MDB Response Queue | MDB_QUEUE_RESPONSE |
| MDB DL Queue | MDB_QUEUE_DLQ |



Table 1-11 DataSource

| ĺ | Datasource Name | Datasource Label | Туре | Default Value |
|-----|-----------------------------------|------------------|--------------------------------------|----------------|
| - 1 | FCUBS_MSG_SCHEM A_CON_POOLNAME | DataSource | XA for MDB and NON- XA for others | FLEXTEST.WORLD |
| | FCUBS_SMS_POOL_N AME | DataSource | NON-XA | jdbc/fcjdevDS |

1.3.5 ELCM

If ELCM application has to be deployed, create the following queues and connection factories in the application server.

| Table 1-12 JMS C | onnection Factories |
|------------------|---------------------|
|------------------|---------------------|

| QCF Label | QCF |
|------------------------|-----------------|
| EL gateway Notify QCF | EL_NOTIFY_QCF |
| EL Gateway MDB QCF | ELMDBQCF |
| Notify Destination QCF | NotifyDestQCF |
| Deferred QCF | DefferedDestQCF |
| Notify QCF | NOTIFY_MDB_QCF |
| Incoming QCF | EmsQcf |
| BIP QCF | BIPQCF |
| GI Upload QCF | GI_UPLOAD_QCF |

Table 1-13JMS Queues

| QUEUE Label | QUEUE |
|--|---------------------|
| EL gateway Notify Request Queue Name | EL_NOTIFY_REQ_Q |
| EL gateway Notify Response Queue Name | EL_NOTIFY_RES_Q |
| EL gateway Notify DeadLetter Queue Name | EL_NOTIFY_DLQ |
| EL Gateway MDB Request Queue Name | ELMDB_REQ_Q |
| EL Gateway MDB Response Queue Name | ELMDB_RES_Q |
| EL Gateway MDB DeadLetter Queue Name | ELMDB_DLQ |
| Notify Destination Queue Name | NOTIFY_DEST_QUEUE |
| Deferred Queue Name | DEFFERED_DEST_QUEUE |
| Notify Queue Name | NOTIFY_QUEUE |
| Dead Letter Queue name | NOTIFY_QUEUE_DLQ |
| Incoming BackupQueue name | EMS_QUEUE_BACK |
| Incoming Dead Letter Queue name | EMS_QUEUE_DLQ |



| Table 1-13 | (Cont.) JMS Queues |
|------------|--------------------|
|------------|--------------------|

| QUEUE Label | QUEUE |
|----------------------------------|-------------------------------|
| Incoming Queue Name | EMS_INQUEUE |
| Outgoing Queue Name | EMS_OUTQUEUE |
| SFMS Incoming Queue | SFMS_INQUEUE |
| RTGS Incoming Queue | RTGS_INQUEUE |
| BIP Queue Name | BIPREPORT_QUEUE |
| BIP Dead Letter Queue Name | INTERNAL_BIP_QUEUE_DLQ |
| BIPadvice Queue Name | BIPADVREPORT_QUEUE |
| BIPadvice Dead Letter Queue Name | INTERNAL_BIP_ADVICE_QUEUE_DLQ |
| GI Upload Queue Name | INTERNAL_GI_UPLOAD_QUEUE |
| GI Upload Dead Letter Queue Name | INTERNAL_GI_UPLOAD_DLQ |

For ELCM, We need to create the following data sources for JDBC resources:

| Datasource Name | Datasource Label | Туре | Default Value |
|--------------------|----------------------|--------|---------------------|
| INIT_DATASOURCE | Data Source | NON-XA | jdbc/fcjdevDS |
| EL_INIT_DATASOURCE | Scheduler DataSource | NON-XA | jdbc/fcjSchedulerDS |

1.3.6 REST API services

The following Datasource has to be created for REST API Service Application:

Table 1-14Data Source:

| Datasource Name | Datasource Label | Туре | Default Value |
|-----------------|------------------|------|---------------|
| INIT_DATASOURCE | Data Source | ХА | jdbc/fcjdevDS |