

Oracle® Fusion Middleware

Creating Schemas with the Repository Creation Utility



14c (14.1.2.1.0)

F85502-02

March 2025

The Oracle logo, consisting of the word "ORACLE" in white, uppercase, sans-serif font, centered within a solid red square.

ORACLE®

Oracle Fusion Middleware Creating Schemas with the Repository Creation Utility, 14c (14.1.2.1.0)

F85502-02

Copyright © 2018, 2025, Oracle and/or its affiliates.

Primary Author: Oracle Corporation

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle®, Java, MySQL, and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

Preface

Intended Audience	vii
Documentation Accessibility	vii
Diversity and Inclusion	vii
Related Documents	viii
Conventions	viii

1 About the Repository Creation Utility

Verifying RCU System and Database Requirements	1-1
RCU Supported Platforms	1-1
Finding a Certified Database	1-2
Database Requirements for RCU	1-2
Preparing for Schema Creation	1-2
About System Load and Product Load	1-3
Granting Permissions to Users for Querying System Load Objects	1-4
About Custom Prefixes	1-4
About the Service Table Schema	1-5
Planning Your Schema Creation	1-5
Organizing Schemas on a Single Database for a Single Domain	1-6
Organizing Schemas on Multiple Databases for a Single Domain	1-6
Organizing Schemas on a Single Database for Multiple Domains	1-7
Organizing Schemas on Multiple Databases for Multiple Domains	1-8
Integrating Components Using Declarative XML	1-8
Prerequisites for Schema Creation on an Autonomous Transaction Processing Database	1-9
Settings to connect to an Autonomous Transaction Processing Database	1-9
Settings to connect to an Autonomous Transaction Processing Database for Oracle Internet Directory	1-10
Applying Patches on Oracle Home	1-11
Using RCU with Java Access Bridge (Windows Only)	1-11
Install Java Access Bridge	1-11
Configure RCU to Use Java Access Bridge	1-12

2 Obtaining and Running Repository Creation Utility

Obtaining RCU	2-1
Starting RCU	2-2
Creating Schemas	2-3
Creating Schemas as a User with Full SYS or SYSDBA Privileges	2-3
Creating Schemas for Oracle Access Manager and Oracle Internet Directory As a User with Full SYS or SYSDBA Privileges	2-5
Verifying Schema Version Numbers	2-7
Creating Schemas as a User With Limited Database Privileges	2-8
Creating Schemas for Oracle Access Manager as a User with Limited Database Privileges	2-11
Creating Schemas for WebLogic Server on an ATP-S Database	2-15
Creating Schemas as a User with Full Database Privileges	2-16
Creating Schemas as a User With Limited Database Privileges	2-16
Verifying Schema Version Numbers	2-17
Dropping Schemas	2-18
About Dropping Shared Tablespaces	2-18
Dropping Schemas and Deleting Datafiles (Windows Only)	2-19

3 Running Repository Creation Utility from the Command Line

Command-Line Syntax and Parameters	3-2
RCU Modes Available from the Command Line	3-2
RCU Operations Available from the Command Line	3-3
RCU Command Line Parameters	3-3
Using the -silent Command	3-8
Using the -validate Parameter to Verify Prerequisites	3-10
Using a Wallet to Store Passwords	3-11
Using the -interactive Command	3-12
Using Response Files	3-13
About Response Files	3-13
Creating a RCU Response File from the Graphical Interface	3-14
Creating a RCU Response File from the Command Line	3-14
Performing RCU Operations by Using a Response File	3-15
Creating a Repository from the Command Line	3-15
Generating a System Load Script From the Command Line	3-16
Loading Data Into the Repository From the Command Line	3-17
Dropping a Repository from the Command Line	3-17
Generating a List of Components in an Oracle Home from the Command Line	3-18
Generating a List of Schemas in a Database from the Command Line	3-18
RCU Environment Variables	3-19

A Repository Creation Utility Screens

Welcome	A-2
Create Repository	A-2
Create Repository	A-2
Drop Repository	A-3
Database Connection Details	A-3
Connection Credentials for Oracle Databases and Oracle Databases with Edition-Based Redefinition	A-4
Connection Credentials for an Autonomous Transaction Processing Database	A-6
Select Components (for Create Operation)	A-8
Select Components (for Drop Operation)	A-9
Schema Passwords	A-9
Custom Variables	A-10
Map Tablespaces	A-10
Default Tablespace Mappings	A-11
Changing Default and Temporary Tablespaces	A-12
Viewing and Changing Additional Tablespaces	A-12
Managing Tablespaces and Datafiles	A-12
Adding, Modifying, and Removing Tablespaces	A-13
Adding, Modifying, and Removing Datafiles	A-13
Encrypting Tablespaces	A-14
Summary (for Create Operation)	A-15
Summary (for Drop Operation)	A-16
Completion Summary (for Create Operation)	A-17
Completion Summary (for Drop Operation)	A-18

B About Repository Creation Utility Schemas, IDs, and Tablespaces

Repository Creation Utility Schemas, IDs, and Tablespaces	B-1
---	-----

C Extending Repository Creation Utility to Configure Custom Application Repositories

RCU Integration Options	C-1
RCU JDBC Engine Compliant SQL*Plus Scripts	C-1
Pure JDBC Scripts	C-2
SQL*Plus Scripts	C-2
External Processes	C-3
Java Code Using JavaAction	C-3
RCU Configuration Files	C-4
XML DTDs Defined by RCU	C-4
Component Descriptor Configuration File	C-5

Repository Configuration File	C-6
Primary List of Supported Components	C-7
Storage Attributes Configuration File	C-8
Component Repository Configuration File	C-10
Soft-Prerequisite Support	C-16
Default Tablespaces Configuration File	C-17
RCU Script Writing Guidelines	C-17
Guidelines for RCU JDBC Engine Compliant SQL*Plus Scripts	C-18
Guidelines for Pure JDBC Scripts	C-18
Guidelines for SQL*Plus Scripts	C-19
Guidelines for SQL Server-Based Scripts	C-19

D Troubleshooting Repository Creation Utility

General Troubleshooting Tips	D-1
RCU Log Files	D-2
SOAINFRA Schema Creation Fails on a Hardened Database	D-2
Troubleshooting Tips for Schema Creation on an Autonomous Transaction Processing Database	D-2
Known Limitation for Oracle WebCenter Sites ATP-S Migration	D-3
Need More Help?	D-4

Preface

The *Creating Schemas with the Repository Creation Utility* book contains overview information and usage instructions for Oracle Repository Creation Utility (RCU).

- [Intended Audience](#)
- [Documentation Accessibility](#)
- [Diversity and Inclusion](#)
- [Related Documents](#)
- [Conventions](#)

Intended Audience

This guide is intended for users who are installing Oracle Fusion Middleware products and are comfortable running some system administration operations, such as creating users and groups, adding users to groups, and installing operating system patches on the computer where Oracle Fusion Middleware products will be installed. Users on UNIX systems need `root` access to run some scripts.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Diversity and Inclusion

Oracle is fully committed to diversity and inclusion. Oracle respects and values having a diverse workforce that increases thought leadership and innovation. As part of our initiative to build a more inclusive culture that positively impacts our employees, customers, and partners, we are working to remove insensitive terms from our products and documentation. We are also mindful of the necessity to maintain compatibility with our customers' existing technologies and the need to ensure continuity of service as Oracle's offerings and industry standards evolve. Because of these technical constraints, our effort to remove insensitive terms is ongoing and will take time and external cooperation.

Related Documents

For additional information, see the following resources:

- Preparing for an Oracle Fusion Middleware Installation in *Planning an Installation of Oracle Fusion Middleware*

This document contains important information about planning and preparing for Oracle Fusion Middleware product installations.

- Installing the Infrastructure Software in *Installing and Configuring the Oracle Fusion Middleware Infrastructure*

The Repository Creation Utility is included with the Oracle Fusion Middleware Infrastructure distribution.

Conventions

The following text conventions are used in this document:

Convention	Meaning
Boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>Italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
Monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

1

About the Repository Creation Utility

Many of the Oracle Fusion Middleware components require the existence of schemas in a database before configuration. These schemas are created and loaded in your database by using the Repository Creation Utility (RCU).

The following topics introduce you to the concepts and features that you should be familiar with before you use RCU:

- [Verifying RCU System and Database Requirements](#)
Use the certification and system requirements documents to find important information about supported platforms for RCU, certified databases, and database configuration information.
- [Preparing for Schema Creation](#)
Before you create your schemas, ensure that you understand the concepts regarding schema creation and organization.
- [Prerequisites for Schema Creation on an Autonomous Transaction Processing Database](#)
Before you create schemas on an Autonomous Transaction Processing database (both Autonomous Transaction Processing - Dedicated and Autonomous Transaction Processing-Shared), you must modify the wallet settings and set the environment variables, and apply patches on `ORACLE_HOME`.
- [Using RCU with Java Access Bridge \(Windows Only\)](#)
Java Access Bridge enables assistive technologies, such as JAWS screen reader, to read Java applications that run on the Windows platform.

Verifying RCU System and Database Requirements

Use the certification and system requirements documents to find important information about supported platforms for RCU, certified databases, and database configuration information.

Read this information carefully before you obtain and run RCU.

- [RCU Supported Platforms](#)
Use the system requirements document to review the supported platforms on which you can run RCU.
- [Finding a Certified Database](#)
If you do not have a database where you can install schemas, you must install and configure a certified database.
- [Database Requirements for RCU](#)
Ensure to review the general and component-specific database requirements that must be met before you run RCU.

RCU Supported Platforms

Use the system requirements document to review the supported platforms on which you can run RCU.

To know the platforms on which you can run RCU, see *Oracle Fusion Middleware System Requirements and Specifications* document.

Finding a Certified Database

If you do not have a database where you can install schemas, you must install and configure a certified database.

For a list of certified databases that can be used with RCU, see *System Requirements and Supported Platforms for Oracle Fusion Middleware* certification document for your release, located on the *Oracle Fusion Middleware Supported System Configurations* page.

Database Requirements for RCU

Ensure to review the general and component-specific database requirements that must be met before you run RCU.

Not all schemas are supported on all databases. So, before you begin using RCU, see the *System Requirements and Supported Platforms for Oracle Fusion Middleware* document in Oracle Fusion Middleware Supported System Configurations page. In the certification information, you can see that MySQL database is supported for Oracle Data Integrator and Oracle GoldenGate Studio Fusion Middleware components only.

Make sure you have read the information in this section carefully so that you configure a certified database that supports the schemas that you need for your Fusion Middleware components.

Preparing for Schema Creation

Before you create your schemas, ensure that you understand the concepts regarding schema creation and organization.

- [About System Load and Product Load](#)
Schema creation in RCU is performed in multiple phases; each phase requires a different level of access to your database.
- [Granting Permissions to Users for Querying System Load Objects](#)
If you want to give a user with limited privileges the ability to query the system load objects, you must grant the user certain permissions before they can query the system load.
- [About Custom Prefixes](#)
Use custom prefixes to organize and group schemas in your database.
- [About the Service Table Schema](#)
The Service Table schema is a special schema that is automatically created once per prefix. The service table stores basic schema configuration information (for example, schema prefixes and passwords) that can then be accessed and used by other Oracle Fusion Middleware components during domain creation.
- [Planning Your Schema Creation](#)
Before you run RCU, make sure that you understand how schemas can be grouped together and distributed depending on your specific environment.
- [Integrating Components Using Declarative XML](#)
RCU provides extensibility with XML DTDs. Using these DTDs, component owners can integrate their components and prerequisites with RCU by providing a configuration file that adheres to the provided DTD.

About System Load and Product Load

Schema creation in RCU is performed in multiple phases; each phase requires a different level of access to your database.

- System Load Phase

During the system load phase, RCU creates the necessary tablespaces and schemas. If it is not already present, RCU also creates the `schema_version_registry`. One entry for each component is created in `schema_version_registry`, and the entry will have the appropriate access and status set to **LOADED** in the `schema_version_registry` table.

User with SYS or SYSDBA privileges must perform these actions; authentication credentials must be provided on the [Database Connection Details](#) screen when running RCU.

If you do not have the necessary privileges, you can select the **Prepare Scripts for System Load** on the [Create Repository](#) screen. This option generates a SQL script that contains the same SQL statements and blocks that would have been called if RCU were to execute the actions for the selected components. After the script is generated, a user with the necessary SYS or SYSDBA privileges can execute the script to complete the system load phase.

After the system load phase is complete, any user with the privileges described in [Granting Permissions to Users for Querying System Load Objects](#) can then run RCU again to complete the schema creation by performing the product load phase.

 **Note:**

If you need to generate the script for system load, you can only create schemas on Oracle and Oracle EBR databases; the system load script is not supported on any other database.

If you are performing the system load with full SYS or SYSDBA privileges, then you can create the schemas on any certified database.

- Product Load Phase

During the product load phase, RCU creates procedures, functions, tables, indexes, and other objects within schemas and runs any action that does not require DBA access. Any non-DBA user or the REGISTRYOWNER user can be used for this step.

Before performing the product load phase, the user must be granted the following:

```
grant REGISTRYACCESS to user;  
grant STBROLE to user;
```

After the product load phase is complete, status is changed to **VALID**, if there is no post-product load for that component.

- Optional Post-Product Load Phase

This step is only needed for components that generate the `script_postDataLoad.sql` script that requires DBA privileges during the system load phase. After the product load phase is complete, someone with SYS or SYSDBA privileges should execute the `script_postDataLoad.sql` script.

This step is required for the following components:

- Audit Services (IAU)
- Oracle Enterprise Scheduler (ESS)

 **Note:**

The Repository Creation Utility fails to load schemas for SOAINFRA when you run schemas on an Oracle hardened database. See [SOAINFRA Schema Creation Fails on a Hardened Database](#).

Granting Permissions to Users for Querying System Load Objects

If you want to give a user with limited privileges the ability to query the system load objects, you must grant the user certain permissions before they can query the system load.

 **Note:**

This user will be used for connecting to the system for queries, but the generated scripts from the system load phase must be run by someone with DBA privileges.

```
grant select_catalog_role to user;  
grant select any dictionary to user;  
grant create session to user;  
grant select on schema_version_registry to user;
```

 **Note:**

You may encounter a *Table or view does not exist* error message when you execute the last command; this can be ignored.

After you perform the system load, grant the following permission to the same user in order for them to perform data load:

```
grant REGISTRYACCESS to user;  
grant STBROLE to user;
```

About Custom Prefixes

Use custom prefixes to organize and group schemas in your database.

The prefix is prepended to and separated from the schema name with an underscore (`_`) character, as shown below:

prefix_schemaname

Prefixes:

- Can only contain alpha-numeric characters; no spaces or other special characters.

- Must begin with a letter.
- Must not be longer than 12 characters.

 **Note:**

The total length of the prefixed schema name (your custom prefix plus the component schema name) must not be longer than 30 characters.

The default prefix used by RCU is `DEV`; if `DEV` has already been used, then RCU defaults to `DEV1`, then `DEV2`, and so on. Prefixes are used to create and organize logical groups of schemas. For example, you may want to create a test version of the Metadata Services (schema name `MDS`) called `TEST_MDS`; then, when you are ready for your production version, you can create a second version of the schema called `PROD_MDS`. Both `TEST_MDS` and `PROD_MDS` may reside on the same or separate databases.

You are only allowed to use a prefix once per schema within a single database. For example, if you have a version of the Metadata Services schema called `DEV_MDS`, then you cannot use the `DEV` prefix again to create another version of the Metadata Services schema (for example, `DEV_MDS2`).

If you want to create another version of the schema using the same prefix, you must first drop the existing schema and then create the schema again.

The mapping between the prefixes and schemas is maintained in `schema_version_registry`.

About the Service Table Schema

The Service Table schema is a special schema that is automatically created once per prefix. The service table stores basic schema configuration information (for example, schema prefixes and passwords) that can then be accessed and used by other Oracle Fusion Middleware components during domain creation.

For example, the Configuration Wizard has screens which you can configure to use the data that is stored in the service table when RCU was run. After you provide the service table schema credentials, the data from the service table is used to populate the fields on the screen, thus saving you the need to manually populate that data yourself.

Once created, service tables are used to wire Oracle Fusion Middleware components together. For more information about wiring various components together, see *Wiring Components to Work Together* in *Administering Oracle Fusion Middleware*.

Planning Your Schema Creation

Before you run RCU, make sure that you understand how schemas can be grouped together and distributed depending on your specific environment.

For more information, the following examples are provided:

- [Organizing Schemas on a Single Database for a Single Domain](#)
This example shows a set of schemas in a single database being used by a single WebLogic domain.
- [Organizing Schemas on Multiple Databases for a Single Domain](#)
This example shows a single set of schemas that are distributed on multiple databases being used by a single WebLogic domain.


- [Organizing Schemas on a Single Database for Multiple Domains](#)
This example shows how schemas on a single database should be grouped for multiple domains.
- [Organizing Schemas on Multiple Databases for Multiple Domains](#)
This example shows how to organize schemas on multiple databases for use with multiple WebLogic domains.

Organizing Schemas on a Single Database for a Single Domain

This example shows a set of schemas in a single database being used by a single WebLogic domain.

This is the simple scenario in which all schemas using the `DEV` prefix are grouped together and used by a single WebLogic domain.


Figure 1-1 Schemas on a Single Database for a Single Domain



Organizing Schemas on Multiple Databases for a Single Domain

This example shows a single set of schemas that are distributed on multiple databases being used by a single WebLogic domain.

Figure 1-2 Schemas on Multiple Databases for a Single Domain




You can use the same schema prefix (in this case, `DEV`) can be used to group these related schemas together, even across multiple databases.

Organizing Schemas on a Single Database for Multiple Domains

This example shows how schemas on a single database should be grouped for multiple domains.

Figure 1-3 Schemas on a Single Database for Multiple Domains




In this example, the prefixes are grouped together by using DEV1 for one set of schemas (used by WebLogic Domain 1), and DEV2 for the second set (used by WebLogic Domain 2).

It is not possible to share a single set of schemas across multiple domains; each domain must have its own set of schemas.

Organizing Schemas on Multiple Databases for Multiple Domains

This example shows how to organize schemas on multiple databases for use with multiple WebLogic domains.

Figure 1-4 Schemas on Multiple Databases for Multiple Domains



In this scenario, it is possible to have separate domains on the same host that use schemas with the same name and prefix (DEV), since the schemas are located on different databases.

Integrating Components Using Declarative XML

RCU provides extensibility with XML DTDs. Using these DTDs, component owners can integrate their components and prerequisites with RCU by providing a configuration file that adheres to the provided DTD.

For more information about integrating various components, see [Extending Repository Creation Utility to Configure Custom Application Repositories](#).

Prerequisites for Schema Creation on an Autonomous Transaction Processing Database

Before you create schemas on an Autonomous Transaction Processing database (both Autonomous Transaction Processing - Dedicated and Autonomous Transaction Processing-Shared), you must modify the wallet settings and set the environment variables, and apply patches on `ORACLE_HOME`.

- [Settings to connect to an Autonomous Transaction Processing Database](#)
To connect to an Autonomous Transaction Processing database (both Autonomous Transaction Processing - Dedicated and Autonomous Transaction Processing-Shared), modify the wallet settings and set the environment variables as described in this section.
- [Applying Patches on Oracle Home](#)
You must apply the required patches on the existing `ORACLE_HOME`, before creating schemas using the Repository Creation Utility screens.

Settings to connect to an Autonomous Transaction Processing Database

To connect to an Autonomous Transaction Processing database (both Autonomous Transaction Processing - Dedicated and Autonomous Transaction Processing-Shared), modify the wallet settings and set the environment variables as described in this section.

 **Note:**

For Oracle Internet Directory, to connect to an Autonomous database, see [Settings to connect to an Autonomous Transaction Processing Database for Oracle Internet Directory](#).

To modify the wallet settings:

1. Download the wallet for the Autonomous Transaction Processing database, and unzip the wallet to the `/users/test/wallet_dbname/` directory.

 **Note:**

`/users/test/wallet_dbname/` directory is an example of wallet location. You can download the wallet to the desired location.

You must ensure that the wallet contains keystore for JDBC connection.

2. In the wallet, modify the wallet location in the `sqlnet.ora` file as follows:

```
WALLET_LOCATION = (SOURCE=(METHOD=FILE) (METHOD_DATA=(DIRECTORY="/users/test/wallet_dbname/")))
```

 **Note:**

If you downloaded the wallet to a different location, change the directory location to your wallet location.

3. In the wallet, add the following command at the end of the `ojdbc.properties` file:

```
SSL_SERVER_DN_MATCH=yes
```

To set the environment variables:

1. Before starting RCU, run the following commands:

```
export RCU_SSL_MODE=true
```

```
export TNS_ADMIN=/users/test/wallet_dbname/
```

 **Note:**

In the command to export `TNS_ADMIN`, change `/users/test/wallet_dbname/` directory to your wallet location.

- [Settings to connect to an Autonomous Transaction Processing Database for Oracle Internet Directory](#)

To connect to Autonomous Transaction Processing database (both Autonomous Transaction Processing - Dedicated and Autonomous Transaction Processing-Shared), for Oracle Internet Directory, modify the wallet settings and set the environment variables as described in this section.

Settings to connect to an Autonomous Transaction Processing Database for Oracle Internet Directory

To connect to Autonomous Transaction Processing database (both Autonomous Transaction Processing - Dedicated and Autonomous Transaction Processing-Shared), for Oracle Internet Directory, modify the wallet settings and set the environment variables as described in this section.

To modify the wallet settings:

1. Download the wallet for the Autonomous Transaction Processing database to the `<${ORACLE_HOME}/network/admin` directory.

You must change `${ORACLE_HOME}` to your Oracle Home location. For example, `/users/test/network/admin`.

You must ensure that the wallet contains keystore for JDBC connection.

2. In the wallet, modify the wallet location in the `sqlnet.ora` file as follows:

```
WALLET_LOCATION = (SOURCE=(METHOD=FILE)  
(METHOD_DATA=(DIRECTORY="<${ORACLE_HOME}/network/admin")))
```

You must change `${ORACLE_HOME}` to your Oracle Home location. For example, `/users/test/network/admin`.

3. In the wallet, add the following command at the end of the `ojdbc.properties` file:

```
SSL_SERVER_DN_MATCH=yes
```

To set the environment variables:

1. Before starting RCU, run the following commands:

```
export RCU_SSL_MODE=true
```

```
export TNS_ADMIN=<$ORACLE_HOME>/network/admin
```

You must change `$ORACLE_HOME` to your Oracle Home location. For example, `/users/test/network/admin`.

Applying Patches on Oracle Home

You must apply the required patches on the existing `ORACLE_HOME`, before creating schemas using the Repository Creation Utility screens.

Be sure to check My Oracle Support for the latest patches, if any, for your product. You can search for patches by patch ID or number, or by product or family.

1. Sign in to My Oracle Support at: <https://support.oracle.com>.
2. Click the **Patches and Updates** tab. The Patches and Updates page opens and displays the Patch Search region. You have the following options:
 - In the Patch ID or Number is field, enter the number of the patch you want. (This number is the same as the primary bug number fixed by the patch.) This option is useful if you already know the patch number.
 - To find a patch by product name, release, and platform, click the Product or Family link to enter one or more search criteria.
3. Click **Search** to execute your query. The Patch Search Results page opens.
4. Click the patch ID number. The system displays details about the patch. In addition, you can view the Read Me file before downloading the patch.
5. Click **Download**. Follow the instructions in the patch Read Me to install the patch.

Using RCU with Java Access Bridge (Windows Only)

Java Access Bridge enables assistive technologies, such as JAWS screen reader, to read Java applications that run on the Windows platform.

Assistive technologies can read Java-based interfaces, such as Oracle Universal Installer and Oracle Enterprise Manager.

For more information, see the following topics:

- [Install Java Access Bridge](#)
Follow these steps to download and install Java Access Bridge.
- [Configure RCU to Use Java Access Bridge](#)
To configure RCU to use Java Access Bridge after you complete the installation, set the system variable `ORACLE_OEM_CLASSPATH` to point to the installed Java Access Bridge files.

Install Java Access Bridge

Follow these steps to download and install Java Access Bridge.

1. Download Java Access Bridge from the following URL:

<http://www.oracle.com/technetwork/java/javase/tech/index-jsp-136191.html>

2. For complete information and procedure about Java Access Bridge installation, see [Java Access Bridge Installation procedure](#).

Configure RCU to Use Java Access Bridge

To configure RCU to use Java Access Bridge after you complete the installation, set the system variable `ORACLE_OEM_CLASSPATH` to point to the installed Java Access Bridge files.

1. Display **System** in the Control Panel.
2. Select the **Advanced** tab.
3. Click **New** button in the System Variable list. The New System Variable dialog appears.
4. In the Variable Name field, enter `ORACLE_OEM_CLASSPATH`.
5. In the Variable Value field, enter the full path for the `access-bridge.jar` and `jaccess-1_4.jar`.

Use a semicolon to separate the two paths. Do not use quotes or character spaces.

6. Click **OK**.

2

Obtaining and Running Repository Creation Utility

Use these instructions to obtain and run the Repository Creation Utility (RCU) to create and drop schemas.

- [Obtaining RCU](#)
The Repository Creation Utility is available with the Oracle Fusion Middleware Infrastructure distribution.
- [Starting RCU](#)
After you install Oracle Fusion Middleware Infrastructure and create your Oracle home, you can start RCU from the `ORACLE_HOME/oracle_common/bin` directory.
- [Creating Schemas](#)
Follow these instructions to create schemas in the database and verify that they are installed properly.
- [Creating Schemas for WebLogic Server on an ATP-S Database](#)
Follow these instructions to create schemas for WebLogic Server on an Autonomous Transaction Processing-Shared database, and verify that they are installed properly.
- [Dropping Schemas](#)
Follow these instructions to drop schemas from the database.

Obtaining RCU

The Repository Creation Utility is available with the Oracle Fusion Middleware Infrastructure distribution.

For information about how to install and obtain RCU, see Installing the Infrastructure Software in *Installing and Configuring the Oracle Fusion Middleware Infrastructure*.

Starting RCU

After you install Oracle Fusion Middleware Infrastructure and create your Oracle home, you can start RCU from the `ORACLE_HOME/oracle_common/bin` directory.

Note:

- If you run the RCU by using a non-English database, you will need to set the following language environment variables: `LANG`, `LC_ALL`, and `NLS_LANG`. Use the environment commands that are appropriate for your environment.

For example, for UNIX operating systems running `csh` run the following:

```
setenv LANG en_US.UTF8
setenv LC_ALL $LANG
setenv NLS_LANG american_america
```

- To start RCU, you do not need to set the `JAVA_HOME` environment variable. But, in case you want to use a specific JDK, ensure that the `JAVA_HOME` environment variable is set to the location of a certified JDK on your system.

For example, on UNIX operating systems, if your JDK is located in `/home/Oracle/Java/`:

```
setenv JAVA_HOME /home/Oracle/Java/jdk17.0.12
```

Be sure to replace the JDK location in this example with the actual JDK location on your system.

On Linux operating systems:

```
cd ORACLE_HOME/oracle_common/bin
./rcu
```

On Windows operating systems:

```
cd ORACLE_HOME\oracle_common\bin
rcu.bat
```

Note:

For Autonomous Transaction Processing-Shared database, Oracle Data Integrator supports only RCU silent mode for schema loading. For more information, see [Starting the Repository Creation Utility \(RCU\)](#).

RCU provides a command-line interface in situations where Xserver is not available or you have access to telnet terminals without display capabilities. The command-line interface also allows you to embed RCU from command-line scripts or with some Oracle Fusion Middleware components (for example, Enterprise Manager).

For more information about using the Command Line Interface (CLI), see [Running Repository Creation Utility from the Command Line](#).

Creating Schemas

Follow these instructions to create schemas in the database and verify that they are installed properly.

 **Note:**

The following sections are not applicable when you create schemas for Oracle GoldenGate products on Autonomous Transaction Processing database (both Autonomous Transaction Processing - Dedicated and Autonomous Transaction Processing-Shared) as you need to run RCU in silent mode for Oracle GoldenGate. See [Run RCU for Oracle GoldenGate on ATP databases in silent mode](#).

To create schemas for WebLogic Server on an Autonomous Transaction Processing-Shared, see [Creating Schemas for WebLogic Server on an ATP-S Database](#) and [Run RCU for Oracle WebLogic Server on ATP-S database in silent mode](#).

- [Creating Schemas as a User with Full SYS or SYSDBA Privileges](#)
If you are a user with full SYS or SYSDBA privileges and are able to provide valid authentication credentials for database access, follow these instructions to create schemas.
- [Verifying Schema Version Numbers](#)
When the schemas are created in your database, RCU creates and maintains a table called `schema_version_registry`. This table contains schema information such as version number, component name and ID, date of creation and modification, and custom prefix.
- [Creating Schemas as a User With Limited Database Privileges](#)
If you are a user without SYS or SYSDBA privileges, follow these instructions to create schemas.

Creating Schemas as a User with Full SYS or SYSDBA Privileges

If you are a user with full SYS or SYSDBA privileges and are able to provide valid authentication credentials for database access, follow these instructions to create schemas.

 **Note:**

The following schema creation steps are applicable for all components except Oracle Access Manager (OAM) and Oracle Internet Directory (OID). For OAM and OID, see [Creating Schemas for Oracle Access Manager and Oracle Internet Directory As a User with Full SYS or SYSDBA Privileges](#).

Click the screen name to see detailed information for that screen. Unless otherwise noted, click **Next** to continue to the next screen.

Table 2-1 Schema Creation Steps for Full-Privilege Users

Screen	Description
Welcome	This screen introduces you to RCU.
Create Repository	<p>Select Create Repository, then select System Load and Product Load.</p> <p>If you do not have full SYS or SYSDBA privileges on the database, select Prepare Scripts for System Load and follow the schema creation instructions in Creating Schemas as a User With Limited Database Privileges.</p> <p>For an Autonomous Transaction Processing database (both Autonomous Transaction Processing - Dedicated and Autonomous Transaction Processing-Shared), you must create schemas as a Normal user, and though, you do not have full SYS or SYSDBA privileges on the database, you must select System Load and Product Load.</p>
Database Connection Details	<p>Specify your database connection credentials.</p> <p>Remember that if you are creating schemas on an IBM DB2 database, you must have already created one operating system user for each schema that you want to create.</p> <p>Click Next when you have specified your credentials. A separate dialog window appears while RCU checks connectivity and the database prerequisites. When the database checking has passed without errors, click OK to dismiss the dialog window and go to the next screen.</p> <p>If you are creating schemas on an Autonomous Transaction Processing database (both Autonomous Transaction Processing - Dedicated and Autonomous Transaction Processing-Shared), you receive a warning message on selecting the database user role as <code>Normal</code>. You can ignore the warning and continue with the schema creation. For more information, see Troubleshooting Tips for Schema Creation on an Autonomous Transaction Processing Database.</p>
Select Components (for Create Operation)	<p>Select the components for which you want to create schemas, and specify a prefix to group them together.</p> <p>You must remember the prefix and schema names for the components you are installing; you need this information during the configuration phase of your product installation. Oracle recommends that you write down these values.</p>
Schema Passwords	<p>Specify the passwords for your schema owners.</p> <p>You must remember the passwords you enter on this screen; you need this information during the configuration phase of your product installation.</p>
Custom Variables	<p>Use the Custom Variables screen to specify additional product configuration information.</p> <p>The Custom Variables screen appears only if you selected one or more of the following components on the Select Components screen. You can select a component on the Select Components screen only if the Oracle home in which RCU was started contains that component.</p>
Map Tablespaces	<p>Use this screen to configure the desired tablespace mapping for the schemas that you want to create.</p> <p>When you click Next, a separate dialog window appears asking you to confirm that you want to create these tablespaces. Click OK to proceed and dismiss the dialog window.</p> <p>A second dialog window appears showing the progress of tablespace creation. After the tablespaces are created, click OK to dismiss this window and go to the next screen.</p>
Summary (for Create Operation)	Verify the information on this screen, then click Create to begin schema creation.
Completion Summary (for Create Operation)	Review the information on this screen to verify that the operation was completed successfully. Click Close to complete the schema creation and dismiss RCU.

- [Creating Schemas for Oracle Access Manager and Oracle Internet Directory As a User with Full SYS or SYSDBA Privileges](#)
If you are a user with full SYS or SYSDBA privileges and are able to provide valid authentication credentials for database access, follow these instructions to create schemas for Oracle Access Manager (OAM) and Oracle Internet Directory (OID).

Creating Schemas for Oracle Access Manager and Oracle Internet Directory As a User with Full SYS or SYSDBA Privileges

If you are a user with full SYS or SYSDBA privileges and are able to provide valid authentication credentials for database access, follow these instructions to create schemas for Oracle Access Manager (OAM) and Oracle Internet Directory (OID).



Note:

IDM schemas do not support EBR, so you must invoke RCU twice when creating schemas. When you invoke RCU the first time, select the Database type as **Oracle Database enabled for edition-based redefinition** and load the EBR-dependent components (STB, OPSS, IAU, IAU_Append, IAU_Viewer, and WLS). When you invoke RCU the second time, select Database type as **Oracle Database** and load IDM schemas

To create schemas for OAM and OID, perform the following steps:

1. Start RCU from the `ORACLE_HOME/oracle_common/bin` directory.
`./rcu`
2. Create schemas for Oracle Fusion Middleware components that support Edition-Based Redefinition (EBR) using **Oracle Database enabled for edition-based redefinition** database type. For schema creation steps, see [Table 2-2](#).
3. Start RCU from the `ORACLE_HOME/oracle_common/bin` directory.
`./rcu`
4. Create schemas for Oracle Fusion Middleware components, OAM and OID that do not support Edition-Based Redefinition (EBR) using **Oracle Database** database type. For schema creation steps, see [Table 2-3](#).

[Table 2-2](#) describes the screens and the steps to be performed to create schemas for Oracle Fusion Middleware components that support EBR, for a user with full SYS or SYSDBA privileges.

Click the screen name to see detailed information for that screen. Unless otherwise noted, click **Next** to continue to the next screen.

Table 2-2 Creating Schemas As a User with Full Privileges for Components That Support EBR

Screen	Description
Welcome	This screen introduces you to RCU.
Create Repository	Select Create Repository , then select System Load and Product Load .

Table 2-2 (Cont.) Creating Schemas As a User with Full Privileges for Components That Support EBR

Screen	Description
Database Connection Details	<p>Select Oracle Database enabled for edition-based redefinition and then specify the other database connection credentials.</p> <p>Click Next when you have specified your credentials. A separate dialog window appears while RCU checks connectivity and the database prerequisites. When the database checking has passed without errors, click OK to dismiss the dialog window and go to the next screen.</p>
Select Components (for Create Operation)	<p>To create schemas, select only the components that support EBR, and specify a prefix to group the selected schemas together.</p> <ul style="list-style-type: none"> • For Oracle Access Manager, select the following dependent components that support EBR: <ul style="list-style-type: none"> – Common Infrastructure Services – Oracle Platform Security Services – Audit Services – Audit Services Append – Audit Services Viewer – Metadata Services – WebLogic Services • For Oracle Internet Directory, select the following dependent components that support EBR: <ul style="list-style-type: none"> – Common Infrastructure Services – Oracle Platform Security Services – Audit Services – Audit Services Append – Audit Services Viewer – WebLogic Services <p>Note: The components, Oracle Access Manager (OAM) and Oracle Internet Directory (OID) do not support EBR. Hence, when you create schemas for OAM, do not select Oracle Access Manager, and when you create schemas for OID, do not select Oracle Internet Directory.</p> <p>You must remember the prefix and schema names for the components you are installing; you need this information during the configuration phase of your product installation. Oracle recommends that you write down these values.</p>
Schema Passwords	<p>Specify the passwords for your schema owners.</p> <p>You must remember the passwords you enter on this screen; you need this information during the configuration phase of your product installation.</p>
Map Tablespaces	<p>Use this screen to configure the desired tablespace mapping for the schemas that you want to create.</p> <p>When you click Next, a separate dialog window appears asking you to confirm that you want to create these tablespaces. Click OK to proceed and dismiss the dialog window.</p> <p>A second dialog window appears showing the progress of tablespace creation. After the tablespaces are created, click OK to dismiss this window and go to the next screen.</p>
Summary (for Create Operation)	<p>Verify the information on this screen, then click Create to begin schema creation.</p>
Completion Summary (for Create Operation)	<p>Review the information on this screen to verify that the operation was completed successfully. Click Close to complete the schema creation and dismiss RCU.</p>

Table 2-3 describes the screens and the steps to be performed to create schemas for OAM and OID Oracle Fusion Middleware components, for a user with full SYS or SYSDBA privileges.

Table 2-3 Creating Schemas As a User with Full Privileges for OAM and OID Components

Screen	Description
Welcome	This screen introduces you to RCU.
Create Repository	Select Create Repository , then select System Load and Product Load .
Database Connection Details	Select Oracle Database and then specify the other database connection credentials. Click Next when you have specified your credentials. A separate dialog window appears while RCU checks connectivity and the database prerequisites. When the database checking has passed without errors, click OK to dismiss the dialog window and go to the next screen.
Select Components (for Create Operation)	Select Select Existing prefix and use the existing schema prefix you specified when you created schemas for components that support EBR. See Table 2-2 . If you create schemas for OAM, select Oracle Access Manager , and if you create schemas for OID, select, Oracle Internet Directory . You must remember the prefix and schema names for the components you are installing; you need this information during the configuration phase of your product installation. Oracle recommends that you write down these values.
Schema Passwords	Specify the passwords for your schema owners. You must remember the passwords you enter on this screen; you need this information during the configuration phase of your product installation.
Map Tablespaces	Use this screen to configure the desired tablespace mapping for the OAM or OID schema that you want to create. When you click Next , a separate dialog window appears asking you to confirm that you want to create these tablespaces. Click OK to proceed and dismiss the dialog window. A second dialog window appears showing the progress of tablespace creation. After the tablespaces are created, click OK to dismiss this window and go to the next screen.
Summary (for Create Operation)	Verify the information on this screen, then click Create to begin schema creation.
Completion Summary (for Create Operation)	Review the information on this screen to verify that the operation was completed successfully. Click Close to complete the schema creation and dismiss RCU.

Verifying Schema Version Numbers

When the schemas are created in your database, RCU creates and maintains a table called `schema_version_registry`. This table contains schema information such as version number, component name and ID, date of creation and modification, and custom prefix.

To verify that the schemas are installed properly, run the following query after you sign in to SQL*Plus:

```
select comp_name, version from schema_version_registry;
```

The `comp_name` argument retrieves the name of the component, and `version` retrieves the version number. For example:

```
SQL> select comp_name, version from schema_version_registry;
```

```
COMP_NAME
-----
VERSION
-----
Audit Service
14.1.2.0.0
```

```
Audit Service Append
14.1.2.0.0
```

```
Audit Service Viewer
14.1.2.0.0
```

```
COMP_NAME
-----
```

```
VERSION
-----
```

```
Metadata Services
14.1.2.0.0
```

```
Oracle Platform Security Services
14.1.2.0.0
```

```
Service Table
14.1.2.0.0
```

```
COMP_NAME
-----
```

```
VERSION
-----
```

```
WebLogic Services
14.1.2.0.0
```

```
7 rows selected.
```

Creating Schemas as a User With Limited Database Privileges

If you are a user without SYS or SYSDBA privileges, follow these instructions to create schemas.

Note:

To create schemas in PDB using a user other than SYSDBA, RCU users need to create a common user and grant DBA to that common user, before running RCU. Local user with DBA privilege will not work correctly.

The following schema creation steps are applicable for all components except Oracle Access Manager (OAM). For OAM, see [Creating Schemas for Oracle Access Manager as a User with Limited Database Privileges](#).

Table 2-4 Schema Creation Steps for Limited-Privilege Users

Screen	Description
Welcome	This screen introduces you to RCU.
Create Repository	Select Create Repository , then select Prepare Scripts for System Load . See About System Load and Product Load for more information about these operations.

Table 2-4 (Cont.) Schema Creation Steps for Limited-Privilege Users


Screen	Description
Database Connection Details	<p>Specify your database connection credentials.</p> <p>Click Next when you have specified your credentials. A separate dialog window appears while RCU checks connectivity and the database prerequisites. When the database checking has passed without errors, click OK to dismiss the dialog window and go to the next screen.</p>
	<div style="border: 1px solid #0070C0; padding: 10px; background-color: #E6F2FF;"> <p> Note:</p> <p>Performing system load and product load separately is only supported on Oracle and Oracle EBR databases.</p> </div>
Select Components (for Create Operation)	<p>Select the components for which you want to create schemas, and specify a prefix to group them together.</p> <p>You must remember the prefix and schema names for the components you are installing; you need this information during the configuration phase of your product installation. Oracle recommends that you write down these values.</p>
Custom Variables	<p>Use the Custom Variables screen to specify additional product configuration information. The Custom Variables screen appears only if you selected one or more of the following components on the Select Components screen. You can select a component on the Select Components screen only if the Oracle home in which RCU was started contains that component.</p>
Map Tablespaces	<p>Use this screen to configure the desired tablespace mapping for the schemas that you want to create.</p>
Summary (for Create Operation)	<p>Verify the information on this screen, then click Generate to begin script generation. By default, the scripts are generated in the <code>RCUdate_timestamp_random_number/logs</code> directory inside the temporary directory on your system. For example, on UNIX operating systems, the scripts are generated in the <code>/tmp/RCUdate_timestamp_random_number/logs</code> directory, by default. If you want to specify a different location, click Browse and select a location on your system.</p> <p>The names of the scripts generated are <code>script_systemLoad.sql</code> and <code>script_postDataLoad.sql</code>.</p>
Completion Summary (for Create Operation)	<p>Review the information on this screen to verify that the operation was completed successfully. Click Close to complete the script generation and dismiss RCU.</p>
N/A	<p>After the scripts are created, user with SYS or SYSDBA privileges must execute the <code>script_systemLoad.sql</code> script:</p> <ol style="list-style-type: none"> 1. Sign in to SQL*Plus. 2. Enter the following command to execute the <code>script_systemLoad.sql</code> script (replace the path to the script if you chose to save it in a custom location): <pre>@/tmp/RCUdate_timestamp_random_number/logs/script_systemLoad.sql</pre> 3. While the script is running, the user is prompted to set the schema password for each schema being created. Specify the passwords as prompted. <p>You are returned to your system prompt when the script has been executed.</p>
N/A	<p>After the script is executed, start RCU again and perform the product load phase to complete schema creation.</p>
Welcome	<p>This screen introduces you to RCU.</p>

Table 2-4 (Cont.) Schema Creation Steps for Limited-Privilege Users

Screen	Description
Create Repository	Select Create Repository , then select Perform Product Load . See About System Load and Product Load for more information about these operations.
Database Connection Details	Specify your database connection credentials. Click Next when you have specified your credentials. A separate dialog window appears while RCU checks connectivity and the database prerequisites. When the database checking has passed without errors, click OK to dismiss the dialog window and go to the next screen.
Select Components (for Create Operation)	From the drop-down list, select the prefix you specified earlier in this procedure. Then, select the components for which you want to perform the product load.
Schema Passwords	Specify the passwords for your schema owners. Ensure to specify the same passwords that were entered while running the <code>script_systemLoad.sql</code> script through SQL*Plus. You must remember the passwords you enter on this screen; you need this information during the configuration phase of your product installation.
Custom Variables	Use the Custom Variables screen to specify additional product configuration information. The Custom Variables screen appears only if you selected one or more of the following components on the Select Components screen. You can select a component on the Select Components screen only if the Oracle home in which RCU was started contains that component.
Summary (for Create Operation)	Verify the information on this screen, then click Data Load to begin schema creation.
Completion Summary (for Create Operation)	Review the information on this screen to verify that the operation was completed successfully. Click Close to complete the schema creation and dismiss RCU.
N/A	This optional step is needed for components that generate and must execute product load scripts requiring DBA privileges. After the product load phase is complete, someone with SYS or SYSDBA privileges must execute the <code>script_postDataLoad.sql</code> script. This step is needed for the Audit Services (IAU) and Oracle Enterprise Scheduler (ESS) components. <ol style="list-style-type: none"> 1. Sign in to SQL*Plus. 2. Enter the following command to execute the <code>script_postDataLoad.sql</code> script (replace the path to the script if you chose to save it in a custom location): <pre>@/tmp/RCUdate_timestamp_random_number/logs/script_postDataLoad.sql</pre> You are returned to your system prompt when the script has been executed.

- [Creating Schemas for Oracle Access Manager as a User with Limited Database Privileges](#)
If you are a user without SYS or SYSDBA privileges, follow these instructions to create schemas for Oracle Access Manager (OAM).

Creating Schemas for Oracle Access Manager as a User with Limited Database Privileges

If you are a user without SYS or SYSDBA privileges, follow these instructions to create schemas for Oracle Access Manager (OAM).

 **Note:**

To create schemas in PDB using a user other than SYSDBA, RCU users need to create a common user without DBA privileges, before running RCU.

To create schemas for OAM, perform the following steps:

1. Grant the following permissions to the user before querying the system load objects:

```
grant select_catalog_role to user;
grant select any dictionary to user;
grant create session to user;
grant select on schema_version_registry to user;
```

 **Note:**

When you execute the last command, you may encounter the `Table or view does not exist` error message. You may ignore this message.

2. Start RCU from the `ORACLE_HOME/oracle_common/bin` directory.
`./rcu`
3. Using **Prepare Scripts for System Load**, create schemas for Oracle Fusion Middleware components that support Edition-Based Redefinition (EBR) using **Oracle Database enabled for edition-based redefinition** database type. For schema creation steps, see [Table 2-5](#).
4. Start RCU from the `ORACLE_HOME/oracle_common/bin` directory.
`./rcu`
5. Using **Prepare Scripts for System Load**, create schemas for OAM component that does not support Edition-Based Redefinition (EBR) using **Oracle Database** database type and with a schema prefix, which is different than the schema prefix you used for components that support Edition-Based Redefinition (EBR). For schema creation steps, see [Table 2-6](#).
6. After the scripts are created, a user with SYS or SYSDBA privileges must run the `script_systemLoad.sql` scripts generated from [step 3](#) and [step 5](#) as follows:
 - a. Sign in to SQL*Plus.
 - b. Enter the following command to run the `script_systemLoad.sql` script (replace the path to the script if you chose to save it in a custom location):

```
@/tmp/RCUdate_timestamp_random_number/logs/script_systemLoad.sql
```

- c. While the script is running, the user is prompted to set the schema password for each schema being created. Specify the passwords as prompted.

You are returned to your system prompt when the script execution is complete.

7. While running with SYS or SYSDBA privileges, grant the following permissions to the user before performing the product load:

```
grant REGISTRYACCESS to user;
grant STBROLE to user;
```

8. Start RCU from the `ORACLE_HOME/oracle_common/bin` directory.


```
./rcu
```
9. Using **Perform Product Load**, create schemas for Oracle Fusion Middleware components that support EBR using **Oracle Database enabled for edition-based redefinition** database type and with the same prefix you used when you created schemas for these Oracle Fusion Middleware components in [step 3](#). For schema creation steps, see [Table 2-7](#).
10. Start RCU from the `ORACLE_HOME/oracle_common/bin` directory.


```
./rcu
```
11. Using **Perform Product Load**, create schemas for OAM using **Oracle Database** database type and with the same schema prefix that you used when you created schemas for OAM in [step 5](#). For schema creation steps, see [Table 2-8](#).
12. After the product load phase is complete, user with SYS or SYSDBA privileges must run the `script_postDataLoad.sql` generated from [step 3](#) and [step 5](#) as follows:
 - a. Sign in to SQL*Plus.
 - b. Enter the following command to run the `script_postDataLoad.sql` script (replace the path to the script if you chose to save it in a custom location):

```
@/tmp/RCUdate_timestamp_random_number/logs/script_postDataLoad.sql
```

You are returned to your system prompt when the script execution is complete.

[Table 2-5](#) describes the screens and the steps to be performed to create schemas for Oracle Fusion Middleware components that support EBR, for a user with limited database privileges.

Table 2-5 Creating Schemas As a User with Limited-Privileges for Components That Support EBR

Screen	Description
Welcome	This screen introduces you to RCU.
Create Repository	Select Create Repository , then select Prepare Scripts for System Load . See About System Load and Product Load for more information about these operations.
Database Connection Details	Select Oracle Database enabled for edition-based redefinition and then specify the other database connection credentials. Click Next when you have specified your credentials. A separate dialog window appears while RCU checks connectivity and the database prerequisites. When the database checking has passed without errors, click OK to dismiss the dialog window and go to the next screen.

Table 2-5 (Cont.) Creating Schemas As a User with Limited-Privileges for Components That Support EBR

Screen	Description
Select Components (for Create Operation)	<p>To create schemas, select only the following components that support EBR: Common Infrastructure Services, Oracle Platform Security Services, Audit Services, Audit Services Append, Audit Services Viewer, Metadata Services, and WebLogic Services, and then specify a prefix to group the selected schemas together.</p> <p>Note:The Oracle Access Manager (OAM) component does not support EBR. Hence, when you create schemas for OAM, do not select Oracle Access Manager.</p> <p>You must remember the prefix and schema names for the components you are installing; you need this information during the configuration phase of your product installation. Oracle recommends that you write down these values.</p>
Map Tablespaces	Use this screen to configure the desired tablespace mapping for the schemas that you want to create.
Summary (for Create Operation)	<p>Verify the information on this screen, then click Generate to begin script generation.</p> <p>By default, the scripts are generated in the <code>RCUdate_timestamp_random_number/logs</code> directory inside the temporary directory on your system. For example, on UNIX operating systems, the scripts are generated in the <code>/tmp/RCUdate_timestamp_random_number/logs</code> directory, by default. If you want to specify a different location, click Browse and select a location on your system.</p> <p>The names of the scripts generated are <code>script_systemLoad.sql</code> and <code>script_postDataLoad.sql</code>.</p>
Completion Summary (for Create Operation)	Review the information on this screen to verify that the operation was completed successfully. Click Close to complete the script generation and dismiss RCU.

[Table 2-6](#) describes the screens and the steps to be performed to create schemas for OAM component, for a user with limited database privileges.

Table 2-6 Creating Schemas As a User with Limited-Privileges for OAM

Screen	Description
Welcome	This screen introduces you to RCU.
Create Repository	<p>Select Create Repository, then select Prepare Scripts for System Load.</p> <p>See About System Load and Product Load for more information about these operations.</p>
Database Connection Details	<p>Select Oracle Database and then specify the other database connection credentials.</p> <p>Click Next when you have specified your credentials. A separate dialog window appears while RCU checks connectivity and the database prerequisites. When the database checking has passed without errors, click OK to dismiss the dialog window and go to the next screen.</p>
Select Components (for Create Operation)	<p>Select Create new prefix and specify a prefix name different than the prefix name you specified when you created schemas for components that support EBR.</p> <p>To create schemas for OAM, select Oracle Access Manager, and the dependent mandatory components, Common Infrastructure Services and WebLogic Services.</p> <p>You must remember the prefix and schema names for the components you are installing; you need this information during the configuration phase of your product installation. Oracle recommends that you write down these values.</p>
Map Tablespaces	Use this screen to configure the desired tablespace mapping for the schemas that you want to create.

Table 2-6 (Cont.) Creating Schemas As a User with Limited-Privileges for OAM

Screen	Description
Summary (for Create Operation)	<p>Verify the information on this screen, then click Generate to begin script generation.</p> <p>By default, the scripts are generated in the <code>RCUdate_timestamp_random_number/logs</code> directory inside the temporary directory on your system. For example, on UNIX operating systems, the scripts are generated in the <code>/tmp/RCUdate_timestamp_random_number/logs</code> directory, by default. If you want to specify a different location, click Browse and select a location on your system.</p> <p>The names of the scripts generated are <code>script_systemLoad.sql</code> and <code>script_postDataLoad.sql</code>.</p>
Completion Summary (for Create Operation)	<p>Review the information on this screen to verify that the operation was completed successfully. Click Close to complete the script generation and dismiss RCU.</p>

[Table 2-7](#) describes the screens and the steps to be performed to create schemas for Oracle Fusion Middleware components that support EBR with the same schema prefix in [Table 2-5](#), for a user with limited database privileges.

Table 2-7 Creating Schemas As a User with Limited-Privileges for Components That Support EBR with the Same Schema Prefix Used for EBR-Compatible Components

Screen	Description
Welcome	This screen introduces you to RCU.
Create Repository	<p>Select Create Repository, then select Perform Product Load.</p> <p>See About System Load and Product Load for more information about these operations.</p>
Database Connection Details	<p>Select Oracle Database enabled for edition-based redefinition and then specify the other database connection credentials.</p> <p>Click Next when you have specified your credentials. A separate dialog window appears while RCU checks connectivity and the database prerequisites. When the database checking has passed without errors, click OK to dismiss the dialog window and go to the next screen.</p>
Select Components (for Create Operation)	<p>Select Select Existing prefix and use the existing schema prefix you specified when you created schemas for components that support EBR. See Table 2-5.</p> <p>To create schemas, select only the following components that support EBR: Common Infrastructure Services, Oracle Platform Security Services, Audit Services, Audit Services Append, Audit Services Viewer, Metadata Services, and WebLogic Services.</p> <p>Note:The Oracle Access Manager (OAM) component does not support EBR. Hence, when you create schemas for OAM, do not select Oracle Access Manager.</p> <p>You must remember the prefix and schema names for the components you are installing; you need this information during the configuration phase of your product installation. Oracle recommends that you write down these values.</p>
Schema Passwords	<p>Specify the passwords for your schema owners.</p> <p>Ensure to specify the same passwords that were entered while running the <code>script_systemLoad.sql</code> script through SQL*Plus.</p> <p>You must remember the passwords you enter on this screen; you need this information during the configuration phase of your product installation.</p>
Summary (for Create Operation)	<p>Verify the information on this screen, then click Data Load to begin schema creation.</p>
Completion Summary (for Create Operation)	<p>Review the information on this screen to verify that the operation was completed successfully. Click Close to complete the script generation and dismiss RCU.</p>

[Table 2-8](#) describes the screens and the steps to be performed to create schemas for OAM component with the same prefix in [Table 2-6](#), for a user with limited database privileges.

Table 2-8 Creating Schemas As a User with Limited-Privileges for OAM Component with the Same Schema Prefix Used for OAM

Screen	Description
Welcome	This screen introduces you to RCU.
Create Repository	Select Create Repository , then select Perform Product Load . See About System Load and Product Load for more information about these operations.
Database Connection Details	Select Oracle Database and then specify the other database connection credentials. Click Next when you have specified your credentials. A separate dialog window appears while RCU checks connectivity and the database prerequisites. When the database checking has passed without errors, click OK to dismiss the dialog window and go to the next screen.
Select Components (for Create Operation)	Select Select Existing prefix and use the existing schema prefix you specified when you created schemas for OAM component. See Table 2-6 . To create schemas for OAM, select Oracle Access Manager , and the dependent mandatory components, Common Infrastructure Services and WebLogic Services .
Schema Passwords	Specify the passwords for your schema owners. Ensure to specify the same passwords that were entered while running the <code>script_systemLoad.sql</code> script through SQL*Plus. You must remember the passwords you enter on this screen; you need this information during the configuration phase of your product installation.
Summary (for Create Operation)	Verify the information on this screen, then click Data Load to begin schema creation.
Completion Summary (for Create Operation)	Review the information on this screen to verify that the operation was completed successfully. Click Close to complete the script generation and dismiss RCU.

Creating Schemas for WebLogic Server on an ATP-S Database

Follow these instructions to create schemas for WebLogic Server on an Autonomous Transaction Processing-Shared database, and verify that they are installed properly.

Ensure that you have completed the prerequisites for schema creation. See [Settings to connect to an Autonomous Transaction Processing Database](#).

To create schemas for WebLogic server on an Autonomous Transaction Processing-Shared database in silent mode, see [Run RCU for Oracle WebLogic Server on ATP-S database in silent mode](#).

- [Creating Schemas as a User with Full Database Privileges](#)
If you are a user with full database privileges and are able to provide valid authentication credentials for database access, follow these instructions to create schemas.
- [Creating Schemas as a User With Limited Database Privileges](#)
If you are a user without full database privileges, follow these instructions to create schemas.
- [Verifying Schema Version Numbers](#)
When the schemas are created in your database, RCU creates and maintains a table called `schema_version_registry`. This table contains schema information such as version number, component name and ID, date of creation and modification, and custom prefix.

Creating Schemas as a User with Full Database Privileges

If you are a user with full database privileges and are able to provide valid authentication credentials for database access, follow these instructions to create schemas.

Click the screen name to see detailed information for that screen. Unless otherwise noted, click **Next** to continue to the next screen.

Table 2-9 Schema Creation Steps for Full-Privilege Users

Screen	Description
Welcome	This screen introduces you to RCU.
Create Repository	Select Create Repository , then select System Load and Product Load .
Database Connection Details	Specify your database connection credentials using the Connection String format only. See Settings to connect to an Autonomous Transaction Processing Database . After you have specified your credentials, click Next. The user privileges warning is displayed. You can ignore the warning and continue with the schema creation. For more information, see Troubleshooting Tips for Schema Creation on an Autonomous Transaction Processing Database .
Select Components (for Create Operation)	Select the components for which you want to create schemas, and specify a prefix to group them together. You must remember the prefix and schema names for the components you are installing; you need this information during the configuration phase of your product installation. Oracle recommends that you write down these values.
Schema Passwords	Specify the passwords for your schema owners. You must remember the passwords you enter on this screen; you need this information during the configuration phase of your product installation.
Map Tablespaces	Use this screen to configure the desired tablespace mapping for the schemas that you want to create. Note: If you created the schemas using an existing prefix, override the default and temporary tablespaces by selecting <i>DATA</i> from the drop-down list in the <i>Default Tablespace</i> column, and <i>TEMP</i> from the drop-down list in the <i>Temp Tablespace</i> column. In case of additional tablespaces, override the tablespace name by selecting <i>DATA</i> from the drop-down list in the <i>Tablespace Name</i> column. When you click Next , the user privileges warning is displayed. You can ignore the warning and continue with the schema creation. For more information, see Troubleshooting Tips for Schema Creation on an Autonomous Transaction Processing Database . On the confirmation window, click OK to confirm that you want to create these tablespaces. You can view progress of tablespace creation. After the tablespaces are created, click Next to go to the next screen.
Summary (for Create Operation)	Verify the information on this screen, then click Create to begin schema creation.
Completion Summary (for Create Operation)	Review the information on this screen to verify that the operation was completed successfully. Click Close to complete the schema creation and dismiss RCU.

Creating Schemas as a User With Limited Database Privileges

If you are a user without full database privileges, follow these instructions to create schemas.

To create schemas, a user with limited database privileges needs to follow the steps in Create Repository in [Creating Schemas as a User with Full Database Privileges](#)

 **Note:**

To create schemas in PDB using a user other than a user with full database privileges, Repository Creation Utility (RCU) users need to create a common user and grant DBA to that common user, before running RCU. Local user with DBA privilege will not work correctly.

Verifying Schema Version Numbers

When the schemas are created in your database, RCU creates and maintains a table called `schema_version_registry`. This table contains schema information such as version number, component name and ID, date of creation and modification, and custom prefix.

To verify that the schemas are installed properly, run the following query after you sign in to SQL*Plus:

```
select comp_name, version from schema_version_registry;
```

The `comp_name` argument retrieves the name of the component, and `version` retrieves the version number. For example:

```
SQL> select comp_name, version from schema_version_registry;
```

```
COMP_NAME
-----
VERSION
-----
```

```
Audit Service
14.1.2.0.0
```

```
Audit Service Append
14.1.2.0.0
```

```
Audit Service Viewer
14.1.2.0.0
```

```
COMP_NAME
-----
VERSION
-----
```

```
Metadata Services
14.1.2.0.0
```

```
Oracle Platform Security Services
14.1.2.0.0
```

```
Service Table
14.1.2.0.0
```

```
COMP_NAME
-----
VERSION
-----
```

```
WebLogic Services
14.1.2.0.0
```

7 rows selected.

Dropping Schemas

Follow these instructions to drop schemas from the database.

To see detailed information for a particular screen, click on the screen name. Unless otherwise noted, click **Next** to continue to the next screen.

Table 2-10 RCU Screens and Description for Dropping Schemas

Screen	Instructions and Action Required
Welcome	This screen introduces you to RCU.
Create Repository	Select Drop Repository .
Database Connection Details	Specify your database connection credentials. Click Next when you have specified your credentials. A separate dialog window appears while RCU checks connectivity and the database prerequisites. When the database checking has passed without errors, click OK to dismiss the dialog window and go to the next screen.
Select Components (for Drop Operation)	Select the prefix and the schemas that you want to drop, then click Next . A separate dialog window appears asking you to verify that you want to drop the selected schemas. Click OK to dismiss this window. A second dialog window appears while RCU checks the prerequisites for the schemas that you are dropping. After prerequisite checking is complete, click OK to dismiss this window and go to the next screen.
Custom Variables	The Custom Variables screen appears only if you selected one or more of the following components on the Select Components screen. You can select a component on the Select Components screen only if the Oracle home in which RCU was started contains that component.
Summary (for Drop Operation)	Review the information on this screen, then click Drop to drop the schemas.
Completion Summary (for Drop Operation)	Note the location of the log files, then click Close to dismiss the screen.

- [About Dropping Shared Tablespaces](#)
Tablespaces that are shared among multiple schemas are not dropped.
- [Dropping Schemas and Deleting Datafiles \(Windows Only\)](#)
If you used RCU to drop a schema from a Windows-based database, and you want to recreate the dropped schema, you will have to manually delete the datafiles that were not automatically removed when the schema was dropped.

About Dropping Shared Tablespaces

Tablespaces that are shared among multiple schemas are not dropped.

For example, if you created both the Audit Services (for example, `DEV_IAU`) and Metadata Services (for example, `DEV_MDS`) schemas, both schemas would use the temporary tablespace `DEV_IAS_TEMP` (see [Default Tablespace Mappings](#)).

If you then drop the `DEV_IAU` schema, the `DEV_IAS_TEMP` tablespace would not be dropped since it is also used by the `DEV_MDS` schema.

Dropping Schemas and Deleting Datafiles (Windows Only)

If you used RCU to drop a schema from a Windows-based database, and you want to recreate the dropped schema, you will have to manually delete the datafiles that were not automatically removed when the schema was dropped.

Change to the `DB_HOME\oradata` directory and manually delete any remaining datafiles before you recreate the schema.

Oracle recommends that you check this directory for any remaining datafiles before you attempt to recreate any dropped schema.

3

Running Repository Creation Utility from the Command Line

The command-line interface (CLI) is necessary for integration with both the Oracle Fusion Middleware installer and Enterprise Manager during application deployment. Additionally, you can use the CLI in cases where Xserver is not configured or if you are using a telnet terminal that does not have proper display capabilities.

For more information on how to run RCU from the command line, see the following topics:

- [Command-Line Syntax and Parameters](#)
To run RCU from the command line, you need to specify a mode, an operation, and any necessary parameters. Make sure that you understand the syntax and the various command-line parameters you can use for your operation.
- [Using the `-silent` Command](#)
Use the `-silent` command if you want to run RCU with minimal interaction once you have entered the command.
- [Using the `-interactive` Command](#)
Use the `-interactive` command to run the RCU graphical interface. This is the default value if neither `-silent` nor `-interactive` is specified.
- [Using Response Files](#)
Before you run RCU, you can provide information that is required to perform a specific operation in a response file. For example, you can provide your database connection details, a list of components to be added or dropped, and the schema prefix to RCU through a response file.
- [Creating a Repository from the Command Line](#)
If you are a user with full SYS or SYSDBA privileges, use the `-createRepository` operation to create a repository.
- [Generating a System Load Script From the Command Line](#)
If you are a user without SYS or SYSDBA privileges, use the `-generateScript` operation to generate a script. A user with DBA privileges can run the script later to complete the system load phase.
- [Loading Data Into the Repository From the Command Line](#)
After the system load scripts are run by a user with DBA privileges, any user can then use the `-dataLoad` operation to load data into a repository.
- [Dropping a Repository from the Command Line](#)
Use the `-dropRepository` operation to drop a repository.
- [Generating a List of Components in an Oracle Home from the Command Line](#)
Use the `-listComponents` command to generate a list of valid components that are available in a given Oracle home. This command displays the name, component ID, and the supported database types for each component that is available in the Oracle home in which RCU was started.
- [Generating a List of Schemas in a Database from the Command Line](#)
Use the `-listSchemas` command to generate a list of valid schemas in a given database.

- [RCU Environment Variables](#)
The RCU environment variables are the variables picked up by RCU from the environment. If an environment variable is not set, then RCU uses the default value.

Command-Line Syntax and Parameters

To run RCU from the command line, you need to specify a mode, an operation, and any necessary parameters. Make sure that you understand the syntax and the various command-line parameters you can use for your operation.

The syntax for the RCU command-line interface is:

```
rcu mode operation {parameters}
```

There are two modes (`-silent` and `-interactive`) and eight operations (`-generateResponseFile`, `-responseFile`, `-createRepository`, `-generateScript`, `-dataLoad`, `-dropRepository`, `-listComponents`, and `-listSchemas`). So, the command can be written out as follows:

```
rcu [-silent | -interactive] [-generateResponseFile | -responseFile | -createRepository  
| -generateScript | -dataLoad |  
-dropRepository | -listComponents | -listSchemas]  
{parameters}
```

The following topics describe each of the modes, operations, and parameters:

- [RCU Modes Available from the Command Line](#)
There are two RCU modes available from the command line, `-silent` mode and `-interactive` mode.
- [RCU Operations Available from the Command Line](#)
There are eight RCU operations that are available from the command-line.
- [RCU Command Line Parameters](#)
You can pass the RCU command-line parameters to RCU as input by directly entering the parameters on the command line or by using a response file.

RCU Modes Available from the Command Line

There are two RCU modes available from the command line, `-silent` mode and `-interactive` mode.

Table 3-1 RCU Modes Available from the Command Line

Command	Description
<code>-silent</code>	Run RCU with minimal or no interaction from the command line. For more information about silent mode, see Using the -silent Command .
<code>-interactive</code>	Run the RCU graphical interface. This is the default if neither <code>-silent</code> nor <code>-interactive</code> is specified. This command (whether specified or not) allows you to prepopulate certain screens with the information that is specified in the response file or from the command line. You can prepopulate the Create Repository and Database Connection Details screens. For more information about graphical mode, see Using the -interactive Command .

RCU Operations Available from the Command Line

There are eight RCU operations that are available from the command-line.

Table 3-2 RCU Operations Available from the Command Line

Command	Description
-generateResponseFile	Run RCU with <code>-silent</code> to generate a RCU response file that contains all valid RCU command line parameters. See Creating a RCU Response File from the Command Line
-responseFile	Run RCU with either <code>-silent</code> or <code>-interactive</code> to perform a RCU operation using a response file. See Performing RCU Operations by Using a Response File
-createRepository	Run RCU with either <code>-silent</code> or <code>-interactive</code> to create a repository. See Creating a Repository from the Command Line .
-generateScript	Run RCU with either <code>-silent</code> or <code>-interactive</code> to generate a script for system load. See Generating a System Load Script From the Command Line .
-dataLoad	Run RCU with either <code>-silent</code> or <code>-interactive</code> to load data into the repository. See Loading Data Into the Repository From the Command Line .
-dropRepository	Run RCU with either <code>-silent</code> or <code>-interactive</code> to drop a repository. See Dropping a Repository from the Command Line .
-listComponents	Run RCU with <code>-silent</code> to generate a list of components for a given Oracle home. See Generating a List of Components in an Oracle Home from the Command Line .
-listSchemas	Run RCU with <code>-silent</code> to list the schemas in a given database. See Generating a List of Schemas in a Database from the Command Line .

RCU Command Line Parameters

You can pass the RCU command-line parameters to RCU as input by directly entering the parameters on the command line or by using a response file.

Table 3-3 RCU Command Line Parameters and Descriptions

Parameter	Required?	Valid for Which Operation?	Description
-compInfoXMLLocation	No	-createRepository -generateScript -dataLoad -dropRepository	The full path to the location of the ComponentInfo.xml file. The default location is <code>ORACLE_HOME/oracle_common/rcu/config</code> (on UNIX operating systems) or <code>ORACLE_HOME\oracle_common\rcu\config</code> (on Windows operating systems).
-storageXMLLocation	No	-createRepository -generateScript -dataLoad -dropRepository	The full path to the location of the StorageInfo.xml file. The default location is <code>ORACLE_HOME/oracle_common/rcu/config</code> (on UNIX operating systems) or <code>ORACLE_HOME\oracle_common\rcu\config</code> (on Windows operating systems).

Table 3-3 (Cont.) RCU Command Line Parameters and Descriptions

Parameter	Required?	Valid for Which Operation?	Description
-databaseType	No	-createRepository -generateScript -dataLoad -dropRepository -listSchemas	<p>The type of database to which you are connecting.</p> <p>If you perform the system load and product load concurrently as a user with full DBA privileges, the valid options are ORACLE, SQLSERVER, IBMBD2, MYSQL, or EBR.</p> <p>MySQL database is supported for Oracle Data Integrator and Oracle GoldenGate Studio Fusion Middleware components only.</p> <p>If you do not have permissions to perform the system load and product load concurrently and need to generate a script, you can only use the ORACLE and EBR database types.</p> <p>For more information about system load and product load, see About System Load and Product Load.</p>
-connectString	Yes	-createRepository -generateScript -dataLoad -dropRepository -listSchemas	<p>The credentials to connect to your database.</p> <p>For Oracle or EBR-enabled databases, use the following format:</p> <p><i>host:port:sid</i></p> <p>OR:</p> <p><i>host:port/service</i></p> <p>For all other database types, use:</p> <p><i>server_name/host:port:database_name</i></p>
-edition	No	-createRepository -generateScript -dataLoad -dropRepository -listSchemas	<p>The edition name. This parameter is only valid if you specify databaseType=EBR.</p>
-dbUser	Yes	-createRepository -generateScript -dataLoad -dropRepository -generateResponseFile -listSchemas	<p>The database user name. For example, the SYS user on Oracle databases).</p> <p>This parameter is required if the -createWallet parameter is provided during the -generateResponseFile operation. RCU uses the database user name as the key or alias to store the database user password when generating a wallet. If the -createWallet parameter is not provided, the database user name is optional.</p>
-dbRole	No	-createRepository -generateScript -dataLoad -dropRepository -listSchemas	<p>The database user role. For example, SYSDBA for the SYS user on Oracle databases).</p> <p>This parameter is needed only if -dbUser is specified and the role is SYSDBA.</p>

Table 3-3 (Cont.) RCU Command Line Parameters and Descriptions

Parameter	Required?	Valid for Which Operation?	Description
-unicodeSupport	No	-createRepository -dropRepository	Specify either <i>Yes</i> or <i>No</i> for unicode support. Default parameter is <i>Yes</i> . This parameter is only valid if you specify <code>databaseType=SQLSERVER</code> .
-skipCleanupOnFailure	No	-createRepository -generateScript -dataLoad	If the schema creation fails, specify whether you want to skip the schema cleanup. The valid values are <i>Yes</i> or <i>No</i> . The default value is <i>No</i> .
-skipTablespaceDropOnFailure	No	-createRepository -generateScript -dataLoad	If schema creation fails, whether or not you want to skip the schema cleanup. The valid values are <i>Yes</i> or <i>No</i> . The default value is <i>No</i> . Specify <i>Yes</i> to retain tablespaces for failed components during schema cleanup. Specify <i>No</i> to drop tablespaces for failed components during schema cleanup.
-scriptLocation	No	-generateScript	Specify the location to save the generated script for system load repository.
-useSamePasswordForAllSchemasUsers	No	-createRepository -dataLoad -generateResponseFile	Whether you want to use the same password for all schemas. The valid values are <i>true</i> or <i>false</i> . The default value is <i>false</i> .
-selectDependentsForComponents	No	-createRepository -generateScript -dataLoad -dropRepository -generateResponseFile	Whether you want to have RCU automatically select dependent schemas for your components. The valid values are <i>true</i> or <i>false</i> . The default value is <i>false</i> . STB schema is created independent of this switch, whether the value is <i>true</i> or <i>false</i>
-honorOMF	No	-createRepository -generateScript	If the value is set to <i>true</i> , RCU creates datafiles using the Oracle-Managed Files (OMF) naming format. The valid values are <i>true</i> or <i>false</i> . The default value is <i>false</i> .
-encryptTablespace	No	-createRepository -generateScript	Specify whether you want to encrypt all new tablespaces that are created by RCU. This option is valid only if you have TDE (Transparent Data Encryption) enabled in the database (Oracle or Oracle EBR) when you start RCU. TDE tablespace encryption allows you to encrypt sensitive data stored in tablespaces. The valid values are <i>true</i> or <i>false</i> . The default value is <i>false</i> . If the value is set to <i>true</i> , <i>all new</i> tablespaces created by RCU are encrypted only if TDE is enabled in the database. Tablespaces that were created before RCU was launched cannot be encrypted by using this option.

Table 3-3 (Cont.) RCU Command Line Parameters and Descriptions

Parameter	Required?	Valid for Which Operation?	Description
-skipTablespaceDrop	No	-dropRepository	This parameter allows you to skip dropping tablespaces during the -dropRepository operation. The valid values are Yes or No. Specify Yes to skip tablespace drop. The default value is No.
-variables	No	-createRepository -generateScript -dataLoad -dropRepository	Comma-separated variables in the format <i>variablename=value</i> . See RCU Environment Variables for a list of RCU environment variables.
-schemaPrefix	No	-createRepository -generateScript -dataLoad -dropRepository -generateResponseFile	Prefix for your schemas. For more information about schema prefixes, see Planning Your Schema Creation and Select Components (for Create Operation) . This parameter is required for the -createRepository, -generateScript, -dataLoad, and -dropRepository operations. Also, this parameter is required if the -createWallet parameter is provided during the -generateResponseFile operation. RCU uses the prefixed schema name as the key or alias to store schema passwords when generating a wallet. If the -createWallet parameter is not provided, the schema prefix is optional.
-component	Yes	-createRepository -generateScript -dataLoad -dropRepository	ID of the component that you want to add or drop. To specify a single component, use the format: <code>-component component_ID</code> To specify multiple components, use the format: <code>-component component_ID -component component_ID</code> For a list of valid component (schema) IDs, see About Repository Creation Utility Schemas, IDs, and Tablespaces . Multiple components are sometimes necessary because of dependencies; for example, you can not create the Oracle Platform Security Services (OPSS) schema if the Audit Services (IAU) schema does not exist. In this case, you must specify both schemas: <code>-component OPSS -component IAU</code>
-tablespace	No	-createRepository -generateScript	Tablespace name of the component. This tablespace must exist in the database if you are using this option.
-tempTablespace	No	-createRepository -generateScript	TEMP tablespace name of the component. This tablespace must exist in the database if you are using this option.

Table 3-3 (Cont.) RCU Command Line Parameters and Descriptions

Parameter	Required?	Valid for Which Operation?	Description
-createWallet	No	- generateResponseFile	<p>Provide this parameter if you want to create a wallet file to securely store your RCU passwords, such as the database user password, schema passwords, and custom variable passwords.</p> <p>RCU accepts password credentials stored in an Oracle Wallet. That is, you can use the generated wallet later in silent situations to provide your passwords to RCU without having to directly enter any passwords on the command line.</p> <p>The wallet is generated in the same directory as the response file.</p>
-walletDir	No	-createRepository -generateScript -dataLoad -dropRepository -listSchemas	<p>The absolute path of the wallet directory where your RCU passwords that are used for creating or dropping schemas are stored. If you choose to use a wallet to pass passwords to RCU, RCU retrieves the required passwords from the specified directory. This option is valid for silent mode only.</p> <p>If you use this option, the wallet must already exist and contain the required passwords. If the wallet does not contain the required passwords, RCU prompts you for the missing passwords on the command line.</p> <p>This directory should contain a valid <code>cwallet.sso</code> file. RCU supports auto-login wallets only (password is not needed to open wallet).</p>
-responseFileDir	No	- generateResponseFile	<p>The absolute path of the response file directory.</p> <p>If specified, RCU generates a response file named <code>rcuResponseFile.properties</code> in the given directory.</p> <p>If not specified, RCU generates a response file in the <code>\$HOME/.rcu</code> directory by default.</p>
-componentList	No	- generateResponseFile	<p>Comma-separated list of component IDs for the components in the Oracle home that you want to add to the response file. To generate a list of valid component IDs for a specific Oracle home, see Generating a List of Components in an Oracle Home from the Command Line.</p> <p>If not specified, all valid components in the Oracle home are added to the response file by default.</p>
-validate	No	-createRepository -generateScript -dataLoad -dropRepository	<p>Use this option to execute validation checks in silent mode and verify that all prerequisites for the specified operation have been met.</p> <p>With this option, RCU only checks for the prerequisites that are required to perform the operation and then exits. For more information about validate parameter, see Using the -validate Parameter to Verify Prerequisites.</p>
-schemaPrefixes	No	-listSchemas	<p>Comma-separated list of schema prefixes. If provided, RCU only lists the schemas with the given prefixes.</p>

Using the `-silent` Command

Use the `-silent` command if you want to run RCU with minimal interaction once you have entered the command.

Run RCU for all databases in silent mode

You must specify all mandatory command-line parameters in the command. For example:

```
rcu -silent -createRepository -connectString database_connect_string -dbUser  
database_user -component component
```

In this scenario, RCU prompts you for the database and component schema passwords from the command line. If you specify multiple components, you are prompted for the passwords in the order in which the components are specified.

Instead of directly entering all the RCU parameters on the command line, you can provide the location and name of a file that contains certain input values. This file (called a response file) allows you to pass values for all valid command-line parameters to RCU through a text file. When you run RCU with a response file, all values are read from the file to create or drop your schemas. For more information about response file, see [Using Response Files](#).

If you want to avoid all interaction from the command line, you can create a text file contains all the necessary passwords (one password per line) and then use the `-f` option to pass this password file to RCU. For example, if you create a file called `passwordfile.txt`, you can use the command below:

```
rcu -silent -createRepository -connectString database_connect_string -dbUser  
database_user -component component1_name -component  
component2_name -f < passwordfile.txt
```

The `passwordfile.txt` file would contain, in order:

```
database_password  
component1_schema_password  
component2_schema_password
```

When schemas are created for multiple components, `-tablespace` and `-tempTablespace` has to be declared for each component individually.

For example:

```
./rcu -silent -createRepository -connectString <connectString> -dbUser SYS  
-dbRole SYSDBA -schemaPrefix DEV01 -selectDependentsForComponents true \  
-component MDS -tablespace FMW_INFRA -tempTablespace TEMP \  
-component IAU -tablespace FMW_INFRA -tempTablespace TEMP \  
-component IAU_APPEND -tablespace FMW_INFRA -tempTablespace TEMP \  
-component IAU_VIEWER -tablespace FMW_INFRA -tempTablespace TEMP \  
-component STB -tablespace FMW_INFRA -tempTablespace TEMP -f <
```

It is important to make sure that the passwords in the file are specified in the same order as the components on the command line.

Once the installation is complete, the password file must be removed. The passwords are maintained in cleartext format, and therefore present a security risk if the password file is left in place after installation.

Instead of using a plain text password file, you can also create an Oracle Wallet file that contains all the necessary passwords and then use the `-walletDir` parameter to pass this file to RCU. In this case, RCU does not prompt you for any passwords that are stored in the wallet. For more information about using wallet, see [Using a Wallet to Store Passwords](#).

For more information on running RCU in `-silent` mode, see the following topics:

Run RCU for Oracle GoldenGate on ATP databases in silent mode

Note:

To create schemas on an Autonomous Transaction Processing database (both Autonomous Transaction Processing - Dedicated and Autonomous Transaction Processing-Shared) for Oracle GoldenGate, you can use only the silent command and cannot use the Repository Creation Utility screens (GUI mode).

For example, use the following command to run RCU in silent mode:

```
./rcu -silent -createRepository -connectString '(description=(CONNECT_TIMEOUT=120)
(RETRY_COUNT=20)(RETRY_DELAY=3) \
(TRANSPORT_CONNECT_TIMEOUT=3)(ADDRESS_LIST=(LOAD_BALANCE=on)
(ADDRESS=(PROTOCOL=protocol_name) \
(HOST=host_name)(PORT=port_number)))(CONNECT_DATA=(SERVICE_NAME=service_name))) -dbUser
admin -dbRole normal \
-useSSL -sslArgs javax.net.ssl.trustStore=/home/opc/veridata/
cwallet.sso,javax.net.ssl.trustStoreType=SSO, \
javax.net.ssl.keyStore=/home/opc/veridata/
cwallet.sso,javax.net.ssl.trustStoreType=SSO,oracle.net.ssl_server_dn_match=true, \
oracle.net.ssl_version=1.2 -useSamePasswordForAllSchemaUsers true -
selectDependentsForComponents true \
-schemaPrefix OGG1ATP -component UCSUMS \
-component OPSS -component IAU -component STB -component WLS -component IAU_APPEND -
component IAU_VIEWER -component MDS -component VERIDATA \
-serverDN "CN=adwc.uscom-east-1.oraclecloud.com,OU=Oracle BMCS
US,O=OracleCorporation,L=Redwood City,ST=California,C=US"
```

Run RCU for Oracle WebLogic Server on ATP-S database in silent mode

Use the following command to run RCU in silent mode:

```
./rcu -silent -createRepository -databaseType ORACLE -connectString
jdbc:oracle:thin:@dbname_tp?TNS_ADMIN=/users/test/wallet_dbname/ -dbUser admin -dbRole
normal \
-useSamePasswordForAllSchemaUsers true -selectDependentsForComponents true \
-schemaPrefix WLS1001 -component STB -tablespace DATA -tempTablespace TEMP \
-component WLS -tablespace DATA -tempTablespace TEMP \
-component IAU_APPEND -tablespace DATA -tempTablespace TEMP \
-component IAU_VIEWER -tablespace DATA -tempTablespace TEMP \
-component OPSS -tablespace DATA -tempTablespace TEMP \
-component IAU -tablespace DATA -tempTablespace TEMP \
-component MDS -tablespace DATA -tempTablespace TEMP \
-f < ~/<rcu_atp_password>
```

- [Using the -validate Parameter to Verify Prerequisites](#)
Before you run an operation from the command line, you can use the `-validate` option in silent mode to verify that all RCU prerequisites have been met.

- **Using a Wallet to Store Passwords**
If you are running RCU from the command line, password credentials (for example, schema passwords) can be stored in an Oracle Wallet file. This wallet file can be provided to RCU from the command line.

Using the `-validate` Parameter to Verify Prerequisites

Before you run an operation from the command line, you can use the `-validate` option in silent mode to verify that all RCU prerequisites have been met.

When you run RCU with the `-validate` option, RCU performs validation checks to validate all prerequisites for the specified operation, and then exits. For example, this command validates the values for any command-line parameters and verifies that the minimum requirements are met in the database prior to schema creation.

You can add the `-validate` option to any valid operation to run the validation checks, as shown in the following example:

```
./rcu -silent -createRepository -useSamePasswordForAllSchemaUsers true -databaseType
ORACLE
-connectString examplehost.exampledomain.com:1521:exampleSID -dbUser sys -dbRole sysdba
-selectDependentsForComponents true -schemaPrefix DEV -component MDS -component OPSS
-component STB -component BIPLATFORM -validate
```

If a prerequisite check fails, RCU returns a non-zero exit code and prints the issue to the console. You can refer to the command output and log file to manually fix the issue, and then rerun the `-validate` command to ensure that all checks are successful.

If all prerequisite checks pass, the exit status is zero (0).

If a validation check fails, the following table provides more information about the exit codes returned by RCU.

Validation Check	Description	Exit Code Number
Database Connection Check	<p>Validates the provided connection credentials for the database in which you create or drop schemas.</p> <p>This check ensures that a database connection can be established by using the values provided for the database connect string, user name, and password.</p> <p>If the <code>-encryptTablespace true</code> option is provided, RCU verifies that TDE (Transparent Data Encryption) is enabled in the database.</p>	<ul style="list-style-type: none"> • Database connection failed: 100 • Unsupported database type: 101 • Empty field: 102 • Invalid port: 103
Global Prerequisites Check	<p>Verifies the global prerequisites listed in the global <code>ComponentInfo.xml</code> file (in <code>ORACLE_HOME/oracle_common/rcu/config</code>).</p> <p>For example, this check verifies the database version and the values for the database initialization parameters.</p>	<ul style="list-style-type: none"> • Global prerequisite failed: 200 • Metadata initialization failed: 201 • TDE not enabled: 202

Validation Check	Description	Exit Code Number
Schema Prefix Check	Validates the <code>-schemaPrefix</code> parameter. <ul style="list-style-type: none"> For the create operation, RCU ensures that the prefix follows the expected pattern and does not exceed the allowed number of characters. For the drop operation, RCU ensures that the schema prefix already exists. 	<ul style="list-style-type: none"> Schema prefix validation failed: 300
Component Name Check	Validates the list of component schema names provided. For the create operation, RCU ensures that the components do not exist for the given prefix and any dependent components are selected.	<ul style="list-style-type: none"> Component validation failed: 400 Component dependency validation failed: 401
Schema Password Check	Verifies that a given schema password follows the supported password pattern and does not exceed 30 characters.	<ul style="list-style-type: none"> Schema password validation failed: 700
Component Prerequisites Check	Validates the component-specific prerequisites of each component. The prerequisites are listed in the component repository configuration file (<code>component.xml</code>) in <code>ORACLE_HOME/product_directory/common/sql/component</code> for each component.	<ul style="list-style-type: none"> Component prerequisite failed: 500
Tablespace Validation Check	Validates the tablespace names and verifies that the tablespace prerequisites are met.	<ul style="list-style-type: none"> Tablespace validation failed: 600 Mapping tablespace to component validation failed: 601
Custom Variables Check	Validates component custom variables and their values.	<ul style="list-style-type: none"> Custom variable validation failed: 800
Script Location Validation Check	Validates the value provided for the <code>-scriptLocation</code> argument and checks whether the value is null or empty.	<ul style="list-style-type: none"> Value for <code>-scriptLocation</code> argument is invalid or not provided: 900

Using a Wallet to Store Passwords

If you are running RCU from the command line, password credentials (for example, schema passwords) can be stored in an Oracle Wallet file. This wallet file can be provided to RCU from the command line.

When you run RCU from the command line, RCU prompts you to enter values for any required passwords by default. To avoid entering passwords on the command line, you can create a wallet file to securely store any necessary password credentials. You can then pass the wallet to RCU by providing the wallet location with the `walletDir` parameter.

Creating a Wallet Using RCU

A wallet for providing RCU passwords can be generated by RCU as part of the response file creation:

- To create a wallet using the RCU graphical interface, see [Creating a RCU Response File from the Graphical Interface](#).
- To create a wallet using the RCU command-line interface, see [Creating a RCU Response File from the Command Line](#).

Once the wallet is created, this file can be reused to store and provide passwords for multiple sessions.

RCU only supports auto-login wallets (no password is needed to open a wallet). Password-protected wallets are not supported.

When RCU generates the wallet, RCU uses the prefixed schema name as the key or alias for storing schema passwords, which allows you to reuse the same wallet for multiple sessions. For the database user password, the alias is the database user name (for example, SYS). If the same password is used for all the schemas, then RCU uses the alias `prefix_COMMON_SCHEMA_PASSWORD` to save the password in the wallet.

Example 3-1 Using the `-walletDir` Parameter

After the wallet is created and contains the necessary passwords, use the `-walletDir` parameter to pass this file to RCU so that you do not have to directly enter your passwords on the command line. Alternatively, the wallet location can be provided to RCU through a response file.

For example:

```
./rcu -silent -createRepository -connectString
examplehost.exampledomain.com:1521:example_sid -dbUser sys -dbRole sysdba
-schemaPrefix DEV -component MDS -component STB -walletDir /home/exampleuser/wallet
```

When you pass the wallet to RCU, RCU expects all the necessary passwords required to perform an operation to be in the wallet, which include your:

- Database user password
- Schema passwords
- Custom Variable passwords (for Oracle Data Integrator)

In this example, the wallet should contain passwords for the database user (sys), the Metadata Services (MDS) schema, and the Service Table (STB) schema. If a wallet does not contain all the necessary passwords, you are prompted to enter the missing passwords on the command line.

Using the `-interactive` Command

Use the `-interactive` command to run the RCU graphical interface. This is the default value if neither `-silent` nor `-interactive` is specified.

You can specify information from the command line that would be populated in the graphical interface to expedite your RCU operation.

For example, if you run RCU with the following command, the **Database Connection Details** screen contains blank fields.

```
./rcu
```

But if you run RCU with a few parameters using the following command, the **Database Connection Details** screen contains the information supplied from the command line.

```
./rcu -interactive -createRepository -connectString  
examplehost.exampledomain.com:1521:example_sid -dbUser SYS -component MDS
```

When you run the RCU graphical interface, you can provide the location and name of a file (called a response file) that contains certain input values (for example, your database connection information). When you use the graphical interface, you are prompted for these values. The values you enter in a response file can be used to populate certain RCU screens. For more information about using response file, see [Using Response Files](#).

Using Response Files

Before you run RCU, you can provide information that is required to perform a specific operation in a response file. For example, you can provide your database connection details, a list of components to be added or dropped, and the schema prefix to RCU through a response file.

You can use a response file to automate a RCU session. When you run RCU by using a response file, RCU reads the information provided in the response file to complete the operation.

For more information, see the following topics:

- [About Response Files](#)
A response file is a properties file in which all RCU command-line parameters can be provided as input to RCU to perform an operation.
- [Creating a RCU Response File from the Graphical Interface](#)
Use the **Save Response File** option on the Summary screen to save the information you provide in the RCU screens to a response file.
- [Creating a RCU Response File from the Command Line](#)
Use the `-generateResponseFile` command to generate a response file.
- [Performing RCU Operations by Using a Response File](#)
Use the `-responseFile` command to perform an operation with a response file. You use a response file to provide input to RCU to automate an operation from the command line or from the graphical interface.

About Response Files

A response file is a properties file in which all RCU command-line parameters can be provided as input to RCU to perform an operation.

Rather than directly entering the [RCU Command Line Parameters](#) on the command line, you can provide values for these parameters to RCU through a text file. You can generate this file from the RCU graphical interface by using the values you provide in the RCU screens or from the command line. After you create a response file, the parameters can be modified in a text editor or be used exactly as-is to perform an operation at a later time.

If you choose to run RCU from the command line with a response file, the values you specify in a response file are the values for the RCU parameters that you would normally provide on the command line during a typical silent RCU session. If you choose to run the RCU graphical interface with a response file, the values you specify in a response file are used to prepopulate the fields on certain screens.

Creating a RCU Response File from the Graphical Interface

Use the **Save Response File** option on the Summary screen to save the information you provide in the RCU screens to a response file.

After you click the **Save Response File** option, you are prompted to specify a location to create this file. By default, RCU saves the response file in the `$HOME/.rcu` directory.

Because the response file needs to contain password information, RCU provides the **Save Passwords in Wallet** option to securely store any passwords that you provide on the RCU screens in a wallet. You can use the wallet later in silent situations to provide the necessary passwords to RCU so that you do not have to directly enter your passwords on the command line. When you run RCU from the command line, the wallet location can be passed to RCU on the command line or through a response file. If a wallet directory is not passed to RCU, you are prompted for the required passwords.

Creating a RCU Response File from the Command Line

Use the `-generateResponseFile` command to generate a response file.

The full syntax for the RCU command-line interface to generate a RCU response file is shown below:

```
rcu -silent -generateResponseFile
  [-responseFileDir absolute_path_of_response_file_directory]
  [-schemaPrefix schema_prefix]
  [-componentList list_of_component_IDs]
  [-createWallet]
  [-useSamePasswordForAllSchemaUsers [true|false]]
  [-selectDependentsForComponents [true|false]]
  [-dbUser database_username]
```

If the `-createWallet` parameter is provided, then values for `-dbUser` and `-schemaPrefix` are required. Otherwise, the `-dbUser` and `-schemaPrefix` parameters are optional. RCU uses the prefixed schema name and the database user name as the key or alias to store schema passwords and the database user password in the wallet, respectively.

If you provide the `-createWallet` and the `-useSamePasswordForAllSchemaUsers true` parameters on the command line, then all schema passwords are set to the same value in the wallet.

If the `-createWallet` parameter is provided, RCU will prompt you to enter a value for each password that is stored in the wallet.

Below is a sample command to generate a response file on a UNIX operating system:

```
./rcu -silent -generateResponseFile -componentList OPSS,IAU -schemaPrefix DEV -
createWallet
-responseFileDir /home/exampleuser/rcu -useSamePasswordForAllSchemaUsers true
-selectDependentsForComponents true -dbUser sys
```

In this example, a response file and wallet is created in the `/home/exampleuser/rcu` directory, and the information provided on the command line (such as the list of components) is added to the response file.

Performing RCU Operations by Using a Response File

Use the `-responseFile` command to perform an operation with a response file. You use a response file to provide input to RCU to automate an operation from the command line or from the graphical interface.

If you choose to run the graphical interface with a response file, RCU prepopulates certain RCU screens (such as the [Database Connection Details](#) screen) based on the input values that you provide in a response file. If you choose to run RCU from the command line, you can use a response file to provide values for all valid RCU parameters rather than directly entering these parameters on the command line.

The full syntax for the RCU command-line interface to perform a RCU operation with a response file is shown below:

```
rcu [-silent|-interactive] -responseFile absolute_path_of_response_file
```

Following is a sample command to automate a silent RCU session by using a response file on a UNIX operating system:

```
./rcu -silent -responseFile /home/exampleuser/rcu/rcuResponseFile.properties
```

Note:

- If you provide a value for a parameter on the command line and in the response file, RCU uses the value that is provided on the command line.
- Before you run RCU, ensure that you have provided the required information in the response file. If some of the mandatory properties in the response file are missing values when you run RCU, RCU will notify you and exit.
- When you run RCU, the `dbRole` parameter is not normally required to connect to certain databases (for example, SQL Server). However, when a RCU response file is generated, the `dbRole` parameter is marked as required in the response file by default. As a result, if you use a response file, the `dbRole` field must not be left blank, even if the database role is not required to connect to a database like SQL Server.

Creating a Repository from the Command Line

If you are a user with full SYS or SYSDBA privileges, use the `-createRepository` operation to create a repository.

The full syntax for the RCU command-line interface to create a repository is shown below:

```
rcu [-silent | -interactive] -createRepository  
  [-compInfoXMLLocation ComponentInfo.xml_file_location]  
  [-storageXMLLocation Storage.xml_file_location]  
  [-databaseType [ORACLE|EBR]]  
  -connectString database_connect_string  
  [-edition edition_name]  
  -dbUser database_username  
  [-dbRole database_user_role]  
  [-unicodeSupport [Yes|No]]  
  [-skipCleanupOnFailure [true|false]]
```

```

[-skipTablespaceDropOnFailure [Yes|No]]
[-useSamePasswordForAllSchemaUsers [true|false]]
[-selectDependentsForComponents [true|false]]
[-honorOMF [true|false]]
[-encryptTablespace [true|false]]
[-variables variablename=value]
[-schemaPrefix schema_prefix]
-component component_ID
[-tablespace component_tablespace_name]
[-tempTablespace component_temp_tablespace_name]
[-walletDir absolute_path_of_wallet_directory]
[-validate]

```

When you specify the `-component`, you must use the correct component IDs, which are listed in [About Repository Creation Utility Schemas, IDs, and Tablespaces](#).

Before you create any schemas, you must be aware of and specify all dependencies for the component that you are loading. For example, the `SOAINFRA` schema depends on the `MDS` and `ORASDPM` schemas; if you try to load the `SOAINFRA` schema without specifying both the `MDS` and `ORASDPM` schemas, or if the `MDS` and `ORASDPM` schemas do not already exist in the database, RCU stops before any loading takes place.

Following is a sample command to create the `OPSS` schema on a UNIX operating system:

```

./rcu -silent -createRepository -databaseType ORACLE -connectString
examplehost.exampledomain.com:1521:exampleSID -dbUser sys
-dbRole sysdba -schemaPrefix TEST -component OPSS -component MDS

```

Generating a System Load Script From the Command Line

If you are a user without `SYS` or `SYSDBA` privileges, use the `-generateScript` operation to generate a script. A user with `DBA` privileges can run the script later to complete the system load phase.

The full syntax for the RCU command-line interface to generate a system load script is shown below:

```

rcu [-silent | -interactive] -generateScript
[-compInfoXMLLocation ComponentInfo.xml_file_location]
[-storageXMLLocation Storage.xml_file_location]
[-databaseType [ORACLE|EBR]]
-connectString database_connect_string
[-edition edition_name]
-dbUser database_username
[-dbRole database_user_role]
[-skipCleanupOnFailure [Yes|No]]
[-skipTablespaceDropOnFailure [Yes|No]]
[-scriptLocation script_location]
[-selectDependentsForComponents [true|false]]
[-honorOMF [true|false]]
[-encryptTablespace [true|false]]
[-variables variablename=value]
[-schemaPrefix schema_prefix]
-component component_ID
[-tablespace component_tablespace_name]
[-tempTablespace component_temp_tablespace_name]
[-walletDir absolute_path_of_wallet_directory]
[-validate]

```

When specifying the `-component`, you must use the correct component IDs, which are listed in [About Repository Creation Utility Schemas, IDs, and Tablespaces](#).

Before you create a script, you must be aware of and specify the all component dependencies. For example, the `SOAINFRA` schema depends on the `MDS` and `ORASDPM` schemas; if you specify the `SOAINFRA` schema without specifying both the `MDS` and `ORASDPM` schemas, or if the `MDS` and `ORASDPM` schemas do not already exist in the database, RCU stops before completing the operation.

Below is a sample command to create a system load script on a UNIX operating system:

```
./rcu -silent -generateScript -databaseType ORACLE -connectString
examplehost.exampledomain.com:1521:exampleSID -dbUser sys
-dbRole sysdba -scriptLocation /tmp/RCUdate_timestamp_random_number/logs/ -schemaPrefix
TEST
-component OPSS -component MDS
```

Loading Data Into the Repository From the Command Line

After the system load scripts are run by a user with DBA privileges, any user can then use the `-dataLoad` operation to load data into a repository.

The full syntax for the RCU command-line interface to load data into a repository is shown below:

```
rcu [-silent | -interactive] -dataLoad
[-compInfoXMLLocation ComponentInfo.xml_file_location]
[-storageXMLLocation Storage.xml_file_location]
[-databaseType [ORACLE|EBR]]
-connectString database_connect_string
[-edition edition_name]
-dbUser database_username
[-dbRole database_user_role]
[-skipCleanupOnFailure [Yes|No]]
[-skipTablespaceDropOnFailure [Yes|No]]
[-useSamePasswordForAllSchemaUsers [true|false]]
[-selectDependentsForComponents [true|false]]
[-variables variablename=value]
[-schemaPrefix schema_prefix]
-component component_ID
[-walletDir absolute_path_of_wallet_directory]
[-validate]
```

Below is a sample command to perform a data load on a UNIX operating system:

```
./rcu -silent -dataLoad -databaseType ORACLE -connectString
examplehost.exampledomain.com:1521:exampleSID -dbUser sys -dbRole
sysdba -schemaPrefix TEST -component OPSS -component MDS
```

Dropping a Repository from the Command Line

Use the `-dropRepository` operation to drop a repository.

The full syntax for the RCU command-line interface to drop a repository is shown below:

```
rcu [-silent | -interactive] -dropRepository
[-compInfoXMLLocation ComponentInfo.xml_file_location]
[-storageXMLLocation Storage.xml_file_location]
[-databaseType [ORACLE|EBR]]
-connectString database_connect_string
```



```

[-edition edition_name]
-dbUser database_username
[-dbRole database_user_role]
[-unicodeSupport [Yes|No]]
[-selectDependentsForComponents [true|false]]
[-skipTablespaceDrop [Yes|No]]
[-variables variablename=value]
[-schemaPrefix schema prefix]
-component component_ID
[-walletDir absolute_path_of_wallet_directory]
[-validate]

```

You must also be aware of schema dependencies when dropping schemas (see [About Repository Creation Utility Schemas, IDs, and Tablespaces](#)). For example, several schemas require the MDS schema to be present; if you choose to drop the MDS schema, then all the schemas that require the MDS schema stops working.

Below is a sample command to drop the OPSS schema on a UNIX operating system:

```

./rcu -silent -dropRepository -databaseType ORACLE -connectString
examplehost.exampledomain.com:1521:exampleSID -dbUser sys -dbRole
sysdba -schemaPrefix TEST -component OPSS

```

Generating a List of Components in an Oracle Home from the Command Line

Use the `-listComponents` command to generate a list of valid components that are available in a given Oracle home. This command displays the name, component ID, and the supported database types for each component that is available in the Oracle home in which RCU was started.

The full syntax for the RCU command-line interface to generate a list of components is shown below:

```
rcu -silent -listComponents
```

The Component ID and database type displayed for each component in the command output are the values that you must specify with the `-component` and `-databaseType` parameters, respectively, when you create schemas from the command line.

Generating a List of Schemas in a Database from the Command Line

Use the `-listSchemas` command to generate a list of valid schemas in a given database.

The full syntax for the RCU command-line interface to list the schemas in a database is shown below:

```

rcu -silent -listSchemas
[-databaseType [ORACLE|EBR]]
-connectString database_connect_string
[-edition edition_name]
-dbUser database_username
[-dbRole database_user_role]
[-schemaPrefixes comma_separated_list_of_prefixes]
[-walletDir absolute_path_of_wallet_directory]

```

Below is a sample command to list the schemas in an Oracle database on a UNIX operating system:

```
./rcu -silent -listSchemas -databaseType ORACLE -connectString
examplehost.exampledomain.com:1521:exampleSID
-dbUser sys -dbRole sysdba
```

You can also specify a comma-separated list of prefixes using the `-schemaPrefixes` argument. If provided, RCU only displays the schemas with those prefixes.

For example:

```
./rcu -silent -listSchemas -databaseType ORACLE -connectString
examplehost.exampledomain.com:1521:exampleSID -dbUser sys
-dbRole sysdba -schemaPrefixes DEV,DEV1
```

RCU Environment Variables

The RCU environment variables are the variables picked up by RCU from the environment. If an environment variable is not set, then RCU uses the default value.

Table 3-4 RCU Environment Variables

Variable	Default Value	Description
RCU_LOG_LOCATION	/tmp (UNIX operating systems) C:\Users\ <i>user_name</i> \AppData \Local\Temp (Windows operating systems)	Location of the RCU log file.
RCU_TIMESTAMP_LOG_DIR	true	Determines whether or not a directory with the format <i>logdir.yyyy-dd_hh-mm</i> is created for the RCU log file. Set this variable to true or false.
RCU_LOG_NAME	rcu.log	Name of the RCU log file.
RCU_LOG_LEVEL	ERROR	Determines the RCU log level. Set this variable to one of SEVERE, ERROR, NOTIFICATION, or TRACE.
RCU_JAVA_OPTIONS	N/A	Set this variable to any Java Virtual Machine (JVM) argument. For example: <pre>setenv RCU_JAVA_OPTIONS -Djava.io.tmpdir=/scratch/mytmpDir</pre>

A

Repository Creation Utility Screens

Use this information to learn more about the various features and elements of the Repository Creation Utility (RCU) screens. Each screen will prompt you for information required to create or drop your schemas.

Note:

The following sections are not applicable when you create schemas for Oracle GoldenGate products on an Autonomous Transaction Processing database (both Autonomous Transaction Processing - Dedicated and Autonomous Transaction Processing-Shared) as you can run RCU only in silent mode for Oracle GoldenGate.

During schema creation for an Autonomous Transaction Processing database (both Autonomous Transaction Processing - Dedicated and Autonomous Transaction Processing-Shared) database, if you encounter warnings in the Repository Creation Utility screens, see [Troubleshooting Tips for Schema Creation on an Autonomous Transaction Processing Database](#).

- [Welcome](#)
The Welcome screen is the first screen that appears when you start RCU. Note the navigation pane on the left that summarizes the tasks that RCU helps you complete.
- [Create Repository](#)
Use the Create Repository screen to select the action that you want to perform.
- [Database Connection Details](#)
Use the Database Connection Details screen to specify the connection credentials to the database in which you will be create or drop your schemas.
- [Select Components \(for Create Operation\)](#)
Use the Select Components screen to select the components for which you want to create schemas, and specify a prefix to group them together.
- [Select Components \(for Drop Operation\)](#)
Use the Select Components screen to select the prefix and the schemas that you want to drop.
- [Schema Passwords](#)
Use the Schema Passwords screen to specify the passwords for your schema owners; there are three ways to specify schema passwords on this screen.
- [Custom Variables](#)
If you are installing a product that requires custom variables, you will see the Custom Variables screen. Use this screen to specify additional product configuration information.
- [Map Tablespaces](#)
Use the Map Tablespaces screen to configure the desired tablespace mapping for the schemas that you want to create.

- [Summary \(for Create Operation\)](#)
On the Summary (for Create operation) screen, verify your information, then click **Create** to begin schema creation.
- [Summary \(for Drop Operation\)](#)
On the Summary (for Drop operation) screen, verify your information, then click **Drop** to drop the schemas.
- [Completion Summary \(for Create Operation\)](#)
The Completion Summary (for Create Operation) screen contains information about the log files that were created from this RCU operation. You can click on the name of a particular log file to view the contents of that file.
- [Completion Summary \(for Drop Operation\)](#)
The Completion Summary (for Drop operation) screen contains information about the log files that are created from this RCU operation. Note the log file names for each component that are visible in the *Logfile* column.

Welcome

The Welcome screen is the first screen that appears when you start RCU. Note the navigation pane on the left that summarizes the tasks that RCU helps you complete.

Each item in the navigation pane represents a specific screen that prompts you for information that is required to create or drop your schemas.

Create Repository

Use the Create Repository screen to select the action that you want to perform.

- [Create Repository](#)
Select **Create Repository** to create component schemas in the database.
- [Drop Repository](#)
Select **Drop Repository** to remove component schemas from the database.

Create Repository

Select **Create Repository** to create component schemas in the database.

The following table describes the options available:

Option	Description
System Load and Product Load	<p>Select this option to perform both System Load and Product Load operations.</p> <p>Users must have DBA or SYSDBA permissions to select this option.</p> <p>For an Autonomous Transaction Processing database (both Autonomous Transaction Processing - Dedicated and Autonomous Transaction Processing-Shared) database, you must create schemas as a Normal user, and though, you do not have full SYS or SYSDBA privileges on the database, you must select System Load and Product Load.</p> <p>This option can be performed on any certified database.</p>

Option	Description
Prepare Scripts for System Load	<p>Select this option to perform actions that require DBA or SYSDBA permissions:</p> <ul style="list-style-type: none"> • Create tablespaces and schemas. • Create the <code>schema_version_registry</code> (if not already present). • Create entries in <code>schema_version_registry</code> for each selected component, set the proper access permissions, and set the status of the component to <code>LOADED</code> in the <code>schema_version_registry</code> table. <p>Any SYSDBA user or non-DBA user with the privileges described in Granting Permissions to Users for Querying System Load Objects can select this option. However, DBA privileges are required to execute the SQL script to complete the system load phase.</p> <p>This option is only supported on Oracle and Oracle EBR databases.</p> <p>If you create schemas on an Autonomous Transaction Processing database (both Autonomous Transaction Processing - Dedicated and Autonomous Transaction Processing-Shared) database, you must not select this option.</p>
Perform Product Load	<p>Select this option to load and create procedures, functions, tables, indexes and other objects within schemas and run any action that does not require DBA access.</p> <p>Any non-DBA user or the REGISTRYOWNER user can select this option.</p> <p>Before you select this option, the user must be granted the following permissions to perform data load:</p> <pre>grant REGISTRYACCESS to user; grant STBROLE to user;</pre> <p>If you create schemas on an Autonomous Transaction Processing database (both Autonomous Transaction Processing - Dedicated and Autonomous Transaction Processing-Shared), you must not select this option.</p>

Drop Repository

Select **Drop Repository** to remove component schemas from the database.

Database Connection Details

Use the Database Connection Details screen to specify the connection credentials to the database in which you will be create or drop your schemas.

Click **Next** when you have finished typing the connection credentials for your database. A screen indicating the progress of the installer establishing the connection with the specified database appears.

If an error occurs while the connection is being established, the error messages appear in the Messages field on the Database Connection Details screen.

Specific database requirements for the various schemas can be found in the *Oracle Fusion Middleware System Requirements and Specifications* document.

For certified database versions, see the *System Requirements and Supported Platforms for Oracle Fusion Middleware* document, which is available on the Oracle Fusion Middleware Supported System Configurations page.

Select one of the following depending on your database:

- [Connection Credentials for Oracle Databases and Oracle Databases with Edition-Based Redefinition](#)
To connect to an Oracle database or Oracle database with edition-based redefinition, you need to specify connection information about the database, such as Host Name, Port, Service Name, Username, Password, and Role.
- [Connection Credentials for an Autonomous Transaction Processing Database](#)
To connect to an Autonomous Transaction Processing database (both Autonomous Transaction Processing-Dedicated (ATP-D) and Autonomous Transaction Processing-Shared (ATP-S)), you need to specify connection information about the database, such as Username and Password.

Connection Credentials for Oracle Databases and Oracle Databases with Edition-Based Redefinition

To connect to an Oracle database or Oracle database with edition-based redefinition, you need to specify connection information about the database, such as Host Name, Port, Service Name, Username, Password, and Role.

Use the **Database Connection Details** screen to specify the connection credentials to the database in which you want to create or drop schemas. You can select different databases, however, all databases are not supported for all Fusion Middleware components.

Database Connection Details screen provides two types of Connection String formats as follows:

- Connection Parameters
- Connect String

Note:

To create schemas on an Autonomous Transaction Processing database (both Autonomous Transaction Processing - Dedicated and Autonomous Transaction Processing-Shared), you can specify the connection credentials only using the Connection String format. See [Connection Credentials for an Autonomous Transaction Processing Database](#).

For various database types and both **Connection String Format**, specify the following connection credentials:

Element	Description
Host Name	Enter the name of the server where your database is running. Use the following format: <code>examplehost.exampledomain.com</code>
Port	For Oracle RAC databases, specify the VIP name or one of the node names in this field. Enter the port number for your database. The default port number for Oracle databases is 1521.

Element	Description
Service Name	<p>Specify the service name for the database. Typically, the service name is the same as the global database name.</p> <p>If you are unsure what the service name for your database is, you can obtain it from the <code>SERVICE_NAMES</code> parameter in the initialization parameter file of the database. If the initialization parameter file does not contain the <code>SERVICE_NAMES</code> parameter, then the service name is the same as the global database name, which is specified in the <code>DB_NAME</code> and <code>DB_DOMAIN</code> parameters.</p> <p>For Oracle RAC databases, specify the service name of one of the nodes in this field. For example:</p> <pre>examplehost.exampledomain.com</pre>
Username	Enter the user name for your database.
Password	<p>Enter the password for your database user.</p> <p>Password must not be more than 31 characters long and can contain alphanumeric, pound, hash, comma, underscore characters. It should not begin with a number or a special character.</p>
Role	<p>Select the database user's role from the drop-down list:</p> <ul style="list-style-type: none"> • Normal • SYSDBA
Unicode Support	<p>Select the Unicode Support from the drop-down list:</p> <ul style="list-style-type: none"> • Yes • No
Database Name	Type the database name. It is case-sensitive.
Connect String	<p>For Oracle Databases and Oracle Database enabled for edition-based redefinition types, type Connect String in one of the following formats:</p> <ul style="list-style-type: none"> • <code><host>:<port>/<service></code> • <code><host>:<port>:<SID></code> • <code>DESCRIPTION=(ADDRESS=(host=host_name)(protocol=protocol_name)(port=port_number))(CONNECT_DATA=(SERVICE_NAME=service_name))</code>

 **Note:**

From Oracle Data Integrator Release 12.2.1.4.0 and later, MySQL connector is upgraded to version 8.0.XX. Due to this, the new MySQL connector performs time offset adjustments on date-time value. For this function to work, you have to either configure your MySQL server with a canonical time zone which is recognized by Java or override the server's time zone by setting the connection property `serverTimezone`, for example, `serverTimezone=UTC` or any other. The new jdbc URL is in the following format:

```
jdbc:mysql://<host>:<port>/<databasename>?serverTimezone=<java  
recognizable time
```

When you connect to a MySQL Database, you have to provide additional information, depending on the Connection String format you use:

- **Connection Parameters:** In this format, provide the following additional parameter:
`serverTimezone=<java recognizable time zone>` along with `<databasename>`

For example:

```
<databasename>?serverTimezone=<java recognizable time zone>
```

- **Connect String:** In this format, provide the following URL:
`jdbc:mysql://<host>:<port>/<database name>?serverTimezone=<java
recognizable time zone>`

Click **Next** after you have entered the connection credentials for your database. A screen indicating the progress of the installer establishing the connection with the specified database appears. If an error occurs while the connection is being established, the error message appears in the Messages field on the Database Connection Details screen.

Specific database requirements for the various schemas can be found in the *Oracle Fusion Middleware System Requirements and Specifications* document.

View the *System Requirements and Supported Platforms for Oracle Fusion Middleware* document for other certified databases that can be used with RCU. This document is available on the *Oracle Fusion Middleware Supported System Configurations* page.

Connection Credentials for an Autonomous Transaction Processing Database

To connect to an Autonomous Transaction Processing database (both Autonomous Transaction Processing-Dedicated (ATP-D) and Autonomous Transaction Processing-Shared (ATP-S)), you need to specify connection information about the database, such as Username and Password.

Field	Description
Connect String for Autonomous Transaction Processing database (both Autonomous Transaction Processing - Dedicated and Autonomous Transaction Processing-Shared)	<p>Enter connect string in the format: <code>dbname_tp?TNS_ADMIN=/users/test/wallet_dbname/</code>.</p> <p>In the connect string, you must pass <code>TNS_alias</code> as the database name found in <code>tnsnames.ora</code>, and <code>TNS_ADMIN</code> property to the location of the wallet files, <code>ojdbc.properties</code>, and <code>tnsnames.ora</code>.</p> <p>Note: For an Autonomous Transaction Processing-Shared database, you must use only one of the database service names, <code><databasename>_tpurgent</code> or <code><databasename>_tp</code>, specified in <code>tnsnames.ora</code>.</p> <p>Example connect string for Autonomous Transaction Processing - Dedicated database: <code>dbname_tp?TNS_ADMIN=/users/test/wallet_dbname/</code></p> <p>Example connect string for Autonomous Transaction Processing-Shared database: <code>dbname_tp?TNS_ADMIN=/users/test/wallet_dbname/</code></p> <p>In case of Oracle Internet Directory, use the connect string specified in <code>tnsnames.ora</code> (located in <code>\$ORACLE_HOME/network/admin</code>) for your service name or <code>TNS_alias</code>.</p> <p>Example connect string for Oracle Internet Directory for Autonomous Transaction Processing - Dedicated database:</p> <pre>(DESCRIPTION=(CONNECT_TIMEOUT=120)(RETRY_COUNT=20)(RETRY_DELAY=3) TRANSPORT_CONNECT_TIMEOUT=3) (ADDRESS_LIST=(LOAD_BALANCE=on)(ADDRESS=(PROTOCOL=<protocol_name>) (HOST=<host_name>) (PORT=<port_number>))) (CONNECT_DATA=(SERVICE_NAME=<service_name>.atp.oraclecloud.com)))</pre> <p>Example connect string for Oracle Internet Directory for Autonomous Transaction Processing-Shared database:</p> <pre>(DESCRIPTION=(CONNECT_TIMEOUT=120)(RETRY_COUNT=20)(RETRY_DELAY=3) (ADDRESS=(PROTOCOL=<protocol_name>) (PORT=<port_number>)(HOST=<host_name>)) (CONNECT_DATA=(SERVICE_NAME=<service_name>.adb.oraclecloud.com) (security=(ssl_server_cert_dn="CN=example.com, OU=<organizational_unit>, O=<organization>, L=<city>, ST=<state>, C=<country>"))))</pre>
Username	Specify the name of a user with administrator privileges.
Password	<p>Enter the password for your database user.</p> <p>Password must be minimum 12 characters, and must contain at least one uppercase, one lower case, and one number.</p>
Role	<p>Select <code>Normal</code> from the drop-down list.</p> <p>When you select <code>Normal</code>, a warning message is displayed. You can ignore the warning and continue with the schema creation. For more information, see Troubleshooting Tips for Schema Creation on an Autonomous Transaction Processing Database.</p>

Select Components (for Create Operation)

Use the Select Components screen to select the components for which you want to create schemas, and specify a prefix to group them together.

When you select **Create Repository** on the [Create Repository](#) screen, the **Select Component** screens appears.

The following table describes the elements on this screen.

Element	Description
Select existing prefix	Use this option to create schemas by using an existing prefix, which you can select from the drop-down list. If you select this option, you can only create schemas that do not already have this prefix in the database. For example, if <code>DEV_MDS</code> already exists, you are unable to select the MDS schema on the page to create it again).
Create new prefix	Use this option to create a new custom prefix that can be used to group your schema together. The prefix name must be a minimum of one character in length and cannot exceed 12 alphanumeric characters (0-9, a-z, or A-Z) in length (not including the underscore character). Prefixes should not start with a number. No whitespace or special characters are allowed. You can edit the schema name or prefix by clicking the item that you want to change in the <i>Schema Owner</i> column and editing the table cell directly. For more information about custom prefixes, see About Custom Prefixes .
Component	Use the <i>Component</i> column in the table to select the component schema that you want to create. When you select a component, any other components that may be required by the component you select are also selected. For example, if you select Oracle Platform and Security Services , then the Audit Services schema is also automatically selected, if it has not already been selected. The Audit Services schema is required by the Oracle Platform and Security Services schema. If a component has a plus sign (+) next to its name, then there are sub components available. Click on the plus sign (+) to expand the category to view all sub components. If you want to select a component with all its subcomponents, click on the top-most box with the plus sign (+).
Schema Owner	This column shows the name of the schema owner for each component (custom prefix and schema name). You can edit the schema owner value by clicking the item that you want to change in this column and editing the table cell directly.



Note:

You must remember the Schema Owner name for the components that you are installing; you need this information during the configuration phase of your Oracle Fusion Middleware product installation. Oracle recommends that you write this value down.

Click **Next** when you are finished specifying your prefix and schema names, and when you are finished selecting components. The screen indicating the progress of component prerequisite checks before schema creation appears.

If an error occurs during the prerequisite checking, the error messages appear in the Messages field on the Select Components screen.

Click **OK** to dismiss this screen.

Select Components (for Drop Operation)

Use the Select Components screen to select the prefix and the schemas that you want to drop.

The Select Components screen appears if you selected **Drop Repository** on the [Create Repository](#) screen.

The following table describes the elements on this screen:

Element	Description
Select schemas with prefix of	Use the drop-down list in this field to select an existing custom prefix.
Component	Select the component schemas you want to remove.
Schema Owner	This column shows the schema owner (custom prefix and schema name). For drop operations, this column cannot be edited.

 **Note:**

Unlike create operations, schema dependencies are not handled automatically by RCU for drop operations. When you remove a schema, you must also remove the schemas which depend on the schema you are removing. For example, the **Audit Services** schema is required by the **Oracle Platform Security Services** schema; if you remove the **Audit Services** schema, the **Oracle Platform Security Services** schema will no longer work.

Click **Next** when you are finished. The screen indicating the progress of component prerequisite checks appears.

If an error occurs during the prerequisite checking, the error message(s) appear in the Messages field on the Select Components screen.

Click **OK** to dismiss this screen.

Schema Passwords

Use the Schema Passwords screen to specify the passwords for your schema owners; there are three ways to specify schema passwords on this screen.

The following table describes the three ways that you can specify schema passwords:

Option	Description
Use same password for all schemas	Select this option if you want to use a single password for all schemas and their auxiliary schemas. In the Password field, enter your password. Enter your password again in the Confirm Password field.

Option	Description
Use main schema passwords for auxiliary schemas	Select this option if you want to specify different passwords for the main schemas, but still have the same password used for their respective auxiliary schemas. If you select this option, only the main schemas are visible in the table. For each schema, you must enter each schema's password in the Schema Password column in the table, and enter the same password in the Confirm Password column.
Specify different passwords for all schemas	Select this option if you want to specify unique passwords for the main schemas and auxiliary schemas. If you select this option, all main schemas and auxiliary schemas are visible in the table. For each schema and auxiliary schema, you must enter the password in the Schema Password column in the table, and enter the same password in the Confirm Password column.

 **Note:**

You must remember the passwords you enter on this screen; you need this information during the configuration phase of your product installation.

For an Autonomous Transaction Processing database (both Autonomous Transaction Processing - Dedicated and Autonomous Transaction Processing-Shared), password must be minimum 12 characters, and must contain at least one uppercase, one lower case, and one number.

Custom Variables

If you are installing a product that requires custom variables, you will see the Custom Variables screen. Use this screen to specify additional product configuration information.

The Custom Variables screen appears only if you selected one or more of the following components on the Select Components screen. You can select a component on the Select Components screen only if the Oracle home in which RCU was started contains that component.

For more information, see the online help.

Map Tablespaces

Use the Map Tablespaces screen to configure the desired tablespace mapping for the schemas that you want to create.

This screen only appears if you selected the **Create Repository** option on the [Create Repository](#) screen.

Click **Next** when you are finished with your tablespace information. The screen prompting you to confirm the creation of tablespaces for any new schemas appears.

 **Note:**

- RCU only creates tablespaces for those components associated with RCU.
- The **Encrypt Tablespace** check box appears on this screen only if Transparent Data Encryption (TDE) is enabled in the database (Oracle or Oracle EBR) when RCU is started. For more information about encrypting Tablespaces, see [Encrypting Tablespaces](#).
- When you create schemas on ATP-D database, you may receive tablespace creation error on the Map Tablespaces screen. For more information, see [Troubleshooting Tips for Schema Creation on an Autonomous Transaction Processing Database](#).
- For an Autonomous Transaction Processing-Shared database, override the default and temporary tablespaces by selecting *DATA* from the drop-down list in the **Default Tablespace** column, and *TEMP* from the drop-down list in the **Temp Tablespace** column. In case of additional tablespaces, override the tablespace name by selecting *DATA* from the drop-down list in the **Tablespace Name** column.

Click **OK** to continue. The screen indicating the progress of the tablespace creation appears.

Click **Stop** to cancel tablespace creation. When the tablespaces are created, click **OK** to dismiss this window.

See the following topics for more about the features and options on the Map Tablespaces screen:

- [Default Tablespace Mappings](#)
In the *Default Tablespace* and *Temp Tablespace* columns, you can click on the tablespace cell to select from a list of available additional tablespace names.
- [Changing Default and Temporary Tablespaces](#)
You can change the default tablespaces and the temporary tablespaces for the components.
- [Viewing and Changing Additional Tablespaces](#)
To view and change additional tablespaces associated with the selected components, click the **Additional Tablespaces** button. Only those components with additional tablespaces as defined in the configuration files appear on this screen.
- [Managing Tablespaces and Datafiles](#)
To manage your tablespaces and datafiles, click the **Manage Tablespaces** button.
- [Encrypting Tablespaces](#)
Select the **Encrypt Tablespace** check box on the Map Tablespaces screen to encrypt all the new tablespaces that are created by RCU.

Default Tablespace Mappings

In the *Default Tablespace* and *Temp Tablespace* columns, you can click on the tablespace cell to select from a list of available additional tablespace names.

The default tablespace mapping for each component are shown in [About Repository Creation Utility Schemas, IDs, and Tablespaces](#).

Changing Default and Temporary Tablespaces

You can change the default tablespaces and the temporary tablespaces for the components.

You can have your components use as many or as few tablespaces as desired to suit your configuration.

To change the default tablespace for a component, select the tablespace name in the Default Tablespace column, then select the tablespace name that you want to use from the drop-down list.

To change the temporary tablespace for a component, select the tablespace name in the Temp Tablespace column, then select the tablespace name that you want to use from the drop-down list.

 **Note:**

For an Autonomous Transaction Processing-Shared database, override the default and temporary tablespaces by selecting *DATA* from the drop-down list in the **Default Tablespace** column, and *TEMP* from the drop-down list in the **Temp Tablespace** column.

Viewing and Changing Additional Tablespaces

To view and change additional tablespaces associated with the selected components, click the **Additional Tablespaces** button. Only those components with additional tablespaces as defined in the configuration files appear on this screen.

Some components have additional tablespaces associated with their schemas. If this is the case, the **Additional Tablespaces** button appears on this screen. If none of the selected components have additional tablespaces, then this button will not appear.

To change the tablespace you want to use for a component, click in the *Tablespace Name* column and select the tablespace that you want to use from the drop-down list.

 **Note:**

For an Autonomous Transaction Processing-Shared database, override the tablespace name, and select *DATA* from the drop-down list in the **Tablespace Name** column.

Managing Tablespaces and Datafiles

To manage your tablespaces and datafiles, click the **Manage Tablespaces** button.

The following topics are covered in this section:

- [Adding, Modifying, and Removing Tablespaces](#)
Only tablespaces that are created by RCU can be modified or removed. Tablespaces that existed before RCU was launched are visible on this screen but are grayed out and cannot be modified or removed.

- [Adding, Modifying, and Removing Datafiles](#)
In the Datafiles section, specify the datafiles that make up the selected tablespace.

Adding, Modifying, and Removing Tablespaces

Only tablespaces that are created by RCU can be modified or removed. Tablespaces that existed before RCU was launched are visible on this screen but are grayed out and cannot be modified or removed.

Only tablespaces that are used by a component are created. You can specify a new tablespace here, but unless it is actually used by a component it is not created.

To modify a tablespace, select the tablespace name on the left-hand portion of the screen, and edit the fields as described in the following table:

Field	Description
Name	Edit the tablespace name in this field to change the name of your tablespace.
Type	Specify whether you want this tablespace to be a temporary tablespace or permanent tablespace.
Block Size (KB)	Specify the block size (in Kilobytes) to be used for data retrieval.
Storage Type	Select Use Bigfile Tablespace if you want to create a bigfile tablespace; this is typically used if you have single large files instead of multiple small files. Select Use Automatic Segment Space Management if you want to use bitmaps to manage the free space within segments.

To add a tablespace, click **Add** and specify the same details as above (for modifying a tablespace) for your new tablespace.

To remove a tablespace, select the tablespace name from the navigation tree, then click **Remove**. This tablespace is not created.

Adding, Modifying, and Removing Datafiles


In the Datafiles section, specify the datafiles that make up the selected tablespace.

To add a datafile, click the icon with the plus sign (+):



The Add Datafile screen appears:

Provide the information described in the following table:

Field	Description
File Name	Specify the name of the datafile.
	<div style="border: 1px solid #0070C0; padding: 10px; background-color: #E6F2FF;"> <p> Note:</p> <p>Datafile names with a dash or hyphen (-) character are not permitted.</p> </div>
File Directory	Specify the location where this datafile will reside.
Size	Specify the initial size of the datafile. Use the drop-down list to specify the size in kilobytes (KB), megabytes (MB), or gigabytes (GB).
Automatically extend datafile when full (AUTOEXTEND)	<p>Select Automatically extend datafile when full (AUTOEXTEND) to automatically extend the size of your datafile when it becomes full. In the <i>Increment</i> field, specify the size by which your datafile should be increased each time it becomes full. Use the drop-down list to specify the size in kilobytes (KB), megabytes (MB), or gigabytes (GB).</p> <p>If you want to limit maximum size of the datafile, specify this value in the <i>Maximum Size</i> field.</p>

Similarly, to modify or edit a datafile, select the icon next to the datafile name that you want to edit, then click the icon with the pencil:



To delete a datafile, select the icon next to the datafile name that you want to delete, then click the icon with the "X":



Encrypting Tablespaces

Select the **Encrypt Tablespace** check box on the Map Tablespaces screen to encrypt all the new tablespaces that are created by RCU.

When you start RCU, the **Encrypt Tablespace** check box appears on the [Map Tablespaces](#) screen only if you have TDE (Transparent Data Encryption) enabled in the database (Oracle or Oracle EBR) when you start RCU. If TDE is not enabled, this check box does not appear. If TDE is enabled in the database and you provide the `-encryptTablespace true` option, the check box is selected by default.

TDE tablespace encryption allows you to encrypt sensitive data stored in tablespaces. For more information about Transparent Data Encryption, see *Introduction to Transparent Data Encryption* in *Oracle Database Advanced Security Guide*.



Note:

When you select this option, *all new* tablespaces created by RCU are encrypted. You cannot select specific tablespaces on this screen to be encrypted. Also, tablespaces that were created before RCU was launched cannot be encrypted by using this option.

Summary (for Create Operation)

On the Summary (for Create operation) screen, verify your information, then click **Create** to begin schema creation.



Note:

When you create schemas on an Autonomous Transaction Processing database (both Autonomous Transaction Processing - Dedicated and Autonomous Transaction Processing-Shared) database, you may receive warnings in case of Oracle WebCenter Content, Oracle Internet Directory, and Oracle Enterprise Scheduler and Oracle Managed File Transfer SOA products. For more information, see [Troubleshooting Tips for Schema Creation on an Autonomous Transaction Processing Database](#).

The Summary screen appears when you select **Create Repository** on the [Create Repository](#) screen.

Click **Save Response File** to save the RCU session to a text file (called a response file). The response file collects all the information that you have provided in the RCU screens.

The values in a response file can be used exactly as-is (or modified as needed) to run RCU at a later time. If you choose to run the graphical interface, the data provided in a response file can be used to prepopulate the RCU screens. If you choose to run RCU from the command line, you can use a response file to provide values for all valid command-line parameters to RCU rather than directly specifying these parameters on the command line. For more information, see [Using Response Files](#).

When you click **Save Response File**, you see the **Save Response File** dialog box.

The following table describes the fields on this dialog box:

Element	Description
Directory to save Response file	Specify the full path of a directory. This directory is where the response file is saved. By default, RCU saves the response file in the <code>\$HOME/.rcu</code> directory. Click Browse to search for a specific directory.

Element	Description
Save Passwords in Wallet	<p>Select this option to securely store the passwords that you entered on the RCU screens in an Oracle Wallet file. For example, the schema passwords entered on the Schema Passwords screen are saved to this file.</p> <p>By default, this option is not selected. RCU does not save your passwords unless you select this option.</p> <p>You can use the wallet later in silent situations to pass the necessary passwords to RCU without having to directly enter your passwords on the command line. If a wallet is not passed to RCU in silent mode, you are prompted to enter the required passwords.</p>

Click **OK** to generate the wallet (if selected) and response file in the given location and return to the **Summary screen**.

Review the information on the Summary screen, and click **Create** to begin schema creation. When you click **Create**, the operations summarized on this page are performed.

While the schemas are being created, you will see the progress screen.

Click **Stop** to stop creating the schemas.

Summary (for Drop Operation)

On the Summary (for Drop operation) screen, verify your information, then click **Drop** to drop the schemas.

If you select **Drop Repository** on the [Create Repository](#) screen, the **Summary screen** appears.

Click **Save Response File** to save the RCU session to a text file (called a response file). The response file collects all the information that you have provided in the RCU screens.

The values in a response file can be used exactly as-is (or modified as needed) to run RCU at a later time. If you choose to run the graphical interface, the data provided in a response file can be used to prepopulate the RCU screens. If you choose to run RCU from the command line, you can use a response file to provide values for all valid command-line parameters to RCU rather than directly specifying these parameters on the command line. For more information, see [Using Response Files](#).

When you click **Save Response File**, you see the **Save Response File** dialog box.

The following table describes the fields on this dialog box:

Element	Description
Directory to save Response file	<p>Specify the full path of a directory. This directory is where the response file is saved. By default, RCU saves the response file in the <code>\$HOME/.rcu</code> directory.</p> <p>Click Browse to search for a specific directory.</p>

Element	Description
Save Passwords in Wallet	<p>Select this option to securely store the passwords that you entered on the RCU screens in an Oracle Wallet file. For example, the schema passwords entered on the Schema Passwords screen are saved to this file.</p> <p>By default, this option is not selected. RCU does not save your passwords unless you select this option.</p> <p>You can use the wallet later in silent situations to pass the necessary passwords to RCU without having to directly enter your passwords on the command line. If a wallet is not passed to RCU in silent mode, you are prompted to enter the required passwords.</p>

Click **OK** to generate the wallet (if selected) and response file in the given location and return to the **Summary** screen.

Review the information on the Summary screen, and click **Drop** to begin the operations summarized on this page.

While the schema(s) are being dropped, you will see the progress screen.

Click **Stop** if you want to cancel the operation.

Completion Summary (for Create Operation)

The Completion Summary (for Create Operation) screen contains information about the log files that were created from this RCU operation. You can click on the name of a particular log file to view the contents of that file.

If you selected **Create Repository** on the [Create Repository](#) screen, **Completion Summary** screen appears.

If there are any problems encountered during schema creation, you can troubleshoot the issue by using the log files. For more information about using log files, see [RCU Log Files](#).

If errors are encountered during a create operation, or if a create operation fails for any component, the **Cleanup for failed components** and **Drop tablespaces for failed components** check boxes that appear on this screen are selected by default.

If both options are selected, RCU performs cleanup operations and drops tablespaces for the components that failed during the create operation.

If you select **Cleanup for failed components** but choose not to select **Drop tablespaces for failed components**, the tablespaces for the failed components are retained during cleanup.

If you choose not to select the **Cleanup for failed components** check box, the cleanup of failed components and tablespaces are skipped. You can clean up the failed components at a later time by performing a drop operation for the failed components.

Review the information on this screen, then click **Close** to dismiss this screen.

Completion Summary (for Drop Operation)

The Completion Summary (for Drop operation) screen contains information about the log files that are created from this RCU operation. Note the log file names for each component that are visible in the *Logfile* column.

If you select **Drop Repository** on the [Create Repository](#) screen, **Completion Summary** screen appears.

By default, the main RCU log (*rcu.log*) and component log files are written to the *RCUdate_timestamp_random_number/logs* directory inside the temporary directory on your system.

For example:

- On UNIX operating systems:

```
/tmp/RCUdate_timestamp_random_number/logs
```

- On Windows operating systems:

```
C:\Users\user_name\AppData\Local\Temp\RCUdate_timestamp_random_number\logs
```

Click **rcu.log** to view the contents of the main RCU log in a separate window.

If there are any problems encountered during schema creation, you can troubleshoot the issue using the log files. For more information about using log files, see [Troubleshooting Repository Creation Utility](#).

Review the information on this screen, then click **Close** to dismiss this screen.

B

About Repository Creation Utility Schemas, IDs, and Tablespaces

Before you run RCU, make sure you understand the available schemas that can be created by using RCU, and also their component IDs and dependencies.

Following sections explain about the RCU schemas and its dependencies:

- [Repository Creation Utility Schemas, IDs, and Tablespaces](#)
Each schema that can be created by using RCU has a schema owner, component ID, and default tablespace mappings. You should also be aware of schema dependencies when you create or drop schemas.

Repository Creation Utility Schemas, IDs, and Tablespaces

Each schema that can be created by using RCU has a schema owner, component ID, and default tablespace mappings. You should also be aware of schema dependencies when you create or drop schemas.

[Table B-1](#) lists the schemas along with their component IDs, tablespace mappings, and dependencies.

The *Schema Owner* is the name of the schema that you see in RCU, and is also the name that you must provide in the Oracle Fusion Middleware Configuration Wizard on the JDBC Component Schema screen, prepended by the custom prefix.

The *Component ID* is the value that you must specify with the `-component` parameter when you create or drop schemas from the command line.

 **Note:**

Not all schemas are supported on all database types. For more information about supported schemas, see Repository Creation Utility Requirements in the *Oracle Fusion Middleware System Requirements and Specifications* document.

Table B-1 Schema Component IDs, Tablespace Mappings, and Dependencies

Component	Schema Owner	Component ID	Default Tablespace	Temp Tablespace	Dependencies
AS Common Schemas					
Metadata Services	MDS	MDS	MDS	IAS_TEMP	None
Audit Services	IAU	IAU	IAU	IAS_TEMP	Audit Services Append (IAU_APPEND) Audit Services Viewer (IAU_VIEWER)

Table B-1 (Cont.) Schema Component IDs, Tablespace Mappings, and Dependencies

Component	Schema Owner	Component ID	Default Tablespace	Temp Tablespace	Dependencies
Audit Services Append	IAU_APPEND	IAU_APPEND	IAU	IAS_TEMP	None
Audit Services Viewer	IAU_VIEWER	IAU_VIEWER	IAU	IAS_TEMP	None
Oracle Platform Security Services	OPSS	OPSS	IAS_OPSS	IAS_TEMP	Audit Services (IAU) Audit Services Append (IAU_APPEND) Audit Services Viewer (IAU_VIEWER)
User Messaging Service	UMS	UCSUMS	IAS_UMS	IAS_TEMP	Metadata Services (MDS)
WebLogic Services	WLS	WLS	WLS	IAS_TEMP	None
Oracle Enterprise Scheduler	ESS	ESS	ESS	IAS_TEMP	Metadata Services (MDS) Audit Services (IAU) Audit Services Append (IAU_APPEND) Audit Services Viewer (IAU_VIEWER) Oracle Platform Security Services (OPSS)
Common Infrastructure Services (formerly Service Table) ¹	STB	STB	STB	IAS_TEMP	None
Oracle Data Integrator					
Master and Work Repository	ODI_REPO	ODI	ODI_USER	ODI_TEMP	
SOA Suite					

Table B-1 (Cont.) Schema Component IDs, Tablespace Mappings, and Dependencies

Component	Schema Owner	Component ID	Default Tablespace	Temp Tablespace	Dependencies
SOA Infrastructure	SOAINFRA	SOAINFRA	SOAINFRA	IAS_TEMP	Metadata Services (MDS) Audit Services (IAU) Audit Services Append (IAU_APPEND) Audit Services Viewer (IAU_VIEWER) Oracle Platform Security Services (OPSS) User Messaging Service (UCSUMS) WebLogic Services (WLS)
Managed File Transfer					
Managed File Transfer	MFT	MFT	MFT	IAS_TEMP	Metadata Services (MDS) Audit Services (IAU) Audit Services Append (IAU_APPEND) Audit Services Viewer (IAU_VIEWER) Oracle Platform Security Services (OPSS) User Messaging Service (UCSUMS) Oracle Enterprise Scheduler (ESS)
Oracle Business Intelligence					

Table B-1 (Cont.) Schema Component IDs, Tablespace Mappings, and Dependencies

Component	Schema Owner	Component ID	Default Tablespace	Temp Tablespace	Dependencies
Business Intelligence Platform	BIPLATFORM	BIPLATFORM	BIPLATFORM	IAS_TEMP	Metadata Services (MDS) Oracle Platform Security Services (OPSS) Audit Services (IAU) Audit Services Append (IAU_APPEND) Audit Services Viewer (IAU_VIEWER) WebLogic Services (WLS)
WebCenter Portal					
Portal and Services	WEBCENTER	WEBCENTER	IAS_WEBCENTER	IAS_TEMP	Metadata Services (MDS) Oracle Platform Security Services (OPSS) Audit Services (IAU) Audit Services Append (IAU_APPEND) Audit Services Viewer (IAU_VIEWER)
Portlet Producers	PORTLET	PORTLET	IAS_PORTLET	IAS_TEMP	Oracle Platform Security Services (OPSS) Audit Services (IAU) Audit Services Append (IAU_APPEND) Audit Services Viewer (IAU_VIEWER)
WebCenter Content					
Oracle WebCenter Content Server — Search Only	OCSSEARCH	CONTENTSEARCH	OCSSEARCH	OCSSEARCH_TEMP	Common Infrastructure Services (STB) WebLogic Services (WLS)

Table B-1 (Cont.) Schema Component IDs, Tablespace Mappings, and Dependencies

Component	Schema Owner	Component ID	Default Tablespace	Temp Tablespace	Dependencies
Oracle WebCenter Content Server — Complete	OCS	CONTENT	OCS	OCS_TEMP	Common Infrastructure Services (STB) Oracle Platform Security Services (OPSS) Audit Services (IAU) Audit Services Append (IAU_APPEND) Audit Services Viewer (IAU_VIEWER) WebLogic Services (WLS)
Oracle WebCenter Enterprise Capture	CAPTURE	CAPTURE	CAPTURE	CAPTURE_TEMP	Common Infrastructure Services (STB) Metadata Services (MDS) Oracle Platform Security Services (OPSS) Audit Services (IAU) Audit Services Append (IAU_APPEND) Audit Services Viewer (IAU_VIEWER) WebLogic Services (WLS)
WebCenter Sites					
WebCenter Sites	WCSITES	WCSITES	TS_WCSITES	TS_TMP_WCSITES	Oracle Platform Security Services (OPSS) Audit Services (IAU) Audit Services Append (IAU_APPEND) Audit Services Viewer (IAU_VIEWER)

Table B-1 (Cont.) Schema Component IDs, Tablespace Mappings, and Dependencies

Component	Schema Owner	Component ID	Default Tablespace	Temp Tablespace	Dependencies
WebCenter Sites — Visitor Services	WCSITES_VS	WCSITESVS	TS_WCSITES_VS	TS_TMP_WCSITES_VS	Oracle Platform Security Services (OPSS) Audit Services (IAU) Audit Services Append (IAU_APPEND) Audit Services Viewer (IAU_VIEWER)
Oracle Enterprise Data Quality (EDQ)					
EDQ Config Repository	EDQCONFIG	EDQ_CONF	EDQ_CONF	EDQ_CONFTEMP	Oracle Platform Security Services (OPSS) Audit Services (IAU) Audit Services Append (IAU_APPEND) Audit Services Viewer (IAU_VIEWER)
EDQ Results Repository	EDQRESULTS	EDQ_RES	EDQ_RES	EDQ_RESTEMP	Oracle Platform Security Services (OPSS) Audit Services (IAU) Audit Services Append (IAU_APPEND) Audit Services Viewer (IAU_VIEWER) EDQ Config Repository (EDQ_CONF)

Table B-1 (Cont.) Schema Component IDs, Tablespace Mappings, and Dependencies

Component	Schema Owner	Component ID	Default Tablespace	Temp Tablespace	Dependencies
EDQ Staging Repository	EDQSTAGING	EDQ_STAGING	EDQ_STAGING	EDQ_STAGING TEMP	Oracle Platform Security Services (OPSS) Audit Services (IAU) Audit Services Append (IAU_APPEND) Audit Services Viewer (IAU_VIEWER) EDQ Config Repository (EDQ_CONF) EDQ Results Repository (EDQ_RES)
Oracle Access Manager (OAM)					
Oracle Access Manager	OAM	OAM	OAM	OAM_TEMP	Common Infrastructure Services (STB) Metadata Services (MDS) Oracle Platform Security Services (OPSS) Audit Services (IAU) Audit Services Append (IAU_APPEND) Audit Services Viewer (IAU_VIEWER) WebLogic Services (WLS)

¹ For more information about the Service Table schema, see [About the Service Table Schema](#).

As an example, [Table B-2](#) provides the schema details for Oracle HTTP Server configuration.

Table B-2 Schemas for Oracle HTTP Server Configured in WebLogic Server Domain

Component Schema	Schema Owner
LocalSvcTbl Schema	STB
WLS Schema	WLS_RUNTIME
OPSS Audit Schema	IAU_APPEND

Table B-2 (Cont.) Schemas for Oracle HTTP Server Configured in WebLogic Server Domain

Component Schema	Schema Owner
OPSS Audit Viewer Schema	IAU_VIEWER
OPSS Schema	OPSS

C

Extending Repository Creation Utility to Configure Custom Application Repositories

You can use configuration XML files to generate custom schema creation and deletion scripts. RCU provides an XML-based framework for component owners to plug in your schema creation and deletion scripts into RCU. The following topics provide some details of the configuration XML files and script-writing guidelines that are used to integrate your components with RCU:

- [RCU Integration Options](#)
RCU provides several options for integrating component scripts.
- [RCU Configuration Files](#)
RCU provides several configuration file types for component integration.
- [RCU Script Writing Guidelines](#)
Use these guidelines when writing RCU scripts.

RCU Integration Options

RCU provides several options for integrating component scripts.

RCU JDBC Engine Compliant SQL*Plus Scripts is the recommended option for integrating component scripts. Components that have a dependency on SQL*Plus scripts cannot be loaded with RCU when running from the installed Oracle home.

- [RCU JDBC Engine Compliant SQL*Plus Scripts](#)
The RCU JDBC Engine emulates a set of SQL*Plus features over JDBC. This set is broad enough to cover the requirements of schema creation.
- [Pure JDBC Scripts](#)
This option is recommended for non-Oracle databases (for Oracle databases, RCU JDBC Engine Compliant SQL*Plus scripts should be used).
- [SQL*Plus Scripts](#)
This option is mainly for the consumption of legacy components that need to be loaded from RCU.
- [External Processes](#)
This option is provided only for those components that have their own configuration tool for schema creation, like OPCA (Oracle Portal 10g).
- [Java Code Using JavaAction](#)
This option is provided to components that have Java code, which can accept a JDBC connection and execute SQL statements.

RCU JDBC Engine Compliant SQL*Plus Scripts

The RCU JDBC Engine emulates a set of SQL*Plus features over JDBC. This set is broad enough to cover the requirements of schema creation.

Your component teams can integrate existing SQL*Plus scripts with a few minor changes.

The RCU JDBC Engine parses the SQL*Plus script to get individual statements and then runs each statement over JDBC. Command-line arguments to scripts and substitution using DEFINE variables are supported. Script can be nested, for example, one script can call other scripts. Component teams can specify a list of expected errors and fatal errors to RCU through configuration files and RCU would interpret these when running the scripts.

These scripts are easy to maintain and use as they can be run in SQL*Plus in a development environment. However, Oracle recommends that you also use the *RCU JDBC Engine* tool in your development environment to ensure that these scripts run properly when integrated with RCU.

Pure JDBC Scripts

This option is recommended for non-Oracle databases (for Oracle databases, RCU JDBC Engine Compliant SQL*Plus scripts should be used).

Contents of the script file should be a valid PL/SQL block, which can be called with `Connection.prepareCall()` or `Connection.createStatement()`. Standard JDBC Bind variables with '?' convention are supported.

Some disadvantages of this option are:

- No nested scripts, which can mean a larger number of scripts.
- May require significant rework for component teams to rewrite the scripts in this format.
- Difficult to maintain as every DDL statement has to be wrapped with in *EXECUTE IMMEDIATE*.
- Cannot be run by using SQL*Plus in a development environment.
- Less useful error support since the whole block would fail in case of any errors.

Below is an example:

```
<Action TYPE="JDBC" PERCENT_PROGRESS="20">
  <ValidIf DBTYPE="ORACLE" />
  <Command TYPE="INLINE">DROP USER %SCHEMA_USER% CASCADE</Command>
</Action>
```

And a second example:

```
<Action TYPE="Java" PERCENT_PROGRESS="100">
  <Command TYPE="METHOD">
    oracle.ias.version.SchemaVersionUtil:utilSetComponentValid
  </Command>

  <Parameters>
    <Parameter TYPE="String">MDS</Parameter>
  </Parameters>
</Action>
```

SQL*Plus Scripts

This option is mainly for the consumption of legacy components that need to be loaded from RCU.

Example:

```
<Action TYPE="SQLPlus" PERCENT_PROGRESS="100">
  <Command TYPE="SCRIPT">%SCRIPT_HOME%/oid/scripts/seedldap.sql</Command>
  <IgnorableErrors>
```

```

        <Error Type="ORA-01918">user name does not exist</Error>
    </IgnorableErrors>
</Action>

```

And a second example:

```

<Action TYPE="JDBCScript" PERCENT_PROGRESS="20">
    <ValidIf DBTYPE="ORACLE" />
    <Command TYPE="SCRIPT">%SCRIPT_HOME%/mds/sql/mds_user.sql</Command>
    <Parameters>
        <Parameter TYPE="CmdLine">%SCHEMA_USER%</Parameter>
        <Parameter TYPE="CmdLine">%SCHEMA_PASSWORD%</Parameter>
        <Parameter TYPE="CmdLine">%DEFAULT_TABLESPACE%</Parameter>
        <Parameter TYPE="CmdLine">%TEMPORARY_TABLESPACE%</Parameter>
    </Parameters>
</Action>

```

External Processes

This option is provided only for those components that have their own configuration tool for schema creation, like OPCA (Oracle Portal 10g).

This is not a recommended option for any new component, as this option cannot make use of the RCU error handling framework.

Example:

```

<Action TYPE="HostCmd">
<Command TYPE="SCRIPT">%RCU_HOME%/rcu/integration/cdb/config/bin/configure</Command>
<Parameters>
    <Parameter TYPE="ProcessInput">%JDBC_CONNECT_STRING%</Parameter>
    <Parameter TYPE="ProcessInput">%DBADMIN_USER%</Parameter>
    <Parameter TYPE="ProcessInput">%DBADMIN_PASSWORD%</Parameter>
    <Parameter TYPE="ProcessInput">%PREFIX_NAME%</Parameter>
    <Parameter TYPE="ProcessInput">%SCHEMA_USER%</Parameter>
    <Parameter TYPE="ProcessInput">%SCHEMA_PASSWORD%</Parameter>
    <Parameter TYPE="ProcessInput">%DEFAULT_TABLESPACE%</Parameter>
    <Parameter TYPE="ProcessInput">%TEMPORARY_TABLESPACE%</Parameter>
</Parameters>
</Action>

```

Java Code Using JavaAction

This option is provided to components that have Java code, which can accept a JDBC connection and execute SQL statements.

This is generally used when huge amounts of data has to be seeded or Large Objects (LOBs) need to be created.

Example:

```

<Action TYPE="Java">
    <Command TYPE="METHOD">
        oracle.ias.version.SchemaVersionUtil:utilCreateRegistryEntry
    </Command>

    <Parameters>
        <Parameter TYPE="Connection"></Parameter>
        <Parameter TYPE="String">%SCHEMA_USER%</Parameter>
    </Parameters>
</Action>

```

A second example:

```
<Action TYPE="Java">
  <Command TYPE="METHOD">oracle.webdb.config.PortalConfigAssistant:main</Command>
  <Parameters>
    <Parameter TYPE="StringArray">-mode PORTAL -s %SCHEMA_USER% -p %DBADMIN_PASSWORD% -
c %DB_HOSTNAME%:%DB_PORTNUMBER%:%DB_SERVICE% -silent -verbose -owa -u
%DEFAULT_TABLESPACE% -t %TEMPORARY_TABLESPACE% -d %SCHEMA_USER%_DOC -l %SCHEMA_USER%_LOG
-in %SCHEMA_USER%_IDX -demo -report -voh %RCU_HOME% -log %RCU_LOG_LOCATION% -oh
%SQLPLUS_HOME% -mrc %PREFIX_NAME% -rcu </Parameter>
  </Parameters>
</Action>
```

RCU Configuration Files

RCU provides several configuration file types for component integration.

The following are the configuration files defined by RCU:

- [XML DTDs Defined by RCU](#)
These are the XML DTDs defined by RCU; they are located in the `ORACLE_HOME/oracle_common/rcu/config` directory.
- [Component Repository Configuration File](#)
A Component Repository Configuration File (`component.xml`) lists the prerequisites and the list of scripts or actions that need to be performed to load or drop a schema.
- [Soft-Prerequisite Support](#)
If a particular `<DBPrerequisiteSet>` or `<DBPrerequisite>` is not mandatory, then you can use the soft-prerequisite option by setting the `SOFT` attribute to `TRUE` in the `ComponentInfo.xml` file
- [Default Tablespaces Configuration File](#)
The default tablespaces configuration file (`Storage.xml`) lists the components, for which, tablespaces are created out-of-the-box. This file is located in the `ORACLE_HOME/oracle_common/rcu/config` directory on UNIX operating systems.

XML DTDs Defined by RCU

These are the XML DTDs defined by RCU; they are located in the `ORACLE_HOME/oracle_common/rcu/config` directory.

Following are the configuration files:

- [Component Descriptor Configuration File](#)
The Component Descriptor configuration file is called `ComponentInfo.dtd` and is located in the `ORACLE_HOME/oracle_common/rcu/config` directory on UNIX operating systems or in the `ORACLE_HOME\oracle_common\rcu\config` directory on Windows operating systems.
- [Repository Configuration File](#)
The Repository configuration file is called `RepositoryConfig.dtd` and is located in the `ORACLE_HOME/oracle_common/rcu/config` directory on UNIX operating systems directory or in the `ORACLE_HOME\oracle_common\rcu\config` directory on Windows operating systems.
- [Primary List of Supported Components](#)
RCU maintains a primary list of supported components, which contains entries for each supported component. Every time a new component is added, the primary list of supported

components is updated with the reference of the XML integration file, which is provided by component owner.

- [Storage Attributes Configuration File](#)
RCU maintains the list of tablespaces or datafiles and their attributes that needs to be created. This way the tablespaces and datafiles attributes can be modified externally.

Component Descriptor Configuration File

The Component Descriptor configuration file is called `ComponentInfo.dtd` and is located in the `ORACLE_HOME/oracle_common/rcu/config` directory on UNIX operating systems or in the `ORACLE_HOME\oracle_common\rcu\config` directory on Windows operating systems.

Each component owner would provides a configuration file that adheres to the following DTD, which lists the prerequisites and actions:

```
<?xml version="1.0" encoding="UTF-8" ?>
<!ENTITY % commonDTD SYSTEM "RCUCommon.dtd">
%commonDTD;
<!ELEMENT ComponentInfo (Display?, PrefixSettings?, Component*, ComponentConfigFiles?,
PrerequisiteDescriptor*,
ExecutionDescriptor*, FatalErrors?, IgnorableErrors?)>
<!ATTLIST ComponentInfo
    VERSION CDATA #IMPLIED
    TYPE CDATA #IMPLIED
    RESOURCE_BUNDLE_PACKAGE CDATA #IMPLIED>
<!ELEMENT PrefixSettings (DetectQuery*)>
<!ATTLIST PrefixSettings
    USE_SCHEMA_PREFIX (TRUE|FALSE) "TRUE"
    USE_TABLESPACE_PREFIX (TRUE|FALSE) "TRUE">
<!ELEMENT ComponentConfigFiles (ConfigFile*)>
<!ATTLIST ConfigFile
    ID CDATA #REQUIRED>
<!ELEMENT ConfigFile (#PCDATA)>
<!ELEMENT Component (ValidIfSet?, ValidIf?, Display,Consolidate*,SchemaBase*,
RepositoryConfigFile?, DetectQuery*, SchemaVersion?,
SchemaUser?, AdditionalSchemaUser*, Dependents?, DatabaseName?, Tablespaces?,
CustomVariables?)>
<!ATTLIST Component
    ID CDATA #REQUIRED
    PROGRESS_UNITS CDATA #IMPLIED
    IS_GROUPING_COMPONENT (TRUE|FALSE) "FALSE"
    DEFAULT_SELECTED (TRUE|FALSE) "FALSE"
    CHILD_OF CDATA #IMPLIED
    MANDATORY_SELECTED (TRUE|FALSE) "FALSE">
<!ELEMENT Display (#PCDATA)>
<!ATTLIST Display
    NLS_ID CDATA #IMPLIED>
<!ELEMENT Consolidate EMPTY>
<!ATTLIST Consolidate
    VALID (TRUE|FALSE) "FALSE"
    DYNAMIC_OBJECTS (TRUE|FALSE) "FALSE">
<!ELEMENT SchemaBase (#PCDATA) >
<!ATTLIST SchemaBase
    PARENT (TRUE|FALSE) "FALSE"
    TBS_OVERRIDE (TRUE|FALSE) "FALSE"
    TBS_OVERRIDE_USE_CUSTOM (TRUE|FALSE) "FALSE"
    COMPONENT_DROP (TRUE|FALSE) "FALSE">
<!ELEMENT RepositoryConfigFile (#PCDATA)>
<!ELEMENT DetectQuery (#PCDATA)>
<!ATTLIST DetectQuery
```

```

        OPERATION (CREATE|DROP|DATALOAD) 'CREATE'
        TYPE (ORACLE|SQLSERVER|IBMDB2|EBR|MYSQL|JAVADB) 'ORACLE'>
<!ELEMENT SchemaVersion (#PCDATA)>
<!ELEMENT SchemaUser (#PCDATA)>
<!ATTLIST SchemaUser
        USER_EDITABLE (TRUE|FALSE) "TRUE"
        PREFIXABLE (TRUE|FALSE) "TRUE"
        IS_CREATED (TRUE|FALSE) "TRUE"
        MAX_LENGTH CDATA "30">
<!ELEMENT AdditionalSchemaUser (#PCDATA)>
<!ATTLIST AdditionalSchemaUser
        STARTS_WITH_SCHEMA_USER (TRUE|FALSE) "TRUE"
        COMPONENT_ID CDATA #IMPLIED>
<!ELEMENT Dependents (Dependent*)>
<!ELEMENT Dependent (#PCDATA)>
<!ATTLIST Dependent
        COMPONENT_ID CDATA #REQUIRED
        ALT_COMPONENT_ID CDATA #IMPLIED>
<!ELEMENT DatabaseName (#PCDATA)>
<!ELEMENT Tablespaces (Tablespace*)>
<!ATTLIST Tablespace TYPE (DEFAULT_TABLESPACE|TEMPORARY_TABLESPACE|
ADDITIONAL_TABLESPACE1|ADDITIONAL_TABLESPACE2|ADDITIONAL_TABLESPACE3|
ADDITIONAL_TABLESPACE4|ADDITIONAL_TABLESPACE5|ADDITIONAL_TABLESPACE6|
ADDITIONAL_TABLESPACE7|ADDITIONAL_TABLESPACE8|ADDITIONAL_TABLESPACE9|
ADDITIONAL_TABLESPACE10|ADDITIONAL_TABLESPACE11|ADDITIONAL_TABLESPACE12|
ADDITIONAL_TABLESPACE13|ADDITIONAL_TABLESPACE14|ADDITIONAL_TABLESPACE15|
ADDITIONAL_TABLESPACE16|ADDITIONAL_TABLESPACE17|ADDITIONAL_TABLESPACE18|
ADDITIONAL_TABLESPACE19|ADDITIONAL_TABLESPACE20|ADDITIONAL_TABLESPACE21|
ADDITIONAL_TABLESPACE22|ADDITIONAL_TABLESPACE23|ADDITIONAL_TABLESPACE24|
ADDITIONAL_TABLESPACE25|ADDITIONAL_TABLESPACE26|ADDITIONAL_TABLESPACE27|
ADDITIONAL_TABLESPACE28|ADDITIONAL_TABLESPACE29|ADDITIONAL_TABLESPACE30|
ADDITIONAL_TABLESPACE31) "DEFAULT_TABLESPACE">
<!ELEMENT Tablespace (Prompt, TablespaceName)>
<!ELEMENT Prompt (#PCDATA)>
<!ATTLIST Prompt NLS_ID CDATA #IMPLIED>
<!ELEMENT TablespaceName (#PCDATA)>
<!ELEMENT CustomVariables (Variable*, ValidationDescriptor*)>
<!ATTLIST Variable
        TYPE (STRING|NUMBER|PASSWORD|EXISTING_PASSWORD|FILE|LIST) "STRING"
        MAX_LENGTH CDATA "30"
        MIN_LENGTH CDATA "0"
        MAX_VALUE CDATA #IMPLIED
        MIN_VALUE CDATA #IMPLIED
        OPERATION (CREATE|DROP|SYSTEM_LOAD|DATA_LOAD|BOTH) "BOTH"
        DEFAULT_VALUE CDATA ""
        PROMPT_ON_DEFAULT_VALUE (YES|NO) "YES"
        VALUES CDATA "">
<!ELEMENT Variable (Name,Display)>
<!ELEMENT ValidationDescriptor (Action*)>
<!ATTLIST ValidationDescriptor
        OPERATION (CREATE|DROP|SYSTEM_LOAD|DATA_LOAD|BOTH) "BOTH">
<!ELEMENT Name (#PCDATA)>

```

Repository Configuration File

The Repository configuration file is called `RepositoryConfig.dtd` and is located in the `ORACLE_HOME/oracle_common/rcu/config` directory on UNIX operating systems directory or in the `ORACLE_HOME\oracle_common\rcu\config` directory on Windows operating systems.

```

<?xml version="1.0" encoding="UTF-8" ?>
<!ENTITY % commonDTD SYSTEM "RCUCommon.dtd">

```

```
%commonDTD;
<!ELEMENT RepositoryConfig (PrerequisiteDescriptor*, ExecutionDescriptor,
DeleteDescriptor?)>
<!ATTLIST RepositoryConfig
      COMP_ID CDATA #REQUIRED>
<!ELEMENT DeleteDescriptor (Action*)>
```

Primary List of Supported Components

RCU maintains a primary list of supported components, which contains entries for each supported component. Every time a new component is added, the primary list of supported components is updated with the reference of the XML integration file, which is provided by component owner.

This configuration file is called `RCUCommon.dtd` and is located in the `ORACLE_HOME/oracle_common/rcu/config` directory on UNIX operating systems or in the `ORACLE_HOME\oracle_common\rcu\config` directory on Windows operating systems:

```
<?xml version="1.0" encoding="UTF-8" ?>
<!ELEMENT PrerequisiteDescriptor (DBPrerequisiteSet*, DBPrerequisite*)>
<!ATTLIST PrerequisiteDescriptor
      TYPE (CREATE|DROP|REGISTER|DEREGISTER|SYSTEMLOAD|DATALOAD) 'CREATE'>
<!ELEMENT DBPrerequisiteSet (ValidIfSet?, ValidIf?, PrereqSetErrorMsg?, DBPrerequisite*)>
<!ATTLIST DBPrerequisiteSet
      OPERATOR (OR|AND) "OR"
      SOFT (TRUE|FALSE) "FALSE">
<!ELEMENT DBPrerequisite (ValidIfSet?, ValidIf?, PrereqIdentifier, PrereqValue,
PrereqErrorMsg?)>
<!ATTLIST DBPrerequisite
PREREQ_TYPE (InitParameter|DBOption|Java|DBComponent|DBVersion|DBObject|CustomSQL|
TablespaceFreeMB) "CustomSQL"
      DATA_TYPE (STRING|NUMBER|VERSION) "STRING"
      COMPARE_OPERATOR (EQ|GT|LT|NE|GE|LE|COMPARE_VERSION) "EQ"
      SOFT (TRUE|FALSE) "FALSE">

<!ELEMENT PrereqIdentifier (#PCDATA)>
<!ELEMENT PrereqValue (#PCDATA)>
<!ELEMENT PrereqSetErrorMsg (#PCDATA)>
<!ATTLIST PrereqSetErrorMsg
      NLS_ID CDATA #IMPLIED>
<!ELEMENT PrereqErrorMsg (#PCDATA)>
<!ATTLIST PrereqErrorMsg
      NLS_ID CDATA #IMPLIED>
<!ATTLIST PrereqValue
      UNIT (KB|MB|NoUnit) 'NoUnit'>
<!ELEMENT ExecutionDescriptor (Action*)>
<!ATTLIST ExecutionDescriptor
      TYPE (Load|PreLoad|PostLoad|DataLoad|PostDataLoad) "Load">
<!ELEMENT Action (ValidIfSet?, ValidIf?, Command, Parameters?, FatalErrors?,
IgnorableErrors?)>
<!ATTLIST Action
      TYPE (JDBCScript|JDBC|SQLPlus|HostCmd|Java) "JDBCScript"
      DB_VERSION CDATA #IMPLIED
      PERCENT_PROGRESS CDATA #IMPLIED
      CONNECT_AS_OWNER (TRUE|FALSE) "FALSE"
      CONNECT_AS_REGISTRYOWNER (TRUE|FALSE) "FALSE"
      RESET_SESSION (TRUE|FALSE) "FALSE">
<!ELEMENT Command (#PCDATA)>
<!ATTLIST Command
      TYPE (SCRIPT|INLINE|METHOD) "SCRIPT">
<!ELEMENT Parameters (Parameter*)>
```

```

<!ELEMENT Parameter (#PCDATA)>
<!ATTLIST Parameter
    TYPE (BindVar|CmdLine|ProcessInput|EnvVar|Connection|int|String|StringArray|
boolean) "CmdLine">
<!ELEMENT FatalErrors (Error*)>
<!ELEMENT IgnorableErrors (Error*)>
<!ELEMENT Error (#PCDATA)>
<!ATTLIST Error
    Type CDATA #REQUIRED>
<!ELEMENT ValidIfSet (ValidIf*)>
<!ATTLIST ValidIfSet
    DBTYPE CDATA #IMPLIED
    DBVERSION CDATA #IMPLIED
    OSNAME CDATA #IMPLIED
    OPERATION_TYPE CDATA "ALL"
    OPERATOR (OR|AND) "OR">
<!ELEMENT ValidIf (CustomQueryFilter?)>
<!ATTLIST ValidIf
    DBTYPE CDATA #IMPLIED
    DBVERSION CDATA #IMPLIED
    OSNAME CDATA #IMPLIED
    OPERATION_TYPE CDATA "ALL">
<!ELEMENT CustomQueryFilter (#PCDATA)>
<!ATTLIST CustomQueryFilter
    DATA_TYPE (STRING|NUMBER) "STRING"
    COMPARE_OPERATOR (EQ|GT|LT|NE|GE|LE|COMPARE_VERSION) "EQ"
    VALUE CDATA #REQUIRED >

```

Storage Attributes Configuration File

RCU maintains the list of tablespaces or datafiles and their attributes that needs to be created. This way the tablespaces and datafiles attributes can be modified externally.

The Storage Attributes configuration file is called `Storage.dtd` and is located in the `ORACLE_HOME/oracle_common/rcu/config` directory on UNIX operating systems) or in the `ORACLE_HOME\oracle_common\rcu\config` directory on Windows operating systems.

```

<?xml version="1.0" encoding="UTF-8" ?>
<!ELEMENT StorageAttributes ( ComponentStorageFiles?, TablespaceAttributes*)>
<!ELEMENT ComponentStorageFiles (StorageFile*)>
<!ATTLIST StorageFile
    ID CDATA #REQUIRED>
<!ELEMENT StorageFile (#PCDATA)>
<!ELEMENT TablespaceAttributes (ValidIfSet?,
ValidIf?,Type?,DefaultTemp?,BlockSize?,ExtentSize?,PageSize?,AutoResize?,IncreaseSize?,Ma
xSize?,Bigfile?,AutoSegmentSpaceManagement?, DatafilesList)>
<!ATTLIST TablespaceAttributes
    NAME CDATA #REQUIRED
    OMF (TRUE|FALSE) "FALSE">
<!ELEMENT ValidIfSet (ValidIf*)>
<!ATTLIST ValidIfSet
    DBTYPE CDATA #IMPLIED
    DBVERSION CDATA #IMPLIED
    OSNAME CDATA #IMPLIED
    OPERATOR (OR|AND) "OR">
<!ELEMENT ValidIf (CustomQueryFilter?)>
<!ATTLIST ValidIf
    DBTYPE CDATA #IMPLIED
    DBVERSION CDATA #IMPLIED
    OSNAME CDATA #IMPLIED >
<!ELEMENT Type (#PCDATA)>

```

```

<!ELEMENT DefaultTemp (#PCDATA)>
<!ELEMENT BlockSize (#PCDATA)>
<!ELEMENT ExtentSize (#PCDATA)>
<!ELEMENT PageSize (#PCDATA)>
<!ATTLIST PageSize
    UNIT (KB|NoUnit) 'KB'>
<!ELEMENT AutoResize (#PCDATA)>
<!ELEMENT IncreaseSize (#PCDATA)>
<!ATTLIST IncreaseSize
    UNIT (KB|MB|GB) 'MB'>
<!ELEMENT MaxSize (#PCDATA)>
<!ATTLIST MaxSize
    UNIT (KB|MB|GB) 'MB'>
<!ELEMENT Bigfile (#PCDATA)>
<!ELEMENT AutoSegmentSpaceManagement (#PCDATA)>
<!ELEMENT DatafilesList (DatafileAttributes+)>
<!ELEMENT DatafileAttributes (Size, Reuse?, AutoExtend?, Increment?, Maxsize?)>
<!ATTLIST DatafileAttributes
    ID CDATA #REQUIRED>
<!ELEMENT Size (#PCDATA)>
<!ATTLIST Size
    UNIT (KB|MB|GB) 'MB'>
<!ELEMENT Reuse (#PCDATA)>
<!ELEMENT AutoExtend (#PCDATA)>
<!ELEMENT Increment (#PCDATA)>
<!ATTLIST Increment
    UNIT (KB|MB|GB) 'KB'>
<!ELEMENT Maxsize (#PCDATA)>
<!ATTLIST Maxsize
    UNIT (KB|MB|GB) 'MB'>

```

Table C-1 RCU XML Configuration File Details

Element	Attribute	Description	Supported Values
TablespaceAttributes	Name	Indicates the name of the tablespace	—
Type	—	Indicates the type of the tablespace, default or temporary	<ul style="list-style-type: none"> • Temporary • Permanent
Bigfile	—	Indicates whether the tablespace is a bigfile tablespace based on the value	<ul style="list-style-type: none"> • True • False
DatafilesList	—	Groups the datafile information	—
DatafileAttributes: Size	ID	Indicates the size of tablespace	Integer value
	For example, <DatafileAttributes ID="%DATAFILE_LOCA TION%/mfs.dbf"> <Size UNIT="MB" 100 </Size>		
DatafileAttributes: Reuse	—	Allows to reuse an existing file	<ul style="list-style-type: none"> • True • False
DatafileAttributes: AutoExtend	—	Allows to enable or disable the automatic extension of a new datafile or tempfile based on value	<ul style="list-style-type: none"> • True • False
DatafileAttributes: Increment	—	Indicates the size of the next extent to be allocated to the object in bytes	Integer value
DatafileAttributes: Maxsize	—	Indicates maximum size of segments	Value is -1, if maxsize is unlimited, else specify required value

Table C-1 (Cont.) RCU XML Configuration File Details

Element	Attribute	Description	Supported Values
—	UNIT	Indicates the unit of the tablespace size	KB/MB/GB Default value is MB.
AutoSegmentSpaceManagement		Indicates dictionary managed tablespace or local managed tablespace based on value	<ul style="list-style-type: none"> • True • False 'True' indicates dictionary managed tablespace and 'False' indicates local managed tablespace.

For more information about database tablespaces, see `DBA_TABLESPACES` in *Oracle® Database Reference guide*.

Component Repository Configuration File

A Component Repository Configuration File (`component.xml`) lists the prerequisites and the list of scripts or actions that need to be performed to load or drop a schema.

This file is provided and maintained by component owners.

Each `component.xml` file can be found in the `ORACLE_HOME/oracle_common/common/sql/component/component.xml` directory on UNIX operating systems.

Component owners can use a set of predefined RCU parameters, which are substituted at runtime by RCU based on user input. Here is the list of predefined parameters:

Table C-2 Predefined RCU Parameters

RCU Parameter	Description
<code>%ORACLE_HOME%</code>	Location of the Oracle home directory.
<code>%SCRIPT_HOME%</code>	Location where scripts are located. It may be same as <code>ORACLE_HOME</code> .
<code>%SCHEMA_USER%</code>	Database schema name (owner) entered by the user in RCU.
<code>%SCHEMA_PASSWORD%</code>	Database schema password entered by the user in RCU.
<code>%ADDITIONAL_SCHEMA_USER%</code>	Additional schema users as defined in the <code>ComponentInfo.xml</code> file
<code>%ADDITIONAL_SCHEMA_PASSWORD<n>%</code>	Password for the additional schema users.
<code>%DEFAULT_TABLESPACE%</code>	Default tablespace assigned to the component by the user.
<code>%TEMPORARY_TABLESPACE%</code>	Temporary tablespace assigned to the component by the user.
<code>%ADDITIONAL_TABLESPACE<n>%</code>	Additional tablespace assigned to the component by the user. Up to three additional tablespaces are supported.
<code>%DEFAULT_PERMANENT_TABLESPACE%</code>	Default permanent tablespace in the database (for example, <code>USERS</code> or <code>SYSTEM</code>) is none is set.
<code>%DEFAULT_TEMP_TABLESPACE%</code>	Default temporary tablespace in the database (for example, <code>TEMP</code> in Oracle shipped databases or <code>SYSTEM</code>) if none is set.
<code>%DATAFILE_LOCATION%</code>	Default location where the tablespace/datafile will be created.
<code>%JDBC_CONNECT_STRING%</code>	JDBC connect string.
<code>%PREFIX_NAME%</code>	User-specified prefix for schema and tablespace names.

Table C-2 (Cont.) Predefined RCU Parameters

RCU Parameter	Description
%CONNECTION%	Already-connected <code>java.sql.Connection</code> object to be passed into <code>JavaAction</code> .
%DBADMIN_USER%	Database admin user that is provided on the Database Connection Details .
%DBADMIN_PASSWORD%	Database admin user password that is provided on the Database Connection Details .
%DBADMIN_ROLE%	Database admin user role that is provided on the Database Connection Details .
%DB_HOSTNAME%	Database hostname that is provided on the Database Connection Details .
%DB_SERVICE%	Database service name.
%DB_PORTNUMBER%	Database port number that is provided on the Database Connection Details .
%RCU_HOME%	Directory where RCU is installed.
%SQLPLUS_HOME%	<code>ORACLE_HOME</code> where SQL*Plus is located.
%RCU_LOG_LOCATION%	Location of the directory where RCU log files are created.
%DATABASE_NAME%	Database name (for SQLServer database).

Below is a sample Component Repository Configuration file for OPSS (`opss.xml`), which lists the series of prerequisites and actions:

```
<?xml version="1.0" encoding="UTF-8" ?>

<!DOCTYPE RepositoryConfig SYSTEM "RepositoryConfig.dtd">
<RepositoryConfig COMP_ID="OPSS">

  <!-- Prerequisites for OPSS -->
  <PrerequisiteDescriptor>
    <!-- ORACLE Prerequisites -->
    <DBPrerequisite PREREQ_TYPE="TablespaceFreeMB" DATA_TYPE="NUMBER"
      COMPARE_OPERATOR="GT">
      <ValidIf DBTYPE="ORACLE" />
      <PrereqIdentifier>%DEFAULT_TABLESPACE%</PrereqIdentifier>
      <PrereqValue>50</PrereqValue>
    </DBPrerequisite>
    <DBPrerequisite PREREQ_TYPE="TablespaceFreeMB" DATA_TYPE="NUMBER"
      COMPARE_OPERATOR="GT">
      <ValidIf DBTYPE="ORACLE" />
      <PrereqIdentifier>%TEMPORARY_TABLESPACE%</PrereqIdentifier>
      <PrereqValue>50</PrereqValue>
    </DBPrerequisite>

    <!-- ORACLE EBR Prerequisites -->
    <DBPrerequisite PREREQ_TYPE="TablespaceFreeMB" DATA_TYPE="NUMBER"
      COMPARE_OPERATOR="GT">
      <ValidIf DBTYPE="EBR" />
      <PrereqIdentifier>%DEFAULT_TABLESPACE%</PrereqIdentifier>
      <PrereqValue>50</PrereqValue>
    </DBPrerequisite>
    <DBPrerequisite PREREQ_TYPE="TablespaceFreeMB" DATA_TYPE="NUMBER"
      COMPARE_OPERATOR="GT">
      <ValidIf DBTYPE="EBR" />
      <PrereqIdentifier>%TEMPORARY_TABLESPACE%</PrereqIdentifier>
      <PrereqValue>50</PrereqValue>
    </DBPrerequisite>
  </PrerequisiteDescriptor>
</RepositoryConfig>
```

```

        </DBPrerequisite>

    <!-- SQLServer Prerequisites -->

    <!-- DB2 Prerequisites -->

</PrerequisiteDescriptor>

<PrerequisiteDescriptor TYPE="DROP">
    <!-- ORACLE Prerequisites -->
    <DBPrerequisite PREREQ_TYPE="CustomSQL" DATA_TYPE="NUMBER"
        COMPARE_OPERATOR="EQ">
        <ValidIf DBTYPE="ORACLE" />
        <PrereqIdentifier>
            select count(*) from v$session where username='%SCHEMA_USER%'
        </PrereqIdentifier>
        <PrereqValue>0</PrereqValue>
        <PrereqErrorMsg>
            The schema owner %SCHEMA_USER% is connected to the
            database. Please disconnect and try again.
        </PrereqErrorMsg>
    </DBPrerequisite>

    <!-- ORACLE EBR Prerequisites -->
    <DBPrerequisite PREREQ_TYPE="CustomSQL" DATA_TYPE="NUMBER" COMPARE_OPERATOR="EQ">
        <ValidIf DBTYPE="EBR" />
        <PrereqIdentifier>select count(*) from v$session where
username='%SCHEMA_USER%'</PrereqIdentifier>
        <PrereqValue>0</PrereqValue>
        <PrereqErrorMsg NLS_ID="WC_USER_CONNECTED">The schema owner
%SCHEMA_USER% is connected to the database. Please disconnect and try again.</
PrereqErrorMsg>
    </DBPrerequisite>

    <!-- SQLServer Prerequisites -->

    <!-- DB2 Prerequisites -->

</PrerequisiteDescriptor>

<!-- Creating the OPSS Schema and Setting it to valid in the Registry -->
<ExecutionDescriptor>
    <Action TYPE="Java" PERCENT_PROGRESS="20">
        <Command
TYPE="METHOD">oracle.ias.version.SchemaVersionUtil:utilCreateRegistryEntry</Command>
        <Parameters>
            <Parameter TYPE="Connection"></Parameter>
            <Parameter TYPE="String">OPSS</Parameter>
            <Parameter TYPE="String">Oracle Platform Security Services</Parameter>
            <Parameter TYPE="String">%PREFIX_NAME%</Parameter>
            <Parameter TYPE="String">OPSS</Parameter>
            <Parameter TYPE="String">OPSS</Parameter>
            <Parameter TYPE="String">%SCHEMA_USER%</Parameter>
            <Parameter TYPE="String">12.1.2.0.0</Parameter>
            <Parameter TYPE="String">LOADING</Parameter>
        </Parameters>
    </Action>
    <Action TYPE="JDBCsqlScript" PERCENT_PROGRESS="40">
        <ValidIf DBTYPE="ORACLE" />
        <Command TYPE="SCRIPT">%SCRIPT_HOME%/opss/scripts/opss_user.sql</Command>

```



```

    <Parameters>
      <Parameter TYPE="CmdLine">%SCHEMA_USER%/Parameter>
      <Parameter TYPE="CmdLine">%SCHEMA_PASSWORD%/Parameter>
      <Parameter TYPE="CmdLine">%DEFAULT_TABLESPACE%/Parameter>
      <Parameter TYPE="CmdLine">%TEMPORARY_TABLESPACE%/Parameter>
    </Parameters>
    <IgnorableErrors>
      <Error Type="ORA-01918">user name does not exist</Error>
    </IgnorableErrors>
  </Action>
  <Action TYPE="JDBCScript" PERCENT_PROGRESS="20">
    <ValidIf DBTYPE="EBR" />
    <Command TYPE="SCRIPT">%SCRIPT_HOME%/opss/scripts/oracleEbr/opss_user.sql</
Command>
    <Parameters>
      <Parameter TYPE="CmdLine">%SCHEMA_USER%/Parameter>
      <Parameter TYPE="CmdLine">%SCHEMA_PASSWORD%/Parameter>
      <Parameter TYPE="CmdLine">%DEFAULT_TABLESPACE%/Parameter>
      <Parameter TYPE="CmdLine">%TEMPORARY_TABLESPACE%/Parameter>
      <Parameter TYPE="CmdLine">%EDITION_NAME%/Parameter>
    </Parameters>
    <IgnorableErrors>
      <Error Type="ORA-01918">user name does not exist</Error>
    </IgnorableErrors>
  </Action>

  <Action TYPE="JDBCScript" PERCENT_PROGRESS="40">
    <ValidIf DBTYPE="SQLSERVER" />
    <Command TYPE="SCRIPT">%SCRIPT_HOME%/opss/scripts/sqlserver/opss_user.sql</
Command>
    <Parameters>
      <Parameter TYPE="CmdLine">%SCHEMA_USER%/Parameter>
      <Parameter TYPE="CmdLine">%SCHEMA_PASSWORD%/Parameter>
      <Parameter TYPE="CmdLine">%DATABASE_NAME%/Parameter>
    </Parameters>
  </Action>
  <Action TYPE="JDBCScript" PERCENT_PROGRESS="40">
    <ValidIf DBTYPE="IBMDB2" />
    <Command TYPE="SCRIPT">%SCRIPT_HOME%/opss/scripts/db2/opss_user.sql</Command>
    <Parameters>
      <Parameter TYPE="CmdLine">%SCHEMA_USER%/Parameter>
      <Parameter TYPE="CmdLine">%DEFAULT_TABLESPACE%/Parameter>
      <Parameter TYPE="CmdLine">%SCHEMA_USER%/Parameter>
    </Parameters>
  </Action>

  <Action TYPE="JDBCScript" PERCENT_PROGRESS="60">
    <ValidIf DBTYPE="ORACLE" />
    <Command TYPE="SCRIPT">%SCRIPT_HOME%/opss/scripts/opss_tables.sql</Command>
    <Parameters>
      <Parameter TYPE="CmdLine">%SCHEMA_USER%/Parameter>
    </Parameters>
    <IgnorableErrors>
      <Error Type="ORA-00942">table or view does not exist</Error>
    </IgnorableErrors>
  </Action>
  <Action TYPE="JDBCScript" PERCENT_PROGRESS="60">
    <ValidIf DBTYPE="EBR" />
    <Command TYPE="SCRIPT">%SCRIPT_HOME%/opss/scripts/oracleEbr/opss_tables.sql</
Command>
    <Parameters>
      <Parameter TYPE="CmdLine">%SCHEMA_USER%/Parameter>

```

```
        <Parameter TYPE="CmdLine">%EDITION_NAME%/</Parameter>
    </Parameters>
    <IgnorableErrors>
        <Error Type="ORA-00942">table or view does not exist</Error>
    </IgnorableErrors>
</Action>

<Action TYPE="JDBCsqlScript" PERCENT_PROGRESS="60">
    <ValidIf DBTYPE="SQLSERVER" />
    <Command TYPE="SCRIPT">%SCRIPT_HOME%/opss/scripts/sqlserver/opss_tables.sql</
Command>
    <Parameters>
        <Parameter TYPE="CmdLine">%DATABASE_NAME%/</Parameter>
    </Parameters>
</Action>
<Action TYPE="JDBCsqlScript" PERCENT_PROGRESS="60">
    <ValidIf DBTYPE="IBMDB2" />
    <Command TYPE="SCRIPT">%SCRIPT_HOME%/opss/scripts/db2/opss_tables.sql</Command>
    <Parameters>
        <Parameter TYPE="CmdLine">%SCHEMA_USER%/</Parameter>
        <Parameter TYPE="CmdLine">%DEFAULT_TABLESPACE%/</Parameter>
        <Parameter TYPE="CmdLine">%TEMPORARY_TABLESPACE%/</Parameter>
    </Parameters>
</Action>

<Action TYPE="JDBCsqlScript" PERCENT_PROGRESS="70">
    <ValidIf DBTYPE="ORACLE" />
    <Command TYPE="SCRIPT">%SCRIPT_HOME%/opss/scripts/opss_version.sql</Command>
    <Parameters>
        <Parameter TYPE="CmdLine">%SCHEMA_USER%/</Parameter>
    </Parameters>
</Action>
<Action TYPE="JDBCsqlScript" PERCENT_PROGRESS="70">
    <ValidIf DBTYPE="EBR" />
    <Command TYPE="SCRIPT">%SCRIPT_HOME%/opss/scripts/oracleEbr/opss_version.sql</
Command>
    <Parameters>
        <Parameter TYPE="CmdLine">%SCHEMA_USER%/</Parameter>
        <Parameter TYPE="CmdLine">%EDITION_NAME%/</Parameter>
    </Parameters>
</Action>

<Action TYPE="JDBCsqlScript" PERCENT_PROGRESS="70">
    <ValidIf DBTYPE="SQLSERVER" />
    <Command TYPE="SCRIPT">%SCRIPT_HOME%/opss/scripts/sqlserver/opss_version.sql</
Command>
    <Parameters>
        <Parameter TYPE="CmdLine">%DATABASE_NAME%/</Parameter>
    </Parameters>
</Action>
<Action TYPE="JDBCsqlScript" PERCENT_PROGRESS="70">
    <ValidIf DBTYPE="IBMDB2" />
    <Command TYPE="SCRIPT">%SCRIPT_HOME%/opss/scripts/db2/opss_version.sql</Command>
    <Parameters>
        <Parameter TYPE="CmdLine">%SCHEMA_USER%/</Parameter>
    </Parameters>
</Action>

<Action TYPE="JDBCsqlScript" PERCENT_PROGRESS="80">
    <ValidIf DBTYPE="ORACLE" />
    <Command TYPE="SCRIPT">%SCRIPT_HOME%/opss/scripts/opss_gencatalog.sql</Command>
    <Parameters>
```

```

        <Parameter TYPE="CmdLine">%SCHEMA_USER%/</Parameter>
    </Parameters>
</Action>

<Action TYPE="JDBCScript" PERCENT_PROGRESS="80">
    <ValidIf DBTYPE="SQLSERVER" />
    <Command TYPE="SCRIPT">%SCRIPT_HOME%/opss/scripts/sqlserver/
opss_gencatalog.sql</Command>
    <Parameters>
        <Parameter TYPE="CmdLine">%DATABASE_NAME%/</Parameter>
    </Parameters>
</Action>

<Action TYPE="JDBCScript" PERCENT_PROGRESS="80">
    <ValidIf DBTYPE="IBMDB2" />
    <Command TYPE="SCRIPT">%SCRIPT_HOME%/opss/scripts/db2/opss_gencatalog.sql</
Command>
    <Parameters>
        <Parameter TYPE="CmdLine">%SCHEMA_USER%/</Parameter>
    </Parameters>
</Action>

<Action TYPE="JDBCScript" PERCENT_PROGRESS="80">
    <ValidIf DBTYPE="EBR" />
    <Command TYPE="SCRIPT">%SCRIPT_HOME%/opss/scripts/oracleEbr/
opss_gencatalog.sql</Command>
    <Parameters>
        <Parameter TYPE="CmdLine">%SCHEMA_USER%/</Parameter>
        <Parameter TYPE="CmdLine">%EDITION_NAME%/</Parameter>
    </Parameters>
</Action>

<Action TYPE="JDBCScript" CONNECT_AS_OWNER="TRUE" PERCENT_PROGRESS="100">
    <ValidIf DBTYPE="ORACLE" />
    <Command TYPE="SCRIPT">%SCRIPT_HOME%/opss/scripts/upgd_mgmt_schema.sql</Command>
</Action>

<Action TYPE="Java">
    <Command
TYPE="METHOD">oracle.ias.version.SchemaVersionUtil:utilSetComponentValid</Command>
    <Parameters>
        <Parameter TYPE="String">OPSS</Parameter>
    </Parameters>
</Action>
</ExecutionDescriptor>

<!-- Deleting the OPSS Schema and removing it from the Registry -->
<DeleteDescriptor>
    <Action TYPE="JDBC" PERCENT_PROGRESS="50">
        <ValidIf DBTYPE="ORACLE" />
        <Command TYPE="INLINE">DROP USER %SCHEMA_USER% CASCADE</Command>
    </Action>
    <Action TYPE="JDBC" PERCENT_PROGRESS="50">
        <ValidIf DBTYPE="EBR" />
        <Command TYPE="INLINE">DROP USER %SCHEMA_USER% CASCADE</Command>
    </Action>

    <Action TYPE="JDBCScript" PERCENT_PROGRESS="20">
        <ValidIf DBTYPE="SQLSERVER" />
        <Command TYPE="SCRIPT">%SCRIPT_HOME%/opss/scripts/sqlserver/
opss_drop_table.sql</Command>
        <Parameters>
            <Parameter TYPE="CmdLine">%DATABASE_NAME%/</Parameter>

```

```

        </Parameters>
    </Action>
    <Action TYPE="JDBCScript" PERCENT_PROGRESS="50">
        <ValidIf DBTYPE="SQLSERVER" />
        <Command TYPE="SCRIPT">%SCRIPT_HOME%/opss/scripts/sqlserver/opss_drop_user.sql</
Command>
        <Parameters>
            <Parameter TYPE="CmdLine">%DATABASE_NAME%</Parameter>
            <Parameter TYPE="CmdLine">%SCHEMA_USER%</Parameter>
        </Parameters>
    </Action>

    <Action TYPE="Java" PERCENT_PROGRESS="50">
        <ValidIf DBTYPE="IBMDB2" />
        <Command
TYPE="METHOD">oracle.sysman.assistants.common.dbutil.jdbc.DB2DropUtil:dropCompRepos</
Command>
        <Parameters>
            <Parameter TYPE="Connection"></Parameter>
            <Parameter TYPE="String">%SCHEMA_USER%</Parameter>
        </Parameters>
    </Action>

    <Action TYPE="Java" PERCENT_PROGRESS="100">
        <Command
TYPE="METHOD">oracle.ias.version.SchemaVersionUtil:utilDropRegistryEntry</Command>
        <Parameters>
            <Parameter TYPE="Connection"></Parameter>
            <Parameter TYPE="String">OPSS</Parameter>
            <Parameter TYPE="String">%PREFIX_NAME%</Parameter>
            <Parameter TYPE="String">OPSS</Parameter>
        </Parameters>
    </Action>
</DeleteDescriptor>
</RepositoryConfig>

```

Soft-Prerequisite Support

If a particular `<DBPrerequisiteSet>` or `<DBPrerequisite>` is not mandatory, then you can use the soft-prerequisite option by setting the `SOFT` attribute to `TRUE` in the `ComponentInfo.xml` file

When a soft-prerequisite is not met, a pop-up dialog window with an error or warning message appears; the user has the option to ignore the message or abort the operation. You can define a soft-prerequisite at the `<DBPrerequisiteSet>` level, the `<DBPrerequisite>` level, or both; if both are defined, then `<DBPrerequisiteSet>` takes higher precedence.

Below is an example of setting a soft-prerequisite at the `<DBPrerequisite>` level:

```

<DBPrerequisiteSet>
...
    <DBPrerequisite PREREQ_TYPE="CustomSQL" DATA_TYPE="STRING" COMPARE_OPERATOR="EQ"
SOFT="TRUE">
        <PrereqIdentifier>select value from nls_database_parameters where parameter =
'NLS_CHARACTERSET'</PrereqIdentifier>
        <PrereqValue>AL32UTF8</PrereqValue>
        <PrereqErrorMsg>
            The database you are connecting is with non-AL32UTF8 character set.
            Oracle strongly recommends using AL32UTF8 as the database character
            set.
        </PrereqErrorMsg>
    </DBPrerequisite>

```

```
...
<DBPrerequisiteSet>
```

Default Tablespaces Configuration File

The default tablespaces configuration file (`Storage.xml`) lists the components, for which, tablespaces are created out-of-the-box. This file is located in the `ORACLE_HOME/oracle_common/rcu/config` directory on UNIX operating systems.

The actual tablespace configuration file for each component is located in the `ORACLE_HOME/oracle_common/rcu/integrationcomponent/component_Storage.xml` directory on UNIX operating systems. Each component has its own tablespaces configuration file.

Below is a sample `opss_Storage.xml` file:

```
<?xml version="1.0" encoding="UTF-8" ?>

<!-- OPSS START -->
<TablespaceAttributes NAME="IAS_OPSS">
  <Type>Permanent</Type>
  <DefaultTemp>False</DefaultTemp>
  <Bigfile>False</Bigfile>
  <DatafilesList>
    <DatafileAttributes ID="%DATAFILE_LOCATION%/ias_opss.dbf">
      <Size UNIT="MB">60</Size>
      <Reuse>True</Reuse>
      <AutoExtend>True</AutoExtend>
    </DatafileAttributes>
  </DatafilesList>
</TablespaceAttributes>
<!-- OPSS END -->
```

For RCU XML Configuration File Details, refer [Table C-1](#) in [Storage Attributes Configuration File](#)

RCU Script Writing Guidelines

Use these guidelines when writing RCU scripts.

Schema user names and passwords should not be hard coded. They should be coded as substitutable variables.

- If schema user needs to be created, it should be created first by using the parameters passed by RCU.
- Tablespace and temporary tablespace references should not be hard coded; they should be coded as variables.
- Do not use `CONNECT`; instead, use `ALTER SESSION SET CURRENT_SCHEMA = <SCHEMA_OWNER>` after you create the schema user.
- The set of ignorable and fatal `ORA` errors (if any) should be listed in the RCU XML component configuration file.
- Avoid any `shutdown` or `startup` that would bounce the database instance.
- `SCHEMA_VERSION_REGISTRY` should be updated before and after loading schema. This can be done by using `JavaAction` as shown in [Java Code Using JavaAction](#) or within the component scripts by using the `SCHEMA_VERSION PL/SQL` package.
- Block comments that contain line comments (`/* -- comment */`) are not supported.

The following are the guidelines for RCU for various scripts:

- [Guidelines for RCU JDBC Engine Compliant SQL*Plus Scripts](#)
Use these guidelines for writing the RCU JDBC Engine SQL*Plus scripts.
- [Guidelines for Pure JDBC Scripts](#)
Use these guidelines for writing Pure JDBC scripts for RCU.
- [Guidelines for SQL*Plus Scripts](#)
Use these guidelines for writing SQL*Plus scripts for RCU.
- [Guidelines for SQL Server-Based Scripts](#)
Use these guidelines for writing SQL Server-based scripts for RCU.

Guidelines for RCU JDBC Engine Compliant SQL*Plus Scripts

Use these guidelines for writing the RCU JDBC Engine SQL*Plus scripts.

- All statements must be terminated with appropriate terminating chars. *CREATE PACKAGE*, *TYPE* needs to be terminated with a ; (semicolon) with / (forward slash) on the next line. All other statements (Create TABLE, VIEW, and so on.) need to be terminated by either ; (semicolon) or / (forward slash).
- *EXECUTE* calls should be replaced with *BEGIN/END* blocks.
- *DEFINE* statements should be in one line, no comments in the same line and no ; (semicolon) at the end.
- *SET*, *SHOW*, *SPOOL*, *WHENEVER*, *BREAK*, *EXIT* statements are ignored.
- *HOST* command is not supported yet.
- *VARIABLE* and *COL(UMN)* are not supported.

Dynamically calling another SQL Script within a PL/SQL block using the following technique is not supported:

```
VARIABLE initfile VARCHAR2(32)
COLUMN :initfile NEW_VALUE init_file NOPRINT;
BEGIN
  IF (some condition) THEN
    :initfile := 'initcdc.sql';
  ELSE
    :initfile := 'nothing.sql';
  END IF;
END;
/
SELECT :initfile FROM DUAL;
@@&init_file
```

The work around is to have a separate Action with a *ValidIf* tag to specify the condition.

Guidelines for Pure JDBC Scripts

Use these guidelines for writing Pure JDBC scripts for RCU.

- Should not contain any SQL*Plus directives (like SET, WHENEVER, and so on.).
- All DEFINES should be changed to PL/SQL variable declarations.
- All SQL statements should be wrapped in *EXECUTE IMMEDIATE*.

- PL/SQL style comments are allowed, but SQL*Plus style (REM) comments are not allowed.
- DROP statements that precedes CREATE statements do not work. DROP should only be done after checking for the existence of the object. Ideally, all DROP statements should put into different PL/SQL script and RCU can call this script before calling a CREATE script, if that is desired.
- Contents of the script file should be a valid PL/SQL block, which can be called within `Connection.prepareCall()`.

Guidelines for SQL*Plus Scripts

Use these guidelines for writing SQL*Plus scripts for RCU.

- Should not have any *exit* statements or *WHENEVER ERROR EXIT* directives. This would cause RCU SQL*Plus session to exit unexpectedly and may impact other component scripts to be executed later.
- Scripts should not have any spool commands. RCU would generate a spool log for each component.

Guidelines for SQL Server-Based Scripts

Use these guidelines for writing SQL Server-based scripts for RCU.

- Support is a subset of what is supported in t-sql scripts that can be executed by `sqlcmd`.
- *ValidIf* tags should be added around all database-specific Actions and Prerequisites. For example:

```
<DBPrerequisite PREREQ_TYPE="TablespaceFreeMB" DATA_TYPE="NUMBER"
COMPARE_OPERATOR="GT">
  <ValidIf DBTYPE="ORACLE" />
  <PrereqIdentifier>%DEFAULT_TABLESPACE%</PrereqIdentifier>
  <PrereqValue>50</PrereqValue>
</DBPrerequisite>
```

- RCU supports recursive variable definitions such as:

```
setvar var1 value1
setvar var2 $(var1)
```

- There should be a *go* statement to end blocks of statements. All statements that precedes the *go* statement are executed as a single statement over JDBC.
- The JDBC connection is created in the auto-commit *on* mode.
- Currently, the begin transaction and commit transaction statements are not supported.
- Variables passed to scripts through the XML file are passed as follows:

```
Script.sql -v v1=value1 v2=value2
```

This is only for scripts called by using the XML files. If a script calls another script, you can use any other variable name.

D

Troubleshooting Repository Creation Utility

Review this information to help you understand and troubleshoot any errors or issues that you encounter while you run the RCU.

- [General Troubleshooting Tips](#)
Use these tips to help troubleshoot any errors that you encounter during installation.
- [RCU Log Files](#)
When you run RCU to create or drop your schemas, the main RCU log file is written to the `/tmp/RCUdate_timestamp_random_number/logs` directory on UNIX operating systems, by default. Review the log files for important information that may help you resolve your issues.
- [SOAINFRA Schema Creation Fails on a Hardened Database](#)
Use this workaround if the RCU schemas for `SOAINFRA` does not load successfully on an Oracle hardened database.
- [Troubleshooting Tips for Schema Creation on an Autonomous Transaction Processing Database](#)
Use these tips to troubleshoot any errors you encounter during schema creation on an Autonomous Transaction Processing database (both Autonomous Transaction Processing - Dedicated and Autonomous Transaction Processing-Shared).
- [Known Limitation for Oracle WebCenter Sites ATP-S Migration](#)
- [Need More Help?](#)
If this guide does not solve the problem that you encountered, try looking for a solution on My Oracle Support (formerly Oracle MetaLink).

General Troubleshooting Tips

Use these tips to help troubleshoot any errors that you encounter during installation.

- See *Install and Configure* in the *Release Notes for Oracle Fusion Middleware Infrastructure* for the latest updates and issues related to Oracle Fusion Middleware product installation and configuration.
- Verify that your computer meets the requirements as specified in the *Oracle Fusion Middleware System Requirements and Specifications* document.
Select the document that is applicable for your release.
- Verify that your environment meets the certification requirements for your release and platform, as specified on the *Oracle Fusion Middleware Supported System Configurations* page.
- Make sure that your database is up and running.
- If you entered incorrect information on one of the screens, use the navigation pane on the left most side of the graphical interface to return to that screen.
- If an error occurred while running RCU:
 1. Note the error and review the installation log files (see [RCU Log Files](#)).

2. Correct the issue that caused the error. Depending on the type of error, you may either continue with your RCU operation, or you are forced to restart RCU.
3. Continue or restart RCU to complete your desired operation.

RCU Log Files

When you run RCU to create or drop your schemas, the main RCU log file is written to the `/tmp/RCUdate_timestamp_random_number/logs` directory on UNIX operating systems, by default. Review the log files for important information that may help you resolve your issues.

SOAINFRA Schema Creation Fails on a Hardened Database

Use this workaround if the RCU schemas for `SOAINFRA` does not load successfully on an Oracle hardened database.

In case of an Oracle hardened database, when the public grants are revoked for the PL/SQL packages, the schema creation for `SOAINFRA` fails with the following error:

```
Received Non-Ignorable Error: ORA-04063: package body "XDB.DBMS_CSX_INT" has errors
```

Grant the following permission to the user and run the Repository Creation Utility (RCU) again to create the schemas for `SOAINFRA`.

```
GRANT EXECUTE ON DBMS_LOB TO XDB;
```

Troubleshooting Tips for Schema Creation on an Autonomous Transaction Processing Database

Use these tips to troubleshoot any errors you encounter during schema creation on an Autonomous Transaction Processing database (both Autonomous Transaction Processing - Dedicated and Autonomous Transaction Processing-Shared).

- See Issues Pertaining to Product Installation and Configuration with Autonomous Database in the *Release Notes for Oracle Fusion Middleware Infrastructure* for issues related to installation and configuration for Oracle Fusion Middleware products on an Autonomous Transaction Processing database.
- In the **Database Connection Details** screen, when you select the database user role as `Normal`, the following warning is displayed:

```
Sysdba or dba privileges are required to load schema
```

You can click **Ignore** and continue with the schema creation.

- If you are creating schemas on an Autonomous Transaction Processing - Dedicated database, in the **Map Tablespaces** screen, if you receive any tablespace creation error due to insufficient privileges or exceeding of maximum number of `DB_FILES`, you can override the default and temporary tablespaces for the selected components by selecting existing tablespaces from the drop-down list in the **Default Tablespace** column and **Temp Tablespace** column.

For example, to override the default and temporary tablespaces, you can select `DATA` from the drop-down list in the **Default Tablespace** column, and `TEMP` from the drop-down list in the **Temp Tablespace** column.

 **Note:**

If you are creating schemas on an Autonomous Transaction Processing-Shared database, in the **Map Tablespaces** screen, you must override the default and temporary tablespaces. See [Map Tablespaces](#).

- During Oracle WebCenter Content schema creation, warnings are displayed in the **Summary** screen.

You can click **Ignore** and continue with the schema creation.

Example warning messages:

```
ORA-01031: insufficient privileges
File:/home/opc/idm/oracle_common/../wcccontent/common/sql/content/sql/oracle/contentserverrole.sql
Statement: GRANT SELECT ON CTXSYS.DR$PENDING TO contentserver_role
```

```
ORA-01450: maximum key length (6398) exceeded
File:/home/opc/jrf/oracle_common/../wcccontent/common/sql/content/sql/oracle/contentserverrole.sql
Statement: CREATE TABLE RunTimeConfigData
```

```
ORA-01450: maximum key length (6398) exceeded
File:/home/opc/jrf/oracle_common/../wcccontent/common/sql/content/sql/oracle/intradoc.sql
STATEMENT Create table Subscription
```

where, /home/opc/idm and /home/opc/jrf are the ORACLE HOME locations.

- During Oracle Internet Directory schema creation, when the schemas are loading, the warning ORA-28007: the password cannot be reused is displayed in the **Summary** screen.
You can click **Ignore** and continue with the schema creation.
- During SOAINFRA schema creation, for Oracle Identity Management, the warning ORA-24010: QUEUE DEV24_SOAINFRA.IP_IN_QUEUE does not exist is displayed in the RCU logs. This warning does not have any functional impact and can be ignored.
- During schema creation of Oracle Enterprise Scheduler and Oracle Managed File Transfer SOA products, in the **Summary** screen, the following warning "ORA-01031: insufficient privileges" is displayed and the schema creation fails.
Add the *create any job* privilege to the ADMIN user, and restart the schema creation.
- During schema creation of Oracle Enterprise Scheduler and Oracle Managed File Transfer SOA products, even after adding the *create any job* privilege, in the **Summary** screen, the warning "ORA-01031: insufficient privileges" is displayed.

For ATP-D, you can apply the patch [31443286](#) and restart the schema creation., and for ATP-S, you can apply the patch [33351665](#) and restart the schema creation.

Known Limitation for Oracle WebCenter Sites ATP-S Migration

For Oracle WebCenter Sites, you cannot install and configure FirstSiteII sample site, and therefore, you cannot create new promotion assets, after you migrate an on-premises database to an Oracle Autonomous Transaction Processing (ATP-S) database.

As there is no workaround available, you must exclude FirstSiteII during the installation.

Need More Help?

If this guide does not solve the problem that you encountered, try looking for a solution on My Oracle Support (formerly Oracle MetaLink).

<https://support.oracle.com/>

If you are unable to find a solution for your problem, open a service request.