

Oracle® Fusion Middleware

Release Notes for Oracle TopLink



14c (14.1.2.0.0)
G17425-01
December 2024

ORACLE®

Copyright © 2014, 2024, Oracle and/or its affiliates.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle®, Java, MySQL, and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

1 Release Notes for Oracle TopLink

TopLink Grid Deprecated	1-1
TopLink Object-Relational Issues	1-1
Error Parsing validation.xml	1-1
Exalogic TuningAgent Profiler is not Set	1-2
Cannot set EclipseLink log level in WLS System MBean Browser	1-2
UnitOfWork.release() not Supported with External Transaction Control	1-2
Returning Policy for UPDATE with Optimistic Locking	1-2
JDBC Drivers Returning Timestamps as Strings	1-3
Allowing Zero Value Primary Keys	1-3
Managed Servers on Sybase with JCA Oracle Database Service	1-4
Logging Configuration with EclipseLink Using Container Managed JPA	1-4
Documentation Accessibility	1-4

1

Release Notes for Oracle TopLink

This document details issues associated with Oracle TopLink. It includes the following topics:

- [TopLink Grid Deprecated](#)
- [TopLink Object-Relational Issues](#)
- [Allowing Zero Value Primary Keys](#)
- [Managed Servers on Sybase with JCA Oracle Database Service](#)
- [Logging Configuration with EclipseLink Using Container Managed JPA](#)
- [Documentation Accessibility](#)

TopLink Grid Deprecated

The TopLink Grid feature in Oracle TopLink 12.2.1 is deprecated.

TopLink Object-Relational Issues

This section contains information on the following issues:

- [Error Parsing validation.xml](#)
- [Exalogic TuningAgent Profiler is not Set](#)
- [Cannot set EclipseLink log level in WLS System MBean Browser](#)
- [UnitOfWork.release\(\) not Supported with External Transaction Control](#)
- [Returning Policy for UPDATE with Optimistic Locking](#)
- [JDBC Drivers Returning Timestamps as Strings](#)

Error Parsing validation.xml

Under some configurations, users may encounter a warning log message in the log file such as the following one. The log message is harmless and indicates TopLink's search for the `validation.xml` file, which is defined in the *JSR 303 Bean Validation specification*. TopLink is able only to read the `validation.xml` from the filesystem, not from archives of any kind.

```
[WARNING] [] [org.eclipse.persistence.jaxb.BeanValidationHelper] [tid:
[STANDBY].ExecuteThread: '35' for queue: 'weblogic.kernel.Default
(self-tuning)'] [ecid: 8ee5cff5-3f55-4f1b-a389-4328958blee9-0000003d,0] [APP:
webcenter] [partition-name: DOMAIN] [tenant-name: GLOBAL] Error parsing
validation.xml[[
java.util.concurrent.ExecutionException: java.lang.IllegalArgumentException:
URI scheme is not "file"
```

Exalogic TuningAgent Profiler is not Set

When using the TopLink Exalogic automated tuner, the `oracle.toplink.exalogic.tuning.TuningAgent` profiler is not enabled. The `TuningAgent` profiler has been disabled due to issues with stuck threads.

Cannot set EclipseLink log level in WLS System MBean Browser

Use Oracle Enterprise Manager to set the EclipseLink log level; do not use the WLS System MBean Browser to complete this action.

UnitOfWork.release() not Supported with External Transaction Control

A unit of work synchronized with a Java Transaction API (JTA) will throw an exception if it is released. If the current transaction requires its changes to not be persisted, the JTA transaction must be rolled back.

When in a container-demarcated transaction, call `setRollbackOnly()` on the EJB/session context:

```
@Stateless
public class MySessionBean
{
    @Resource
    SessionContext sc;

    public void someMethod()
    {
        ...
        sc.setRollbackOnly();
    }
}
```

When in a bean-demarcated transaction then you call `rollback()` on the `UserTransaction` obtained from the EJB/session context:

```
@Stateless
@TransactionManagement(TransactionManagementType.BEAN)
public class MySessionBean implements SomeInterface
{
    @Resource
    SessionContext sc;

    public void someMethod()
    {
        sc.getUserTransaction().begin();
        ...
        sc.getUserTransaction().rollback();
    }
}
```

Returning Policy for UPDATE with Optimistic Locking

The returning policy, which allows values modified during `INSERT` and `UPDATE` to be returned and populated in cached objects, does not work in conjunction with numeric version optimistic locking for `UPDATE`. The value returned for all `UPDATE` operations is 1 and does not provide meaningful locking protection.

Do not use a returning policy for `UPDATE` in conjunction with numeric optimistic locking.

The use of returning policy for `INSERT` when using optimistic locking works correctly.

JDBC Drivers Returning Timestamps as Strings

TopLink assumes that date and time information returned from the server will use `Timestamp`. If the JDBC driver returns a `String` for the current date, TopLink will throw an exception. This is the case when using a DB2 JDBC driver.

To work around this issue, consider using a driver that returns `Timestamp` (such as `COM.ibm.db2.jdbc.app.DB2Driver`) or change the policy to use local time instead of server time.

Another option is to use a query re-director on the `ValueReadQuery` used by the platform:

```
ValueReadQuery vrq = new ValueReadQuery(
    "SELECT to_char(sysdate, 'YYYY-MM-DD HH:MM:SS.SSSSS') FROM DUAL"
);
vrq.setRedirector(new TSQueryRedirector());
...
class TSQueryRedirector implements QueryRedirector
{
    public Object invokeQuery(DatabaseQuery query, Record arguments, Session session)
    {
        String value = (String)session.executeQuery(query);
        return ConversionManager.getDefaultManager().convertObject(
            value, java.sql.Timestamp.class
        );
    }
}
```

Allowing Zero Value Primary Keys

By default, EclipseLink interprets *zero* as *null* for primitive types that cannot be null (such as `int` and `long`) causing zero to be an invalid value for primary keys. You can modify this setting by using the `allow-zero-id` property in the `persistence.xml` file. Valid values are:

- `true` – EclipseLink interprets zero values as *zero*. This permits primary keys to use a value of zero.
- `false` (default) – EclipseLink interprets zero as *null*.

Refer the *EclipseLink User's Guide* at <http://wiki.eclipse.org/EclipseLink/UserGuide> for more information.



Note:

Adding this configuration property is potentially dangerous, as configuring this particular setting through `persistence.xml` affects ALL applications running on the server

Managed Servers on Sybase with JCA Oracle Database Service

When using a JCA service with the Oracle Database adapter in a cluster to perform database operations on a Sybase database, the managed nodes in the cluster process the messages and may attempt to perform duplicate operations.

Because supported versions of Sybase do not support Oracle TopLink record locking, Sybase allows the duplicate operation attempts.

Logging Configuration with EclipseLink Using Container Managed JPA

By default, EclipseLink users in container managed JPA will use the Oracle WebLogic Server logging options to report all log messages generated by EclipseLink. Refer to "Configuring WebLogic Logging Services" in *Oracle® Fusion Middleware Configuring Log Files and Filtering Log Messages for Oracle WebLogic Server*.

To use the EclipseLink native logging configuration, add the following property to your `persistence.xml` file:

```
<property name="eclipselink.logging.logger" value="DefaultLogger"/>
```

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customer access to and use of Oracle support services will be pursuant to the terms and conditions specified in their Oracle order for the applicable services.