

Oracle® Fusion Middleware

Oracle Fusion Middleware Bundle Patch Release Notes for IDM Stack Patch Bundle



12.2.1.4.240712

G30111-01

July 2024

ORACLE®

Oracle Fusion Middleware Oracle Fusion Middleware Bundle Patch Release Notes for IDM Stack Patch Bundle,
12.2.1.4.240712

G30111-01

Copyright © 2024, Oracle and/or its affiliates.

Primary Authors: Oracle, Panendra Puttachar

Contributing Authors: Madhusudhanan Venugopalan, Bruce Bergeron, Sree Ramanan

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle®, Java, MySQL, and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

1	Bundle Patch Release Notes for IDM SPB	
2	About the Oracle Identity Management Stack Patch Bundle (SPB)	
3	About the SPBAT Utility	
4	System Overview	
5	Prerequisites	
	5.1 Staging and verification	5-1
	5.2 Minimum OPatch Version Check	5-2
	5.3 Backup	5-2
	5.4 Setting Heap size for OPatch	5-2
	5.5 Removing Inactive Patches	5-2
6	SPB Patches and their Applicability	
7	SPB usage Instructions	
8	Phases in the Patching Process	
9	Applying the SPB Patches using SPBAT	
10	Post-Install and Configuration Steps - OAM	

11 Post-Install and Configuration Steps - OIG

12 Post-Install and Configuration Steps - OUD

13 Post-Install and Configuration Steps - OID

14 Troubleshooting

15 Limitations

1

Bundle Patch Release Notes for IDM SPB

This README provides information about the SPBAT utility used for applying Oracle Identity Management SPB.

This document contains the following sections:

- [About the Oracle Identity Management Stack Patch Bundle \(SPB\)](#)
- [About the SPBAT Utility](#)
- [System Overview](#)
- **Prerequisites**
- [SPB Patches and their Applicability](#)
- [SPB usage Instructions](#)
- [Phases in the Patching Process](#)
- [Applying the SPB Patches using SPBAT](#)
- [Post-Install and Configuration Steps - OAM](#)
- [Post-Install and Configuration Steps - OIG](#)
- [Post-Install and Configuration Steps - OUD](#)
- [Post-Install and Configuration Steps - OID](#)
- [Troubleshooting](#)
- [Limitations](#)

2

About the Oracle Identity Management Stack Patch Bundle (SPB)

Oracle Identity Management Stack Patch Bundle (SPB) which is released every quarter, is essentially a collection of latest upper stack and lower stack mandatory patches applicable for IDM 12.2.1.4 installed environments. IDM 12.2.1.4 customer environments are broadly divided into following categories:

1. OAM - Oracle Access Manager
2. OIG - Oracle Identity Governance
3. OUD - Oracle Universal Directory
4. OID - Oracle Internet Directory

IDM customers belonging to above categories are required to apply the mandatory Patches prescribed for their respective installed environments. Please go through the remaining sections in this document for more information on applying the above patches on IDM 12.2.1.4 installed environments.

3

About the SPBAT Utility

Stack Patch Bundle Automation Tool (SPBAT) applies IDM patches (delivered via IDM Quarterly Stack Patch Bundle) on IDM 12.2.1.4 installed environments. On-Premise customers can use this tool directly. In case of any issues or additional guidance the Customers can open a Service Request (SR) with Oracle Support.

4

System Overview

The SPBAT utility is developed by using SHELL and Python scripts. This utility is supported only for LINUX X86-64, SOLARIS_SPARC64, SOLARIS64(x86), WINDOWS64 platforms on which IDM 12.2.1.4 suite is deployed.

ORACLE_HOME (Oracle Home) setup for IDM 12.2.1.4 is broadly divided into the following categories:

1. OAM - Oracle Access Manager
2. OIG - Oracle Identity Governance
3. OUD - Oracle Universal Directory
4. OID - Oracle Internet Directory

In the following sections, the above categories are described as separate install types, each containing a dedicated ORACLE_HOME deployed in dedicated VMs/Hosts.

In case the setup is spread across multiple VMs/Hosts, then perform the patching steps for each ORACLE_HOME on respective VMs. If there are multiple ORACLE_HOME locations on the same VM, then perform the patching steps for each ORACLE_HOME separately. If two or more install types share the same ORACLE_HOME, then perform the patching steps for each install type against the ORACLE_HOME.

5

Prerequisites

Ensure that you meet the following requirements before you attempt to run the SPBAT utility on IDM 12.2.1.4 installed environment.

- [Staging and verification](#)
- [Minimum OPatch Version Check](#)
- [Backup](#)
- [Setting Heap size for OPatch](#)
- [Removing Inactive Patches](#)

5.1 Staging and verification

1. Decide where you want to install the SPB bundle. The location should have 50GB of free space. The location should be accessible to all IDM hosts with "read", "write" and "execute" rights enabled on the file system. Extract the zip to this location and verify it contains the following directory structure:

IDM_SPB_12.2.1.4_<VERSION>/

spbat-bundle.properties (file)

README.txt (file)

README.html (this file)

binary_patches (dir)

tools (dir)

etc (dir)

upgrade_installers (dir)

2. Navigate to the SPBAT directory and verify it contains the following directory structure:

IDM_SPB_12.2.1.4_<VERSION>/tools/spbat/generic/SPBAT

ExecEngine (dir)

README.txt (file)

bin(dir)

config(dir)

env (dir)

spbat.bat (file)

spbat.sh (file)

tools (dir)

version.txt (file)

3. DO NOT make any changes to the directory structure under `IDM_SPB_12.2.1.4_<VERSION>` location.

5.2 Minimum OPatch Version Check

Ensure that `ORACLE_HOME` has minimum required OPatch version, that is, 13.9.4.2.13 or higher.

To verify, run the following command under the `ORACLE_HOME/OPatch` directory:

```
-bash-4.2$ ./opatch
```

```
versionOPatch Version: 13.9.4.2.13
```

```
OPatch Succeeded.
```

5.3 Backup

1. Create a complete backup of `ORACLE_HOME` and `DOMAIN_HOME` locations before Downtime phase.
2. Create a cold backup of the entire IDM setup by using standard backup software/utilities.

5.4 Setting Heap size for OPatch

OPatch sets the default Heap size to 3 GB for LinuxX86-64 and to 1.5GB for other platforms. It is suggested to override this default value for platform patches (except LinuxX86-64) before OPatch session is invoked by setting the parameter as:

```
export OPATCH_JRE_MEMORY_OPTIONS="-Xmx3072m"
```

5.5 Removing Inactive Patches

Customers who want to improve storage and SPB patching performance should consider the following steps:

1. Choose the level of rollback capability needed.
To keep the rollback level of SPB environment at N-1 (where N is the current patch level), update the `RETAIN_INACTIVE_PATCHES` parameter to value 1 (`RETAIN_INACTIVE_PATCHES=1`) in the `<ORACLE_HOME>/OPatch/config/opatch.properties` file.
2. Run the following command to delete the inactive patches:

```
<ORACLE_HOME>/OPatch/opatch util deleteinactivepatches -oh <ORACLE_HOME>
```

Known Issue :

Currently the `deleteinactivepatches` option deletes only 1 PSU/BP/RU chain and its overlays. In Oracle Homes where there are more than 1 inactive PSU/BP/RU chain (for

example, DBRU, GIRU applied/installed on `ORACLE_HOME`), the user needs to run `opatch` command with `deleteinactivepatches` option multiple times.

As a verification point, after each run of `opatch` command with `deleteinactivepatches` option, run the following command:

```
<ORACLE_HOME>/OPatch/opatch util listorderedinactivepatches -oh  
<ORACLE_HOME>
```

When the output of this command looks like the following:

```
Total: 1 inactive RU/CPU patch (es) and 1 inactive overlay patch (es).
```

then there is no need to run again the `opatch` command with `deleteinactivepatches` option as the desired rollback level has been achieved.

3. Run the following command to perform cleanup:

```
<ORACLE_HOME>/OPatch/opatch util cleanup -oh <ORACLE_HOME>
```

This would cleanup any stale files.

6

SPB Patches and their Applicability

Following is the list of patches included in the SPB and which will be applied on the respective ORACLE_HOME using SPBAT utility:

Patches	Patch Number	Applicability			
MERGE REQUEST ON TOP OF 12.2.1.4.0 FOR BUGS 34065178 34113169	36649916	OAM	OIG	ODU	OID
OIM 12CPS3 UPGRADE STUCK AT SCHEMAREAD INESSQUERIE S QUERYINDEX NAMES	32999272	OAM	OIG	ODU	OID
MERGE REQUEST ON TOP OF 12.2.1.4.0 FOR BUGS 34280277 26354548 26629487 29762601	34542329	OAM	OIG	ODU	OID
FMW PLATFORM 12.2.1.4.0 SPU FOR APRCPU2021	33093748	OAM	OIG	ODU	OID
Fix for Bug 32720458	32720458	OAM	OIG	ODU	OID
OID BUNDLE PATCH 12.2.1.4.221222	34947852	-	-	-	OID
DATABASE RELEASE UPDATE 19.23.0.0.0 FOR FMW DBCLIENT	36392269	-	-	-	OID
ONE OFF PATCH TO RELINK OID WITH DBCLIENT - JUL'24 BP	36758533	-	-	-	OID

Patches	Patch Number	Applicability			
NEED OPATCHABLE PATCH FROM OINAV_MAIN_ GENERIC DATED LABEL	35780760	OAM	OIG	-	-
MERGE REQUEST ON TOP OF 12.2.1.4.0 FOR BUGS 20623024 29790738	31676526	OAM	OIG	-	-
OAS 12.2.1.4.5 - RCU CREATION WITH RAC DB SHOWS INCORRECT PORT WARNING	30540494	OAM	OIG	-	-
ONE-OFF FOR OSDT JAR	36490262	-	-	OLD	-
OSS 19C BUNDLE PATCH 12.2.1.4.240606	36706228	-	-	-	OID
ADR FOR WEBLOGIC SERVER 12.2.1.4.0 - SIZE OPTIMIZED FOR JAN 2024	35965629	OAM	OIG	OLD	OID
RDA release 24.3-2024716 for FMW 12.2.1.4.0	36553894	OAM	OIG	OLD	OID
FMW Thirdparty Bundle Patch 12.2.1.4.240625	36770738	OAM	OIG	OLD	OID
WLS PATCH SET UPDATE 12.2.1.4.240704	36805124	OAM	OIG	OLD	OID
Coherence 12.2.1.4 Cumulative Patch 22 (12.2.1.4.22)	36725924	OAM	OIG	OLD	OID
WEBLOGIC SAMPLES SPU 12.2.1.4.240416	36426672	OAM	OIG	OLD	OID
OPSS BUNDLE PATCH 12.2.1.4.240220	36316422	OMA	OIG	-	-

Patches	Patch Number	Applicability			
OWSM BUNDLE PATCH 12.2.1.4.240625	36769312	OMA	OIG	-	-
OAM BUNDLE PATCH 12.2.1.4.240701	36791515	OMA	OIG	-	-
OIM BUNDLE PATCH 12.2.1.4.240705	36807639	OMA	OIG	-	-
ODU BUNDLE PATCH 12.2.1.4.240603	36690369	-	-	ODU	-
ADF BUNDLE PATCH 12.2.1.4.240605	36700543	OAM	OIG	ODU	OID
SOA Bundle Patch 12.2.1.4.240605	36697785	-	OIG	-	-
WebCenter Core Bundle Patch 12.2.1.4.240617	36741053	-	OIG	-	-

Customers upgrading from Oct'22 IDM SPB or earlier, please note:

From July 2024 Bundle Patch cycle, the underlying DB Client in OID 12.2.1.4 ORACLE HOME should be updated to 19.23 version.

This update is delivered via the following patches:

- DB Client 19c Installer - 34761383
- DB Client 19.23 - 36392269
- OSS 19c BP - 36706228
- OID BP - 34947852

IDM SPB 12.2.1.4_<VERSION> includes all the above-mentioned deliverables (along with other OID dependent patches) and helps in installing the updates.

The SPBAT utility (in the PreStop phase) will detect DB Client version in OID Home and if the DB Client version is found to be 12c (12.1.0.2 series), the SPBAT PreStop phase will fail. In the SPBAT execution log, we will see the recommendation to update DB Client to 19c (12.2.1.19.0) version.

Sample snippet of SPBAT PreStop execution log:

```
[FAILED] Environment has not met the minimum DBClient version(Database_Client
12.2.1.19.0) requirement.Please perform the following steps
```

```
1)Shutdown all IDM services running on oid12214ga19cdbserv4dbpsu
```

```
2)Take a backup of MW_HOME : /scratch/oseidmqa/MW/Oracle and the
CENTRAL_INVENTORY: /scratch/oseidmqa/oraInventory
```

3) Run following script to upgrade dbclient

```
/scratch/oseidmqa/IDM_SPB_12.2.1.4_<VERSION>/tools/spbat/generic/SPBAT/logs/  
oid12214ga19cdbserv4dbpsu_oid_12.2.1.4_<VERSION>/preCheck/dbclient/  
dbclient_upgrade.sh
```

OSS Bundle Patch and OID Bundle Patch will be updated via the SPBAT Downtime phase update.

7

SPB usage Instructions

To run the SPBAT utility, navigate to the `IDM_SPB_12.2.1.4_<VERSION>/tools/spbat/generic/SPBAT/` directory.

The SPBAT utility usage and execution steps are as follows:

- To get usage details on the command line, enter:

```
[Unix]
./spbat.sh
```

```
[Windows]
spbat.bat
```

- To obtain SPBAT utility version, enter:

```
./spbat.sh -version
```

- To apply the patches using SPBAT utility, enter:

```
[Unix]
./spbat.sh -type <install_type> -phase <phase> -mw_home <mw_home> -
spb_download_dir <spb_download_dir> -log_dir <log_dir>
```

```
[Windows]
spbat.bat -type <install_type> -phase <phase> -mw_home <mw_home> -
spb_download_dir <spb_download_dir> -log_dir <log_dir>
```

Here:	
-install_type:	The install type or IDM component, such as oam/oig/oud/oid.
-phase:	The various phases of applying the patch, such as PreStop/Downtime/PostStart.
-mw_home:	The path to Oracle Home directory.
-spb_download_dir:	The path to IDM_SPB_12.2.1.4_<VERSION> stage location directory.
-log_dir (optional):	The path to log_dir directory, this is where you want logs to go on your file system. The default directory is created under IDM_SPB_<VERSION>/tools/spbat/generic/SPBAT/logs location, or you can set your

	own location which exists and has "write" access.
-verbose (optional):	To be set to "true" or "false" value. This is to display additional information on the default output stream (STDOUT).
-force (optional and applicable for PreStop phase):	To be set to "true" or "false" value. When set to "true", it forces performing all the validations.

- To know the status of SPBAT anytime once the patching has started, enter:

```
[Unix]
./spbat.sh -status report -type <install_type> -mw_home <mw_home> -log_dir
<log_dir>
```

```
[Windows]
spbat.bat -status report -type <install_type> -mw_home <mw_home> -log_dir
<log_dir>
```

Here:	
-report:	is a constant implying status report.
-install_type:	refers to install type, such as oam/oig/oud/oid.
-mw_home:	is the path to Oracle Home directory.
-log_dir (optional):	The path to log_dir directory, this is where you want logs to go on your file system. The default directory is created under IDM_SPB_<VERSION>/tools/spbat/generic/SPBAT/logs location, or you can set your own location which exists and has "write" access.

Important Note for Windows users: Please open the Command Prompt as Administrator and execute the spbat.bat script for patching.

8

Phases in the Patching Process

Once the steps described in section [Prerequisites](#) are completed, the sequences of phases in applying the SPB patches using SPBAT utility on the IDM 12.2.1.4 installed environment are:

a. PreStop	Run the SPBAT utility for the PreStop phase to evaluate the environment prior to patching. Verify the html report summary and refer to the logs and reports, if needed. This phase can be run while the services, instances and/or servers are up and running.
b. Stop Services	Stop all IDM related services (including WebLogic Servers) running on IDM hosts.
c. Backup	Create a cold backup of the entire ORACLE_HOME and DOMAIN_HOME directories.
d. Downtime Patching	Run the SPBAT utility for the Downtime phase.
e. Start Services	Start all IDM related services (including WebLogic Servers) running on IDM hosts, and make sure these are up and running.
f. PostStart	Run the SPBAT utility for the PostStart phase.
g. Complete Validation	Once the SPB patching activity is complete, verify the environment and URLs.

For detailed information about the steps in the execution phases, please refer to section "8 Applying the SPB Patches using SPBAT".

Applying the SPB Patches using SPBAT

After completing the steps described in section [Prerequisites](#), follow the next steps to apply the SPB patches in the IDM 12.2.1.4 environment:

PreStop:

To be done on all IDM hosts, as described in section [System Overview](#):

1. Run the SPBAT utility with appropriate options for the PreStop phase based on the install type:
[Unix - Please open the bash shell and execute]

```
cd IDM_SPB_12.2.1.4.<VERSION>/tools/spbat/generic/SPBAT
./spbat.sh -type <oam/oig/oud/oid> -phase prestop -mw_home <path to
mw_home> -spb_download_dir <path to IDM_SPB_12.2.1.4.<VERSION> stage
location> -log_dir <log_dir>
```

[Windows - Please open the Command Prompt as Administrator and execute]

```
cd IDM_SPB_12.2.1.4.<VERSION>\tools\spbat\generic\SPBAT
spbat.bat -type <oam/oig/oud/oid> -phase prestop -mw_home <path to
mw_home> -spb_download_dir <path to IDM_SPB_12.2.1.4.<VERSION> stage
location> -log_dir <log_dir>
```

2. Perform the following after running the script:
 - a. Review the html reports before proceeding with the next phase. The analysis reports are generated under <log_dir>/<hostname_type>patch_log_dir/spbat-logs/reports location.
 - b. Upgrade OPatch after creating a full backup of ORACLE_HOME if the minimum OPatch version requirement is not met.
 - c. If there are any issues that need to be addressed, you can run the **PreStop** phase again but will need to create and use a new logs directory prior to doing so.
 - d. If no issues are found, for Downtime and **PostStart** phases please use the same log directory as in the **Prestop** phase.
3. For IDM cluster, repeat steps 1 and 2 on each VM. Make sure that the patching user and ORACLE_HOME install user/owner are same to avoid permission issues.
4. If two or more install types share the same ORACLE_HOME, then repeat steps 1 and 2 against ORACLE_HOME for each install type.

Stop Services:

1. Stop all IDM related services (including WebLogic servers) running on IDM hosts.
2. Make sure that no services are accessing the ORACLE_HOME binaries.

Backup:

1. Create a complete backup of ORACLE_HOME and DOMAIN_HOME locations.
2. Create a cold backup of the entire IDM setup by using standard backup software/utilities.
3. Create a backup of the database.

Downtime Patching:

To be done on all IDM hosts, as described in section [System Overview](#):

1. Run the SPBAT utility with appropriate options for the Downtime phase based on the install type:
[Unix - Please open the bash shell and execute]

```
cd IDM_SPB_12.2.1.4.<VERSION>/tools/spbat/generic/SPBAT
./spbat.sh -type <oam/oig/oud/oid> -phase downtime -mw_home <path to
mw_home> -spb_download_dir <path to IDM_SPB_12.2.1.4.<VERSION> > -log_dir
<log_dir>
```

[Windows - Please open the Command Prompt as Administrator and execute]

```
cd IDM_SPB_12.2.1.4.<VERSION>\tools\spbat\generic\SPBAT
spbat.bat -type <oam/oig/oud/oid> -phase downtime -mw_home <path to
mw_home> -spb_download_dir <path to IDM_SPB_12.2.1.4.<VERSION> > -log_dir
<log_dir>
```

2. Perform the following after running the script:
 - a. In case of any failure, review the patching logs before proceeding to next steps.
3. Perform appropriate Post-Install and Configuration steps before the servers are started up:
 - a. OAM - Please refer to item **A. Before Server Startup** of section [Post-Install and Configuration Steps - OAM](#) in this document.
 - b. OIG - Please refer to item **A. Before Server Startup** of section [Post-Install and Configuration Steps - OIG](#) in this document.
 - c. OUD - Please refer to item **A. Before Server Startup** of section [Post-Install and Configuration Steps - OUD](#) in this document.
 - d. OID - Please refer to item **A. Before Server Startup** of section [Post-Install and Configuration Steps - OID](#) in this document.
4. For IDM cluster, repeat steps 1 and 2 on each VM. Make sure that the patching user and ORACLE_HOME install user/owner are the same to avoid permission issues.
5. If two or more install types share the same ORACLE_HOME, then repeat steps 1,2 and 3 against ORACLE_HOME for each install type.

Start Services:

Start all IDM related services (including WebLogic Servers) running on IDM hosts.

PostStart:

To be done on all IDM hosts, as described in section [System Overview](#):

1. Run the SPBAT utility with appropriate options for the PostStart phase based on the install type:

[Unix - Please open the bash shell and execute]

```
cd IDM_SPB_12.2.1.4.<VERSION>/tools/spbat/generic/SPBAT
./spbat.sh -type <oam/oig/oud/oid> -phase poststart -mw_home <path to
mw_home> -spb_download_dir <path to IDM_SPB_12.2.1.4.<VERSION> > -log_dir
<log_dir>
```

[Windows - Please open the Command Prompt as Administrator and execute]

```
cd IDM_SPB_12.2.1.4.<VERSION>\tools\spbat\generic\SPBAT
spbat.bat -type <oam/oig/oud/oid> -phase poststart -mw_home <path to
mw_home> -spb_download_dir <path to IDM_SPB_12.2.1.4.<VERSION> > -log_dir
<log_dir>
```

2. After running the script, review the patching logs generated under /patch_log_dir/spbat-logs for any failures.
3. Perform appropriate Post-Install and Configuration steps after the servers are started up:
 - a. OAM - Please refer to item "B. After Server Startup" of section "9 Post-Install and Configuration Steps - OAM" in this document
 - b. OIG - Please refer to item "B. After Server Startup" of section "10 Post-Install and Configuration Steps - OIG" in this document
 - c. OUD - Please refer to item "B. After Server Startup" of section "11 Post-Install and Configuration Steps - OUD" in this document
 - d. OID - Please refer to item "B. After Server Startup" of section "12 Post-Install and Configuration Steps - OID" in this document
4. For IDM cluster, repeat steps 1 and 2 on each VM. Make sure that the patching user and ORACLE_HOME install user/owner are the same to avoid permissions issues.
5. If two or more install types share the same ORACLE_HOME, then repeat steps 1,2 and 3 against ORACLE_HOME for each install type.

Complete Validation:

Once the SPB patching activity is completed, restart and verify the environment and URLs.

Post-Install and Configuration Steps - OAM

Following are the post-install and configuration steps which are required to be performed after Downtime phase once the OAM binaries are applied using OPatch:

A. Before Server Startup

After applying patches, clear out the contents of any `cache/tmp/stage` directories which exist in all `$DOMAIN_HOME/servers/<SERVER_NAME>` locations, prior to restarting.

B. After Server Startup

There are no post-install and configuration actions to be performed currently.

Post-Install and Configuration Steps - OIG

Following are the post-install and configuration steps which are required to be performed after Downtime phase once the OIG binaries are applied using OPatch:

A. Before Server Startup

After applying patches, clear out the contents of any `cache/tmp/stage/dc` directories which exist in all `$DOMAIN_HOME/servers/<SERVER_NAME>` locations, prior to restarting.

B. After Server Startup

1. Update `$OIM_ORACLE_HOME/server/bin/patch_oim_wls.profile` file.
For detailed instructions, please refer to the section *Stage 2: Filling in the patch_oim_wls.profile File* in `IDM_SPB_12.2.1.4.<VERSION>/etc/OIG_Bundle_Patch_Readme.html`.
2. Execute `$OIM_ORACLE_HOME/server/bin/patch_oim_wls.sh` script.

Post-Install and Configuration Steps - OUD

Following are the post-install and configuration steps which are required to be performed after Downtime phase once the OUD binaries are applied using OPatch:

A. Before Server Startup

After applying patches, clear out the contents of any `cache/tmp/stage` directories which exist in all `$DOMAIN_HOME/servers/<SERVER_NAME>` locations, prior to restarting.

B. After Server Startup

There are no post-install and configuration actions to be performed currently.

13

Post-Install and Configuration Steps - OID

There are no post-install and configuration actions to be performed currently.

Troubleshooting

1. If the minimum OPatch version requirement is not met, then upgrade the OPatch after creating a full backup of `ORACLE_HOME`.
2. If you encounter an error in roll-back of OID one-off patch, please refer to [Doc ID 2944818.1](#) for further details.
3. As more and more patches are applied, OPatch backs up subset patches in the `ORACLE_HOME/.patch_storage` directory to facilitate a rollback. This might result in performance issues. If you observe such performance issues, please refer to [Doc ID 2942050.1](#) for further details.
4. If you encounter any errors during any phase of applying the patch, contact Oracle Support.

Limitations

1. The SPBAT utility automates the binary patch apply for the patches that are obtained through the SPB bundle only. It excludes the configuration actions and server restart operations.
2. The SPBAT utility does not handle the start, stop, and post-patching configuration operations of the servers. The user can use either custom startup/shutdown scripts or the ones available with the product. The post-patching configuration operations, if any, must be manually performed, as documented in the `SPB README.html`.
3. The SPBAT utility supports only IDM 12.2.1.4 and 12.2.1.3 versions deployed on `LinuxX86-64`, `SOLARIS_SPARC64`, `SOLARIS64(x86)`, `WINDOWS64` platforms.
4. The SPBAT utility has minimalistic error handling, and it relies on the correctness of the input values provided by the user while using the tool.
5. The SPBAT utility does not create any backup of the environment/application/configuration/data prior to individual patching of the product or component.
6. The SPBAT utility does not provide rollback support. For any issues, use the backups (created before Downtime phase) to restore the environment. However, while applying SPB, existing one-offs present in the `ORACLE_HOME` can be rolled back. Manually review the `ORACLE_HOME` inventory and re-apply any one-offs that might have been rolled back during the application of IDM SPB.