

Oracle Cloud Native Environment

Release Notes for Release 2



F96191-06
March 2025



Oracle Cloud Native Environment Release Notes for Release 2,
F96191-06

Copyright © 2024, 2025, Oracle and/or its affiliates.

Contents

Preface

Documentation License	iv
Conventions	iv
Documentation Accessibility	iv
Access to Oracle Support for Accessibility	iv
Diversity and Inclusion	iv

1 CVE and Bug Fix Updates

2 Component Versions

3 New Features and Notable Changes

Release 2.1.1	3-1
Release 2.1.0	3-1
Release 2.0.5	3-1
Release 2.0.4	3-2
Release 2.0.2	3-2
Release 2.0.1	3-2
Release 2.0.0	3-2

4 Documentation Changes

Release 2	4-1
-----------	-----

Preface

This document contains information about Oracle Cloud Native Environment (Oracle CNE). It includes information on component versions, new features, documentation changes, and known issues for Oracle CNE.

Documentation License

The content in this document is licensed under the [Creative Commons Attribution–Share Alike 4.0 \(CC-BY-SA\)](#) license. In accordance with CC-BY-SA, if you distribute this content or an adaptation of it, you must provide attribution to Oracle and retain the original copyright notices.

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <https://www.oracle.com/corporate/accessibility/>.

Access to Oracle Support for Accessibility

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <https://www.oracle.com/corporate/accessibility/learning-support.html#support-tab>.

Diversity and Inclusion

Oracle is fully committed to diversity and inclusion. Oracle respects and values having a diverse workforce that increases thought leadership and innovation. As part of our initiative to build a more inclusive culture that positively impacts our employees, customers, and partners, we are working to remove insensitive terms from our products and documentation. We are also

mindful of the necessity to maintain compatibility with our customers' existing technologies and the need to ensure continuity of service as Oracle's offerings and industry standards evolve. Because of these technical constraints, our effort to remove insensitive terms is ongoing and will take time and external cooperation.

1

CVE and Bug Fix Updates

Describes how to find information about CVE and bug fix updates in Oracle Cloud Native Environment (Oracle CNE).

Product enhancements, Common Vulnerabilities, and Exposures (CVEs) and bug fix updates are available for Oracle CNE as described in [Oracle Linux: Product Life Cycle Information](#).

Notices for Common Vulnerabilities and Exposures (CVEs) and bug fix updates for Oracle CNE are available on the Unbreakable Linux Network at:

<https://linux.oracle.com/errata>

You can subscribe to the `el-errata@oss.oracle.com` email list to receive these notices via email at:

<https://oss.oracle.com/mailman/listinfo/el-errata>

All Oracle CNE CVE and bug fix update notices are listed on ULN and on the email list mentioned, and aren't included in this document.

You might also find it helpful to check the list of new and updated packages posted on the Oracle Linux yum server available at:

<https://yum.oracle.com/whatsnew.html>

Changes and bug fixes for the Oracle CNE Command Line Interface (CLI) are also listed on the GitHub project at:

<https://github.com/oracle-cne/ocne/releases>

2

Component Versions

Describes the version information for components included with Oracle CNE.

Oracle Container Host for Kubernetes Image

Kubernetes Release 1.31 is included with Oracle CNE Release 2.1.

The Oracle Container Host for Kubernetes (OCK) image includes both the host Oracle Linux OS, and the Kubernetes software distribution. The OCK image is distributed on the Oracle Container Registry.

A bootable container image, in the Qcow2 format, is available at:

`container-registry.oracle.com/olcne/ock`

An OSTree commit based container image, is available at:

`container-registry.oracle.com/olcne/ock-ostree`

Both images use the container label for the Kubernetes version they match, for example, 1.31.

Kubernetes minor and patch updates are provided with updated container images. For information on updating Kubernetes, see [Oracle Cloud Native Environment: Kubernetes Clusters](#).

Application Catalog

A list of the cloud native applications available in the Oracle CNE application catalog for each release is available on the Oracle CNE GitHub project at:

<https://github.com/oracle-cne/catalog/>

CLI

A list of the available versions of the Oracle CNE Command Line Interface (CLI) is available on the Oracle CNE GitHub project at:

<https://github.com/oracle-cne/ocne/releases>

If you have the CLI installed, you can see the version number using the `ocne info` command:

```
ocne info
```

To update to the latest CLI, use:

```
sudo dnf update ocne
```

3

New Features and Notable Changes

Lists the new features and notable changes Oracle CNE releases.

This chapter lists the new features and notable changes in each Oracle CNE release. For more details on bug fixes and other changes, see the release information on the [Oracle CNE GitHub](#) page.

Release 2.1.1

This section lists the notable changes in Release 2.1.1 of Oracle CNE.

CLI

The CLI is updated to Release 2.1.1.

OCI Configuration Option

The OCI provider has a new configuration option to set the connection profile to use in the OCI CLI configuration file. This improvement means you can have more than one connection profile in the OCI CLI configuration file and set it in a cluster configuration file. For information on the CLI configuration file options for the OCI provider, see [Oracle Cloud Native Environment: Kubernetes Clusters](#).

IPv6

Kubernetes clusters can be provisioned using IPv6 and IPv6/IPv4 dual stack configurations.

Release 2.1.0

This section lists the notable changes in Release 2.1.0 of Oracle CNE.

Kubernetes

Kubernetes is updated to Release 1.31.

CLI

The CLI is updated to Release 2.1.

OCI Cluster Upgrades

Kubernetes can be upgraded in OCI clusters using the Kubernetes Cluster API. This method provisions new nodes, running an updated OCK image, that includes an updated version of Kubernetes. Old nodes are then scaled out. In place upgrades are also available for situations where the compute instance must remain the same. For information on upgrading clusters, see [Oracle Cloud Native Environment: Kubernetes Clusters](#).

Release 2.0.5

This section lists the notable changes in Release 2.0.5 of Oracle CNE.

CLI information

A new `ocne info` command is added to show information about the CLI, including the release number and environment variable values that are used by the CLI. For more information on the `ocne info` command, see [Oracle Cloud Native Environment: CLI](#).

Default configuration file

A new `OCNE_DEFAULTS` environment variable is available to set the location of the default configuration file. This might be useful when testing using different default configuration settings. For more information on the environment variables used by the CLI, see [Oracle Cloud Native Environment: CLI](#).

Cluster dump options

The `ocne cluster dump` command is updated to include new options. The `--json` option dumps cluster resources in JSON format, instead of the default YAML. The `--managed` option dumps cluster resources as managed fields so that Kubernetes can track changes to those resources. For more information on the `ocne cluster dump` command, see [Oracle Cloud Native Environment: CLI](#).

Release 2.0.4

This section lists the notable changes in Release 2.0.4 of Oracle CNE.

OCI provider

Including the Virtual Cloud Network and load balancer subnets in a cluster configuration file is no longer required. The CLI detects these values automatically, if possible. For more information the OCI provider, see [Oracle Cloud Native Environment: Kubernetes Clusters](#).

Release 2.0.2

This section lists the notable changes in Release 2.0.2 of Oracle CNE.

Application updates

The `ocne application update` command is updated to include new options. The `--reset-values` option resets the values to the ones built into the chart. The `--catalog` option sets the name of the catalog that contains the application. For more information the `ocne application update` command, see [Oracle Cloud Native Environment: CLI](#).

Release 2.0.1

This section lists the notable changes in Release 2.0.1 of Oracle CNE.

Cluster console

The `ocne cluster console` command is updated to include new options. The `--direct` option starts the console `chrooted` to the root of the target node's file system. The `--` option runs a command on the console and returns the results. For more information the `ocne cluster console` command, see [Oracle Cloud Native Environment: CLI](#).

Release 2.0.0

Release 2.0.0 of Oracle CNE provides a new way of creating and managing Kubernetes clusters, compared to previous releases. This section lists new features introduced in this release.

Kubernetes

Kubernetes is updated to Release 1.30.

CLI

The Oracle CNE Command Line Interface (CLI) is the command line tool to create and manage Kubernetes clusters in Oracle CNE. The CLI (`ocne` command) includes a help system to show all command options, and a set of configuration files at various levels to configure the environment and Kubernetes clusters.



Note:

This is a new CLI and isn't backwardly compatible with the CLI (`olcnectl`) in previous releases.

For more information on using the CLI, see [Oracle Cloud Native Environment: CLI](#).

Oracle Container Host for Kubernetes (OCK) Images

Oracle CNE includes a CLI that can manage the life cycle of Kubernetes clusters, using OSTree based container images. The container image includes both the host Oracle Linux OS, and the Kubernetes software distribution. The image is deployed to hosts or Virtual Machines (VMs) to create nodes in a Kubernetes cluster. This image is referred to in this documentation as the Oracle Container Host for Kubernetes (OCK) image.

The OCK image is distributed on the Oracle Container Registry in the following formats:

Bootable image

This is a container image in the Qcow2 format, available at:

`container-registry.oracle.com/olcne/ock`

The bootable image contains a single VM image in the Qcow2 format, and is used to create boot media for virtualized platforms. This image is used as the boot media for clusters created with the libvirt and OCI providers.

By default, the image is configured to work with the libvirt provider. A conversion of the boot image to the appropriate format for OCI can be performed automatically when you upload the image to OCI.

OSTree image

This is an OSTree commit based container image, available at:

`container-registry.oracle.com/olcne/ock-ostree`

This image is used as the basis for an OSTree archive for customized installations using the Bring Your Own provider.

This image is also used for updating cluster nodes to stage patch updates, and to update to the next Kubernetes minor release.

For information on OSTree containers, see the [upstream OSTree documentation](#).

For more information on the OCK image, see [Oracle Cloud Native Environment: Kubernetes Clusters](#).

Cluster Providers

Oracle CNE includes the following providers, which use the OCK image to create Kubernetes clusters:

libvirt Provider

The libvirt provider can be used to provision clusters in a Kernel-based Virtual Machine/QEMU (KVM) environment. This is the default provider.

OCI Provider

The OCI provider can be used to create clusters on OCI. This provider uses the Kubernetes Cluster API to provision the clusters.

Bring Your Own Provider

The Bring Your Own provider can be used to create clusters on bare metal or other virtual instances, not provided explicitly by Oracle CNE.

For information on using these providers to create clusters, see [Oracle Cloud Native Environment: Kubernetes Clusters](#).

Application Catalogs

Oracle CNE provides application catalogs for deploying Cloud Native applications into a Kubernetes cluster.

An application catalog is a searchable collection of software that can be installed into a Kubernetes cluster. Installed catalogs can be searched using both the Oracle CNE Command Line Interface (CLI) and the User Interface (UI).

An application catalog is set up in two flavors: a Helm repository, and a service that's compatible with Artifact Hub (an external catalog). The Oracle catalog is a Helm repository, while an external catalog typically points to artifacthub.io and is compatible with Artifact Hub.

For information on using application catalogs and installing applications into a cluster, see [Oracle Cloud Native Environment: Applications](#).

Web-Based UI

The Oracle CNE UI provides a web-based interface to manage the maintenance and installation of Kubernetes cluster resources, and applications.

The UI is based on the open source Kubernetes UI Headlamp application. For more information on the Headlamp project, see the [upstream Headlamp documentation](#).

For information on installing the UI, see [Oracle Cloud Native Environment: Kubernetes Clusters](#) and for information on using the UI to install applications, see [Oracle Cloud Native Environment: Applications](#).

4

Documentation Changes

Lists the notable changes to the Oracle CNE documentation.

This chapter lists notable changes to the Oracle CNE documentation.

Release 2

A new set of documents are provided in this release. The document list for this release is:

Oracle Cloud Native Environment: Release Notes

This document provides an overview of the new features introduced in Oracle CNE.

Oracle Cloud Native Environment: Concepts

This document provides an overview of the different components of Oracle CNE and explains key concepts that are essential to working with Oracle CNE.

Oracle Cloud Native Environment: Quick Start

This document guides you through creating a Kubernetes cluster using the Oracle CNE CLI (CLI) with the default `libvirt` provider. It also covers installing applications from the default Oracle application catalog, and accessing the web-based Oracle CNE UI.

Oracle Cloud Native Environment: Kubernetes Clusters

This document covers using the Oracle Container Host for Kubernetes (OCK) image to create and manage Kubernetes clusters with the cluster providers. The book also shows how you can use cluster templates and configuration files to create customized clusters. Administration operations, such as updating Kubernetes clusters with the latest OCK images, are also included.

Oracle Cloud Native Environment: CLI

This document provides information on how to install and use the CLI. The document provides a CLI command reference with syntax and usage examples, and also shows how to set options in YAML configuration files to customize the CLI and clusters.

Oracle Cloud Native Environment: Applications

This document covers the different aspects of application management, for example searching for, installing, and updating applications, hosted in the Oracle Catalog, into a Kubernetes cluster. The document covers using both the CLI and the UI to perform these tasks.

Oracle Cloud Native Environment: Kubernetes

This document provides introductory information on the architecture of Kubernetes. It also includes an entry level tutorial on using Kubernetes and Kata Containers.

Oracle Cloud Native Environment: Oracle Container Host for Kubernetes Image Builder

This document includes information on the Oracle Container Host for Kubernetes Image Builder (OCK Image Builder). This is a tool that builds bootable media for Oracle Container Host for Kubernetes (OCK), based on a treefile configuration.