

Oracle Linux 9

Release Notes for Oracle Linux 9.8



G53138-01
June 2026



Oracle Linux 9 Release Notes for Oracle Linux 9.8,

G53138-01

Copyright © 2026, Oracle and/or its affiliates.

Documentation License

The content in this document is licensed under the [Creative Commons Attribution–Share Alike 4.0](#) (CC-BY-SA) license. In accordance with CC-BY-SA, if you distribute this content or an adaptation of it, you must provide attribution to Oracle and retain the original copyright notices.

Contents

1 About Oracle Linux 9

System Requirements and Limitations	1
Available Architectures	1
Shipped Kernels	1
About the Unbreakable Enterprise Kernel	2
User Space Compatibility	2
Obtaining Installation Images	2
Upgrading From Previous Oracle Linux Releases	3
Upgrading From Previous Oracle Linux Update Releases	3

2 New Features and Changes

Installation and Boot	1
UEK R8 Default Kernel Handling	1
Infrastructure Services	2
chrony rebased to version 4.8	2
valgrind rebased to upstream version 3.26.0	2
SystemTap is rebased to version 5.4	2
elfutils rebased to 0.194	2
sscg rebased to version 4.0.3	2
Security	2
AIDE rebased to 0.19.2	2
p11-kit-client.so separates to the p11-kit-client subpackage	2
OpenSSH provided in version 9.9	2
Valkey runs with the redis_t SELinux type	3
fapolicyd rebased to 1.4.5	3
CanonicalMatchUser in sshd_config prevents privilege escalation for capitalized AD usernames	3
GnuTLS rebased to 3.8.10	3
crypto-policies supports hybrid ML-KEM and pure ML-DSA in GnuTLS	3
/dev/papr-* devices have more specific SELinux labels	3
p11-kit rebased to 0.26.1	4
New package: clevis-pin-trustee	4
crypto-policies enables mlkem768x25519-sha256 for OpenSSH	4

OpenSCAP rebased to 1.3.13	4
SCAP Security Guide rebased to 0.1.80	4
Networking	4
iproute rebased to version 6.17.0	4
FRRouting 10 package introduced in Oracle Linux 9 AppStream repository	4
Unbound rebased to version 1.24.2	5
Kernel and System Libraries	5
crash rebased to 9.0.2	5
File Systems and Storage	5
cryptsetup rebased to version 2.8.0	5
snapm rebased to 0.7.0	5
High Availability and Clusters	5
HAProxy rebased to 2.8	5
Dynamic Programming Languages, Web and Database Servers	5
A new module stream: postgresql:18	5
A new module stream: mariadb:11.8	6
New ruby:4.0 runtime module stream with database connectors	6
The mysql:8.4 module now includes the perl-DBD-MySQL package	6
New Python 3.14 stack is available	6
Compilers and Development Tools	6
Rust Toolset is rebased to version 1.92.0	6
Rebase llvm toolset to version 21	6
Containers	6
container-selinux rebased to version 2.245.0-1	6
Cockpit Web Console	7
cockpit rebased to version 356	7
Identity and Authentication	7
samba rebased to 4.23.0	7
ipa rebased to 4.13.0	7
cepces rebased to 0.3.12	7
pki rebased to 11.7.1	7
ansible-freeipa rebased to 1.16.0	7
389-ds-base rebased to 2.8.0	7
sudo rebased to sudo-1.9.17p2	7
Operating System and Software Management	8
librepo rebased to 1.19.0	8
Shells and Command Line Tools	8
Security and TLS improvements in openwsman 2.8.1	8
openCryptoki rebased to 3.26.0	8
Oracle build of OpenJDK 25 available in Oracle Linux 9	8

3 Technology Preview

Security	1
KTLS	1
QUIC Protocol in OpenSSL	1
io_uring Asynchronous I/O Interface	1
Infrastructure Services	2
Socket API for TuneD	2
Networking	2
gpsd-minimal	2
WireGuard	2
systemd-resolved Service	2
PRP and HSR	2
IPsec Packet Offloading	3
Various Modem Network Drivers	3
Segment Routing Over IPv6	3
Kernel	3
Soft iWarp	3
File Systems and Storage	3
nvme-stas Package	3
Compilers and Development Tools	4
jmc-core and owasp-java-encoder	4
Flexible Array Conversion Warning-Suppression in libabigail Available As a Technology Preview	4
Virtualization	4
Nested VMs	4
SEV and SEV-ES	4

4 Deprecated Features

Installation	1
Kickstart Commands	1
initial-setup Package	1
inst.geoloc Boot Option Values provider_hostip And provider_fedora_geoip	1
Anaconda Screenshots	1
Anaconda Help	2
Software Management	2
DNF debug plugin	2
DNF libreport	2
Shell and Command Line	2
dump Utility	2
Bacula Sqlite Backend Database	2
TMPDIR Variable in the ReaR Configuration File	2

Security	3
Unprivileged Access to dmesg Output	3
OVAL Data Format	3
Using update-ca-trust Without Arguments	3
Configuring STunnel Clients to Use the Trusted Root CA Files	3
NSS Deprecated Algorithms	3
pam_ssh_agent_auth	3
scap-workbench	3
oscap-anaconda-addon	3
/etc/system-fips	4
libcrypt.so.1	4
SHA-1 Algorithm	4
SCP Protocol	4
OpenSSL Cryptographic Algorithms	4
Digest-MD5	5
/etc/system-fips File	5
libcrypt.so.1	5
fapolicyd.rules File	5
OpenSSL RSA Encryption Without Padding	5
OpenSSL Engines API	5
openssl-pkcs11	6
Networking	6
Soft-iWarp	6
Network Teams	6
dhcp-client Package	6
firewalld Lockdown	6
/etc/sysconfig/network-scripts File	6
iptables Framework	6
PF_KEYv2 Kernel API	7
Network Manager nmcli Language Changes	7
TigerVNC	7
Kernel	7
crashkernel=auto Option	7
Asynchronous Transfer Mode	8
kexec_load in kexec_tools	8
cgroupsv1	8
File Systems and Storage	8
lsscsi NVMe	8
sg3_utils NVMe	8
lvm2-activation-generator	8
PMDK Library	9
md-linear and md-faulty MD RAID Kernel Modules	9

Virtual Data Optimizer Parameters in sysfs	10
High Availability	10
Several Pacemaker Configuration Options	10
Dynamic Programming Languages, Web and Database Servers	10
Berkeley DB (libdb)	10
Compilers and Development	11
Redis in Grafana, PCP, and grafana-pcp	11
llvm-doc HTML Content	11
Keys Smaller Than 2048-bits in OpenSSL	11
Some PKCS1 v1.5 modes	11
32-bit multilib Linking	11
Identity Management and Authentication	11
PAM Console	11
BDB backend (in 389-ds-base)	11
sss_ssh_knownhostsproxy	11
libsss_simpleifp	12
SSSD Files Provider	12
OpenLDAP Utility Options	12
nsslapd-idlistscanlimit Parameter and Default Value	12
SMB1 Protocol	12
Virtualization	12
Signatures Using SHA-1	13
Virtual Machine Manager	13
Virtual Machine Snapshots	13
libvirtd Daemon	13
Virtual Floppy Driver	13
qcow2-v2 Format	13
Legacy CPU Models	13
RDMA-based Live Migration	13
Windows 8 and Windows Server 2012 Guest Operating System	14
NIC Device Drivers for iPXE	14
Intel vGPU	14
pmem Device Passthrough	14
Containers	14
containers.conf for System Connections	15
slirp4net	15
cgroupsv1 in Rootless Containers	15
runc Container Runtime	15
pasta as a Network Name	15
BoltDB Database Backend	15
Oracle Linux 9 Containers on Oracle Linux 7 Hosts	15
SHA-1 Algorithm Within Podman	15

CNI Network Stack	15
Deprecated Packages	16

5 Known Issues

Installation Issues	1
(aarch64) Minimum XFS File System Size During Install Is 300 MB	1
Virtualization Issues	1
KVM Virtual Machines Panic When Started on Oracle Linux 9 Hosts	1
Virtual Machines Fail to Start at Boot Because the virbr0 Interface Isn't Available	2
Kernel Issues	2
Kdump Might Fail on Some AMD Hardware	2
(aarch64) Some GUI Elements Aren't Displayed During Installation and Boot Using VGA Output	2
Certain SEV Guest Configurations Might Cause Hypervisor CPU Soft-Lockup Warnings	3
Systems With Btrfs Fail to Boot in FIPS Mode	3

6 Package Changes From the Upstream Release

Changes to Binary Packages	1
Added Binary Packages for BaseOS by Oracle	1
Added Binary Packages for AppStream by Oracle	2
Added Binary Packages for CodeReady Linux Builder by Oracle	3
Modified BaseOS Binary Packages	3
Modified Binary Packages for CodeReady Linux Builder by Oracle	15
Modified AppStream Binary Packages	19
Removed BaseOS Binary Packages	42
Removed AppStream Binary Packages	44
Removed CodeReady Linux Builder Binary Packages	47
Changes to Source Packages	48
Added Source Packages for BaseOS by Oracle	48
Added Source Packages for AppStream by Oracle	48
Modified BaseOS Source Packages	49
Modified AppStream Source Packages	51
Modified Source Packages for CodeReady Linux Builder by Oracle	55
Removed BaseOS Source Packages	56
Removed AppStream Source Packages	56

Preface

[Oracle Linux 9: Release Notes for Oracle Linux 9.8](#) provides information about the new features and known issues in the Oracle Linux 9.8 release. The information applies to both x86_64 and 64-bit Arm (aarch64) architectures. This document might be updated after first publication.

1

About Oracle Linux 9

The current Oracle Linux 9 release contains new features and enhancements that improve performance in different areas including automation and management, security and compliance, container management, and developer tools. These enhancements are especially designed to make the OS adaptable to different types of deployment such as on-premises installations, hybrid deployments that combine on-premises and cloud installations, and full cloud deployment.

Important

Upgrading from an Oracle Linux Developer Preview release to its later official version is not supported. If you're running the Developer Preview version, you must reinstall the official Oracle Linux release upon its general availability.

System Requirements and Limitations

To check whether a specific hardware is supported on the current Oracle Linux 9 release, see the Hardware Certification List at <https://linux.oracle.com/hardware-certifications>. Note that as hardware becomes available and validated, the hardware is added to the list.

CPU, memory, disk and file system limits for all Oracle Linux releases are described in [Oracle Linux: Limits](#).

Available Architectures

The release is available for installation on the following platforms:

- Intel® 64-bit (x86_64) (x86-64-v2)
- AMD 64-bit (x86_64) (x86-64-v2)
- 64-bit Arm (aarch64) (Arm v8.0-A)

The Arm platform runs only with Unbreakable Enterprise Kernel Release (UEK).

Shipped Kernels

For the x86_64 platform, the current Oracle Linux 9 release ships with the following kernel packages:

- **kernel-uek-6.12.0-203.76.7.3** (Unbreakable Enterprise Kernel 8 Update 2 (UEK 8U2)) (Default)
- **kernel-5.14.0-687.5.3** (Red Hat Compatible Kernel (RHCK))

For new installations, UEK 8 is automatically enabled and installed. It also becomes the default kernel on first boot.

In the case of updates, switching to UEK R8 isn't automatic. If you're upgrading from any prior update release of Oracle Linux 9 that has UEK R7 as default, the system continues to run with the kernel that's already installed. See [UEK R8 Default Kernel Handling](#) for more information.

For the aarch64 platform, Oracle Linux ships with the UEK kernel only.

The Oracle Linux release is tested as a bundle, as shipped on the installation media image. When installed from the installation media image, the kernel's version included in the image is the minimum version that's supported. Downgrading kernel packages isn't supported, unless recommended by Oracle Support.

For more information about kernel availability on Oracle Linux 9 releases, see <https://docs.oracle.com/en-us/iaas/oracle-linux/boot/boot-oracle-linux-kernel-reference-composite.htm#oracle%20linux%209>.

About the Unbreakable Enterprise Kernel

The Unbreakable Enterprise Kernel (UEK) is a Linux kernel built by Oracle and supported through Oracle Linux support. UEK is tested on Arm (aarch64), Intel® x86, and AMD x86 (x86_64) platforms. Each release contains added features, bug fixes, and updated drivers to provide support for key functional requirements, improve performance, and optimize the kernel for use on Oracle products such as Oracle's Engineered Systems, Oracle Cloud Infrastructure, and large enterprise deployments for Oracle customers.

Typically, a UEK release contains changes to the kernel ABI relative to a previous UEK release. These changes require recompilation of third-party kernel modules on the system. To minimize impact on interoperability during releases, the Oracle Linux team works with third-party vendors regarding hardware and software that have dependencies on kernel modules. Thus, before installing the latest UEK release, verify its support status with the application vendor.

The kernel ABI for a UEK release remains unchanged in all later updates to the initial release.

The kernel source code for UEK is available after the initial release through a public git source code repository at <https://github.com/oracle/linux-uek>.

For more information about UEK such as tutorials, notices, and release notes of different UEK versions, go to [Unbreakable Enterprise Kernel documentation](#).

User Space Compatibility

Oracle Linux maintains user space compatibility with Red Hat Enterprise Linux (RHEL) that's independent of the kernel version that underlies the OS. Existing applications in user space continue to run unmodified on UEK with no required recertifications for Oracle Linux certified applications.

Obtaining Installation Images

The following installation images for the current Oracle Linux 9 release are available:

- Full ISO of Oracle Linux for typical on-premises installations
- Boot ISO of Oracle Linux for network installations
- Boot ISO of the official UEK release for installing on hardware which is supported only on UEK
- Source DVDs

You can download these images from the following locations. Note that the images in these locations are for both the x86_64 and aarch64 platforms, unless indicated otherwise:

- Oracle Linux yum server at <https://yum.oracle.com/oracle-linux-downloads.html>
For more information managing and updating software on Oracle Linux systems, see [Oracle Linux: Managing Software on Oracle Linux](#).
- Oracle Software Delivery Cloud at <https://edelivery.oracle.com>

To prepare a downloaded image for installing Oracle Linux, see [Oracle Linux 9: Installing Oracle Linux](#).

Note

Aside from installation ISO images, you can also use Oracle Linux images to create compute instances on Oracle Cloud Infrastructure. For information about these images, see the release notes for the specific image that you're using on the [Oracle Cloud Infrastructure Documentation](#) page.

To use Oracle Linux on Oracle Cloud Infrastructure, see <https://docs.oracle.com/iaas/oracle-linux/home.htm>.

For information about the available ISO images for the three most recent updates to the Oracle Linux releases, see <https://yum.oracle.com/oracle-linux-isos.html>.

Upgrading From Previous Oracle Linux Releases

You can upgrade an Oracle Linux 8 system to the Oracle Linux 9 release by using the `leapp` utility.

For step-by-step instructions and information about any known issues that might arise when upgrading the system, see [Oracle Linux 9: Upgrading Systems With Leapp](#).

Upgrading From Previous Oracle Linux Update Releases

You can upgrade an Oracle Linux 9 system from a previous update level to the current update level by running the `sudo dnf update` command.

After performing a system update where many packages are updated, we recommend that you reboot the system. System functionality might become unstable if core packages are updated and the system isn't restarted to load the most recent updates. You can check whether a system requires a restart by running:

```
dnf needs-restarting -r
```

2

New Features and Changes

Unless indicated otherwise, the following new features, major enhancements, bug fixes, and other changes that are introduced in this release of Oracle Linux 9 apply to both the x86_64 and 64-bit Arm (aarch64) platforms.

Installation and Boot

The following features, enhancements, and changes related to installation and boot are introduced in this release of Oracle Linux 9.

UEK R8 Default Kernel Handling

If you're performing a fresh Oracle Linux 9.8 installation from an ISO image, then after the installation completes, the UEK R8 kernel is automatically enabled.

UEK R8 Update 2 includes many new features including security and performance enhancements. For more details, see [Unbreakable Enterprise Kernel 8 Update 2: Release Notes \(6.12.0-200\)](#).

If you select RHCK as the default kernel instead of UEK, ensure that you disable UEK yum repositories or ULN channels. For more information about switching to RHCK, see [Oracle Linux 9: Managing Kernels and System Boot](#).

In the case of updates, switching to UEK R8 isn't automatic. If you're upgrading from a prior update release of Oracle Linux 9, the system continues to run with the kernel that's already installed.

If the system is using UEK R7, you can upgrade to UEK R8 by using the following instructions:

- **Updating by using yum**

When you update to Oracle Linux 9.8, the previous kernel is preserved. At the same time, the UEK R8 yum repository is also added to the system yum configuration. To move to the latest kernel, run the following commands:

```
sudo dnf config-manager --disable ol9_UEKR7
sudo dnf config-manager --enable ol9_UEKR8
sudo dnf install -y kernel-uek
sudo dnf update
```

- **Updating by using ULN**

Similar to the previous scenario, the previous kernel is preserved. However, system subscriptions might change as a result. Sign in to <https://linux.oracle.com>, and update the system channel subscriptions to enable the `ol9_x86_64_UEKR8` or `ol9_aarch64_UEKR8`, as required. After you have updated the system channel subscriptions, run:

```
sudo dnf install -y kernel-uek
sudo dnf update
```

After setting the default kernel, you can further configure kernel boot parameters so that these parameters are applied at every system boot. For instructions, see [Oracle Linux 9: Managing Kernels and System Boot](#).

Infrastructure Services

The following features, enhancements, and changes related to infrastructure services are introduced in this Oracle Linux 9 release.

chrony rebased to version 4.8

The chrony packages are rebased to upstream version 4.8.

valgrind rebased to upstream version 3.26.0

The package is upgraded to version 3.26.0.

SystemTap is rebased to version 5.4

SystemTap is rebased to version 5.4.

elfutils rebased to 0.194

This package is upgraded to version 0.194.

sscg rebased to version 4.0.3

The sscg packages are rebased to upstream version 4.0.3.

Security

The following features, enhancements, and changes related to security are introduced in this Oracle Linux 9 release.

AIDE rebased to 0.19.2

The aide package, which provides the Advanced Intrusion Detection Environment (AIDE) utility, has been rebased to upstream version 0.19.2.

p11-kit-client.so separates to the p11-kit-client subpackage

The p11-kit-client.so module moves from the p11-kit-server subpackage to the new p11-kit-client subpackage. With the separated subpackages, you can install only the required parts and avoid redundant content on host systems or in containers.

OpenSSH provided in version 9.9

Oracle Linux 9.8 provides OpenSSH in version 9.9, which introduces many fixes and improvements over OpenSSH 8.7, which was provided in Oracle Linux 9.7.

Valkey runs with the redis_t SELinux type

Before this update, Valkey processes did not use the redis_t SELinux type. This caused behavioral inconsistencies with Redis in Oracle Linux 9. With this update, the SELinux policy has been enhanced to run Valkey as redis_t. As a result, Valkey processes align with Redis behavior, providing a consistent security context for these services in Oracle Linux 9 environments.

fapolicyd rebased to 1.4.5

The fapolicyd packages are rebased to upstream version 1.4.5 and provide many enhancements and bug fixes over the previous version.

CanonicalMatchUser in sshd_config prevents privilege escalation for capitalized AD usernames

This update of the openssh packages introduces the CanonicalMatchUser directive for the sshd_config configuration file. With the new directive, you can configure Match User blocks so that sshd first attempts to obtain the username from a password database instead of using an alias. As a result, Active Directory (AD) users can no longer bypass chroot restrictions when using capital letters in their usernames, which might lead to privilege escalation.

GnuTLS rebased to 3.8.10

The gnutls package is rebased to upstream version 3.8.10. This update introduces several enhancements and bug fixes.

crypto-policies supports hybrid ML-KEM and pure ML-DSA in GnuTLS

This update of the system-wide cryptographic policies adds support for hybrid ML-KEM (Module-Lattice-Based Key-Encapsulation Mechanism) and pure ML-DSA (Module-Lattice-Based Digital Signature) post-quantum (PQ) algorithms in GnuTLS. As a result, you can use GnuTLS in Oracle Linux 9.8 to negotiate TLS connections that use hybrid ML-KEM or pure ML-DSA as long as the other side supports them, and the PQ system-wide cryptographic subpolicy is applied.

/dev/papr-* devices have more specific SELinux labels

With this update of the selinux-policy packages, the following devices have more specific SELinux labels:

- /dev/papr-indices
- /dev/papr-physical-attestation
- /dev/papr-platform-dump

This aligns with the addition of new character device interfaces to the kernel, providing user-space application binary interface (ABI) access to the Power Architecture Platform Reference (PAPR) system parameters, in addition to the existing kernel-internal API.

As a result, the SELinux policy assigns distinct labels to these devices so that different permissions can apply to various services accessing them.

p11-kit rebased to 0.26.1

The p11-kit packages have been upgraded to upstream version 0.26.1.

New package: clevis-pin-trustee

The clevis-pin-trustee package provides a new Clevis pin trustee that enables automated encryption and decryption of LUKS-encrypted volumes by using remote attestation through the Trustee Key Broker Service (KBS). The trustee pin integrates with the standard Clevis framework through the clevis-encrypt-trustee and clevis-decrypt-trustee commands, and it includes a Dracut module 60clevis-pin-trustee for automated root volume unlocking during early boot.

In scenarios such as confidential clusters for OpenShift and confidential virtual machines with OpenShift Virtualization, the Trustee server acts as the policy enforcement point, releasing the disk encryption key only when the requesting platform's attestation evidence validates against a set of reference values.

As a result, you can bind LUKS-encrypted volumes to one or more Trustee servers by using a clevis luks bind -d <device> trustee '<config>' command. You can also combine the trustee pin with other Clevis pins, such as tang and tpm2, for multi-factor or multi-policy unlock configurations.

crypto-policies enables mlkem768x25519-sha256 for OpenSSH

This update of the system-wide cryptographic policies adds support for the ML-KEM (Module-Lattice-Based Key-Encapsulation Mechanism) post-quantum (PQ) key exchange mlkem768x25519-sha256 algorithm for OpenSSH. This aligns with support for ML-KEM in OpenSSH, providing a quantum-resistant key exchange method for your SSH sessions when you use the PQ system-wide cryptographic policy.

OpenSCAP rebased to 1.3.13

The OpenSCAP packages have been rebased to upstream version 1.3.13.

SCAP Security Guide rebased to 0.1.80

For additional information, see the

Networking

The following features, enhancements, and changes related to networking are introduced in this Oracle Linux 9 release.

iproute rebased to version 6.17.0

The iproute package has been updated to upstream version 6.17.0.

FRRouting 10 package introduced in Oracle Linux 9 AppStream repository

A new package, frr10, is available in the Oracle Linux 9 AppStream repository. This package provides FRRouting (FRR) version 10 alongside the existing frr version 8 package. You can

now access newer routing features without replacing the earlier version. By introducing `frr10` as a separate package, this update enables flexible adoption and testing of the latest FRR capabilities while maintaining compatibility with existing deployments.

Unbound rebased to version 1.24.2

The Unbound packages have been rebased to version 1.24.2.

Kernel and System Libraries

The following notable features, enhancements, and changes apply to the Red Hat Compatible Kernel (RHCK) that's shipped with the current Oracle Linux 9 version.

crash rebased to 9.0.2

The crash package, which provides a kernel analysis utility for live systems and various types of dump files, is rebased to upstream version 9.0.2.

File Systems and Storage

The following features, enhancements, and changes related to file systems and storage are introduced in this Oracle Linux 9 release.

cryptsetup rebased to version 2.8.0

The cryptsetup package has been upgraded to version 2.8.0.

snappm rebased to 0.7.0

The snappm package has been rebased to upstream version 0.7.0.

High Availability and Clusters

The following features, enhancements, and changes related to high availability are introduced in this Oracle Linux 9 release.

HAProxy rebased to 2.8

The HAProxy package has been rebased to the upstream Long-Term Support (LTS) version 2.8.

For a complete list of changes, see the [HAProxy webpage](#).

Dynamic Programming Languages, Web and Database Servers

The following features, enhancements, and changes related to programming languages, web servers, and database servers are introduced in this Oracle Linux 9 release.

A new module stream: postgresql:18

Oracle Linux 9.8 introduces PostgreSQL 18 as the `postgresql:18` module stream.

A new module stream: mariadb:11.8

MariaDB 11.8 is available as a new module stream, mariadb:11.8.

New ruby:4.0 runtime module stream with database connectors

The ruby module provides a new Ruby 4.0 runtime, including database connector support. As a result, Oracle Linux 9.8 users can use Ruby 4.0 alongside existing Ruby streams to develop and run Ruby applications with supported database connectivity.

The mysql:8.4 module now includes the perl-DBD-MySQL package

This update adds the perl-DBD-MySQL package to the mysql:8.4 module. Starting with Oracle Linux 9.7, the perl-DBD-MySQL package is linked against libmysqlclient instead of libmariadb. To ensure compatibility, perl-DBD-MySQL is included within mysql:8.4. As a result, the perl-DBD-MySQL package is fully compatible with the mysql:8.4 module, which resolves dependency conflicts and installation failures.

New Python 3.14 stack is available

Oracle Linux 9.8 now includes the python3.14 stack. This new alternative stack provides Python 3.14 for developing and running applications.

Compilers and Development Tools

The following features, enhancements, and changes related to compilers and development tools are introduced in this Oracle Linux 9 release.

Rust Toolset is rebased to version 1.92.0

In Oracle Linux 9.8, rust-toolset is rebased to version 1.92.0 from version 1.88.0. This update delivers multiple improvements to debugging, systems programming features, memory safety diagnostics, and Rust workflow tooling for Oracle Linux developers.

Rebase llvm toolset to version 21

The llvm toolset has been rebased to version 21 in Oracle Linux 9.8. This rebase provides updated compiler and tooling features for building and optimizing applications that depend on llvm.

Containers

The following features, enhancements, and changes related to containers are introduced in this Oracle Linux 9 release.

container-selinux rebased to version 2.245.0-1

The container-selinux package, which provides necessary SELinux policies, types, and rules to confine and secure container runtimes, has been rebased to version 2.245.0-1. This version provides important enhancements, most notably, it streamlines the process, enhances data

protection, and ensures confidentiality in deployments, while reducing potential security risks associated with public storage endpoints.

Cockpit Web Console

The following features, enhancements, and changes related to the Cockpit web console are introduced in this Oracle Linux 9 release.

cockpit rebased to version 356

The cockpit packages have been rebased to version 356, which provides many improvements and fixes compared to version 344 in Oracle Linux 9.7.

Identity and Authentication

The following features, enhancements, and changes related to identity and authentication are introduced in this Oracle Linux 9 release.

samba rebased to 4.23.0

The samba packages, which provide file and print services using the SMB protocol, have been rebased to upstream version 4.23.0.

ipa rebased to 4.13.0

The ipa packages have been rebased to upstream version 4.13.0.

cepces rebased to 0.3.12

The cepces package, which provides a certificate enrollment client for Microsoft Active Directory Certificate Services (AD CS), has been rebased to upstream version 0.3.12.

pki rebased to 11.7.1

The pki packages have been rebased to upstream version 11.7.1.

ansible-freeipa rebased to 1.16.0

The ansible-freeipa packages, which provide Ansible modules and roles for Identity Management (IdM), have been rebased to upstream version 1.16.0.

389-ds-base rebased to 2.8.0

The 389-ds-base package, which provides an enterprise-class LDAP server, has been rebased to upstream version 2.8.0.

sudo rebased to sudo-1.9.17p2

The sudo packages have been rebased to upstream version 1.9.17p2.

Operating System and Software Management

The following features, enhancements, and changes related to the OS and software management are introduced in this Oracle Linux 9 release.

librepo rebased to 1.19.0

The librepo packages are rebased to upstream version 1.19.0.

Shells and Command Line Tools

The following features, enhancements, and changes related to shells and command line tools are introduced in this Oracle Linux 9 release.

Security and TLS improvements in openwsman 2.8.1

The openwsman package has been updated to version 2.8.1.

openCryptoki rebased to 3.26.0

The openCryptoki packages are updated to upstream version 3.26.0.

Oracle build of OpenJDK 25 available in Oracle Linux 9

Oracle build of OpenJDK 25 and the maven-openjdk25 subpackages are available in Oracle Linux 9. This version provides the latest long-term support (LTS) release of the Open Java Development Kit (OpenJDK). As a result, you can leverage the latest Java features and performance improvements for your applications.

3

Technology Preview

The following items are available as technical previews in this release of Oracle Linux. Note that some items listed apply to Red Hat Compatible Kernel (RHCK) and might already be available in UEK.

Security

The following features for security are available as technology preview.

KTLS

Oracle Linux 9 provides kernel Transport Layer Security (KTLS) as a technology preview.

The Linux Kernel TLS (KTLS) handles TLS records for the AES-GCM cipher. KTLS also provides the interface for offloading TLS record encryption to NICs that support this functionality.

OpenSSL 3.0 is able to use KTLS if the `enable-ktls` configuration option is used during compiling.

The updated `gnutls` packages can use KTLS for accelerating data transfer on encrypted channels. To enable KTLS, add the `tls.ko` kernel module using the `modprobe` command, and create a new configuration file `/etc/crypto-policies/local.d/gnutls-ktls.txt` for the system-wide cryptographic policies with the following content:

```
[global]
ktls = true
```

Note that `gnutls` doesn't permit you to update traffic keys through TLS KeyUpdate messages, which impacts the security of AES-GCM ciphersuites.

QUIC Protocol in OpenSSL

OpenSSL clients can use the QUIC transport layer network protocol as a technical preview.

`io_uring` Asynchronous I/O Interface

Although available, the `io_uring` asynchronous I/O interface is disabled in RHCK by default. To enable the feature, set the `kernel.io_uring_disabled` variable to any one of the following values when running the `sysctl` command:

- 0: All processes can create `io_uring` instances as usual.
- 1: Creating `io_uring` is disabled for unprivileged processes. With this setting, the `io_uring_setup` fails with the `-EPERM` error. It only successfully completes if the calling process is privileged by the `CAP_SYS_ADMIN` capability. However, existing `io_uring` instances can still be used.

- 2 (default): Creating `io_uring` creation is disabled for all processes. With this setting, the `io_uring_setup` always fails with `-EPERM`. However, existing `io_uring` instances can still be used.

To use this feature, an updated version of the SELinux policy to enable the `mmap` system call on anonymous inodes is also required.

Note that `io_uring` support has been available in UEK from UEK R6U3.

Infrastructure Services

The following features for infrastructure services are available as technology previews.

Socket API for TuneD

The socket API for TuneD maps one-to-one with the D-Bus API and provides an alternative communication method for cases where D-Bus isn't available. With the socket API, you can control the TuneD daemon to optimize the performance, and change the values of various tuning parameters. The socket API is disabled by default. You can enable it in the `tuned-main.conf` file.

Networking

The following networking features are available as technology previews.

`gpsd-minimal`

The `gpsd-minimal` package is available as a technical preview. `gpsd` is a service daemon that mediates access to a GPS sensor connected to the host computer by serial or USB interface, making its data on the location, course, and velocity of the sensor available to be queried on TCP port 2947 of the host computer.

WireGuard

WireGuard is a VPN solution that has improved security features and is easily configurable.

Note that WireGuard is fully supported in UEK. See [Oracle Linux: Configuring Virtual Private Networks](#) for more information on using WireGuard on Oracle Linux.

`systemd-resolved` Service

The `systemd-resolved` service provides name resolution to local applications. Its components include a caching and validating DNS stub resolver, a Link-Local Multicast Name Resolution (LLMNR), and Multicast DNS resolver and responder.

PRP and HSR

The `hsr` kernel module is included with RHCK to provide the following protocols as a technology preview:

- Parallel Redundancy Protocol (PRP)
- High-availability Seamless Redundancy (HSR)

IPsec Packet Offloading

In RHCK, complete IPsec encapsulation can be offloaded to a Network Interface Controller (NIC) to reduce workload. This functionality is offered as a technology preview.

Various Modem Network Drivers

Oracle Linux provides modem drivers in RHCK with limited functionality as a technology preview:

- Qualcomm MHI WWAN MBIM - Telit FN990Axx
- Intel IPC over Shared Memory (IOSM) - Intel XMM 7360 LTE Advanced
- Mediatek t7xx (WWAN) - Fibocom FM350GL
- Intel IPC over Shared Memory (IOSM) - Fibocom L860GL modem

Segment Routing Over IPv6

Segment Routing over IPv6 (SRv6) is available as a technology preview in RHCK. SRv6 can improve traffic flows in edge computing and provides a mechanism to program network slicing and resource reservation.

Kernel

The following kernel features are available as technology previews for RHCK.

Soft iWarp

Soft-iWARP (`siw`) is an Internet Wide-area RDMA Protocol (iWARP) software kernel driver. The driver implements the iWARP protocol suite over the TCP/IP network stack. The suite is implemented in software. Therefore, it doesn't require an RDMA hardware. The protocol suite enables a system with a standard Ethernet adapter to connect to an iWARP adapter or to another system that already has `siw` installed.

Note that from Oracle Linux 9.5, this driver is deprecated.

File Systems and Storage

The following features that are related to file systems and storage are available as technology preview.

`nvme-stas` Package

The `nvme-stas` package, which is a Central Discovery Controller (CDC) client for Linux, handles the following functionalities:

- Asynchronous Event Notifications (AEN)
- Automated NVMe subsystem connection controls
- Error handling and reporting
- Automatic (zeroconf) and Manual configuration.

This package consists of two daemons, Storage Appliance Finder (stafd) and Storage Appliance Connector (stacd).

Compilers and Development Tools

The following features for compilers and development tools are available as technology previews.

`jmc-core` and `owasp-java-encoder`

`jmc-core` is a library that provides core APIs for Java Development Kit (JDK) Mission Control, including APIs for:

- Parsing and writing Java Flight Recording files
- Discovering Java Virtual Machines (JVMs) through the Java Discovery Protocol (JDP)

The `owasp-java-encoder` package provides a collection of high-performance low-overhead contextual encoders for Java.

The packages are available in the Oracle Linux 9 CodeReady Builder repository, which is unsupported, and which you must explicitly enable.

Flexible Array Conversion Warning-Suppression in `libabigail` Available As a Technology Preview

When comparing binaries, you can suppress warnings related to fake flexible arrays that were converted to true flexible arrays by using the following suppression specification:

- `---type_kind = struct has_size_change = true`
- `---has_strict_flexible_array_data_member_conversion = true`

This features is available as a technology preview.

Virtualization

The following virtualization features are available as technology previews.

Nested VMs

Nested KVM virtualization is provided as a technology preview for KVM virtual machines (VMs) running on Oracle Linux 9.

SEV and SEV-ES

The Secure Encrypted Virtualization (SEV) feature is provided for AMD EPYC host machines that use the KVM hypervisor. It encrypts a virtual machine's memory and protects the VM from access by the host.

SEV's enhanced Encrypted State version (SEV-ES) encrypts all CPU register contents when a VM stops running, thus preventing the host from modifying the VM's CPU registers or reading any information from them.

Note that SEV is supported in UEK.

4

Deprecated Features

This chapter lists features and functionalities that are deprecated in Oracle Linux 9. While these features might be included and operative in the release, support isn't guaranteed in future major releases. Thus, these features must not be used in new Oracle Linux 9 deployments.

Installation

The following installation related features and functionalities are deprecated in Oracle Linux 9.

Kickstart Commands

- `timezone --ntpservers`
- `timezone --nntp`
- `logging --level`
- `%packages --excludeWeakdeps`
- `%packages --instLangs`
- `%anaconda`
- `pwpolicy`
- `nvdim`

Even though specific options are listed as deprecated, the base command and the other options remain available and operative. If you use a deprecated command in kickstart files, warnings are generated in the logs. To change deprecated command warnings to errors, set the `inst.ksstrict` boot option.

`initial-setup` Package

Instead of using this package, use the `gnome-initial-setup` package as a replacement.

`inst.geoloc` Boot Option Values `provider_hostip` And `provider_fedora_geop`

The `provider_hostip` and `provider_fedora_geop` values for the `inst.geoloc=` boot option are deprecated. You can use the `geolocation_provider=URL` option to set the required geolocation in the installation program configuration file, if required. Use the `inst.geoloc=0` option to disable the geolocation.

Anaconda Screenshots

Capturing screenshots of the Anaconda GUI by using a global hotkey is deprecated.

Anaconda Help

The built-in documentation from spokes and hubs of all Anaconda user interfaces that was available during Anaconda installation is deprecated. The interface is self-documented and the [Oracle Linux 9: Installing Oracle Linux](#) can be used for further assistance.

Software Management

The following software management related features and functionalities are deprecated in Oracle Linux 9.

DNF `debug` plugin

The DNF debug plugin, which includes the `dnf debug-dump` and `dnf debug-restore` commands, is deprecated.

DNF `libreport`

The DNF `libreport` library is deprecated.

Shell and Command Line

The following shell and command line related features and functionalities are deprecated in Oracle Linux 9.

`dump` Utility

The dump utility that's included in the `dump` package is deprecated.

You can alternatively use the `tar` or `dd` to achieve similar functionality.

Note that the `restore` utility, originally included in the `dump` package, remains available in Oracle Linux 9 and can be installed by using the `restore` package.

Bacula Sqlite Backend Database

The use of a SQLite backend database for the Bacula backup utility is deprecated. Bacula can use a MySQL backend database and you can migrate existing deployments to MySQL. Avoid using SQLite for new deployments of the Bacula backup utility.

TMPDIR Variable in the ReaR Configuration File

Exporting using the `TMPDIR` environment variable in the `/etc/rear/local.conf` or `/etc/rear/site.conf` ReaR configuration files, is deprecated.

Instead, you can specify a custom directory for ReaR temporary files by exporting the variable in the shell environment before executing ReaR. For example, run the `export TMPDIR=...` statement and then run the `rear` command in the same shell session or script.

Security

The following security related features and functionalities are deprecated in Oracle Linux 9.

Unprivileged Access to `dmesg` Output

Unprivileged access to `dmesg` output is deprecated and will be removed in a future release of UEK 8 and might be removed in a future release of Oracle Linux. Use the `sudo` command to escalate to administrator privileges when running the `dmesg` command. See [Oracle Linux 9: Enhancing System Security](#) for more information on how to restrict access to kernel ring buffer messages as good security practice.

OVAL Data Format

The Open Vulnerability Assessment Language (OVAL) data format used by the OpenSCAP suite is deprecated. Declarative security data is now provided in the Common Security Advisory Framework (CSAF) format, which is the successor of OVAL.

Using `update-ca-trust` Without Arguments

Using the `update-ca-trust` command without arguments to update the CA trust store is deprecated. Use the `update-ca-trust extract` command to update the CA trust store.

Configuring STunnel Clients to Use the Trusted Root CA Files

The option to configure STunnel Clients `CAFiles` directive to point to a file that contains trusted root certificates in the BEGIN TRUSTED CERTIFICATE format. If you use `CAfile`
= `/etc/pki/tls/certs/ca-bundle.trust.crt`, change the location to `CAfile`
= `/etc/pki/tls/certs/ca-bundle.crt`.

NSS Deprecated Algorithms

The following algorithms are deprecated in the Network Security Services (NSS) cryptographic library.

- Digital Signature Algorithm (DSA)
- SEED

Use RSA, ECDSA, SHB-DSA, ML-DSA, or FN-DSA instead.

`pam_ssh_agent_auth`

`pam_ssh_agent_auth` is deprecated.

`scap-workbench`

`scap-workbench` is deprecated.

`oscap-anaconda-addon`

`oscap-anaconda-addon` is deprecated.

`/etc/system-fips`

The `/etc/system-fips` file, that was used to indicate FIPS mode is removed. To install Oracle Linux in FIPS mode, add the `fips=1` parameter to the kernel command line during the system installation. You can check whether Oracle Linux operates in FIPS mode by using the `fips-mode-setup --check` command.

`libcrypt.so.1`

The `libcrypt.so.1` library is deprecated.

SHA-1 Algorithm

The SHA1 algorithm is deprecated in Oracle Linux 9. Digital signatures using SHA-1 hash algorithm are no longer considered secure and therefore not allowed on Oracle Linux 9 systems by default. Oracle Linux 9 has been updated to avoid using SHA-1 in security-related use cases.

However, the HMAC-SHA1 message authentication code and the Universal Unique Identifier (UUID) values can still be created by using SHA-1.

In cases where you need SHA-1 to verify existing or third party cryptographic signatures, you can enable SHA-1 as follows:

```
sudo update-crypto-policies --set DEFAULT:SHA1
```

As an alternative, you can switch the systemwide crypto policies to the LEGACY policy. However, this policy also enables other algorithms that are not secure, and therefore risks making the system vulnerable.

Furthermore, use of the SHA-1 algorithm at SECLEVEL=2 is deprecated in OpenSSL.

SCP Protocol

In the `scp` utility, secure copy protocol (SCP) is replaced by the SSH File Transfer Protocol (SFTP) by default. Likewise, SCP is deprecated in the `libssh` library.

Oracle Linux 9 doesn't use SCP in the OpenSSH suite.

OpenSSL Cryptographic Algorithms

- MD2
- MD4
- MDC2
- Whirlpool
- RIPEMD160
- Blowfish
- CAST
- DES

- IDEA
- RC2
- RC4
- RC5
- SEED
- PBKDF1

The implementations of these algorithms have been moved to the legacy provider in OpenSSL.

For instructions on how to load the legacy provider and enable support for the deprecated algorithms, see the `/etc/pki/tls/openssl.cnf` configuration file.

Digest-MD5

The Digest-MD5 authentication mechanism in the Simple Authentication Security Layer (SASL) framework is deprecated.

`/etc/system-fips` File

The `/etc/system-fips` file was used to indicate the FIPS mode in the system. This file is removed in Oracle Linux 9.

To install Oracle Linux 9 in FIPS mode, add the `fips=1` parameter to the kernel command line during the system installation. To check whether Oracle Linux 9 is operating in FIPS mode, use the `fips-mode-setup --check` command.

`libcrypt.so.1`

The `libcrypt.so.1` cryptogarhic library is deprecated.

`fapolicyd.rules` File

The `/etc/fapolicyd/fapolicyd.rules` file is deprecated. You can store policy rules for `fapolicyd` in the `/etc/fapolicyd/rules.d/` directory. The `fagenrules` script merges all component rule files in this directory to the `/etc/fapolicyd/compiled.rules` file.

Rules in `/etc/fapolicyd/fapolicyd.trust` continue to be processed by `fapolicyd` for backward compatibility.

OpenSSL RSA Encryption Without Padding

RSA encryption without padding for OpenSSL in FIPS mode is no longer accepted. However, key encapsulation with RSA (RSASVE) which doesn't use padding continues to be supported for OpenSSL.

OpenSSL Engines API

The Engines API is deprecated in the OpenSSL 3.0 TLS toolkit. Use the `pkcs11-provider` Providers API instead. Equally use of the OpenSSL Engines API in Stunnel is deprecated.

openssl-pkcs11

The openssl-pkcs11 (engine_pkcs11) package, which relates to the deprecated OpenSSL Engins API, is now deprecated. Use the pkcs11-provider package instead.

Networking

The following network related features and functionalities are deprecated in Oracle Linux 9.

Soft-iWarp

Soft-iWarp, which was available as a technology preview in previous releases of Oracle Linux 9, is deprecated.

Network Teams

The teamd service, and the libteam library, and support for configuring network teams are deprecated in favor of network bonds. You should use network bonds instead, which have similar functions as teams, and which would receive enhancements and updates.

dhcpcd Package

The dhcpcd package and the dhcpcd tool that it contained are deprecated in favor of the internal DHCP client library built into NetworkManager.

firewalld Lockdown

The lockdown feature in firewalld is deprecated because it can't prevent processes that are running as root from adding themselves to the allow list.

/etc/sysconfig/network-scripts File

Network configurations profiles used to be in ifcfg format and stored in the /etc/sysconfig/network-scripts directory. This format is deprecated. In Oracle Linux 9, new network configurations are stored in /etc/NetworkManager/system-connections in keyfile format. This format works with all the connection settings provided by NetworkManager.

However, information in the /etc/sysconfig/network-scripts remain operative, and modifications to existing profiles continue to update the older files.

iptables Framework

With the deprecation of the iptables framework, the iptables backend and the direct interface are also deprecated.

Therefore, the following packages are also deprecated:

- iptables-devel
- iptables-libs
- iptables-nft

- `iptables-nft-services`
- `iptables-utils`

As an alternative to using `direct` interface, use the native features in `firewalld` to configure the required rules.

PF_KEYv2 Kernel API

The PF_KEYv2 API is used to configure kernel IPsec implementation. However, this API isn't maintained upstream. Therefore, this API is deprecated. Instead, use the `netlink` API as a replacement.

Network Manager `nmcli` Language Changes

Because Oracle is fully committed to diversity and inclusion, the Network Manager `connection.master`, `connection.slave-type`, and `connection.autoconnect-slaves` connection property names are deprecated. They are retained for backward compatibility. However, consider using the following replacement terms instead:

- Instead of `connection.master`, use `connection.controller`
- Instead of `connection.slave-type`, use `connection.port-type`
- Instead of `connection.autoconnect-slaves` use `connection.autoconnect-ports`

TigerVNC

The TigerVNC remote desktop solution is deprecated.

The following packages are deprecated:

- `tigervnc`
- `tigervnc-icons`
- `tigervnc-license`
- `tigervnc-selinux`
- `tigervnc-server`
- `tigervnc-server-minimal`
- `tigervnc-server-module`

The `gnome-connections` application can be used as an alternative VNC client, but it doesn't provide a VNC server.

Future remote desktop solutions are likely to use Remote Desktop Protocol (RDP).

Kernel

The following kernel related features and functionalities are deprecated in Oracle Linux 9.

`crashkernel=auto` Option

The `crashkernel=auto` option is deprecated and no longer supported on Oracle Linux 9 and is also unsupported for UEK R7 and later. Some platforms, such as the Raspberry Pi have

maximum limits for `crashkernel` memory reservation and these must be specified explicitly. This option will be removed in a future UEK release.

Asynchronous Transfer Mode

Asynchronous Transfer Mode (ATM) encapsulation enables Layer-2 (Point-to-Point Protocol, Ethernet) or Layer-3 (IP) connectivity for the ATM Adaptation Layer 5 (AAL-5). Currently, these protocols are used only in chipsets that use ADSL technology, which are being phased out.

`kexec_load` in `kexec_tools`

The `kexec_load` system call for `kexec-tools` is deprecated.

The `kexec_file_load` system call replaces `kexec_load` and is the default system call.

`cgroupsv1`

`cgroupsv1` is deprecated in Oracle Linux 9 in favor of `cgroupsv2`. See [Oracle Linux 9: Managing the System With systemd](#) and [Oracle Linux 9: Managing Kernels and System Boot](#) for more information on using `cgroups`.

File Systems and Storage

The following features and functionalities related to file systems and storage are deprecated in Oracle Linux 9.

`lsscsi` NVMe

Using `lsscsi` to list information about Non-Volatile Memory Express (NVMe) devices is deprecated. Use `nvme-cli`, `lsblk`, and `blkid` instead.

`sg3_utils` NVMe

Using any of the tools in the `sg3_utils` package to work with Non-Volatile Memory Express (NVMe) devices is deprecated. Use `nvme-cli` instead.

`lvm2-activation-generator`

The `lvm2-activation-generator` program is deprecated, together with its generated services as follows:

- `lvm2-activation`
- `lvm2-activation-early`
- `lvm2-activation-net`

The `lvm.conf` `event_activation` that used to activate these services no longer works. The only method that is used for automatic activation of volume groups is event based activation.

PMDK Library

The Persistent Memory Development Kit (pmdk) is a collection of libraries and tools for simplifying the management and access of persistent memory devices. This set of libraries are deprecated, including the -debuginfo packages.

The following list of pmdk-related binary packages, including the nvml source package, have been deprecated:

- libpmem
- libpmem-devel
- libpmem-debug
- libpmem2
- libpmem2-devel
- libpmem2-debug
- libpmemblk
- libpmemblk-devel
- libpmemblk-debug
- libpmemlog
- libpmemlog-devel
- libpmemlog-debug
- libpmemobj
- libpmemobj-devel
- libpmemobj-debug
- libpmempool
- libpmempool-devel
- libpmempool-debug
- pmempool
- daxio
- pmreorder
- pmdk-convert
- libpmemobj++
- libpmemobj++-devel
- libpmemobj++-doc

md-linear and md-faulty MD RAID Kernel Modules

The following MD RAID kernel modules have been deprecated:

- CONFIG_MD_LINEAR or md-linear: Concatenates multiple drives so that when a single member disk becomes full, data is written to the next disk until all disks are full.

- `CONFIG_MD_FAULTY` or `md-faulty`: Tests a block device that occasionally returns read or write errors for testing purposes.

Virtual Data Optimizer Parameters in `sysfs`

Virtual Data Optimizer (VDO) parameters that appears in `sysfs` have been deprecated except for the `log_level` parameter. These include the following:

- All `kvdo` module-level `sysfs` parameters
- All individual `dm-vdo` `sysfs` parameters targets specific to VDO

Parameters that are common to all DM targets don't change. Configuration values for `dm-vdo` targets, which are set by updating the removed module-level parameters, can no longer be changed.

You can no longer access statistics and configuration values for `dm-vdo` targets using `sysfs`. However, these values are accessible using `dmsetup message stats`, `dmsetup status`, and `dmsetup table dmsetup` commands.

High Availability

The following high availability related features and functionalities are deprecated in Oracle Linux 9.

Several Pacemaker Configuration Options

Several Pacemaker configuration options are deprecated.

- Configuring a score parameter in order constraints
- Use of the `rkt` container engine in bundles
- Use of `upstart` and `nagios` resources
- The `monthdays`, `weekdays`, `weekyears`, `yearsdays` and moon date specification options when configuring Pacemaker rules
- The `yearsdays` and moon duration options for configuring Pacemaker rules

The `pcs` command emits a warning when a system is configured to use any of the deprecated features or options.

Dynamic Programming Languages, Web and Database Servers

The following features and functionalities that are related to dynamic programming, web, and database servers are deprecated in Oracle Linux 9.

Berkeley DB (`libdb`)

Deprecation of the Berkely DB (`libdb`) package includes the removal of cryptographic algorithms and dependencies. Users of `libdb` should migrate to a different key-value database.

Compilers and Development

The following compiler and development related features and functionalities are deprecated in Oracle Linux 9.

Redis in Grafana, PCP, and `grafana-pcp`

Use of Redis in Grafana, PCP, and `grafana-pcp` is deprecated and will be replaced with Valkey.

`llvm-doc` HTML Content

The HTML content in the `llvm-doc` package is deprecated. See the content at <https://llvm.org/>.

Keys Smaller Than 2048-bits in OpenSSL

OpenSSL 3.0 has deprecated keys smaller than 2048 bits. Keys smaller than 2048 bits might not work in FIPS mode.

Some PKCS1 v1.5 modes

Some PKCS1 v1.5 modes aren't approved in FIPS-140-3 for encryption and are disabled.

32-bit `multilib` Linking

Linking against 32-bit `multilib` packages (*.i686 packages) are deprecated.

Identity Management and Authentication

The following identity management and authentication features and functionalities are deprecated in Oracle Linux 9.

PAM Console

`pam_console` module is deprecated. It grants file permissions and authentication to users logged in at the physical console or terminals, and adjusts these privileges based on console login status and user presence.

BDB backend (in 389-ds-base)

Berkeley Database (BDB) backend is deprecated in 389-ds-base package, the 389 Directory Server. As a replacement, Directory Server can now create instances with Lightning Memory-Mapped Database (LMDB) available as a Technology Preview.

`sss_ssh_knownhostsproxy`

`sss_ssh_knownhostsproxy`, a utility in the System Security Services Daemon (SSSD) package, is deprecated.

libsss_simpleifp

libsss_simpleifp that provides the libsss_simpleifp.so library is deprecated.

SSSD Files Provider

The SSSD files provider, which retrieves user information from local files such as /etc/shadow and group information from /etc/groups, is deprecated and disabled by default in Oracle Linux 9.

To retrieve user and group information from local files with SSSD:

1. Configure SSSD. Choose one of the following options:
 - a. Explicitly configure a local domain with the `id_provider=files` option in the `sssd.conf` configuration file.

```
[domain/local]
id_provider=files
...
```

- b. Enable the files provider by setting `enable_files_domain=true` in the `sssd.conf` configuration file.

```
[sssd]
enable_files_domain = true
```

2. Configure the name services switch.

```
sudo authselect enable-feature with-files-provider
```

OpenLDAP Utility Options

The OpenLDAP project has deprecated the `-h` and `-p` options in its utilities, and recommends using the `-H` option instead to specify the LDAP URI.

nsslapd-idlistscanlimit Parameter and Default Value

Because of optimizations to filter reordering, the `nsslapd-idlistscanlimit` parameter results in having a negative impact on search performance and is therefore deprecated. Further, the parameter's default value is changed to 2147483646

SMB1 Protocol

Beginning with Samba 4.11, the Server Message Block version 1 (SMB1) protocol is deprecated because of its insecure features. By default, this protocol is disabled in both Samba server and client utilities.

Virtualization

The following virtualization related features and functionalities are deprecated in Oracle Linux 9.

Signatures Using SHA-1

The use of SHA1-based signatures to perform SecureBoot image verification on UEFI (PE/COFF) executables is deprecated. Instead, use signatures that are based on SHA-2 or later.

Virtual Machine Manager

In place of the deprecated Virtual Machine Manager (`virt-manager`), use the web console, otherwise known as Cockpit.

Virtual Machine Snapshots

Support for creating snapshots of VMs is limited only to those that do not use UEFI firmware. However, the operation might cause the QEMU monitor to become blocked and affects hypervisor operations.

As an alternative, use external snapshots.

`libvirtd` Daemon

As a replacement of the deprecated `libvirtd` daemon, use the modular daemons in the `libvirt` library. For example, the `virtqemud` handles QEMU drivers.

Virtual Floppy Driver

The `isa-fdc` driver controls virtual floppy disk devices. To ensure compatibility with migrated virtual machines (VMs), you should not use floppy disk devices in virtual machines that you subsequently host on Oracle Linux 9.

`qcow2-v2` Format

For virtual disk images, use the `qcow2-v3` format instead.

Legacy CPU Models

The following legacy CPU models are deprecated for use in VMs:

- For Intel® : models prior to Intel® Xeon 55xx and 75xx Processor families (also known as Nehalem)
- For AMD: models prior to AMD Opteron G4

To check whether a VM is using a deprecated CPU model, use the `virsh dominfo` command, and look for a line similar to the following in the Messages section:

```
tainted: use of deprecated configuration settings
deprecated configuration: CPU model 'i486'
```

RDMA-based Live Migration

In this release, RDMA-based live migration of virtual machines is deprecated.

Windows 8 and Windows Server 2012 Guest Operating System

The following Windows versions are deprecated as a guest operating system:

- Windows 8
- Windows 8.1
- Windows Server 2012
- Windows Server 2012 R2

These are deprecated because they are no longer supported by Microsoft.

NIC Device Drivers for iPXE

The following device drivers are deprecated:

- All device drivers in the ipxe-roms subpackage
- The following binary files from ipxe-bootimgs-x86:
 - /usr/share/ipxe/ipxe-i386.efi
 - /usr/share/ipxe/ipxe-x86_64.efi
 - /usr/share/ipxe/ipxe.dsk
 - /usr/share/ipxe/ipxe.iso
 - /usr/share/ipxe/ipxe.lkrm
 - /usr/share/ipxe/ipxe.usb

Use the following binary files from the ipxe-bootimgs package to provide NIC device drivers for iPXE network boot:

- /usr/share/ipxe/ipxe-snponly-x86_64.efi
- /usr/share/ipxe/undionly.kpxe

Intel vGPU

Dividing select Intel vGPUs into multiple virtual GPUs and assigning them to VMs is no longer supported.

pmem Device Passthrough

The non-volatile memory library (nvm1) packages are deprecated. When they are removed in a future release, you will be unable to pass persistent memory (pmem) devices to VMs. You also will be unable to configure emulated NVDIMM devices backed by volatile memory or files as persistent, but the devices will remain available.

Containers

The following features and functionalities that are related to containers are deprecated in Oracle Linux 9.

containers.conf for System Connections

The `containers.conf` file is read-only for Podman commands. The system connections and farm information must be stored in the `podman.connections.json` file, managed only by Podman.

Podman continues to support the old configuration options such as `[engine.service_destinations]` and the `[farms]` section. You can still add connections or farms manually if needed, however, it's not possible to delete a connection from the `containers.conf` file with the `podman system connection rm` command.

slirp4net

The `slirp4netns` network mode is deprecated. The `pasta` network mode is the default network mode for rootless containers.

cgroupsv1 in Rootless Containers

Using `cgroupsv1` for rootless containers is deprecated.

Note that `cgroupsv1` is deprecated on Oracle Linux 9. See [cgroupsv1](#).

runc Container Runtime

The `runc` container runtime is deprecated. The default container runtime is `crun`.

pasta as a Network Name

Using `pasta` as a network name value is deprecated.

BoltDB Database Backend

The BoltDB database backend is deprecated in favor of the SQLite database backend.

Oracle Linux 9 Containers on Oracle Linux 7 Hosts

Creating Oracle Linux 9 containers on an Oracle Linux 7 host is unsupported. Attempts to deploy this configuration might succeed, but isn't guaranteed.

SHA-1 Algorithm Within Podman

Support for using the SHA-11 algorithm to generate the filename of the rootless network namespace is removed in Podman. You should restart rootless containers that were configured by using Podman earlier than version 4.1.1. Restarting these containers rather than just using `slirp4netns` ensures that these containers and join the network and connect with containers that were created with upgraded Podman versions.

CNI Network Stack

The Container Network Interface (CNI) network stack is deprecated. You can use the Netavark network stack with Podman and other Open Container Initiative (OCI) container management

applications. The Netavark network stack for Podman is also compatible with advanced Docker functionalities.

Deprecated Packages

The support status of deprecated packages remains unchanged within Oracle Linux 9. For more information about the length of support, see [Oracle Linux: Product Life Cycle Information](#).

The following packages are deprecated in Oracle Linux 9:

- aacraid
- aajohan-comfortaa-fonts
- adwaita-gtk2-theme
- adwaita-gtk2-theme
- adwaita-qt5
- af_key
- anaconda-user-help
- anaconda-user-help
- ant-javamail
- apr-util-bdb
- aspnetcore-runtime-7.0
- aspnetcore-targeting-pack-6.0
- aspnetcore-targeting-pack-7.0
- atkmm
- atlas
- atlas-devel
- atlas-z14
- atlas-z15
- authselect-compat
- autoconf271
- autoconf-latest
- autocorr-af
- autocorr-bg
- autocorr-ca
- autocorr-cs
- autocorr-da
- autocorr-de
- autocorr-dsb
- autocorr-el
- autocorr-en

- autocorr-es
- autocorr-fa
- autocorr-fi
- autocorr-fr
- autocorr-ga
- autocorr-hr
- autocorr-hsb
- autocorr-hu
- autocorr-is
- autocorr-it
- autocorr-ja
- autocorr-ko
- autocorr-lb
- autocorr-lt
- autocorr-mn
- autocorr-nl
- autocorr-pl
- autocorr-pt
- autocorr-ro
- autocorr-ru
- autocorr-sk
- autocorr-sl
- autocorr-sr
- autocorr-sv
- autocorr-tr
- autocorr-vi
- autocorr-vro
- autocorr-zh
- babl
- bind9.18-libs
- bitmap-fangsongti-fonts
- bnx2
- bnx2fc
- bnx2i
- bogofilter
- Box2D
- brasero-nautilus

- cairomm
- cheese
- cheese-libs
- clucene-contribs-lib
- clucene-core
- clutter
- clutter-gst3
- clutter-gtk
- cnic
- cogl
- compat-hesiod
- compat-locales-sap
- compat-locales-sap-common
- compat-openssl11
- compat-paratype-pt-sans-fonts-f33-f34
- compat-sap-c++-12
- compat-sap-c++-13
- containernetworking-plugins
- containers-common-extra
- culmus-aharoni-clm-fonts
- culmus-caladings-clm-fonts
- culmus-david-clm-fonts
- culmus-drugulin-clm-fonts
- culmus-ellinia-clm-fonts
- culmus-fonts-common
- culmus-frank-ruehl-clm-fonts
- culmus-hadasim-clm-fonts
- culmus-miriam-clm-fonts
- culmus-miriam-mono-clm-fonts
- culmus-nachlieli-clm-fonts
- culmus-simple-clm-fonts
- culmus-stamashkenaz-clm-fonts
- culmus-stamsefarad-clm-fonts
- culmus-yehuda-clm-fonts
- curl-minimal
- daxio
- dbus-glib

- dbus-glib-devel
- devhelp
- devhelp-libs
- dhcp-client
- dhcp-common
- dhcp-relay
- dhcp-server
- dotnet-apphost-pack-6.0
- dotnet-apphost-pack-7.0
- dotnet-hostfxr-6.0
- dotnet-hostfxr-7.0
- dotnet-runtime-6.0
- dotnet-runtime-7.0
- dotnet-sdk-6.0
- dotnet-sdk-7.0
- dotnet-targeting-pack-6.0
- dotnet-targeting-pack-7.0
- dotnet-templates-6.0
- dotnet-templates-7.0
- double-conversion
- efs-utils
- enchant
- enchant-devel
- eog
- evince
- evince-libs
- evince-nautilus
- evince-previewer
- evince-thumbnailer
- evolution
- evolution-bogofilter
- evolution-data-server-ui
- evolution-data-server-ui-devel
- evolution-devel
- evolution-ews
- evolution-ews-langpacks
- evolution-help

- evolution-langpacks
- evolution-mapi
- evolution-mapi-langpacks
- evolution-pst
- evolution-spamassassin
- festival
- festival-data
- festvox-slt-arctic-hts
- firefox
- firefox
- firefox-x11
- firewire-core
- flite
- flite-devel
- fltk
- flute
- fontawesome-fonts
- gc
- gcr-base
- gedit
- gedit-plugin-bookmarks
- gedit-plugin-bracketcompletion
- gedit-plugin-codecomment
- gedit-plugin-colorpicker
- gedit-plugin-colorschemer
- gedit-plugin-commander
- gedit-plugin-drawspaces
- gedit-plugin-findinfiles
- gedit-plugin-joинlines
- gedit-plugin-multiedit
- gedit-plugins
- gedit-plugins-data
- gedit-plugin-sessionsaver
- gedit-plugin-smartspaces
- gedit-plugin-synctex
- gedit-plugin-terminal
- gedit-plugin-textsize

- gedit-plugin-translate
- gedit-plugin-wordcompletion
- ghc-srpm-macros
- ghostscript-x11
- git-p4
- glade
- glade-libs
- glibmm24
- gl-manpages
- gnome-backgrounds
- gnome-backgrounds-extras
- gnome-common
- gnome-logs
- gnome-photos
- gnome-photos-tests
- gnome-screenshot
- gnome-session-xsession
- gnome-shell-extension-panel-favorites
- gnome-shell-extension-updates-dialog
- gnome-terminal
- gnome-terminal-nautilus
- gnome-themes-extra
- gnome-tweaks
- gnome-video-effects
- google-noto-cjk-fonts-common
- google-noto-sans-cjk-ttc-fonts
- google-noto-sans-khmer-ui-fonts
- google-noto-sans-lao-ui-fonts
- google-noto-sans-thai-ui-fonts
- gspell
- gtk2
- gtk2-devel
- gtk2-devel-docs
- gtk2-immodules
- gtk2-immodule-xim
- gtkmm30
- gtksourceview4

- gtksourceview4
- gubbi-fonts
- gvfs-devel
- ha-openstack-support
- hesiod
- hexchat
- highcontrast-icon-theme
- http-parser
- ibus-gtk2
- initial-setup
- initial-setup-gui
- inkscape
- inkscape-docs
- inkscape-view
- iptables-devel
- iptables-libs
- iptables-nft
- iptables-nft-services
- iptables-utils
- iputils-ninfod
- ipxe-roms
- jakarta-activation2
- jboss-jaxrs-2.0-api
- jboss-logging
- jboss-logging-tools
- jdeparser
- julietaula-montserrat-fonts
- kacst-art-fonts
- kacst-book-fonts
- kacst-decorative-fonts
- kacst-digital-fonts
- kacst-farsi-fonts
- kacst-fonts-common
- kacst-letter-fonts
- kacst-naskh-fonts
- kacst-office-fonts
- kacst-one-fonts

- `kacst-pen-fonts`
- `kacst-poster-fonts`
- `kacst-qurn-fonts`
- `kacst-screen-fonts`
- `kacst-title-fonts`
- `kacst-title1-fonts`
- `khmer-os-battambang-fonts`
- `khmer-os-bokor-fonts`
- `khmer-os-content-fonts`
- `khmer-os-fasthand-fonts`
- `khmer-os-freehand-fonts`
- `khmer-os-handwritten-fonts`
- `khmer-os-metal-chrieng-fonts`
- `khmer-os-muol-fonts`
- `khmer-os-muol-fonts-all`
- `khmer-os-muol-pali-fonts`
- `khmer-os-siemreap-fonts`
- `kmod-kvdo`
- `lasso`
- `libabw`
- `libadwaita-qt5`
- `libbase`
- `libblockdev-kbd`
- `libcanberra-gtk2`
- `libcdr`
- `libcmis`
- `libdazzle`
- `libdb`
- `libdb-devel`
- `libdb-utils`
- `libdmx`
- `libepubgen`
- `libetonyek`
- `libexttextcat`
- `libfonts`
- `libformula`
- `libfreehand`

- libgdata
- libgdata-devel
- libgnomekbd
- libiscsi
- libiscsi-utils
- liblangtag
- liblangtag-data
- liblayout
- libloader
- libmatchbox
- libmspub
- libmwaw
- libnsl2
- libnumbertext
- libodfgen
- liborcus
- libotr
- libpagemaker
- libpmem
- libpmem2
- libpmem2-debug
- libpmem2-devel
- libpmemblk
- libpmemblk-debug
- libpmemblk-devel
- libpmem-debug
- libpmem-devel
- libpmemlog
- libpmemlog-debug
- libpmemlog-devel
- libpmemobj
- libpmemobj-debug
- libpmemobj++-devel
- libpmemobj-devel
- libpmemobj++-doc
- libpmempool
- libpmempool-debug

- libpmpool-devel
- libpng15
- libpst-libs
- libqxp
- LibRaw
- libreoffice
- libreoffice-base
- libreoffice-calc
- libreoffice-core
- libreoffice-data
- libreoffice-draw
- libreoffice-emailmerge
- libreoffice-filters
- libreoffice-gdb-debug-support
- libreoffice-graphicfilter
- libreoffice-gtk3
- libreoffice-help-ar
- libreoffice-help-bg
- libreoffice-help-bn
- libreoffice-help-ca
- libreoffice-help-cs
- libreoffice-help-da
- libreoffice-help-de
- libreoffice-help-dz
- libreoffice-help-el
- libreoffice-help-en
- libreoffice-help-eo
- libreoffice-help-es
- libreoffice-help-et
- libreoffice-help-eu
- libreoffice-help-fi
- libreoffice-help-fr
- libreoffice-help-gl
- libreoffice-help-gu
- libreoffice-help-he
- libreoffice-help-hi
- libreoffice-help-hr

- libreoffice-help-hu
- libreoffice-help-id
- libreoffice-help-it
- libreoffice-help-ja
- libreoffice-help-ko
- libreoffice-help-lt
- libreoffice-help-lv
- libreoffice-help-nb
- libreoffice-help-nl
- libreoffice-help-nn
- libreoffice-help-pl
- libreoffice-help-pt-BR
- libreoffice-help-pt-PT
- libreoffice-help-ro
- libreoffice-help-ru
- libreoffice-help-si
- libreoffice-help-sk
- libreoffice-help-sl
- libreoffice-help-sv
- libreoffice-help-ta
- libreoffice-help-tr
- libreoffice-help-uk
- libreoffice-help-zh-Hans
- libreoffice-help-zh-Hant
- libreoffice-impress
- libreofficekit
- libreoffice-langpack-af
- libreoffice-langpack-ar
- libreoffice-langpack-as
- libreoffice-langpack-bg
- libreoffice-langpack-bn
- libreoffice-langpack-br
- libreoffice-langpack-ca
- libreoffice-langpack-cs
- libreoffice-langpack-cy
- libreoffice-langpack-da
- libreoffice-langpack-de

- libreoffice-langpack-dz
- libreoffice-langpack-el
- libreoffice-langpack-en
- libreoffice-langpack-eo
- libreoffice-langpack-es
- libreoffice-langpack-et
- libreoffice-langpack-eu
- libreoffice-langpack-fa
- libreoffice-langpack-fi
- libreoffice-langpack-fr
- libreoffice-langpack-fy
- libreoffice-langpack-ga
- libreoffice-langpack-gl
- libreoffice-langpack-gu
- libreoffice-langpack-he
- libreoffice-langpack-hi
- libreoffice-langpack-hr
- libreoffice-langpack-hu
- libreoffice-langpack-id
- libreoffice-langpack-it
- libreoffice-langpack-ja
- libreoffice-langpack-kk
- libreoffice-langpack-kn
- libreoffice-langpack-ko
- libreoffice-langpack-lt
- libreoffice-langpack-lv
- libreoffice-langpack-mai
- libreoffice-langpack-ml
- libreoffice-langpack-mr
- libreoffice-langpack-nb
- libreoffice-langpack-nl
- libreoffice-langpack-nn
- libreoffice-langpack-nr
- libreoffice-langpack-nso
- libreoffice-langpack-or
- libreoffice-langpack-pa
- libreoffice-langpack-pl

- libreoffice-langpack-pt-BR
- libreoffice-langpack-pt-PT
- libreoffice-langpack-ro
- libreoffice-langpack-ru
- libreoffice-langpack-si
- libreoffice-langpack-sk
- libreoffice-langpack-sl
- libreoffice-langpack-sr
- libreoffice-langpack-ss
- libreoffice-langpack-st
- libreoffice-langpack-sv
- libreoffice-langpack-ta
- libreoffice-langpack-te
- libreoffice-langpack-th
- libreoffice-langpack-tn
- libreoffice-langpack-tr
- libreoffice-langpack-ts
- libreoffice-langpack-uk
- libreoffice-langpack-ve
- libreoffice-langpack-xh
- libreoffice-langpack-zh-Hans
- libreoffice-langpack-zh-Hant
- libreoffice-langpack-zu
- libreoffice-math
- libreoffice-ogltrans
- libreoffice-opensymbol-fonts
- libreoffice-pdfimport
- libreoffice-pyuno
- libreoffice-sdk
- libreoffice-sdk-doc
- libreoffice-ure
- libreoffice-ure-common
- libreoffice-voikko
- libreoffice-wiki-publisher
- libreoffice-writer
- libreoffice-x11
- libreoffice-xsltfilter

- librepository
- libvenge
- libvenge-gdb
- libserializer
- libsigc++20
- libsigsegv
- libmbios
- libsoup
- libsoup-devel
- libstaroffice
- libstemmer
- libstoragemgmt-smis-plugin
- libteam
- libuser
- libuser-devel
- libvisio
- libvisual
- libwpd
- libwpe
- libwpe-devel
- libwpg
- libwps
- libxcrypt-compat
- libxklavier
- libXp
- libXp-devel
- libXScrnSaver
- libXScrnSaver-devel
- libXxf86dga
- libXxf86dga-devel
- libzmf
- lklug-fonts
- lohit-gurmukhi-fonts
- lpsolve
- man-pages-overrides
- mcpp
- memkind

- mesa-libGLw
- mesa-libGLw-devel
- mlocate
- mod_auth_mellon
- mod_jk
- mod_security
- mod_security_crs
- mod_security-mlogc
- motif
- motif-devel
- mythes
- mythes-bg
- mythes-ca
- mythes-cs
- mythes-da
- mythes-de
- mythes-el
- mythes-en
- mythes-eo
- mythes-es
- mythes-fr
- mythes-ga
- mythes-hu
- mythes-it
- mythes-lv
- mythes-nb
- mythes-nl
- mythes-nn
- mythes-pl
- mythes-pt
- mythes-ro
- mythes-ru
- mythes-sk
- mythes-sl
- mythes-sv
- mythes-uk
- navilu-fonts

- nbdkit-gzip-filter
- neon
- NetworkManager-initscripts-updown
- nginx
- nginx-all-modules
- nginx-core
- nginx-filesystem
- nginx-mod-devel
- nginx-mod-http-image-filter
- nginx-mod-http-perl
- nginx-mod-http-xslt-filter
- nginx-mod-mail
- nginx-mod-stream
- nispor
- nscd
- nvme-stas
- opal-firmware
- opal-prd
- opal-utils
- openal-soft
- openchange
- openscap-devel
- openscap-python3
- openslp-server
- overpass-fonts
- paktype-naqsh-fonts
- paktype-tehreer-fonts
- pam_ssh_agent_auth
- pangomm
- pentaho-libxml
- pentaho-reporting-flow-engine
- perl-AnyEvent
- perl-B-Hooks-EndOfScope
- perl-Class-Accessor
- perl-Class-Data-Inheritable
- perl-Class-Singleton
- perl-Class-Tiny

- perl-Crypt-OpenSSL-Bignum
- perl-Crypt-OpenSSL-Random
- perl-Crypt-OpenSSL-RSA
- perl-Date-ISO8601
- perl-DateTime
- perl-DateTime-Format-Builder
- perl-DateTime-Format-ISO8601
- perl-DateTime-Format-Strptime
- perl-DateTime-Locale
- perl-DateTime-TimeZone
- perl-DateTime-TimeZone-SystemV
- perl-DateTime-TimeZone-Tzfile
- perl-DB_File
- perl-Devel-CallChecker
- perl-Devel-Caller
- perl-Devel-LexAlias
- perl-Digest-SHA1
- perl-Dist-CheckConflicts
- perl-DynaLoader-Functions
- perl-Encode-Detect
- perl-Eval-Closure
- perl-Exception-Class
- perl-File-chdir
- perl-File-Copy-Recursive
- perl-File-Find-Object
- perl-File-Find-Rule
- perl-HTML-Tree
- perl-Importer
- perl-Mail-AuthenticationResults
- perl-Mail-DKIM
- perl-Mail-Sender
- perl-Mail-SPF
- perl-MIME-Types
- perl-Module-Implementation
- perl-Module-Pluggable
- perl-namespace-autoclean
- perl-namespace-clean

- perl-NetAddr-IP
- perl-Net-CIDR-Lite
- perl-Net-DNS
- perl-Number-Compare
- perl-Package-Stash
- perl-Package-Stash-XS
- perl-PadWalker
- perl-Params-Classify
- perl-Params-Validate
- perl-Params-ValidationCompiler
- perl-Perl-Destruct-Level
- perl-Ref-Util
- perl-Ref-Util-XS
- perl-Scope-Guard
- perl-Specio
- perl-Sub-Identify
- perl-Sub-Info
- perl-Sub-Name
- perl-Switch
- perl-Sys-CPU
- perl-Sys-MemInfo
- perl-Test-LongString
- perl-Test-Taint
- perl-Variable-Magic
- perl-XML-DOM
- perl-XML-RegExp
- perl-XML-Twig
- pinfo
- pki-jackson-annotations
- pki-jackson-core
- pki-jackson-databind
- pki-jackson-jaxrs-json-provider
- pki-jackson-jaxrs-providers
- pki-jackson-module-jaxb-annotations
- pki-resteasy-client
- pki-resteasy-core
- pki-resteasy-jackson2-provider

- pki-resteasy-servlet-initializer
- plymouth-theme-charge
- pmdk-convert
- pmempool
- podman-plugins
- poppler-qt5
- postgresql-test-rpm-macros
- power-profiles-daemon
- pulseaudio-module-x11
- python3.11
- python3.11-cffi
- python3.11-charset-normalizer
- python3.11-cryptography
- python3.11-devel
- python3.11-idna
- python3.11-libs
- python3.11-lxml
- python3.11-mod_wsgi
- python3.11-numpy
- python3.11-numpy-f2py
- python3.11-pip
- python3.11-pip-wheel
- python3.11-ply
- python3.11-psycopg2
- python3.11-pycparser
- python3.11-PyMySQL
- python3.11-PyMySQL+rsa
- python3.11-pysocks
- python3.11-pyyaml
- python3.11-requests
- python3.11-requests+security
- python3.11-requests+socks
- python3.11-scipy
- python3.11-setuptools
- python3.11-setuptools-wheel
- python3.11-six
- python3.11-tkinter

- python3.11-urllib3
- python3.11-wheel
- python3.12-PyMySQL+rsa
- python3-bind
- python3-chardet
- python3-lasso
- python3-libproxy
- python3-netifaces
- python3-nispor
- python3-py
- python3-pycdlib
- python3-pycurl
- python3-pyqt5-sip
- python3-pyrsistent
- python3-pysocks
- python3-pytz
- python3-pywbem
- python3-qt5
- python3-qt5-base
- python3-requests+security
- python3-requests+socks
- python3-scour
- python3-toml
- python3-tomli
- python3-tracer
- python3-wx-siplib
- python-botocore
- python-gflags
- python-netifaces
- python-pyroute2
- python-qt5-rpm-macros
- qgnomeplatform
- qla4xxx
- qt5
- qt5-assistant
- qt5-designer
- qt5-devel

- qt5-doctools
- qt5-linguist
- qt5-qdbusviewer
- qt5-qt3d
- qt5-qt3d-devel
- qt5-qt3d-doc
- qt5-qt3d-examples
- qt5-qtbase
- qt5-qtbase-common
- qt5-qtbase-devel
- qt5-qtbase-doc
- qt5-qtbase-examples
- qt5-qtbase-gui
- qt5-qtbase-mysql
- qt5-qtbase-odbc
- qt5-qtbase-postgresql
- qt5-qtbase-private-devel
- qt5-qtbase-static
- qt5-qtconnectivity
- qt5-qtconnectivity-devel
- qt5-qtconnectivity-doc
- qt5-qtconnectivity-examples
- qt5-qtdeclarative
- qt5-qtdeclarative-devel
- qt5-qtdeclarative-doc
- qt5-qtdeclarative-examples
- qt5-qtdeclarative-static
- qt5-qtddoc
- qt5-qtgraphicaleffects
- qt5-qtgraphicaleffects-doc
- qt5-qtimageformats
- qt5-qtimageformats-doc
- qt5-qtlocation
- qt5-qtlocation-devel
- qt5-qtlocation-doc
- qt5-qtlocation-examples
- qt5-qtmultimedia

- qt5-qtmultimedia-devel
- qt5-qtmultimedia-doc
- qt5-qtmultimedia-examples
- qt5-qtquickcontrols
- qt5-qtquickcontrols2
- qt5-qtquickcontrols2-devel
- qt5-qtquickcontrols2-doc
- qt5-qtquickcontrols2-examples
- qt5-qtquickcontrols-doc
- qt5-qtquickcontrols-examples
- qt5-qtscript
- qt5-qtscript-devel
- qt5-qtscript-doc
- qt5-qtscript-examples
- qt5-qtsensors
- qt5-qtsensors-devel
- qt5-qtsensors-doc
- qt5-qtsensors-examples
- qt5-qtserialbus
- qt5-qtserialbus-devel
- qt5-qtserialbus-doc
- qt5-qtserialbus-examples
- qt5-qtserialport
- qt5-qtserialport-devel
- qt5-qtserialport-doc
- qt5-qtserialport-examples
- qt5-qtsvg
- qt5-qtsvg-devel
- qt5-qtsvg-doc
- qt5-qtsvg-examples
- qt5-qttools
- qt5-qttools-common
- qt5-qttools-devel
- qt5-qttools-doc
- qt5-qttools-examples
- qt5-qttools-libs-designer
- qt5-qttools-libs-designercomponents

- qt5-qttools-libs-help
- qt5-qttools-static
- qt5-qttranslations
- qt5-qtwayland
- qt5-qtwayland-devel
- qt5-qtwayland-doc
- qt5-qtwayland-examples
- qt5-qtwebchannel
- qt5-qtwebchannel-devel
- qt5-qtwebchannel-doc
- qt5-qtwebchannel-examples
- qt5-qtwebsockets
- qt5-qtwebsockets-devel
- qt5-qtwebsockets-doc
- qt5-qtwebsockets-examples
- qt5-qtwebkit-extras
- qt5-qtwebkit-extras-devel
- qt5-qtwebkit-extras-doc
- qt5-qtwebkit-patterns
- qt5-qtwebkit-patterns-devel
- qt5-qtwebkit-patterns-doc
- qt5-qtwebkit-patterns-examples
- qt5-rpm-macros
- qt5-srpm-macros
- raptor2
- rasqal
- redis
- redis-devel
- redis-doc
- redland
- rpmlint
- runc
- saab-fonts
- sac
- scap-workbench
- sendmail
- sendmail-cf

- sendmail-doc
- setxkbmap
- sgabios
- sgabios-bin
- sil-scheherazade-fonts
- spamassassin
- speech-tools-libs
- suitesparse
- sushi
- team
- teamd
- thai-scalable-fonts-common
- thai-scalable-garuda-fonts
- thai-scalable-kinnari-fonts
- thai-scalable-loma-fonts
- thai-scalable-norasi-fonts
- thai-scalable-purisa-fonts
- thai-scalable-sawasdee-fonts
- thai-scalable-tlwgmono-fonts
- thai-scalable-tlwgtypewriter-fonts
- thai-scalable-tlwgtypist-fonts
- thai-scalable-tlwgtypo-fonts
- thai-scalable-umpush-fonts
- thunderbird
- tigervnc
- tigervnc-icons
- tigervnc-license
- tigervnc-selinux
- tigervnc-server
- tigervnc-server-minimal
- tigervnc-server-module
- tracer-common
- ucs-miscfixed-fonts
- usb_modeswitch
- usb_modeswitch-data
- usbredir-server
- webkit2gtk3

- webkit2gtk3-devel
- webkit2gtk3-jsc
- webkit2gtk3-jsc-devel
- wpebackend-fdo
- wpebackend-fdo-devel
- xmlsec1-gcrypt
- xmlsec1-gcrypt-devel
- xmlsec1-gnutls
- xmlsec1-gnutls-devel
- xorg-x11-drivers
- xorg-x11-drv-dummy
- xorg-x11-drv-evdev
- xorg-x11-drv-fbdev
- xorg-x11-drv-libinput
- xorg-x11-drv-v4l
- xorg-x11-drv-vmware
- xorg-x11-drv-wacom
- xorg-x11-drv-wacom-serial-support
- xorg-x11-server-common
- xorg-x11-server-utils
- xorg-x11-server-Xdmx
- xorg-x11-server-Xephyr
- xorg-x11-server-Xnest
- xorg-x11-server-Xorg
- xorg-x11-server-Xvfb
- xorg-x11-utils
- xorg-x11-xbitmaps
- xorg-x11-xinit
- xorg-x11-xinit-session
- xsane
- xsane-common
- xxhash
- xxhash-libs
- yelp
- yelp-libs
- ypbind
- ypserv

- yp-tools
- zhongyi-song-fonts

5

Known Issues

This chapter describes known issues that you may encounter when installing and using the Oracle Linux 9 software. Unless indicated otherwise, the issues apply to both x86_64 and aarch64 systems. Information that pertains only to a specific platform is also noted accordingly.

Installation Issues

The following are known installation issues for Oracle Linux 9.

(aarch64) Minimum XFS File System Size During Install Is 300 MB

The more recent version of the xfsprogs package that's included on the Oracle Linux 9.7 ISO for Arm platforms sets a minimum XFS file system size of 300 MB. This limit isn't applied when installing on x86_64 platforms.

Because the x86_64 ISO includes RHCK, an earlier version of xfsprogs is available to maintain compatibility. On aarch64, only UEK is available and a newer version of xfsprogs is included. The 300 MB limit is set by the newer version of xfsprogs included with UEK 8.

(Bug 37832961)

Virtualization Issues

The following are known virtualization issues for Oracle Linux 9

KVM Virtual Machines Panic When Started on Oracle Linux 9 Hosts

The glibc version that's included with Oracle Linux 9 checks for compatibility between a system's CPU and new architectures that are supported. A system might pass the compatibility check. However, the CPU flags that are set on the system after passing the check might be unknown to the KVM virtual machines that are hosted on that system. Consequently, the VMs panic when they're booted.

To work around this issue, run the following command:

```
virsh edit vm-name
```

Then, add the following declaration in the virtual machine's XML file:

```
<cpu mode='host-model' check='partial' />
```

The check parameter's partial setting sets libvirt to check the VM's CPU specification before starting a domain. However, the rest of the checking remains on the hypervisor, which can still provide a different virtual CPU.

(Bug ID 34224821)

Virtual Machines Fail to Start at Boot Because the `virbr0` Interface Isn't Available

After reboot, the `virbr0` network interface might be missing, which can prevent virtual machines from automatically starting up after boot.

The libvirt daemons on Oracle Linux 9 are modular to handle atomic features within the virtualization environment and are started and run as required, and stopped after two minutes of inactivity. The daemon responsible for setting up the networking interfaces for libvirt is `virtnetworkd`. This service isn't automatically started when a virtual machine is started.

To work around this issue, enable the `virtnetworkd` service so that the service starts at boot:

```
sudo systemctl enable --now virtnetworkd
```

(Bug ID 34237540)

Kernel Issues

The following are known kernel issues in Oracle Linux 9.

Kdump Might Fail on Some AMD Hardware

Kdump might fail on some AMD hardware that's running the current Oracle Linux release. Impacted hardware includes the AMD EPYC CPU servers.

To work around this issue, modify the `/etc/sysconfig/kdump` configuration file and remove the `iommu=off` command line option from the `KDUMP_COMMANDLINE_APPEND` variable. Restart the `kdump` service for the changes to take effect.

This issue appears to affect systems running RHCK.

(Bug ID 31274238, 34211826, 34312626)

(aarch64) Some GUI Elements Aren't Displayed During Installation and Boot Using VGA Output

During installations on the Arm platform, the Oracle Linux installer doesn't display some GUI elements, such as the progress update screen, on VGA output. Output is displayed on the serial console, instead.

Additionally, if you install Oracle Linux with GUI on an encrypted disk, for example, by choosing Server with GUI during the installation stage, and VGA is enabled, the password prompt doesn't appear on the VGA output at system boot, and consequently, the boot process can't be completed. The prompt appears only on a serial console, and therefore, you would need to switch to a serial console to provide the password there.

This issue is specific to systems on the Arm platform only and occurs regardless of whether you are using secure boot or non secure boot. Further, the issue applies to Oracle Linux 8 or Oracle Linux 9 systems that use UEKR6 and UEKR7. The issue occurs wherever Plymouth graphical elements are loaded in the GUI.

To resolve these GUI issues and to cause these elements to display on VGA output without using a serial console, add `plymouth.ignore-serial- consoles` to the kernel command line in the GRUB configuration. For instructions, see [Oracle Linux 9: Managing Kernels and System Boot](#).

(Bug ID 35034465 and 35270637)

Certain SEV Guest Configurations Might Cause Hypervisor CPU Soft-Lockup Warnings

On older generation AMD systems that are based on the AMD Rome processors, such as E2 and E3 systems, a guest with more than 350GB memory that's configured to use Secure Encrypted Virtualization (SEV) memory encryption can trigger a CPU soft-lockup warning on the hypervisor host during guest boot or shutdown operations.

The time that's needed to flush the pinned memory that's being encrypted is proportional to the amount of guest memory. However, with larger amounts of memory in excess of 350GB, the time on the CPU to flush the memory becomes excessive, which consequently triggers a warning. After the memory is flushed, the hypervisor resumes normal operations.

Newer systems that are based on the AMD Milan processor, such as E4 systems, have hardware support that can minimize the time required for flushing the memory. Therefore, the CPU soft-hang issue isn't encountered.

As a workaround, if a SEV enabled guest with more than 350GB of memory is required, create the guest on a system that's based on the AMD Milan processor. If you are using systems with the AMD Rome processor, limit the guest memory to less than 350GB if the guest is configured with SEV memory encryption.

(Bug ID 34050377)

Systems With Btrfs Fail to Boot in FIPS Mode

When booted in FIPS mode, a system using Btrfs fails with the following message:

```
FATAL: FIPS integrity test failed
Refusing to continue
```

(Bug ID 39109133)

6

Package Changes From the Upstream Release

The following sections list the changes to binary and source packages from the upstream release.

Changes to Binary Packages

This section contains information about the removed, modified, and new **binary** packages in this release. For information about the **source** package changes, see [Changes to Source Packages](#).

Added Binary Packages for BaseOS by Oracle

The following binary packages have been added to BaseOS by Oracle:

- bcache-tools
- btrfs-progs
- dtrace
- iwl3945-firmware
- iwl4965-firmware
- iwl6000-firmware
- iwlax2xx-firmware
- kernel-uek
- kernel-uek-core
- kernel-uek-debug
- kernel-uek-debug-core
- kernel-uek-debug-devel
- kernel-uek-debug-modules
- kernel-uek-debug-modules-core
- kernel-uek-debug-modules-desktop
- kernel-uek-debug-modules-extra
- kernel-uek-debug-modules-extra-netfilter
- kernel-uek-debug-modules-usb
- kernel-uek-debug-modules-wireless
- kernel-uek-devel
- kernel-uek-doc

- kernel-uek-modules
- kernel-uek-modules-core
- kernel-uek-modules-desktop
- kernel-uek-modules-extra
- kernel-uek-modules-extra-netfilter
- kernel-uek-modules-usb
- kernel-uek-modules-wireless
- libertas-sd8686-firmware
- libertas-usb8388-firmware
- libertas-usb8388-olpc-firmware
- linux-firmware-core
- liquidio-firmware
- NetworkManager-config-connectivity-oracle
- ocfs2-tools
- oracle-backgrounds
- oracle-indexhtml
- oraclelinux-release
- oraclelinux-release-el9
- oracle-logos
- oracle-logos-httpd
- oracle-logos-ipa

Added Binary Packages for AppStream by Oracle

The following binary packages have been added to AppStream by Oracle:

- dnf-plugin-spacewalk
- dtrace-devel
- dtrace-testsuite
- libblockdev-btrfs
- pcp-pmda-rocestat
- python3-botoecore
- python3-dnf-plugin-spacewalk
- python3-dnf-plugin-ulninfo
- python3-hwdata
- python3-pyOpenSSL
- python3-rhn-check
- python3-rhn-client-tools
- python3-rhnlib

- python3-rhn-setup
- python3-rhn-setup-gnome
- rhn-check
- rhn-client-tools
- rhnlib
- rhnsd
- rhn-setup
- rhn-setup-gnome

Added Binary Packages for CodeReady Linux Builder by Oracle

The following binary packages have been added to CodeReady Linux Builder by Oracle:

- oraclelinux-sb-certs

Modified BaseOS Binary Packages

The following binary packages from the BaseOS upstream release have been modified:

- adcli
- adcli-selinux
- alternatives
- audispd-plugins
- audispd-plugins-zos
- audit
- audit-libs
- autofs
- binutils
- binutils-gold
- biosdevname
- chkconfig
- chrony
- cockpit
- cockpit-bridge
- cockpit-doc
- cockpit-system
- cockpit-ws
- cockpit-ws-selinux
- coreutils
- coreutils-common
- coreutils-single

- crypto-policies
- crypto-policies-scripts
- dbus
- dbus-common
- dbus-libs
- dbus-tools
- dnf
- dnf-automatic
- dnf-data
- dnf-plugins-core
- dracut
- dracut-config-generic
- dracut-config-rescue
- dracut-network
- dracut-squash
- dracut-tools
- efibootmgr
- efi-filesystem
- firewalld
- firewalld-filesystem
- fwupd
- glibc
- glibc-all-langpacks
- glibc-common
- glibc-gconv-extra
- glibc-langpack-aa
- glibc-langpack-af
- glibc-langpack-agr
- glibc-langpack-ak
- glibc-langpack-am
- glibc-langpack-an
- glibc-langpack-anp
- glibc-langpack-ar
- glibc-langpack-as
- glibc-langpack-ast
- glibc-langpack-ayc
- glibc-langpack-az

- glibc-langpack-be
- glibc-langpack-bem
- glibc-langpack-ber
- glibc-langpack-bg
- glibc-langpack-bhb
- glibc-langpack-bho
- glibc-langpack-bi
- glibc-langpack-bn
- glibc-langpack-bo
- glibc-langpack-br
- glibc-langpack-brx
- glibc-langpack-bs
- glibc-langpack-byn
- glibc-langpack-ca
- glibc-langpack-ce
- glibc-langpack-chr
- glibc-langpack-ckb
- glibc-langpack-cmn
- glibc-langpack-crh
- glibc-langpack-cs
- glibc-langpack-csb
- glibc-langpack-cv
- glibc-langpack-cy
- glibc-langpack-da
- glibc-langpack-de
- glibc-langpack-doi
- glibc-langpack-dsb
- glibc-langpack-dv
- glibc-langpack-dz
- glibc-langpack-el
- glibc-langpack-en
- glibc-langpack-eo
- glibc-langpack-es
- glibc-langpack-et
- glibc-langpack-eu
- glibc-langpack-fa
- glibc-langpack-ff

- glibc-langpack-fi
- glibc-langpack-fil
- glibc-langpack-fo
- glibc-langpack-fr
- glibc-langpack-fur
- glibc-langpack-fy
- glibc-langpack-ga
- glibc-langpack-gd
- glibc-langpack-gez
- glibc-langpack-gl
- glibc-langpack-gu
- glibc-langpack-gv
- glibc-langpack-ha
- glibc-langpack-hak
- glibc-langpack-he
- glibc-langpack-hi
- glibc-langpack-hif
- glibc-langpack-hne
- glibc-langpack-hr
- glibc-langpack-hsb
- glibc-langpack-ht
- glibc-langpack-hu
- glibc-langpack-hy
- glibc-langpack-ia
- glibc-langpack-id
- glibc-langpack-ig
- glibc-langpack-ik
- glibc-langpack-is
- glibc-langpack-it
- glibc-langpack-iu
- glibc-langpack-ja
- glibc-langpack-ka
- glibc-langpack-kab
- glibc-langpack-kk
- glibc-langpack-kl
- glibc-langpack-km
- glibc-langpack-kn

- glibc-langpack-ko
- glibc-langpack-kok
- glibc-langpack-ks
- glibc-langpack-ku
- glibc-langpack-kw
- glibc-langpack-ky
- glibc-langpack-lb
- glibc-langpack-lg
- glibc-langpack-li
- glibc-langpack-lij
- glibc-langpack-ln
- glibc-langpack-lo
- glibc-langpack-lt
- glibc-langpack-lv
- glibc-langpack-lzh
- glibc-langpack-mag
- glibc-langpack-mai
- glibc-langpack-mfe
- glibc-langpack-mg
- glibc-langpack-mhr
- glibc-langpack-mi
- glibc-langpack-miq
- glibc-langpack-mjw
- glibc-langpack-mk
- glibc-langpack-ml
- glibc-langpack-mn
- glibc-langpack-mni
- glibc-langpack-mnw
- glibc-langpack-mr
- glibc-langpack-ms
- glibc-langpack-mt
- glibc-langpack-my
- glibc-langpack-nan
- glibc-langpack-nb
- glibc-langpack-nds
- glibc-langpack-ne
- glibc-langpack-nhn

- glibc-langpack-niu
- glibc-langpack-nl
- glibc-langpack-nn
- glibc-langpack-nr
- glibc-langpack-nso
- glibc-langpack-oc
- glibc-langpack-om
- glibc-langpack-or
- glibc-langpack-os
- glibc-langpack-pa
- glibc-langpack-pap
- glibc-langpack-pl
- glibc-langpack-ps
- glibc-langpack-pt
- glibc-langpack-quz
- glibc-langpack-raj
- glibc-langpack-ro
- glibc-langpack-ru
- glibc-langpack-rw
- glibc-langpack-sa
- glibc-langpack-sah
- glibc-langpack-sat
- glibc-langpack-sc
- glibc-langpack-sd
- glibc-langpack-se
- glibc-langpack-sgs
- glibc-langpack-shn
- glibc-langpack-shs
- glibc-langpack-si
- glibc-langpack-sid
- glibc-langpack-sk
- glibc-langpack-sl
- glibc-langpack-sm
- glibc-langpack-so
- glibc-langpack-sq
- glibc-langpack-sr
- glibc-langpack-ss

- glibc-langpack-st
- glibc-langpack-sv
- glibc-langpack-sw
- glibc-langpack-szl
- glibc-langpack-ta
- glibc-langpack-tcy
- glibc-langpack-te
- glibc-langpack-tg
- glibc-langpack-th
- glibc-langpack-the
- glibc-langpack-ti
- glibc-langpack-tig
- glibc-langpack-tk
- glibc-langpack-tl
- glibc-langpack-tn
- glibc-langpack-to
- glibc-langpack-tpi
- glibc-langpack-tr
- glibc-langpack-ts
- glibc-langpack-tt
- glibc-langpack-ug
- glibc-langpack-uk
- glibc-langpack-unm
- glibc-langpack-ur
- glibc-langpack-uz
- glibc-langpack-ve
- glibc-langpack-vi
- glibc-langpack-wa
- glibc-langpack-wae
- glibc-langpack-wal
- glibc-langpack-wo
- glibc-langpack-xh
- glibc-langpack-yi
- glibc-langpack-yo
- glibc-langpack-yue
- glibc-langpack-yuw
- glibc-langpack-zh

- glibc-langpack-zu
- glibc-minimal-langpack
- grub2-common
- grub2-efi-aa64-modules
- grub2-efi-x64
- grub2-efi-x64-cdboot
- grub2-efi-x64-modules
- grub2-pc
- grub2-pc-modules
- grub2-tools
- grub2-tools-efi
- grub2-tools-extra
- grub2-tools-minimal
- grubby
- initscripts
- initscripts-rename-device
- initscripts-service
- iputils
- irqbalance
- iscsi-initiator-utils
- iscsi-initiator-utils-iscsiuio
- iwl1000-firmware
- iwl100-firmware
- iwl105-firmware
- iwl135-firmware
- iwl2000-firmware
- iwl2030-firmware
- iwl3160-firmware
- iwl3945-firmware
- iwl4965-firmware
- iwl5000-firmware
- iwl5150-firmware
- iwl6000-firmware
- iwl6000g2a-firmware
- iwl6000g2b-firmware
- iwl6050-firmware
- iwl7260-firmware

- iwlan2xx-firmware
- kexec-tools
- kmod
- kmod-kvdo
- kmod-libs
- krb5-libs
- krb5-pkinit
- krb5-server
- krb5-server-ldap
- krb5-workstation
- krb5-xrealmauthz
- libatomic
- libblkid
- libdb
- libdnf
- libertas-sd8686-firmware
- libertas-sd8787-firmware
- libertas-usb8388-firmware
- libertas-usb8388-olpc-firmware
- libfdisk
- libgcc
- libgfortran
- libgomp
- libipa_hbac
- libkadm5
- libkcapi
- libkcapi-hmaccalc
- libmount
- libnfsidmap
- libnsl
- libnvme
- libquadmath
- libreport-filesystem
- libsmartcols
- libsss_autofs
- libsss_certmap
- libsss_idmap

- libsss_nss_idmap
- libsss_simpleifp
- libsss_sudo
- libstdc++
- libuuid
- linux-firmware
- linux-firmware-core
- linux-firmware-whence
- liquidio-firmware
- mcelog
- mdadm
- microcode_ctl
- netconsole-service
- netronome-firmware
- NetworkManager
- NetworkManager-adsl
- NetworkManager-bluetooth
- NetworkManager-config-connectivity-oracle
- NetworkManager-config-server
- NetworkManager-initscripts-updown
- NetworkManager-libnm
- NetworkManager-team
- NetworkManager-tui
- NetworkManager-wifi
- NetworkManager-wwan
- nfs-utils
- nscd
- nvme-cli
- nvmetcli
- openssh
- openssh-clients
- openssh-keycat
- openssh-server
- openssl
- openssl-fips-provider
- openssl-fips-provider-so
- openssl-lib

- os-prober
- pam
- parted
- pcre2
- pcre2-syntax
- polkit
- polkit-libs
- procps-ng
- procps-ng-i18n
- python3
- python3-cffi
- python3-chardet
- python3-configshell
- python3-dmidecode
- python3-dnf
- python3-dnf-plugin-multisig
- python3-dnf-plugin-post-transaction-actions
- python3-dnf-plugins-core
- python3-dnf-plugin-versionlock
- python3-firewall
- python3-hawkey
- python3-idna
- python3-libdnf
- python3-libipa_hbac
- python3-libs
- python3-libsss_nss_idmap
- python3-ply
- python3-pycparser
- python3-pysocks
- python3-pyyaml
- python3-six
- python3-sss
- python3-sssdconfig
- python3-sss-murmur
- readonly-root
- redhat-release
- rhel-net-naming-sysattrs

- selinux-policy
- selinux-policy-doc
- selinux-policy-mls
- selinux-policy-sandbox
- selinux-policy-targeted
- shim-x64
- smartmontools
- sos
- sos-audit
- sssd
- sssd-ad
- sssd-client
- sssd-common
- sssd-common-pac
- sssd-dbus
- sssd-ipa
- sssd-kcm
- sssd-krb5
- sssd-krb5-common
- sssd-ldap
- sssd-nfs-idmap
- sssd-passkey
- sssd-polkit-rules
- sssd-proxy
- sssd-tools
- sssd-winbind-idmap
- systemd
- systemd-container
- systemd-libs
- systemd-oomd
- systemd-pam
- systemd-resolved
- systemd-rpm-macros
- systemd-udev
- tpm2-tools
- tuned
- tuned-profiles-cpu-partitioning

- util-linux
- util-linux-core
- util-linux-user
- vim-filesystem
- vim-minimal
- yum
- yum-utils

Modified Binary Packages for CodeReady Linux Builder by Oracle

The following binary packages to CodeReady Linux Builder by Oracle have been modified:

- anaconda-widgets-devel
- bind-devel
- bind-doc
- crash-devel
- cups-filters-devel
- dotnet-sdk-10.0-source-built-artifacts
- dotnet-sdk-6.0-source-built-artifacts
- dotnet-sdk-7.0-source-built-artifacts
- dotnet-sdk-8.0-source-built-artifacts
- dotnet-sdk-9.0-source-built-artifacts
- edk2-aarch64
- edk2-tools
- edk2-tools-doc
- expect-devel
- fwupd-devel
- gdal-devel
- gdm-devel
- gdm-pam-extensions-devel
- glibc-benchtests
- glibc-nss-devel
- glibc-static
- java-11-openjdk-demo-fastdebug
- java-11-openjdk-demo-slowdebug
- java-11-openjdk-devel-fastdebug
- java-11-openjdk-devel-slowdebug
- java-11-openjdk-fastdebug
- java-11-openjdk-headless-fastdebug

- java-11-openjdk-headless-slowdebug
- java-11-openjdk-jmods-fastdebug
- java-11-openjdk-jmods-slowdebug
- java-11-openjdk-slowdebug
- java-11-openjdk-src-fastdebug
- java-11-openjdk-src-slowdebug
- java-11-openjdk-static-libs-fastdebug
- java-11-openjdk-static-libs-slowdebug
- java-17-openjdk-demo-fastdebug
- java-17-openjdk-demo-slowdebug
- java-17-openjdk-devel-fastdebug
- java-17-openjdk-devel-slowdebug
- java-17-openjdk-fastdebug
- java-17-openjdk-headless-fastdebug
- java-17-openjdk-headless-slowdebug
- java-17-openjdk-jmods-fastdebug
- java-17-openjdk-jmods-slowdebug
- java-17-openjdk-slowdebug
- java-17-openjdk-src-fastdebug
- java-17-openjdk-src-slowdebug
- java-17-openjdk-static-libs-fastdebug
- java-17-openjdk-static-libs-slowdebug
- java-1.8.0-openjdk-demo-fastdebug
- java-1.8.0-openjdk-demo-slowdebug
- java-1.8.0-openjdk-devel-fastdebug
- java-1.8.0-openjdk-devel-slowdebug
- java-1.8.0-openjdk-fastdebug
- java-1.8.0-openjdk-headless-fastdebug
- java-1.8.0-openjdk-headless-slowdebug
- java-1.8.0-openjdk-slowdebug
- java-1.8.0-openjdk-src-fastdebug
- java-1.8.0-openjdk-src-slowdebug
- java-21-openjdk-demo-fastdebug
- java-21-openjdk-demo-slowdebug
- java-21-openjdk-devel-fastdebug
- java-21-openjdk-devel-slowdebug
- java-21-openjdk-fastdebug

- java-21-openjdk-headless-fastdebug
- java-21-openjdk-headless-slowdebug
- java-21-openjdk-jmods-fastdebug
- java-21-openjdk-jmods-slowdebug
- java-21-openjdk-slowdebug
- java-21-openjdk-src-fastdebug
- java-21-openjdk-src-slowdebug
- java-21-openjdk-static-libs-fastdebug
- java-21-openjdk-static-libs-slowdebug
- java-25-openjdk-crypto-adapter-fastdebug
- java-25-openjdk-crypto-adapter-slowdebug
- java-25-openjdk-demo-fastdebug
- java-25-openjdk-demo-slowdebug
- java-25-openjdk-devel-fastdebug
- java-25-openjdk-devel-slowdebug
- java-25-openjdk-fastdebug
- java-25-openjdk-headless-fastdebug
- java-25-openjdk-headless-slowdebug
- java-25-openjdk-jmods-fastdebug
- java-25-openjdk-jmods-slowdebug
- java-25-openjdk-slowdebug
- java-25-openjdk-src-fastdebug
- java-25-openjdk-src-slowdebug
- java-25-openjdk-static-libs-fastdebug
- java-25-openjdk-static-libs-slowdebug
- kmod-devel
- libdb-cxx
- libdb-cxx-devel
- libdb-devel-doc
- libdb-sql
- libdb-sql-devel
- libdnf-devel
- libfdisk-devel
- libgfortran-static
- libguestfs-devel
- libguestfs-gobject
- libguestfs-gobject-devel

- libguestfs-man-pages-ja
- libguestfs-man-pages-uk
- libnfsidmap-devel
- libnvme-devel
- libquadmath-static
- librados-devel
- libradospp-devel
- librbd-devel
- libreoffice-sdk
- libreoffice-sdk-doc
- libsmartcols-devel
- libsss_certmap-devel
- libsss_idmap-devel
- libsss_nss_idmap-devel
- libstdc++-static
- libudisks2-devel
- libvirt-daemon-plugin-sanlock
- libvirt-devel
- libvirt-docs
- lua-guestfs
- munge-devel
- NetworkManager-libnm-devel
- nss_db
- nss_hesiod
- ocaml-libguestfs
- ocaml-libguestfs-devel
- OpenIPMI-devel
- PackageKit-glib-devel
- papi-testsuite
- parted-devel
- pcre2-tools
- php-libguestfs
- procps-ng-devel
- python3.11-debug
- python3.11-idle
- python3.11-test
- python3.12-debug

- python3.12-idle
- python3.12-test
- python3-debug
- python3-idle
- python3-ipatests
- python3-mpich
- python3-psutil-tests
- python3-test
- python-packaging-doc
- ruby-libguestfs
- sanlock-devel
- sendmail-milter
- sendmail-milter-devel
- tog-pegasus-devel
- virt-v2v-man-pages-ja
- virt-v2v-man-pages-uk
- WALinuxAgent-cvm

Modified AppStream Binary Packages

The following binary packages from the AppStream upstream release have been modified:

- anaconda
- anaconda-core
- anaconda-dracut
- anaconda-gui
- anaconda-install-env-deps
- anaconda-install-img-deps
- anaconda-tui
- anaconda-user-help
- anaconda-widgets
- aspNetcore-runtime-10.0
- aspNetcore-runtime-6.0
- aspNetcore-runtime-7.0
- aspNetcore-runtime-8.0
- aspNetcore-runtime-9.0
- aspNetcore-runtime-dbg-10.0
- aspNetcore-runtime-dbg-8.0
- aspNetcore-runtime-dbg-9.0

- `aspnetcore-targeting-pack-10.0`
- `aspnetcore-targeting-pack-6.0`
- `aspnetcore-targeting-pack-7.0`
- `aspnetcore-targeting-pack-8.0`
- `aspnetcore-targeting-pack-9.0`
- `audit-libs-devel`
- `autocorr-af`
- `autocorr-bg`
- `autocorr-ca`
- `autocorr-cs`
- `autocorr-da`
- `autocorr-de`
- `autocorr-dsb`
- `autocorr-el`
- `autocorr-en`
- `autocorr-es`
- `autocorr-fa`
- `autocorr-fi`
- `autocorr-fr`
- `autocorr-ga`
- `autocorr-hr`
- `autocorr-hsb`
- `autocorr-hu`
- `autocorr-is`
- `autocorr-it`
- `autocorr-ja`
- `autocorr-ko`
- `autocorr-lb`
- `autocorr-lt`
- `autocorr-mn`
- `autocorr-nl`
- `autocorr-pl`
- `autocorr-pt`
- `autocorr-ro`
- `autocorr-ru`
- `autocorr-sk`
- `autocorr-sl`

- autocorr-sr
- autocorr-sv
- autocorr-tr
- autocorr-vi
- autocorr-vro
- autocorr-zh
- bind
- bind9.18-dyndb-ldap
- bind-chroot
- bind-dnssec-doc
- bind-dnssec-utils
- bind-libs
- bind-license
- bind-utils
- binutils-devel
- blivet-data
- boom-boot
- boom-boot-conf
- buildah
- buildah-tests
- clang-resource-filesystem
- cloud-init
- cockpit-composer
- cockpit-machines
- cockpit-packagekit
- cockpit-session-recording
- cockpit-storaged
- compat-libgfortran-48
- containers-common
- containers-common-extra
- container-tools
- cpp
- crash
- cups-filters
- cups-filters-libs
- dbus-daemon
- dbus-devel

- `dbus-x11`
- `ddiskit`
- `delve`
- `dnf-bootc`
- `dotnet-apphost-pack-10.0`
- `dotnet-apphost-pack-6.0`
- `dotnet-apphost-pack-7.0`
- `dotnet-apphost-pack-8.0`
- `dotnet-apphost-pack-9.0`
- `dotnet-host`
- `dotnet-hostfxr-10.0`
- `dotnet-hostfxr-6.0`
- `dotnet-hostfxr-7.0`
- `dotnet-hostfxr-8.0`
- `dotnet-hostfxr-9.0`
- `dotnet-runtime-10.0`
- `dotnet-runtime-6.0`
- `dotnet-runtime-7.0`
- `dotnet-runtime-8.0`
- `dotnet-runtime-9.0`
- `dotnet-runtime-dbg-10.0`
- `dotnet-runtime-dbg-8.0`
- `dotnet-runtime-dbg-9.0`
- `dotnet-sdk-10.0`
- `dotnet-sdk-6.0`
- `dotnet-sdk-7.0`
- `dotnet-sdk-8.0`
- `dotnet-sdk-9.0`
- `dotnet-sdk-aot-10.0`
- `dotnet-sdk-aot-9.0`
- `dotnet-sdk-dbg-10.0`
- `dotnet-sdk-dbg-8.0`
- `dotnet-sdk-dbg-9.0`
- `dotnet-targeting-pack-10.0`
- `dotnet-targeting-pack-6.0`
- `dotnet-targeting-pack-7.0`
- `dotnet-targeting-pack-8.0`

- dotnet-targeting-pack-9.0
- dotnet-templates-10.0
- dotnet-templates-6.0
- dotnet-templates-7.0
- dotnet-templates-8.0
- dotnet-templates-9.0
- dracut-caps
- dracut-live
- edk2-ovmf
- efi-srpm-macros
- expect
- fips-provider-next
- firefox
- firefox-x11
- firewall-applet
- firewall-config
- fwupd-plugin-flashrom
- galera
- gcc
- gcc-c++
- gcc-gfortran
- gcc-offload-nvptx
- gcc-plugin-annobin
- gcc-plugin-devel
- gcc-toolset-12-gcc
- gcc-toolset-12-gcc-c++
- gcc-toolset-12-gcc-gfortran
- gcc-toolset-12-gcc-plugin-annobin
- gcc-toolset-12-gcc-plugin-devel
- gcc-toolset-12-libasan-devel
- gcc-toolset-12-libatomic-devel
- gcc-toolset-12-libgccjit
- gcc-toolset-12-libgccjit-devel
- gcc-toolset-12-libgccjit-docs
- gcc-toolset-12-libitm-devel
- gcc-toolset-12-liblsan-devel
- gcc-toolset-12-libquadmath-devel

- gcc-toolset-12-libstdc++-devel
- gcc-toolset-12-libstdc++-docs
- gcc-toolset-12-libtsan-devel
- gcc-toolset-12-libubsan-devel
- gcc-toolset-12-offload-nvptx
- gcc-toolset-13-binutils
- gcc-toolset-13-binutils-devel
- gcc-toolset-13-binutils-gold
- gdal
- gdal-libs
- gdb
- gdb-doc
- gdb-gdbserver
- gdb-headless
- gdb-minimal
- gdm
- glibc-devel
- glibc-doc
- glibc-headers
- glibc-locale-source
- glibc-utils
- gnome-session
- gnome-session-wayland-session
- gnome-session-xsession
- gnome-shell-extension-background-logo
- golang
- golang-bin
- golang-docs
- golang-misc
- golang-race
- golang-src
- golang-tests
- go-toolset
- gpsd-minimal
- gpsd-minimal-clients
- httpd
- httpd-core

- httpd-devel
- httpd-filesystem
- httpd-manual
- httpd-tools
- idm-pki-acme
- idm-pki-base
- idm-pki-ca
- idm-pki-java
- idm-pki-kra
- idm-pki-server
- idm-pki-tools
- image-builder
- initial-setup
- initial-setup-gui
- ipa-client
- ipa-client-common
- ipa-client-encrypted-dns
- ipa-client-epn
- ipa-client-samba
- ipa-common
- ipa-selinux
- ipa-selinux-luna
- ipa-selinux-nfast
- ipa-server
- ipa-server-common
- ipa-server-dns
- ipa-server-encrypted-dns
- ipa-server-trust-ad
- iputils-ninford
- java-11-openjdk
- java-11-openjdk-demo
- java-11-openjdk-devel
- java-11-openjdk-headless
- java-11-openjdk-javadoc
- java-11-openjdk-javadoc-zip
- java-11-openjdk-jmods
- java-11-openjdk-src

- java-11-openjdk-static-libs
- java-17-openjdk
- java-17-openjdk-demo
- java-17-openjdk-devel
- java-17-openjdk-headless
- java-17-openjdk-javadoc
- java-17-openjdk-javadoc-zip
- java-17-openjdk-jmods
- java-17-openjdk-src
- java-17-openjdk-static-libs
- java-1.8.0-openjdk
- java-1.8.0-openjdk-demo
- java-1.8.0-openjdk-devel
- java-1.8.0-openjdk-headless
- java-1.8.0-openjdk-javadoc
- java-1.8.0-openjdk-javadoc-zip
- java-1.8.0-openjdk-src
- java-21-openjdk
- java-21-openjdk-demo
- java-21-openjdk-devel
- java-21-openjdk-headless
- java-21-openjdk-javadoc
- java-21-openjdk-javadoc-zip
- java-21-openjdk-jmods
- java-21-openjdk-src
- java-21-openjdk-static-libs
- java-25-openjdk
- java-25-openjdk-crypto-adapter
- java-25-openjdk-demo
- java-25-openjdk-devel
- java-25-openjdk-headless
- java-25-openjdk-javadoc
- java-25-openjdk-javadoc-zip
- java-25-openjdk-jmods
- java-25-openjdk-src
- java-25-openjdk-static-libs
- kernel-rpm-macros

- kernel-srpm-macros
- krb5-devel
- ksh
- libasan
- libblkid-devel
- libblockdev
- libblockdev-btrfs
- libblockdev-crypto
- libblockdev-dm
- libblockdev-fs
- libblockdev-kbd
- libblockdev-loop
- libblockdev-lvm
- libblockdev-lvm-dbus
- libblockdev-mdraid
- libblockdev-mpath
- libblockdev-nvdim
- libblockdev-nvme
- libblockdev-part
- libblockdev-plugins-all
- libblockdev-swap
- libblockdev-tools
- libblockdev-utils
- libdb-devel
- libdb-utils
- libgccjit
- libgccjit-devel
- libgomp-offload-nvptx
- libguestfs
- libguestfs-appliance
- libguestfs-bash-completion
- libguestfs-inspect-icons
- libguestfs-rescue
- libguestfs-rsync
- libguestfs-xfs
- libitm
- libitm-devel

- libkdumpfile
- libkdumpfile-devel
- liblsan
- libmount-devel
- libquadmath-devel
- librados2
- librbdl
- libreoffice
- libreoffice-base
- libreoffice-calc
- libreoffice-core
- libreoffice-data
- libreoffice-draw
- libreoffice-emailmerge
- libreoffice-filters
- libreoffice-gdb-debug-support
- libreoffice-graphicsfilter
- libreoffice-gtk3
- libreoffice-help-ar
- libreoffice-help-bg
- libreoffice-help-bn
- libreoffice-help-ca
- libreoffice-help-cs
- libreoffice-help-da
- libreoffice-help-de
- libreoffice-help-dz
- libreoffice-help-el
- libreoffice-help-en
- libreoffice-help-eo
- libreoffice-help-es
- libreoffice-help-et
- libreoffice-help-eu
- libreoffice-help-fi
- libreoffice-help-fr
- libreoffice-help-gl
- libreoffice-help-gu
- libreoffice-help-he

- libreoffice-help-hi
- libreoffice-help-hr
- libreoffice-help-hu
- libreoffice-help-id
- libreoffice-help-it
- libreoffice-help-ja
- libreoffice-help-ko
- libreoffice-help-lt
- libreoffice-help-lv
- libreoffice-help-nb
- libreoffice-help-nl
- libreoffice-help-nn
- libreoffice-help-pl
- libreoffice-help-pt-BR
- libreoffice-help-pt-PT
- libreoffice-help-ro
- libreoffice-help-ru
- libreoffice-help-si
- libreoffice-help-sk
- libreoffice-help-sl
- libreoffice-help-sv
- libreoffice-help-ta
- libreoffice-help-tr
- libreoffice-help-uk
- libreoffice-help-zh-Hans
- libreoffice-help-zh-Hant
- libreoffice-impress
- libreofficekit
- libreoffice-langpack-af
- libreoffice-langpack-ar
- libreoffice-langpack-as
- libreoffice-langpack-bg
- libreoffice-langpack-bn
- libreoffice-langpack-br
- libreoffice-langpack-ca
- libreoffice-langpack-cs
- libreoffice-langpack-cy

- libreoffice-langpack-da
- libreoffice-langpack-de
- libreoffice-langpack-dz
- libreoffice-langpack-el
- libreoffice-langpack-en
- libreoffice-langpack-eo
- libreoffice-langpack-es
- libreoffice-langpack-et
- libreoffice-langpack-eu
- libreoffice-langpack-fa
- libreoffice-langpack-fi
- libreoffice-langpack-fr
- libreoffice-langpack-fy
- libreoffice-langpack-ga
- libreoffice-langpack-gl
- libreoffice-langpack-gu
- libreoffice-langpack-he
- libreoffice-langpack-hi
- libreoffice-langpack-hr
- libreoffice-langpack-hu
- libreoffice-langpack-id
- libreoffice-langpack-it
- libreoffice-langpack-ja
- libreoffice-langpack-kk
- libreoffice-langpack-kn
- libreoffice-langpack-ko
- libreoffice-langpack-lt
- libreoffice-langpack-lv
- libreoffice-langpack-mai
- libreoffice-langpack-ml
- libreoffice-langpack-mr
- libreoffice-langpack-nb
- libreoffice-langpack-nl
- libreoffice-langpack-nn
- libreoffice-langpack-nr
- libreoffice-langpack-nso
- libreoffice-langpack-or

- libreoffice-langpack-pa
- libreoffice-langpack-pl
- libreoffice-langpack-pt-BR
- libreoffice-langpack-pt-PT
- libreoffice-langpack-ro
- libreoffice-langpack-ru
- libreoffice-langpack-si
- libreoffice-langpack-sk
- libreoffice-langpack-sl
- libreoffice-langpack-sr
- libreoffice-langpack-ss
- libreoffice-langpack-st
- libreoffice-langpack-sv
- libreoffice-langpack-ta
- libreoffice-langpack-te
- libreoffice-langpack-th
- libreoffice-langpack-tn
- libreoffice-langpack-tr
- libreoffice-langpack-ts
- libreoffice-langpack-uk
- libreoffice-langpack-ve
- libreoffice-langpack-xh
- libreoffice-langpack-zh-Hans
- libreoffice-langpack-zh-Hant
- libreoffice-langpack-zu
- libreoffice-math
- libreoffice-ogltrans
- libreoffice-opensymbol-fonts
- libreoffice-pdfimport
- libreoffice-pyuno
- libreoffice-ure
- libreoffice-ure-common
- libreoffice-wiki-publisher
- libreoffice-writer
- libreoffice-x11
- libreoffice-xsltfilter
- libreport

- libreport-anaconda
- libreport-cli
- libreport-gtk
- libreport-plugin-bugzilla
- libreport-plugin-reportuploader
- libreport-web
- libreswan
- libstdc++-devel
- libstdc++-docs
- libtsan
- libubsan
- libudisks2
- libuuid-devel
- libvirt
- libvirt-client
- libvirt-client-qemu
- libvirt-daemon
- libvirt-daemon-common
- libvirt-daemon-config-network
- libvirt-daemon-config-nwfilter
- libvirt-daemon-driver-interface
- libvirt-daemon-driver-network
- libvirt-daemon-driver-nodedev
- libvirt-daemon-driver-nwfilter
- libvirt-daemon-driver-qemu
- libvirt-daemon-driver-secret
- libvirt-daemon-driver-storage
- libvirt-daemon-driver-storage-core
- libvirt-daemon-driver-storage-disk
- libvirt-daemon-driver-storage-iscsi
- libvirt-daemon-driver-storage-logical
- libvirt-daemon-driver-storage-mpath
- libvirt-daemon-driver-storage-rbd
- libvirt-daemon-driver-storage-scsi
- libvirt-daemon-kvm
- libvirt-daemon-lock
- libvirt-daemon-log

- libvirt-daemon-plugin-lockd
- libvirt-daemon-proxy
- libvirt-libs
- libvirt-nss
- libvirt-ssh-proxy
- libxslt
- libxslt-devel
- lorax
- lorax-docs
- lorax-lmc-novirt
- lorax-lmc-virt
- lorax-templates-generic
- lorax-templates-rhel
- mecab-ipadic
- mecab-ipadic-EUCJP
- mesa-compat-libOSMesa
- mesa-compat-libOSMesa-devel
- mesa-compat-libxatracker
- mesa-compat-libxatracker-devel
- mod_ldap
- mod_lua
- mod_proxy_html
- mod_session
- mod_ssl
- mpich
- mpich-autoload
- mpich-devel
- mpich-doc
- mrtg
- munge
- munge-libs
- net-snmp
- net-snmp-agent-libs
- net-snmp-devel
- net-snmp-libs
- net-snmp-perl
- net-snmp-utils

- netstandard-targeting-pack-2.1
- NetworkManager-cloud-setup
- NetworkManager-dispatcher-routing-rules
- NetworkManager-ovs
- NetworkManager-ppp
- nfs-utils-coreos
- nfsv4-client-utils
- nginx
- nginx-all-modules
- nginx-core
- nginx-filesystem
- nginx-mod-devel
- nginx-mod-http-image-filter
- nginx-mod-http-perl
- nginx-mod-http-xslt-filter
- nginx-mod-mail
- nginx-mod-stream
- ntsysv
- opa-address-resolution
- opa-basic-tools
- opa-fastfabric
- opa-fm
- opa-libopamgt
- OpenIPMI
- OpenIPMI-lanserv
- OpenIPMI-libs
- openssh-askpass
- openssl-devel
- openssl-perl
- open-vm-tools
- open-vm-tools-desktop
- open-vm-tools-salt-minion
- open-vm-tools-sdmp
- open-vm-tools-test
- osbuild
- osbuild-container-selinux
- osbuild-depsolve-dnf

- osbuild-initrd
- osbuild-luks2
- osbuild-lvm2
- osbuild-ostree
- osbuild-selinux
- osinfo-db
- pacemaker-cluster-libs
- pacemaker-libs
- pacemaker-schemas
- PackageKit
- PackageKit-command-not-found
- PackageKit-glib
- PackageKit-gstreamer-plugin
- PackageKit-gtk3-module
- pam-devel
- pam-docs
- pam_ssh_agent_auth
- papi
- papi-devel
- papi-libs
- pcp
- pcp-conf
- pcp-devel
- pcp-doc
- pcp-export-pcp2elasticsearch
- pcp-export-pcp2graphite
- pcp-export-pcp2influxdb
- pcp-export-pcp2json
- pcp-export-pcp2openmetrics
- pcp-export-pcp2spark
- pcp-export-pcp2xml
- pcp-export-pcp2zabbix
- pcp-export-zabbix-agent
- pcp-geolocate
- pcp-gui
- pcp-import-collectl2pcp
- pcp-import-ganglia2pcp

- `pcp-import-iostat2pcp`
- `pcp-import-mrtg2pcp`
- `pcp-import-sar2pcp`
- `pcp-libs`
- `pcp-libs-devel`
- `pcp-pmda-activemq`
- `pcp-pmda-amdgpu`
- `pcp-pmda-apache`
- `pcp-pmda-bash`
- `pcp-pmda-bcc`
- `pcp-pmda-bind2`
- `pcp-pmda-bonding`
- `pcp-pmda-bpf`
- `pcp-pmda-bpftrace`
- `pcp-pmda-cifs`
- `pcp-pmda-cisco`
- `pcp-pmda-dbping`
- `pcp-pmda-denki`
- `pcp-pmda-dm`
- `pcp-pmda-docker`
- `pcp-pmda-ds389`
- `pcp-pmda-ds389log`
- `pcp-pmda-elasticsearch`
- `pcp-pmda-farm`
- `pcp-pmda-gfs2`
- `pcp-pmda-gluster`
- `pcp-pmda-gpfs`
- `pcp-pmda-gpsd`
- `pcp-pmda-hacluster`
- `pcp-pmda-haproxy`
- `pcp-pmda-infiniband`
- `pcp-pmda-json`
- `pcp-pmda-libvirt`
- `pcp-pmda-lio`
- `pcp-pmda-lmsensors`
- `pcp-pmda-logger`
- `pcp-pmda-lustre`

- pcp-pmda-lustrecomm
- pcp-pmda-mailq
- pcp-pmda-memcache
- pcp-pmda-mic
- pcp-pmda-mongodb
- pcp-pmda-mounts
- pcp-pmda-mssql
- pcp-pmda-mysql
- pcp-pmda-named
- pcp-pmda-netcheck
- pcp-pmda-netfilter
- pcp-pmda-news
- pcp-pmda-nfsclient
- pcp-pmda-nginx
- pcp-pmda-nvidia-gpu
- pcp-pmda-openmetrics
- pcp-pmda-openvswitch
- pcp-pmda-oracle
- pcp-pmda-pdns
- pcp-pmda-perfevent
- pcp-pmda-podman
- pcp-pmda-postfix
- pcp-pmda-postgresql
- pcp-pmda-rabbitmq
- pcp-pmda-redis
- pcp-pmda-resctrl
- pcp-pmda-rocestat
- pcp-pmda-roomtemp
- pcp-pmda-rsyslog
- pcp-pmda-samba
- pcp-pmda-sendmail
- pcp-pmda-shping
- pcp-pmda-slurm
- pcp-pmda-smart
- pcp-pmda-snmp
- pcp-pmda-sockets
- pcp-pmda-statsd

- pcp-pmda-summary
- pcp-pmda-systemd
- pcp-pmda-trace
- pcp-pmda-unbound
- pcp-pmda-uwsgi
- pcp-pmda-weblog
- pcp-pmda-zimbra
- pcp-pmda-zswap
- pcp-selinux
- pcp-system-tools
- pcp-testsuite
- pcp-zeroconf
- pcre2-devel
- pcre2-utf16
- pcre2-utf32
- perl-PCP-LogImport
- perl-PCP-LogSummary
- perl-PCP-MMV
- perl-PCP-PMDA
- perl-Sys-Guestfs
- perl-XML-Parser
- pesign
- plymouth
- plymouth-core-libs
- plymouth-devel
- plymouth-graphics-libs
- plymouth-plugin-fade-throbber
- plymouth-plugin-label
- plymouth-plugin-script
- plymouth-plugin-space-flares
- plymouth-plugin-two-step
- plymouth-scripts
- plymouth-system-theme
- plymouth-theme-charge
- plymouth-theme-fade-in
- plymouth-theme-script
- plymouth-theme-solar

- plymouth-theme-spinfinity
- plymouth-theme-spinner
- podman
- podman-docker
- podman-plugins
- podman-remote
- podman-tests
- polkit-devel
- polkit-docs
- pykickstart
- python3.11
- python3.11-devel
- python3.11-libs
- python3.11-tkinter
- python3.12
- python3.12-devel
- python3.12-libs
- python3.12-tkinter
- python3-attrs
- python3-audit
- python3-bind
- python3-blivet
- python3-blockdev
- python3-boom
- python3-devel
- python3-dnf-plugin-leaves
- python3-dnf-plugin-modulesync
- python3-dnf-plugin-show-leaves
- python3-idm-pki
- python3-ipaclient
- python3-ipalib
- python3-ipaserver
- python3-iscsi-initiator-utils
- python3-kickstart
- python3-libguestfs
- python3-libmount
- python3-libnvme

- python3-libreport
- python3-net-snmp
- python3-osbuild
- python3-packaging
- python3-pcp
- python3-psutil
- python3-psycpg2
- python3-PyMySQL
- python3-rtslib
- python3-sanlock
- python3-tkinter
- python3-toml
- python3-virt-firmware
- python-unversioned-command
- rasdaemon
- rear
- redhat-rpm-config
- redis
- redis-devel
- redis-doc
- rhel-system-roles
- rpmdevtools
- rsyslog
- rsyslog-crypto
- rsyslog-doc
- rsyslog-elasticsearch
- rsyslog-gnutls
- rsyslog-gssapi
- rsyslog-kafka
- rsyslog-logrotate
- rsyslog-mmaudit
- rsyslog-mmfields
- rsyslog-mmjsonparse
- rsyslog-mmkubernetes
- rsyslog-mmnormalize
- rsyslog-mmsnmptrapd
- rsyslog-mysql

- rsyslog-omamqp1
- rsyslog-openssl
- rsyslog-pgsql
- rsyslog-relp
- rsyslog-snmp
- rsyslog-udp spoof
- sanlock
- sanlock-lib
- scap-security-guide
- scap-security-guide-doc
- selinux-policy-devel
- sendmail
- sendmail-cf
- sendmail-doc
- setroubleshoot
- setroubleshoot-plugins
- setroubleshoot-server
- sssd-idp
- sysstat
- systemd-boot-unsigned
- systemd-devel
- systemd-journal-remote
- systemd-ukify
- systemtap
- systemtap-client
- systemtap-devel
- systemtap-exporter
- systemtap-initscript
- systemtap-runtime
- systemtap-runtime-java
- systemtap-runtime-python3
- systemtap-runtime-virtguest
- systemtap-runtime-virtnhost
- systemtap-sdt-devel
- systemtap-sdt-dtrace
- systemtap-server
- targetcli

- target-restore
- thunderbird
- tog-pegasus
- tog-pegasus-libs
- tuned-gtk
- tuned-ppd
- tuned-profiles-atomic
- tuned-profiles-mssql
- tuned-profiles-oracle
- tuned-profiles-postgresql
- tuned-profiles-spectrumscale
- tuned-utils
- udisks2
- udisks2-iscsi
- udisks2-lsm
- udisks2-lvm2
- uki-direct
- uuid
- vim-common
- vim-enhanced
- vim-X11
- virt-p2v
- virt-top
- virt-v2v
- virt-v2v-bash-completion
- WALinuxAgent
- WALinuxAgent-udev
- xsane
- xsane-common

Removed BaseOS Binary Packages

The following binary packages from the BaseOS upstream release have been removed:

- bpftool
- kmod-redhat-arc4
- kmod-redhat-arc4-devel
- kmod-redhat-cfg80211
- kmod-redhat-cfg80211-devel

- kmod-redhat-mac80211
- kmod-redhat-mac80211-devel
- kmod-redhat-rtw89
- kmod-redhat-rtw89-devel
- kpatch
- kpatch-dnf
- kpatch-patch-5_14_0-162_12_1
- kpatch-patch-5_14_0-162_18_1
- kpatch-patch-5_14_0-162_22_2
- kpatch-patch-5_14_0-162_23_1
- kpatch-patch-5_14_0-162_6_1
- kpatch-patch-5_14_0-284_11_1
- kpatch-patch-5_14_0-284_18_1
- kpatch-patch-5_14_0-284_25_1
- kpatch-patch-5_14_0-284_30_1
- kpatch-patch-5_14_0-362_13_1
- kpatch-patch-5_14_0-362_18_1
- kpatch-patch-5_14_0-362_8_1
- kpatch-patch-5_14_0-427_13_1
- kpatch-patch-5_14_0-427_31_1
- kpatch-patch-5_14_0-503_15_1
- kpatch-patch-5_14_0-503_26_1
- kpatch-patch-5_14_0-570_17_1
- kpatch-patch-5_14_0-570_39_1
- kpatch-patch-5_14_0-611_36_1
- kpatch-patch-5_14_0-611_9_1
- kpatch-patch-5_14_0-70_13_1
- kpatch-patch-5_14_0-70_17_1
- kpatch-patch-5_14_0-70_22_1
- kpatch-patch-5_14_0-70_26_1
- kpatch-patch-5_14_0-70_30_1
- libdnf-plugin-subscription-manager
- python3-cloud-what
- python3-perf
- python3-subscription-manager-rhsm
- redhat-release-eula
- rhsm-icons

- subscription-manager
- subscription-manager-cockpit
- subscription-manager-plugin-ostree
- subscription-manager-rhsm-certificates

Removed AppStream Binary Packages

The following binary packages from the AppStream upstream release have been removed:

- adobe-source-code-pro-fonts
- ansible-collection-microsoft-sql
- ansible-collection-redhat-leapp
- ansible-collection-redhat-rhel_mgmt
- boom-boot-grub2
- cargo-doc
- cockpit-leapp
- cockpit-pcp
- command-line-assistant
- command-line-assistant-selinux
- cxl-libs
- dotnet-sdk-8.0-source-built-artifacts
- fapolicyd-dnf-plugin
- ha-openstack-support
- idm-pki-est
- idm-tomcatjss
- insights-client
- insights-client-ros
- insights-core
- insights-core-selinux
- jmc-core
- jq
- jss
- kbd-legacy
- ktls-utils
- ldapjdk
- leapp
- leapp-deps
- leapp-upgrade-el9toel10
- leapp-upgrade-el9toel10-deps

- leapp-upgrade-el9toel10-fapolicyd
- libdrm
- libblockfile
- libomp-test
- libreport-rhel-anaconda-bugzilla
- libtool-ltdl
- lld-test
- mesa-libglapi
- mesa-libxatracker
- NetworkManager-config-connectivity-redhat
- nmstate-plugin-ovsdb
- oniguruma
- opentelemetry-collector
- osbuild-composer-dnf-json
- owasp-java-encoder
- pki-acme
- pki-base
- pki-base-java
- pki-ca
- pki-kra
- pki-resteasy
- pki-server
- pki-symkey
- pki-tools
- plotnetcfg
- podman-catatonit
- podman-gvproxy
- protobuf-c
- python3-cffi
- python3-cryptography
- python3-leapp
- python3-pki
- python3-ply
- python3-pycparser
- python3-tdb
- qemu-ga-win
- qemu-kvm-device-display-virtio-gpu-gl

- `qemu-kvm-device-display-virtio-gpu-pci-gl`
- `qemu-kvm-device-display-virtio-vga-gl`
- `qt5-doc`
- `qt5-qtcharts-doc`
- `qt5-qtdataavis3d-doc`
- `qt5-qtgamepad-doc`
- `qt5-qt purchasing-doc`
- `qt5-qtremoteobjects-doc`
- `qt5-qtscxml-doc`
- `qt5-qt speech-doc`
- `qt5-qtvirtualkeyboard-doc`
- `qt5-qtwebview-doc`
- `realtime-tests`
- `redhat-backgrounds`
- `redhat-cloud-client-configuration`
- `redhat-cloud-client-configuration-cdn`
- `redhat-indexhtml`
- `redhat-logos`
- `redhat-logos-httpd`
- `redhat-logos-ipa`
- `rhc`
- `rhc-playbook-verifier`
- `rhc-worker-playbook`
- `rls`
- `rust-analysis`
- `rust-std-static-wasm32-wasi`
- `s390utils`
- `s390utils-se-data`
- `tdb-tools`
- `tomcatjss`
- `toolbox`
- `toolbox-tests`
- `virtio-win`
- `virt-who`

Removed CodeReady Linux Builder Binary Packages

The following binary packages from the CodeReady Linux Builder upstream release have been removed:

- `dpkg-devel`
- `dyninst-testsuite`
- `flexiblas-devel`
- `flexiblas-netlib64`
- `flexiblas-openblas-openmp64`
- `gcc-plugin-devel`
- `gsl-devel`
- `javapackages-local`
- `libarchive-devel`
- `libgudev-devel`
- `libvirt-client-qemu`
- `libvirt-lock-sanlock`
- `maven-local`
- `mesa-libgbm-devel`
- `mesa-libOSMesa`
- `mesa-libOSMesa-devel`
- `mingw-binutils-generic`
- `mysql-libs`
- `openblas-openmp64`
- `poppler-qt5`
- `python3-docutils`
- `python3-iniconfig`
- `python3-markdown`
- `python3-pluggy`
- `python3-py`
- `python3-pytest`
- `python3-ruamel-yaml`
- `python3-ruamel-yaml-club`
- `python3-samba-devel`
- `python3-wcwidth`
- `redhat-sb-certs`
- `rhc-devel`
- `snactor`

- snappy-devel
- systemd-boot-unsigned
- xcb-util-image-devel
- xcb-util-renderutil-devel

Changes to Source Packages

This section contains information about the removed, modified, and new **source** packages in this release. For information about the **binary** package changes, see [Changes to Binary Packages](#).

Added Source Packages for BaseOS by Oracle

The following source packages have been added to the BaseOS by Oracle:

- bcache-tools
- btrfs-progs
- dtrace
- kernel-uek
- ocfs2-tools
- oracle-indexhtml
- oraclelinux-release
- oraclelinux-release-el9
- oracle-logos

Added Source Packages for AppStream by Oracle

The following source packages have been added to AppStream by Oracle:

- aopalliance
- dnf-plugin-spacewalk
- dtrace
- nodejs-packaging
- pgvector
- php-pecl-redis6
- postgis
- pyOpenSSL
- python3-dnf-plugin-ulninfo
- python-boto-core
- python-hwdata
- rapidjson
- rhn-client-tools

- rhnlib
- rhnsd

Modified BaseOS Source Packages

The following source packages from the BaseOS upstream release have been modified:

- adcli
- audit
- autofs
- binutils
- biosdevname
- chkconfig
- chrony
- cockpit
- coreutils
- crypto-policies
- dbus
- dnf
- dnf-plugins-core
- dracut
- efibootmgr
- efi-rpm-macros
- firewalld
- fwupd
- gcc
- glibc
- grub2
- grubby
- initscripts
- iputils
- irqbalance
- iscsi-initiator-utils
- kexec-tools
- kmod
- kmod-kvdo
- krb5
- libdb
- libdnf

- libkcapi
- libnvme
- libreport
- linux-firmware
- mcelog
- mdadm
- microcode_ctl
- NetworkManager
- nfs-utils
- nvme-cli
- nvmetcli
- openssh
- openssl
- openssl-fips-provider
- os-prober
- pam
- parted
- pcre2
- polkit
- procps-ng
- python3.9
- python-cffi
- python-chardet
- python-configshell
- python-dmidecode
- python-idna
- python-ply
- python-pycparser
- python-pysocks
- python-six
- PyYAML
- redhat-release
- selinux-policy
- shim
- smartmontools
- sos
- sssd

- systemd
- tpm2-tools
- tuned
- util-linux
- vim

Modified AppStream Source Packages

The following source packages from the AppStream upstream release have been modified:

- anaconda
- anaconda-user-help
- audit
- bind
- bind9.18-dyndb-ldap
- binutils
- boom-boot
- buildah
- ceph
- chkconfig
- clang
- cloud-init
- cockpit
- cockpit-composer
- cockpit-machines
- cockpit-session-recording
- compat-libgfortran-48
- containers-common
- container-tools
- crash
- cups-filters
- dbus
- ddiskit
- delve
- dnf
- dnf-plugins-core
- dotnet10.0
- dotnet6.0
- dotnet7.0

- dotnet8.0
- dotnet9.0
- dracut
- edk2
- efi-rpm-macros
- expect
- fips-provider-next
- firefox
- firewalld
- fwupd
- galera
- gcc
- gcc-toolset-12-gcc
- gcc-toolset-13-binutils
- gdal
- gdb
- gdm
- glibc
- gnome-session
- gnome-shell-extension-background-logo
- golang
- gpsd-minimal
- httpd
- image-builder
- initial-setup
- ipa
- iputils
- iscsi-initiator-utils
- java-11-openjdk
- java-17-openjdk
- java-1.8.0-openjdk
- java-21-openjdk
- java-25-openjdk
- kernel-srpm-macros
- krb5
- ksh
- libblockdev

- libdb
- libguestfs
- libkdumpfile
- libnvme
- libreoffice
- libreport
- libreswan
- libvirt
- libxslt
- lorax
- lorax-templates-rhel
- mecab-ipadic
- mesa-compat
- mpich
- mrtg
- munge
- net-snmp
- NetworkManager
- nfs-utils
- nginx
- opa-ff
- opa-fm
- OpenIPMI
- openssh
- openssl
- open-vm-tools
- osbuild
- osinfo-db
- pacemaker
- PackageKit
- pam
- papi
- pcp
- pcre2
- perl-XML-Parser
- pesign
- pki-core

- plymouth
- podman
- polkit
- pykickstart
- python3.11
- python3.12
- python3.9
- python-attrs
- python-blivet
- python-packaging
- python-psutil
- python-psycopg2
- python-PyMySQL
- python-rtslib
- python-toml
- python-virt-firmware
- rasdaemon
- rear
- redhat-rpm-config
- redis
- rhel-system-roles
- rpmdevtools
- rsyslog
- sanlock
- scap-security-guide
- selinux-policy
- sendmail
- setroubleshoot
- setroubleshoot-plugins
- sssd
- sysstat
- systemd
- systemtap
- targetcli
- thunderbird
- tog-pegasus
- tuned

- udisks2
- util-linux
- vim
- virt-p2v
- virt-top
- virt-v2v
- WALinuxAgent
- xsane

Modified Source Packages for CodeReady Linux Builder by Oracle

The following binary packages to CodeReady Linux Builder by Oracle have been modified:

- anaconda
- bind
- ceph
- crash
- cups-filters
- dotnet10.0
- dotnet6.0
- dotnet7.0
- dotnet8.0
- dotnet9.0
- edk2
- expect
- fwupd
- gcc
- gdal
- gdm
- glibc
- ipa
- java-11-openjdk
- java-17-openjdk
- java-1.8.0-openjdk
- java-21-openjdk
- java-25-openjdk
- kmod
- libdb
- libdnf

- libguestfs
- libnvme
- libreoffice
- libvirt
- mpich
- munge
- NetworkManager
- nfs-utils
- OpenIPMI
- PackageKit
- papi
- parted
- pcre2
- procs-ng
- python3.11
- python3.12
- python3.9
- python-packaging
- python-psutil
- sanlock
- sendmail
- sssd
- tog-pegasus
- udisks2
- util-linux
- virt-v2v
- WALinuxAgent

Removed BaseOS Source Packages

The following source packages from the BaseOS upstream release have been removed:

- kpatch
- subscription-manager
- subscription-manager-cockpit
- subscription-manager-rhsm-certificates

Removed AppStream Source Packages

The following source packages from the AppStream upstream release have been removed:

- `ansible-collection-microsoft-sql`
- `ansible-collection-redhat-leapp`
- `ansible-collection-redhat-rhel_mgmt`
- `cockpit-leapp`
- `command-line-assistant`
- `insights-client`
- `insights-core`
- `leapp`
- `opentelemetry-collector`
- `realtime-tests`
- `redhat-cloud-client-configuration`
- `redhat-indexhtml`
- `redhat-logos`
- `rhc`
- `rhc-playbook-verifier`
- `rhc-worker-playbook`
- `s390utils`
- `toolbox`
- `virtio-win`
- `virt-who`