

Oracle® Fusion Middleware

Infrastructure Security WLST Command Reference

12c (12.2.1)

E63559-01

September 2015

This document describes the Oracle Fusion Middleware Infrastructure Security commands available to use with the WebLogic Scripting Tool.

Copyright © 2014, 2015 Oracle and/or its affiliates. All rights reserved.

Primary Author: Carlos Subi

Contributing Authors: Vinaye Misra, Devahsi Mohan

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

Preface	v
Audience	v
Documentation Accessibility	v
Related Documentation	v
Conventions	v
1 Introduction and Roadmap	
1.1 Document Scope and Audience	1-1
1.2 Guide to This Document	1-1
2 Infrastructure Security Custom WLST Commands	
2.1 Infrastructure Commands	2-1
2.1.1 OPSS Security Store Commands	2-1
2.1.2 Audit Configuration Commands	2-24
2.1.3 OPSS Keystore Service Commands	2-34
2.1.4 Identity Directory Service Commands	2-47
2.1.5 Library Oracle Virtual Directory (libOVD) Commands	2-66
3 SSL Configuration WLST Commands	
3.1 About SSL Configuration Commands	3-1
3.2 Properties Files for SSL	3-2
3.2.1 Structure of Properties Files	3-2
3.2.2 Examples of Properties Files	3-3
4 Wallet Configuration WLST Commands	
4.1 The WLST Wallet Commands	4-1

Preface

This guide describes the security WebLogic Scripting Tool (WLST) commands for the Oracle Platform Security Services (OPSS).

Audience

The intended audience of this guide are experienced Java developers, administrators, deployers, and application managers who want to use the security OPSS commands.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Related Documentation

Additional information is found in the following documents:

- *Securing Applications with Oracle Platform Security Services*
- *Administering Oracle Fusion Middleware*
- *Oracle Fusion Middleware Security and Administrator's Guide for Web Services*

For a comprehensive list of Oracle documentation or to search for a particular topic within Oracle documentation libraries, see <http://www.oracle.com/technetwork/indexes/documentation/index.html>.

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action.

Convention	Meaning
<i>italic</i>	Italic type indicates book titles, emphasis, terms defined in text, or placeholder variables for which you supply particular values.
monospace	Monospace type within a paragraph indicates commands, URLs, Java class names and method names, file and directory names, text that appears on the screen, or text that you enter.

Introduction and Roadmap

This chapter describes the audience for and contents and organization of this guide—*Infrastructure Security WLST Command Reference*.

This chapter includes the following sections:

- [Document Scope and Audience](#)
- [Guide to This Document](#)

1.1 Document Scope and Audience

This document describes all of the Infrastructure Security custom WLST commands that are available to use with the WebLogic Scripting Tool (WLST).

Note: Custom WLST commands for a given Oracle Fusion Middleware component are available for use only if the component is installed in the `ORACLE_HOME` directory.

This document is written for WebLogic Server administrators and operators who deploy Java EE applications using the Java Platform, Enterprise Edition (Java EE) from Oracle. It is assumed that readers are familiar with Web technologies and the operating system and platform where WebLogic Server and Fusion Middleware products are installed.

1.2 Guide to This Document

This document is organized as follows:

- This chapter, "Introduction and Roadmap," introduces the organization of this guide and lists related documentation.
- [Chapter 2, "Infrastructure Security Custom WLST Commands,"](#) provides detailed descriptions for each of the custom WLST commands for audit configuration, SSL configuration, Oracle Identify Federation, Directory Integration Platform, OPSS, Oracle Keystore Service, Identity Directory Service, and Library Oracle Virtual Directory (libOVD).

Infrastructure Security Custom WLST Commands

This chapter describes the Oracle Fusion Middleware Infrastructure Security WLST commands.

It includes the following topic:

- [Infrastructure Commands](#)

Related Topics

Securing Applications with Oracle Platform Security Services.

Using Custom WLST Commands in the *Administering Oracle Fusion Middleware*.

2.1 Infrastructure Commands

The infrastructure WLST security commands are divided into the following categories:

Table 2–1 *WLST Command Categories*

Command Category	Description
OPSS Security Store Commands	Manage domain and credential domain stores and migrate domain policy store.
Audit Configuration Commands	View and manage audit policies and the audit repository configuration
OPSS Keystore Service Commands	Manage the OPSS keystore service.
Identity Directory Service Commands	Manage Identity Directory Service entity attributes, entity definitions, relationships, and default operational configurations.
Library Oracle Virtual Directory (libOVD) Commands	View and manage Library Oracle Virtual Directory (libOVD) configurations associated with a particular OPSS context.

Note: In syntax descriptions, optional arguments are enclosed in between square brackets; all other arguments are required.

2.1.1 OPSS Security Store Commands

Use the WLST security commands listed in [Table 2–2](#) to operate on a domain policy or credential store, to migrate policies and credentials from a source repository to a target repository, and to import and export (credential) encryption keys.

Table 2–2 WLST Security Commands

Use this command...	To...	Use with WLST...
addBootstrapCredential	Add a credential to the bootstrap credential store	Offline
addResourceToEntitlement	Add a resource to an entitlement.	Online
createAppRole	Create a new application role.	Online
createCred	Create a new credential.	Online
createEntitlement	Create an entitlement.	Online
createResource	Create a resource.	Online
createResourceType	Create a new resource type.	Online
deleteAppPolicies	Remove all policies in an application.	Online
deleteAppRole	Remove an application role.	Online
deleteCred	Remove a credential.	Online
deleteEntitlement	Remove an entitlement.	Online
deleteResource	Remove a resource.	Online
deleteResourceType	Remove an existing resource type.	Online
exportEncryptionKey	Export the domain encryption key to the file <code>ewallet.p12</code> .	Offline
getEntitlement	List an entitlement.	Online
getResourceType	Fetch an existing resource type.	Online
grantAppRole	Add a principal to a role.	Online
grantEntitlement	Create an entitlement.	Online
grantPermission	Create a new permission.	Online
importEncryptionKey	Import the encryption key in file <code>ewallet.p12</code> to the domain.	Offline
listAppRoles	List all roles in an application.	Online
listAppRolesMembers	List all members in an application role.	Online
listAppStripes	List application stripes in policy store.	Online
listCodeSourcePermissions	List permissions assigned to a source code in global policies.	Online
listEntitlement	List an entitlement.	Online
listEntitlements	List entitlements in an application stripe.	Online
listPermissions	List all permissions granted to a principal.	Online
listResourceActions	List actions in a resource.	Online
listResourceTypes	List resource types in an application stripe.	Online
listResources	List resources in an application stripe.	Online
listSecurityStoreInfo	List the type and location of the OPSS security store, and the user allowed to access it.	Offline
migrateSecurityStore	Migrate policies or credentials from a source repository to a target repository.	Offline
modifyBootstrapCredential	Update bootstrap credential store	Offline

Table 2–2 (Cont.) WLST Security Commands

Use this command...	To...	Use with WLST...
reassociateSecurityStore	Reassociate policies and credentials to an LDAP repository	Online
restoreEncryptionKey	Restore the domain encryption key as it was before the last importing.	Offline
revokeAppRole	Remove a principal from a role.	Online
revokeEntitlement	Remove an entitlement.	Online
revokePermission	Remove a permission.	Online
revokeResourceFromEntitlement	Remove a resource from an entitlement	Online
rollOverEncryptionKey	Replace the current domain encryption key with a new one.	Offline
updateCred	Modify the attribute values of a credential.	Online
updateTrustServiceConfig	Update the configuration of the trust service.	Online

2.1.1.1 addBootstrapCredential

Offline command that adds a credential to the bootstrap credential store.

Description

Adds a password credential with the given map, key, user name, and user password to the bootstrap credentials configured in the default JPS context of a JPS configuration file. In the event of an error, the command returns a `WLSTException`.

Syntax

```
addBootstrapCredential(jpsConfigFile, map, key, username, password)
```

Argument	Definition
<i>jpsConfigFile</i>	Specifies the location of the file <code>jps-config.xml</code> relative to the location where the command is run.
<i>map</i>	Specifies the map of the credential to add.
<i>key</i>	Specifies the key of the credential to add.
<i>username</i>	Specifies the name of the user in the credential to add.
<i>password</i>	Specifies the password of the user in the credential to add.

Example

The following example adds a credential to the bootstrap credential store:

```
wls:/mydomain/serverConfig>
addBootstrapCredential(jpsConfigFile='./jps-config.xml', map='myMapName',
key='myKeyName', username='myUser', password='myPassword')
```

2.1.1.2 addResourceToEntitlement

Online command that adds a resource with specified actions to an entitlement.

Description

Adds a resource with specified actions to an entitlement in a specified application stripe. The passed resource type must exist in the passed application stripe.

Syntax

```
addResourceToEntitlement (appStripe="appStripeName", name="entName",
resourceName="resName",actions="actionList")
```

Argument	Definition
<i>appStripe</i>	Specifies the application stripe where the entitlement is located.
<i>name</i>	Specifies the name of the entitlement to modify.
<i>resourceName</i>	Specifies the name of the resource to add.
<i>resourceType</i>	Specifies the type of the resource to add. The passed resource type <i>must</i> be present in the application stripe at the time this script is invoked.
<i>actions</i>	Specifies the comma-separated list of actions for the added resource.

Example

The following example adds the resource myResource to the entitlement myEntitlement in the application stripe myApplication:

```
wls:/mydomain/serverConfig> addResourceToEntitlement (appStripe="myApplication",
name="myEntitlement", resourceName="myResource", resourceType="myResType",
actions="view,edit")
```

2.1.1.3 createAppRole

Online command that creates a new application role.

Description

Creates a new application role in the domain policy store with a given application and role name. In the event of an error, the command returns a `WLSTException`.

Syntax

```
createAppRole(appStripe, appRoleName)
```

Argument	Definition
<i>appStripe</i>	Specifies an application stripe.
<i>appRoleName</i>	Specifies a role name.

Example

The following example creates a new application role with application stripe myApp and role name myRole:

```
wls:/mydomain/serverConfig> createAppRole(appStripe="myApp", appRoleName="myRole")
```

2.1.1.4 createCred

Online command that creates a new credential in the domain credential store.

Description

Creates a new credential in the domain credential store with a given map name, key name, type, user name and password, URL and port number. In the event of an error, the command returns a `WLSTException`. This command runs in interactive mode only.

Syntax

```
createCred(map, key, user, password, [desc])
```

Argument	Definition
<i>map</i>	Specifies a map name (folder).
<i>key</i>	Specifies a key name.
<i>user</i>	Specifies the credential user name.
<i>password</i>	Specifies the credential password.
<i>desc</i>	Specifies a string describing the credential.

Example

The following example creates a new password credential with the specified data:

```
wls:/mydomain/serverConfig> createCred(map="myMap, key="myKey", user="myUsr",
password="myPassw", desc="updated usr name and passw to connect to app xyz")
```

2.1.1.5 createEntitlement

Online command that creates a new entitlement.

Description

Creates a new entitlement with just one resource and a list of actions in a specified application stripe. Use `addResourceToEntitlement` to add additional resources to an existing entitlement; use `revokeResourceFromEntitlement` to delete resources from an existing entitlement.

Syntax

```
createEntitlement(appStripe="appStripeName", name="entitlementName",
resourceName="resName", actions="actionList" [-displayName="dispName"]
[-description="descript"])
```

Argument	Definition
<i>appStripe</i>	Specifies the application stripe where the entitlement is created.
<i>name</i>	Specifies the name of the entitlement created.
<i>resourceName</i>	Specifies the name of the one resource member of the entitlement created.
<i>actions</i>	Specifies a comma-separated the list of actions for the resource <code>resourceName</code> .
<i>displayName</i>	Specifies the display name of the resource created. Optional.
<i>description</i>	Specifies the description of the entitlement created. Optional.

Example

The following example creates the entitlement `myEntitlement` with just the resource `myResource` in the stripe `myApplication`:

```
wls:/mydomain/serverConfig> createEntitlement(appStripe="myApplication",
name="myEntitlement", resourceName="myResource", actions="read,write")
```

2.1.1.6 createResource

Online command that creates a new resource.

Description

Creates a resource of a specified type in a specified application stripe. The passed resource type must exist in the passed application stripe.

Syntax

```
createResource(appStripe="appStripeName", name="resName", type="resTypeName"
[,-displayName="dispName"] [,-description="descript"])
```

Argument	Definition
<i>appStripe</i>	Specifies the application stripe where the resource is created.
<i>name</i>	Specifies the name of the resource created.
<i>type</i>	Specifies the type of resource created. The passed resource type <i>must</i> be present in the application stripe at the time this script is invoked.
<i>displayName</i>	Specifies the display name of the resource created. Optional.
<i>description</i>	Specifies the description of the resource created. Optional.

Example

The following example creates the resource myResource in the stripe myApplication:

```
wls:/mydomain/serverConfig> createResource(appStripe="myApplication",
name="myResource", type="myResType", displayName="myNewResource")
```

2.1.1.7 createResourceType

Online command that creates a new resource type in the domain policy store within a given application stripe.

Description

Creates a new resource type element in the domain policy store within a given application stripe and with specified name, display name, description, and actions. In the event of an error, the command returns a `WLSTException`.

Syntax

```
createResourceType(appStripe, resourceTypeName, displayName, description [,
provider] [, matcher], actions [, delimiter])
```

Argument	Definition
<i>appStripe</i>	Specifies the application stripe where to insert the resource type.
<i>resourceTypeName</i>	Specifies the name of the resource type to insert.
<i>displayName</i>	Specifies the name for the resource type used in UI gadgets.
<i>description</i>	Specifies a brief description of the resource type.
<i>provider</i>	Specifies the provider for the resource type.

Argument	Definition
<i>matcher</i>	Specifies the class of the resource type. If unspecified, it defaults to <code>oracle.security.jps.ResourcePermission</code> .
<i>actions</i>	Specifies the actions allowed on instances of the resource type.
<i>delimiter</i>	Specifies the character used to delimit the list of actions. If unspecified, it defaults to comma ','.

Example

The following example creates a resource type in the stripe `myApplication` with actions `BWPrint` and `ColorPrint` delimited by a semicolon:

```
wls:/mydomain/serverConfig> createResourceType(appStripe="myApplication",
resourceTypeName="resTypeName", displayName="displName", description="A resource
type", provider="Printer", matcher="com.printer.Printer",
actions="BWPrint;ColorPrint" [, delimiter=";"])
```

2.1.1.8 deleteAppPolicies

Online command that removes all policies with a given application stripe.

Description

Removes all policies with a given application stripe. In the event of an error, the command returns a `WLSTException`.

Syntax

```
deleteAppPolicies(appStripe)
```

Argument	Definition
<i>appStripe</i>	Specifies an application stripe. If not specified, the command works on system policies.

Example

The following example removes all policies of application `myApp`:

```
wls:/mydomain/serverConfig> deleteAppPolicies(appStripe="myApp")
```

2.1.1.9 deleteAppRole

Online command that removes an application role.

Description

Removes an application role in the domain policy store with a given application and role name. In the event of an error, the command returns a `WLSTException`.

Syntax

```
createAppRole(appStripe, appRoleName)
```

Argument	Definition
<i>appStripe</i>	Specifies an application stripe.
<i>appRoleName</i>	Specifies a role name.

Example

The following example removes the role with application stripe myApp and role name myRole:

```
wls:/mydomain/serverConfig> deleteAppRole(appStripe="myApp", appRoleName="myRole")
```

2.1.1.10 deleteEntitlement

Online command that deletes an entitlement.

Description

Deletes an entitlement in a specified application stripe. It performs a cascading deletion by removing all references to the specified entitlement in the application stripe.

Syntax

```
deleteEntitlement(appStripe=appStripeName, name=entitlementName)
```

Argument	Definition
<i>appStripe</i>	Specifies the application stripe where the entitlement is deleted.
<i>name</i>	Specifies the name of the entitlement to delete.

Example

The following example deletes the entitlement myEntitlement in the stripe myApplication:

```
wls:/mydomain/serverConfig> deleteEntitlement(appStripe="myApplication",
name="myEntitlement")
```

2.1.1.11 deleteCred

Online command that removes a credential in the domain credential store.

Description

Removes a credential with given map name and key name from the domain credential store. In the event of an error, the command returns a `WLSTException`.

Syntax

```
deleteCred(map, key)
```

Argument	Definition
<i>map</i>	Specifies a map name (folder).
<i>key</i>	Specifies a key name.

Example

The following example removes the credential with map name myMap and key name myKey:

```
wls:/mydomain/serverConfig> deleteCred(map="myApp", key="myKey")
```

2.1.1.12 deleteResource

Online command that deletes a resource.

Description

Deletes a resource and all its references from entitlements in an application stripe. It performs a cascading deletion: if the entitlement refers to one resource only, it removes the entitlement; otherwise, it removes from the entitlement the resource actions for the passed type.

Syntax

```
deleteResource(appStripe="appStripeName", name="resName", type="resTypeName")
```

Argument	Definition
<i>appStripe</i>	Specifies the application stripe where the resource is deleted.
<i>name</i>	Specifies the name of the resource deleted.
<i>type</i>	Specifies the type of resource deleted. The passed resource type <i>must</i> be present in the application stripe at the time this script is invoked.

Example

The following example deletes the resource myResource in the stripe myApplication:

```
wls:/mydomain/serverConfig> deleteResource(appStripe="myApplication",
name="myResource", type="myResType")
```

2.1.1.13 deleteResourceType

Online command that removes a resource type from the domain policy store within a given application stripe.

Description

Removes a <resource-type> entry in the domain policy store within a given application stripe and with specified name. In the event of an error, the command returns a WLSTException.

Syntax

```
deleteResourceType(appStripe, resourceTypeName)
```

Argument	Definition
<i>appStripe</i>	Specifies the application stripe from where to remove the resource type.
<i>resourceTypeName</i>	Specifies the name of the resource type to remove.

Example

The following example removes the resource type myResType from the stripe myApplication:

```
wls:/mydomain/serverConfig> deleteResourceType(appStripe="myApplication",
resourceTypeName="myResType")
```

2.1.1.14 exportEncryptionKey

Offline command that extracts the encryption key from a domain's bootstrap wallet to the file ewallet.p12.

Description

Writes the domain's credential encryption key to the file `ewallet.p12`. The password passed must be used to import data from that file with the command `importEncryptionKey`.

```
exportEncryptionKey(jpsConfigFile, keyFilePath, keyFilePassword)
```

Syntax

Argument	Definition
<code>jpsConfigFile</code>	Specifies the location of the file <code>jps-config.xml</code> relative to the location where the command is run.
<code>keyFilePath</code>	Specifies the directory where the file <code>ewallet.p12</code> is created; note that the content of this file is encrypted and secured by the value passed to <code>keyFilePassword</code> .
<code>keyFilePassword</code>	Specifies the password to secure the file <code>ewallet.p12</code> ; note that this same password must be used when importing that file.

Example

The following example writes the file `ewallet.p12` in the directory `myDir`:

```
exportEncryptionKey(jpsConfigFile="pathName", keyFilePath="myDir",
, keyFilePassword="password")
```

2.1.1.15 getEntitlement

Online command that gets an entitlement.

Description

Returns the name, display name, and all the resources (with their actions) of an entitlement in an application stripe.

Syntax

```
getEntitlement(appStripe="appStripeName", name="entitlementName")
```

Argument	Definition
<code>appStripe</code>	Specifies the application stripe where the entitlement is located.
<code>name</code>	Specifies the name of the entitlement to access.

Example

The following example returns the information of the entitlement `myEntitlement` in the stripe `myApplication`:

```
wls:/mydomain/serverConfig> getEntitlement(appStripe="myApplication",
name="myEntitlement")
```

2.1.1.16 getResourceType

Online command that fetches a resource type from the domain policy store within a given application stripe.

Description

Gets the relevant parameters of a <resource-type> entry in the domain policy store within a given application stripe and with specified name. In the event of an error, the command returns a `WLSTException`.

Syntax

```
getResourceType(appStripe, resourceTypeName)
```

Argument	Definition
<i>appStripe</i>	Specifies the application stripe from where to fetch the resource type.
<i>resourceTypeName</i>	Specifies the name of the resource type to fetch.

Example

The following example fetches the resource type `myResType` from the stripe `myApplication`:

```
wls:/mydomain/serverConfig> getResourceType(appStripe="myApplication",
resourceTypeName="myResType")
```

2.1.1.17 grantAppRole

Online command that adds a principal to a role.

Description

Adds a principal (class or name) to a role with a given application stripe and name. In the event of an error, the command returns a `WLSTException`.

Syntax

```
grantAppRole(appStripe, appRoleName,principalClass, principalName)
```

Argument	Definition
<i>appStripe</i>	Specifies an application stripe.
<i>appRoleName</i>	Specifies a role name.
<i>principalClass</i>	Specifies the fully qualified name of a class.
<i>principalName</i>	Specifies the principal name.

Example

The following example adds a principal to the role with application stripe `myApp` and role name `myRole`:

```
wls:/mydomain/serverConfig> grantAppRole(appStripe="myApp",
appRoleName="myRole",principalClass="com.example.xyzPrincipal",
principalName="myPrincipal")
```

2.1.1.18 grantEntitlement

Online command that grant an entitlement to a named principal.

Description

Grants an entitlement to a specified principal in a specified application stripe.

Syntax

```
grantEntitlement(appStripe="appStripeName", principalClass="principalClass",
principalName="principalName" , -permSetName="entName")
```

Argument	Definition
<i>appStripe</i>	Specifies the application stripe where the principal resides.
<i>principalClass</i>	Specifies the class associated with the principal.
<i>principalName</i>	Specifies the name of the principal to which the entitlement is granted.
<i>permSetName</i>	Specifies the name of the entitlement granted.

Example

The following example grants the entitlement `myEntitlement` in the stripe `myApplication` to the principal `myPrincipalName`:

```
wls:/mydomain/serverConfig> grantEntitlement(appStripe="myApplication",
principalClass="oracle.security.jps.service.policystore.ApplicationRole",
principalName="myPrincipalName", permSetName="myEntitlement")
```

2.1.1.19 grantPermission

Online command that creates a new permission.

Description

Creates a new permission for a given code base or URL. In the event of an error, the command returns a `WLSTException`.

Syntax

```
grantPermission([appStripe,] [codeBaseURL,] [principalClass,] [principalName,]
permClass, [permTarget,] [permActions])
```

Argument	Definition
<i>appStripe</i>	Specifies an application stripe. If not specified, the command works on system policies.
<i>codeBaseURL</i>	Specifies the URL of the code granted the permission.
<i>principalClass</i>	Specifies the fully qualified name of a class (grantee).
<i>principalName</i>	Specifies the name of the grantee principal.
<i>permClass</i>	Specifies the fully qualified name of the permission class.
<i>permTarget</i>	Specifies, when available, the name of the permission target. Some permissions may not include this attribute.
<i>permActions</i>	Specifies a comma-separated list of actions granted. Some permissions may not include this attribute and the actions available depend on the permission class.

Example

The following example creates a new application permission (for the application with application stripe `myApp`) with the specified data:

```
wls:/mydomain/serverConfig> grantPermission(appStripe="myApp",
principalClass="my.custom.Principal", principalName="manager",
permClass="java.security.AllPermission")
```

The following example creates a new system permission with the specified data:

```
wls:/mydomain/serverConfig> grantPermission(principalClass="my.custom.Principal",
principalName="manager",
permClass="java.io.FilePermission", permTarget="/tmp/fileName.ext",
permTarget="/tmp/fileName.ext", permActions="read,write")
```

2.1.1.20 importEncryptionKey

Offline command that imports keys from the specified ewallet.p12 file into the domain.

Description

Imports encryption keys from the file `ewallet.p12` into the domain. The password passed must be the same as that used to create the file with the command `exportEncryptionKey`.

Syntax

```
importEncryptionKey(jpsConfigFile, keyFilePath, keyFilePassword)
```

Argument	Definition
<i>jpsConfigFile</i>	Specifies the location of the file <code>jps-config.xml</code> relative to the location where the command is run.
<i>keyFilePath</i>	Specifies the directory where the <code>ewallet.p12</code> is located.
<i>keyFilePassword</i>	Specifies the password used when the file <code>ewallet.p12</code> was generated.

Example

```
importEncryptionKey(jpsConfigFile="pathName", keyFilePath="dirloc",
,keyFilePassword="password")
```

2.1.1.21 listAppRoles

Online command that lists all roles in an application.

Description

Lists all roles within a given application stripe. In the event of an error, the command returns a `WLSTException`.

Syntax

```
listAppRoles(appStripe)
```

Argument	Definition
<i>appStripe</i>	Specifies an application stripe.

Example

The following example returns all roles with application stripe `myApp`:

```
wls:/mydomain/serverConfig> listAppRoles(appStripe="myApp")
```

2.1.1.22 listAppRolesMembers

Online command that lists all members in a role.

Description

Lists all members in a role with a given application stripe and role name. In the event of an error, the command returns a `WLSTException`.

Syntax

```
listAppRoleMembers(appStripe, appRoleName)
```

Argument	Definition
<i>appStripe</i>	Specifies an application stripe.
<i>appRoleName</i>	Specifies a role name.

Example

The following example returns all members in the role with application stripe `myApp` and role name `myRole`:

```
wls:/mydomain/serverConfig> listAppRoleMembers(appStripe="myApp",
appRoleName="myRole")
```

2.1.1.23 listAppStripes

Online or offline command that lists the application stripes in the policy store.

Description

This script can be run in offline or online mode. When run in offline mode, a configuration file must be passed, and it lists the application stripes in the policy store referred to by the configuration in the default context of the passed configuration file; the default configuration *must not* have a service instance reference to an identity store. When run in online mode, a configuration file must not be passed, and it lists stripes in the policy store of the domain to which you connect. In any mode, if a regular expression is passed, it lists the application stripes with names that match the regular expression; otherwise, it lists all application stripes.

Syntax

```
listAppStripes([configFile="configFileName"] [, regularExpression="aRegExp"])
```

Argument	Definition
<i>configFile</i>	Specifies the path to the OPSS configuration file. Optional. If specified, the script runs offline; the default context in the specified configuration file <i>must not</i> have a service instance reference to an identity store. If unspecified, the script runs online and it lists application stripes in the policy store.
<i>regularExpression</i>	Specifies the regular expression that returned stripe names should match. Optional. If unspecified, it matches all names. To match substrings, use the character <code>*</code> .

Example

The following (online) invocation returns the list of application stripes in the policy store:

```
wls:/mydomain/serverConfig> listAppStripes
```

The following (offline) invocation returns the list of application stripes in the policy store referenced in the default context of the specified configuration file:

```
wls:/mydomain/serverConfig> listAppStripes (configFile="
/home/myFile/jps-config.xml")
```

The following (online) invocation returns the list of application stripes that contain the prefix App:

```
wls:/mydomain/serverConfig> listAppStripes (regularExpression="App*")
```

2.1.1.24 listCodeSourcePermissions

Online command that lists permissions assigned to a source code in global policies.

Description

This command allows listing codebase permissions in global policies.

Syntax

```
listCodeSourcePermissions ([codeBase="codeUrl"])
```

Argument	Definition
<i>codeBaseURL</i>	Specifies the name of the grantee codebase URL.

Example

The following example returns the list permissions assigned to a code source in all global policies:

```
wls:/mydomain/serverConfig>
listCodeSourcePermissions (codeBaseURL="file:/tmp/lib/myJars.jar")
```

2.1.1.25 listEntitlement

Online command that lists an entitlement in a specified application stripe.

Description

If a principal name and a class are specified, it lists the entitlements that match the specified principal; otherwise, it lists all the entitlements.

Syntax

```
listEntitlement (appStripe="appStripeName" [, principalName="principalName",
principalClass="principalClass"])
```

Argument	Definition
<i>appStripe</i>	Specifies the application stripe where the entitlement is deleted.
<i>principalName</i>	Specifies the name of the principal to match. Optional.
<i>principalClass</i>	Specifies the class of the principal to match. Optional.

Example

The following example lists all entitlements in the stripe myApplication:

```
wls:/mydomain/serverConfig> listEntitlement (appStripe="myApplication")
```

2.1.1.26 listEntitlements

Online command that lists the entitlements in an application stripe.

Description

Lists all the entitlements in an application stripe. If a resource name and a resource type are specified, it lists the entitlements that have a resource of the specified type matching the specified resource name; otherwise, it lists all the entitlements in the application stripe.

Syntax

```
listEntitlements (appStripe="appStripeName" [,resourceTypeName="resTypeName",
resourceName="resName"])
```

Argument	Definition
<i>appStripe</i>	Specifies the application stripe from where to list entitlements.
<i>resourceTypeName</i>	Specifies the name of the type of the resources to list. Optional.
<i>resourceName</i>	Specifies the name of resource to match. Optional.

Examples

The following example lists all the entitlements in the stripe myApplication:

```
wls:/mydomain/serverConfig> listEntitlements (appStripe="myApplication")
```

The following example lists all the entitlements in the stripe myApplication that contain a resource type myResType and a resource whose name match the resource name myResName:

```
wls:/mydomain/serverConfig> listEntitlements (appStripe="myApplication",
resourceTypeName="myResType", resourceName="myResName")
```

2.1.1.27 listPermissions

Online command that lists all permissions granted to a given principal.

Description

Lists all permissions granted to a given principal. In the event of an error, the command returns a WLSTException.

Syntax

```
listPermissions ([appStripe,] principalClass, principalName)
```

Argument	Definition
<i>appStripe</i>	Specifies an application stripe. If not specified, the command works on system policies.
<i>principalClass</i>	Specifies the fully qualified name of a class (grantee).
<i>principalName</i>	Specifies the name of the grantee principal.

Example

The following example lists all permissions granted to a principal by the policies of application myApp:

```
wls:/mydomain/serverConfig> listPermissions (appStripe="myApp",
principalClass="my.custom.Principal", principalName="manager")
```

The following example lists all permissions granted to a principal by system policies:


```
wls:/mydomain/serverConfig> listPermissions(principalClass="my.custom.Principal",
principalName="manager")
```

2.1.1.28 listResourceActions

Online command that lists the resources and actions in an entitlement.

Description

Lists the resources and actions in an entitlement within an application stripe.

Syntax

```
listResourceActions(appStripe="appStripeName", permSetName="entitlementName")
```

Argument	Definition
<i>appStripe</i>	Specifies the application stripe where the entitlement resides.
<i>permSetName</i>	Specifies the name of the entitlement whose resources and actions to list.

Example

The following example lists the resources and actions of the entitlement myEntitlement in the stripe myApplication:

```
wls:/mydomain/serverConfig> listResourceActions(appStripe="myApplication",
permSetName="myEntitlement")
```

2.1.1.29 listResources

Online command that lists resources in a specified application stripe.

Description

If a resource type is specified, it lists all the resources of the specified resource type; otherwise, it lists all the resources of all types.

Syntax

```
listResources(appStripe="appStripeName" [,type="resTypeName"])
```

Argument	Definition
<i>appStripe</i>	Specifies the application stripe where the resources are listed.
<i>type</i>	Specifies the type of resource listed. The passed resource type <i>must</i> be present in the application stripe at the time this script is invoked.

Example

The following example lists all resources of type myResType in the stripe myApplication:

```
wls:/mydomain/serverConfig> listResources(appStripe="myApplication",
type="myResType")
```

2.1.1.30 listResourceTypes

Online command that lists resource types.

Description

Lists all the resource types in a specified application stripe.

Syntax

```
listResourceTypes (appStripe=" appStripeName ")
```

Argument	Definition
<i>appStripe</i>	Specifies the application stripe where the resource types are located.

Example

The following example lists all resource types in the stripe myApplication:

```
wls:/mydomain/serverConfig> listResourceTypes (appStripe="myApplication")
```

2.1.1.31 listSecurityStoreInfo

Offline command that lists the type, the location, and the administrative user of the domain security store.

Description

The script runs in offline mode and outputs the type of the OPSS security store (file, OID, or DB), its location, and the user allowed to access it (typically a security administrator).

Syntax

```
listSecurityStoreInfo (domainConfig=" configFilePath ")
```

Argument	Definition
<i>domainConfig</i>	Specifies the full absolute path to the OPSS configuration file jps-config.xml; the file jps-config-jse.xml is also expected to be in the passed directory.

Example

The following example returns the type, location, and administrative user of the OPSS policy store:

```
wls:/mydomain/serverConfig> listSecurityStoreInfo (domainConfig="/home/myConfigPathDirectory/config/fmwconfig")
```

The following lines illustrate a sample output generated by this command:

```
For jps-config.xml
Store Type: DB_ORACLE
Location/Endpoint: jdbc:oracle:thin:@adc2120515.us.myComp.com:1555/OWSM.US.COM
User: DEV_OPSS
Datasource: jdbc/OpssDataSource
For jps-config-jse.xml
Store Type: DB_ORACLE
Location/Endpoint: jdbc:oracle:thin:@adc2120515.us.myComp.com:1521/OWSM.US.COM
User: DEV_OPSS
```

2.1.1.32 migrateSecurityStore

Offline command that migrates identities, application-specific, system policies, a specific credential folder, or all credentials.

Description

Migrates security artifacts from a source repository to a target repository. For full details, see *Migrating with the Script migrateSecurityStore*.

2.1.1.33 modifyBootStrapCredential

Offline command that updates a bootstrap credential store.

Description

Updates a bootstrap credential store with given user name and password. In the event of an error, the command returns a `WLSTException`.

Typically used in the following scenario: suppose that the domain policy and credential stores are LDAP-based, and the credentials to access the LDAP store (stored in the LDAP server) are changed. Then this command can be used to seed those changes into the bootstrap credential store.

Syntax

```
modifyBootStrapCredential(jpsConfigFile, username, password)
```

Argument	Definition
<i>jpsConfigFile</i>	Specifies the location of the file <code>jps-config.xml</code> relative to the location where the command is run.
<i>username</i>	Specifies the distinguished name of the user in the LDAP store.
<i>password</i>	Specifies the password of the user.

Example

Suppose that in the LDAP store the password of the user with distinguished name `cn=orcladmin` has been changed to `welcome1`, and that the configuration file `jps-config.xml` is located in the current directory.

Then the following example changes the password in the bootstrap credential store to `welcome1`:

```
wls:/mydomain/serverConfig>
modifyBootStrapCredential(jpsConfigFile='./jps-config.xml',
username='cn=orcladmin', password='welcome1')
```

Any output regarding the audit service can be disregarded.

2.1.1.34 reassociateSecurityStore

Online command that migrates the policy and credential stores to an LDAP repository.

Description

The script `reassociateSecurityStore` migrates the OPSS security store from a source to a target LDAP- or DB-based store, and it resets services in the files `jps-config.xml` and `jps-config-jse.xml` to the target repository. It also allows specifying that the OPSS security store be shared with that in a different domain (see optional argument `join` below). The OPSS binaries and the target policy store must have compatible versions.

For complete details and samples see *Securing Applications with Oracle Platform Security Services*.

2.1.1.35 restoreEncryptionKey

Offline command to restore the domain credential encryption key.

Description

Restores the state of the domain bootstrap keys as it was before running `importEncryptionKey`.

Syntax

```
restoreEncryptionKey(jpsConfigFile)
```

Argument	Definition
<i>jpsConfigFile</i>	Specifies the location of the file <code>jps-config.xml</code> relative to the location where the command is run.

Example

```
restoreEncryptionKey(jpsConfigFile="pathName")
```

2.1.1.36 revokeAppRole

Online command that removes a principal from a role.

Description

Removes a principal (class or name) from a role with a given application stripe and name. In the event of an error, the command returns a `WLSTException`.

Syntax

```
revokeAppRole(appStripe, appRoleName, principalClass, principalName)
```

Argument	Definition
<i>appStripe</i>	Specifies an application stripe.
<i>appRoleName</i>	Specifies a role name.
<i>principalClass</i>	Specifies the fully qualified name of a class.
<i>principalName</i>	Specifies the principal name.

Example

The following example removes a principal to the role with application stripe `myApp` and role name `myRole`:

```
wls:/mydomain/serverConfig> revokeAppRole(appStripe="myApp",  
appRoleName="myRole",principalClass="com.example.xyzPrincipal",  
principalName="myPrincipal")
```

2.1.1.37 revokeEntitlement

Online command that deletes an entitlement.

Description

Deletes an entitlement and revokes the entitlement from the principal in a specified application stripe.

Syntax

```
revokeEntitlement(appStripe="appStripeName", principalClass="principalClass",
principalName="principalName" , -permSetName="entName")
```

Argument	Definition
<i>appStripe</i>	Specifies the application stripe where the entitlement is deleted.
<i>principalClass</i>	Specifies the class associated with the principal.
<i>principalName</i>	Specifies the name of the principal to which the entitlement is revoked.
<i>permSetName</i>	Specifies the name of the entitlement deleted.

Example

The following example deleted the entitlement myEntitlement in the stripe myApplication:

```
wls:/mydomain/serverConfig> revokeEntitlement(appStripe="myApplication",
principalClass="oracle.security.jps.service.policystore.ApplicationRole",
principalName="myPrincipalName", permSetName="myEntitlement")
```

2.1.1.38 revokePermission

Online command that removes a permission.

Description

Removes a permission for a given code base or URL. In the event of an error, the command returns a WLSTException.

Syntax

```
revokePermission([appStripe,] [codeBaseURL,] [principalClass,] [principalName,]
permClass, [permTarget,] [permActions])
```

Argument	Definition
<i>appStripe</i>	Specifies an application stripe. If not specified, the command works on system policies.
<i>codeBaseURL</i>	Specifies the URL of the code granted the permission.
<i>principalClass</i>	Specifies the fully qualified name of a class (grantee).
<i>principalName</i>	Specifies the name of the grantee principal.
<i>permClass</i>	Specifies the fully qualified name of the permission class.
<i>permTarget</i>	Specifies, when available, the name of the permission target. Some permissions may not include this attribute.
<i>permActions</i>	Specifies a comma-separated list of actions granted. Some permissions may not include this attribute and the actions available depend on the permission class.

Example

The following example removes the application permission (for the application with application stripe myApp) with the specified data:

```
wls:/mydomain/serverConfig> revokePermission(appStripe="myApp",
principalClass="my.custom.Principal", principalName="manager",
permClass="java.security.AllPermission")
```

The following example removes the system permission with the specified data:

```
wls:/mydomain/serverConfig> revokePermission(principalClass="my.custom.Principal",
principalName="manager",
permClass="java.io.FilePermission", permTarget="/tmp/fileName.ext",
permActions="read,write")
```

2.1.1.39 revokeResourceFromEntitlement

Online command that removes a resource from an entitlement.

Description

Removes a resource from an entitlement in a specified application stripe.

Syntax

```
revokeResourceFromEntitlement(appStripe="appStripeName", name="entName",
resourceName="resName", resourceType="resTypeName", actions="actionList")
```

Argument	Definition
<i>appStripe</i>	Specifies the application stripe where the entitlement is located.
<i>name</i>	Specifies the name of the entitlement to modify.
<i>resourceName</i>	Specifies the name of the resource to remove.
<i>resourceType</i>	Specifies the type of the resource to remove.
<i>actions</i>	Specifies the comma-separated list of actions to remove.

Example

The following example removes the resource myResource from the entitlement myEntitlement in the stripe myApplication:

```
wls:/mydomain/serverConfig>
revokeResourceFromEntitlement(appStripe="myApplication", name="myEntitlement",
resourceName="myResource", resourceType="myResType", actions="view,edit")
```

2.1.1.40 rollOverEncryptionKey

Offline command that changes the domain encryption key.

Description

This offline script replaces the current domain OPSS encryption key with a new one; the current key is not deleted but archived, since it is used to decrypt data that was encrypted using that key.

Note the following important points:

- This command should be executed from the administration server in the domain. No server restart is needed after its execution.
- If the domain is the only domain accessing the security store, nothing else is required.
- However, if two or more domains share the security store, the newly generated key should be exported from the domain where the script was run and imported into each of the other domains sharing the security store, using the scripts [exportEncryptionKey](#) and [importEncryptionKey](#).

Syntax

```
rolloverEncryptionKey(jpsConfigFile="pathName")
```

Argument	Definition
<i>jpsConfigFile</i>	Specifies the location of the file <code>jps-config.xml</code> ; either relative to the location where the script is run, or the full path.

Example

The following example lists all resource types in the stripe `myApplication`:

```
wls:/mydomain/serverConfig> rolloverEncryptionKey(jpsConfigFile="myConfig")
```

2.1.1.41 updateCred

Online command that modifies the type, user name, and password of a credential.

Description

Modifies the type, user name, password, URL, and port number of a credential in the domain credential store with given map name and key name. This command can update the data encapsulated in credentials of type password only. In the event of an error, the command returns a `WLSTException`. This command runs in interactive mode only.

Syntax

```
updateCred(map, key, user, password, [desc])
```

Argument	Definition
<i>map</i>	Specifies a map name (folder).
<i>key</i>	Specifies a key name.
<i>user</i>	Specifies the credential user name.
<i>password</i>	Specifies the credential password.
<i>desc</i>	Specifies a string describing the credential.

Example

The following example updates a password credential with the specified data:

```
wls:/mydomain/serverConfig> updateCred(map="myMap", key="myKey", user="myUsr",
password="myPassw", desc="updated passw cred to connect to app xyz")
```

2.1.1.42 updateTrustServiceConfig

Online command that updates the configuration of the domain trust service service with the values passed in a property file.

Description

Updates the trust service domain configuration. In the event of an error, the command returns a `WLSTException`.

Syntax

```
updateTrustServiceConfig([providerName="<the provider name>",]
propsFile="<path of properties file>")
```

Argument	Definition
<code>providerName</code>	Specifies the name of the trust service provider; optional; if unspecified, it defaults to <code>trust.provider.embedded</code> .
<code>propsFile</code>	Specifies the path to the file where the property values are set.

Here is a sample property file:

```
trust.keystoreType=KSS
trust.keyStoreName=kss://<stripeName>/<keystoreName>
trust.trustStoreName=kss://<stripeName>/<truststoreName>
trust.aliasName=<aliasName>
trust.issuerName=<aliasName>
```

Note that the list of specified properties differs according to the value of the property `trust.keystoreType`. The type can be `KSS` or `JKS`; if a property is set to the empty string, then that property is removed from the trust service configuration. For the list of available properties, see section Trust Service Properties.

Example

The following example updates the trust store service with the specifications in the file `myProps`:

```
wls:/mydomain/serverConfig> updateTrustServiceConfig(providerName="myProvider",
propsFile="myProps")
```

2.1.2 Audit Configuration Commands

Use the WLST commands listed in [Table 2-3](#) to view and manage audit policies and the audit repository configuration.

Table 2-3 WLST Audit Commands

Use this command	To	Use with WLST
createIAUView	Generate an SQL script to create an IAU view in the database.	Online
createAuditDBView	Generate an SQL script to create an audit definitions view in the database.	Online
deregisterAudit	Remove audit definitions of a specified component from the audit store.	Online
exportAuditConfig	Export a component's audit configuration.	Online
getIAUViewInfo	Get information about a view.	Online
getNonJavaEEAuditMBeanName	Display the mBean name for a non-Java EE component.	Online
getAuditPolicy	Display audit policy settings.	Online
getAuditRepository	Display audit repository settings.	Online
importAuditConfig	Import a component's audit configuration.	Online
listAuditComponents	List components that can be audited.	Online
listAuditEvents	List audit events for one or all components.	Online
setAuditPolicy	Update audit policy settings.	Online
setAuditRepository	Update audit repository settings.	Online

Table 2–3 (Cont.) WLST Audit Commands

Use this command	To	Use with WLST
<code>registerAudit</code>	Register audit definitions for a specified component in the audit store.	Online

For more information, see the *Securing Applications with Oracle Platform Security Services*.

2.1.2.1 `getNonJavaEEAuditMBeanName`

Online command that displays the mbean name for non-Java EE components.

Description

This command displays the mbean name for non-Java EE components given the instance name, component name, component type, and the name of the Oracle WebLogic Server on which the component's audit mbean is running. The mbean name is a required parameter to other audit WLST commands when managing a non-Java EE component.

Syntax

```
getNonJavaEEAuditMBeanName(instName, compName, compType, svrName)
```

Argument	Definition
<i>instName</i>	Specifies the name of the application server instance.
<i>compName</i>	Specifies the name of the component instance.
<i>compType</i>	Specifies the type of component. Valid values are ohs, oid, ovd, and WebCache.
<i>svrName</i>	Specifies the name of the Oracle WebLogic Server.

Example

The following example displays the mBean name for an Oracle Internet Directory:

```
wls:/mydomain/serverConfig> getNonJavaEEAuditMBeanName(instName='inst1',
compName='oid1', compType='oid', svrName='AdminServer')
```

2.1.2.2 `getAuditPolicy`

Online command that displays the audit policy settings.

Description

This command displays audit policy settings including the filter preset, special users, custom events, maximum log file size, and maximum log directory size. The component mbean name is required for non-Java EE components like Oracle HTTP Server.

Note: You can obtain a non-Java EE component's MBean name using the `getNonJavaEEAuditMBeanName` command.

Syntax

```
getAuditPolicy([mbeanName, componentType])
```

Argument	Definition
<i>mbeanName</i>	Specifies the name of the component audit MBean for non-Java EE components.
<i>componentType</i>	Requests the audit policy for a specific component registered in the audit store. If not specified, the audit policy in <code>jps-config.xml</code> is returned.

Example

The following example displays the audit settings for a Java EE component:

```
wls:/mydomain/serverConfig> getAuditPolicy(componentType='JPS');
Location changed to domainRuntime tree. This is a read-only tree with DomainMBean
as the root.
For more help, use help(domainRuntime)
```

```
FilterPreset:All
Max Log File Size:104857600
```

The following example displays the audit settings for MBean `CSAuditProxyMBean`:

```
wls:/mydomain/serverConfig>
getAuditPolicy(on='oracle.security.audit.test:type=CSAuditMBean,
name=CSAuditProxyMBean')
```

2.1.2.3 setAuditPolicy

Online command that updates an audit policy.

Description

Online command that configures the audit policy settings. You can set the filter preset, add or remove users, and add or remove custom events. The component mbean name is required for non-Java EE components like Oracle HTTP Server.

Note: You can obtain a non-Java EE component's MBean name using the [getNonJavaEEAuditMBeanName](#) command.

Syntax

```
setAuditPolicy([mbeanName], [filterPreset], [addSpecialUsers],
[removeSpecialUsers], [addCustomEvents], [removeCustomEvents], [componentType],
[maxFileSize], [andCriteria], [orCriteria], [componentEventsFile])
```

Argument	Definition
<i>mbeanName</i>	Specifies the name of the component audit MBean for non-Java EE components.
<i>filterPreset</i>	Specifies the filter preset to be changed.
<i>addSpecialUsers</i>	Specifies the special users to be added.
<i>removeSpecialUsers</i>	Specifies the special users to be removed.
<i>addCustomEvents</i>	Specifies the custom events to be added.
<i>removeCustomEvents</i>	Specifies the custom events to be removed.

Argument	Definition
<i>componentType</i>	Specifies the component definition type to be updated. The audit runtime policy for the component is registered in the audit store. If not specified, the audit configuration defined in <code>jps-config.xml</code> is modified.
<i>maxFileSize</i>	Specifies the maximum size of the log file.
<i>andCriteria</i>	Specifies the and criteria in a custom filter preset definition.
<i>orCriteria</i>	Specifies the or criteria in a custom filter preset definition.
<i>componentEventsFile</i>	Specifies a component definition file under the 11g Release 1 (11.1.1.6) metadata model. This parameter is required if you wish to create/update an audit policy in the audit store for an 11g Release 1 (11.1.1.6) metadata model component, and the filter preset level is set to "Custom".

Examples

The following example sets audit policy to None level, and adds users `user2` and `user3` while removing `user1` from the policy:

```
wls:/mydomain/serverConfig> setAuditPolicy (filterPreset=
'None',addSpecialUsers='user2,user3',removeSpecialUsers='user1',componentType='JPS
')
```

```
wls:/mydomain/serverConfig> getAuditPolicy(componentType='JPS');
Already in Domain Runtime Tree
```

```
FilterPreset:None
Special Users:user2,user3
Max Log File Size:104857600
```

The following example adds login events while removing logout events from the policy:

```
wls:/mydomain/serverConfig> setAuditPolicy(filterPreset=
'Custom',addCustomEvents='UserLogin',removeCustomEvents='UserLogout')
```

The following example sets audit policy to a Low level:

```
wls:/IDMDomain/domainRuntime>
setAuditPolicy(filterPreset='Low',componentType='JPS');
Already in Domain Runtime Tree
Audit Policy Information updated successfully
```

```
wls:/IDMDomain/domainRuntime> getAuditPolicy(componentType='JPS')
Already in Domain Runtime Tree
FilterPreset:Low
Max Log File Size:104857600
```

The following example sets a custom filter to audit the `CheckAuthorization` event:

```
wls:/IDMDomain/domainRuntime>setAuditPolicy(filterPreset='Custom',
componentType='JPS',addCustomEvents='Authorization:CheckPermission,
CheckSubject;CredentialManagement:CreateCredential,DeleteCredential');
Already in Domain Runtime Tree
```

```
Audit Policy Information updated successfully
wls:/IDMDomain/domainRuntime> getAuditPolicy(componentType='JPS');
```

Already in Domain Runtime Tree

```
FilterPreset:Custom
Special Users:user1
Max Log File Size:104857600
Custom Events:JPS:CheckAuthorization
```

2.1.2.4 getAuditRepository

Online command that displays audit repository settings.

Description

This command displays audit repository settings for Java EE components and applications (for other components like Oracle Internet Directory, the repository configuration resides in `opmn.xml`). Also displays database configuration if the repository is a database type.

Syntax

```
getAuditRepository
```

Example

The following example displays audit repository configuration:

```
wls:/IDMDomain/domainRuntime> getAuditRepository()
Already in Domain Runtime Tree
```

```
Repository Type:File
```

2.1.2.5 setAuditRepository

Online command that updates audit repository settings.

Description

This command sets the audit repository settings for Java EE and SE components and applications (for other components like Oracle Internet Directory, the repository is configured by editing `opmn.xml`).

Syntax

```
setAuditRepository([switchToDB], [dataSourceName], [interval],
                   [timezone], [repositoryType], [logDirectory],
                   [jdbcString], [dbUser], [dbPassword])
```

Argument	Definition
<i>switchToDB</i>	If <code>true</code> , switches the repository from file to database. Valid value: <code>true</code> .
<i>dataSourceName</i>	Specifies the JNDI name of the data source. This data source must be configured in the specified Oracle Weblogic Server domain.
<i>interval</i>	Specifies the time, in seconds, that the audit loader sleeps.
<i>timezone</i>	Specifies the time zone in which the audit loader records the timestamps of the audit events. Valid values are <code>utc</code> and <code>local</code> .
<i>repostoryType</i>	Specifies the database type to which the data has to be uploaded. The supported databases are Oracle, MS SQL Server and IBM DB2.
<i>logDirectory</i>	Specifies the audit log directory for SE applications to store bus stop files.

Argument	Definition
<i>jdbcString</i>	Specifies the audit repository jdbc connection string for SE applications.
<i>dbUser</i>	Specifies the audit repository IAU schema user.
<i>interval</i>	Specifies the audit repository IAU schema password.

Example

The following example changes audit repository to a specific database and sets the audit loader interval to 14 seconds, and the time zone to utc:

```
wls:/mydomain/serverConfig> setAuditRepository(switchToDB="true",
dataSourceName="jdbc/AuditDB",interval="14",timezone="utc",
repositoryType="DB_ORACLE", logDirectory="/foo",
jdbcString="jdbc:oracle:thin:@db.example.com:5001:sid",
dbUser="scott_iau", dbPassword="tiger")
```

2.1.2.6 listAuditEvents

Online command that displays a component's audit events.

Description

This command displays a component's audit events and attributes. For non-Java EE components, pass the component mbean name as a parameter. Java EE applications and services like Oracle Platform Security Services (OPSS) do not need the mbean parameter. Without a component type, all generic attributes applicable to all components are displayed.

Note: You can obtain a non-Java EE component's MBean name using the [getNonJavaEEAuditMBeanName](#) command.

Syntax

```
listAuditEvents([mbeanName],[componentType])
```

Argument	Definition
<i>mbeanName</i>	Specifies the name of the component MBean.
<i>componentType</i>	Specifies the component type to limit the list to all events of the component type.

Examples

The following example displays audit events for the Oracle Platform Security Services component:

```
wls:/IDMDomain/domainRuntime> listAuditEvents(componentType='JPS');
Already in Domain Runtime Tree
```

Common Attributes

ComponentType

Type of the component. For MAS integrated SystemComponents this is the componentType

InstanceId

Name of the MAS Instance, that this component belongs to

HostId

DNS hostname of originating host

HostNwaddr
IP or other network address of originating host
ModuleId
ID of the module that originated the message. Interpretation is unique within
Component ID.
ProcessId
ID of the process that originated the message

The following example displays audit events for Oracle HTTP Server:

```
wls:/mydomain/serverConfig> listAuditEvents(componentType='ohs')
```

The following example displays all audit events:

```
wls:/IDMDomain/domainRuntime> listAuditEvents();
```

```
Already in Domain Runtime Tree
Components:
DIP
JPS
OIF
OWSM-AGENT
OWSM-PM-EJB
ReportsServer
WS-PolicyAttachment
WebCache
WebServices
Attributes applicable to all components:
ComponentType
InstanceId
HostId
HostNwaddr
ModuleId
ProcessId
OracleHome
HomeInstance
ECID
RID
...
```

2.1.2.7 exportAuditConfig

Online command that exports a component's audit configuration.

Description

This command exports the audit configuration to a file. For non-Java EE components, pass the component mbean name as a parameter. Java EE applications and services like Oracle Platform Security Services (OPSS) do not need the mbean parameter.

Note: You can obtain a non-Java EE component's MBean name using the [getNonJavaEEAuditMBeanName](#) command.

Syntax

```
exportAuditConfig([mbeanName], fileName, [componentType])
```

Argument	Definition
<i>mbeanName</i>	Specifies the name of the non-Java EE component MBean.

Argument	Definition
<i>fileName</i>	Specifies the path and file name to which the audit configuration should be exported.
<i>componentType</i>	Specifies that only events of the given component be exported to the file. If not specified, the audit configuration in <code>jps-config.xml</code> is exported.

Example

The following example exports the audit configuration for a component:

```
wls:/mydomain/serverConfig>
exportAuditConfig(on='oracle.security.audit.test:type=CSAuditMBean,
name=CSAuditProxyMBean', fileName='/tmp/auditconfig')
```

The following example exports the audit configuration for a Java EE component; no `mBean` is specified:

```
wls:/mydomain/serverConfig> exportAuditConfig(fileName='/tmp/auditconfig')
```

2.1.2.8 importAuditConfig

Online command that imports a component's audit configuration.

Description

This command imports the audit configuration from an external file. For non-Java EE components, pass the component `mbean` name as a parameter. Java EE applications and services like Oracle Platform Security Services (OPSS) do not need the `mbean` parameter.

Note: You can obtain a non-Java EE component's MBean name using the [getNonJavaEEAuditMBeanName](#) command.

Syntax

```
importAuditConfig([mbeanName], fileName, [componentType])
```

Argument	Definition
<i>mbeanName</i>	Specifies the name of the non-Java EE component MBean.
<i>fileName</i>	Specifies the path and file name from which the audit configuration should be imported.
<i>componentType</i>	Specifies that only events of the given component be imported from the file. If not specified, the audit configuration in <code>jps-config.xml</code> is imported.

Examples

The following example imports the audit configuration for a component:

```
wls:/mydomain/serverConfig>
importAuditConfig(on='oracle.security.audit.test:type=CSAuditMBean,
name='CSAuditProxyMBean', fileName='/tmp/auditconfig')
```

The following example imports the audit configuration from a file; no `mBean` is specified:

```
wls:/mydomain/serverConfig> importAuditConfig(fileName='/tmp/auditconfig')
```

2.1.2.9 createAuditDBView

Creates a SQL script that generates a view for audit in the database.

Description

This command generates a SQL script that you can use to create a database view of the audit definitions of a specified component. The script is written to the specified file and also printed out to the console.

Upon execution, the result of the SQL script depends on the audit model at your site:

- If using the 11.1.1.6.0 model, and the component is registered in the audit store, the script creates a view using the system component tables (IAU_COMMON, IAU_USERSESSION, IAU_AUDITSERVICE and IAU_CUSTOM) for the specified component.
- If using the pre-11.1.1.6.0 model, the component is not registered in the audit store but its event definitions reside in the component_events.xml file (in the oracle_common/modules/oracle.iau_11.1.1/components/*componentType* directory), and the view is created using the IAU_BASE and component tables.

Syntax

```
createAuditDBView(fileName, componentType, [dbType], [viewType])
```

Argument	Definition
<i>fileName</i>	The path and file name to which the SQL script is written.
<i>componentType</i>	The name of the registered component.
<i>dbType</i>	The database type. One of the following: DB_ORACLE, MS_SQL_SERVER, IBM_DB2.
<i>viewType</i>	The view type. One of the following: SIMPLE, INDEXABLE.

Example

```
wls:/mydomain/serverConfig>
createAuditDBView(fileName="/tmp/JPSAuditView.sql", componentType="JPS",
                  dbType="DB_ORACLE", viewType=INDEXABLE)
```

2.1.2.10 createIAUView

Generates an SQL script to create an IAU view in the database.

Description

The generated script creates, by default, a SIMPLE view when the component is registered with the audit service; it switches the view from SIMPLE to INDEXABLE, or creates a view in the database. INDEXABLE views are supported for an Oracle database only. SIMPLE views can be created for all supported databases in the IAU_VIEWER schema.

Syntax

```
createIAUView(componentType, [viewType])
```

Argument	Definition
<i>componentType</i>	The component whose definitions are the basis of the view.

Argument	Definition
<i>viewType</i>	The type of view; valid values are SIMPLE or INDEXABLE. Default is SIMPLE.

Examples

```
wls:/mydomain/serverConfig>createIAUView(componentType="AuditApp,
viewType="INDEXABLE")
```

```
wls:/mydomain/serverConfig>createIAUView(componentType="AuditApp,
viewType="SIMPLE")
```

```
wls:/mydomain/serverConfig>createIAUView(componentType="AuditApp")
```

2.1.2.11 getIAUViewInfo

Returns information about the view of a component.

Description

Retrieves information about the view of a specified component.

Syntax

```
getIAUViewInfo(componentType)
```

Argument	Definition
<i>componentType</i>	The component whose definitions are the basis of the view.

Example

```
wls:/mydomain/serverConfig> getIAUViewInfo(componentType="JPS")
```

2.1.2.12 listAuditComponents

Lists components that can be audited.

Description

This command creates a list of the components that can be audited. It lists components registered in the audit store using both the 11.1.1.6.0 model and the pre-11.1.1.6.0 model.

Syntax

```
listAuditComponents(fileName)
```

Argument	Definition
<i>fileName</i>	Specifies the path and file name to which the output is written.

Example

```
listAuditComponents(fileName = "/tmp/complist.txt")
```

2.1.2.13 registerAudit

Registers a component with the audit service.

Description

Adds the event definition and translation content for a specified component to the audit store. If you try to register using the pre-11.1.1.6.0 audit XML schema definition, it is upgraded to the 11.1.1.6.0 XML schema definition and then registered with the audit store.

Syntax

```
registerAudit(xmlFile, [xlfFile], componentType, [mode=OVERWRITE|UPGRADE],
             [createView=SIMPLE|INDEXABLE|DISABLE])
```

Argument	Definition
<i>xmlFile</i>	Specifies the Component Event definition file.
<i>xlfFile</i>	Specifies the component xlf jar file. Optional.
<i>componentType</i>	Specifies the component to be registered.
<i>mode</i>	Optional. OVERWRITE or UPGRADE. Default is UPGRADE.
<i>createView</i>	Optional. SIMPLE, INDEXABLE or DISABLE. Default is SIMPLE.

Example

```
wls:/mydomain/serverConfig>registerAudit(xmlFile="/tmp/comp.xml",
xmlFile="/tmp/comp_xlf.jar", componentType="AuditApp", mode="UPGRADE",
createView=INDEXABLE)
```

2.1.2.14 deregisterAudit

Removes the event definition and translation content from the audit store. for a component.

Description

Removes an existing event definition and translation content for a specified component or application from the audit store.

Syntax

```
deregisterAudit(componentType)
```

Argument	Definition
<i>componentType</i>	Specifies the component whose definitions are to be removed.

Example

```
wls:/mydomain/serverConfig> deregisterAudit(componentType="AuditApp")
```

2.1.3 OPSS Keystore Service Commands

This section contains commands used with the OPSS keystore service.

Note: You need to acquire an OPSS handle to use keystore service commands; this handle is denoted by 'svc' in the discussion that follows. For details, see Managing Keys and Certificates with the Keystore Service in *Securing Applications with Oracle Platform Security Services*.

Table 2–4 lists the WLST commands used to manage the keystore service.

Table 2–4 OPSS Keystore Service Commands

Use this Command...	to...	Use with WLST...
<code>changeKeyPassword</code>	Change the password for a key.	Online
<code>changeKeyStorePassword</code>	Change the password on a keystore.	Online
<code>createKeyStore</code>	Create a keystore.	Online
<code>deleteKeyStore</code>	Delete a keystore.	Online
<code>deleteKeyStoreEntry</code>	Delete an entry in a keystore.	Online
<code>exportKeyStore</code>	Export a keystore to file.	Online
<code>exportKeyStoreCertificate</code>	Export a certificate to a file.	Online
<code>exportKeyStoreCertificateRequest</code>	Export a certificate request to a file.	Online
<code>generateKeyPair</code>	Generate a keypair.	Online
<code>generateSecretKey</code>	Generate a secret key.	Online
<code>getKeyStoreCertificates</code>	Get information about a certificate or trusted certificate.	Online
<code>getKeyStoreSecretKeyProperties</code>	Get the secret key properties.	Online
<code>importKeyStore</code>	Import a keystore from file.	Online
<code>importKeyStoreCertificate</code>	Import a certificate or other object.	Online
<code>listExpiringCertificates</code>	List certificates expiring in a specified period.	Online
<code>listKeyStoreAliases</code>	List aliases in a keystore.	Online
<code>listKeyStores</code>	List all the keystores in a stripe.	Online
<code>syncKeyStores</code>	Synchronizes the keystores in the administration server with keystores in the security store.	Online

2.1.3.1 changeKeyPassword

Changes a key password.

Description

Changes the password for a key.

Syntax

```
changeKeyPassword(appStripe='stripe', name='keystore', password='password',
alias='alias', currentkeypassword='currentkeypassword',
newkeypassword='newkeypassword')
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>appStripe</i>	Specifies the name of the stripe containing the keystore
<i>name</i>	Specifies the name of the keystore

Argument	Definition
<i>password</i>	Specifies the keystore password
<i>alias</i>	Specifies the alias of the key entry whose password is changed
<i>currentkeypassword</i>	Specifies the current key password
<i>newkeypassword</i>	Specifies the new key password

Example

The following example changes the password on the key entry *orakey*:

```
wls:/mydomain/serverConfig> changeKeyPassword(appStripe='system',
name='keystore', password='password',
alias='orakey', currentkeypassword='currentkeypassword',
newkeypassword='newkeypassword')
```

2.1.3.2 changeKeyStorePassword

Changes the password of a keystore.

Description

Changes the password of the specified keystore.

Syntax

```
changeKeyStorePassword(appStripe='stripe', name='keystore',
currentpassword='currentpassword', newpassword='newpassword')
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>appStripe</i>	Specifies the name of the stripe containing the keystore
<i>name</i>	Specifies the name of the keystore
<i>currentpassword</i>	Specifies the current keystore password
<i>newpassword</i>	Specifies the new keystore password

Example

The following example changes the password for *keystore2*.

```
wls:/mydomain/serverConfig> changeKeyStorePassword(appStripe='system',
name='keystore2',
currentpassword='currentpassword', newpassword='newpassword')
```

2.1.3.3 createKeyStore

This keystore service command creates a new keystore.

Description

Creates a new keystore on the given application stripe.

Syntax

```
createKeyStore(appStripe='stripe', name='keystore',
password='password', permission=true|false)
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>appStripe</i>	Specifies the name of the stripe where the keystore is created.
<i>name</i>	Specifies the name of the new keystore.
<i>password</i>	Specifies the keystore password.
<i>permission</i>	This parameter is true if the keystore is protected by permission only, false if protected by both permission and password.

Example

The following example creates a keystore named `keystore1`.

```
wls:/mydomain/serverConfig> createKeyStore(appStripe='system',
name='keystore1', password='password', permission=true)
```

2.1.3.4 deleteKeyStore

Deletes the named keystore.

Description

This keystore service command deletes a specified keystore.

Syntax

```
deleteKeyStore(appStripe='stripe', name='keystore', password='password')
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>appStripe</i>	Specifies the name of the stripe where the keystore resides.
<i>name</i>	Specifies the name of the keystore to be deleted.
<i>password</i>	Specifies the keystore password.

Example

The following example deletes the keystore named `keystore1`.

```
wls:/mydomain/serverConfig> deleteKeyStore(appStripe='system', name='keystore1',
password='password')
```

2.1.3.5 deleteKeyStoreEntry

Deletes a keystore entry.

Description

This command deletes the specified entry in a keystore.

Syntax

```
deleteKeyStoreEntry(appStripe='stripe', name='keystore',
password='password', alias='alias', keypassword='keypassword')
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>appStripe</i>	Specifies the name of the stripe where the keystore resides.
<i>name</i>	Specifies the name of the keystore.
<i>password</i>	Specifies the keystore password.
<i>alias</i>	Specifies the alias of the entry to be deleted
<i>keypassword</i>	Specifies the key password of the entry to be deleted

Example

The following example deletes a keystore entry denoted by alias `orakey`.

```
wls:/mydomain/serverConfig> deleteKeyStoreEntry(appStripe='system',
name='keystore2', password='password', alias='orakey', keypassword='keypassword')
```

2.1.3.6 exportKeyStore

Exports a keystore to a file.

Description

Exports a keystore to a specified file.

Syntax

```
exportKeyStore(appStripe='stripe', name='keystore', password='password',
aliases='comma-separated-aliases', keypasswords='comma-separated-keypasswords',
type='keystore-type', filepath='absolute_file_path')
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>appStripe</i>	Specifies the name of the stripe where the keystore resides.
<i>name</i>	Specifies the name of the keystore.
<i>password</i>	Specifies the keystore password. The value also applies to the output file, based on the current usage of the command: <ul style="list-style-type: none"> ■ For password-protected keystores of all types, this will be the password of the output file; ■ For permission-protected keystores of type JKS or JCEKS, this will be the password of the output file; ■ For permission-protected keystores of type OracleWallet, if the password value is non-empty, this will be the password of the output file; an empty value will create an auto-login wallet. <p>If the keystore is password-based, the value of this argument must be the same as the password specified when the password-based keystore was created. Otherwise, if the keystore is not password-based, any value is valid.</p>
<i>aliases</i>	Specifies a comma separated list of aliases to be exported.

Argument	Definition
<i>keypasswords</i>	Specifies the password(s) of the key(s) being exported. The usage depends on the keystore type: <ul style="list-style-type: none"> ▪ If type is JKS or JCEKS, and the keystore is permission-protected, this is a comma separated list of the key passwords corresponding to aliases in the output file. ▪ If type is JKS or JCEKS, and the keystore is password-protected, this is a comma separated list of the key passwords corresponding to aliases in both the source keystore and the output file. ▪ If type is OracleWallet, this parameter is ignored.
<i>type</i>	Exported keystore type. Valid values are 'JKS' or 'JCEKS' or 'OracleWallet'.
<i>filepath</i>	For type JKS or JCEKS, the absolute path of the file where the keystore is exported, including filename. For type OracleWallet, the absolute path of the directory where the keystore is exported.

Examples

The following example exports two aliases from the specified keystore.

```
wls:/mydomain/serverConfig> exportKeyStore(appStripe='system', name='keystore2',
password='password', aliases='orakey, seckey',
keypasswords='keypassword1, keypassword2',
type='JKS', filepath='/tmp/file.jks')
```

The following example exports a keystore to create an Oracle Wallet file:

```
wls:/mydomain/serverConfig> exportKeyStore(appStripe='system', name='keystore2',
password='mypassword', aliases='orakey, seckey',
keypasswords='', type='OracleWallet', filepath='/tmp')
```

2.1.3.7 exportKeyStoreCertificate

Exports a certificate.

Description

Exports a certificate, trusted certificate or certificate chain.

Syntax

```
exportKeyStoreCertificate(appStripe='stripe', name='keystore',
password='password', alias='alias', keypassword='keypassword',
type='entrytype', filepath='absolute_file_path')
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>appStripe</i>	Specifies the name of the stripe where the keystore resides.
<i>name</i>	Specifies the name of the keystore.
<i>password</i>	Specifies the keystore password.
<i>alias</i>	Specifies the alias of the entry to be exported
<i>keypassword</i>	Specifies the key password.

Argument	Definition
<i>type</i>	Specifies the type of keystore entry to be exported. Valid values are 'Certificate', 'TrustedCertificate' or 'CertificateChain'.
<i>filepath</i>	Specifies the absolute path of the file where certificate, trusted certificate or certificate chain is exported.

Example

The following example exports a certificate corresponding to the `orakey` alias:

```
wls:/mydomain/serverConfig> exportKeyStoreCertificate(appStripe='system',
name='keystore2',
password='password', alias='orakey', keypassword='keypassword',
type='Certificate', filepath='/tmp/cert.txt')
```

2.1.3.8 exportKeyStoreCertificateRequest

Exports a certificate request.

Description

Generates and exports a certificate request from a keystore.

Syntax

```
exportKeyStoreCertificateRequest(appStripe='stripe', name='keystore',
password='password', alias='alias', keypassword='keypassword',
filepath='absolute_file_path')
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>appStripe</i>	Specifies the name of the stripe where the keystore resides.
<i>name</i>	Specifies the name of the keystore.
<i>password</i>	Specifies the keystore password.
<i>alias</i>	Specifies the entry's alias name.
<i>keypassword</i>	Specifies the key password.
<i>filepath</i>	Specifies the absolute path of the file where certificate request is exported.

Example

The following example exports a certificate request corresponding to the `orakey` alias.

```
wls:/mydomain/serverConfig> exportKeyStoreCertificateRequest(appStripe='system',
name='keystore2',
password='password', alias='orakey', keypassword='keypassword',
filepath='/tmp/certreq.txt')
```

2.1.3.9 generateKeyPair

Generates a key pair in a keystore.

Description

Generates a key pair using a specified algorithm, and wraps it in a demo CA-signed certificate.

Syntax

```
generateKeyPair(appStripe='stripe', name='keystore', password='password',
dn='distinguishedname', keysize='keysize', alias='alias',
keypassword='keypassword'[, algorithm='algoName'])
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>appStripe</i>	Specifies the name of the stripe where the keystore resides.
<i>name</i>	Specifies the name of the keystore.
<i>password</i>	Specifies the keystore password.
<i>dn</i>	Specifies the distinguished name of the certificate wrapping the key pair.
<i>keysize</i>	Specifies the key size.
<i>alias</i>	Specifies the alias of the key pair entry.
<i>keypassword</i>	Specifies the key password.
<i>algorithm</i>	Specifies the algorithm to use to encrypt the generated keys. The only valid values are RSA or EC (Elliptic Curve Cryptography). Optional. If not specified, the command used the RSA algorithm.

Examples

The following example generates a keypair in keystore2 using the default RSA algorithm:

```
wls:/mydomain/serverConfig> generateKeyPair(appStripe='system', name='keystore2',
password='password', dn='cn=www.oracle.com', keysize='1024', alias='orakey',
keypassword='keypassword')
```

The following example generates a keypair in keystore2 using the RSA algorithm:

```
wls:/mydomain/serverConfig> generateKeyPair(appStripe='system', name='keystore2',
password='password', dn='cn=www.oracle.com', keysize='1024', alias='orakey',
keypassword='keypassword', algorithm='RSA')
```

The following example generates a keypair in keystore2. using the ECC (Elliptic Curve Cryptography) algorithm:

```
wls:/mydomain/serverConfig> generateKeyPair(appStripe='system', name='keystore2',
password='password', dn='cn=www.oracle.com', keysize='1024', alias='orakey',
keypassword='keypassword', algorithm='EC')
```

2.1.3.10 generateSecretKey

Generates a secret key.

Description

Generates a symmetric key in a keystore.

Syntax

```
generateSecretKey(appStripe='stripe', name='keystore', password='password',
algorithm='algorithm', keysize='keysize', alias='alias',
keypassword='keypassword')
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>appStripe</i>	Specifies the name of the stripe where the keystore resides.
<i>name</i>	Specifies the name of the keystore.
<i>password</i>	Specifies the keystore password.
<i>algorithm</i>	Specifies the symmetric key algorithm.
<i>keysize</i>	Specifies the key size.
<i>alias</i>	Specifies the alias of the key entry.
<i>keypassword</i>	Specifies the key password.

Example

The following example generates a keypair with keysize 128 in keystore2.

```
wls:/mydomain/serverConfig> generateSecretKey(appStripe='system',
name='keystore2', password='password',
algorithm='AES', keysize='128', alias='seckey', keypassword='keypassword')
```

2.1.3.11 getKeyStoreCertificates

Gets a certificate from the keystore.

Description

Retrieves information about a certificate or trusted certificate.

Syntax

```
getKeyStoreCertificates(appStripe='stripe', name='keystore',
password='password', alias='alias', keypassword='keypassword')
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>appStripe</i>	Specifies the name of the stripe where the keystore resides.
<i>name</i>	Specifies the name of the keystore.
<i>password</i>	Specifies the keystore password.
<i>alias</i>	Specifies the alias of the certificate, trusted certificate or certificate chain to be displayed.
<i>keypassword</i>	Specifies the key password.

Example

The following example gets certificates associated with keystore3.

```
wls:/mydomain/serverConfig> getKeyStoreCertificates(appStripe='system',
name='keystore3', password='password', alias='orakey', keypassword='keypassword')
```

2.1.3.12 getKeyStoreSecretKeyProperties

Retrieves secret key properties.

Description

Retrieves secret key properties like the algorithm.

Syntax

```
getKeyStoreSecretKeyProperties (appStripe='stripe', name='keystore',
password='password', alias='alias', keypassword='keypassword')
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>appStripe</i>	Specifies the name of the stripe where the keystore resides.
<i>name</i>	Specifies the name of the keystore.
<i>password</i>	Specifies the keystore password.
<i>alias</i>	Specifies the alias of the secret key whose properties are displayed.
<i>keypassword</i>	Specifies the secret key password.

Example

The following example gets properties for secret key seckey:

```
wls:/mydomain/serverConfig> getKeyStoreSecretKeyProperties (appStripe='system',
name='keystore3',
password='password', alias='seckey', keypassword='keypassword')
```

2.1.3.13 importKeyStore

Imports a keystore from file.

Description

Imports a keystore from a system file.

Syntax

```
importKeyStore (appStripe='stripe', name='keystore', password='password',
aliases='comma-separated-aliases', keypasswords='comma-separated-keypasswords',
type='keystore-type', permission=true|false, filepath='absolute_file_path')
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>appStripe</i>	Specifies the name of the stripe where the keystore will reside.
<i>name</i>	Specifies the name of the keystore.
<i>password</i>	Specifies the keystore password. These rules apply: <ul style="list-style-type: none"> ▪ If importing an auto-login Oracle Wallet file, no password is needed. ▪ If importing a password-protected Oracle Wallet file (ewallet.p12), enter a password of minimum eight characters.
<i>aliases</i>	Specifies the comma-separated aliases of the entries to be imported from the file. If type is set to OracleWallet, it is not required; otherwise, it is a required argument.

Argument	Definition
<i>keypasswords</i>	Specifies the passwords of the keys in the file. These rules apply: <ul style="list-style-type: none"> ▪ If type is JKS or JCEKS, enter comma-separated passwords of the keys. ▪ If type is OracleWallet, no password is needed. The key passwords will be the same as the keystore password.
<i>type</i>	Specifies the imported keystore type. Valid values are 'JKS' or 'JCEKS' or 'OracleWallet'.
<i>filepath</i>	If type is set to JKS or JCEKS, it specifies the absolute path of the keystore file to be imported, including filename. If type is set to OracleWallet, it specifies the absolute path of the directory where the Oracle Wallet is located.
<i>permission</i>	Specifies true if keystore is protected by permission only, false if protected by both permission and password. If set to true, the imported file is permission protected, so when call getKeyStore or getKey, set password to null.

Example

The following example imports a JKS keystore file to keystore2:

```
wls:/mydomain/serverConfig> importKeyStore(appStripe='system', name='keystore2',
password='password', aliases='orakey,seckey', keypasswords='keypassword1,
keypassword2', type='JKS', permission=true, filepath='/tmp/file.jks')
```

The following example imports an Oracle Wallet to keystore2:

```
importKeyStore(appStripe='system', name='keystore2',
password='mypassword', aliases='orakey,seckey', keypasswords='',
type='OracleWallet', permission=true, filepath='/tmp')
```

2.1.3.14 importKeyStoreCertificate

Imports a certificate or other specified object.

Description

Imports a certificate, trusted certificate or certificate chain.

Syntax

```
importKeyStoreCertificate(appStripe='stripe', name='keystore',
password='password', alias='alias', keypassword='keypassword',
type='entrytype', filepath='absolute_file_path')
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to getOpssService().
<i>appStripe</i>	Specifies the name of the stripe where the keystore resides.
<i>name</i>	Specifies the name of the keystore.
<i>password</i>	Specifies the keystore password.
<i>alias</i>	Specifies the alias of the entry to be imported.
<i>keypassword</i>	Specifies the key password of the newly imported entry.
<i>type</i>	Specifies the type of keystore entry to be imported. Valid values are 'Certificate', 'TrustedCertificate' or 'CertificateChain'.

Argument	Definition
<i>filepath</i>	Specifies the absolute path of the file from where certificate, trusted certificate or certificate chain is imported.

Example

The following example imports a certificate into keystore2.

```
wls:/mydomain/serverConfig> importKeyStoreCertificate(appStripe='system',
name='keystore2',
password='password', alias='orakey', keypassword='keypassword',
type='Certificate', filepath='/tmp/cert.txt')
```

2.1.3.15 listExpiringCertificates

Lists expiring certificates.

Description

Lists expiring certificates and optionally renews them.

Syntax

```
listExpiringCertificates(days='days', autorenew=true|false)
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>days</i>	Specifies that the list should only include certificates within this many days from expiration.
<i>autorenew</i>	Specifies true for automatically renewing expiring certificates, false for only listing them.

Example

The following example lists certificates expiring within one year, and requests that they be renewed:

```
wls:/mydomain/serverConfig> listExpiringCertificates(days='365', autorenew=true)
```

2.1.3.16 listKeyStoreAliases

Lists the aliases in a keystore.

Description

Lists the aliases in a keystore for a given type of entry.

Syntax

```
listKeyStoreAliases(appStripe='stripe', name='keystore',
password='password', type='entrytype')
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>appStripe</i>	Specifies the name of the stripe where the keystore resides.
<i>name</i>	Specifies the name of the keystore.

Argument	Definition
<i>password</i>	Specifies the keystore password.
<i>type</i>	Specifies the type of entry for which aliases are listed. Valid values are 'Certificate', 'TrustedCertificate', 'SecretKey' or '*'.

Example

The following example lists secret keys in keystore2:

```
wls:/mydomain/serverConfig> listKeyStoreAliases (appStripe='system',
name='keystore2',
password='password', type='SecretKey')
```

2.1.3.17 listKeyStores

Lists all the keystores in a stripe.

Description

Lists all the keystores in the specified stripe.

Syntax

```
listKeyStores (appStripe='stripe')
```

Argument	Definition
<i>svc</i>	Specifies the service command object obtained through a call to <code>getOpssService()</code> .
<i>appStripe</i>	Specifies the name of the stripe whose keystores are listed.

Example

The following example lists all keystores on all stripes.

```
wls:/mydomain/serverConfig> listKeyStores (appStripe='*')
```

2.1.3.18 syncKeyStores

Synchronizes Oracle WebLogic Server and system keystores from the central repository to the domain `config` directory on the administration server.

Description

Synchronizes keystores in the central security store with those present in the domain directory.

If the target format is Oracle Wallet, the command synchronizes the contents of all KSS keystores for a given stripe into auto-login wallets on the server.

Syntax

The syntax is as follows:

```
syncKeyStores (stripeName='component-type#component-name',
keystoreFormat='exported_file_format',
rootDirectory='root_dir_absolute_path')
```

Argument	Definition
<i>StripeName</i>	Specifies the name of the stripe corresponding to the component. If <code>keystoreFormat</code> is 'OracleWallet', enter the stripe name in the format ' <i>component-type#component-name</i> '. Keystores in this stripe should be permission-protected only, never password-protected.
<i>keystoreFormat</i>	Specifies the format of the target keystore. Valid formats are 'KSS' and 'OracleWallet'.
<i>rootDirectory</i>	For the Oracle Wallet format, specifies the absolute path of the server directory where the wallet(s) are created. If not specified, defaults to <code>Admin_Server_Root/config/fmwconfig/</code> .

Note: The `svc` argument does not apply to this command.

Example

The following example looks up the central repository for the "system" stripe and downloads its contents into the `keystores.xml` file under the `DOMAIN_HOME/config/fmwconfig` directory. It also downloads the contents of the domain trust store into the same file:

```
wls:/mydomain/serverConfig> syncKeyStores()
```

The following example generates Oracle Wallets corresponding to all keystores in the stripe 'ohs#ohs1':

```
syncKeyStores(stripeName="ohs#ohs1",
keystoreFormat="OracleWallet", rootDirectory="/tmp/bin")
```

2.1.4 Identity Directory Service Commands

Use the WLST commands listed in [Table 2-5](#) to manage Identity Directory Service entity attributes, entity definitions, relationships and default operational configurations.

Table 2-5 WLST Identity Directory Service Commands

Use this command...	To...	Use with WLST...
activateIDSCfgChanges	Reload the Identity Directory Service configuration.	Online
addAttributeInEntityConfig	Add a new attribute to the entity configuration.	Online
addAttributePropsInEntityConfig	Add new properties for an attribute in an entity configuration.	Online
addAttributeRefForEntity	Add a new attribute to the specified entity.	Online
addAttrrefPropsInEntityConfig	Add new properties for an attribute reference in an entity configuration.	Online
addCommonPropertyForOperationConfig	Add a new property for a specified operation configuration.	Online
addEntity	Add a new entity to the entity configuration.	Online
addEntityProps	Add new properties for an entity in an entity configuration.	Online

Table 2–5 (Cont.) WLST Identity Directory Service Commands

Use this command...	To...	Use with WLST...
addEntityRelation	Add a new entity relation to the entity configuration.	Online
addIdentityDirectoryService	Add a new Identity Directory Service to the configuration.	Online
addOperationConfig	Add a new operation configuration to the entity configuration.	Online
addPropertyForOperationConfig	Add a new property to a specified operation configuration.	Online
deleteAttributeInEntityConfig	Delete an attribute from an entity configuration.	Online
deleteAttributePropsInEntityConfig	Delete attribute properties in an entity configuration.	Online
deleteAttrrefPropsInEntityConfig	Delete attribute reference properties in an entity configuration.	Online
deleteEntity	Delete an entity from an entity configuration.	Online
deleteEntityProps	Delete entity properties in an entity configuration.	Online
deleteEntityRelation	Delete the specified entity relation.	Online
deleteIdentityDirectoryService	Delete the specified Identity Directory Service in the configuration.	Online
deleteOperationConfig	Delete operation configuration in an entity configuration.	Online
listAllAttributeInEntityConfig	List all attributes in the entity configuration.	Online
listAllEntityInEntityConfig	List all entities defined in the specified entity configuration.	Online
listAllIdentityDirectoryService	List all Identity Directory Services in the configuration.	Online
removeAttributeRefForEntity	Remove an attribute from the specified entity.	Online
removeCommonPropertyForOperationConfig	Remove a property for the specified operation configuration.	Online
removePropertyForOperationConfig	Remove a property for the specified operation configuration.	Online
updateAttributeInEntityConfig	Update attributes in an entity configuration.	Online
updateAttributePropsInEntityConfig	Update attribute properties in an entity configuration.	Online
updateAttrrefPropsInEntityConfig	Update attribute reference properties in an entity configuration.	Online
updateEntity	Update an entity's properties in an entity configuration.	Online
updateEntityAttrs	Update an entity's properties in an entity configuration.	Online
updateEntityProps	Update the entity properties in an entity configuration.	Online

2.1.4.1 activateIDConfigChanges

Online command that reloads the configuration for Identity Directory Service.

Description

Reloads the Identity Directory Service configuration.

Syntax

```
activateIDConfigChanges()
```

This command has no arguments.

Example

The following command reloads the Identity Directory Service configuration:

```
activateIDConfigChanges()
```

2.1.4.2 addAttributeInEntityConfig

Online command that adds an attribute to the entity configuration.

Description

Adds a new attribute to the entity configuration.

Syntax

```
addAttributeInEntityConfig(name, datatype, description, readOnly, pwdAttr,
appName)
```

Table 2–6 *addAttributeInEntityConfig Arguments*

Argument	Definition
<i>name</i>	Name of the attribute to be added.
<i>datatype</i>	The attribute's type is defined as one of the following: <ul style="list-style-type: none"> ▪ binary ▪ boolean ▪ datetime ▪ double ▪ integer ▪ rfc822name ▪ string ▪ x500name
<i>description</i>	Description of the attribute to be added.
<i>readOnly</i>	Flag to specify whether the attribute is read only or can be modified.
<i>pwdAttr</i>	Flag to specify whether the attribute defines a password or not.
<i>appName</i>	Name of the Identity Directory Service.

Example

The following command adds an attribute `commonname` of `userrole` entity:

```
addAttributeInEntityConfig('commonname', 'string', 'common
```

```
name', false, false, 'userrole')
```

2.1.4.3 addAttributePropsInEntityConfig

Online command that adds properties for an attribute in an entity configuration.

Description

Adds new properties for an attribute in an entity configuration.

Syntax

```
addAttributePropsInEntityConfig(name, propName, propVals, appName)
```

Table 2–7 addAttributePropsInEntityConfig Arguments

Argument	Definition
<i>name</i>	Name of the attribute to be added.
<i>propNames</i>	List of property names separated by " ". The properties (<i>propNames</i> and <i>propVals</i>) are free key/value pairs. Applications can store any required metadata at the attribute level in these properties. The Identity Directory Service does not perform any validation for these property names and does not interpret or use these properties internally. For configuration attributes, however, the Identity Directory Service performs a schema check and interprets the configuration names and their values.
<i>propVals</i>	List of corresponding property values separated by " ".
<i>appName</i>	Name of the Identity Directory Service.

Example

The following command adds an attribute `orgunit` of entity `userrole`:

```
addAttributePropsInEntityConfig('orgunit', 'labelname|multivalued', 'common  
name|true', 'userrole')
```

2.1.4.4 addAttributeRefForEntity

Online command that adds attribute to an entity.

Description

Adds a new attribute to the specified entity.

Syntax

```
addAttributeRefForEntity(name, attrRefName, attrRefFilter, attrRefDefaultFetch,  
appName)
```

Table 2–8 addAttributeRefForEntity Arguments

Argument	Definition
<i>name</i>	Name of the entity to which the attribute will be added.
<i>attrRefName</i>	Name of the attribute to be added to the entity.

Table 2–8 (Cont.) addAttributeRefForEntity Arguments

Argument	Definition
<i>attrRefFilter</i>	Type of filter to be used with the attribute, defined as one of the following: <ul style="list-style-type: none"> ▪ beginswith ▪ contains ▪ doesnotcontain ▪ dynamic ▪ endswith ▪ equals ▪ greaterequal ▪ greaterthan ▪ lessequal ▪ lessthan ▪ none ▪ notequals
<i>attrRefDefaultFetch</i>	Flag to specify whether the attribute is fetched by default.
<i>appName</i>	Name of the Identity Directory Service.

Example

The following command adds an attribute `User` to `userrole` entity:

```
addAttributeRefForEntity('User', 'givenname', 'none', 'true', 'userrole')
```

2.1.4.5 addAttrrefPropsInEntityConfig

Online command that adds property for an attribute reference.

Description

Adds new properties for an attribute reference in an entity configuration.

Syntax

```
addAttrrefPropsInEntityConfig(entityName, attrName, propNames, propVals, appName)
```

Table 2–9 addAttrrefPropsInEntityConfig Arguments

Argument	Definition
<i>entityName</i>	Name of the entity.
<i>attrName</i>	Name of the attribute reference.
<i>propNames</i>	List of property names separated by " ". The properties (<i>propNames</i> and <i>propVals</i>) are free key/value pairs. Applications can store any required metadata at the attribute level in these properties. The Identity Directory Service does not perform any validation for these property names and does not interpret or use these properties internally. For configuration attributes, however, the Identity Directory Service performs a schema check and interprets the configuration names and their values.

Table 2–9 (Cont.) addAttrrefPropsInEntityConfig Arguments

Argument	Definition
<i>propVals</i>	List of corresponding property values separated by " ".
<i>appName</i>	Name of the Identity Directory Service.

Example

The following command adds a multivalued property `labelname` for `org` entity:

```
addAttrrefPropsInEntityConfig('org', 'orgunit', 'labelname|multivalued', 'common
name|true', 'userrole')
```

2.1.4.6 addCommonPropertyForOperationConfig

Online command that adds a property for an operation configuration.

Description

Adds a new property for a specified operation configuration.

Syntax

```
addCommonPropertyForOperationConfig(entityName, propName, propValue, appName)
```

Table 2–10 addCommonPropertyForOperationConfig Arguments

Argument	Definition
<i>entityName</i>	Name of the entity.
<i>propName</i>	Name of the property to be added for this operation configuration.
<i>propValue</i>	Value of the property to be added for this operation configuration.
<i>appName</i>	Name of the Identity Directory Service.

Example

The following command adds a new property member:

```
addCommonPropertyForOperationConfig('groupmember.attr', 'member', 'userrole')
```

2.1.4.7 addEntity

Online command that adds an entity to the configuration.

Description

Adds a new entity to the entity configuration.

Syntax

```
addEntity(name, type, idAttr, create, modify, delete, search, attrRefNames,
attrRefFilters, attrRefDefaultFetches, appName)
```

Table 2–11 *addEntity Arguments*

Argument	Definition
<i>name</i>	Name of the entity to which the attribute will be added.
<i>type</i>	Name of the attribute to be added to the entity.
<i>idAttr</i>	Identity attribute of the entity to be added.
<i>create</i>	Flag to specify the create is allowed.
<i>modify</i>	Flag to specify the modify is allowed.
<i>delete</i>	Flag to specify the delete is allowed.
<i>search</i>	Flag to specify the search is allowed.
<i>attrRefNames</i>	Array of attribute names.
<i>attrRefFilters</i>	An array of filter type values, defined as one of the following: <ul style="list-style-type: none"> ▪ beginswith ▪ contains ▪ doesnotcontain ▪ dynamic ▪ endswith ▪ equals ▪ greaterequal ▪ greaterthan ▪ lessequal ▪ lessthan ▪ none ▪ notequals
<i>attrRefDefaultFetches</i>	Array of boolean strings (true, false).
<i>appName</i>	Name of the Identity Directory Service.

Example

The following command adds an attribute `group` to the `Group` entity.

```
addEntity('Group', 'group', 'commonname', true, true, true, true, 'name|commonname', 'none|none', 'true|false', 'userrole')
```

2.1.4.8 addEntityProps

Adds property for an entity.

Description

Online command that adds new properties for an entity in an entity configuration.

Syntax

```
addEntityProps(name, propName, propVals, appName)
```

Table 2–12 *addEntityProps Arguments*

Argument	Definition
<i>name</i>	Name of the entity.

Table 2–12 (Cont.) addEntityProps Arguments

Argument	Definition
<i>propNames</i>	List of property names separated by " ".
<i>propValues</i>	List of corresponding property values separated by " ".
<i>appName</i>	Name of the Identity Directory Service.

Example

The following command adds `inclobjclasses` and `exclobjclasses` properties:

```
addEntityProps('User', 'inclobjclasses|exclobjclasses', 'inetorgperson|orclidxperson', 'userrole')
```

2.1.4.9 addEntityRelation

Online command that adds entity relation to an entity.

Description

Add a new entity relation to the entity configuration for the specified attributes.

Syntax

```
addEntityRelation(name, type, fromEntity, fromAttr, toEntity, toAttr, recursive, appName)
```

Table 2–13 addEntityRelation Arguments

Argument	Definition
<i>name</i>	Name of the relation between the entities for the given attributes.
<i>type</i>	Type of the entity relation ("ManyToMany", "ManyToOne", "OneToMany", "OneToOne").
<i>fromEntity</i>	Name of the from entity.
<i>fromAttr</i>	Name of the from attribute.
<i>toEntity</i>	Name of the to entity.
<i>toAttr</i>	Name of the to attribute.
<i>recursive</i>	Flag to set the entity relationship as recursive.
<i>appName</i>	Name of the Identity Directory Service.

Example

The following command adds the `manager` relation between the `manager` and `User` entities:

```
addEntityRelation('manager', 'ManyToOne', 'User', 'manager', 'User', 'principal', false, 'userrole')
```

2.1.4.10 addIdentityDirectoryService

Online command that adds an Identity Store Service.

Description

Adds a new IdentityStoreService to the Identity Directory Service configuration.

Syntax

```
addIdentityDirectoryService(name, description, propNames, propValues)
```

Table 2–14 addIdentityDirectoryService Arguments

Argument	Definition
<i>name</i>	Name of the IdentityStoreService to be added.
<i>description</i>	Description of the IdentityStoreService.
<i>propNames</i>	An array of property names to be added to the IdentityStoreService configuration.
<i>propValues</i>	An array of values to be defined for the property names added to the IdentityStoreService configuration.

Example

The following command adds the userrole IdentityStoreService:

```
addIdentityDirectoryService('userrole', 'user role', 'ovd.context|entity.config',
'default|userrole')
```

2.1.4.11 addOperationConfig

Online command that adds operation configuration to an entity.

Description

Adds a new operation configuration to the entity configuration.

Syntax

```
addOperationConfig(entityName, propNames, propValues, appName)
```

Table 2–15 addOperationConfig Arguments

Argument	Definition
<i>entityName</i>	Name of the entity to which the operation configuration will be added.
<i>propNames</i>	An array of property names to be added to the operation configuration.
<i>propValues</i>	An array of property values for the properties added to the operation configuration.
<i>appName</i>	Name of the Identity Directory Service.

Example

The following command adds the User entity to which the operation configuration will be added:

```
addOperationConfig('User', 'entity.searchbase', 'cn=users,dc=oracle,dc=com',
'userrole')
```

2.1.4.12 addPropertyForOperationConfig

Online command that adds a property to an operation configuration.

Description

Adds a new property to a specified operation configuration.

Syntax

```
addPropertyForOperationConfig(entityName, propName, propValue, appName)
```

Table 2–16 *addPropertyForOperationConfig Arguments*

Argument	Definition
<i>entityName</i>	Name of the entity to which the operation configuration will be added.
<i>propName</i>	A property name to be added to the operation configuration.
<i>propValue</i>	A value for the property added to the operation configuration.
<i>appName</i>	Name of the Identity Directory Service.

Example

The following command adds the property to the operation configuration:

```
addPropertyForOperationConfig('User', 'entity.searchbase',
'cn=users,dc=oracle,dc=com', 'userrole')
```

2.1.4.13 deleteAttributeInEntityConfig

Online command that deletes attribute from an entity.

Description

Deletes an attribute from an entity configuration.

Syntax

```
deleteAttributeInEntityConfig(name, appName)
```

Table 2–17 *deleteAttributeInEntityConfig Arguments*

Argument	Definition
<i>name</i>	Name of the attribute to be deleted.
<i>appName</i>	Name of the Identity Directory Service.

Example

The following command deletes the commonname attribute.

```
deleteAttributeInEntityConfig('commonname', 'userrole')
```

2.1.4.14 deleteAttributePropsInEntityConfig

Online command that deletes the properties of an attribute.

Description

Deletes attribute properties in an entity configuration.

Syntax

```
deleteAttributePropsInEntityConfig(name, propNames, appName)
```

Table 2–18 deleteAttributePropsInEntityConfig Arguments

Argument	Definition
<i>name</i>	Name of the attribute.
<i>propNames</i>	List of property names separated by " ".
<i>appName</i>	Name of the Identity Directory Service.

Example

The following example deletes the property `labelname` from the `userrole` entity:

```
deleteAttributePropsInEntityConfig('orgunit', 'labelname|multivalued', 'userrole')
```

2.1.4.15 deleteAttrrefPropsInEntityConfig

Online command that deletes attribute reference properties in an entity.

Description

Deletes one or more attribute reference properties in an entity configuration.

Syntax

```
deleteAttrrefPropsInEntityConfig(entityName, attrName, propNames, appName)
```

Table 2–19 deleteAttrrefPropsInEntityConfig Arguments

Argument	Definition
<i>entityName</i>	Name of the entity.
<i>attrName</i>	Name of the attribute reference.
<i>propNames</i>	List of property names to be deleted. If multiple properties are to be deleted, they should be separated by " ".
<i>appName</i>	Name of the Identity Directory Service.

Example

The following command deletes two properties from attribute reference `orgunit` of entity `org`:

```
deleteAttrrefPropsInEntityConfig('org',
'orgunit', 'labelname|multivalued', 'userrole')
```

2.1.4.16 deleteEntity

Online command that deletes an entity.

Description

Deletes an entity from an entity configuration.

Syntax

```
deleteEntity(name, appName)
```

Table 2–20 *deleteEntity Arguments*

Argument	Definition
<i>name</i>	Name of the entity to be deleted.
<i>appName</i>	Name of the Identity Directory Service.

Example

The following command deletes the User entity.

```
deleteEntity('User', 'userrole')
```

2.1.4.17 deleteEntityProps

Online command that deletes the properties of an entity.

Description

Deletes entity properties in an entity configuration.

Syntax

```
deleteEntityProps(name, propNames, appName)
```

Table 2–21 *deleteEntityProps Arguments*

Argument	Definition
<i>name</i>	Name of the entity.
<i>propNames</i>	List of property names separated by " ".
<i>appName</i>	Name of the Identity Directory Service.

Example

The following command deletes the two properties `inclobjclasses` and `exclobjclasses` of User entity:

```
deleteEntityProps('User', 'inclobjclasses|exclobjclasses', 'userrole')
```

2.1.4.18 deleteEntityRelation

Online command that deletes the relationship between entities.

Description

Deletes the specified entity relation between entities for the given attributes.

Syntax

```
deleteEntityRelation(name, appName)
```

Table 2–22 *deleteEntityRelation Arguments*

Argument	Definition
<i>name</i>	Name of the relation between the entities for the given attributes.
<i>appName</i>	Name of the Identity Directory Service.

Example

The following command deletes the manager relation specified between entities:

```
deleteEntityRelation('manager', 'userrole')
```

2.1.4.19 deleteIdentityDirectoryService

Online command that deletes the specified IdentityStoreService.

Description

Deletes the specified IdentityStoreService in the Identity Directory Service configuration.

Syntax

```
deleteIdentityDirectoryService(name)
```

where *name* is the name of the IdentityStoreService configuration to be deleted.

Example

The following example deletes ids1 IdentityStoreService configuration.

```
deleteIdentityDirectoryService('ids1')
```

2.1.4.20 deleteOperationConfig

Online command that deletes an operation configuration.

Description

Deletes an operation configuration in an entity configuration.

Syntax

```
deleteOperationConfig(entityName, appName)
```

Table 2–23 *deleteOperationConfig Arguments*

Argument	Definition
<i>entityName</i>	Name of the entity from which the operation configuration will be removed.
<i>appName</i>	Name of the Identity Directory Service.

Example

The following command deletes the operation configuration associated with entity User and application userrole:

```
deleteOperationConfig('User', 'userrole')
```

2.1.4.21 listAllAttributeInEntityConfig

Online command that lists all attributes.

Description

Lists all attributes in the entity configuration.

Syntax

```
listAllAttributeInEntityConfig(appName)
```

where *appName* is the name of the Identity Directory Service that contains the entity configuration from which the list of attributes is retrieved.

Example

The following command obtains the list of attributes from `userrole` entity:

```
listAllAttributeInEntityConfig('userrole')
```

2.1.4.22 listAllEntityInEntityConfig

Online command that lists all entities for an entity configuration.

Description

Lists all entities defined in the specified entity configuration.

Syntax

```
listAllEntityInEntityConfig(appName)
```

where *appName* is the name of the Identity Directory Service that contains the entity configuration from which the list of entities is retrieved.

Example

The following command obtains the list of entities associated with `userrole` entity:

```
listAllEntityInEntityConfig('userrole')
```

2.1.4.23 listAllIdentityDirectoryService

Online command that lists all `IdentityStoreService` for an Identity Directory Service configuration.

Description

Lists all `IdentityStoreService` in Identity Directory Service configuration.

Syntax

```
listAllIdentityDirectoryService()
```

This command has no arguments.

Example

The following command lists all the `IdentityStoreService` for an Identity Directory Service configuration:

```
listAllIdentityDirectoryService()
```

2.1.4.24 removeAttributeRefForEntity

Online command that deletes an attribute from an entity.

Description

Removes an attribute from the specified entity.

Syntax

```
removeAttributeRefForEntity(name, attrRefName, appName)
```

Table 2–24 *removeAttributeRefForEntity Arguments*

Argument	Definition
<i>name</i>	Name of the entity from which the attribute will be removed.
<i>attrRefName</i>	The name of the attribute to be removed.
<i>appName</i>	Name of the Identity Directory Service.

Example

The following command deletes the `givenname` attribute associated with `User` entity:

```
removeAttributeRefForEntity('User', 'givenname', 'userrole')
```

2.1.4.25 removeCommonPropertyForOperationConfig

Online command that deletes a property for an operation configuration.

Description

Removes a property for the specified operation configuration.

Syntax

```
removeCommonPropertyForOperationConfig(entityName, propName, appName)
```

Table 2–25 *removeCommonPropertyForOperationConfig Arguments*

Argument	Definition
<i>entityName</i>	Name of the entity.
<i>propName</i>	Name of property to be removed for this operation configuration.
<i>appName</i>	Name of the Identity Directory Service.

Example

The following command removes `groupmember.attr` property associated with `User` entity:

```
removeCommonPropertyForOperationConfig('User', 'groupmember.attr', 'userrole')
```

2.1.4.26 removePropertyForOperationConfig

Online command that removes a property for an operation configuration.

Description

Removes a property for the specified operation configuration.

Syntax

```
removePropertyForOperationConfig(entityName, propName, appName)
```

Table 2–26 *removePropertyForOperationConfig Arguments*

Argument	Definition
<i>entityName</i>	Name of the entity from which the operation configuration will be removed.
<i>propName</i>	A property name to be removed from the operation configuration.
<i>appName</i>	Name of the Identity Directory Service.

Example

The following command removes `entity.searchbase` property associated with User entity:

```
removePropertyForOperationConfig('User', 'entity.searchbase', 'userrole')
```

2.1.4.27 updateAttributeInEntityConfig

Online command that updates an attribute for an entity configuration.

Description

Updates attributes in an entity configuration.

Syntax

```
updateAttributeInEntityConfig(name, attrNames, attrVals, appName)
```

Table 2–27 *updateAttributeInEntityConfig Arguments*

Argument	Definition
<i>name</i>	Name of the entity attribute to be updated.
<i>attrNames</i>	List of configuration attribute names separated by " ". Valid configuration attribute names are: <ul style="list-style-type: none"> ▪ dataType ▪ description ▪ readOnly ▪ pwdAttr ▪ attrInUse
<i>attrVals</i>	List of corresponding attribute values separated by " ".
<i>appName</i>	Name of the Identity Directory Service.

Example

The following command updates the `commonname` attribute:

```
updateAttributeInEntityConfig('commonname', 'readOnly|pwdAttr|attrInUse', 'true|false|false', 'userrole')
```

2.1.4.28 updateAttributePropsInEntityConfig

Online command that updates the properties of an attribute for an entity.

Description

Updates attribute properties in an entity configuration.

Syntax

```
updateAttributePropsInEntityConfig(name, propName, propVals, appName)
```

Table 2–28 *updateAttributePropsInEntityConfig Arguments*

Argument	Definition
<i>name</i>	Name of the attribute to be updated.
<i>propNames</i>	List of property names separated by " ".
<i>propVals</i>	List of corresponding property values separated by " ".
<i>appName</i>	Name of the Identity Directory Service.

Example

The following command updates the properties for orgunit attribute associated with userrole application:

```
updateAttributePropsInEntityConfig('orgunit', 'multivalued', 'multivalued', 'userrole')
'
```

2.1.4.29 updateAttrrefPropsInEntityConfig

Online command that updates attribute reference properties for an entity.

Description

Updates attribute reference properties in an entity configuration.

Syntax

```
updateAttrrefPropsInEntityConfig(entityName, attrName, propName, propVals, appName)
```

Table 2–29 *updateAttrrefPropsInEntityConfig Arguments*

Argument	Definition
<i>entityName</i>	Name of the entity.
<i>attrName</i>	Name of the attribute reference.
<i>propNames</i>	List of property names separated by " ".
<i>propVals</i>	List of corresponding property values separated by " ".
<i>appName</i>	Name of the Identity Directory Service.

Example

The following command updates the attribute reference properties:

```
updateAttrrefPropsInEntityConfig('org',
'orgunit', 'entity.searchbase', 'multivalued', 'userrole')
```

2.1.4.30 updateEntity

Online command that updates properties of an entity.

Description

Updates an entity's properties in an entity configuration.

Syntax

```
updateEntity(name, type, idAttr, create, modify, delete, search, appName)
```

Table 2–30 *updateEntity Arguments*

Argument	Definition
<i>name</i>	Name of the entity to be updated.
<i>type</i>	Type of the entity.
<i>idAttr</i>	Identity attribute of the entity.
<i>create</i>	Flag to specify the create is allowed.
<i>modify</i>	Flag to specify the modify is allowed.
<i>delete</i>	Flag to specify the delete is allowed.
<i>search</i>	Flag to specify the search is allowed.
<i>appName</i>	Name of the Identity Directory Service.

Example

The following command updates the properties associated with Group entity:

```
updateEntity('Group', 'group', 'commonname', true, true, true, true, 'userrole')
```

2.1.4.31 updateEntityAttrs

Online command that updates the configuration attributes for an entity.

Description

Updates the configuration attributes for an entity attribute.

Syntax

```
updateEntityAttrs(name, attrNames, attrVals, appName)
```

Table 2–31 *updateEntityAttrs Arguments*

Argument	Definition
<i>name</i>	Name of the entity attribute. To update the properties of an entity attribute, see updateAttributePropsInEntityConfig .

Table 2–31 (Cont.) updateEntityAttrs Arguments

Argument	Definition
<i>attrNames</i>	List of configuration attribute names. If multiple configuration attributes are to be updated, they should be separated by " ". Valid configuration attribute names are: <ul style="list-style-type: none"> ■ idAttr ■ pwdAttr ■ firstnameAttr ■ lastnameAttr ■ mailAttr ■ displayNameAttr ■ descriptionAttr ■ challengeQnAttr ■ challengeAnsAttr ■ commonIdAttr.
<i>attrVals</i>	List of corresponding configuration attribute values separated by " ".
<i>appName</i>	Name of the Identity Directory Service.

Example

The following command updates configuration attributes associated with User entity:

```
updateEntityAttrs('User','idAttr|firstnameAttr','uid|givenname','userrole')
```

2.1.4.32 updateEntityProps

Online command that updates the properties of an entity.

Description

Updates the entity properties in an entity configuration.

Syntax

```
updateEntityProps(name, propName, propVals, appName)
```

Table 2–32 updateEntityProps Arguments

Argument	Definition
<i>name</i>	Name of the attribute to be updated.
<i>propNames</i>	List of property names separated by " ".
<i>propVals</i>	List of corresponding property values separated by " ".
<i>appName</i>	Name of the Identity Directory Service.

Example

The following command updates the properties associated with User entity:

```
updateEntityProps('User','inclobjclasses|exclobjclasses','inetorgperson|orclidxper  
son','userrole')
```

2.1.4.33 deleteAttributePropsInEntityConfig

Online command that deletes the attribute properties in an entity configuration.

Description

Deletes the attribute properties in an entity configuration.

Syntax

```
deleteAttributePropsInEntityConfig(name, propNames, appName)
```

Table 2–33 *deleteAttributePropsInEntityConfig*

Argument	Definition
<i>name</i>	Name of the attribute to be deleted.
<i>propNames</i>	List of property names separated by " ".
<i>appName</i>	Name of the Identity Directory Service.

Example

The following command deletes the attribute property, orgunit from the userrole.

```
deleteAttributePropsInEntityConfig('orgunit', 'labelname|validvalues', 'userrole')
```

2.1.5 Library Oracle Virtual Directory (libOVD) Commands

Use the WLST commands listed in [Table 2–34](#) to manage a libOVD configuration associated with a specific Oracle Platform Security Services (OPSS) context.

Table 2–34 *WLST libOVD Commands*

Use this command...	To...	Use with WLST...
addDNAttribute	Add an attribute to the DN attributes list for an existing adapter.	Online
activateLibOVDConfigChanges	Reload the libOVD configuration.	Online
addAttributeExclusionRule	Add a attribute exclusion rule.	Online
addAttributeRule	Add a new attribute mapping rule.	Online
addDomainExclusionRule	Add a domain exclusion rule.	Online
addDomainRule	Add a new domain mapping rule.	Online
addJoinRule	Add a join rule to an existing Join Adapter for a libOVD configuration.	Online
addLDAPHost	Add a new remote host to an existing LDAP adapter.	Online
addMappingContext	Create a new mapping context.	Online
addPlugin	Add a plug-in to an existing adapter or at the global level.	Online
addPluginParam	Add new parameter values to the existing adapter level plug-in or global plug-in.	Online
addToRequestControlExcludeList	Add a control to the Request Control Exclude List for an existing LDAP adapter configuration.	Online
addToRequestControlIncludeList	Add a control to the Request Control Include List for an existing LDAP adapter configuration.	Online
assignViewToAdapter	Assign the given view to an adapter.	Online
createJoinAdapter	Create a new Join Adapter for a libOVD configuration.	Online

Table 2–34 (Cont.) WLST libOVD Commands

Use this command...	To...	Use with WLST...
createLDAPAdapter	Create a new LDAP adapter for a libOVD configuration.	Online
createLDAPAdapterWithDefaultPlugins	Create a new LDAP adapter with default plug-ins based on the specified directory type.	Online
createView	Create a new view.	Online
deleteAdapter	Delete an existing adapter for a libOVD configuration.	Online
deleteAttributeExclusionRule	Delete a attribute exclusion rule.	Online
deleteAttributeRule	Delete a attribute mapping rule.	Online
deleteDomainExclusionRule	Delete a domain exclusion rule.	Online
deleteDomainRule	Delete a domain mapping rule.	Online
deleteMappingContext	Delete the specified mapping context.	Online
deleteView	Delete the specified view.	Online
getAdapterDetails	Display the details of an existing adapter for a libOVD configuration.	Online
listAdapters	List the name and type of all adapters that are configured for a libOVD configuration.	Online
listAllMappingContextIds	List all the mapping contexts.	Online
listAttributeRules	List all the attribute rules.	Online
listDomainRules	List all the domain rules.	Online
listViews	List all views	Online
modifyLDAPAdapter	Modify the existing LDAP adapter configuration.	Online
modifySocketOptions	Modify the socket options for an existing LDAP adapter configuration.	Online
removeAllRequestControlExcludeList	Remove all controls from the Request Control Exclude List for an existing LDAP adapter configuration.	Online
removeAllRequestControlIncludeList	Remove all controls from a Request Control Include List for an existing LDAP adapter configuration.	Online
removeDNAAttribute	Remove an attribute from the DN attributes list for an existing LDAP adapter configuration.	Online
removeFromRequestControlExcludeList	Remove a control from the Request Control Exclude List for an existing LDAP adapter configuration.	Online
removeFromRequestControlIncludeList	Removes a control from the Request Control Include List for an existing LDAP adapter configuration.	Online
removeJoinRule	Remove a join rule from a Join Adapter configured for a libOVD configuration.	Online
removeLDAPHost	Remove a remote host from an existing LDAP adapter configuration.	Online
removePlugin	Remove a plug-in from an existing adapter or at the global level.	Online
removePluginParam	Remove an existing parameter from a configured adapter level plug-in or global plug-in.	Online
replacePluginParam	Replace existing parameter values for an adapter level plug-in or global plug-in.	Online
unassignViewFromAdapter	Un-assign a view from an adapter.	Online
listSSLStoreType	List the type of SSL store in use for libOVD.	Online
enableKSSForSSL	Enable KSS for libOVD.	Online
enableJKSForSSL	Enable JKS for libOVD.	Online

Table 2–34 (Cont.) WLST libOVD Commands

Use this command...	To...	Use with WLST...
<code>createKeyStoreAndEnableJKSForSSL</code>	Enable JKS for libOVD.	Online
<code>importTrustedCertificateIntoSSLStore</code>	Import given trusted certificate into SSL store.	Online
<code>migrateAllTrustedCertificatesFromJKSToKSS</code>	Migrate all trusted certificates from JKS to KSS store.	Online
<code>migrateTrustedCertificatesFromJKSToKSS</code>	Migrate given trusted certificates from JKS to KSS store.	Online
<code>changeLDAPHostPort</code>	Change given LDAP host and port in an existing LDAP adapter configuration to the new host and port.	Online
<code>removeLDAPHostPort</code>	Remove a remote host and a port from an existing LDAP adapter configuration.	Online
<code>setReadOnlyForLDAPHost</code>	Set the given host and port to read-only/writable in an existing LDAP adapter configuration.	Online

2.1.5.1 addDNAttribute

Online command that adds an attribute to the DN Attributes List.

Description

Adds an attribute to the DN Attributes List for an existing adapter configured for the libOVD configuration associated with an OPSS context.

Syntax

```
addDNAttribute(adapterName, attributeName, [contextName])
```

Table 2–35 addDNAttribute Arguments

Argument	Definition
<code>adapterName</code>	Name of the adapter to be updated.
<code>attributeName</code>	Name of the new DN attribute to be added.
<code>contextName</code>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is <code>default</code> .

Example

The following example adds `memberof` attribute to `ldap1` adapter:

```
addDNAttribute(adapterName='ldap1', attributeName='memberof',
contextName='default')
```

2.1.5.2 activateLibOVDConfigChanges

Online command that reloads the libOVD configuration.

Description

Reloads the libOVD configuration associated with a specific OPSS context.

Syntax

```
activateLibOVDConfigChanges([contextName])
```

Table 2–36 *activateLibOVDConfigChanges Arguments*

Argument	Definition
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is default.

Example

The following command reloads the default libOVD configuration for a specified OPSS context:

```
activateLibOVDConfigChanges('default')
```

2.1.5.3 addAttributeExclusionRule

Online command that adds an attribute exclusion rule.

Description

Adds an attribute exclusion rule to the exclusion list.

Syntax

```
addAttributeExclusionRule(attribute, mappingContextId, [contextName])
```

Table 2–37 *addAttributeExclusionRule Arguments*

Argument	Definition
<i>attribute</i>	Name of the attribute to be added to the exclusion list.
<i>mappingContextId</i>	Name of the mapping context.
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is default.

Example

The following command add objectsid to the exclusion list:

```
addAttributeExclusionRule('objectsid', 'userrole')
```

2.1.5.4 addAttributeRule

Online command that adds a new attribute mapping rule.

Description

Adds a new attribute mapping rule to the libOVD configuration associated with a specific OPSS context..

Syntax

```
addAttributeRule(srcAttrs, srcObjectClass, srcAttrType, dstAttr, dstObjectClass, dstAttrType, mappingExpression, direction, mappingContextId, [contextName])
```

Table 2–38 *addAttributeRule Arguments*

Argument	Definition
<i>mappingContextId</i>	Name of the mapping context.

Table 2–38 (Cont.) addAttributeRule Arguments

Argument	Definition
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is default.

Example

The following command creates a mapping rule for the libOVD configuration. Here, the `lastname` is mapped to the `cn`.

```
addAttributeRule('lastname', '', '', 'sn', '', '', 'Inbound', 'userrole')
```

2.1.5.5 addDomainExclusionRule

Online command that adds a domain exclusion rule.

Description

Adds a domain exclusion rule to the exclusion list.

Syntax

```
addDomainExclusionRule(domain, mappingContextId, [contextName])
```

Table 2–39 addDomainExclusionRule Arguments

Argument	Definition
<i>domain</i>	Distinguished name (DN) of the attribute to be added to the exclusion list.
<i>mappingContextId</i>	Name of the mapping context.
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Example

The following command adds `cn=group,dc=oracle,dc=com` to the exclusion list:

```
addDomainExclusionRule('cn=group,dc=oracle,dc=com', 'userrole')
```

2.1.5.6 addDomainRule

Online command that adds a new domain mapping rule.

Description

Adds a new domain mapping rule.

Syntax

```
addDomainRule(srcDomain, destDomain, domainConstructRule, mappingContextId, [contextName])
```

Table 2–40 addDomainRule Arguments

Argument	Definition
<i>srcDomain</i>	Source domain.

Table 2–40 (Cont.) addDomainRule Arguments

Argument	Definition
<i>destDomain</i>	Destination domain
<i>domainConstructRule</i>	Name of the attribute to be added to the exclusion list.
<i>mappingContextId</i>	Name of the mapping context.
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is default.

Example

The following command creates a domain mapping rule:

```
addDomainRule('dc=oracle,dc=com', 'dc=oracle,dc=com', '', 'defaultContext',
'default')
```

2.1.5.7 addJoinRule

Online command that adds a join rule to a Join Adapter.

Description

Adds a join rule to an existing Join Adapter for the libOVD configuration associated with the specified OPSS context.

Syntax

```
addJoinRule(adapterName, secondary, condition, [joinerType], [contextName])
```

Table 2–41 addJoinRule Arguments

Argument	Definition
<i>adapterName</i>	Name of the Join Adapter to be modified.
<i>secondary</i>	Name of the adapter to join to.
<i>condition</i>	The attribute(s) to join on.
<i>joinerType</i>	Optional. Defines the type of Join. Values can be Simple (default), Conditional, OneToMany, or Shadow.
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is default.

Examples

The following commands create different join rules for an existing Join adapter:

```
addJoinRule('join1','secondaryldap','cn=cn', 'Simple', 'default')
```

```
addJoinRule('join1','secondaryldap','cn=cn', 'Conditional', 'default')
```

```
addJoinRule(adapterName='join1', secondary='LDAP3', condition='uid=cn',
JoinerType='OneToMany')
```

```
addJoinRule(adapterName='join1', secondary='LDAP2',condition='uid=cn',
contextName='myContext')
```

2.1.5.8 addLDAPHost

Online command that adds a new remote host.

Description

Adds a new remote host (host and port) to an existing LDAP adapter. By default, the new host is configured in Read-Write mode with percentage set to 100.

Syntax

```
addLDAPHost(adapterName, host, port, [contextName])
```

Table 2–42 addLDAPHost Arguments

Argument	Definition
<i>adapterName</i>	Name of the Join Adapter to be modified.
<i>host</i>	Remote LDAP host to which the LDAP adapter will communicate.
<i>port</i>	Remote LDAP host port.
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Example

The following commands add a host and a port to an existing LDAP adapter:

```
addLDAPHost(adapterName='ldap1', host='myhost.example.com', port=389)
```

```
addLDAPHost('ldap1', 'myhost.example.com', '389', 'myContext')
```

2.1.5.9 addMappingContext

Online command that creates a new mapping context.

Description

Creates a new mapping context for the libOVD configuration associated with the specified OPSS context.

Syntax

```
addMappingContext(mappingContextId, [contextName])
```

Table 2–43 addMappingContext Arguments

Argument	Definition
<i>mappingContextId</i>	Name of the mapping context.
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Example

The following command creates a mapping context for the libOVD configuration:

```
addMappingContext('defaultContext', 'context')
```


2.1.5.10 addPlugin

Online command that adds a plug-in to an existing adapter or at the global level.

Description

Adds a plug-in to an existing adapter or at the global level. The "i"th key corresponds to "i"th value. The plug-in is added to default chain.

Syntax

```
addPlugin(pluginName, pluginClass, paramKeys, paramValues, [adapterName],
[contextName])
```

Table 2–44 addPlugin Arguments

Argument	Definition
<i>pluginName</i>	Name of the plug-in to be created.
<i>pluginClass</i>	Class of the plug-in.
<i>paramKeys</i>	Init Param Keys separated by " ".
<i>paramValues</i>	Init Param Values separated by " ".
<i>adapterName</i>	Optional. Name of the adapter to be modified. If not specified, the plug-in is added at the global level.
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Examples

The following commands add a plug-in to an existing adapter:

```
wls:/mydomain/serverConfig> addPlugin(adapterName='ldap1',
pluginName='VirtualAttr',pluginClass='oracle.ods.virtualization.engine.chain.plugins.virtualattr.VirtualAttributePlugin', paramKeys='AddAttribute | MatchFilter | ContainerDN', paramValues='cn=%uid% | objectclass=person | dc=oracle,dc=com')
```

```
wls:/mydomain/serverConfig>
addPlugin(pluginName='VirtualAttr',pluginClass='oracle.ods.virtualization.engine.c
hain.plugins.virtualattr.VirtualAttributePlugin', paramKeys='AddAttribute |
MatchFilter | ContainerDN', paramValues='cn=%uid% | objectclass=person |
dc=oracle,dc=com')
```

```
wls:/mydomain/serverConfig>
addPlugin(pluginName='DMSMetrics',pluginClass='oracle.ods.virtualization.engine.ch
ain.plugins.DMSMetrics.MonitorPerformance',
paramKeys='None',paramValues='None',adapterName='ldap1',contextName='default')
```

2.1.5.11 addPluginParam

Online command that adds new parameter values to the existing adapter level plug-in or global plug-in.

Description

Adds new parameter values to the existing adapter level plug-in or the global plug-in. If the parameter already exists, the new value is added to the existing set of values. The "i"th key corresponds to "i"th value.

Syntax

```
addPluginParam(pluginName, paramKeys, paramValues, [adapterName], [contextName])
```

Table 2–45 addPluginParam Arguments

Argument	Definition
<i>pluginName</i>	Name of the plug-in to be modified.
<i>paramKeys</i>	Init Param Keys separated by " ".
<i>paramValues</i>	Init Param Values separated by " ".
<i>adapterName</i>	Optional Name of the adapter to be modified. If not specified, the global plug-in is modified.
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Examples

The following commands add a new plug-in parameter for an existing plug-in:

```
wls:/mydomain/serverConfig> addPluginParam(adapterName='ldap1',
pluginName='VirtualAttr', paramKeys='ReplaceAttribute | MatchFilter',
paramValues='cn=%uid% | objectclass=person')
```

```
wls:/mydomain/serverConfig> addPluginParam(pluginName='VirtualAttr',
paramKeys='ReplaceAttribute | MatchFilter', par)
```

2.1.5.12 addToRequestControlExcludeList

Online command that adds a control to the Request Control Exclude List.

Description

Adds a control to the Request Control Exclude List for an existing LDAP adapter configuration.

Syntax

```
addToRequestControlExcludeList(adapterName, control, [contextName])
```

Table 2–46 addToRequestControlExcludeList Arguments

Argument	Definition
<i>adapterName</i>	Name of the LDAP adapter to be modified.
<i>control</i>	LDAP control object identifier (OID).
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Example

The following command adds 2.16.840.1.113894.1.8.31 control to ldap1 adapter's Request Control Exclude List:

```
addToRequestControlExcludeList(adapterName='ldap1',
control='2.16.840.1.113894.1.8.31', contextName='default')
```

2.1.5.13 addToRequestControlIncludeList

Online command that adds a control to the Request Control Include List.

Description

Adds a control to the Request Control Include List for an existing LDAP adapter configuration.

Syntax

```
addToRequestControlIncludeList(adapterName, control, [contextName])
```

Table 2–47 *addToRequestControlIncludeList Arguments*

Argument	Definition
<i>adapterName</i>	Name of the LDAP adapter to be modified.
<i>control</i>	LDAP control object identifier (OID).
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Example

The following command adds 2.16.840.1.113894.1.8.31 control to ldap1 adapter's Request Control Include List:

```
addToRequestControlIncludeList(adapterName='ldap1',
control='2.16.840.1.113894.1.8.31', contextName='default')
```

2.1.5.14 assignViewToAdapter

Online command that assigns a view to an LDAP adapter.

Description

Assigns a view to an LDAP adapter in the libOVD configuration associated with an OPSS context.

Syntax

```
assignViewToAdapter(viewName, adapterName, [contextName])
```

Table 2–48 *assignViewToAdapter Arguments*

Argument	Definition
<i>viewName</i>	Name of the view.
<i>adapterName</i>	Name of the LDAP adapter.
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Example

The following command assigns userView to ldap1 adapter:

```
assignViewToAdapter('userView','ldap1', 'default')
```

2.1.5.15 createJoinAdapter

Online command that creates a new join adapter.

Description

Creates a new join adapter for the libOVD configuration associated with an OPSS context.

Syntax

```
createJoinAdapter(adapterName, root, primaryAdapter, [bindAdapter],[contextName])
```

Table 2–49 createJoinAdapter Arguments

Argument	Definition
<i>adapterName</i>	Name of the Join Adapter to be created.
<i>primaryAdapter</i>	Specifies the identifier of the primary adapter, which is the adapter searched first in the join operation.
<i>root</i>	root
<i>bindAdapter</i>	Specifies identifier of the bind adapter(s), which are the adapter(s) whose proxy account is used to bind in the LDAP operation. By default, <i>primaryAdapter</i> is set as <i>bindAdapter</i> .
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Examples

The following commands create a Join adapter:

```
createJoinAdapter('join1','dc=join','primaryldap','myldap', 'myContext')
```

```
createJoinAdapter(adapterName='join1', root='dc=join', primaryAdapter='myldap')
```

2.1.5.16 createLDAPAdapter

Online command that creates a new LDAP adapter.

Description

Creates a new LDAP adapter for the libOVD configuration associated with an OPSS context.

Syntax

```
createLDAPAdapter(adapterName, root, host, port, remoteBase, [isSecure], [bindDN], [bindPasswd], [passCred], [contextName])
```

Table 2–50 createLDAPAdapter Arguments

Argument	Definition
<i>adapterName</i>	Name of the LDAP adapter to be created.
<i>root</i>	Virtual Namespace of the LDAP adapter.
<i>host</i>	Remote LDAP host with which the LDAP adapter will communicate.
<i>port</i>	Remote LDAP host port number.

Table 2–50 (Cont.) createLDAPAdapter Arguments

Argument	Definition
<i>remoteBase</i>	Location in the remote DIT to which root corresponds.
<i>isSecure</i>	Optional. Boolean value that enables secure SSL/TLS connections to the remote hosts when set to true. The default is false.
<i>bindDN</i>	Optional. Proxy BindDN used to communicate with remote host. Default is "".
<i>bindPasswd</i>	Optional. Proxy BindPasswd used to communicate with the remote host. Default is "".
<i>passCred</i>	Optional. Controls the credentials, if any, the libOVD configuration will pass to the back-end (remote host) LDAP server. Values can be Always (default), None, or BindOnly.
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Examples

The following commands create an LDAP adapter:

```
createLDAPAdapter("testLDAP", "dc=us,dc=oracle,dc=com", "myhost.example.com",
3060, "dc=uk,dc=oid", false, "cn=testuser", "welcome1", "Always", "myContext"
```

```
createLDAPAdapter(adapterName='ldap1', root='dc=com', host='myhost.example.com',
port=5566, remoteBase='dc=oid')
```

2.1.5.17 createLDAPAdapterWithDefaultPlugins

Online command that creates a new LDAP adapter.

Description

Creates a new LDAP adapter with default plug-ins based on the directory type for the libOVD configuration associated with an OPSS context.

Syntax

```
createLDAPAdapterWithDefaultPlugins(adapterName, directoryType, root, host, port,
remoteBase, [isSecure], [bindDN], [bindPasswd], [contextName])
```

Table 2–51 createLDAPAdapterWithDefaultPlugins Arguments

Argument	Definition
<i>adapterName</i>	Name of the LDAP adapter to be created.
<i>directoryType</i>	Directory type. The value can be one of the following directories: <ul style="list-style-type: none"> ▪ OID - Oracle Internet Directory ▪ OUD - Oracle Unified Directory ▪ SUNONE- Sun Java System Directory Server ▪ OVD - Oracle Virtual Directory ▪ ACTIVE_DIRECTORY - Microsoft Active Directory ▪ EDIRECTORY - Novell eDirectory ▪ OPEN_LDAP - Open LDAP ▪ WLS_OVD - Oracle WebLogic Server OVD ▪ TIVOLI - IBM Tivoli Directory Server

Table 2–51 (Cont.) createLDAPAdapterWithDefaultPlugins Arguments

Argument	Definition
<i>root</i>	Virtual Namespace of the LDAP adapter.
<i>host</i>	Remote LDAP host to which LDAP adapter should communicate.
<i>port</i>	Remote host port.
<i>remoteBase</i>	Location in the remote DIT to which the root corresponds.
<i>isSecure</i>	Optional. Boolean value that enables secure SSL/TLS connections to the remote hosts when set to true. The Default is false.
<i>bindDN</i>	Optional. Proxy BindDN used to communicate with remote host. Default is "".
<i>bindPasswd</i>	Optional. Proxy BindPasswd used to communicate with the remote host. Default is "".
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Examples

The following commands create an LDAP adapter with default plug-ins based on the directory type:

```
wls:/mydomain/serverConfig> createLDAPAdapterWithDefaultPlugins("testLDAP", "OID",
"dc=us,dc=oracle,dc=com", "myhost.example.domain.com", 3060, "dc=uk,dc=oid",
false, "cn=testuser", "welcome1", "myContext")
```

```
wls:/mydomain/serverConfig>
createLDAPAdapterWithDefaultPlugins(adapterName='ldap1', directoryType="OID",
root='dc=com', host='myhost.example.domain.com', port=5566,
remoteBase='dc=oid', bindDN="cn=testuser", bindPasswd="welcome1", contextName='default')
t')
```

2.1.5.18 createView

Online command that creates a new view.

Description

Creates a new view for the libOVD configuration associated with an OPSS context.

Syntax

```
createView(viewName, [contextName])
```

Table 2–52 createView Arguments

Argument	Definition
<i>viewName</i>	Name of the new view.
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Example

The following command create a view named, `userView`:

```
createView('userView', 'default')
```

2.1.5.19 deleteAdapter

Online command that deletes an existing adapter.

Description

Deletes an existing adapter for the libOVD configuration associated with an OPSS context.

Syntax

```
deleteAdapter(adapterName, [contextName])
```

Table 2–53 deleteAdapter Arguments

Argument	Definition
<i>adapterName</i>	Name of the Join Adapter to be deleted.
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Example

The following command deletes join1 adapter:

```
deleteAdapter(adapterName='join1') deleteAdapter('join1', 'default')
```

2.1.5.20 deleteAttributeExclusionRule

Online command that deletes an attribute exclusion rule.

Description

Deletes an attribute exclusion rule for the libOVD configuration associated with an OPSS context.

Syntax

```
deleteAttributeExclusionRule(attribute, mappingContextId, [contextName])
```

Table 2–54 deleteAttributeExclusionRule Arguments

Argument	Definition
<i>attribute</i>	Name of the attribute to be removed from the exclusion list.
<i>mappingContextId</i>	Name of the mapping context.
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Example

The following command deletes the objectsid attribute exclusion rule for the associated libOVD configuration:

```
deleteAttributeExclusionRule('objectsid', 'userrole')
```

2.1.5.21 deleteAttributeRule

Online command that delete an attribute mapping rule.

Description

Deletes an attribute mapping rule for the libOVD configuration associated with an OPSS context.

Syntax

```
deleteAttributeRule(srcAttrs, dstAttr, mappingContextId, [contextName])
```

Table 2–55 *deleteEntityRelation Arguments*

Argument	Definition
<i>srcAttrs</i>	Source attributes.
<i>dstAttr</i>	Destination attribute.
<i>mappingContextId</i>	Name of the mapping context.
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Example

The following command deletes the lastname attribute mapping rule from cn:

```
deleteAttributeRule('lastname','sn')
```

2.1.5.22 deleteDomainExclusionRule

Online command that deletes a domain exclusion rule.

Description

Deletes a domain exclusion rule for the libOVD configuration associated with an OPSS context.

Syntax

```
deleteDomainExclusionRule(domain, mappingContextId, [contextName])
```

Table 2–56 *deleteEntityRelation Arguments*

Argument	Definition
<i>domain</i>	Distinguished Name of the container to be removed from the exclusion list.
<i>mappingContextId</i>	Name of the mapping context.
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Example

The following command deletes 'cn=group,dc=oracle,dc=com' domain exclusion rule:

```
deleteDomainExclusionRule('cn=group,dc=oracle,dc=com')
```

2.1.5.23 deleteDomainRule

Online command that deletes a domain mapping rule.

Description

Deletes a domain mapping rule for the libOVD configuration associated with an OPSS context.

Syntax

```
deleteDomainRule(srcDomain, destDomain, mappingContextId, [contextName])
```

Table 2–57 *deleteDomainRule Arguments*

Argument	Definition
<i>srcDomain</i>	Source domain.
<i>destDomain</i>	Destination domain.
<i>mappingContextId</i>	Name of the mapping context.
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Example

The following command deletes 'dc=oracle,dc=com' domain mapping rule:

```
deleteDomainRule('dc=oracle,dc=com', 'dc=oracle,dc=com', 'userrole')
```

2.1.5.24 deleteDomainExclusionRule

Deletes a domain exclusion rule.

Description

Deletes a domain exclusion rule for the libOVD configuration associated with an OPSS context.

Syntax

```
deleteDomainExclusionRule(domain, mappingContextId, [contextName])
```

Table 2–58 *deleteDomainExclusionRule Attributes*

Argument	Definition
<i>domain</i>	Distinguished Name of the container to be removed from the exclusion list.
<i>mappingContextId</i>	Name of the mapping context.
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default value is default.

Example

```
deleteDomainExclusionRule('cn=group,dc=oracle,dc=com', 'userrole')
```

2.1.5.25 deleteMappingContext

Online command that deletes a mapping context.

Description

Deletes the specified mapping context for the libOVD configuration associated with an OPSS context.

Syntax

```
deleteMappingContext(mappingContextId, [contextName])
```

Table 2–59 deleteMappingContext Arguments

Argument	Definition
<i>mappingContextId</i>	Name of the mapping context.
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Example

The following command deletes a mapping context for a libOVD configuration:

```
deleteMappingContext('defaultContext', 'context')
```

2.1.5.26 deleteView

Online command that deletes a view.

Description

Deletes a view for the libOVD configuration associated with an OPSS context.

Syntax

```
createView(viewName, [contextName])
```

Table 2–60 createView Arguments

Argument	Definition
<i>viewName</i>	Name of the view to delete.
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Example

The following command deletes `userView` view:

```
deleteView('userView', 'default')
```

2.1.5.27 getAdapterDetails

Online command that displays the details of an existing adapter.

Description

Displays the details of an existing adapter configured for the libOVD configuration associated with an OPSS context.

Syntax

```
getAdapterDetails(adapterName, [contextName])
```

Table 2–61 getAdapterDetails Arguments

Argument	Definition
<i>adapterName</i>	Name of the adapter that contains the details to be displayed.

Table 2–61 (Cont.) *getAdapterDetails* Arguments

Argument	Definition
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Examples

The following commands display the details of `ldap1` and `join1` adapter respectively:

```
getAdapterDetails(adapterName='ldap1', contextName='default')
```

```
getAdapterDetails(adapterName='join1')
```

2.1.5.28 listAdapters

Online command that lists the name and type of all adapters.

Description

Lists the name and type of all adapters that are configured for the libOVD configuration associated with an OPSS context.

Syntax

```
listAdapters([contextName])
```

Table 2–62 *listAdapters* Arguments

Argument	Definition
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Example

The following command displays the name and type of all adapters configured for a libOVD configuration:

```
listAdapters()
```

```
listAdapters(contextName='myContext')
```

2.1.5.29 listAllMappingContextIds

Online command that lists all mapping contexts.

Description

Lists the mapping contexts associated with the specified OPSS context.

Syntax

```
listAllMappingContextIds([contextName])
```

Table 2–63 *listAllMappingContextIds* Arguments

Argument	Definition
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Example

The following command lists all the mapping contexts:

```
listAllMappingContextIds('default')
```

2.1.5.30 listAttributeRules

Online command that lists all the attribute rules.

Description

List all the attribute rules in the format *SOURCE_ATTRIBUTE:DESTINATION_ATTRIBUTE:DIRECTION*.

Syntax

```
listAttributeRules(mappingContextId, [contextName])
```

Table 2–64 listAttributeRules Arguments

Argument	Definition
<i>mappingContextId</i>	Name of the mapping context.
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Example

The following command lists all the attribute rules:

```
listAttributeRules('defaultContext','default')
```

2.1.5.31 listDomainRules

Online command that lists all domain rules.

Description

Lists all the domain rules in the format of *SOURCE_DOMAIN:DESTINATION_DOMAIN*.

Syntax

```
listDomainRules(mappingContextId, [contextName])
```

Table 2–65 listDomainRules Arguments

Argument	Definition
<i>mappingContextId</i>	Name of the mapping context.
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Example

The following command lists all domain rules:

```
listDomainRules('defaultContext','default')
```

2.1.5.32 listViews

Online command that lists all views

Description

Lists all views for a libOVD configuration associated with an OPSS context.

Syntax

```
listViews([contextName])
```

Table 2–66 *listViews Arguments*

Argument	Definition
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Example

The following command lists all views:

```
listViews('default')
```

2.1.5.33 modifyLDAPAdapter

Modifies parameters in an LDAP adapter.

Description

Modifies the following LDAP adapter parameters:

- Remote Base
- Root
- Secure
- BindDN
- BindPassword
- PassCredentials
- MaxPoolSize
- MaxPoolChecks
- MaxPoolWait
- InitialPoolSize
- PoolCleanupInterval
- MaxPoolConnectionIdleTime
- Active
- PingProtocol
- PingBindDN
- PingBindPassword
- PageSize
- HeartBeatInterval
- OperationTimeout
- SearchCountLimit
- Visible
- Critical
- InclusionFilter
- ExclusionFilter

- DNPattern
- RequestControlAllowServerSupported
- MaxPoolConnectionReuseTime
- ConnectTimeout
- PoolConnectionReclaimTime

Syntax

```
modifyLDAPAdapter(adapterName, attribute, value, [contextName])
```

Table 2–67 *modifyLDAPAdapter Arguments*

Argument	Definition
<i>adapterName</i>	Name of the LDAP adapter to be modified.
<i>attribute</i>	Name of the attribute to be modified.
<i>value</i>	New value for the attribute.
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Examples

The following examples illustrate how to set attributes in ldap1:

```
modifyLDAPAdapter(adapterName='ldap1', attribute='Root', value='dc=us, dc=oracle,
dc=com', contextName='mydefault')
```

```
modifyLDAPAdapter(adapterName='ldap1', attribute='RemoteBase', value='dc=org',
contextName='mydefault')
```

```
modifyLDAPAdapter(adapterName='ldap1', attribute='PassCredentials',
value='BindOnly', contextName='mydefault')
```

```
modifyLDAPAdapter(adapterName='ldap1', attribute='BindDN',
value='cn=proxyuser,dc=com', contextName='mydefault')
```

```
modifyLDAPAdapter(adapterName='ldap1', attribute='BindPassword',
value='testwelcome123', contextName='mydefault')
```

```
modifyLDAPAdapter(adapterName='ldap1', attribute='Secure', value=true,
contextName='mydefault')
```

```
modifyLDAPAdapter(adapterName='ldap1', attribute='MaxPoolSize', value=500,
contextName='mydefault')
```

```
modifyLDAPAdapter(adapterName='ldap1', attribute='MaxPoolChecks', value=10,
contextName='mydefault')
```

```
modifyLDAPAdapter(adapterName='ldap1', attribute='MaxPoolWait', value=120000,
contextName='mydefault') [value is in milliseconds]
```

```
modifyLDAPAdapter(adapterName='ldap1', attribute='InitialPoolSize', value=10,
contextName='mydefault')
```

```
modifyLDAPAdapter(adapterName='ldap1', attribute='PoolCleanupInterval', value=300,
contextName='mydefault') [value is in seconds]
```

```
modifyLDAPAdapter(adapterName='ldap1', attribute='MaxPoolConnectionIdleTime',
value=300, contextName='mydefault') [value is in seconds]

modifyLDAPAdapter(adapterName='ldap1', attribute='Active', value=false,
contextName='mydefault')

modifyLDAPAdapter(adapterName='ldap1', attribute='PingProtocol', value='LDAP',
contextName='mydefault')

modifyLDAPAdapter(adapterName='ldap1', attribute='PingBindDN',
value='cn=proxyuser', contextName='mydefault')

modifyLDAPAdapter(adapterName='ldap1', attribute='PingBindPassword',
value='welcome1', contextName='mydefault')

modifyLDAPAdapter(adapterName='ldap1', attribute='PageSize', value=500,
contextName='mydefault')

modifyLDAPAdapter(adapterName='ldap1', attribute='HeartBeatInterval', value=120,
contextName='mydefault') [value is in seconds]

modifyLDAPAdapter(adapterName='ldap1', attribute='OperationTimeout', value=120000,
contextName='mydefault') [value is in milliseconds]

modifyLDAPAdapter(adapterName='ldap1', attribute='SearchCountLimit', value=100,
contextName='mydefault')

modifyLDAPAdapter(adapterName='ldap1', attribute='Visible', value='Yes',
contextName='mydefault')

modifyLDAPAdapter(adapterName='ldap1', attribute='Critical', value='false',
contextName='mydefault')

modifyLDAPAdapter(adapterName='ldap1', attribute='InclusionFilter',
value='objectclass=inetorgperson#base', contextName='mydefault')

modifyLDAPAdapter(adapterName='ldap1', attribute='ExclusionFilter',
value='uniquemember=*#base', contextName='mydefault')

modifyLDAPAdapter(adapterName='ldap1', attribute='DNPattern',
value='(.*cn=[a-z0-9]*$', contextName='mydefault')

modifyLDAPAdapter(adapterName='ldap1',
attribute='RequestControlAllowServerSupported', value=false,
contextName='mydefault')

modifyLDAPAdapter(adapterName='ldap1', attribute='MaxPoolConnectionReuseTime',
value=3600, contextName='mydefault') [value is in seconds]

modifyLDAPAdapter(adapterName='ldap1', attribute='ConnectTimeout', value=10000,
contextName='mydefault') [value is in milli seconds]

modifyLDAPAdapter(adapterName='ldap1', attribute='PoolConnectionReclaimTime',
value=180, contextName='mydefault')
```

2.1.5.34 modifySocketOptions

Online command that modifies socket options.

Description

Modifies socket options for an existing LDAP adapter configuration.

Syntax

```
modifySocketOptions(adapterName, reuseAddress, keepAlive, tcpNoDelay, readTimeout,
[contextName])
```

Table 2–68 *modifySocketOptions Arguments*

Argument	Definition
<i>adapterName</i>	Name of the LDAP adapter to be modified.
<i>reuseAddress</i>	Value of <i>reuseAddress</i> .
<i>keepAlive</i>	Value of <i>keepAlive</i> .
<i>tcpNoDelay</i>	Value of <i>tcpNoDelay</i> .
<i>readTimeout</i>	Value of <i>readTimeout</i> in seconds.
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Example

The following command modifies the socket option for ldap1 adapter:

```
modifySocketOptions(adapterName='ldap1', reuseAddress=true, keepAlive=true,
tcpNoDelay=true, readTimeout=180000, contextName='default')
```

2.1.5.35 removeAllRequestControlExcludeList

Online command that removes all controls from the Request Control Exclude List.

Description

Removes all controls from the Request Control Exclude List for an existing LDAP adapter configuration.

Syntax

```
removeAllRequestControlExcludeList(adapterName, [contextName])
```

Table 2–69 *removeAllRequestControlExcludeList Arguments*

Argument	Definition
<i>adapterName</i>	Name of the adapter to be updated.
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Example

The following command removes all controls from ldap1 adapter's Request Control Exclude List:

```
removeAllRequestControlExcludeList(adapterName='ldap1', contextName='default')
```


2.1.5.36 `removeAllRequestControlIncludeList`

Online command that removes all controls from the Request Control Include List.

Description

Removes all controls from the Request Control Include List for an existing LDAP adapter configuration.

Syntax

```
removeAllRequestControlIncludeList(adapterName, [contextName])
```

Table 2–70 *removeAllRequestControlIncludeList Arguments*

Argument	Definition
<i>adapterName</i>	Name of the adapter to be updated.
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Example

The following command removes all controls from `ldap1` adapter's Request Control Include List:

```
removeAllRequestControlIncludeList(adapterName='ldap1', contextName='default')
```

2.1.5.37 `removeFromRequestControlExcludeList`

Online command that removes a control from the Request Control Exclude List.

Description

Removes a control from the Request Control Exclude List for an existing LDAP adapter configuration.

Syntax

```
removeFromRequestControlExcludeList(adapterName, control, [contextName])
```

Table 2–71 *removeFromRequestControlExcludeList Arguments*

Argument	Definition
<i>adapterName</i>	Name of the LDAP adapter to be modified.
<i>control</i>	LDAP control object identifier (OID).
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Example

The following command removes `2.16.840.1.113894.1.8.31` control from `ldap1` adapter's Request Control Exclude List:

```
removeFromRequestControlExcludeList(adapterName='ldap1',
control='2.16.840.1.113894.1.8.31', contextName='default')
```

2.1.5.38 removeDNAttribute

Online command that removes a attribute from the DN Attributes List.

Description

Removes a attribute from the DN Attributes List for an existing adapter that is configured for the libOVD associated with an OPSS context.

Syntax

```
removeDNAttribute(adapterName attributeName, [contextName])
```

Table 2–72 *removeDNAttribute Arguments*

Argument	Definition
<i>adapterName</i>	Name of the adapter to be updated.
<i>attributeName</i>	Name of the new DN attribute to be removed.
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Example

The following command removes `memberof` attribute from `ldap1` adapter's attribute list:

```
removeDNAttribute(adapterName='ldap1', attributeName='memberof',
contextName='default')
```

2.1.5.39 removeFromRequestControlIncludeList

Online command that removes a control from the Request Control Include List.

Description

Removes a control from the Request Control Include List for an existing LDAP adapter configuration.

Syntax

```
removeFromRequestControlIncludeList(adapterName, control, [contextName])
```

Table 2–73 *removeFromRequestControlIncludeList Arguments*

Argument	Definition
<i>adapterName</i>	Name of the LDAP adapter to be modified.
<i>control</i>	LDAP control object identifier (OID).
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Example

The following command removes `2.16.840.1.113894.1.8.31` control from `ldap1` adapter's Request Control Include List:

```
removeFromRequestControlIncludeList(adapterName='ldap1',
control='2.16.840.1.113894.1.8.31', contextName='default')
```

2.1.5.40 removeJoinRule

Online command that removes a join rule from a Join Adapter.

Description

Removes a join rule from a Join Adapter configured for the libOVD configuration associated with the specified OPSS context.

Syntax

```
removeJoinRule(adapterName, secondary, [contextName])
```

Table 2–74 *removeJoinRule Arguments*

Argument	Definition
<i>adapterName</i>	Name of the Join Adapter to be modified.
<i>secondary</i>	The join rules corresponding to this secondary adapter are removed from the Join Adapter.
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Examples

The following command removes 2.16.840.1.113894.1.8.31 control from ldap1 adapter's Request Control Include List:

```
removeJoinRule('join1', 'secondaryldap1', 'default')
```

```
removeJoinRule(adapterName='join1', secondary='LDAP3')
```

2.1.5.41 removeLDAPHost

Online command that removes a remote host from an existing LDAP adapter.

Description

Removes a remote host (host:port) from an existing LDAP adapter.

Syntax

```
removeLDAPHost(adapterName, host, [contextName])
```

Table 2–75 *removeLDAPHost Arguments*

Argument	Definition
<i>adapterName</i>	Name of the LDAP adapter to be modified.
<i>host</i>	Location of a remote LDAP host with which the LDAP adapter will communicate.
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Example

The following command removes the host and port from ldap1 adapter:

```
removeLDAPHost(adapterName='ldap1', host='myhost.example.com')
```

```
removeLDAPHost('ldap1', 'myhost.example.com', 'myContext')
```

2.1.5.42 removePlugin

Online command that removes a plug-in from an existing adapter.

Description

Removes a plug-in from an existing adapter or at the global level.

Syntax

```
removePlugin(pluginName, [adapterName], [contextName])
```

Table 2–76 *removePlugin Arguments*

Argument	Definition
<i>pluginName</i>	Name of the plug-in to be removed.
<i>adapterName</i>	Optional. Name of the adapter to be modified. If not specified, the global plug-in is removed.
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Example

The following commands remove VirtualAttr plug-in from ldap1 adapter:

```
removePlugin(adapterName='ldap1', pluginName='VirtualAttr')
```

```
removePlugin(pluginName='VirtualAttr')
```

2.1.5.43 removePluginParam

Online command that removes an existing parameter from a configured adapter level plug-in.

Description

Removes an existing parameter from a configured adapter level plug-in or a global plug-in. This command removes all values of a particular parameter from the plug-in.

Syntax

```
removePluginParam(pluginName, paramKey, [adapterName], [contextName])
```

Table 2–77 *removePluginParam Arguments*

Argument	Definition
<i>pluginName</i>	Name of the plug-in to be modified.
<i>paramKey</i>	Parameter to be removed.
<i>adapterName</i>	Optional. Name of the adapter to be modified. If not specified, the global plug-in is modified.
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Example

The following commands remove the plug-in parameter `ReplaceAttribute` from `VirtualAttr` plug-in:

```
removePluginParam(adapterName='ldap1', pluginName='VirtualAttr',
paramKey='ReplaceAttribute')

removePluginParam(pluginName='VirtualAttr', paramKey='ReplaceAttribute')
```

2.1.5.44 replacePluginParam

Online command that replaces parameter values for a plug-in.

Description

Replaces existing parameter values for the specified adapter level plug-in or global plug-in.

Syntax

```
replacePluginParam(pluginName, paramName, paramValues,
[adapterName,][contextName])
```

Table 2–78 *replacePluginParam Arguments*

Argument	Description
<i>pluginName</i>	Name of the plug-in to be modified.
<i>paramName</i>	Name of the parameter to be replaced.
<i>paramValues</i>	New values of the parameter. For more than one new value, separate each new parameter value are by a " ".
<i>adapterName</i>	Optional. Name of the adapter to be modified. If not specified, the global plug-in is modified.
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Examples

The following commands replace the parameter values for the associated plug-in for an adapter:

```
replacePluginParam(adapterName='ldap1', pluginName='VirtualAttr',
paramName='ReplaceAttribute', paramValues='cn=%uid%')

replacePluginParam(adapterName='ldap1', pluginName='UserManagement',
paramName='mapAttribute', paramValues='orclguid=objectGuid | uniquemember=member')
```

2.1.5.45 unassignViewFromAdapter

Online command that unassigns a view from an adapter.

Description

Unassigns a view from an LDAP adapter configuration.

Syntax

```
unassignViewFromAdapter(viewName, adapterName, [contextName])
```

Table 2–79 *unassignViewFromAdapter Arguments*

Argument	Definition
<i>viewName</i>	Name of the view.
<i>adapterName</i>	Name of the LDAP adapter.
<i>contextName</i>	Optional. Name of the OPSS context with which the libOVD configuration is associated. Default is "default".

Example

The following command unassigns `userView` associated with `ldap1` adapter:

```
unassignViewFromAdapter('userView','ldap1', 'default')
```

2.1.5.46 listSSLStoreType

Online command that lists the type of SSL store in use.

Description

This command lists the type of SSL store in use for libOVD (JKS or KSS).

Syntax

```
listSSLStoreType(contextName=[contextName])
```

Table 2–80 *listSSLStoreType Arguments*

Argument	Definition
<i>contextName</i>	Name of the OPSS context with which libOVD configuration is associated. The default value is <code>default</code> .

Example

This following command list the SSL store types in use:

```
listSSLStoreType(contextName='default')
```

2.1.5.47 enableKSSForSSL

Online command to enable KSS for libOVD.

Description

This command enables KSS for SSL, and disables JKS if it was enabled before. For more information about KSS, see *Oracle® Fusion Middleware Securing Applications with Oracle Platform Security Services*.

Syntax

```
enableKSSForSSL(contextName=[contextName])
```

Table 2–81 *enableKSSForSSL Arguments*

Argument	Definition
<i>contextName</i>	Optional. Name of the OPSS context with which libOVD configuration is associated. The default value is <code>default</code> .

Example

The following command enables KSS for SSL:

```
enableKSSForSSL(contextName='default')
```

2.1.5.48 enableJKSForSSL

Online command to enable JKS for libOVD.

Description

This command enables JKS for SSL, and disables KSS if it was enabled before. The command assumes that the libOVD adapters.jks file exists.

Syntax

```
enableJKSForSSL(contextName=[contextName])
```

Table 2–82 *enableJKSForSSL Arguments*

Argument	Definition
contextName	Optional. Name of the OPSS context with which libOVD configuration is associated. The default value is default.

Example

The following command enables JKS for SSL:

```
enableJKSForSSL(contextName='default')
```

2.1.5.49 createKeyStoreAndEnableJKSForSSL

Online command to enable JKS for SSL.

Description

This command enables JKS for SSL, and disables KSS if it was enabled before. The command creates the libOVD adapters.jks file.

Syntax

```
createKeyStoreAndEnableJKSForSSL(keystorePassword=[password],
contextName=[contextName])
```

Table 2–83 *createKeyStoreAndEnableJKSForSSL Arguments*

Argument	Definition
keystorePassword	Password for libOVD adapters.jks file.
contextName	Optional. Name of the OPSS context with which libOVD configuration is associated. The default value is default.

Example

The following command enable JKS for SSL:

```
createKeyStoreAndEnableJKSForSSL(keystorePassword='welcome1',
contextName='default')
```

2.1.5.50 importTrustedCertificateIntoSSLStore

Online command to import trusted certificate into SSL store.

Description

This command imports the provided trusted certificate into SSL store.

Syntax

```
importTrustedCertificateIntoSSLStore(certificateFileName=[cert_
file], aliasName=[aliasName], contextName=[contextName])
```

Table 2–84 *importTrustedCertificateIntoSSLStore Arguments*

Argument	Definition
certificateFileName	File name that contains the certificate.
aliasName	Alias name for the certificate.
contextName	Optional. Name of the OPSS context with which libOVD configuration is associated. The default value is default.

Example

The following command imports the provided trusted certificate into SSL store:

```
importTrustedCertificateIntoSSLStore(certificateFileName='/tmp/cert.txt', aliasName
='myCert1', contextName='default')
```

2.1.5.51 migrateAllTrustedCertificatesFromJKSToKSS

Online command to migrate all trusted certificates from JKS-based libOVD truststore to KSS store.

Description

This command migrates all trusted certificates from JKS-based libOVD truststore to KSS store.

Syntax

```
migrateAllTrustedCertificatesFromJKSToKSS(contextName=[contextName])
```

Table 2–85 *migrateAllTrustedCertificatesFromJKSToKSS Arguments*

Argument	Definition
contextName	Optional. Name of the OPSS context with which libOVD configuration is associated. The default value is default.

Example

The following command migrates all trusted certificates from JKS-based libOVD truststore to KSS store:

```
migrateAllTrustedCertificatesFromJKSToKSS(contextName='default')
```


2.1.5.52 migrateTrustedCertificatesFromJKSToKSS

Online command to migrate given trusted certificates from JKS-based libOVD truststore to KSS store.

Description

This command migrates the given trusted certificates from JKS-based libOVD truststore to KSS store.

Syntax

```
migrateTrustedCertificatesFromJKSToKSS (aliasNames=[alias_names],
contextName=[contextName])
```

Table 2–86 migrateTrustedCertificatesFromJKSToKSS Arguments

Argument	Definition
aliasNames	List of alias names to migrate separated by a comma.
contextName	Optional. Name of the OPSS context with which libOVD configuration is associated. The default value is default.

Example

The following command migrates the specified trusted certificates from JKS-based libOVD truststore to KSS store:

```
migrateTrustedCertificatesFromJKSToKSS (aliasNames='alias1,alias2',
contextName='default')
```

2.1.5.53 changeLDAPHostPort

Online command to change given LDAP host and port in an existing LDAP adapter configuration to a new host and port.

Description

This command changes given LDAP host and port in an existing LDAP adapter configuration to a new host and port.

Syntax

```
changeLDAPHostPort (adapterName=[adapterName], oldHost=[oldHost],
oldPort=[oldPort], newHost=[newHost], newPort=[newPort],
contextName=[contextName])
```

Table 2–87 changeLDAPHostPort Arguments

Argument	Definition
adapterName	Name of the LDAP adapter to be modified.
oldHost	Old LDAP host.
oldPort	Old LDAP port.
newHost	New LDAP host.
newPort	New LDAP port.
contextName	Optional. Name of the OPSS context with which libOVD configuration is associated. The default value is default.

Example

The following command changes given LDAP host and port in an existing LDAP adapter configuration to a new host and port:

```
changeLDAPHostPort(adapterName='ldap1', oldHost='oldhost.example.domain.com',
oldPort=389, newHost='newhost.example.domain.com', newPort=389)
```

2.1.5.54 removeLDAPHostPort

Online command to remove a remote host and a port from an existing LDAP adapter configuration.

Description

This command removes a remote host and a port from an existing LDAP adapter configuration.

Syntax

```
removeLDAPHostPort(adapterName=[adapterName], host=[host], port=[port],
contextName=[contextName])
```

Table 2–88 *removeLDAPHostPort Arguments*

Argument	Definition
adapterName	Name of the LDAP adapter to be modified.
host	Remote LDAP host.
port	Remote LDAP port.
contextName	Optional. Name of the OPSS context with which libOVD configuration is associated. The default value is default.

Example

The following command removes a remote host and a port from an existing LDAP adapter configuration:

```
removeLDAPHostPort(adapterName='ldap1', host='myhost.example.domain.com',
port=389)
```

2.1.5.55 setReadOnlyForLDAPHost

Online command to set the given host and port to read-only/writable in an existing LDAP adapter configuration.

Description

This command sets the given host and port to read-only/writable in an existing LDAP adapter configuration.

Syntax

```
setReadOnlyForLDAPHost(adapterName=[adapterName], host=[host], port=[port],
readOnly=[true/false], contextName=[contextName])
```

Table 2–89 *setReadOnlyForLDAPHost Arguments*

Argument	Definition
adapterName	Name of the LDAP adapter to be modified.
host	LDAP host.
port	LDAP port.
readOnly	It has values: true or false.
contextName	Optional. Name of the OPSS context with which libOVD configuration is associated. The default value is default.

Example

The following command sets the given host and port to read-only in an existing LDAP adapter configuration:

```
setReadOnlyForLDAPHost(adapterName='ldap1', host='myhost.example.domain.com',  
port=389, readOnly=true)
```

SSL Configuration WLST Commands

This chapter describes SSL configuration WLST commands.

This chapter contains the following sections:

- [About SSL Configuration Commands](#)
- [Properties Files for SSL](#)

3.1 About SSL Configuration Commands

WLST commands are available to configure and manage SSL for Oracle Fusion Middleware components.

Use the commands listed in [Table 3-1](#) for this task.

See Also: *Administering Oracle Fusion Middleware* for important instructions on how to launch the WLST shell to run SSL-related commands. Do not launch the WLST interface from any other location.

Note: All WLST commands for SSL configuration must be run in online mode.

You can obtain help for each command by issuing:

```
help('command_name')
```

Certain commands require parameters like instance name, ias-component and process type. You can obtain this information with the command:

```
state('serverName') [in WebLogic domain]
```

```
nmServerStatus(serverName='name', serverType='type') [in Standalone domain]
```

Table 3-1 *WLST Commands for SSL Configuration*

Use this command...	To...	Use with WLST...
configureSSL	Set the SSL attributes for a component listener.	Online
getSSL	Display the SSL attributes for a component listener.	Online

3.2 Properties Files for SSL

SSL configuration employs certain properties files for use with the WLST `configureSSL` command.

The files contain parameters to specify the desired SSL configuration, such as authentication type, cipher values, and SSL version.

You can use descriptive names if you need to manage multiple properties files for different components. For example, you could have properties files named `ohs-ssl-properties.prop` or `ovd-ssl-properties.prop`.

3.2.1 Structure of Properties Files

All the SSL properties files have a consistent structure.

[Table 3–2](#) provides details about the key-value structure and usage of these files.

Table 3–2 Parameters in Properties File

Key	Mandatory?	Allowed Values for Oracle HTTP Server	Usage
SSLEnabled	No	true false	Either value
Ciphers	No	SSL_RSA_WITH_RC4_128_MD5 SSL_RSA_WITH_RC4_128_SHA SSL_RSA_WITH_3DES_EDE_CBC_SHA SSL_RSA_WITH_DES_CBC_SHA SSL_DH_anon_WITH_RC4_128_MD5 SSL_DH_anon_WITH_DES_CBC_SHA SSL_DH_anon_WITH_3DES_EDE_CBC_SHA TLS_RSA_WITH_AES_128_CBC_SHA TLS_RSA_WITH_AES_256_CBC_SHA	One or more comma separated values
SSLVersions	No	nzos_Version_3_0 nzos_Version_3_0_With_2_0_Hello nzos_Version_1_0	One or more comma separated values
CertValidation	No	none crl	Either value
CertValidation Path	No	file://crl_file_path dir://crl_dir_path	Path of the CRL file, or directory containing CRL files
KeyStore	No	Valid wallet name	
TrustStore	No	N/A	
AuthenticationType	No	None Server Optional Mutual	Any one value

[Table 3–3](#) shows the default values:

Table 3–3 Default Values of Parameters

Key	Default Value for Oracle HTTP Server
SSLEnabled	true
Ciphers	null
SSLVersions	null
CertValidation	none
CertValidation Path	null
KeyStore	default
TrustStore	-
Authentication Type	Server

Note:

- At least one DH_anon cipher must be used in SSL no-auth mode. For all other modes, at least one RSA cipher must be used.
- The value of the KeyStore parameter must be specified when configuring SSL in server-auth, mutual-auth, or optional client auth.
- If only AES ciphers have been specified, the SSLVersions parameter must contain TLSv1 or nzos_Version_1_0.
- If you are doing CRL-based validation, the value of the CertValidation parameter should be `crl` and the value of the CertValidationPath parameter should point to the CRL file/directory.

3.2.2 Examples of Properties Files

Some examples demonstrating the use of the properties files follow.

Example 1: Basic Properties File

```
SSLEnabled=true
AuthenticationType=None
CertValidation=none
```

This properties file specifies no authentication mode, and default values will be used during SSL configuration for ciphers and SSL version. Keystore and truststore properties are not specified since the authentication type is `None`. For other authentication types, keystore must be specified.

Example 2: Basic Properties File

```
SSLEnabled=
AuthenticationType=None
CertValidation=none
```

This properties file is exactly the same as above, except that `SSLEnabled` is explicitly specified without any value. This is the same as not specifying the key at all. In both cases, the default value will be used.

Therefore, all the following three settings have the same meaning:

- The setting:

```
SSLEnabled=true
```

Here the value `true` is explicitly specified.

- The setting:

```
SSLEnabled=
```

Since no value is mentioned here, the default value of `SSLEnabled` (`true`) is used.

- The key `SSLEnabled` is not present in the properties file.

Since the key is not present, its default value (`true`) is used.

Example 3: Properties File with Version for OHS

```
SSLEnabled=true
AuthenticationType=Mutual
SSLVersion=nzos_Version_3_0
CertValidation=crl
CertValidationPath=file:///tmp/file.crl
KeyStore=ohs1
```

This properties file has:

- Default values for ciphers
- Keystore
- SSL version v3
- CRL validation turned on
- Mutual Authentication mode

configureSSL

Online command that sets SSL attributes.

Description

This command sets the SSL attributes for a component listener. The attributes are specified in a properties file format (name=value). If a properties file is not provided, or it does not contain any SSL attributes, then default attribute values are used.

For details about the format of properties files, see [Section 3.2, "Properties Files for SSL."](#)

Syntax

```
configureSSL('instName', 'compName', 'compType', 'listener', 'filePath')
```

Argument	Definition
instName	Specifies the name of the application server instance.
compName	Specifies the name of the component instance.
compType	Specifies the type of component. Valid value is 'ohs'.
listener	Specifies the name of the component listener to be configured for SSL.
filePath	Specifies the absolute path of the properties file containing the SSL attributes to set.

Example

Here are some examples of `configureSSL` command usage.

The following command configures SSL attributes specified in the properties file `/tmp/ssl.properties` for Oracle Virtual Directory instance `ovd1` in application server instance `inst1`, for listener `listener1`:

```
wls:/mydomain/serverConfig> configureSSL('inst1', 'ovd1', 'ovd',
'listener1', '/tmp/ssl.properties')
```

The following command configures SSL attributes without specifying a properties file. Since no file is provided, the default SSL attribute values are used:

```
wls:/mydomain/serverConfig> configureSSL('inst1', 'ovd1', 'ovd', 'listener2')
```

getSSL

Online command that lists the configured SSL attributes.

Description

This command lists the configured SSL attributes for the specified component listener.

Syntax

```
getSSL('instName', 'compName', 'compType', 'listener')
```

Argument	Definition
instName	Specifies the name of the application server instance.
compName	Specifies the name of the component instance.
compType	Specifies the type of component. Valid value is 'ohs'.
listener	Specifies the name of the component listener.

Example

The following command shows the SSL attributes configured for Oracle HTTP Server instance ohs1, in application server instance inst1, for listener sslport1:

```
wls:/mydomain/serverConfig> getSSL('inst1', 'ohs1', 'ohs', 'sslport1')
```

Wallet Configuration WLST Commands

This chapter describes how to configure Oracle wallets using WLST commands.

This chapter contains the following topic:

- [The WLST Wallet Commands](#)

4.1 The WLST Wallet Commands

WLST commands allow to manage Oracle wallets for Oracle Fusion Middleware components. [Table 4-1](#) lists the available commands.

To obtain help for a command, invoke a command like the following:

```
help('command_name')
```

Certain commands require parameters like instance name, ias-component or process type. To obtain such information, invoke commands like the following:

```
state('serverName') [in WebLogic domain]
nmServerStatus(serverName='name', serverType='type') [in Standalone domain]
```

Note: WLST allows you to import certificates in only PEM format.

Table 4-1 WLST Commands for Oracle Wallet Management

Use this command...	To...	Use with WLST...
addCertificateRequest	Generate a certificate signing request in an Oracle wallet.	Online
addSelfSignedCertificate	Add a self-signed certificate to an Oracle wallet.	Online
changeWalletPassword	Change the password to an Oracle wallet.	Online
createWallet	Create an Oracle wallet.	Online
deleteWallet	Delete an Oracle wallet.	Online
exportWallet	Export an Oracle wallet to a file.	Online
exportWalletObject	Export an object (for example, a certificate) from an Oracle wallet to a file.	Online
getWalletObject	Display a certificate or other object present in an Oracle wallet.	Online
importWallet	Import an Oracle wallet from a file.	Online

Table 4–1 (Cont.) WLST Commands for Oracle Wallet Management

Use this command...	To...	Use with WLST...
<code>importWalletObject</code>	Import a certificate or other object from a file to an Oracle wallet.	Online
<code>listWalletObjects</code>	List all objects (such as certificates) present in an Oracle wallet.	Online
<code>listWallets</code>	List all Oracle wallets configured for a component instance.	Online
<code>removeWalletObject</code>	Remove a certificate or other object from a component instance's Oracle wallet.	Online

See Also: *Administering Oracle Fusion Middleware* for important instructions on how to launch the WLST shell to run SSL-related commands. Do not launch the WLST interface from any other location.

addCertificateRequest

Online command that generates a certificate signing request in an Oracle wallet.

Description

This command generates a certificate signing request in Base64 encoded PKCS#10 format in an Oracle wallet for a component instance (Oracle HTTP Server). To get a certificate signed by a certificate authority (CA), send the certificate signing request to your CA.

Syntax

```
addCertificateRequest('instName', 'compName', 'compType', 'walletName',
'password', 'DN', 'keySize')
```

Argument	Definition
instName	Specifies the name of the application server instance.
compName	Specifies the name of the component instance.
compType	Specifies the type of component. Valid value is 'ohs'.
walletName	Specifies the name of the wallet file.
password	Specifies the password of the wallet.
DN	Specifies the Distinguished Name of the key pair entry.
keySize	Specifies the key size in bits.

Example

The following command generates a certificate signing request with DN `cn=www.acme.com` and key size 1024 in wallet1, for Oracle HTTP Server instance ohs1, in application server instance inst1:

```
wls:/mydomain/serverConfig> addCertificateRequest('inst1', 'ohs1',
'ohs','wallet1', 'password', 'cn=www.acme.com', '1024',)
```

addSelfSignedCertificate

Online command that adds a self-signed certificate.

Description

This command creates a key pair and wraps it in a self-signed certificate in an Oracle wallet for the specified component instance (Oracle HTTP Server). Only keys based on the RSA algorithm are generated.

Syntax

```
addSelfSignedCertificate('instName', 'compName', 'compType', 'walletName',  
                        'password', 'DN', 'keySize')
```

Argument	Definition
instName	Specifies the name of the application server instance.
compName	Specifies the name of the component instance.
compType	Specifies the type of component. Valid value is 'ohs'.
walletName	Specifies the name of the wallet file.
password	Specifies the password of the wallet.
DN	Specifies the Distinguished Name of the key pair entry.
keySize	Specifies the key size in bits.

Example

The following command adds a self-signed certificate with DN `cn=www.acme.com`, key size 1024 to `wallet1`, for Oracle HTTP Server instance `ohs1`, in application server instance `inst1`:

```
wls:/mydomain/serverConfig> addSelfSignedCertificate('inst1', 'ohs1',  
'ohs', 'wallet1', 'password', 'cn=www.acme.com', '1024')
```

changeWalletPassword

Online command that changes the password of an Oracle wallet.

Description

This command changes the password of an Oracle wallet for the specified component instance (Oracle HTTP Server). This command is only applicable to password-protected wallets.

Syntax

```
changeWalletPassword('instName', 'compName', 'compType',
'walletName', 'currPassword', 'newPassword')
```

Argument	Definition
instName	Specifies the name of the application server instance.
compName	Specifies the name of the component instance.
compType	Specifies the type of component. Valid value is 'ohs'.
walletName	Specifies the filename of the wallet.
currPassword	Specifies the current wallet password.
newPassword	Specifies the new wallet password.

Example

The following command changes the password for wallet1 from currpassword to newpassword for Oracle HTTP Server instance ohs1 in application server instance inst1:

```
wls:/mydomain/serverConfig> changeWalletPassword('inst1', 'ohs1', 'ohs', 'wallet1',
'currpassword', 'newpassword')
```

createWallet

Online command that creates an Oracle wallet.

Description

This command creates an Oracle wallet for the specified component instance (Oracle HTTP Server). Wallets can be of password-protected or auto-login type.

Syntax

```
createWallet('instName', 'compName', 'compType', 'walletName', 'password')
```

Argument	Definition
instName	Specifies the name of the application server instance.
compName	Specifies the name of the component instance.
compType	Specifies the type of component. Valid value is 'ohs'.
walletName	Specifies the name of the wallet file to be created.
password	Specifies the wallet password.

Example

The following command creates a wallet named `wallet1` with password `password`, for Oracle HTTP Server instance `ohs1` in application server instance `inst1`:

```
wls:/mydomain/serverConfig> createWallet('inst1', 'ohs1', 'ohs', 'wallet1',  
'password')
```

The following command creates an auto-login wallet named `wallet2` for Oracle WebCache instance `wc1`, in application server instance `inst1`:

```
wls:/mydomain/serverConfig> createWallet('inst1', 'wc1', 'webcache', 'wallet2', '')
```

deleteWallet

Online command that deletes an Oracle wallet.

Description

This command deletes an Oracle wallet for the specified component instance.

Syntax

```
deleteWallet('instName', 'compName', 'compType', 'walletName')
```

Argument	Definition
instName	Specifies the name of the application server instance.
compName	Specifies the name of the component instance.
compType	Specifies the type of component. Valid value is 'ohs'.
walletName	Specifies the name of the wallet file to be deleted.

Example

The following command deletes a wallet named `wallet1` for Oracle HTTP Server instance `ohs1` in application server instance `inst1`:

```
wls:/mydomain/serverConfig> deleteWallet('inst1', 'ohs1', 'ohs', 'wallet1')
```

exportWallet

Online command that exports an Oracle wallet.

Description

This command exports an Oracle wallet, configured for a specified component instance, to files under the given directory. If the exported file is an auto-login only wallet, the file name is `cwallet.sso`. If it is password-protected wallet, two files are created—`ewallet.p12` and `cwallet.sso`.

Syntax

```
exportWallet('instName', 'compName', 'compType', 'walletName', 'password', 'path')
```

Argument	Definition
<code>instName</code>	Specifies the name of the application server instance.
<code>compName</code>	Specifies the name of the component instance.
<code>compType</code>	Specifies the type of component. Valid value is 'ohs'.
<code>walletName</code>	Specifies the name of the wallet file.
<code>password</code>	Specifies the password of the wallet.
<code>path</code>	Specifies the absolute path of the directory under which the object is exported.

Example

The following command exports auto-login wallet `wallet1` for Oracle HTTP Server instance `ohs1` to file `cwallet.sso` under `/tmp`:

```
wls:/mydomain/serverConfig> exportWallet('inst1', 'ohs1', 'ohs',  
'wallet1','','/tmp')
```

The following command exports password-protected wallet `wallet2` for Oracle HTTP Server instance `ohs1` to two files, `ewallet.p12` and `cwallet.sso`, under `/tmp`:

```
wls:/mydomain/serverConfig> exportWallet('inst1', 'ohs1', 'ohs', 'wallet2',  
'password', '/tmp')
```

exportWalletObject

Online command that exports a certificate or other wallet object to a file.

Description

This command exports a certificate signing request, certificate, certificate chain or trusted certificate present in an Oracle wallet to a file for the specified component instance. DN indicates the object to be exported.

Syntax

```
exportWalletObject('instName', 'compName', 'compType', 'walletName', 'password',
'type', 'path', 'DN')
```

Argument	Definition
instName	Specifies the name of the application server instance.
compName	Specifies the name of the component instance.
compType	Specifies the type of component. Valid value is 'ohs'.
walletName	Specifies the name of the wallet file.
password	Specifies the password of the wallet.
type	Specifies the type of wallet object to be exported. Valid values are 'CertificateRequest', 'Certificate', 'TrustedCertificate' or 'TrustedChain'.
path	Specifies the absolute path of the directory under which the object is exported as a file base64.txt.
DN	Specifies the Distinguished Name of the wallet object being exported.

Example

The following command exports a certificate signing request with DN `cn=www.acme.com` in `wallet1`, for Oracle HTTP Server instance `ohs1`, in application server instance `inst1`. The certificate signing request is exported under the directory `/tmp`:

```
wls:/mydomain/serverConfig> exportWalletObject('inst1', 'ohs1', 'ohs','wallet1',
'password', 'CertificateRequest', '/tmp','cn=www.acme.com')
```

The following command exports a certificate with DN `cn=www.acme.com` in `wallet1`, for Oracle HTTP Server instance `ohs1`, in application server instance `inst1`. The certificate or certificate chain is exported under the directory `/tmp`:

```
wls:/mydomain/serverConfig> exportWalletObject('inst1', 'ohs1', 'ohs','wallet1',
'password', 'Certificate', '/tmp','cn=www.acme.com')
```

The following command exports a trusted certificate with DN `cn=www.acme.com` in `wallet1`, for Oracle HTTP Server instance `ohs1`, in application server instance `inst1`. The trusted certificate is exported under the directory `/tmp`:

```
wls:/mydomain/serverConfig> exportWalletObject('inst1', 'ohs1', 'ohs','wallet1',
'password', 'TrustedCertificate', '/tmp','cn=www.acme.com')
```

The following command exports a certificate chain with DN `cn=www.acme.com` in `wallet1`, for Oracle HTTP Server instance `ohs1`, in application server instance `inst1`. The certificate or certificate chain is exported under the directory `/tmp`:

```
wls:/mydomain/serverConfig> exportWalletObject('inst1', 'ohs1', 'ohs', 'wallet1',  
'password', 'TrustedChain', '/tmp', 'cn=www.acme.com')
```

getWalletObject

Online command that displays information about a certificate or other object in an Oracle wallet.

Description

This command displays a specific certificate signing request, certificate or trusted certificate present in an Oracle wallet for the specified component instance. The wallet object is indicated by its index number, as given by the `listWalletObjects` command. For certificates or trusted certificates, it shows the certificate details including DN, key size, algorithm and other data. For certificate signing requests, it shows the subject DN, key size and algorithm.

Syntax

```
getWalletObject('instName', 'compName', 'compType', 'walletName', 'password',
'type', 'index')
```

Argument	Definition
instName	Specifies the name of the application server instance.
compName	Specifies the name of the component instance.
compType	Specifies the type of component. Valid value is 'ohs'.
walletName	Specifies the name of the wallet file.
password	Specifies the password of the wallet.
type	Specifies the type of wallet object to be exported. Valid values are 'CertificateRequest', 'Certificate', and 'TrustedCertificate'.
index	Specifies the index number of the wallet object as returned by the <code>listWalletObjects</code> command.

Example

The following command shows certificate signing request details for the object with index 0 present in `wallet1`, for Oracle HTTP Server instance `ohs1`, in application server instance `inst1`:

```
wls:/mydomain/serverConfig> getKeyStoreObject('inst1', 'ohs1',
'ohs', 'wallet1', 'password', 'CertificateRequest', '0')
```

The following command shows certificate details for the object with index 0 present in `wallet1`, for Oracle HTTP Server instance `ohs1`, in application server instance `inst1`:

```
wls:/mydomain/serverConfig> getKeyStoreObject('inst1', 'ohs1',
'ohs', 'wallet1', 'password', 'Certificate', '0')
```

The following command shows trusted certificate details for the object with index 0, present in `wallet1`, for Oracle HTTP Server instance `ohs1`, in application server instance `inst1`:

```
wls:/mydomain/serverConfig> getKeyStoreObject('inst1', 'ohs1',
'ohs', 'wallet1', 'password', 'TrustedCertificate', '0')
```

importWallet

Online command that imports an Oracle wallet from a file.

Description

This command imports an Oracle wallet from a file to the specified component instance for manageability. If the wallet being imported is an auto-login wallet, the file path must point to `cwallet.sso`; if the wallet is password-protected, it must point to `ewallet.p12`. The wallet name must be unique for the component instance.

Syntax

```
importWallet('instName', 'compName', 'compType', 'walletName', 'password',  
'filePath')
```

Argument	Definition
instName	Specifies the name of the application server instance.
compName	Specifies the name of the component instance.
compType	Specifies the type of component. Valid value is 'ohs'.
walletName	Specifies the name of the wallet being imported. The name must be unique for the component instance.
password	Specifies the password of the wallet.
filePath	Specifies the absolute path of the wallet file being imported.

Example

The following command imports the auto-login wallet file `/tmp/cwallet.sso` as `wallet1` into Oracle HTTP Server instance `ohs1`. Subsequently, the wallet is managed with the name `wallet1`. No password is passed since it is an auto-login wallet:

```
wls:/mydomain/serverConfig> importWallet('inst1', 'ohs1', 'ohs', 'wallet1', '',  
'/tmp/cwallet.sso')
```

The following command imports password-protected wallet `/tmp/ewallet.p12` as `wallet2` into Oracle HTTP Server instance `ohs1`. Subsequently, the wallet is managed with the name `wallet2`. The wallet password is passed as a parameter:

```
wls:/mydomain/serverConfig> importWallet('inst1', 'ohs1', 'ohs', 'wallet2',  
'password', '/tmp/ewallet.p12')
```

importWalletObject

Online command that imports a certificate or other object into an Oracle wallet.

Description

This command imports a certificate, trusted certificate or certificate chain into an Oracle wallet for the specified component instance. When importing a certificate, use the same wallet file from which the certificate signing request was generated.

Syntax

```
importWalletObject('instName', 'compName', 'compType', 'walletName', 'password',
'filePath')
```

Argument	Definition
instName	Specifies the name of the application server instance.
compName	Specifies the name of the component instance.
compType	Specifies the type of component. Valid value is 'ohs'.
walletName	Specifies the name of the wallet file.
password	Specifies the password of the wallet.
type	Specifies the type of wallet object to be imported. Valid values are 'Certificate', 'TrustedCertificate' and 'TrustedChain'.
filePath	Specifies the absolute path of the file containing the wallet object.

Example

The following command imports a certificate chain in PKCS#7 format from file `chain.txt` into `wallet1`, for Oracle HTTP Server instance `ohs1`, in application server instance `inst1`:

```
wls:/mydomain/serverConfig> importWalletObject('inst1', 'ohs1', 'ohs','wallet1',
'password', 'TrustedChain','/tmp/chain.txt')
```

The following command imports a certificate from file `cert.txt` into `wallet1`, for Oracle HTTP Server instance `ohs1`, in application server instance `inst1`:

```
wls:/mydomain/serverConfig> > importWalletObject('inst1', 'ohs1', 'ohs','wallet1',
'password', 'Certificate','/tmp/cert.txt')
```

The following command imports a trusted certificate from file `trust.txt` into `wallet1`, for Oracle HTTP Server instance `ohs1`, in application server instance `inst1`:

```
wls:/mydomain/serverConfig> importWalletObject('inst1', 'ohs1', 'ohs','wallet1',
'password', 'TrustedCertificate','/tmp/trust.txt')
```

listWalletObjects

Online command that lists all objects in an Oracle wallet.

Description

This command lists all certificate signing requests, certificates, or trusted certificates present in an Oracle wallet for the specified component instance.

Syntax

```
listWalletObjects('instName', 'compName', 'compType', 'walletName', password',  
'type')
```

Argument	Definition
instName	Specifies the name of the application server instance.
compName	Specifies the name of the component instance.
compType	Specifies the type of component. Valid value is 'ohs'.
walletName	Specifies the name of the wallet file.
password	Specifies the password of the wallet.
type	Specifies the type of wallet object to be listed. Valid values are 'CertificateRequest', 'Certificate', and 'TrustedCertificate'.

Example

The following command lists all certificate signing requests in `wallet1`, for Oracle HTTP Server instance `ohs1`, in application server instance `inst1`:

```
wls:/mydomain/serverConfig> > listWalletObjects('inst1', 'ohs1',  
'ohs', 'wallet1', 'password', 'CertificateRequest')
```

The following command lists all certificates in `wallet1`, for Oracle HTTP Server instance `ohs1`, in application server instance `inst1`:

```
wls:/mydomain/serverConfig> listWalletObjects('inst1', 'ohs1',  
'ohs', 'wallet1', 'password', 'Certificate')
```

The following command lists all trusted certificates in `wallet1`, for Oracle HTTP Server instance `ohs1`, in application server instance `inst1`:

```
wls:/mydomain/serverConfig> listWalletObjects('inst1', 'ohs1',  
'ohs', 'wallet1', 'password', 'TrustedCertificate')
```

listWallets

Online command that lists all wallets configured for a component instance.

Description

This command displays all the wallets configured for the specified component instance, and identifies the auto-login wallets.

Syntax

```
listWallets('instName', 'compName', 'compType')
```

Argument	Definition
instName	Specifies the name of the application server instance.
compName	Specifies the name of the component instance
compType	Specifies the type of component. Valid value is 'ohs'.

Example

The following command lists all wallets for Oracle HTTP Server instance ohs1 in application server instance inst1:

```
wls:/mydomain/serverConfig> > listWallets('inst1', 'ohs1', 'ohs')
```

removeWalletObject

Online command that removes a certificate or other object from an Oracle wallet.

Description

This command removes a certificate signing request, certificate, trusted certificate or all trusted certificates from an Oracle wallet for the specified component instance. DN is used to indicate the object to be removed.

Syntax

```
removeWalletObject('instName', 'compName', 'compType', 'walletName', 'password',
'type', 'DN')
```

Argument	Definition
instName	Specifies the name of the application server instance.
compName	Specifies the name of the component instance.
compType	Specifies the type of component. Valid value is 'ohs'.
walletName	Specifies the name of the wallet file.
password	Specifies the password of the wallet.
type	Specifies the type of the keystore object to be removed. Valid values are 'CertificateRequest', 'Certificate', 'TrustedCertificate' or 'TrustedAll'.
DN	Specifies the Distinguished Name of the wallet object to be removed.

Example

The following command removes all trusted certificates from wallet1, for Oracle HTTP Server instance ohs1, in application server instance inst1. It is not necessary to provide a DN, so you pass null (denoted by None) for the DN parameter:

```
wls:/mydomain/serverConfig> removeWalletObject('inst1', 'ohs1', 'ohs','wallet1',
'password', 'TrustedAll',None)
```

The following command removes a certificate signing request indicated by DN cn=www.acme.com from wallet1, for Oracle HTTP Server instance ohs1, in application server instance inst1:

```
wls:/mydomain/serverConfig> removeWalletObject('inst1', 'ohs1', 'ohs','wallet1',
'password', 'CertificateRequest', 'cn=www.acme.com')
```

The following command removes a certificate indicated by DN cn=www.acme.com from wallet1, for Oracle HTTP Server instance ohs1, in application server instance inst1:

```
wls:/mydomain/serverConfig> removeWalletObject('inst1', 'ohs1', 'ohs','wallet1',
'password', 'Certificate', 'cn=www.acme.com')
```

The following command removes a trusted certificate indicated by DN cn=www.acme.com from wallet1, for Oracle HTTP Server instance ohs1, in application server instance inst1:

```
wls:/mydomain/serverConfig> removeWalletObject('inst1', 'ohs1', 'ohs','wallet1',
'password', 'TrustedCertificate', 'cn=www.acme.com')
```